



規制番号 名称		05-0162	東西橋南詰		運 用	2014年11月26日		製造番号	K0000024
制御機機種		交通信号制御機		EC5450C+34001001		開始日時	12時11分	～	製造年月
警交仕規第1012号版3		製作所	日本信号株式会社		作動時間	6:00～21:00以後閃光		施工会社	(株)中電工
署別	因島	付加機能	新型錠						

[illegible][illegible]

	(1) 平日	(2) 土曜	(3) 日曜	(4) 特殊日1	(5) 特殊日2	(6) 特殊日3	(7) 特殊日4										
パ タ ン 切 替	切替 番号	ハ タ ン 番 号	時 分	ハ タ ン 番 号	時 分	ハ タ ン 番 号	時 分	ハ タ ン 番 号	時 分	ハ タ ン 番 号	時 分	ハ タ ン 番 号	時 分	ハ タ ン 番 号	時 分	ハ タ ン 番 号	
	1	6	00	1	6	00	1	6	00	1							
	2	7	00	3	7	00	3	7	00	3							
	3	9	00	2	9	00	2	9	00	2							
	4	16	00	3	16	00	3	16	00	3							
	5	19	00	1	19	00	1	19	00	1							
	6																
	7																
	8																
	9																
A																	
動 作 切 替	閃光	21:00～6:00		21:00～6:00		21:00～6:00											
系 統 動 作 定 数	同期点																
	追従幅																
	追従階梯秒数配分																
	主現示追従階梯																
	従現示追従階梯																
	時刻修正			○(GPS)													
連 動 子 機 能 定 数	DC方式																
	AC方式																
	同期階梯1(B/Y1)																
	同期階梯2(A/Y2)																
	周期監視時間																
	共通オフセット1																
	共通オフセット2																
	連動親機																
交 通 弱 者 感 応 定 数	感應階梯		ステップ														
	補正階梯		ステップ														
	倍率指定 (10～19)		×0.1倍														
	弱者用保証青時間(0～99)		秒														
ギ ャ ッ プ 感 応 定 数	単位1				単位2												
		短縮	延長	単位青	単位青		短縮	延長	単位青	単位青							
		Ts	Te	上り0.1秒	下り0.1秒		Ts	Te	上り0.1秒	下り0.1秒							
	P1					P1											
	P2					P2											
	P3					P3											
	P4					P4											
	P5					P5											
	P6					P6											
	P7					P7											
	P8					P8											
	P9					P9											
	PA					PA											
	感應階梯				感應階梯												
	リ コ ー ル 定 数	感應階梯		ステップ													
補正階梯		ステップ															