

		(1) 平日		(2) 土曜		(3) 日曜		(4) 特殊日1		(5) 特殊日2		(6) 特殊日3		(7) 特殊日4			
パ タ ン 切 替	切替 番号	時	分	ハタン 番号	時	分	ハタン 番号	時	分	ハタン 番号	時	分	ハタン 番号	時	分	ハタン 番号	
	1	00	00	1	00	00	1	00	00	1							
	2																
	3																
	4																
	5																
	6																
	7																
	8																
	9																
A																	
動 作 切 替	閃光 系統	00:00～06:00		00:00～06:00		00:00～06:00											
		00:00～00:00		00:00～00:00		00:00～00:00											
系 統 動 作 定 数	同期点				1ステップ始め												
	追従幅				-5/+15(20%)												
	追従階梯秒数配分				等分												
	主現示追従階梯				1ステップ												
	従現示追従階梯				6ステップ												
	時刻修正				●(GPS)												
運 動 子 機 能 定 数	DC方式								分 周 期 連 動 機 能 定 数	実行しきい値							
	AC方式									連動パターン							
	同期階梯1(B/Y1)																
	同期階梯2(A/Y2)																
	周期監視時間																
	共通オフセット1																
	共通オフセット2																
	連動親機																
交通弱者感応定数																	
感応階梯								ステップ									
補正階梯								ステップ									
倍率指定 (10～19)								×0.1倍									
弱者用保証青時間(0～99)								秒									
ギ ャ ッ プ 感 応 定 数	単位1								単位2								
	短縮		延長		単位青		単位青		短縮		延長		単位青		単位青		
	Ts		Te		上り0.1秒 下り0.1秒				Ts		Te		上り0.1秒 下り0.1秒				
	P1								P1								
	P2								P2								
	P3								P3								
	P4								P4								
	P5								P5								
	P6								P6								
	P7								P7								
	P8								P8								
	P9								P9								
PA								PA									
感応階梯								感応階梯									
リ コ ー ル 定 数	感応階梯				ステップ												
	補正階梯				ステップ												
	感知器指定		押ボタン				車両										
	押ボタン受付禁止階梯						開始				終了						
	車両リコール受付禁止階梯						開始				終了						
曜日固定祝祭日テーブル																	
月		週		曜日		休日解除											
1		1		2		1											
2		7		3		1											
3		9		3		1											
4		10		2		1											
						</											