



The diagram illustrates the intersection of National Route 1 (vertical) and National Route 100 (horizontal). A proposed bus lane is shown as a solid line with arrows, running vertically through the intersection. The lane width is specified as 31.5m on the left side and 32.4m on the right side. The speed limit for all roads is 40km/h. The diagram also shows the existing road layout, including the intersection of National Route 1 and National Route 100, and the location of the bus lane relative to the intersection. A compass rose is located in the top right corner, indicating the orientation of the diagram.

流動図	10. 5m 歩灯2  10. 8m 歩灯2	11. 5m 歩灯2  11. 1m 歩灯2	
------------	---	---	---

[illegible]

パ タ ン 切 替		(1) 平日			(2) 土曜			(3) 日曜			(4) 特殊日1			(5) 特殊日2			(6) 特殊日3			(7) 特殊日4		
	切替 番号	時	分	ハタ 番号	時	分	ハタ 番号	時	分	ハタ 番号	時	分	ハタ 番号	時	分	ハタ 番号	時	分	ハタ 番号	時	分	ハタ 番号
	1	6	00	1	6	00	1	6	00	1												
	2	7	00	3	7	00	3	7	00	3												
	3	9	00	2	9	00	2	9	00	2												
	4	16	00	4	16	00	4	16	00	4												
	5	19	00	2	19	00	2	19	00	2												
	6	20	00	1	20	00	1	20	00	1												
	7																					
	8																					
	9																					
	A																					
動 作 切 替	系統	00:00~00:00			00:00~00:00			00:00~00:00														

系 統 動 作 定 数	同期点	1ステップ 始め			
	追従幅	-5%／+20%			
	追従階梯秒数配分	スプリット比配分			
	主現示追従階梯	1			
	従現示追従階梯	6			
	時刻修正	●（GPS）			
連 動 子 機 能 定 数	DC方式		分 周 期 連 動 機 能 定 数	実行しきい値	
	AC方式			連動パターン	
	同期階梯1（B／Y1）				
	同期階梯2（A／Y2）				
	周期監視時間				
	共通オフセット1				
	共通オフセット2				
	連動親機				

高齢者感応定数	
感応階梯	ステップ
補正階梯	ステップ
倍率指定 (10~19)	×0.1倍
高齢者用保証青時間(0~99)	秒

ギ ャ ッ プ 感 応 定 数	単位1				単位2			
	短縮	延長	単位青	単位青	短縮	延長	単位青	単位青
	Ts	Te	上り0.1秒	下り0.1秒	Ts	Te	上り0.1秒	下り0.1秒
	P1				P1			
	P2				P2			
	P3				P3			
	P4				P4			
	P5				P5			
	P6				P6			
	P7				P7			
	P8				P8			
	P9				P9			
	PA				PA			
	感応階梯				感応階梯			
	補正階梯				補正階梯			
	感知器指定				感知器指定			

リ コ ー ル 定 数	感応階梯		ステップ					
	補正階梯		ステップ					
	感知器指定	押ボタン			車両			
	押ボタン受付禁止階梯					開始	終了	
	車両リコール受付禁止階梯					開始	終了	

曜日固定祝祭日テーブル				
月	週	曜日	日種	
1	1	2	1	3
2	7	3	1	3
3	9	3	1	3
4	10	2	1	3

規制番号	08-0090
名 称	新扇橋南詰

備 考
地点感応制御機の場合左記の
ギャップ感応定数表の内容は
下記の通りです。

短縮 Ts → ありません。
延長 Te → 限度青です。
単位青 上り → 単位青です。
単位青 下り → ありません。
単位青秒数は 0.5秒単位です。

名称はこうに変更してください。

設定変更履歴	
年月日	変更内容
2026年3月29日	新設交差点運用開始