

		(1) 平日				(2) 土曜				(3) 日曜				(4) 特殊日1				(5) 特殊日2				(6) 特殊日3				(7) 特殊日4														
バ タ ン 切 替	切替 番号	時	分	ハタ ン 番 号	時	分	ハタ ン 番 号	時	分	ハタ ン 番 号	時	分	ハタ ン 番 号	時	分	ハタ ン 番 号	時	分	ハタ ン 番 号	時	分	ハタ ン 番 号	時	分	ハタ ン 番 号															
		1	6	00	1	6	00	1	6	00	1																													
		2																																						
		3																																						
		4																																						
		5																																						
		6																																						
		7																																						
		8																																						
		9																																						
	A																																							
動 作 切 替	連動子機	00:00～00:00				00:00～00:00				00:00～00:00																														
系 統 動 作 定 数	同期点 追従幅																																							
	追従階梯秒数配分																																							
	主現示追従階梯																																							
	従現示追従階梯																																							
	時刻修正																																							
連 動 子 機 能 定 数	DC方式								○								<table border="1" style="width:100%; border-collapse: collapse;"> <tr><td>実行しきい値</td><td></td></tr> <tr><td>連動パターン</td><td></td></tr> <tr><td></td><td></td></tr> <tr><td></td><td></td></tr> <tr><td></td><td></td></tr> <tr><td></td><td></td></tr> <tr><td></td><td></td></tr> <tr><td></td><td></td></tr> </table>								実行しきい値		連動パターン													
	実行しきい値																																							
	連動パターン																																							
AC方式																																								
同期階梯1(B/Y1)								1																																
同期階梯2(A/Y2)																																								
周期監視時間																																								
共通オフセット1								5																																
共通オフセット2																																								
連動親機								10229 楠木町4丁目																																
交通弱者感応定数																																								
感応階梯																ステップ																								
補正階梯																ステップ																								
倍率指定 (10～19)																×0.1倍																								
弱者用保証青時間 (0～99)																秒																								
ギ ャ ッ 感 応 定 数	単位1								単位2								備考 地点感応制御機の場合左記のギャップ感応定数表の内容は下記の通りです。 短縮 Ts → ありません。 延長 Te → 限度青です。 単位青 上り → 単位青です。 単位青 下り → ありません。 単位青秒数は0.5秒単位です。																							
		短縮	延長	単位青	単位青		短縮	延長	単位青	単位青		短縮	延長	単位青	単位青																									
		Ts	Te	上り0.1秒	下り0.1秒		Ts	Te	上り0.1秒	下り0.1秒		Ts	Te	上り0.1秒	下り0.1秒																									
	P1					P1					P1																													
	P2					P2					P2																													
	P3					P3					P3																													
	P4					P4					P4																													
	P5					P5					P5																													
	P6					P6					P6																													
	P7					P7					P7																													
	P8					P8					P8																													
	P9					P9					P9																													
	PA					PA					PA																													
	感応階梯								感応階梯																															
リ コ ー ル 定 数	感応階梯								ステップ																															
	補正階梯								ステップ																															
	感知器指定								押ボタン								車両																							
	押ボタン受付禁止階梯								開始								終了																							
	車両リコール受付禁止階梯								開始								終了																							