

交差点図

速度表示なし

至 光南3丁目3番

2

21.0m

27.7m

40km

1

至 吉島通り

40km

速度表示なし

流動図

The flowchart illustrates the traffic flow at the intersection. It shows four main lanes with arrows indicating the direction of travel. Dimensions are provided for each lane: 7.8m for the top lane, 7.7m for the bottom lane, 9.7m for the left lane, and 9.6m for the right lane. Labels '歩灯なし' (No pedestrian signal) are present for the top and bottom lanes. The flowchart also shows the flow of vehicles and pedestrians, with arrows indicating the direction of travel.

備考: PO はAプロのみ設定。

		(1) 平日			(2) 土曜			(3) 日曜			(4) 特殊日1			(4) 特殊日2			(4) 特殊日3			(4) 特殊日4		
パターン切替	切替番号	時	分	パタン番号	時	分	パタン番号	時	分	パタン番号	時	分	パタン番号	時	分	パタン番号	時	分	パタン番号	時	分	パタン番号
	1	6	00	1	6	00	1	6	00	1												
	2																					
	3																					
	4																					
	5																					
	6																					
	7																					
	8																					
	9																					
A																						
動作切替	閃光	20:00～06:00			20:00～06:00			20:00～06:00														
系統動作定数	同期点																					
	追従幅																					
	追従階梯秒数配分																					
	主現示追従階梯																					
	従現示追従階梯																					
連動子機能定数	時刻修正				●																	
	DC方式								分周期連動機能定数	実行しきい値												
AC方式								運動パターン														
同期階梯1(B/Y1)																						
同期階梯2(A/Y2)																						
周期監視時間																						
共通オフセット1																						
共通オフセット2																						
運動親機																						
交通弱者感応定数																						
感応階梯								ステップ														
補正階梯								ステップ														
倍率指定 (10～19)								×0.1倍														
弱者用保証青時間 (0～99)								秒														
ギャップ感応定数	単位1						単位2															
		短縮	延長	単位青	単位青		短縮	延長	単位青	単位青												
		Ts	Te	上り0.1秒	下り0.1秒		Ts	Te	上り0.1秒	下り0.1秒												
	P1					P1																
	P2					P2																
	P3					P3																
	P4					P4																
	P5					P5																
	P6					P6																
	P7					P7																
	P8					P8																
	P9					P9																
PA					PA																	
感応階梯				感応階梯																		
補正階梯				補正階梯																		
感知器指定				感知器指定																		
リコール定数	感応階梯				ステップ																	
	補正階梯				ステップ																	
	感知器指定		押ボタン				車両															
	押ボタン受付禁止階梯								開始				終了									
車両リコール受付禁止階梯								開始				終了										
特殊日(プロ多)																						
日種	西暦	月	日																			
				平日(1)																		
				土曜(2)																		
				休日(3)																		
				毎年(55)																		
設定変更履歴																						
年月日				変更内容																		
2006年9月4日				夜間滅灯解除、夜間閃光運用に変更																		
2008年11月20日				制御機更新																		
2018年点検				作動時間表記誤りにて修正																		