

		(1) 平日			(2) 土曜			(3) 日曜			(4)特殊日1			(5)特殊日2			(6)特殊日3			(7)特殊日4		
パ タ ン 切 替	切替 番号	時	分	ハタ ン番号	時	分	ハタ ン番号	時	分	ハタ ン番号	時	分	ハタ ン番号	時	分	ハタ ン番号	時	分	ハタ ン番号	時	分	ハタ ン番号
	1	00	00	1	00	00	1	00	00	1												
	2																					
	3																					
	4																					
	5																					
	6																					
	7																					
	8																					
	9																					
A																						
動 作 切 替	連動子機 リコール	00:00～00:00			00:00～00:00			00:00～00:00														
系 統 動 作 定 数	同期点																					
	追従幅																					
	追従階梯秒数配分																					
	主現示追従階梯																					
	従現示追従階梯																					
	時刻修正																					
連 動 子 機 機 能 定 数	DC方式				-				分 周 期 連 動 機 能 定 数		実行しきい値		0									
	AC方式				○						連動パターン		1/1									
	同期階梯1(B/Y1)				2(親の1Yで同期)																	
	同期階梯2(A/Y2)				-																	
	周期監視時間				255秒																	
	共通オフセット1				個別オフセット																	
	共通オフセット2				-																	
	連動親機				01-1064 安東駅(西)																	
交通弱者感応定数																						
感応階梯								ステップ														
補正階梯								ステップ														
倍率指定 (10～19)								×0.1倍														
弱者用保証青時間(0～99)								秒														
ギ ャ ッ プ 感 応 定 数	単位1								単位2													
		短縮	延長	単位青	単位青		短縮	延長	単位青	単位青		短縮	延長	単位青	単位青							
		Ts	Te	上り0.1秒	下り0.1秒		Ts	Te	上り0.1秒	下り0.1秒		Ts	Te	上り0.1秒	下り0.1秒							
	P1					P1					P1											
	P2					P2					P2											
	P3					P3					P3											
	P4					P4					P4											
	P5					P5					P5											
	P6					P6					P6											
	P7					P7					P7											
	P8					P8					P8											
	P9					P9					P9											
	PA					PA					PA											
	感応階梯								感応階梯													
感応階梯		1		ステップ																		
補正階梯				ステップ																		
感知器指定		押ボタン				PB1		車両														
押ボタン受付禁止階梯										開始		5		終了		5						
車両リコール受付禁止階梯										開始				終了								
特殊日(プロ多)																						
平土休		西暦		月		日																