

Technical drawing of a road intersection, likely a T-junction or a complex intersection. The drawing includes the following elements:

- Top Left:** A compass rose indicating North (N) and South (S).
- Top Center:** A label "40km" in a box, indicating a speed limit or distance marker.
- Top Right:** Labels for road widths: "CVV-SS (2¹ × 20¹) 11.0" and "CVV-SS (2¹ × 2¹)". Below these is "中電柱 ヤマニシ幹 9 右 1 右 1".
- Center:** A vertical road with a "20.3m" dimension. A horizontal road crosses it, with a "26.4m" dimension. A "20°" angle is marked at the intersection.
- Bottom Center:** A label "40km" in a box, indicating a speed limit or distance marker.
- Left Side:** Labels for road widths: "CVV-SS (2¹ × 8¹) 17.0" and "CVV-SS (2¹ × 8¹) 17.0". A label "路管 (1) 号 CP9-14-500" is at the top left. A label "路管 (3) 号 SGP150 (A) BP-6" is at the bottom left. A label "速度表示無し" (No speed limit sign) is in a box.
- Right Side:** Labels for road widths: "CVV-SS (2¹ × 12¹) 17.0" and "CVV-SS (2¹ × 12¹) 17.0". A label "路管 (2) 号 SGP150 (A) BP-6 HS. 3" is at the bottom right. A label "速度表示無し" (No speed limit sign) is in a box.
- Other Labels:** "鉄製" (Iron) is used multiple times to describe materials. "φ300 鉄製" and "φ250 L=2.5 鉄製" are specific labels for pipes or structures. "φ750" is also labeled.

Figure 1 illustrates three examples of pedestrian crossing facilities, labeled (a), (b), and (c). Each example shows a crosswalk with a specific width and the number of pedestrian lights installed.

- (a) Crosswalk width: 8.2m, labeled "歩灯2灯" (2 pedestrian lights).
- (b) Crosswalk width: 8.4m, labeled "歩灯2灯" (2 pedestrian lights).
- (c) Crosswalk width: 9.1m, labeled "歩灯2灯" (2 pedestrian lights).

[illegible][illegible]

