

Diagram illustrating a road intersection scenario. The diagram shows a cross-section of the intersection with a central vertical road and a horizontal road crossing it. A vehicle is shown approaching from the left on the horizontal road, with a speed limit of 40km/h. Another vehicle is shown approaching from the top on the vertical road, with a speed limit of 40km/h. A third vehicle is shown approaching from the right on the horizontal road, with a speed limit of 40km/h. A fourth vehicle is shown approaching from the bottom on the vertical road, with a speed limit of 40km/h. The diagram includes dimensions: 30.2m for the horizontal distance from the center of the intersection to the vehicle on the right, and 32.9m for the vertical distance from the center of the intersection to the vehicle on the bottom. A label '速度無し' (No speed) is present at the top. A compass rose is located in the top right corner, indicating North (N) and South (S). The text '至 呉' (To R) is on the left, and '至 竹原' (To Takuhara) is on the right.

[illegible]

	(1) 平日			(2) 土曜			(3) 日曜			(4) 特殊日1			(5) 特殊日2			(6) 特殊日3			(7) 特殊日4		
パターン切替	切替番号	時	分	ハタン番号	時	分	ハタン番号	時	分	ハタン番号	時	分	ハタン番号	時	分	ハタン番号	時	分	ハタン番号		
	1	6	00	1	6	00	1	6	00	1											
	2	7	00	2	7	00	2	9	00	2											
	3	9	00	1	9	00	1	15	00	3											
	4	16	00	2	10	00	2	18	00	2											
	5	19	00	1	12	00	1	19	00	1											
	6				15	00	2														
	7				18	00	3														
	8				19	00	1														
	9																				
A																					
動作切替	閃光系統	23:00～06:00			23:00～06:00			23:00～06:00													
		00:00～00:00			00:00～00:00			00:00～00:00													
系統動作定数	同期点追従幅				1ステップ始め -5%/+20%																
	追従階梯秒数配分				スプリット比配分																
	主現示追従階梯				1																
	従現示追従階梯				6																
	時刻修正				●(GPS)																
連動子機能定数	DC方式								分周期連動機能定数	実行しきい値											
	AC方式									連動パターン											
	同期階梯1(B/Y1)																				
	同期階梯2(A/Y2)																				
	周期監視時間																				
	共通オフセット1																				
	共通オフセット2																				
	連動親機																				
高齢者感応定数																					
感応階梯				ステップ																	
補正階梯				ステップ																	
倍率指定 (10～19)				×0.1倍																	
高齢者用保証青時間(0～99)				秒																	
ギャップ感応定数	単位1				単位2																
		短縮	延長	単位青	単位青		短縮	延長	単位青	単位青											
		Ts	Te	上り0.1秒	下り0.1秒		Ts	Te	上り0.1秒	下り0.1秒											
	P1					P1															
	P2					P2															
	P3					P3															
	P4					P4															
	P5					P5															
	P6					P6															
	P7					P7															
	P8					P8															
	P9					P9															
	PA					PA															
	感応階梯				感応階梯																
補正階梯				補正階梯																	
感知器指定				感知器指定																	
リコール定数	感応階梯		ステップ																		
	補正階梯		ステップ																		
	感知器指定		押ボタン				車両														
	押ボタン受付禁止階梯								開始				終了								
	車両リコール受付禁止階梯								開始				終了								
曜日固定祝祭日テーブル																					
	月	週	曜日	日種																	
1	1	2	1	3																	
2	7	3	1	3																	
3	9	3	1	3																	
4	10	2	1	3																	
設定変更履歴																					
年月日				変更内容																	
2006年11月24日				現示変更(3現示→2現示)																	
2011年8月30日				制御機更新																	
2013年12月17日				設定表確認修正																	
2019年8月7日				制御機更新(災害被害)																	