

Technical drawing of the Saitama Expressway (Saitama Expressway) showing various bridge structures, spans, and dimensions. The drawing includes labels for bridge types (e.g., CVV-SS, SS), spans (e.g., 19.0, 20.0), and dimensions (e.g., 250φ, 142.5m). It also shows the location of the bridge relative to the surrounding area, including the Saitama Expressway and the Saitama Expressway Bridge.

流動図	至 大野町 10. 3m 歩灯なし 至 西広島バイパス		
------------	--	--	--

[illegible][illegible]

パ タ ン 切 替		(1) 平日			(2) 土曜			(3) 日曜			(4)特殊日1			(5)特殊日2			(6)特殊日3			(7)特殊日4		
	切替 番号	時	分	パタン 番号	時	分	パタン 番号	時	分	パタン 番号	時	分	パタン 番号	時	分	パタン 番号	時	分	パタン 番号	時	分	パタン 番号
	1	6	30	1	6	30	1	6	30	1												
	2	7	00	3	7	00	3	8	00	2												
	3	9	00	2	9	00	2	20	00	1												
	4	17	00	3	17	00	3															
	5	19	00	2	19	00	2															
	6	20	00	1	20	00	1															
	7																					
	8																					
9																						
A																						
動 作 切 替	閃光	22:00～06:30			22:00～06:30			22:00～06:30														
	リコール	06:30～07:00			06:30～07:00			06:30～07:00														
	リコール	09:00～22:00			09:00～22:00			09:00～22:00														
	系統	00:00～00:00			00:00～00:00			00:00～00:00														
系 統 動 作 定 数	同期点				1ステップ始め																	
	追従幅				-5%/+20%																	
	追従階梯秒数配分				スプリット比配分																	
	主現示追従階梯				1																	
	従現示追従階梯				7																	
	時刻修正				●																	
運 動 子 機 能 定 数	DC方式								分 周 期 運 動 機 能 定 数	実行しきい値												
	AC方式									連動パターン												
	同期階梯1(B/Y1)																					
	同期階梯2(A/Y2)																					
	周期監視時間																					
	共通オフセット1																					
	共通オフセット2																					
連動親機																						
交通弱者感応定数																						
感応階梯										ステップ												
補正階梯										ステップ												
倍率指定 (10～19)										×0.1倍												
弱者用保証青時間 (0～99)										秒												
ギ ャ ッ プ 感 応 定 数	単位1								単位2													
		短縮	延長	単位青	単位青		短縮	延長	単位青	単位青		短縮	延長	単位青	単位青							
		Ts	Te	上り0.1秒	下り0.1秒		Ts	Te	上り0.1秒	下り0.1秒		Ts	Te	上り0.1秒	下り0.1秒							
	P1					P1					P1											
	P2					P2					P2											
	P3					P3					P3											
	P4					P4					P4											
	P5					P5					P5											
	P6					P6					P6											
	P7					P7					P7											
	P8					P8					P8											
	P9					P9					P9											
	PA					PA					PA											
	感応階梯								感応階梯													
補正階梯								補正階梯														
感知器指定								感知器指定														
リ コ ー ル 定 数	感応階梯		1		ステップ																	
	補正階梯				ステップ																	
	感知器指定		押ボタン		PB1		車両		D1													
			押ボタン受付禁止階梯				開始		7		終了		7									
			車両リコール受付禁止階梯				開始		7		終了		9									
曜日固定祝祭日テーブル																						
	月	週	曜日																			
1	1	2	1																			
2	7	3	1																			
3	9	3	1																			
4	10	2	1																			
設定変更履歴																						
年月日				変更内容																		
2013年7月24日				制御機更新																		

備 考
地点感応制御機の場合左記の
ギャップ感応定数表の内容は
下記の通りです。

短縮 Ts → ありません。
延長 Te → 限度青です。
単位青 上り → 単位青です。
単位青 下り → ありません。
単位青秒数は 0.5秒単位です。

名称はこのように変更してください。

規制番号	28-0043
名 称	阿品台西4番