



Technical drawing of a bridge section. The drawing shows a horizontal bridge structure with a central span labeled "17.5m". Below the bridge, there are two sets of tracks or roads. On the left, a box contains the text "40km/h". On the right, a box contains the text "40km/h". Above the bridge, there are two vertical lines with circles at the top, possibly representing support structures or sensors. A diagonal line with a circle at the bottom and an arrow pointing upwards is also shown. The drawing is oriented horizontally, with the bridge spanning from left to right. The text "至 広島" (To Hiroshima) is on the left and "至 福岡" (To Fukuoka) is on the right. A north arrow is located in the top right corner.

流動図			
------------	---	---	---

[illegible][illegible]

	(1) 平日			(2) 土曜			(3) 日曜			(4)特殊日1			(5)特殊日2			(6)特殊日3			(7)特殊日4					
パ タ ン 切 替	切替 番号	時	分	ハタン 番号	時	分	ハタン 番号	時	分	ハタン 番号	時	分	ハタン 番号	時	分	ハタン 番号	時	分	ハタン 番号	時	分	ハタン 番号		
	1	6	00	1	6	00	1	6	00	1														
	2	7	00	6	7	30	3	7	30	3														
	3	8	00	5	9	00	5	9	00	5														
	4	9	00	4	10	00	6	10	00	6														
	5	10	00	3	11	00	5	11	00	5														
	6	14	00	4	15	00	4	15	00	4														
	7	17	00	5	17	00	5	17	00	5														
	8	19	00	3	18	30	4	18	30	4														
	9	20	00	1	19	30	1	19	30	1														
	A																							
動 作 切 替	系統	00:00～00:00			00:00～00:00			00:00～00:00																
系 統 動 作 定 数	同期点 追従幅						1ステップ始め -5%/+20%																	
	追従階梯秒数配分						スプリット比配分																	
	主現示追従階梯						1																	
	従現示追従階梯						7																	
	時刻修正						●(GPS)																	
連 動 子 機 能 定 数	DC方式						分 周 期 連 動 機 能 定 数						実行しきい値											
	AC方式												連動パターン											
	同期階梯1(B/Y1)																							
	同期階梯2(A/Y2)																							
	周期監視時間																							
	共通オフセット1																							
	共通オフセット2																							
	連動親機																							
高齢者感応定数																								
感応階梯										ステップ														
補正階梯										ステップ														
倍率指定 (10～19)										×0.1倍														
高齢者用保証青時間(0～99)										秒														
ギ ャ ッ プ 感 応 定 数	単位1								単位2								備 考 地点感応制御機の場合左記の ギャップ感応定数表の内容は 下記の通りです。 短縮 Ts → ありません。 延長 Te → 限度青です。 単位青 上り → 単位青です。 単位青 下り → ありません。 単位青秒数は 0.5秒単位です。 名称はこのように変更してください。							
		短縮	延長	単位青	単位青		短縮	延長	単位青	単位青		短縮	延長	単位青	単位青									
		Ts	Te	上り0.1秒	下り0.1秒		Ts	Te	上り0.1秒	下り0.1秒		Ts	Te	上り0.1秒	下り0.1秒									
	P1					P1					P1													
	P2					P2					P2													
	P3					P3					P3													
	P4					P4					P4													
	P5					P5					P5													
	P6					P6					P6													
	P7					P7					P7													
	P8					P8					P8													
	P9					P9					P9													
	PA					PA					PA													
	感応階梯								感応階梯															
	補正階梯								補正階梯															
	感知器指定								感知器指定															
リ コ ー ル 定 数	感応階梯				ステップ																			
	補正階梯				ステップ																			
	感知器指定				押ボタン												車両							
	押ボタン受付禁止階梯																開始				終了			
	車両リコール受付禁止階梯																開始				終了			
曜日固定祝祭日テーブル																								
月	週	曜日	日種																					
1	1	2	1	3																				
2	7	3	1	3																				
3	9	3	1	3																				