

		(1) 平日			(2) 土曜			(3) 日曜			(4) 特殊日1			(5) 特殊日2			(6) 特殊日3			(7) 特殊日4		
パ タ ン 切 替	切替 番号	時	分	ハタ ン番号	時	分	ハタ ン番号	時	分	ハタ ン番号	時	分	ハタ ン番号	時	分	ハタ ン番号	時	分	ハタ ン番号	時	分	ハタ ン番号
	1	6	00	1	6	00	1	6	00	1												
	2																					
	3																					
	4																					
	5																					
	6																					
	7																					
	8																					
	9																					
A																						
動 作 切 替	系統	00:00～00:00			00:00～00:00			00:00～00:00														
	リコール1	00:00～00:00			00:00～00:00			00:00～00:00														
系 統 動 作 定 数	同期点 追従幅				1ステップ始め -5%/+20%																	
	追従階梯秒数配分				スプリット比配分																	
	主現示追従階梯				1																	
	従現示追従階梯				7																	
	時刻修正				●(GPS)																	
連 動 子 機 能 定 数	DC方式								分 周 期 連 動 機 能 定 数	実行しきい値												
	AC方式									連動パターン												
	同期階梯1(B/Y1)																					
	同期階梯2(A/Y2)																					
	周期監視時間																					
	共通オフセット1																					
	共通オフセット2																					
	連動親機																					
高齢者感応定数																						
感応階梯				ステップ																		
補正階梯				ステップ																		
倍率指定 (10～19)				×0.1倍																		
高齢者用保証青時間(0～99)				秒																		
ギ ャ ッ プ 感 応 定 数	単位1					単位2					備 考											
	短縮	延長	単位青	単位青		短縮	延長	単位青	単位青													
	Ts	Te	上り0.1秒	下り0.1秒		Ts	Te	上り0.1秒	下り0.1秒													
	P1					P1								地点感応制御機の場合左記の ギャップ感応定数表の内容は 下記の通りです。 短縮 Ts → ありません。 延長 Te → 限度青です。 単位青 上り → 単位青です。 単位青 下り → ありません。 単位青秒数は 0.5秒単位です。								
	P2					P2																
	P3					P3																
	P4					P4																
	P5					P5																
	P6					P6																
	P7					P7																
	P8					P8																
	P9					P9																
	PA					PA																
	感応階梯					感応階梯																
補正階梯					補正階梯																	
感知器指定					感知器指定																	
リ コ ー ル 定 数	感応階梯		1		ステップ																	
	補正階梯				ステップ																	
	感知器指定		押ボタン		PB1		車両															
	押ボタン受付禁止階梯							開始		7		終了		7								