


Diagram illustrating a road intersection with a speed limit sign and a speed limit indicator.

The diagram shows a road intersection with a speed limit sign (40km/h) and a speed limit indicator (40km/h). The road is labeled "至 広島" (To Hiroshima) and "至 福山" (To Fuyukawa). The speed limit is indicated as "40km/h".

The diagram also shows a speed limit sign with the text "速度表示なし" (No speed limit sign) and a speed limit indicator with the text "速度表示なし" (No speed limit sign).

The diagram includes a north arrow and a scale bar indicating 29.7m and 21.5m.

流動図	4. 3m 歩灯2  10. 3m 歩灯2	10. 5m 歩灯2 	
------------	--	---	---

[illegible][illegible]

パ タ ン 切 替		(1) 平日			(2) 土曜			(3) 日曜			(4)特殊日1			(5)特殊日2			(6)特殊日3			(7)特殊日4			
	切替 番号	時	分	パタ ン番号	時	分	パタ ン番号	時	分	パタ ン番号	時	分	パタ ン番号	時	分	パタ ン番号	時	分	パタ ン番号	時	分	パタ ン番号	
	1	6	00	1	6	00	1	6	00	1													
	2	6	30	3	7	30	3	7	30	3													
	3	7	00	7	8	0	5	8	00	5													
	4	9	00	6	9	0	6	9	00	6													
	5	12	00	7	10	0	7	10	00	7													
	6	19	00	5	19	0	5	19	00	5													
	7	20	00	2	20	0	2	20	00	2													
	8	21	00	1	21	0	1	21	00	1													
9																							
A																							
動 作 切 替	系統	00:00～00:00			00:00～00:00			00:00～00:00															
系 統 動 作 定 数	同期点			1ステップ始め																			
	追従幅			-5%/+20%																			
	追従階梯秒数配分			スプリット比配分																			
	主現示追従階梯			1																			
	従現示追従階梯			7																			
	時刻修正			●(GPS)																			
運 動 子 機 能 定 数	DC方式																		分 周 期 連 動 機 能 定 数	実行しきい値			
	AC方式																			連動パターン			
	同期階梯1(B/Y1)																						
	同期階梯2(A/Y2)																						
	周期監視時間																						
	共通オフセット1																						
	共通オフセット2																						
連動親機																							
高齢者感応定数																							
感応階梯										ステップ													
補正階梯										ステップ													
倍率指定 (10～19)										×0.1倍													
高齢者用保証青時間(0～99)										秒													
ギ ャ ッ プ 感 応 定 数	単位1								単位2								備 考 地点感応制御機の場合左記の ギャップ感応定数表の内容は 下記の通りです。 短縮 Ts → ありません。 延長 Te → 限度青です。 単位青 上り → 単位青です。 単位青 下り → ありません。 単位青秒数は 0.5秒単位です。 名称はこうに変更してください。						
		短縮	延長	単位青	単位青		短縮	延長	単位青	単位青													
		Ts	Te	上り0.1秒	下り0.1秒		Ts	Te	上り0.1秒	下り0.1秒													
	P1					P1																	
	P2					P2																	
	P3					P3																	
	P4					P4																	
	P5					P5																	
	P6					P6																	
	P7					P7																	
	P8					P8																	
	P9					P9																	
	PA					PA																	
	感応階梯				感応階梯																		
補正階梯				補正階梯																			
感知器指定				感知器指定																			
リ コ ー ル 定 数	感応階梯		ステップ																				
	補正階梯		ステップ																				
	感知器指定		押ボタン		車両																		
			押ボタン受付禁止階梯		開始		終了																
		車両リコール受付禁止階梯		開始		終了																	
曜日固定祝祭日テーブル																							
月	週	曜日	日種																				
1	1	2	1	3																			
2	7	3	1	3																			
3	9	3	1	3																			
4	10	2	1	3																			
設定変更履歴																							
年月日				変更内容																			
2025年11月28日				制御機更新(地域外制御に変更)																			