

The flow diagram illustrates the traffic layout at the intersection. It features a north arrow pointing upwards. The diagram is divided into four quadrants by the intersection. The top-left quadrant is labeled '至 蓮池' (To Lotus Pond) and shows a vertical road with a distance of 7.1m and '歩灯なし' (No pedestrian crossing). The top-right quadrant is labeled '至 蓮池' (To Lotus Pond) and shows a vertical road with a distance of 6.3m and '歩灯なし' (No pedestrian crossing). The bottom-left quadrant is labeled '至 国道2号' (To National Route 2) and shows a vertical road with a distance of 7.4m and '歩灯なし' (No pedestrian crossing). The bottom-right quadrant is labeled '至 福山駅' (To Fukuyama Station) and shows a vertical road with a distance of 7.2m and '歩灯なし' (No pedestrian crossing). Arrows indicate the direction of traffic flow for each road.

[illegible]

パ タ ン 切 替	(1) 平日			(2) 土曜			(3) 日曜			(4) 特殊日1			(5) 特殊日2			(6) 特殊日3			(7) 特殊日4		
	切替 番号	時	分	パタ ン 番 号	時	分	パタ ン 番 号	時	分	パタ ン 番 号	時	分	パタ ン 番 号	時	分	パタ ン 番 号	時	分	パタ ン 番 号		
	1	7	00	5	7	00	5	7	00	3											
2	9	00	3	9	00	3	9	00	5												
3	12	00	4	12	00	4	12	00	4												
4	16	00	6	16	00	6	21	00	2												
5	19	00	4	19	00	4															
6	21	00	2	21	00	2															
7																					
8																					
9																					
A																					
動作切替	系統	00:00～00:00			00:00～00:00			00:00～00:00													
系統動作定数	同期点						1ステップ始め														
	追従幅						-5%/+20%														
	追従階梯秒数配分						スプリット比配分														
	主現示追従階梯						1														
	従現示追従階梯						6														
	時刻修正						●(GPS)														
連動子機能定数	DC方式												分 周 期 連 動 機 能 定 数	実行しきい値							
	AC方式													連動パターン							
	同期階梯1(B/Y1)																				
	同期階梯2(A/Y2)																				
	周期監視時間																				
	共通オフセット1																				
	共通オフセット2																				
連動親機																					
高齢者感応定数																					
感応階梯						ステップ															
補正階梯						ステップ															
倍率指定 (10～19)						×0.1倍															
高齢者用保証青時間(0～99)						秒															
ギャップ感応定数	単位1								単位2												
	短縮		延長		単位青		単位青		短縮		延長		単位青		単位青						
	Ts		Te		上り0.1秒		下り0.1秒		Ts		Te		上り0.1秒		下り0.1秒						
	P1								P1												
	P2								P2												
	P3								P3												
	P4								P4												
	P5								P5												
	P6								P6												
	P7								P7												
	P8								P8												
	P9								P9												
	PA								PA												
	感応階梯						感応階梯														
補正階梯						補正階梯															
感知器指定						感知器指定															
リコール定数	感応階梯				ステップ																
	補正階梯				ステップ																
	感知器指定		押ボタン				車両														
			押ボタン受付禁止階梯						開始				終了								
		車両リコール受付禁止階梯						開始				終了									
曜日固定祝祭日テーブル																					
月	週	曜日	日種																		
1	1	2	1	3																	
2	7	3	1	3																	
3	9	3	1	3																	
4	10	2	1	3																	
設定変更履歴																					
年月日				変更内容																	
2018年12月20日				制御機更新																	

規制番号	07-0318
名称	西2番ガード南

備考
 地点感応制御機の場合左記のギャップ感応定数表の内容は下記の通りです。

短縮 Ts → ありません。
 延長 Te → 限度青です。
 単位青 上り → 単位青です。
 単位青 下り → ありません。
 単位青秒数は 0.5秒単位です。

名称はこうに変更してください。