CSS Bookmark Properties

This example demonstrates the GCPM `bookmark-level` and `bookmark-label` properties. Open the PDF in a viewer that shows the outline (bookmarks) panel to see the result.

Automatic Headings

Headings h1 and h2 automatically appear in the PDF outline via fulgur's built-in UA stylesheet. Each heading gets a bookmark at its corresponding level with its text content as the label.

Suppressed Subheading

This h3 has `bookmark-level: none` in the author stylesheet, so it does *not* appear in the outline — even though fulgur's UA stylesheet would normally assign it level 3.

Custom Elements

Any element can opt into the outline. The appendix sections below use `bookmark-level: 2` and `bookmark-label: "Appendix: " attr(data-title)` to create outline entries from a `data-title` attribute.

> ### Appendix A — Glossary
>
> **bookmark-level**: Sets the nesting depth of an outline entry. An integer (1–6 typical) or none to suppress.
>
> **bookmark-label**: Defines the text shown in the outline. Accepts `content()`, `attr()`, and string literals.

Appendix B — References

CSS Generated Content for Paged Media Module Level 3, §7 Bookmarks. W3C Working Draft.

Prince XML — `prince-bookmark-state` property documentation.

Outline structure: "CSS Bookmark Properties" (level 1) → "Automatic Headings" (level 2), "Custom Elements" (level 2), "Appendix: Glossary" (level 2), "Appendix: References" (level 2). The h3 "Suppressed Subheading" is absent from the outline.