# Quarterly Accessibility Report

This document demonstrates fulgur's Tagged PDF output. When rendered with `--tagged` or `--pdf-ua`, the PDF contains a structure tree that screen readers and accessibility tools can traverse.

## Summary

Tagged PDF embeds semantic structure — headings, paragraphs, lists, tables, figures, and links — directly in the PDF file. This structure is required for PDF/UA-1 conformance and enables assistive technologies to present documents in a meaningful order.

## Supported Elements

The following HTML elements map to PDF structure tags:

| HTML element | PDF structure tag |
|---|---|
| `h1`–`h6` | H1–H6 |
| `p`, `div` | P, Div |
| `span` | Span |
| `ul` | L (unordered) |
| `ol` | L (ordered) |
| `li` | LI → Lbl + LBody |
| `table` | Table |
| `thead` / `tbody` / `tfoot` | THead / TBody / TFoot |
| `tr` | TR |
| `th` | TH (scope: Row/Column/Both) |
| `td` | TD |
| `img` | Figure (alt text propagated) |
| `a` | Link |

## Step-by-Step Workflow

1. Author semantic HTML using the elements listed above.
2. Run fulgur with `--tagged` (structure tree) or `--pdf-ua` (full PDF/UA-1).
3. Verify the output with a PDF accessibility checker such as PAC 2024 or Adobe Acrobat's accessibility tool.

## Known Limitations

- Alt text is propagated from `img alt` attributes only; CSS background images are not tagged.
- PDF/UA-1 requires a document language. Always pass `--language` (CLI) or `.lang()` (API) when using `--pdf-ua`.
- Python and Ruby bindings do not yet expose `tagged` / `pdf_ua` options.

## CLI Usage

Generate a Tagged PDF:

```
fulgur render --tagged --language en -o report.pdf report.html
```

Generate a PDF/UA-1 conformant PDF (implies --tagged and --bookmarks):

```
fulgur render --pdf-ua --language en -o report.pdf report.html
```