

Bruce M.
Boghosian

Motivation

Bayesian
search
strategy

Summary

Bayesian estimation

Bayesian search strategy

Bruce M. Boghosian



Tufts
UNIVERSITY

School of Arts
and Sciences

Department of Mathematics

Tufts University

Bruce M.
Boghosian

Motivation

Bayesian
search
strategy

Summary

1 Motivation

2 Bayesian search strategy

3 Summary

Bruce M.
Boghosian

Motivation

Bayesian
search
strategy

Summary

- Suppose we are trying to find a lost object.
- We have some ideas of regions where to search.
- There is no certainty that we will find the object, even if we search the region in which it is located.
- For example, searches of the ocean floor for lost objects.

Bruce M.
Boghosian

Motivation

Bayesian
search
strategy

Summary

- $A_j :=$ Event missing object is in region r_j
- $B_j :=$ Event object would be found if it was in r_j , and r_j was searched
- $P(A_j \mid B_j^C)$ is probability that the item is in r_j , given that r_j was just searched unsuccessfully.
- Start with *prior* estimates for the probabilities $\{P(A_j)\}_{j=1}^n$. These could be as simple as the uniform distribution

$$\forall j \in \{1, \dots, n\} : P(A_j) = \frac{1}{n}.$$

- Suppose region r_j is searched, and nothing is found there.

- Apply Bayes' Theorem, and note that $P(B_j^C | A_j^C) = 1$

$$\begin{aligned} P(A_j | B_j^C) &= \frac{P(B_j^C | A_j) P(A_j)}{P(B_j^C | A_j) P(A_j) + P(B_j^C | A_j^C) P(A_j^C)} \\ &= \frac{[1 - P(B_j | A_j)] P(A_j)}{[1 - P(B_j | A_j)] P(A_j) + [1 - P(A_j)]} = \left[\frac{1 - P(B_j | A_j)}{1 - P(B_j | A_j) P(A_j)} \right] P(A_j) \end{aligned}$$

- Hence, after unsuccessful search in r_j , prior for $P(A_j)$ is updated to obtain

$$P^*(A_j) = P(A_j | B_j^C) = \left[\frac{1 - P(B_j | A_j)}{1 - P(B_j | A_j) P(A_j)} \right] P(A_j) < P(A_j).$$

- Rescale all the other priors, $P(A_k)$ where $k \neq j$,

$$P^*(A_k) = P(A_k | B_j^c) = \alpha_j P(A_k)$$

- Demand normalization $1 = \sum_{m=1}^n P^*(A_m)$ to find

$$\alpha_j = \frac{1}{1 - P(B_j | A_j)P(A_j)}$$

- So the other priors update as follows

$$P^*(A_k) = P(A_k | B_j^c) = \left[\frac{1}{1 - P(B_j | A_j)P(A_j)} \right] P(A_k) \text{ if } P(A_k) > P(A_j).$$

Bruce M.
Boghossian

Motivation

Bayesian
search
strategy

Summary

- For all $m = 1, \dots, n$:
 - Determine the probabilities that a search in r_m will find the object if it is in r_m .
 - Guess the priors $P(A_m)$.
- Now repeat until the object is found:
 - Suppose value of m for which $P(A_m)$ is highest is $m = j$.
 - Conduct a search in region r_j
 - If the search is unsuccessful, update the priors and repeat.

Bruce M.
Boghossian

Motivation

Bayesian
search
strategy

Summary

- We have studied Bayesian search strategy
- We have presented an algorithm for Bayesian search