ACTIVATED CARBON CATALOG

2026







PT. MUDA EKSPORTINDO RAYA

WEBSITE
Www.cocoblim.com

ADDRESS
Bogor city, Indonesia

WHATSAPP
+62 857 7106 0642

EMAIL
blim00coco@gmail.com



INDONESIA ACTIVATED CARBON PRODUCT

Granular Activated Carbon (GAC)



Powdered Activated Carbon (PAC)



Pelletized Activated Carbon (PAC)





Water Treatment & Air/Gas Purification Activated Carbon



Food Grade Activated Carbon



Industrial Grade Activated Carbon

Whatsapp
+62 857 7106 0642

Website
Www.cocoblim.com

Address
Bogor city, Indonesia



GRANULAR ACTIVATED CARBON (GAC)

SPECIFICATION

- **Mesh Size:** 4x8 / 6x12 / 8x30 / Customized
- **Moisture:** Max 5%
- **Ash Content:** Low (<5%)
- **Iodine Number:** 800 – 1100 mg/g
- **Packaging:** 25kg bag / Jumbo bag / Custom

CHARACTERISTICS

Adsorption Capacity:
High (Iodine Value up to 1000+ mg/g)

Hardness:
High mechanical strength with low attrition

Porosity:
Well developed microporous structure for optimal adsorption

Purity:
Low ash content for enhanced performance

Performance:
Stable and consistent across industrial applications

DESCRIPTION SCHEME

Raw Material: Coconut Shell

Processing Method: Carbonization & Steam Activation

Application: Water treatment, mining, air purification

Production Area: Indonesia

Quality Control: Lab tested & batch controlled

Usage Type: Industrial & commercial application

Export Standard: International specification compliance



POWDERED ACTIVATED CARBON (PAC)

SPECIFICATION

- **Mesh Size:** Powder (typically <100 mesh / customized)
- **Moisture:** Max 5%
- **Ash Content:** Low (<5%)
- **Iodine Number:** 800 – 1100 mg/g
- **Packaging:** 25kg bag / Jumbo bag / Custom

CHARACTERISTICS

Adsorption Capacity:
High (Iodine Value up to 1000+ mg/g)

Particle Size:
Fine powder for rapid adsorption and high surface contact

Porosity:
Highly developed microporous structure for maximum efficiency

Purity:
Low ash content for enhanced performance

Performance:
Fast-acting and highly effective in liquid-phase applications

DESCRIPTION SCHEME

Raw Material: Coconut Shell

Processing Method: Carbonization & Steam Activation

Application: Water treatment, wastewater treatment, food & beverage purification, chemical processing

Production Area: Indonesia

Quality Control: Lab tested & batch controlled

Usage Type: Industrial & commercial application

Export Standard: International specification compliance



PELLETIZED ACTIVATED CARBON (PAC

SPECIFICATION

•**Pellet Diameter:** 2mm / 3mm / 4mm / Customized

• **Moisture:** Max 5%

• **Ash Content:** Low (<5%)

• **Iodine Number:** 800 – 1100 mg/g

• **Packaging:** 25kg bag / Jumbo bag / Custom

CHARACTERISTICS

Adsorption Capacity:
High (Iodine Value up to 1000+ mg/g)

Hardness: Extremely high mechanical strength with minimal attrition and dust formation

Porosity:
Well-developed microporous structure optimized for gas and vapor adsorption

Purity:
Low ash content for enhanced efficiency

Performance:
Stable, long-lasting, and highly efficient in continuous industrial operations

DESCRIPTION SCHEME

Raw Material: Coconut Shell

Processing Method: Carbonization & Steam Activation & Extrusion

Application: Air purification, gas treatment, solvent recovery, VOC removal

Production Area: Indonesia

Quality Control: Lab tested & batch controlled

Usage Type: Industrial & commercial application

Export Standard: International specification compliance



WATER TREATMENT & AIR/GAS PURIFICATION ACTIVATED CARBON

SPECIFICATION

- **Mesh Size:** 4×8 / 6×12 / 8×30 / Customized
- **Moisture:** Max 5%
- **Ash Content:** Low (<5%)
- **Iodine Number:** 800 – 1100 mg/g
- **Packaging:** 25kg bag / Jumbo bag / Custom

CHARACTERISTICS

Adsorption Capacity:
High (Iodine Value up to 1000+ mg/g)

Hardness:
High mechanical strength with low attrition for long service life

Porosity: Highly microporous structure ideal for adsorption of dissolved and gaseous contaminants

Purity:
Low ash content to ensure maximum filtration performance

Performance:
Stable and consistent across continuous filtration systems

DESCRIPTION SCHEME

Raw Material: Coconut Shell

Processing Method: Carbonization & Steam Activation

Application: Water treatment, air purification, gas filtration, VOC removal

Production Area: Indonesia

Quality Control: Lab tested & batch controlled

Usage Type: Industrial & commercial application

Export Standard: International specification compliance



FOOD GRADE ACTIVATED CARBON

SPECIFICATION

•**Mesh Size:** Powder / Fine Mesh / Customized (based on application)

• **Moisture:** Max 5%

• **Ash Content:** Very low (<5%)

• **Iodine Number:** 900 – 1100 mg/g

• **Packaging:** 25kg bag / Jumbo bag / Custom

CHARACTERISTICS

Adsorption Capacity: High (Iodine Value up to 1000+ mg/g)

Purity: Ultra-low ash and impurity content suitable for food-grade applications

Porosity: Highly developed microporous structure for effective removal of color, odor, and contaminants

Safety: Compliant with food-grade processing standards and safe for consumable applications

Color Removal Efficiency: Excellent performance in decolorization of liquids (sugar, oils, beverages)

DESCRIPTION SCHEME

Raw Material: Coconut Shell

Processing Method: Carbonization & Steam Activation

Application: Food & beverage processing, sugar refining, edible oil purification, pharmaceutical filtration

Production Area: Indonesia

Quality Control: Lab tested & batch controlled & food-grade compliant

Usage Type: Food, beverage & pharmaceutical application

Export Standard: International food-grade specification compliance



INDUSTRIAL GRADE ACTIVATED CARBON

SPECIFICATION

- **Mesh Size:** 4×8 / 6×12 / 8×30 / Customized
- **Moisture:** Max 5%
- **Ash Content:** low (<5%)
- **Iodine Number:** 800 – 1100 mg/g
- **Packaging:** 25kg bag / Jumbo bag / Custom

CHARACTERISTICS

Adsorption Capacity:
High (Iodine Value up to 1000+ mg/g)

Hardness: High mechanical strength with low attrition for extended operational use

Porosity: Well-developed microporous structure for broad-spectrum adsorption

Versatility: Suitable for liquid-phase and gas-phase industrial applications

Performance: Stable and consistent across continuous industrial systems

DESCRIPTION SCHEME

Raw Material: Coconut Shell

Processing Method: Carbonization & Steam Activation

Application: Water treatment, air & gas purification, solvent recovery, chemical processing, wastewater treatment

Production Area: Indonesia

Quality Control: Lab tested & batch controlled & food-grade compliant

Usage Type: Food, beverage & pharmaceutical application

Export Standard: International food-grade specification compliance



THANK YOU

PT. MUDA EKSPORTINDO RAYA

WEBSITE

Www.cocoblim.com

ADDRESS

Bogor city, Indonesia

WHATSAPP

+62 857 7106 0462

EMAIL

blim00coco@gmail.com