

GitHub Actions CI/CDガイド

EC2の環境設定

環境変数ファイルの作成

1. 環境変数ファイルの作成

- ファイル:/etc/fullness/frontend.env

```
sudo tee /etc/fullness/frontend.env > /dev/null <<'EOF'  
DB_URL=jdbc:postgresql://trainingdb.cpqokejeyom7.ap-northeast-  
1.rds.amazonaws.com:5432/fullness-ec  
DB_USERNAME=postgres  
DB_PASSWORD=TrainingDBUser  
AWS_REGION=ap-northeast-1  
AWS_S3_BUCKET=fullness-ec-product-images-furukawa  
EOF
```

systemd サービス

1. サービス定義の作成

- ファイル:/etc/systemd/system/fullness-frontend.service

```
sudo tee /etc/systemd/system/fullness-frontend.service > /dev/null <<'EOF'  
[Unit]  
Description=Fullness EC Frontend (ec-answer)  
After=network.target  
  
[Service]  
User=fullness  
EnvironmentFile=/etc/fullness/frontend.env  
ExecStart=/usr/bin/java -jar /opt/fullness/frontend.jar  
SuccessExitStatus=143  
Restart=on-failure  
RestartSec=5  
  
[Install]  
WantedBy=multi-user.target  
EOF
```

2. 起動と有効化

```
sudo systemctl daemon-reload
```

```
sudo systemctl enable fullness-frontend
```

CI/CDワークフロー

```
name: Frontend CI

on:
  push:
    branches: [ main ]
    paths:
      - 'ec-answer/**'
      - '.github/workflows/frontend-cicd.yml'
  pull_request:
    paths:
      - 'ec-answer/**'

jobs:
  build:
    runs-on: ubuntu-latest

    services:
      postgres:
        image: postgres:17
        env:
          POSTGRES_DB: fullness-ec
          POSTGRES_USER: postgres
          POSTGRES_PASSWORD: training
        ports:
          - 5432:5432
        options: >-
          --health-cmd "pg_isready -U postgres -d fullness-ec"
          --health-interval 10s
          --health-timeout 5s
          --health-retries 5

    steps:
      - name: Checkout
        uses: actions/checkout@v4

      - name: Set up JDK 17
        uses: actions/setup-java@v4
        with:
          distribution: temurin
          java-version: '17'

      # スキーマ + シード投入(name_kana 対応版)
      - name: Initialize database (schema + seed)
        env:
          PGPASSWORD: training
        run: |
          psql -h localhost -U postgres -d fullness-ecx -f ec-
```

```
answer/src/main/resources/sql/create_tables.sql
psql -h localhost -U postgres -d fullness-ecx -f ec-
answer/src/main/resources/sql/insert_data.sql

- name: Grant gradlew permission
  working-directory: ec-answer
  run: chmod +x ./gradlew

- name: Build & Test
  working-directory: ec-answer
  env:
    DB_URL: jdbc:postgresql://localhost:5432/fullness-ec
    DB_USERNAME: postgres
    DB_PASSWORD: training
  run: ./gradlew build

- name: Upload test report
  if: always()
  uses: actions/upload-artifact@v4
  with:
    name: frontend-test-report
    path: ec-answer/build/reports/tests/test

deploy:
  needs: build
  if: github.event_name == 'push' && github.ref == 'refs/heads/main'
  runs-on: ubuntu-latest
  steps:
    - name: Checkout
      uses: actions/checkout@v4

    - name: Set up JDK 17
      uses: actions/setup-java@v4
      with:
        distribution: temurin
        java-version: '17'

    - name: 実行用JARをビルド
      working-directory: ec-answer
      run: |
        chmod +x ./gradlew
        ./gradlew clean bootJar

    - name: JARをEC2へ転送
      uses: appleboy/scp-action@v0.1.7
      with:
        host: ${ secrets.EC2_HOST }
        username: ${ secrets.EC2_USER }
        key: ${ secrets.EC2_SSH_KEY }
        source: "ec-answer/build/libs/*-SNAPSHOT.jar"
        target: "/tmp/"
        strip_components: 3

    - name: 配置してサービス再起動
```

```
uses: appleboy/ssh-action@v1.0.3
with:
  host: ${ secrets.EC2_HOST }
  username: ${ secrets.EC2_USER }
  key: ${ secrets.EC2_SSH_KEY }
  script: |
    sudo mv /tmp/*-SNAPSHOT.jar /opt/fullness/frontend.jar
    sudo chown fullness:fullness /opt/fullness/frontend.jar
    sudo systemctl restart fullness-frontend
    sleep 5
    sudo systemctl is-active fullness-frontend
```