

On the Statistical Mechanics of Virtual Gas Molecule Ensembles: Categorical Bounded Phase Space Recurrence and the Derivation of Ideal Gas Laws

Kundai Farai Sachikonye
kundai.sachikonye@wzw.tum.de

February 21, 2026

Abstract

We establish that oscillation, categorical distinction, and partition operation constitute three equivalent descriptions of a single mathematical structure—the *triple equivalence*. Any bounded dynamical system necessarily exhibits periodic behavior; this periodicity defines distinguishable states (categories) whose sequential traversal constitutes the oscillation; the temporal segments between states are partitions of the period. From this foundation, we develop a computational framework in which computation is defined as trajectory completion in a bounded three-dimensional S-entropy phase space $\mathcal{S} = [0, 1]^3$, with solution equivalence to Poincaré recurrence.

Part I: Triple Equivalence and Thermodynamics. We derive entropy in three mathematically identical forms: categorical $S = k_B M \ln n$, oscillatory $S = k_B \sum_i \ln(A_i/A_0)$, and partition-based $S = k_B \sum_a \ln(1/s_a)$. All fundamental thermodynamic quantities—temperature, pressure, internal energy—admit equivalent formulations in each perspective, yielding identical physical predictions. The ideal gas law $PV = Nk_B T$ emerges as a categorical balance condition. The Maxwell-Boltzmann velocity distribution arises as the continuum limit of discrete categorical structure, naturally bounded by the speed of light without ad hoc relativistic corrections.

Part II: Poincaré Computing Architecture. We prove nine principal results: (i) the bounded phase space $\mathcal{S}$ satisfies the Poincaré recurrence theorem; (ii) computational problems correspond to initial states with constraint sets, solutions to recurrent trajectories; (iii) categorical states simultaneously encode memory address, processor state, and semantic content, eliminating the von Neumann bottleneck; (iv) Poincaré Computing and Turing ma-

chines are categorically incomparable paradigms; (v) complexity is measured in categorical completions (Poincarés) rather than FLOPS; (vi) non-halting dynamics with emergent memory and accumulating capability; (vii) categorical topology with 3^k recursive self-similarity; (viii) Saint-Entropy thermodynamics including “miraculous” solutions and processor-oscillator duality; (ix) categorical compiler architecture where solutions are recognized at the ϵ -boundary.

This framework resolves three classical paradoxes: resolution-dependence of temperature, pressure localization at walls, and infinite velocity tails. Experimental validation through hardware timing measurements confirms theoretical predictions with mean deviations below 3%.

Keywords: triple equivalence, categorical entropy, Poincaré recurrence, S-entropy coordinates, ideal gas law, Maxwell-Boltzmann distribution, trajectory completeness, answer equivalence, categorical complexity, processor-oscillator duality, ϵ -boundary solutions

Contents

I Triple Equivalence and Statistical Mechanics	6
1 Introduction: The Structure of Bounded Systems	6
1.1 The Ubiquity of Bounds	6
1.2 Bounded Dynamics Implies Oscillation	6
1.3 Oscillation Defines Categories	6
1.4 Categories Partition the Period	6
1.5 The Triple Equivalence	7
1.6 Quantitative Relationships	7

1.7	From Bounded Systems to Statistical Mechanics and Computing	7	9	Enthalpy: The Equivalence Proof	17
1.8	Scope and Implications	7	9.1	Classical Enthalpy	17
2	Categorical Entropy	8	9.2	Categorical Enthalpy	17
3	Categorical Entropy	8	9.2.1	Categorical Potential	17
3.1	Categories as Distinguishable States	8	9.2.2	Categorical Enthalpy Definition	18
3.2	Derivation of Categorical Entropy	8	9.2.3	Reduction to Classical Enthalpy	18
3.3	Relation to Classical Statistical Mechanics	9	9.3	Oscillatory Enthalpy	18
3.4	Information-Theoretic Foundation	9	9.3.1	Mode Energy	18
3.5	Extensivity and Additivity	9	9.3.2	Mode Potential	18
3.6	Categorical Temperature	9	9.3.3	Oscillatory Enthalpy Definition	19
3.7	Dynamic Categories and Entropy Production	10	9.3.4	Equivalence with Categorical Enthalpy	19
3.8	Resolution Independence	10	9.4	Partition Enthalpy	19
3.9	Summary	10	9.4.1	Transition Work	19
4	Oscillatory Entropy	11	9.4.2	Partition Rate and Occupancy	19
5	Oscillatory Entropy	11	9.4.3	Partition Enthalpy Definition	19
5.1	Oscillators as Fundamental Degrees of Freedom	11	9.4.4	Equivalence with Categorical and Oscillatory Enthalpy	20
5.2	Phase Space Volume of an Oscillator	11	9.5	The Triple Equivalence Theorem	20
5.3	Amplitude as Measure of Accessible States	11	9.6	Extension to Other Thermodynamic Quantities	20
5.4	Derivation of Oscillatory Entropy	12	9.7	Summary	20
5.5	Connection to Energy and Temperature	12	10	Temperature from Three Perspectives	21
5.6	Quantum Oscillatory Entropy	12	11	Temperature: Rate of Categorical Actualization	21
5.7	The Bose-Einstein Distribution	13	11.1	Classical Temperature and Its Limitations	21
5.8	Oscillatory Temperature	13	11.2	Categorical Temperature	21
5.9	Equivalence with Categorical Entropy	13	11.2.1	Resolution Independence	21
5.10	Summary	14	11.2.2	Correct Zero-Point Behavior	22
6	Partition Entropy	14	11.2.3	Physical Meaning of Thermal Equilibrium	22
7	Partition Entropy	14	11.3	Oscillatory Temperature	22
7.1	Partitions as Temporal Segments	14	11.3.1	Connection to Quantum Mechanics	23
7.2	Selectivity and Discrimination	14	11.3.2	Spectral Temperature Distribution	23
7.3	Partition Lag and Transition Time	14	11.4	Partition Temperature	23
7.4	Derivation of Partition Entropy	15	11.4.1	Connection to Relaxation Time	23
7.5	Equivalence with Categorical Entropy	15	11.4.2	Arrhenius Connection	23
7.6	The Aperture Interpretation	15	11.5	Equivalence of Three Definitions	24
7.7	Entropy Production from Partition Dynamics	16	11.6	Recovery of Classical Temperature	24
7.8	Partition Temperature	16	11.7	Temperature Bounds	24
7.9	Connection to Rate Theory and Chemical Kinetics	16	11.7.1	Lower Bound: Absolute Zero	24
7.10	Summary	17	11.7.2	Upper Bound: Planck Temperature	24
8	Enthalpy and Entropy Equivalence	17	11.8	Summary	24
			12	Pressure from Three Perspectives	25

13 Pressure: Categorical Density	25	17.2.4 Physical Interpretation	35
13.1 Classical Pressure and Its Limitations	25	17.3 Oscillatory Derivation	35
13.2 Categorical Pressure	26	17.3.1 Oscillatory Balance	35
13.2.1 Bulk Property, Not Boundary Effect	26	17.3.2 Oscillatory Interpretation . . .	35
13.2.2 Derivation from Thermodynamic Relations	26	17.4 Partition Derivation	36
13.2.3 Scaling of Categories with Volume	26	17.4.1 Partition Balance	36
13.3 Oscillatory Pressure	27	17.4.2 Partition Interpretation	36
13.3.1 Derivation from Virial Theorem	27	17.5 Unified Interpretation	36
13.3.2 Connection to Thermal Energy	27	17.6 Deviations from Ideality	36
13.4 Partition Pressure	27	17.6.1 Categorical Deviations	36
13.4.1 Derivation from Kinetic Theory	27	17.6.2 Oscillatory Deviations	36
13.4.2 Alternative Form	28	17.6.3 Partition Deviations	37
13.5 Equivalence of Three Definitions . .	28	17.7 Generalized Ideal Gas Laws	37
13.6 Pressure as Intensive Variable	28	17.7.1 Relativistic Gas	37
13.7 Pressure Saturation at High Density .	28	17.7.2 Quantum Gas	37
13.8 Summary	28	17.7.3 Photon Gas	37
14 Internal Energy	29	17.8 Summary	37
15 Internal Energy: Active Category Counting	29	18 Maxwell-Boltzmann Distribution	38
15.1 Classical Internal Energy and Equipartition	29	19 The Velocity Distribution: Discrete and Bounded	38
15.2 Categorical Internal Energy	29	19.1 Classical Maxwell-Boltzmann Distribution	38
15.2.1 Why $k_B T$ per Category?	30	19.2 Categorical Distribution	38
15.2.2 Active vs. Total Categories . .	30	19.2.1 Velocity Categories	38
15.2.3 Recovery of Classical Equipartition	30	19.2.2 Categorical Distribution Formula	39
15.3 Oscillatory Internal Energy	30	19.2.3 Physical Interpretation	39
15.3.1 Thermal Occupation	32	19.3 Oscillatory Distribution	39
15.3.2 Low-Temperature Behavior . .	32	19.3.1 Velocity as Oscillation Amplitude	39
15.3.3 Crossover Temperature	32	19.3.2 Oscillatory Distribution Formula	39
15.4 Partition Internal Energy	32	19.3.3 Connection to Velocity Distribution	39
15.4.1 Connection to Categorical and Oscillatory Formulations	32	19.4 Partition Distribution	39
15.5 Equivalence of Three Definitions . .	33	19.4.1 Velocity as Transition Rate . .	39
15.6 Heat Capacity	33	19.4.2 Partition Distribution Formula	40
15.6.1 Categorical Heat Capacity . .	33	19.4.3 Transformation to Velocity . .	40
15.6.2 Oscillatory Heat Capacity (Einstein Model)	33	19.5 Continuum Limit: Recovery of Maxwell-Boltzmann	40
15.6.3 Discrete Steps in Heat Capacity	34	19.6 Relativistic Cutoff	41
15.7 Summary	34	19.6.1 No Velocities Above c	41
16 Derivation of the Ideal Gas Law	34	19.6.2 Relativistic Distribution	41
17 The Ideal Gas Law: Categorical Balance	34	19.6.3 Comparison: Classical vs. Categorical	41
17.1 Classical Statement	34	19.7 Experimental Predictions	41
17.2 Categorical Derivation	34	19.7.1 Velocity Quantisation at Ultra-Cold Temperatures	41
17.2.1 Categorical Densities	34	19.7.2 High-Temperature Relativistic Suppression	41
17.2.2 Categorical Balance Condition	35	19.7.3 Discrete Heat Capacity Contributions	41
17.2.3 From Balance to Ideal Gas Law	35	19.8 Most Probable, Mean, and RMS Velocities	42
		19.8.1 Classical Results	42

19.8.2 Categorical Corrections	42	29.6 Halting Correspondence and Decidability	69
19.9 Equivalence of Three Distributions . .	42		
19.10 Summary	42	30 Identity Unification	70
II Poincaré Computing Architecture	42	31 Identity Unification: Processor, Memory, and Semantics	70
20 The S-Entropy Coordinate Space	42	31.1 Projection Operators	70
21 Bounded Phase Space	42	31.2 Well-Definedness and Independence of Projections	71
21.1 Compactness and Boundedness	43	31.3 Identity Unification Theorem	72
21.2 Measure Structure	43	31.4 Simultaneity of Projections	73
21.3 Hierarchical Discretization	44	31.5 Architectural Implications	74
21.4 Recurrence Preconditions	45	32 Completeness and Answer Equivalence	76
22 Initial States and Computational Problems	45	33 Computational Completeness: Trajectory Equivalence	76
23 Problem Specification as Initial State	45	33.1 The Algorithmic Assumption	76
23.1 Problem Definition	47	33.2 Poincaré Computing: A Non-Algorithmic Framework	77
23.2 Constraint Representation	47	33.3 Answer Equivalence	79
23.3 Problem Encoding	48	33.4 Non-Algorithmic Equivalence	79
23.4 Problem Complexity	50	33.5 Reformulation Abundance	80
24 The Virtual Instrument	51	33.6 The Representation-Solution Gap . . .	81
25 Hardware Grounding: Virtual Instrumentation	51	33.7 Trajectory Completeness	82
25.1 Oscillator Sources	51	33.8 Categorical Distinction and Incomparability	82
25.2 Timing Measurement and Jitter . . .	52	33.9 Implications: Computation Without Algorithms	84
25.3 Coordinate Mapping Functions	53	34 Categorical Complexity Theory	84
25.4 Categorical State Construction	54	35 Complexity Theory: Categorical Rate	84
25.5 Spectrometer-State Identity	55	35.1 Inapplicability of Operation-Based Measures	85
26 Categorical Dynamics	56	35.2 The Unknowable Origin	86
27 Categorical Dynamics	56	35.3 Solution Recognition Through Local Accumulation	87
27.1 Equations of Motion	57	35.4 The Asymptotic Nature of Solutions .	88
27.2 Vector Field Formulation	57	35.5 Categorical Completion Rate	89
27.3 Measure Preservation and Liouville's Theorem	59	35.6 Poincaré Complexity	90
27.4 Harmonic Coincidence Networks . . .	60	35.7 Units of Computation: The Poincaré .	92
27.5 Fixed Points and Periodic Orbits . . .	61	35.8 Comparison with Classical Complexity	92
28 Solution Trajectories and Recurrence	63	35.9 Measurement and Observation	93
29 Solution as Recurrent Trajectory	63	36 Exhaustive Computing and Emergent Memory	94
29.1 Poincaré Recurrence in Categorical Space	64	37 Exhaustive Exploration and Emergent Memory	94
29.2 Solution Definition	64	37.1 Non-Halting Dynamics	95
29.3 Recurrence Time Bounds	66	37.2 Exploration Memory	97
29.4 Constraint Filtering and Admissible Trajectories	67	37.3 Memory by Existence	98
29.5 Solution Uniqueness and Minimal Solutions	68		

37.4 Conditional Complexity and Self-Improvement	98	43.5 Recurrence Time and Equilibrium . . .	125
37.5 Related Problem Benefit	99	43.6 The Second Law as Trajectory Asymmetry	125
37.6 Idle Exploration and Productive Idleness	101	43.7 Connection to Loschmidt Paradox . . .	126
37.7 The Self-Refining System	102	43.8 Phase Space Structure and S-Entropy Coordinates	126
37.8 Research Machine Architecture	103	43.9 Summary: Gas Laws from Trajectories	127
37.9 Comparison with Classical Systems . .	104		
38 Saint-Entropy Thermodynamics	105	44 Categorical Memory Implementation	127
39 Categorical Topology and S-Entropy Foundations	105	45 Categorical Memory: The Computer as Gas Chamber	127
39.1 Categorical Spaces: Axiomatic Foundations	105	45.1 The Virtual Gas Ensemble	127
39.2 Completion Trajectories	106	45.2 Hardware Oscillation Capture	127
39.3 Equivalence Classes and Quotient Structure	108	45.3 Precision-by-Difference Coordinates . .	128
39.4 Categorical Richness and Asymmetry	109	45.4 The 3^k Hierarchical Structure	128
39.5 The S-Distance Metric	110	45.5 Memory as Molecular Trajectory . . .	128
39.6 Recursive Self-Similarity and Scale Ambiguity	111	45.6 Thermodynamic Validation	128
39.7 Categorical Filters and Information Catalysis	112	45.6.1 Entropy Validation	129
39.8 Connection to Poincaré Computing . .	115	45.6.2 Temperature Validation	129
		45.6.3 Pressure Validation	129
40 The Categorical Compiler	116	45.7 The Memory Controller as Maxwell Demon	129
		45.8 Experimental Results	129
		45.9 Summary: Computing as Gas Dynamics	130
41 The Categorical Compiler and Asymptotic Solution Recognition	116	46 Ternary Representation	130
41.1 Bidirectional Translation Architecture	116	47 Ternary Representation: Natural Encoding of Triple Equivalence	130
41.2 Categorical Irreversibility and the One-Step Boundary	117	47.1 The Dimensional Limitation of Binary	130
41.3 Problem Introduction Through Gas Dynamics	119	47.2 Ternary as Natural Three-Dimensional Encoding	131
41.4 The Compiler Runtime Loop	120	47.3 The Triple Equivalence as Ternary Logic	131
41.5 Implications for Computation	122	47.4 Trajectory Encoding	131
		47.5 Continuous Emergence	132
III Validation and Applications	123	47.6 Ternary Operations	132
42 Trajectory Completion in Phase Space	123	47.7 Hardware Instantiation	132
43 Trajectory Completion: Solutions as Recurrent Paths	123	47.8 Comparison: Binary vs. Ternary . . .	132
43.1 The Poincaré Foundation	123	47.9 Implications for Gas Laws	132
43.2 Thermodynamic Quantities as Trajectory Properties	124	47.10 Summary: Ternary as Triple Equivalence	133
43.2.1 Entropy as Trajectory Diversity	124	48 Discussion	134
43.2.2 Temperature as Trajectory Rate	124	48.1 Resolution of Classical Paradoxes . . .	134
43.2.3 Pressure as Trajectory Density	124	48.1.1 Resolution-Dependence of Temperature	134
43.2.4 Internal Energy as Trajectory Activity	124	48.1.2 Localization of Pressure	134
43.3 The Gas Law as a Trajectory Balance	124	48.1.3 Infinite Velocity Tail	134
43.4 Maxwell Distribution from Trajectory Statistics	125	48.2 Unification of Thermodynamics and Computing	134
		48.3 The ϵ -Boundary and Asymptotic Solutions	134

49 Conclusion

Part I

Triple Equivalence and Statistical Mechanics

1 Introduction: The Structure of Bounded Systems

1.1 The Ubiquity of Bounds

Every physical system occupies a finite domain. A gas is confined to a container. An electron is bound to an atom. A planet orbits within a gravitational well. A vibrating string is fixed at its endpoints. A digital oscillator cycles within a bounded frequency range. This boundedness is not incidental but fundamental: unbounded systems would require infinite energy, infinite extent, or both.

We take this observation as our starting point: *physical systems are bounded*. From this single premise, we derive the complete structure of statistical mechanics and establish its equivalence to Poincaré recurrence-based computation.

1.2 Bounded Dynamics Implies Oscillation

Consider a system confined to a finite region of phase space. Let $\mathbf{x}(t)$ denote its trajectory. Since the accessible region is bounded, the trajectory cannot escape to infinity. By the Poincaré recurrence theorem [?], the system must return arbitrarily close to any previous state given sufficient time.

More strongly, for systems with continuous dynamics in bounded domains, the trajectory must eventually reverse direction at the boundaries. This reversal, combined with time-translation invariance, implies periodic or quasi-periodic motion.

Proposition 1.1 (Bounded Oscillation). *Any bounded dynamical system with continuous evolution exhibits oscillatory behavior.*

Proof. Let the system occupy the domain $\mathcal{D} \subset \mathbb{R}^n$ with boundary $\partial\mathcal{D}$. For continuous dynamics, when the trajectory reaches $\partial\mathcal{D}$, it must either stop (equilibrium at the boundary) or reverse (reflection). If it stops, no further dynamics occur. If it reverses,

the trajectory moves back into $\mathcal{D}$. By time-reversal symmetry of conservative dynamics, the return trajectory mirrors the outgoing trajectory. The system thus oscillates between boundary encounters. $\square$

This is not a mathematical abstraction. A pendulum swings between turning points. Gas molecules bounce between container walls. Electrons orbit nuclei. Photons reflect between cavity mirrors. Clock signals oscillate between voltage levels. Oscillation is the universal signature of bounded dynamics.

1.3 Oscillation Defines Categories

An oscillating system traverses distinct states. Consider the pendulum: at each instant, it occupies a specific position x with specific momentum p . The set of (x, p) pairs visited during one period constitutes the oscillation's *categorical structure*.

Definition 1.1 (Category). A *category* is a distinguishable state of an oscillating system.

The categories are not imposed externally; they are defined by the oscillation itself. The pendulum at its leftmost position is categorically distinct from the pendulum at its rightmost position—the oscillation is the traversal between these categories.

Proposition 1.2 (Oscillation-Category Equivalence). *Oscillation and categorical structure are equivalent: oscillation is traversal through categories, and categories are the states that oscillation traverses.*

This equivalence is not tautological. It asserts that there is no oscillation without distinct states to traverse, and no distinct states without dynamics to distinguish them. A static system has no categories; an unbounded system has no oscillation. Categories and oscillation co-emerge from boundedness.

1.4 Categories Partition the Period

The period T of an oscillation is the time required to traverse all categories and return to the initial state. This period naturally decomposes into segments, each corresponding to the time spent in a particular category or transitioning between categories.

Definition 1.2 (Partition). A *partition* is a time segment of the period corresponding to one categorical state or transition.

If the oscillation has M distinguishable categories, the period is partitioned into M segments:

$$T = \sum_{i=1}^M \tau_i \quad (1)$$

where τ_i is the duration of partition i .

Proposition 1.3 (Category-Partition Equivalence). *The partition structure of an oscillation is equivalent to its categorical structure: each partition corresponds to one category, and the union of all partitions equals the period.*

1.5 The Triple Equivalence

We now state the central insight of this work:

Theorem 1.4 (Triple Equivalence). *For any bounded dynamical system, the following three descriptions are mathematically equivalent:*

1. **Oscillatory:** *The system exhibits periodic motion with frequency $\omega = 2\pi/T$.*
2. **Categorical:** *The system traverses M distinguishable states per period.*
3. **Partition:** *The period T is partitioned into M temporal segments.*

These are not three separate phenomena but three perspectives on a single underlying structure.

Proof. From Proposition 1.1, boundedness implies oscillation. From Proposition 1.2, oscillation defines categories. From Proposition 1.3, categories partition the period. The three descriptions are thus logically equivalent—any one implies the other two. Moreover, the quantitative relationships between frequency ω , category count M , and partition durations $\{\tau_i\}$ are deterministic: given any one, the others are uniquely determined. $\square$

1.6 Quantitative Relationships

The triple equivalence establishes precise quantitative relationships:

Rate of category traversal:

$$\frac{dM}{dt} = \frac{M}{T} = \frac{M\omega}{2\pi} \quad (2)$$

Average partition duration:

$$\langle \tau_p \rangle = \frac{T}{M} = \frac{2\pi}{M\omega} \quad (3)$$

Fundamental identity:

$$\boxed{\frac{dM}{dt} = \frac{\omega}{2\pi/M} = \frac{1}{\langle \tau_p \rangle}} \quad (4)$$

Equation (4) expresses the triple equivalence quantitatively: the rate of categorical actualization, the

(scaled) oscillation frequency, and the inverse partition lag are identical. This identity holds for any bounded dynamical system, whether mechanical, electromagnetic, thermal, or computational.

1.7 From Bounded Systems to Statistical Mechanics and Computing

A macroscopic system consists of many oscillators: molecular vibrations, rotations, translations. Each oscillator has its own frequency ω_i , category count M_i , and partition structure. The statistical mechanics of the system emerges from aggregating these oscillatory degrees of freedom.

The key insight is that thermodynamic quantities can be expressed from any of the three perspectives:

- **Categorical:** Count distinguishable states
- **Oscillatory:** Sum over mode amplitudes and frequencies
- **Partition:** Integrate over temporal segments and transition rates

Because these perspectives are equivalent (Theorem 1.4), the three formulations must yield identical predictions. This equivalence provides both a consistency check and new physical insight: phenomena that appear complex in one perspective may be simple in another.

Furthermore, the same triple equivalence structure underlies computation. The S-entropy coordinate space $\mathcal{S} = [0, 1]^3$ provides a bounded phase space in which:

- **Oscillatory:** Hardware oscillators generate timing measurements
- **Categorical:** Each measurement maps to a categorical state
- **Partition:** Trajectories partition the computational problem

The Poincaré recurrence theorem guarantees that measure-preserving dynamics in this bounded space return arbitrarily close to initial states—this recurrence IS the solution to computational problems.

1.8 Scope and Implications

This framework applies to any bounded dynamical system. The triple equivalence structure appears in diverse physical and computational contexts:

- Molecular dynamics (translation, rotation, vibration)




Figure 1: **Triple Equivalence: Oscillatory, Categorical, and Partition Descriptions.** The fundamental theorem establishes that three apparently different descriptions of an ideal gas yield identical entropy: $S = k_B M \ln n$. **Panel A (Hardware Gas in S-Space):** Three-dimensional visualization of virtual gas molecules in categorical S-space (S_k, S_t, S_e), where each point represents a hardware-derived categorical state. The bounded nature of S-coordinates $\in [0, 1]^3$ ensures finite state spaces. **Panel B ($S = k_B M \ln n$):** Linear relationship between entropy and degrees of freedom (DOF), with slope $k_B \ln n$ confirming the fundamental identity. Data points from hardware oscillator sampling show excellent agreement with theory (green circles: S_k , blue squares: S_t , orange triangles: S_{eff}). **Panel C (Partition Tree):** 3D visualization of the categorical partition structure showing hierarchical branching at each level, with n -fold splitting generating n^M total states. **Panel D (Exponential State Growth):** Semi-logarithmic plot demonstrating exponential growth of accessible states $\Omega = n^M$ with DOF for different partition numbers $n = 2, 3, 5, 10$, confirming $S = k_B \ln \Omega = k_B M \ln n$.

- Electromagnetic oscillations (cavity modes, plasma oscillations)
- Quantum systems (energy eigenstates, coherent oscillations)
- Mechanical oscillators (pendula, springs, vibrating strings)
- Digital systems (clock cycles, state transitions, memory addressing)
- Hardware timing (CPU performance counters, oscillator jitter)

The universality of the triple equivalence suggests it reflects a fundamental property of bounded physical systems rather than a domain-specific phenomenon. In the following sections, we derive the complete structure of statistical mechanics from the categorical, oscillatory, and partition perspectives, then establish the Poincaré Computing architecture that unifies thermodynamics and computation through this common foundation.

2 Categorical Entropy

3 Categorical Entropy

3.1 Categories as Distinguishable States

From the triple equivalence (Theorem 1.4), an oscillating system traverses M distinguishable states per period. Each state is a *category*—a region of phase space that the system occupies at some point during its evolution.

Consider a system with M categorical dimensions, each capable of distinguishing n states. The total number of distinguishable configurations is:

$$W = n^M \quad (5)$$

This follows from the independence of categorical dimensions: each of the M dimensions can be in any of its n states, giving $n \times n \times \dots \times n = n^M$ total configurations.

3.2 Derivation of Categorical Entropy

Following Boltzmann’s fundamental postulate [?], entropy is proportional to the logarithm of the number of accessible microstates:

$$S = k_B \ln W = k_B \ln(n^M) = k_B M \ln n \quad (6)$$

This yields the categorical entropy formula:

$$S_{\text{cat}} = k_B M \ln n \quad (7)$$

Physical interpretation:

- M is the number of categorical dimensions (degrees of freedom)
- n is the number of distinguishable states per dimension
- $\ln n$ is the information content per categorical dimension
- k_B converts information units (nats) to thermodynamic units (J/K)

3.3 Relation to Classical Statistical Mechanics

The classical Boltzmann entropy is:

$$S_{\text{Boltzmann}} = k_B \ln \Omega \quad (8)$$

where Ω is the total number of accessible microstates.

When the phase space factorises into M independent dimensions with n states each, we have $\Omega = n^M$, and:

$$S_{\text{Boltzmann}} = k_B \ln(n^M) = k_B M \ln n = S_{\text{cat}} \quad (9)$$

The categorical form is more fundamental because it explicitly separates:

- The *number* of distinctions (M) — how many degrees of freedom there are
- The *depth* of each distinction ($\ln n$) — how finely each degree of freedom is resolved

This separation is not merely notational. It becomes essential when M varies dynamically (as in systems with temperature-dependent degrees of freedom) or when different dimensions have different resolutions. The categorical form makes explicit that entropy has two independent sources: the dimensionality of the phase space and the resolution within each dimension.

3.4 Information-Theoretic Foundation

The categorical entropy has direct information-theoretic meaning. Consider M categorical dimensions, each with n equally probable states. The Shannon entropy [?] of this system is:

$$H = - \sum_{i=1}^{n^M} p_i \ln p_i \quad (10)$$

For uniform probability $p_i = 1/n^M$:

$$H = -n^M \cdot \frac{1}{n^M} \ln \frac{1}{n^M} = \ln(n^M) = M \ln n \quad (11)$$

Thus:

$$S_{\text{cat}} = k_B H \quad (12)$$

The categorical entropy is Boltzmann's constant times the Shannon information content. This establishes a precise correspondence:

Thermodynamic entropy	$\longleftrightarrow$	Information content
k_B (energy/temperature)	$\longleftrightarrow$	1 nat
Temperature	$\longleftrightarrow$	Energy cost per bit

3.5 Extensivity and Additivity

Categorical entropy is extensive. For two independent subsystems with (M_1, n_1) and (M_2, n_2) :

$$S_{\text{total}} = k_B M_1 \ln n_1 + k_B M_2 \ln n_2 \quad (13)$$

If the subsystems have identical categorical structures ($n_1 = n_2 = n$):

$$S_{\text{total}} = k_B (M_1 + M_2) \ln n = k_B M_{\text{total}} \ln n \quad (14)$$

Categorical dimensions are additive. This is the microscopic origin of entropy extensivity: combining systems increases the total number of categorical dimensions while preserving the resolution per dimension.

For N identical subsystems, each with M_0 dimensions:

$$S_{\text{total}} = N k_B M_0 \ln n = k_B M_{\text{total}} \ln n \quad (15)$$

where $M_{\text{total}} = N M_0$. This recovers the familiar extensive scaling $S \propto N$.

3.6 Categorical Temperature

Temperature emerges from the thermodynamic relation:

$$\frac{1}{T} = \left(\frac{\partial S}{\partial U} \right)_{V,N} \quad (16)$$

Substituting $S = k_B M \ln n$:

$$\frac{1}{T} = k_B \ln n \cdot \frac{\partial M}{\partial U} \quad (17)$$

The key insight is that energy determines the number of accessible categorical dimensions. For a quantum oscillator, each quantum $\hbar\omega$ of energy activates one additional categorical dimension:

$$M = \frac{U}{\hbar\omega} \Rightarrow \frac{\partial M}{\partial U} = \frac{1}{\hbar\omega} \quad (18)$$

Thus:

$$\frac{1}{T} = \frac{k_B \ln n}{\hbar\omega} \Rightarrow T = \frac{\hbar\omega}{k_B \ln n} \quad (19)$$

For the natural choice $n = e$ (one nat of information per categorical dimension), we have $\ln n = 1$ and:

$$T = \frac{\hbar\omega}{k_B} \quad (20)$$

This is precisely the quantum mechanical temperature for a single oscillator mode. The categorical perspective reveals that temperature measures the energy cost per categorical dimension.

Alternatively, solving for the number of active dimensions:

$$M_{\text{active}} = \frac{U}{k_B T} \quad (21)$$

At temperature T , the system has $U/(k_B T)$ thermally active categorical dimensions. This provides a direct physical interpretation: temperature sets the scale for how many dimensions are energetically accessible.

3.7 Dynamic Categories and Entropy Production

The number of accessible categorical dimensions can change as the system evolves. The rate of entropy production is:

$$\frac{dS}{dt} = k_B \ln n \cdot \frac{dM}{dt} \quad (22)$$

This has a striking interpretation: *entropy increases at a rate proportional to the categorical actualisation rate*. Rapid exploration of new categorical dimensions corresponds to rapid entropy increase.

At equilibrium, when all accessible dimensions have been uniformly explored, the system reaches a steady state where $\langle dM/dt \rangle = 0$ (averaged over the period) and entropy production ceases. The system has fully actualised its categorical structure.

For a system approaching equilibrium from a constrained initial state:

$$S(t) - S(0) = k_B \ln n \cdot [M(t) - M(0)] \quad (23)$$

The increase in entropy equals the number of newly accessed categorical dimensions multiplied by the information content per dimension. This provides a microscopic picture of the second law: isolated systems spontaneously explore previously inaccessible regions of categorical space.

3.8 Resolution Independence

A crucial feature of categorical entropy is its independence from arbitrary phase space discretization. Classical statistical mechanics requires dividing phase space into cells of volume h^{3N} (where h is often taken as Planck's constant). The choice of h is somewhat arbitrary in classical theory, leading to ambiguities in absolute entropy.

In the categorical formulation, M is not an arbitrary discretization but the number of physically distinguishable states—determined by the oscillation structure itself. The categories are defined by the dynamics, not imposed externally.

For example, a quantum harmonic oscillator has $M = n_{\text{max}}$ categorical dimensions corresponding to energy levels $0, \hbar\omega, 2\hbar\omega, \dots, n_{\text{max}}\hbar\omega$. These are not arbitrary bins but rather physically distinct quantum states. The categorical entropy:

$$S = k_B n_{\text{max}} \ln n \quad (24)$$

depends only on the number of accessible quantum states, with no arbitrary discretization parameter.

3.9 Summary

The categorical perspective yields entropy as:

$$S_{\text{cat}} = k_B M \ln n \quad (25)$$

Key features:

1. **Structural clarity:** Separates the number of categorical dimensions (M) from the information content per dimension ($\ln n$)
2. **Classical correspondence:** Reduces to Boltzmann entropy $S = k_B \ln \Omega$ when $\Omega = n^M$
3. **Information-theoretic foundation:** Equals k_B times Shannon entropy, establishing thermodynamics as physical information theory
4. **Extensivity:** Entropy is additive because categorical dimensions are additive
5. **Temperature:** Emerges as the energy cost per categorical dimension, $T = \hbar\omega/k_B$ for quantum oscillators
6. **Resolution independence:** Categories are defined by the dynamics, not by arbitrary phase space discretization
7. **Dynamic interpretation:** Entropy production measures the rate of categorical actualisation




Figure 2: **Triple Entropy Equivalence:** $S_{\text{osc}} = S_{\text{cat}} = S_{\text{part}} = k_B M \ln n$. Three independent derivations yield identical entropy, establishing the fundamental theorem of categorical thermodynamics. **Panel A (Oscillatory: n^2 modes):** Entropy $S_{\text{osc}}/k_B = M \ln n$ versus degrees of freedom M , computed from oscillator mode counting. Blue shaded region shows linear growth with slope $\ln n$. Each oscillatory mode contributes $k_B \ln n$ to total entropy. **Panel B (Categorical: n^M morphisms):** Entropy $S_{\text{cat}}/k_B = M \ln n^M$ versus categorical levels M , computed from morphism counting in the category of states. Green shaded region confirms identical linear relationship. **Panel C (Partition: $\Omega(n) = 2n^2$ states):** Entropy versus partition depth n on semi-log scale, showing $S = \ln(2n^2)$ (red bars with $\ln(2n^2)$ dashed fit). The factor of 2 accounts for boundary states. **Panel D (Entropy Surface):** 3D surface $S(M, n)$ showing entropy as a function of both degrees of freedom M and partition number n . The surface confirms $S = k_B M \ln n$ across the full parameter space, with color indicating entropy magnitude.

In the following sections, we derive entropy from the oscillatory perspective (Section 5) and the partition perspective (Section 7), then prove that all three formulations are mathematically equivalent (Section 9).

4 Oscillatory Entropy

5 Oscillatory Entropy

5.1 Oscillators as Fundamental Degrees of Freedom

From the triple equivalence (Theorem 1.4), bounded dynamics manifests as oscillation. A macroscopic system decomposes into a collection of oscillators—vibrational modes, rotational modes, translational modes—each characterised by frequency ω_i and amplitude A_i .

The oscillatory perspective derives entropy by summing over these modes, weighted by their phase space volumes.

5.2 Phase Space Volume of an Oscillator

Consider a harmonic oscillator with mass m , frequency ω , and amplitude A . Its trajectory traces an

ellipse in phase space (x, p) :

$$\frac{x^2}{A^2} + \frac{p^2}{(m\omega A)^2} = 1 \quad (26)$$

The area enclosed by this ellipse is:

$$\Gamma = \pi \cdot A \cdot (m\omega A) = \pi m\omega A^2 \quad (27)$$

For an oscillator with energy $E = \frac{1}{2}m\omega^2 A^2$, we have $A^2 = 2E/(m\omega^2)$, which gives:

$$\Gamma = \pi m\omega \cdot \frac{2E}{m\omega^2} = \frac{2\pi E}{\omega} \quad (28)$$

In quantum mechanics, phase space is quantised in units of $h = 2\pi\hbar$. The number of quantum states enclosed is:

$$n = \frac{\Gamma}{h} = \frac{2\pi E}{\omega \cdot 2\pi\hbar} = \frac{E}{\hbar\omega} \quad (29)$$

For a quantum harmonic oscillator with energy $E = (n + 1/2)\hbar\omega$, this gives n as the occupation number, confirming the correspondence between classical phase space volume and quantum state counting.

5.3 Amplitude as Measure of Accessible States

For a classical oscillator, the amplitude A determines the extent of phase space exploration. A larger amplitude means more accessible states. Define a reference amplitude A_0 corresponding to the ground state

(minimum accessible phase space):

$$\Gamma_0 = \pi m \omega A_0^2 \quad (30)$$

The ratio of accessible phase space volumes is:

$$\frac{\Gamma}{\Gamma_0} = \frac{A^2}{A_0^2} \quad (31)$$

This ratio measures how many times more phase space is accessible at amplitude A compared to the ground state amplitude A_0 . In quantum terms, $\Gamma/\Gamma_0 = n/n_0$ is the ratio of occupation numbers.

5.4 Derivation of Oscillatory Entropy

For a system of N independent oscillators with amplitudes $\{A_i\}$ and frequencies $\{\omega_i\}$, the total accessible phase space volume is:

$$\Gamma_{\text{total}} = \prod_{i=1}^N \Gamma_i = \prod_{i=1}^N \pi m_i \omega_i A_i^2 \quad (32)$$

Following Boltzmann's principle, entropy is the logarithm of the accessible phase space volume (in units of h^N):

$$S = k_B \ln \left(\frac{\Gamma_{\text{total}}}{\Gamma_0^N} \right) = k_B \sum_{i=1}^N \ln \left(\frac{\Gamma_i}{\Gamma_0} \right) = k_B \sum_{i=1}^N \ln \left(\frac{A_i^2}{A_0^2} \right) \quad (33)$$

This yields the oscillatory entropy formula:

$$S_{\text{osc}} = k_B \sum_{i=1}^N \ln \left(\frac{A_i}{A_0} \right)^2 \quad (34)$$

Equivalently, in terms of phase space volumes:

$$S_{\text{osc}} = k_B \sum_{i=1}^N \ln \left(\frac{\Gamma_i}{\Gamma_0} \right) \quad (35)$$

Or in terms of energies (using $\Gamma \propto E/\omega$):

$$S_{\text{osc}} = k_B \sum_{i=1}^N \ln \left(\frac{E_i/\omega_i}{E_0/\omega_0} \right) \quad (36)$$

Physical interpretation:

- Each oscillator i contributes $\ln(\Gamma_i/\Gamma_0)$ to the total entropy
- Larger amplitudes (more phase space exploration) contribute more entropy
- The sum over modes reflects the independence of oscillatory degrees of freedom
- The reference amplitude A_0 sets the zero point of entropy (analogous to ground state)

5.5 Connection to Energy and Temperature

For a harmonic oscillator, amplitude and energy are related by:

$$E = \frac{1}{2} m \omega^2 A^2 \Rightarrow A^2 = \frac{2E}{m \omega^2} \quad (37)$$

Thus:

$$\ln \left(\frac{A_i}{A_0} \right)^2 = \ln \left(\frac{E_i}{E_0} \right) \quad (38)$$

The oscillatory entropy becomes expressed as follows:

$$S_{\text{osc}} = k_B \sum_{i=1}^N \ln \left(\frac{E_i}{E_0} \right) \quad (39)$$

For a system in thermal equilibrium at temperature T , the classical equipartition theorem gives $\langle E_i \rangle = k_B T$ per quadratic degree of freedom. For N oscillators (each with kinetic and potential energy):

$$\langle E_i \rangle = k_B T \quad (40)$$

Substituting into the entropy formula:

$$S_{\text{osc}} = k_B N \ln \left(\frac{k_B T}{E_0} \right) \quad (41)$$

This recovers the classical ideal gas entropy structure (the additive constant depends on E_0 and other system-specific parameters).

5.6 Quantum Oscillatory Entropy

For quantum oscillators, phase space is discretised in units of h . An oscillator with occupation number n_i has accessible phase space $\Gamma_i = (n_i + 1)h$ (accounting for zero-point energy). The number of accessible states is:

$$W_i = n_i + 1 \quad (42)$$

The quantum oscillatory entropy is:

$$S_{\text{osc,quantum}} = k_B \sum_{i=1}^N \ln(n_i + 1) \quad (43)$$

Limiting behavior:

- **High temperature:** $n_i = k_B T / (\hbar \omega_i) \gg 1$, so $\ln(n_i + 1) \approx \ln n_i$, recovering the classical limit
- **Low temperature:** $n_i \rightarrow 0$, so $S \rightarrow 0$, satisfying the third law of thermodynamics

This demonstrates that the oscillatory formulation naturally interpolates between quantum and classical regimes.

5.7 The Bose-Einstein Distribution

For a system of quantum oscillators in thermal equilibrium, maximising entropy subject to a fixed total energy yields the Bose-Einstein distribution.

Setup: Maximise

$$S = k_B \sum_{i=1}^N \ln(n_i + 1) \quad (44)$$

subject to the constraint

$$U = \sum_{i=1}^N \hbar \omega_i n_i = \text{constant} \quad (45)$$

Using the method of Lagrange multipliers, we extremize:

$$\mathcal{L} = k_B \sum_i \ln(n_i + 1) - \beta \sum_i \hbar \omega_i n_i \quad (46)$$

Taking the derivative with respect to n_i :

$$\frac{\partial \mathcal{L}}{\partial n_i} = \frac{k_B}{n_i + 1} - \beta \hbar \omega_i = 0 \quad (47)$$

Solving for n_i :

$$n_i + 1 = \frac{k_B}{\beta \hbar \omega_i} \Rightarrow n_i = \frac{k_B}{\beta \hbar \omega_i} - 1 \quad (48)$$

Identifying $\beta = 1/(k_B T)$:

$$\langle n_i \rangle = \frac{1}{e^{\hbar \omega_i / (k_B T)} - 1} \quad (49)$$

This is precisely the Bose-Einstein distribution. The oscillatory entropy formulation naturally yields the correct quantum statistical distribution without additional postulates.

5.8 Oscillatory Temperature

Temperature emerges from the thermodynamic relation:

$$\frac{1}{T} = \left(\frac{\partial S}{\partial U} \right)_{V,N} \quad (50)$$

For the oscillatory entropy $S_{\text{osc}} = k_B \sum_i \ln(A_i/A_0)^2 = k_B \sum_i \ln(E_i/E_0)$:

$$\frac{\partial S}{\partial U} = k_B \sum_i \frac{\partial}{\partial U} \ln E_i = k_B \sum_i \frac{1}{E_i} \frac{\partial E_i}{\partial U} \quad (51)$$

For N independent oscillators sharing total energy U , if energy is distributed uniformly, $E_i = U/N$:

$$\frac{\partial E_i}{\partial U} = \frac{1}{N} \quad (52)$$

Thus:

$$\frac{1}{T} = k_B \sum_i \frac{1}{E_i} \cdot \frac{1}{N} = k_B \sum_i \frac{N}{U} \cdot \frac{1}{N} = \frac{k_B N}{U} \quad (53)$$

Solving for U :

$$\boxed{U = N k_B T} \quad (54)$$

This is the equipartition result for N oscillators with one degree of freedom each. For oscillators with f quadratic degrees of freedom (e.g., $f = 2$ for kinetic + potential energy):

$$U = \frac{f N k_B T}{2} \quad (55)$$

The oscillatory perspective thus recovers classical equipartition as a consequence of the entropy-temperature relationship.

5.9 Equivalence with Categorical Entropy

The oscillatory entropy relates to the categorical entropy through the correspondence between phase space volumes and categorical dimensions.

Key identifications:

1. Each oscillator i corresponds to one categorical dimension: $M = N$
2. The phase space ratio $\Gamma_i/\Gamma_0 = A_i^2/A_0^2$ equals the number of accessible states in that dimension: n_i
3. Thus $\ln(\Gamma_i/\Gamma_0) = \ln n_i$

The oscillatory entropy becomes expressed as follows:

$$S_{\text{osc}} = k_B \sum_{i=1}^N \ln n_i \quad (56)$$

For a system with uniform state distribution ($n_i = n$ for all i):

$$S_{\text{osc}} = k_B N \ln n = k_B M \ln n = S_{\text{cat}} \quad (57)$$

For non-uniform distributions:

$$S_{\text{osc}} = k_B \sum_{i=1}^M \ln n_i = k_B M \langle \ln n \rangle \quad (58)$$

where $\langle \ln n \rangle = (1/M) \sum_i \ln n_i$ is the geometric mean of the state counts.

The oscillatory and categorical entropies are mathematically equivalent. The oscillatory form explicitly demonstrates the contribution of each mode, while the categorical form emphasises the total dimensionality. They are two representations of the same underlying structure.

5.10 Summary

The oscillatory perspective yields entropy as:

$$S_{\text{osc}} = k_B \sum_{i=1}^N \ln \left(\frac{A_i}{A_0} \right)^2 = k_B \sum_{i=1}^N \ln \left(\frac{\Gamma_i}{\Gamma_0} \right) \quad (59)$$

Key features:

1. **Phase space foundation:** Derives from classical phase space volumes of oscillators
2. **Quantum correspondence:** Naturally incorporates quantum mechanics through discretization $\Gamma = nh$
3. **Statistical distributions:** Yields the Bose-Einstein distribution through entropy maximization.
4. **Equipartition:** Recovers classical equipartition $U = Nk_B T$ through the definition of temperature.
5. **Third law compliance:** The quantum version satisfies $S \rightarrow 0$ as $T \rightarrow 0$
6. **Equivalence:** Mathematically identical to categorical entropy: $S_{\text{osc}} = S_{\text{cat}}$

The partition perspective (Section 7) will complete the triple equivalence by deriving entropy from the temporal segmentation of the oscillation period.

6 Partition Entropy

7 Partition Entropy

7.1 Partitions as Temporal Segments

From the triple equivalence (Theorem 1.4), the period of an oscillation is divided into partitions—temporal segments corresponding to categorical states. Each partition has a characteristic duration τ_i and a *selectivity* s_i that measures how precisely it discriminates among states.

The partition perspective derives entropy by summing over these temporal segments, weighted by their selectivities.

7.2 Selectivity and Discrimination

The selectivity of a partition quantifies its discriminatory power—how finely it distinguishes among possible configurations.

Definition 7.1. The *selectivity* of partition a is the fraction of incoming configurations that it accepts:

$$s_a = \frac{\text{number of accepted configurations}}{\text{total number of configurations}} = \frac{1}{n_a} \quad (60)$$

where n_a is the number of distinguishable states within partition a .

Physical interpretation:

- **High selectivity** ($s_a \rightarrow 1$): The partition accepts almost all configurations; low discrimination; few distinguishable states ($n_a \rightarrow 1$). Example: a coarse philtre that passes most molecules.
- **Low selectivity** ($s_a \rightarrow 0$): The partition accepts very few configurations; high discrimination; many distinguishable states ($n_a \rightarrow \infty$). Example: a fine philtre that passes only specific molecular velocities.

A partition's selectivity is the inverse of its categorical depth: $s_a = 1/n_a$. High categorical depth (many distinguishable states) corresponds to low selectivity (high discrimination).

7.3 Partition Lag and Transition Time

The partition lag quantifies the temporal cost of categorical transitions.

Definition 7.2. The *partition lag* τ_p is the average time required to complete one partition—to transition from one categorical state to the next.

From the fundamental identity (Equation ??):

$$\tau_p = \frac{T}{M} = \frac{2\pi}{M\omega} \quad (61)$$

where T is the period, M is the number of partitions, and ω is the angular frequency.

Physical interpretation:

- **Shorter partition lag** ($\tau_p \rightarrow 0$): Rapid categorical transitions; high frequency; high temperature
- **Longer partition lag** ($\tau_p \rightarrow \infty$): Slow categorical transitions; low frequency; low temperature

The partition lag is inversely related to temperature:

$$T \propto \frac{1}{\langle \tau_p \rangle} \quad (62)$$

This establishes a direct connexion between temporal dynamics (how fast the system transitions) and thermodynamic temperature (how energetic the system is).

7.4 Derivation of Partition Entropy

Consider a system with M partitions, each with selectivity s_a . A configuration must pass through all M partitions to complete one full cycle. The probability that a randomly chosen configuration successfully passes through all partitions is:

$$P_{\text{total}} = \prod_{a=1}^M s_a \quad (63)$$

The information content (surprisal) of this event is:

$$I = -\ln P_{\text{total}} = -\ln \left(\prod_{a=1}^M s_a \right) = -\sum_{a=1}^M \ln s_a = \sum_{a=1}^M \ln \left(\frac{1}{s_a} \right) \quad (64)$$

Following Shannon's information theory [?], entropy is the expected information content. For a thermodynamic system, we multiply by Boltzmann's constant to convert from information units (nats) to thermodynamic units (J/K):

$$S_{\text{part}} = k_B \sum_{a=1}^M \ln \left(\frac{1}{s_a} \right) \quad (65)$$

This is the partition entropy.

Alternative form: Since $s_a = 1/n_a$:

$$S_{\text{part}} = k_B \sum_{a=1}^M \ln n_a \quad (66)$$

Physical interpretation:

- Each partition a contributes $\ln(1/s_a) = \ln n_a$ to the total entropy
- Partitions with lower selectivity (higher discrimination) contribute more entropy
- The sum over partitions reflects the cumulative discriminatory power of the full temporal structure

7.5 Equivalence with Categorical Entropy

The partition entropy is mathematically identical to the categorical entropy.

Since $s_a = 1/n_a$, we have:

$$\ln \left(\frac{1}{s_a} \right) = \ln n_a \quad (67)$$

The partition entropy becomes:

$$S_{\text{part}} = k_B \sum_{a=1}^M \ln n_a \quad (68)$$

For uniform selectivity across all partitions ($n_a = n$ for all a):

$$S_{\text{part}} = k_B M \ln n = S_{\text{cat}} \quad (69)$$

For non-uniform selectivity:

$$S_{\text{part}} = k_B \sum_{a=1}^M \ln n_a = k_B M \langle \ln n \rangle \quad (70)$$

where $\langle \ln n \rangle = (1/M) \sum_a \ln n_a$ is the geometric mean of the state counts.

The partition and categorical entropies are mathematically equivalent. The partition form emphasizes temporal structure and selectivity, while the categorical form emphasizes state counting. They are two perspectives on the same underlying quantity.

7.6 The Aperture Interpretation

A useful physical picture emerges by thinking of partitions as *apertures*—selective passages through which configurations must pass.

Definition 7.3. An *aperture* is a partition with selectivity $s_a < 1$ that acts as a selective filter.

Each aperture accepts a fraction s_a of incoming configurations and rejects the rest. The total “filtering power” of the system—the fraction of all possible configurations that survive passage through all apertures—is:

$$P_{\text{survive}} = \prod_{a=1}^M s_a = \prod_{a=1}^M \frac{1}{n_a} = \frac{1}{\prod_a n_a} \quad (71)$$

For uniform apertures ($n_a = n$):

$$P_{\text{survive}} = \frac{1}{n^M} \quad (72)$$

The inverse of this probability is the total number of distinguishable configurations:

$$W = \frac{1}{P_{\text{survive}}} = n^M \quad (73)$$

Taking logarithms:

$$\ln W = M \ln n = \frac{S}{k_B} \quad (74)$$

Interpretation: Entropy measures the total filtering power of all apertures—how many configurations could be distinguished by the full partition

structure. A system with high entropy has many apertures (large M) or highly selective apertures (large n), allowing it to distinguish among many possible configurations.

This aperture picture connects naturally to experimental measurement: any measurement device is effectively an aperture with finite selectivity, and the entropy quantifies the total information extractable through all such measurements.

7.7 Entropy Production from Partition Dynamics

When a system undergoes transitions, each partition completion contributes to entropy production. The rate of entropy production is:

$$\frac{dS}{dt} = k_B \sum_{a=1}^M \frac{1}{\tau_{p,a}} \ln \left(\frac{1}{s_a} \right) \quad (75)$$

where $\tau_{p,a}$ is the lag time for partition a .

For uniform partitions ($\tau_{p,a} = \tau_p$ and $s_a = s$ for all a):

$$\frac{dS}{dt} = \frac{k_B M}{\tau_p} \ln \left(\frac{1}{s} \right) = k_B \frac{M}{\tau_p} \ln n \quad (76)$$

Using $M/\tau_p = dM/dt$ (the rate of partition completion):

$$\frac{dS}{dt} = k_B \ln n \cdot \frac{dM}{dt} \quad (77)$$

This exactly matches the categorical entropy production rate (Section 3), confirming the equivalence of the two perspectives.

Physical interpretation: Entropy increases at a rate proportional to how fast the system completes partitions (traverses categorical states). Rapid partition completion means rapid entropy production.

7.8 Partition Temperature

Temperature emerges from the thermodynamic relation:

$$\frac{1}{T} = \left(\frac{\partial S}{\partial U} \right)_{V,N} \quad (78)$$

Substituting $S = k_B \sum_a \ln(1/s_a) = k_B \sum_a \ln n_a$:

$$\frac{1}{T} = k_B \sum_{a=1}^M \frac{\partial \ln n_a}{\partial U} \quad (79)$$

The key physical insight is that energy determines selectivity: higher energy allows access to more states, thus increasing n_a and decreasing selectivity s_a .

For a system where each quantum $\hbar\omega$ of energy opens one additional state per partition:

$$n_a = \frac{U_a}{\hbar\omega_a} \quad (80)$$

Thus:

$$\frac{\partial \ln n_a}{\partial U_a} = \frac{1}{n_a} \cdot \frac{\partial n_a}{\partial U_a} = \frac{1}{n_a} \cdot \frac{1}{\hbar\omega_a} = \frac{\hbar\omega_a}{U_a \hbar\omega_a} = \frac{1}{U_a} \quad (81)$$

For equipartition ($U_a = U/M$ for each partition):

$$\frac{1}{T} = k_B \sum_{a=1}^M \frac{1}{U_a} = k_B \sum_{a=1}^M \frac{M}{U} = \frac{k_B M}{U} \quad (82)$$

Solving for U :

$$\boxed{U = M k_B T} \quad (83)$$

This is the equipartition result for M classical degrees of freedom, recovered from the partition perspective.

Alternative interpretation: The partition lag $\tau_p = T/M$ is related to temperature by:

$$\tau_p = \frac{T}{M} = \frac{U}{M^2 k_B T} = \frac{U/M}{M k_B T} \quad (84)$$

For $U = M k_B T$:

$$\tau_p = \frac{k_B T}{M k_B T} = \frac{1}{M \omega / 2\pi} \quad (85)$$

Shorter partition lag corresponds to higher temperature, confirming the inverse relationship.

7.9 Connection to Rate Theory and Chemical Kinetics

The partition perspective connects naturally to chemical kinetics and transition state theory [?].

In a chemical reaction:

- The **partition** is the transition state (activated complex)
- The **selectivity** s is the transmission coefficient (reaction probability)
- The **partition lag** τ_p is the inverse attempt frequency

The reaction rate constant is:

$$k = \frac{s}{\tau_p} \quad (86)$$

The entropy of activation is:

$$\Delta S^\ddagger = k_B \ln \left(\frac{1}{s} \right) = k_B \ln n \quad (87)$$

This connects equilibrium thermodynamics (entropy) to non-equilibrium kinetics (rate constants) through the partition structure. The Eyring equation:

$$k = \frac{k_B T}{h} e^{\Delta S^\ddagger/k_B} e^{-\Delta H^\ddagger/k_B T} \quad (88)$$

can be reinterpreted as:

$$k = \frac{1}{\tau_p} \cdot s \cdot e^{-\Delta H^\ddagger/k_B T} \quad (89)$$

where $\tau_p = h/(k_B T)$ is the partition lag at the transition state.

Broader implications: Any rate process—diffusion, relaxation, chemical reaction—can be viewed as partition traversal with characteristic selectivity and lag time. The partition entropy framework unifies equilibrium and non-equilibrium thermodynamics.

7.10 Summary

The partition perspective yields entropy as:

$$S_{\text{part}} = k_B \sum_{a=1}^M \ln \left(\frac{1}{s_a} \right) = k_B \sum_{a=1}^M \ln n_a \quad (90)$$

Key features:

1. **Temporal foundation:** Derives from the selectivity (discrimination power) of temporal partitions
2. **Selectivity-category duality:** Selectivity $s_a = 1/n_a$ links directly to categorical depth
3. **Partition lag:** Determines the transition rate and connects inversely to temperature
4. **Aperture interpretation:** Entropy measures the total filtering power of all selective passages
5. **Rate theory connection:** Naturally connects to chemical kinetics and transition state theory
6. **Equivalence:** Mathematically identical to categorical and oscillatory entropies

Triple equivalence established:

$$S_{\text{cat}} = S_{\text{osc}} = S_{\text{part}} = k_B M \ln n \quad (91)$$

With all three entropy forms derived and shown equivalent, we now demonstrate that this equivalence extends to enthalpy and all other thermodynamic quantities (Section 9).

8 Enthalpy and Entropy Equivalence

9 Enthalpy: The Equivalence Proof

Having derived entropy from three perspectives—categorical, oscillatory, and partition—we now demonstrate that the triple equivalence extends to enthalpy. We derive the same enthalpy formula from each perspective, proving that the three frameworks yield identical thermodynamic predictions.

9.1 Classical Enthalpy

In classical thermodynamics, enthalpy is defined as:

$$H = U + PV \quad (92)$$

where U is internal energy, P is pressure, and V is volume. The PV term represents the work done against external pressure to establish the system's volume.

Enthalpy is the natural thermodynamic potential for processes at constant pressure. Its differential form:

$$dH = TdS + VdP + \mu dN \quad (93)$$

It makes it particularly useful for chemical reactions and phase transitions.

We will derive enthalpy from each of the three perspectives and prove they all reduce to this classical form.

9.2 Categorical Enthalpy

9.2.1 Categorical Potential

In the categorical framework, each category (or aperture) has an associated potential that measures the “cost” of maintaining that categorical distinction.

Definition 9.1. The *categorical potential* of aperture a is:

$$\Phi_a = -k_B T \ln s_a = k_B T \ln n_a \quad (94)$$

where $s_a = 1/n_a$ is the selectivity and n_a is the number of accessible states.

Physical interpretation:

- Φ_a measures the free energy cost of maintaining aperture a in its current state
- High categorical depth ($n_a \gg 1$) implies high potential: many states must be kept accessible

- Low categorical depth ($n_a \rightarrow 1$) implies low potential: few states need maintenance
- Φ_a is the work required to keep aperture a “open” against the system’s tendency to collapse to fewer states

The categorical potential is thermodynamically conjugate to the occupancy: Φ_a is the chemical potential for particles in category a .

9.2.2 Categorical Enthalpy Definition

The categorical enthalpy is internal energy plus the sum of aperture potentials weighted by occupancy:

$$H_{\text{cat}} = U + \sum_{a=1}^M N_a \Phi_a = U + k_B T \sum_{a=1}^M N_a \ln n_a \quad (95)$$

where N_a is the number of particles (or excitations) occupying aperture a .

Physical interpretation:

- U is the kinetic energy of particles
- $\sum_a N_a \Phi_a$ is the potential energy associated with maintaining the categorical structure
- Enthalpy accounts for both the energy of motion and the energy of configuration

9.2.3 Reduction to Classical Enthalpy

For an ideal gas with volume V and N particles, we establish the connection to PV .

Spatial categories: The number of spatial categories scales as:

$$M \propto \frac{V}{V_0} \quad (96)$$

where V_0 is the elementary volume (typically on the order of molecular size).

Categorical depth: The number of accessible states per spatial category is:

$$n \approx \frac{V}{NV_0} \quad (97)$$

This is the volume per particle in units of V_0 .

Total occupancy: The conservation of particles gives:

$$\sum_{a=1}^M N_a = N \quad (98)$$

For uniform distribution ($N_a = N/M$):

$$\sum_a N_a \Phi_a = N \cdot k_B T \ln \left(\frac{V}{NV_0} \right) \quad (99)$$

Taking the volume derivative at a constant temperature:

$$\left(\frac{\partial}{\partial V} \right)_{T,N} \sum_a N_a \Phi_a = N k_B T \cdot \frac{1}{V} = \frac{N k_B T}{V} \quad (100)$$

By the ideal gas law $PV = N k_B T$, we have:

$$\left(\frac{\partial}{\partial V} \right)_{T,N} \sum_a N_a \Phi_a = P \quad (101)$$

This shows that the aperture potential term is thermodynamically conjugate to pressure. Integrating:

$$\sum_a N_a \Phi_a = PV + \text{const} \quad (102)$$

Choosing the constant such that $\Phi_a \rightarrow 0$ as $V \rightarrow V_0$ (minimal volume):

$$\sum_a N_a \Phi_a = PV \quad (103)$$

Therefore:

$$H_{\text{cat}} = U + \sum_a N_a \Phi_a = U + PV = H_{\text{classical}} \quad (104)$$

9.3 Oscillatory Enthalpy

9.3.1 Mode Energy

In the oscillatory framework, the system decomposes into modes with frequencies $\{\omega_i\}$ and occupation numbers $\{n_i\}$. Each mode carries energy:

$$E_i = \hbar \omega_i \left(n_i + \frac{1}{2} \right) \quad (105)$$

The internal energy is:

$$U = \sum_{i=1}^N E_i = \sum_{i=1}^N \hbar \omega_i \left(n_i + \frac{1}{2} \right) \quad (106)$$

9.3.2 Mode Potential

Define the mode potential as the work required to maintain oscillation amplitude against dissipative forces and thermal fluctuations.

Definition 9.2. The *mode potential* is:

$$\Psi_i = \hbar \omega_i \quad (107)$$

This is the energy quantum of mode i —the cost of adding one excitation.

Physical interpretation:

- Ψ_i is the minimum energy required to activate mode i
- Higher frequency modes have higher potentials
- Ψ_i sets the energy scale for thermal activation: modes with $\hbar\omega_i \gg k_B T$ are thermally inaccessible

9.3.3 Oscillatory Enthalpy Definition

The oscillatory enthalpy is internal energy plus the sum of mode potentials weighted by occupation:

$$H_{\text{osc}} = U + \sum_{i=1}^N \Psi_i n_i = U + \sum_{i=1}^N \hbar\omega_i n_i \quad (108)$$

Note that this differs from internal energy: U includes zero-point energy ($\frac{1}{2}\hbar\omega_i$ per mode), while the enthalpy correction term includes only the excitation energy ($\hbar\omega_i n_i$).

Alternative form using amplitude: Since $n_i \propto A_i^2/A_0^2$ (occupation is proportional to amplitude squared):

$$H_{\text{osc}} = U + \sum_i \hbar\omega_i \left\langle \frac{A_i^2}{A_0^2} \right\rangle \quad (109)$$

9.3.4 Equivalence with Categorical Enthalpy

For a system in thermal equilibrium at temperature T , the classical equipartition theorem states:

$$\langle E_i \rangle = k_B T \Rightarrow n_i = \frac{k_B T}{\hbar\omega_i} \quad (110)$$

The mode potential term becomes:

$$\sum_{i=1}^N \hbar\omega_i n_i = \sum_{i=1}^N \hbar\omega_i \cdot \frac{k_B T}{\hbar\omega_i} = N k_B T \quad (111)$$

From categorical enthalpy with uniform apertures ($n_a = n$ for all a) and one particle per aperture ($N_a = 1$):

$$\sum_{a=1}^M N_a \Phi_a = M \cdot k_B T \ln n \quad (112)$$

For the natural choice $\ln n = 1$ (one nat of information per category) and $M = N$ (one mode per categorical dimension):

$$\sum_{a=1}^M N_a \Phi_a = N k_B T = \sum_{i=1}^N \hbar\omega_i n_i \quad (113)$$

Therefore: $H_{\text{osc}} = H_{\text{cat}}$.

Both reduce to $H = U + N k_B T$, which, for an ideal gas, equals $U + PV$.

9.4 Partition Enthalpy

9.4.1 Transition Work

In the partition framework, each partition transition requires work against the selectivity barrier. This work is the free energy cost of passing through the aperture.

Definition 9.3. The *transition work* for partition a is:

$$W_a = -k_B T \ln s_a = k_B T \ln n_a \quad (114)$$

This is identical to the categorical potential Φ_a , reflecting the equivalence between partitions and categories.

Physical interpretation:

- W_a is the activation energy for transition through partition a
- Low selectivity ($s_a \rightarrow 0$) means a high barrier ($W_a \rightarrow \infty$)
- High selectivity ($s_a \rightarrow 1$) means a low barrier ($W_a \rightarrow 0$)

9.4.2 Partition Rate and Occupancy

The rate at which transitions occur through partition a is:

$$\dot{N}_a = \frac{N_a}{\tau_{p,a}} \quad (115)$$

where N_a is the number of particles in partition a and $\tau_{p,a}$ is the partition lag (transition time).

The steady-state occupancy is determined by the balance between influx and efflux:

$$N_a = \dot{N}_a \cdot \tau_{p,a} \quad (116)$$

9.4.3 Partition Enthalpy Definition

The partition enthalpy is internal energy plus the total transition work, weighted by the relative partition lags:

$$H_{\text{part}} = U + \sum_{a=1}^M W_a \cdot \frac{N_a \tau_{p,a}}{\langle \tau_p \rangle} = U + k_B T \sum_{a=1}^M N_a \ln n_a \quad (117)$$

where $\langle \tau_p \rangle = (1/M) \sum_a \tau_{p,a}$ is the average partition lag.

For uniform partition lags ($\tau_{p,a} = \langle \tau_p \rangle$ for all a):

$$H_{\text{part}} = U + k_B T \sum_{a=1}^M N_a \ln n_a \quad (118)$$

This is identical to the categorical enthalpy (Equation 95).

9.4.4 Equivalence with Categorical and Oscillatory Enthalpy

Comparing the three formulations:

$$H_{\text{cat}} = U + k_B T \sum_{a=1}^M N_a \ln n_a \quad (119)$$

$$H_{\text{osc}} = U + \sum_{i=1}^N \hbar \omega_i n_i \quad (120)$$

$$H_{\text{part}} = U + k_B T \sum_{a=1}^M N_a \ln n_a \quad (121)$$

Categorical-Partition equivalence: Immediate from identical functional forms.

Oscillatory equivalence: For thermal equilibrium with $\hbar \omega_i n_i = k_B T$ and uniform occupancy:

$$\sum_i \hbar \omega_i n_i = N k_B T = k_B T \sum_a N_a \ln n \quad (122)$$

(for $\ln n = 1$ and $\sum_a N_a = N$).

All three reduce to:

$$H = U + N k_B T \quad (123)$$

For an ideal gas, using $PV = N k_B T$:

$$H = U + PV = H_{\text{classical}} \quad (124)$$

9.5 The Triple Equivalence Theorem

We have now established the central result:

Theorem 9.1 (Enthalpy Equivalence). *The categorical, oscillatory, and partition formulations of enthalpy are mathematically equivalent:*

$$H_{\text{cat}} = H_{\text{osc}} = H_{\text{part}} \quad (125)$$

and all reduce to the classical enthalpy $H = U + PV$ in the appropriate limits.

Proof. We have shown:

1. Categorical enthalpy: $H_{\text{cat}} = U + k_B T \sum_a N_a \ln n_a$ reduces to $U + PV$ for ideal gases (Section 5.2.3)
2. Oscillatory enthalpy: $H_{\text{osc}} = U + \sum_i \hbar \omega_i n_i$ equals $U + N k_B T = U + PV$ at thermal equilibrium (Section 5.3.4)
3. Partition enthalpy: $H_{\text{part}} = U + k_B T \sum_a N_a \ln n_a$ is identical to H_{cat} (Section 5.4.4)

Therefore $H_{\text{cat}} = H_{\text{osc}} = H_{\text{part}} = U + PV$. $\square$

9.6 Extension to Other Thermodynamic Quantities

The equivalence proven for entropy (Sections 3–7) and enthalpy (this section) extends to all thermodynamic quantities. Since temperature, pressure, chemical potential, free energy, and all other state functions can be derived from entropy and enthalpy through thermodynamic relations, the triple equivalence propagates throughout the entire framework.

Temperature: From the fundamental identity (Equation ??):

$$T_{\text{cat}} = \frac{\hbar}{k_B} \frac{dM}{dt} \quad (\text{categorical actualization rate}) \quad (126)$$

$$T_{\text{osc}} = \frac{\hbar}{k_B} \langle \omega \rangle \quad (\text{average oscillation frequency}) \quad (127)$$

$$T_{\text{part}} = \frac{\hbar}{k_B} \frac{1}{\langle \tau_p \rangle} \quad (\text{inverse partition lag}) \quad (128)$$

All three are equal: $T_{\text{cat}} = T_{\text{osc}} = T_{\text{part}}$.

Pressure: From the volume derivatives:

$$P_{\text{cat}} = k_B T \left(\frac{\partial M}{\partial V} \right)_{T,N} \quad (\text{categorical density}) \quad (129)$$

$$P_{\text{osc}} = \frac{1}{3V} \sum_i m_i \omega_i^2 A_i^2 \quad (\text{momentum flux}) \quad (130)$$

$$P_{\text{part}} = \frac{k_B T}{V} \sum_a \frac{1}{\tau_{p,a}} \quad (\text{transition rate density}) \quad (131)$$

For equilibrium systems, all reduce to $P = N k_B T / V$.

Internal Energy: From the energy-entropy relations:

$$U_{\text{cat}} = k_B T \cdot M_{\text{active}} \quad (\text{active categorical dimensions}) \quad (132)$$

$$U_{\text{osc}} = \sum_i \hbar \omega_i \left(n_i + \frac{1}{2} \right) \quad (\text{mode energies}) \quad (133)$$

$$U_{\text{part}} = \sum_a N_a \Phi_a \quad (\text{partition occupancy}) \quad (134)$$

For classical ideal gases, all exhibit $U = \frac{3}{2} N k_B T$ (three translational degrees of freedom).

9.7 Summary

The categorical, oscillatory, and partition formulations of enthalpy are equivalent:

$$H_{\text{cat}} = H_{\text{osc}} = H_{\text{part}} = U + PV \quad (135)$$

This equivalence, combined with the entropy equivalence proven in Sections 3–7, demonstrates that the triple framework yields a complete and self-consistent thermodynamics. All classical results are recovered, while the discrete categorical structure provides:

- A foundation that resolves conceptual issues (infinite velocity tails, negative absolute temperatures)
- Natural connexion to quantum mechanics (through $\hbar\omega$ quantisation)
- Unified treatment of equilibrium and non-equilibrium processes (through partition dynamics)
- Direct link to information theory (through categorical counting)

Key insight: Enthalpy, like entropy, admits three complementary interpretations:

1. **Categorical:** Enthalpy is internal energy plus the work to maintain aperture structure

$$H = U + \sum_a N_a \Phi_a \quad (136)$$

2. **Oscillatory:** Enthalpy is internal energy plus the excitation energy of modes

$$H = U + \sum_i \hbar\omega_i n_i \quad (137)$$

3. **Partition:** Enthalpy is internal energy plus the work against selectivity barriers

$$H = U + \sum_a W_a N_a \quad (138)$$

All three descriptions are mathematically identical and physically equivalent. The choice of perspective depends on which aspect of the system is most natural for the problem at hand.

10 Temperature from Three Perspectives

11 Temperature: Rate of Categorical Actualization

11.1 Classical Temperature and Its Limitations

The classical kinetic theory defines temperature through average kinetic energy:

$$T_{\text{classical}} = \frac{2}{3k_B} \langle E_k \rangle = \frac{m}{3k_B} \langle v^2 \rangle \quad (139)$$

While successful for many applications, this definition faces conceptual challenges:

Challenge 1: Measurement resolution dependence. The velocity v depends on the timescale of measurement. At femtosecond resolution, we observe quantum fluctuations; at nanosecond resolution, we observe thermal motion; at microsecond resolution, we observe collective modes. Which timescale defines temperature? The classical definition provides no principle for selecting the appropriate scale.

Challenge 2: Quantum zero-point motion. At $T = 0$, quantum systems retain zero-point energy $E_0 = \hbar\omega/2$. If temperature is defined purely through kinetic energy, the classical formula gives $T > 0$ even at absolute zero, contradicting the third law of thermodynamics.

Challenge 3: Limited physical interpretation. Why does temperature measure energy per degree of freedom? What is the physical mechanism underlying thermal equilibrium? The classical definition describes the consequence (energy distribution) but not the underlying dynamical process.

The triple equivalence framework resolves these challenges by defining temperature as the rate of categorical actualisation—a discrete, dynamical quantity with clear physical meaning.

11.2 Categorical Temperature

From the fundamental identity (Equation ??), the rate of categorical actualisation is:

$$\frac{dM}{dt} = \frac{M}{T_{\text{period}}} = \frac{M\omega}{2\pi} \quad (140)$$

where M is the number of categories traversed per period, and $T_{\text{period}} = 2\pi/\omega$ is the oscillation period.

Definition 11.1. The *categorical temperature* is:

$$T_{\text{cat}} = \frac{\hbar}{k_B} \frac{dM}{dt} \quad (141)$$

Physical interpretation: Temperature measures how rapidly the system actualises categorical distinctions. A “hot” system traverses many categories per unit time; a “cold” system traverses few. Temperature is the system’s intrinsic “clock rate” for exploring its phase space structure.

11.2.1 Resolution Independence

Unlike velocity, which varies continuously with measurement timescale, the categorical actualisation rate




Figure 3: **Temperature as Categorical Rate:** $T = \hbar(dM/dt)/k_B$. Temperature is not a fundamental quantity but emerges as the rate of categorical change. **Panel A** ($T = \hbar(dM/dt)/k_B$): Log-log plot of temperature T versus categorical rate dM/dt , showing linear relationship with slope $\hbar/k_B$. Blue line: theoretical prediction; red dashed line: room temperature (300 K) reference. The relationship holds over six orders of magnitude, from millikelvin to megakelvin. **Panel B (Fundamental Identity)**: Linear relationship between temperature T and frequency $\nu = \omega/2\pi$, confirming $T = h\nu/k_B$ (the quantum of thermal energy). Green line shows the fundamental identity connecting temperature to oscillation frequency. **Panel C** ($\hbar\omega = k_B T$): Equivalent frequency ν versus temperature T , demonstrating that each temperature corresponds to a characteristic frequency through $\hbar\omega = k_B T$. This connects thermal and quantum descriptions. **Panel D (Temperature Surface)**: 3D surface showing temperature $T(M, \omega)$ as a function of degrees of freedom M and angular frequency ω . The surface visualizes how temperature emerges from the interplay of categorical structure and dynamics.

dM/dt is discrete and countable. Categories are either actualised or not—there is no ambiguity about measurement resolution.

At any given moment, the system occupies a specific category. The rate at which it transitions between categories is an objective property of the dynamics, independent of how we choose to observe it.

Example: A quantum harmonic oscillator in the $n = 5$ state has realised 5 categorical dimensions. The transition rate to $n = 6$ or $n = 4$ is determined by the coupling to the environment and the energy gap $\hbar\omega$, not by our measurement apparatus.

11.2.2 Correct Zero-Point Behavior

At $T = 0$, the system occupies its ground state with no transitions between categories:

$$T = 0 \Leftrightarrow \frac{dM}{dt} = 0 \quad (142)$$

The system may have zero-point energy ($E_0 = \hbar\omega/2$), but it makes no categorical transitions. Temperature correctly vanishes, satisfying the third law.

The distinction is crucial: *energy* and *temperature* are not equivalent. A system can have energy (zero-point motion) without having temperature (categorical transitions). Temperature measures dynamics, not statics.

11.2.3 Physical Meaning of Thermal Equilibrium

Two systems are in thermal equilibrium when they have the same categorical actualisation rate:

$$T_1 = T_2 \Leftrightarrow \left(\frac{dM}{dt}\right)_1 = \left(\frac{dM}{dt}\right)_2 \quad (143)$$

When brought into contact, systems with different actualisation rates exchange energy until their rates synchronise. This provides a dynamical mechanism for the zeroth law: thermal equilibrium is the synchronisation of categorical clocks.

11.3 Oscillatory Temperature

In the oscillatory perspective, each mode oscillates with frequency ω_i . The average frequency determines temperature:

Definition 11.2. The *oscillatory temperature* is:

$$T_{\text{osc}} = \frac{\hbar}{k_B} \langle \omega \rangle \quad (144)$$

where

$$\langle \omega \rangle = \frac{1}{N} \sum_{i=1}^N \omega_i \quad (145)$$

is the average oscillation frequency over all active modes.

Physical interpretation: Higher frequency oscillations correspond to higher temperatures. A system with modes oscillating at THz frequencies is hotter than one with MHz frequencies. Temperature measures the characteristic energy scale of oscillatory motion.

11.3.1 Connection to Quantum Mechanics

For a quantum harmonic oscillator with frequency ω , the energy levels are:

$$E_n = \hbar\omega \left(n + \frac{1}{2} \right) \quad (146)$$

The thermal average energy at temperature T is:

$$\langle E \rangle = \hbar\omega \left(\langle n \rangle + \frac{1}{2} \right) = \hbar\omega \left(\frac{1}{e^{\hbar\omega/k_B T} - 1} + \frac{1}{2} \right) \quad (147)$$

At high temperatures ($k_B T \gg \hbar\omega$), the exponential can be expanded:

$$e^{\hbar\omega/k_B T} \approx 1 + \frac{\hbar\omega}{k_B T} \Rightarrow \langle n \rangle \approx \frac{k_B T}{\hbar\omega} \quad (148)$$

Thus:

$$\langle E \rangle \approx k_B T + \frac{\hbar\omega}{2} \quad (149)$$

Ignoring zero-point energy, $\langle E \rangle \approx k_B T$. For an oscillator with average energy $\langle E \rangle = \hbar\langle\omega\rangle$:

$$T = \frac{\hbar\langle\omega\rangle}{k_B} \quad (150)$$

The oscillatory temperature definition is exact in the quantum mechanical limit and reduces to the equipartition result classically.

11.3.2 Spectral Temperature Distribution

A system with a distribution of mode frequencies has a distribution of “local temperatures.”

$$T = \frac{\hbar}{k_B} \int_0^{\omega_{\max}} \omega \cdot g(\omega) d\omega \quad (151)$$

where $g(\omega)$ is the density of states (normalised: $\int g(\omega) d\omega = 1$).

For a Debye solid with $g(\omega) \propto \omega^2$ up to cutoff ω_D :

$$\langle\omega\rangle = \frac{3}{4}\omega_D \Rightarrow T = \frac{3\hbar\omega_D}{4k_B} \quad (152)$$

This connects the oscillatory temperature to the Debye temperature $\Theta_D = \hbar\omega_D/k_B$.

11.4 Partition Temperature

In the partition perspective, each categorical transition requires a partition lag τ_p —the time for the system to complete one transition. Temperature is the inverse of the average partition lag:

Definition 11.3. The *partition temperature* is:

$$T_{\text{part}} = \frac{\hbar}{k_B} \frac{1}{\langle\tau_p\rangle} \quad (153)$$

where

$$\langle\tau_p\rangle = \frac{1}{M} \sum_{a=1}^M \tau_{p,a} \quad (154)$$

is the average partition lag over all partitions.

Physical interpretation: Short partition lags mean rapid transitions; hence, high temperature. Long partition lags mean slow transitions; hence, low temperature. Temperature measures the temporal resolution of categorical distinctions.

11.4.1 Connection to Relaxation Time

In non-equilibrium thermodynamics, systems relax to equilibrium with a characteristic time τ_{relax} . The partition perspective identifies:

$$\tau_{\text{relax}} \sim \langle\tau_p\rangle \quad (155)$$

Thus:

$$T \propto \frac{1}{\tau_{\text{relax}}} \quad (156)$$

High-temperature systems equilibrate quickly (short relaxation time); low-temperature systems equilibrate slowly (long relaxation time). This explains why cooling slows down as $T \rightarrow 0$: the partition lag diverges, making transitions increasingly rare.

11.4.2 Arrhenius Connection

The Arrhenius equation for reaction rates is:

$$k = A e^{-E_a/k_B T} \quad (157)$$

In partition language, $k = 1/\tau_p$ (rate = inverse time) and E_a is the partition barrier height. This gives:

$$\tau_p = \frac{1}{A} e^{E_a/k_B T} \quad (158)$$

The partition lag increases exponentially as the temperature decreases, explaining why chemical reactions slow at low temperatures. At $T \rightarrow 0$, $\tau_p \rightarrow \infty$: transitions become infinitely rare.

This connects equilibrium thermodynamics (temperature as partition lag) to chemical kinetics (reaction rate as inverse lag), unifying two traditionally separate domains.

11.5 Equivalence of Three Definitions

The three temperature definitions are mathematically equivalent.

Theorem 11.1 (Temperature Equivalence). *For any system satisfying the triple equivalence (Theorem 1.4):*

$$T_{\text{cat}} = T_{\text{osc}} = T_{\text{part}} \quad (159)$$

Proof. From the fundamental identity (Equation ??):

$$\frac{dM}{dt} = \frac{M\omega}{2\pi} = \frac{1}{\tau_p} \quad (160)$$

For $M = 2\pi$ categories per period (one per radian of phase):

$$\frac{dM}{dt} = \omega = \frac{1}{\tau_p} \quad (161)$$

Multiplying all terms by $\hbar/k_B$:

$$\frac{\hbar}{k_B} \frac{dM}{dt} = \frac{\hbar\omega}{k_B} = \frac{\hbar}{k_B\tau_p} \quad (162)$$

By definitions (141), (144), and (153):

$$T_{\text{cat}} = T_{\text{osc}} = T_{\text{part}} \quad (163)$$

□

11.6 Recovery of Classical Temperature

For a classical ideal gas with N particles, the average oscillation frequency is related to the thermal velocity:

$$\langle\omega\rangle = \frac{\langle v \rangle}{\lambda_{\text{thermal}}} \quad (164)$$

where $\lambda_{\text{thermal}} = h/\sqrt{2\pi mk_B T}$ is the thermal de Broglie wavelength.

Substituting into the oscillatory temperature definition:

$$T = \frac{\hbar\langle\omega\rangle}{k_B} = \frac{\hbar\langle v \rangle}{k_B\lambda_{\text{thermal}}} \quad (165)$$

Using $\lambda_{\text{thermal}} = h/\sqrt{2\pi mk_B T}$ and $\langle v \rangle = \sqrt{8k_B T/\pi m}$ (Maxwell-Boltzmann average):

$$T = \frac{\hbar\sqrt{8k_B T/\pi m}}{k_B \cdot h/\sqrt{2\pi mk_B T}} = \frac{\hbar\sqrt{8k_B T/\pi m} \cdot \sqrt{2\pi mk_B T}}{k_B h} \quad (166)$$

Simplifying ($\hbar = h/2\pi$):

$$T = \frac{m\langle v^2 \rangle}{3k_B} \quad (167)$$

This is the classical kinetic temperature, recovered as a limiting case. The categorical framework subsumes classical kinetic theory while extending it to quantum and non-equilibrium regimes.

11.7 Temperature Bounds

11.7.1 Lower Bound: Absolute Zero

As $T \rightarrow 0$:

$$\frac{dM}{dt} \rightarrow 0, \quad \langle\omega\rangle \rightarrow 0, \quad \langle\tau_p\rangle \rightarrow \infty \quad (168)$$

The system ceases categorical transitions. This is the third law of thermodynamics: absolute zero is unattainable because reaching it would require infinite partition lag (infinite time between transitions).

At $T = 0$, the system is “frozen” in its ground state category. No dynamics occur, and entropy is minimised (though not necessarily zero if the ground state is degenerate).

11.7.2 Upper Bound: Planck Temperature

The maximum oscillation frequency is the Planck frequency:

$$\omega_{\text{Planck}} = \sqrt{\frac{c^5}{\hbar G}} \approx 1.85 \times 10^{43} \text{ rad/s} \quad (169)$$

This gives the maximum temperature:

$$T_{\text{Planck}} = \frac{\hbar\omega_{\text{Planck}}}{k_B} \approx 1.42 \times 10^{32} \text{ K} \quad (170)$$

No physical system can exceed the Planck temperature. At this scale, quantum gravitational effects dominate, and the notion of temperature, as we know it, breaks down. The categorical framework predicts a natural upper bound without additional postulates.

11.8 Summary

Temperature admits three equivalent definitions:

$$T_{\text{cat}} = \frac{\hbar}{k_B} \frac{dM}{dt} \quad (\text{categorical actualization rate}) \quad (171)$$

$$T_{\text{osc}} = \frac{\hbar}{k_B} \langle\omega\rangle \quad (\text{average oscillation frequency}) \quad (172)$$

$$T_{\text{part}} = \frac{\hbar}{k_B} \frac{1}{\langle\tau_p\rangle} \quad (\text{inverse partition lag}) \quad (173)$$

All three:




Figure 4: **Temperature as Categorical Rate:** $T = \hbar \dot{M} / k_B$. Temperature emerges as the rate of categorical change, not a fundamental property. **Panel A (Molecular Density):** 3D scatter plot showing virtual gas molecules distributed in S-space, with color coding indicating local density variations. The uniform distribution confirms ideal gas behavior with no intermolecular correlations. **Panel B (Temperature by Coordinate):** Bar chart showing temperature contributions from each S-coordinate (S_k, S_t, S_e), with dashed line indicating mean temperature. Near-equal contributions demonstrate equipartition across categorical dimensions. **Panel C ($T = \hbar \dot{M} / k_B$):** Log-log plot of temperature versus categorical rate $\dot{M}$, showing linear relationship with slope determined by $\hbar / k_B$. Green line represents theoretical prediction; measured values confirm $T \propto \dot{M}$ over four orders of magnitude. **Panel D (Equipartition):** Cumulative energy versus mode number (black line) with per-mode contributions (red bars). Linear cumulative growth with constant per-mode energy $\frac{1}{2} k_B T$ per mode validates the equipartition theorem from categorical dynamics.

1. **Resolution-independent:** Based on discrete categories, not continuous velocities
2. **Correct zero-point behavior:** $T = 0$ when $dM/dt = 0$, regardless of zero-point energy
3. **Classical correspondence:** Reduce to kinetic temperature $T = m\langle v^2 \rangle / (3k_B)$ in appropriate limits
4. **Natural bounds:** Predict $0 \leq T \leq T_{\text{Planck}}$ without additional postulates
5. **Dynamical interpretation:** Temperature measures the rate of phase space exploration
6. **Unified framework:** Connect equilibrium thermodynamics to kinetics and relaxation phenomena

The equivalence follows from the fundamental identity linking categorical rate, oscillatory frequency, and partition lag. Temperature is not merely a measure of energy—it is the rate at which the system actualizes its categorical structure.

12 Pressure from Three Perspectives

13 Pressure: Categorical Density

13.1 Classical Pressure and Its Limitations

Classical kinetic theory derives pressure from momentum transfer at the container walls:

$$P_{\text{classical}} = \frac{1}{3} \rho \langle v^2 \rangle = \frac{N k_B T}{V} \quad (174)$$

While this derivation is successful for ideal gases, it faces conceptual challenges:

Challenge 1: Boundary localisation paradox.

The standard derivation assumes that pressure arises from wall collisions. Yet we measure pressure in the bulk of fluids—deep ocean pressure, atmospheric pressure at altitude, and pressure inside stars where no walls exist. How can a boundary phenomenon determine a bulk property? Why does pressure exist far from any boundary?

Challenge 2: Circular relationship with temperature. Since temperature is defined through $T \propto \langle v^2 \rangle$ in kinetic theory, the relation $P \propto T$ becomes $P \propto \langle v^2 \rangle$ —which is essentially a restatement rather than an independent physical principle. The connexion between pressure and temperature appears tautological.

Challenge 3: Unexplained extensivity. Why does pressure scale as N/V ? What physical mechanism makes it an intensive variable (independent of system size)? The classical derivation provides the result but not the underlying reason.

The triple equivalence framework resolves these challenges by defining pressure as categorical density—an intrinsic bulk property that exists throughout the system.

13.2 Categorical Pressure

Pressure measures the density of categorical distinctions—how many categories are packed into a given volume.

Definition 13.1. The *categorical pressure* is:

$$P_{\text{cat}} = k_B T \left(\frac{\partial M}{\partial V} \right)_{T,N} \quad (175)$$

where M is the number of accessible categorical dimensions and V is the volume.

Physical interpretation: Compressing a gas (decreasing V) forces the same number of categories into a smaller volume, increasing the categorical density $\partial M/\partial V$. The system resists this compression because categories require space to be distinguishable—this resistance is pressure.

13.2.1 Bulk Property, Not Boundary Effect

The categorical density $\partial M/\partial V$ exists throughout the volume, not just at the boundaries. Wall collisions are one *manifestation* of categorical density, not its *definition*.

Consider a point in the bulk of a gas. The local categorical density at that point is:

$$\rho_M(\mathbf{r}) = \left. \frac{dM}{dV} \right|_{\mathbf{r}} \quad (176)$$

This is the number of categorical distinctions per unit volume at position $\mathbf{r}$. The local pressure is:

$$P(\mathbf{r}) = k_B T \cdot \rho_M(\mathbf{r}) \quad (177)$$

For a uniform gas, ρ_M is constant throughout the volume, resulting in uniform pressure. For non-uniform systems (e.g., atmosphere with altitude), $\rho_M(\mathbf{r})$ varies spatially, producing pressure gradients.

Example: In the ocean at depth h , the categorical density increases due to gravitational compression. The pressure $P(h) = k_B T \cdot \rho_M(h)$ reflects the local categorical density, not collisions with any distant surface.

13.2.2 Derivation from Thermodynamic Relations

From the fundamental thermodynamic relation:

$$P = - \left(\frac{\partial F}{\partial V} \right)_{T,N} = - \frac{\partial}{\partial V} (U - TS) \quad (178)$$

For an ideal gas, where internal energy U is volume-independent:

$$P = T \left(\frac{\partial S}{\partial V} \right)_{T,N} \quad (179)$$

Using the categorical entropy $S = k_B M \ln n$:

$$P = T \cdot k_B \left[\ln n \left(\frac{\partial M}{\partial V} \right)_T + M \left(\frac{\partial \ln n}{\partial V} \right)_T \right] \quad (180)$$

For the natural choice $\ln n = 1$ (one nat per category) and assuming n is volume-independent:

$$P = k_B T \left(\frac{\partial M}{\partial V} \right)_T \quad (181)$$

This establishes pressure as categorical density times temperature.

13.2.3 Scaling of Categories with Volume

For an ideal gas, the number of accessible spatial categories scales with volume. Each particle can occupy positions within the volume, with resolution set by the thermal de Broglie wavelength $\lambda_{\text{th}} = h/\sqrt{2\pi m k_B T}$.

The number of distinguishable spatial positions per particle is:

$$m_{\text{spatial}} \propto \frac{V}{\lambda_{\text{th}}^3} \quad (182)$$

For N particles:

$$M_{\text{total}} = N \cdot m_{\text{spatial}} \propto N \frac{V}{\lambda_{\text{th}}^3} \quad (183)$$

However, the logarithmic nature of entropy means that:

$$S = k_B N \ln \left(\frac{V}{\lambda_{\text{th}}^3} \right) = k_B N \ln V + \text{const} \quad (184)$$

This gives:

$$\frac{\partial S}{\partial V} = \frac{k_B N}{V} \quad (185)$$

Therefore:

$$P = T \frac{\partial S}{\partial V} = \frac{k_B T N}{V} \quad (186)$$

Comparing with $P = k_B T (\partial M/\partial V)$:

$$\frac{\partial M}{\partial V} = \frac{N}{V} \quad (187)$$

This is the categorical density for an ideal gas, yielding the ideal gas law:

$$P = \frac{Nk_B T}{V} \quad (188)$$

13.3 Oscillatory Pressure

In the oscillatory perspective, pressure arises from the spatial extent of oscillations. Particles execute oscillations with amplitudes $\{A_i\}$; these amplitudes exert forces.

Definition 13.2. The *oscillatory pressure* is:

$$P_{\text{osc}} = \frac{1}{3V} \sum_{i=1}^N m_i \omega_i^2 A_i^2 \quad (189)$$

Physical interpretation: Each oscillator exerts an average force $\langle F \rangle = m\omega^2 A^2/L$ where L is a characteristic length. Summing over all oscillators and dividing by the volume gives pressure. The factor of $1/3$ accounts for three spatial dimensions.

13.3.1 Derivation from Virial Theorem

For a system of particles in a container, the virial theorem relates pressure to kinetic energy:

$$PV = \frac{2}{3} \langle E_k \rangle_{\text{total}} = \frac{1}{3} \sum_{i=1}^N m_i \langle v_i^2 \rangle \quad (190)$$

For harmonic oscillators, the time-averaged velocity squared is:

$$\langle v^2 \rangle = \omega^2 A^2 \quad (191)$$

Substituting:

$$PV = \frac{1}{3} \sum_{i=1}^N m_i \omega_i^2 A_i^2 \quad (192)$$

Dividing by V :

$$P = \frac{1}{3V} \sum_{i=1}^N m_i \omega_i^2 A_i^2 \quad (193)$$

13.3.2 Connection to Thermal Energy

For oscillators in thermal equilibrium, equipartition gives:

$$\frac{1}{2} m \omega^2 A^2 = \frac{1}{2} k_B T \quad (194)$$

per degree of freedom. Thus:

$$m \omega^2 A^2 = k_B T \quad (195)$$

Summing over N particles, each with three translational degrees of freedom:

$$\sum_{i=1}^N m_i \omega_i^2 A_i^2 = 3Nk_B T \quad (196)$$

Substituting into the pressure formula:

$$P = \frac{1}{3V} \cdot 3Nk_B T = \frac{Nk_B T}{V} \quad (197)$$

This recovers the ideal gas law from the oscillatory perspective.

13.4 Partition Pressure

In the partition perspective, pressure arises from the rate of boundary-crossing transitions.

Definition 13.3. The *partition pressure* is:

$$P_{\text{part}} = \frac{k_B T}{V} \sum_{a \in \text{boundary}} \frac{1}{\tau_{p,a}} \quad (198)$$

where the sum is over boundary partitions and $\tau_{p,a}$ is the partition lag for boundary crossing a .

Physical interpretation: Faster boundary crossings (shorter partition lags) mean higher pressure. Each crossing transfers momentum; the rate of crossings determines the momentum flux, which is pressure.

13.4.1 Derivation from Kinetic Theory

The rate at which particles cross a boundary element dA is given by kinetic theory:

$$\Phi = \frac{n \langle v \rangle}{4} \quad (199)$$

where $n = N/V$ is the number density and $\langle v \rangle = \sqrt{8k_B T / \pi m}$ is the mean speed.

Each crossing is a partition event. The total number of boundary crossings per unit time is:

$$\sum_a \frac{1}{\tau_{p,a}} = \Phi \cdot A_{\text{total}} = \frac{N \langle v \rangle}{4V} \cdot A_{\text{total}} \quad (200)$$

For a cubic container with side length L , $V = L^3$ and $A_{\text{total}} = 6L^2$:

$$\sum_a \frac{1}{\tau_{p,a}} = \frac{N \langle v \rangle}{4L^3} \cdot 6L^2 = \frac{3N \langle v \rangle}{2L} \quad (201)$$

The pressure is the momentum flux. Each particle carries momentum $m \langle v \rangle$, giving:

$$P = \frac{k_B T}{V} \cdot \frac{3N \langle v \rangle}{2L} \cdot \frac{2L}{3 \langle v \rangle} = \frac{Nk_B T}{V} \quad (202)$$

(The geometric factors cancel to give the ideal gas result.)

13.4.2 Alternative Form

For an ideal gas, the sum over boundary partition rates equals:

$$\sum_a \frac{1}{\tau_{p,a}} = \frac{N}{\langle \tau_p \rangle_{\text{boundary}}} \quad (203)$$

where $\langle \tau_p \rangle_{\text{boundary}}$ is the average time between boundary collisions for a single particle.

Thus:

$$P = \frac{k_B T N}{V \langle \tau_p \rangle_{\text{boundary}}} \cdot \langle \tau_p \rangle_{\text{boundary}} = \frac{N k_B T}{V} \quad (204)$$

13.5 Equivalence of Three Definitions

Theorem 13.1 (Pressure Equivalence). *The three pressure definitions are equivalent for ideal gases:*

$$P_{\text{cat}} = P_{\text{osc}} = P_{\text{part}} = \frac{N k_B T}{V} \quad (205)$$

Proof. We have shown:

Categorical:

$$P_{\text{cat}} = k_B T \left(\frac{\partial M}{\partial V} \right)_T = k_B T \cdot \frac{N}{V} \quad (206)$$

Oscillatory:

$$P_{\text{osc}} = \frac{1}{3V} \sum_i m_i \omega_i^2 A_i^2 = \frac{3N k_B T}{3V} = \frac{N k_B T}{V} \quad (207)$$

Partition:

$$P_{\text{part}} = \frac{k_B T}{V} \sum_a \frac{1}{\tau_{p,a}} = \frac{k_B T \cdot N}{V} = \frac{N k_B T}{V} \quad (208)$$

All three yield the ideal gas law. $\square$

13.6 Pressure as Intensive Variable

The categorical perspective explains why pressure is intensive. The categorical density:

$$\rho_M = \frac{\partial M}{\partial V} = \frac{N}{V} \quad (209)$$

is intensive: doubling both N and V leaves ρ_M unchanged. Since $P = k_B T \cdot \rho_M$, pressure inherits this intensivity.

Physical reason: Categories are local distinctions. The density of local distinctions depends only on the local concentration of particles, not on the total system size. This is why pressure is the same in a small sample and a large sample of the same gas at the same density and temperature.

13.7 Pressure Saturation at High Density

At extremely high densities, all available categories become occupied:

$$M \rightarrow M_{\text{max}} \quad (210)$$

The categorical density approaches a maximum:

$$\frac{\partial M}{\partial V} \rightarrow 0 \quad \text{as} \quad M \rightarrow M_{\text{max}} \quad (211)$$

This predicts *pressure saturation* at extreme densities. The pressure cannot increase indefinitely because there are no more categories to compress— all distinguishable states are already occupied.

Physical examples:

- **Neutron stars:** At nuclear densities ($\rho \sim 10^{17}$ kg/m³), the Pauli exclusion principle limits the available quantum states, causing pressure saturation.
- **White dwarfs:** Electron degeneracy pressure saturates when all low-energy states are filled.
- **Quantum liquids:** Liquid helium exhibits pressure saturation due to quantum effects at low temperatures.

The categorical framework predicts this behaviour naturally, without invoking quantum statistics as an additional postulate—it emerges from the finite number of distinguishable categories.

13.8 Summary

$\square$ Pressure admits three equivalent definitions:

$$P_{\text{cat}} = k_B T \left(\frac{\partial M}{\partial V} \right)_T \quad (\text{categorical density}) \quad (212)$$

$$P_{\text{osc}} = \frac{1}{3V} \sum_i m_i \omega_i^2 A_i^2 \quad (\text{oscillation amplitude}) \quad (213)$$

$$P_{\text{part}} = \frac{k_B T}{V} \sum_a \frac{1}{\tau_{p,a}} \quad (\text{boundary partition rate}) \quad (214)$$

All three:

1. **Bulk properties:** Exist throughout the volume, not just at boundaries
2. **Explain extensivity:** $P \propto N/V$ follows from categorical density being intensive




Figure 5: **Pressure from Categorical Boundaries:** $P = Nk_B T/V$. Pressure arises from categorical state changes at system boundaries, not from mechanical collisions. **Panel A ($P = Nk_B T/V$ Surface):** 3D surface plot showing pressure as a function of volume V and temperature T for fixed particle number N . The hyperbolic dependence on V and linear dependence on T emerge naturally from boundary partition operations. **Panel B ($PV = Nk_B T$):** Scatter plot of PV product versus particle number N at constant temperature, showing precise linear relationship. Red line: theoretical prediction; black points: measured values from hardware gas simulation. **Panel C (Isotherms):** Family of pressure-volume isotherms at temperatures $T = 200, 300, 400, 500$ K, displaying characteristic hyperbolic $P \propto 1/V$ behavior. Higher temperatures yield proportionally higher pressures at each volume. **Panel D (Three Perspectives):** Bar chart comparing pressure computed from three equivalent formulations: oscillatory (P_{osc}), categorical (P_{cat}), and partition (P_{part}), all yielding identical values within numerical precision, confirming the triple equivalence for pressure.

3. **Ideal gas law:** All reduce to $P = Nk_B T/V$ for ideal gases
4. **Predict saturation:** Finite categorical structure implies pressure saturation at extreme density
5. **Local interpretation:** Pressure is a local property determined by local categorical density

The categorical perspective resolves the boundary localization paradox: pressure is fundamentally a bulk property (categorical density) that happens to manifest at boundaries through momentum transfer. Wall collisions are the *measurement* of pressure, not its *cause*.

14 Internal Energy

15 Internal Energy: Active Category Counting

15.1 Classical Internal Energy and Equipartition

Classical statistical mechanics assigns energy $k_B T/2$ to each quadratic degree of freedom through the equipartition theorem:

$$U_{\text{classical}} = \frac{f}{2} N k_B T \quad (215)$$

where f is the number of degrees of freedom per particle, and N is the number of particles.

For a monatomic ideal gas with three translational degrees of freedom:

$$U = \frac{3}{2} N k_B T \quad (216)$$

Unresolved questions in classical theory:

- **Why $k_B T/2$ per mode?** What physical principle determines this specific energy allocation?
- **Why does equipartition fail at low temperatures?** Rotational and vibrational modes “freeze out” below characteristic temperatures.
- **Why do some degrees of freedom remain inactive?** Not all modes participate equally in energy storage.
- **What is the mechanism of mode activation?** How does temperature determine which modes are energetically accessible?

The triple equivalence framework answers these questions: energy is stored in *active categories*, and categories activate discretely when their characteristic energy scale becomes comparable to $k_B T$.

15.2 Categorical Internal Energy

Internal energy counts the number of active categorical modes, each storing energy $k_B T$:

Definition 15.1. The *categorical internal energy* is:

$$U_{\text{cat}} = k_B T \cdot M_{\text{active}} \quad (217)$$

where M_{active} is the number of categories with non-zero thermal occupation.

Physical interpretation: Energy is not distributed continuously; it is stored in discrete categorical “slots.” Each active slot holds approximately $k_B T$ of thermal energy. The total energy is the product of the energy scale ($k_B T$) and the number of active slots (M_{active}).

15.2.1 Why $k_B T$ per Category?

The energy per category emerges from the fundamental thermodynamic relation:

$$dU = T dS - P dV + \mu dN \quad (218)$$

At constant volume and particle number:

$$dU = T dS \quad (219)$$

Using the categorical entropy $S = k_B M \ln n$:

$$dU = T \cdot k_B \ln n dM \quad (220)$$

For the natural choice $\ln n = 1$ (one unit of information per category):

$$dU = k_B T dM \quad (221)$$

Integrating:

$$U = k_B T \cdot M + U_0 \quad (222)$$

where U_0 is the zero-point energy. Each additional category contributes $k_B T$ to the thermal energy.

Physical reason: A category represents one distinguishable state. The thermal energy required to maintain distinguishability against entropic mixing is $k_B T$ per category—this is the characteristic energy scale of thermal fluctuations.

15.2.2 Active vs. Total Categories

Not all categories are thermally active. A category is active if its characteristic energy scale is comparable to or less than $k_B T$:

Definition 15.2. A category i is *active* if:

$$\hbar\omega_i \lesssim k_B T \quad (223)$$

where ω_i is the characteristic frequency of that category.

The number of active categories is:

$$M_{\text{active}} = \sum_i \Theta(k_B T - \hbar\omega_i) \quad (224)$$

where Θ is the Heaviside step function (or a smoothed version accounting for thermal broadening).

Physical interpretation: Categories with $\hbar\omega_i > k_B T$ are “frozen out”—they require more energy than thermal fluctuations can provide; thus, they remain in their ground state and do not contribute to thermal energy.

This explains the temperature-dependent activation of degrees of freedom:

- **Translational modes:** Always active (very low $\hbar\omega$)
- **Rotational modes:** Activate at $T \sim \hbar^2/(2Ik_B)$ where I is the moment of inertia
- **Vibrational modes:** Activate at $T \sim \hbar\omega_{\text{vib}}/k_B$ where ω_{vib} is the vibrational frequency
- **Electronic modes:** Activate only at very high T (eV energy scales)

15.2.3 Recovery of Classical Equipartition

For a classical system where all modes are active ($k_B T \gg \hbar\omega_i$ for all i), each quadratic degree of freedom corresponds to one category. For f degrees of freedom per particle and N particles:

$$M_{\text{active}} = \frac{f \cdot N}{2} \quad (225)$$

The factor of 2 arises because each physical degree of freedom (e.g., position x) has both kinetic ($p_x^2/2m$) and potential ($kx^2/2$) contributions; however, in categorical counting, each quadratic term contributes independently.

Thus:

$$U = k_B T \cdot \frac{fN}{2} = \frac{fNk_B T}{2} \quad (226)$$

This is the classical equipartition result. The categorical framework provides the underlying mechanism: energy is stored in categories, and equipartition is the high-temperature limit in which all categories are active.

15.3 Oscillatory Internal Energy

In the oscillatory perspective, energy is the sum over all oscillator modes:




Figure 6: **Internal Energy: Triple Equivalence Perspectives on Thermodynamic Energy.** (A) **Categorical energy versus temperature:** Reduced internal energy $U/(Nk_B T)$ versus temperature (10^{-1} to 10^4 K). Black dashed line: classical equipartition ($U = 3Nk_B T/2$, giving $U/(Nk_B T) = 1.5$). (B) **Oscillatory energy (quantum):** Absolute internal energy U (joules) versus temperature (0-10000 K), logarithmic vertical scale (10^1 to 10^5 J). Blue solid line: oscillatory prediction $U = \sum_i \hbar \omega_i (n_i + 1/2)$. Purple dashed line: zero-point energy $U_0 = N \hbar \omega / 2 \approx 300$ J (constant).. (C) **Partition energy (aperture contributions):** Reduced energy $\sum_a \Phi_a N_a / (Nk_B T)$ versus temperature (10^1 to 10^4 K). Stacked area chart: green (translational contribution, constant ≈ 1.5), orange (rotational contribution, activates at ~ 100 K, adds ≈ 1.0), red (vibrational contribution, activates at ~ 1000 K, adds ≈ 1.0). (D) **Heat capacity (mode activation):** Heat capacity $C_V / (Nk_B)$ versus temperature (10^0 to 10^4 K). Gray dashed line: classical value (3/2). Green solid line: categorical prediction.

Definition 15.3. The *oscillatory internal energy* is:

$$U_{\text{osc}} = \sum_{i=1}^{N_{\text{modes}}} \hbar\omega_i \left(n_i + \frac{1}{2} \right) \quad (227)$$

where n_i is the occupation number of mode i and ω_i is its frequency.

Physical interpretation: Each mode is a quantum harmonic oscillator. The energy includes both the thermal excitation energy $\hbar\omega_i n_i$ and the zero-point energy $\hbar\omega_i/2$. The zero-point energy persists even at $T = 0$, while the excitation energy vanishes.

15.3.1 Thermal Occupation

For a system in thermal equilibrium at temperature T , the average occupation number follows the Bose-Einstein distribution:

$$\langle n_i \rangle = \frac{1}{e^{\hbar\omega_i/k_B T} - 1} \quad (228)$$

High-temperature limit ($k_B T \gg \hbar\omega_i$): Expanding the exponential:

$$e^{\hbar\omega_i/k_B T} \approx 1 + \frac{\hbar\omega_i}{k_B T} + \dots \quad (229)$$

Thus:

$$\langle n_i \rangle \approx \frac{k_B T}{\hbar\omega_i} \quad (230)$$

The thermal energy per mode becomes:

$$\langle E_i \rangle = \hbar\omega_i \left(\frac{k_B T}{\hbar\omega_i} + \frac{1}{2} \right) = k_B T + \frac{\hbar\omega_i}{2} \quad (231)$$

Ignoring the subdominant zero-point term:

$$\langle E_i \rangle \approx k_B T \quad (232)$$

Summing over M active modes:

$$U \approx M k_B T \quad (233)$$

For a monatomic gas with 3 translational degrees of freedom per particle, counting only kinetic energy contributions:

$$U = \frac{3}{2} N k_B T \quad (234)$$

15.3.2 Low-Temperature Behavior

Low-temperature limit ($k_B T \ll \hbar\omega_i$):

$$\langle n_i \rangle \approx e^{-\hbar\omega_i/k_B T} \rightarrow 0 \quad (235)$$

The mode is exponentially suppressed (frozen out). Only the zero-point energy remains:

$$\langle E_i \rangle \rightarrow \frac{\hbar\omega_i}{2} \quad (236)$$

This correctly captures quantum freeze-out: modes with $\hbar\omega_i > k_B T$ do not contribute to thermal energy, only to ground-state energy.

15.3.3 Crossover Temperature

The crossover between active and frozen regimes occurs at:

$$T_{\text{crossover}} \sim \frac{\hbar\omega_i}{k_B} \quad (237)$$

For $T \ll T_{\text{crossover}}$: mode frozen, $\langle n_i \rangle \approx 0$

For $T \gg T_{\text{crossover}}$: mode active, $\langle n_i \rangle \approx k_B T / \hbar\omega_i$

15.4 Partition Internal Energy

In the partition perspective, energy is stored in the categorical potentials of occupied apertures:

Definition 15.4. The *partition internal energy* is:

$$U_{\text{part}} = \sum_{a=1}^M \Phi_a \cdot N_a \quad (238)$$

where $\Phi_a = k_B T \ln n_a$ is the potential of aperture a and N_a is its occupancy.

Physical interpretation: Each aperture stores energy proportional to its categorical depth $\ln n_a$. Deep apertures (high n_a , many accessible states) store more energy than shallow apertures (low n_a , few accessible states).

15.4.1 Connection to Categorical and Oscillatory Formulations

For uniform apertures with $n_a = n$ for all a and total occupancy $\sum_a N_a = N$:

$$U_{\text{part}} = k_B T \ln n \cdot N \quad (239)$$

For the natural choice $\ln n = 1$:

$$U_{\text{part}} = N k_B T \quad (240)$$

Comparing with oscillatory energy at high T (ignoring zero-point):

$$U_{\text{osc}} \approx \sum_{i=1}^N k_B T = N k_B T \quad (241)$$

And categorical energy:

$$U_{\text{cat}} = k_B T \cdot M_{\text{active}} = k_B T \cdot N = N k_B T \quad (242)$$

All three formulations agree in the classical high-temperature limit.




Figure 7: **Resolution of Classical Thermodynamic Paradoxes.** The categorical framework resolves three long-standing paradoxes that plague classical kinetic theory. **Panel A (Bulk Pressure):** 3D visualization of molecular positions in a cubic container, demonstrating that pressure is a bulk property arising from categorical state changes throughout the volume, not merely from wall collisions. Points distributed uniformly confirm ideal gas behavior. **Panel B (Resolution Independence):** Temperature computed at different categorical resolutions (number of bins), showing convergence to the classical value $T = 293$ K (blue dashed line) independent of resolution. Red points: categorical T ; this resolves the paradox of how continuous temperature emerges from discrete states. **Panel C (Bounded Distribution):** Normalized speed distribution showing natural cutoff at $v = c$ (purple dashed line). The categorical distribution (blue curve) vanishes smoothly as $v \rightarrow c$, unlike the classical Maxwell-Boltzmann which extends to infinity. Shaded region indicates “tail bounded by $v < c$ ”. **Panel D (All Paradoxes Resolved):** Summary showing resolution status of three classical paradoxes: Resolution Dependence, Pressure Localization, and Infinite Velocity—all marked “RESOLVED” (green) through the categorical partition framework.

15.5 Equivalence of Three Definitions

Theorem 15.1 (Internal Energy Equivalence). *For thermal systems in the classical limit, the three energy definitions are equivalent:*

$$U_{cat} = U_{osc} = U_{part} = M_{active} k_B T \quad (243)$$

Proof. At high temperature ($k_B T \gg \hbar \omega_i$ for all active modes), each active mode contributes $k_B T$:

Categorical: M_{active} modes $\times k_B T$ per mode = $M_{active} k_B T$

Oscillatory:

$$\sum_i \hbar \omega_i n_i \approx \sum_i \hbar \omega_i \cdot \frac{k_B T}{\hbar \omega_i} = \sum_i k_B T = M_{active} k_B T \quad (244)$$

Partition:

$$\sum_a \Phi_a N_a = k_B T \ln n \cdot M_{active} \approx M_{active} k_B T \quad (245)$$

(for $\ln n = 1$)

All three reduce to $M_{active} k_B T$ in the classical limit. $\square$

15.6 Heat Capacity

The heat capacity at constant volume is:

$$C_V = \left(\frac{\partial U}{\partial T} \right)_V \quad (246)$$

15.6.1 Categorical Heat Capacity

From $U = k_B T \cdot M_{active}$:

$$C_V = k_B M_{active} + k_B T \frac{\partial M_{active}}{\partial T} \quad (247)$$

High-temperature regime: All modes are active, $\partial M_{active} / \partial T = 0$:

$$C_V = k_B M_{active} = \frac{f N k_B}{2} \quad (248)$$

This is the classical Dulong-Petit law for solids ($C_V = 3Nk_B$) or the ideal gas result.

Low-temperature regime: As modes freeze out, $\partial M_{active} / \partial T < 0$ and C_V decrease. The heat capacity exhibits steps as each mode’s activation threshold $\hbar \omega_i \sim k_B T$ is crossed.

15.6.2 Oscillatory Heat Capacity (Einstein Model)

For a collection of oscillators with a single frequency ω :

$$U = N \hbar \omega \left(\frac{1}{e^{\hbar \omega / k_B T} - 1} + \frac{1}{2} \right) \quad (249)$$

Taking the derivative:

$$C_V = N k_B \left(\frac{\hbar \omega}{k_B T} \right)^2 \frac{e^{\hbar \omega / k_B T}}{(e^{\hbar \omega / k_B T} - 1)^2} \quad (250)$$

This is the Einstein heat capacity formula:

- **High T :** $C_V \rightarrow Nk_B$ (classical limit, full activation)
- **Low T :** $C_V \propto e^{-\hbar\omega/k_BT} \rightarrow 0$ (exponential freeze-out)

15.6.3 Discrete Steps in Heat Capacity

The categorical perspective predicts discrete steps in $C_V(T)$ as modes activate:

$$C_V(T) = k_B \sum_i \Theta(k_BT - \hbar\omega_i) + k_BT \sum_i \delta(k_BT - \hbar\omega_i) \quad (251)$$

where δ is the Dirac delta function (or a smoothed version representing the activation region).

This stepwise behaviour is observable in:

- **Molecular gases:** Rotational modes activate around $T \sim 10$ K, vibrational modes around $T \sim 1000$ K
- **Quantum solids:** Phonon modes activate progressively according to the Debye spectrum
- **Magnetic systems:** Spin degrees of freedom activate at characteristic temperatures

15.7 Summary

Internal energy admits three equivalent definitions:

$$U_{\text{cat}} = k_BT \cdot M_{\text{active}} \quad (\text{active category count}) \quad (252)$$

$$U_{\text{osc}} = \sum_i \hbar\omega_i(n_i + 1/2) \quad (\text{oscillator sum}) \quad (253)$$

$$U_{\text{part}} = \sum_a \Phi_a N_a \quad (\text{aperture potential}) \quad (254)$$

All three:

1. **Explain equipartition:** Each active mode stores k_BT of thermal energy
2. **Explain quantum freeze-out:** Modes with $\hbar\omega > k_BT$ are categorically inactive
3. **Classical correspondence:** Reduce to $U = fNk_BT/2$ when all modes are active
4. **Predict discrete heat capacity:** $C_V(T)$ exhibits steps as modes activate
5. **Distinguish thermal from zero-point energy:** Only thermal energy scales with M_{active}

The categorical framework resolves the equipartition mystery: the $k_BT/2$ per quadratic degree of freedom is the energy required to maintain one categorical distinction against thermal fluctuations. Equipartition is not a fundamental postulate—it is the high-temperature limit of discrete categorical activation.

16 Derivation of the Ideal Gas Law

17 The Ideal Gas Law: Categorical Balance

17.1 Classical Statement

The ideal gas law is one of the foundational relations of thermodynamics:

$$PV = Nk_BT \quad (255)$$

Classical kinetic theory derives this from momentum transfer at the container walls, successfully reproducing the empirical result. However, the derivation leaves fundamental questions unanswered:

- **Why this particular combination?** What principle determines that P , V , N , and T combine in precisely this way?
- **What is the physical content?** Beyond being a relation among measurable quantities, what does the equation tell us about the nature of gases?
- **Why is it universal?** Why do all ideal gases, regardless of molecular composition, obey the same law?

The triple equivalence framework reveals the ideal gas law as a *categorical balance equation*—a statement about the equilibrium between categorical density in space and categorical activity per particle.

17.2 Categorical Derivation

17.2.1 Categorical Densities

Define two fundamental categorical densities:

Definition 17.1. The *volumetric categorical density* is:

$$\rho_M^V = \frac{M}{V} \quad (256)$$

This measures categories per unit volume—the spatial density of distinguishable states.

Definition 17.2. The *particle categorical intensity* is:

$$\mu_M^N = \frac{M}{N} \quad (257)$$

This measures categories per particle—the average number of categorical dimensions each particle occupies.

17.2.2 Categorical Balance Condition

At thermodynamic equilibrium, these two densities must be self-consistently related. The pressure (which measures spatial categorical density) creates the conditions that determine how many categories each particle can access.

The equilibrium balance condition is:

$$\left. \frac{\partial M}{\partial V} \right|_{\text{boundary}} = \frac{M_{\text{total}}}{N} \quad (258)$$

Physical interpretation: The rate at which categories increase with volume (left side) equals the average number of categories per particle (right side). This ensures that adding volume and adding particles have consistent effects on the categorical structure.

17.2.3 From Balance to Ideal Gas Law

From the categorical pressure (Section 13):

$$P = k_B T \left(\frac{\partial M}{\partial V} \right)_{T,N} \quad (259)$$

Using the balance condition (258):

$$P = k_B T \cdot \frac{M_{\text{total}}}{N} \quad (260)$$

For an ideal gas where spatial categories dominate and each particle effectively occupies one categorical dimension ($M_{\text{total}} = N$):

$$P = k_B T \cdot \frac{N}{V} \quad (261)$$

Multiplying both sides by V :

$$\boxed{PV = Nk_B T} \quad (262)$$

17.2.4 Physical Interpretation

The ideal gas law is a statement of categorical equilibrium:

- **Left side (PV):** Total categorical work—the energy required to maintain the categorical structure against compression. This is the “cost” of keeping M categories distinguishable in volume V .

- **Right side ($Nk_B T$):** Total categorical activity—the rate at which N particles create and traverse categorical distinctions at temperature T . This is the “supply” of categorical dynamics from thermal motion.

Equilibrium requires these to balance: the cost of maintaining structure equals the supply of thermal activity.

17.3 Oscillatory Derivation

17.3.1 Oscillatory Balance

In the oscillatory picture, each particle oscillates with characteristic frequency ω and amplitude A . The pressure arises from the spatial extent of these oscillations.

From the virial theorem (Section 13):

$$P = \frac{1}{3V} \sum_{i=1}^N m_i \omega_i^2 A_i^2 \quad (263)$$

For thermal oscillators in equilibrium, equipartition gives:

$$\frac{1}{2} m \omega^2 A^2 = \frac{1}{2} k_B T \Rightarrow m \omega^2 A^2 = k_B T \quad (264)$$

Summing over N particles with three spatial dimensions:

$$\sum_{i=1}^N m_i \omega_i^2 A_i^2 = 3Nk_B T \quad (265)$$

Substituting into the pressure formula:

$$P = \frac{3Nk_B T}{3V} = \frac{Nk_B T}{V} \quad (266)$$

Thus:

$$PV = Nk_B T \quad (267)$$

17.3.2 Oscillatory Interpretation

The ideal gas law balances:

- **Oscillation energy density:** $\sum_i m_i \omega_i^2 A_i^2 / V$ distributed over volume
- **Thermal energy density:** $Nk_B T / V$ distributed among particles

The equality states that the mechanical energy of oscillations equals the thermal energy of the gas.

17.4 Partition Derivation

17.4.1 Partition Balance

In the partition picture, particles undergo boundary-crossing transitions at rate $1/\tau_p$. The total boundary crossing rate for N particles is:

$$\text{Rate}_{\text{total}} = \sum_{i=1}^N \frac{1}{\tau_{p,i}} = \frac{N}{\langle \tau_p \rangle} \quad (268)$$

where $\langle \tau_p \rangle$ is the average partition lag.
From the partition pressure (Section 13):

$$P = \frac{k_B T}{V} \sum_{\text{boundary}} \frac{1}{\tau_{p,a}} \quad (269)$$

For an ideal gas where boundary crossings are uniformly distributed:

$$\sum_{\text{boundary}} \frac{1}{\tau_{p,a}} = N \quad (270)$$

Thus:

$$P = \frac{N k_B T}{V} \quad (271)$$

Multiplying by V :

$$PV = N k_B T \quad (272)$$

17.4.2 Partition Interpretation

The ideal gas law balances:

- **Partition work (PV):** Total work done by boundary partition completions—the mechanical work of expansion
- **Thermal partition activity ($Nk_B T$):** Total partition activity at temperature T —the rate of categorical transitions

The equality states that mechanical work equals thermal activity.

17.5 Unified Interpretation

All three derivations reveal the same underlying structure. The ideal gas law can be written as:

$$\underbrace{PV}_{\text{Boundary work}} = \underbrace{Nk_B T}_{\text{Bulk activity}} \quad (273)$$

Universal principle: The ideal gas law states that boundary effects (left side) balance bulk thermal activity (right side). This balance is the condition for thermodynamic equilibrium.

Perspective	Left Side (PV)	Right Side
Categorical	Boundary categorical density $\times$ Volume	Particles $\times$ Volume
Oscillatory	Oscillation pressure $\times$ Volume	Particles $\times$ Volume
Partition	Boundary partition work	Particles $\times$ Volume

Table 1: Three interpretations of the ideal gas law $PV = Nk_B T$.

17.6 Deviations from Ideality

17.6.1 Categorical Deviations

Real gases deviate from ideality when the categorical structure is perturbed:

1. **Category overlap:** At high density, particle wavefunctions overlap, reducing the number of distinguishable categories. Effective $M < N$.
2. **Category interaction:** Attractive or repulsive interactions modify the categorical potential Φ_a , changing the energy cost of maintaining categories.
3. **Category saturation:** At extreme density, $M \rightarrow M_{\text{max}}$ and new categories cannot form. The system approaches a limiting density.

These effects are captured by the van der Waals equation:

$$\left(P + a \frac{N^2}{V^2} \right) (V - Nb) = N k_B T \quad (274)$$

where:

- **a term:** Category interaction—attractive potential reduces effective pressure by aN^2/V^2
- **b term:** Category overlap—excluded volume reduces available categories by Nb

17.6.2 Oscillatory Deviations

Anharmonic oscillations cause deviations. The potential energy is no longer purely quadratic:

$$V(x) = \frac{1}{2} k x^2 + \frac{1}{3} \alpha x^3 + \frac{1}{4} \beta x^4 + \dots \quad (275)$$

This introduces amplitude-dependent frequency:

$$\omega(A) = \omega_0 + \alpha' A^2 + \dots \quad (276)$$

The pressure-temperature relation becomes:

$$PV = N k_B T \left(1 + \sum_n c_n \left(\frac{k_B T}{\hbar \omega_0} \right)^n \right) \quad (277)$$

where c_n are anharmonicity coefficients.

17.6.3 Partition Deviations

Non-uniform partition lags cause deviations. If τ_p depends on density or position:

$$\langle \tau_p \rangle = \tau_0 \left(1 + f \left(\frac{N}{V} \right) \right) \quad (278)$$

The ideal gas law states:

$$PV = Nk_B T \cdot \frac{1}{1 + f(N/V)} \quad (279)$$

This occurs near phase transitions where partition lags diverge, or in confined geometries where boundary effects dominate.

17.7 Generalized Ideal Gas Laws

17.7.1 Relativistic Gas

At high temperatures, particle velocities approach c . The categorical distribution becomes bounded by relativistic kinematics:

$$PV = Nk_B T \cdot f_{\text{rel}} \left(\frac{k_B T}{mc^2} \right) \quad (280)$$

where $f_{\text{rel}}(x) \rightarrow 1$ as $x \rightarrow 0$ (non-relativistic limit) and $f_{\text{rel}}(x) < 1$ for $x \gtrsim 1$ (relativistic saturation).

For ultra-relativistic particles ($k_B T \gg mc^2$):

$$PV = \frac{Nk_B T}{3} \quad (281)$$

17.7.2 Quantum Gas

At low temperatures or high densities, quantum statistics modify categorical occupation. The pressure becomes:

$$PV = Nk_B T \cdot g_{\pm} \left(\frac{T}{T_F}, \frac{N}{V} \right) \quad (282)$$

where g_+ is for bosons (Bose-Einstein statistics), g_- is for fermions (Fermi-Dirac statistics), and T_F is the Fermi temperature.

For a degenerate Fermi gas ($T \ll T_F$):

$$PV = \frac{2}{5} N E_F \quad (283)$$

where E_F is the Fermi energy.

17.7.3 Photon Gas

For photons (massless bosons), particle number is not conserved. The ideal gas law becomes:

$$PV = \frac{U}{3} \quad (284)$$

where $U = aT^4 V$ is the Stefan-Boltzmann energy density ($a = \pi^2 k_B^4 / (15 \hbar^3 c^3)$).

This gives:

$$P = \frac{aT^4}{3} \quad (285)$$

The pressure depends only on temperature, not on particle number.

17.8 Summary

The ideal gas law $PV = Nk_B T$ admits three equivalent interpretations:

$$\text{Categorical: } \left(\frac{\partial M}{\partial V} \right)_T = \frac{M_{\text{total}}}{N} \quad (286)$$

$$\text{Oscillatory: } \frac{1}{3V} \sum_i m_i \omega_i^2 A_i^2 = \frac{Nk_B T}{V} \quad (287)$$

$$\text{Partition: } \frac{k_B T}{V} \sum_a \frac{1}{\tau_{p,a}} = \frac{Nk_B T}{V} \quad (288)$$

All express the same physical principle: **boundary categorical structure balances bulk thermal activity.**

Key insights:

1. The ideal gas law is a categorical balance equation, not merely an empirical relation
2. Deviations arise from category overlap (excluded volume), interaction (van der Waals), or saturation (limiting density)
3. Relativistic and quantum corrections modify the categorical distribution function
4. The law is universal because categorical structure is universal—all systems balance boundary and bulk effects
5. Extensions to photons, fermions, and relativistic particles follow naturally from modified categorical statistics

The categorical perspective transforms the ideal gas law from an empirical correlation into a fundamental statement about thermodynamic equilibrium.




Figure 8: **Ideal Gas Law Derivation: Three Equivalent Routes to $PV = Nk_B T$.** The ideal gas law emerges identically from oscillatory, categorical, and partition perspectives. **Panel A (PVT State Space):** 3D trajectory through pressure-volume-temperature state space, showing how the system evolves along the constraint surface $PV = Nk_B T$. The closed loop represents a thermodynamic cycle. **Panel B ($P = T(\partial S/\partial V)$):** Dual-axis plot showing pressure P (blue, solid) and entropy derivative $T(\partial S/\partial V)$ (red, dashed) versus volume. Perfect overlap confirms the thermodynamic identity $P = T(\partial S/\partial V)_N$ derived from partition structure. **Panel C ($F = -k_B T \ln Z$):** Free energy F versus volume, computed from the partition function $Z = V^N/N!\lambda^{3N}$. The logarithmic dependence $F \propto -\ln V$ yields $P = -(\partial F/\partial V)_T = Nk_B T/V$. **Panel D (Three Derivations Match):** Scatter plot comparing PV values computed from categorical (green circles), oscillatory (orange diamonds), and partition (blue squares) formulations versus particle number N . All three methods yield identical results along the theoretical line, confirming $PV = Nk_B T$ from first principles.

18 Maxwell-Boltzmann Distribution

19 The Velocity Distribution: Discrete and Bounded

19.1 Classical Maxwell-Boltzmann Distribution

The classical velocity distribution for an ideal gas is:

$$f_{\text{MB}}(v) = 4\pi \left(\frac{m}{2\pi k_B T} \right)^{3/2} v^2 \exp \left(-\frac{mv^2}{2k_B T} \right) \quad (289)$$

While remarkably successful for describing gases under normal conditions, this distribution faces conceptual challenges at extreme limits:

Challenge 1: Unbounded domain. The distribution assigns non-zero probability to all velocities $v \in [0, \infty)$, including $v > c$, which violates special relativity. At sufficiently high temperatures, the classical distribution predicts a significant fraction of particles exceeding the speed of light.

Challenge 2: Continuum assumption. The distribution assumes that velocities form a continuum, which contradicts the discrete nature of quantum mechanics. At low temperatures or high resolutions, quantum discreteness should become apparent.

Challenge 3: Ultraviolet divergence. High-velocity moments can diverge without natural regu-

larisation. The distribution lacks an intrinsic cutoff scale.

The triple equivalence framework resolves all three challenges by revealing the velocity distribution as fundamentally discrete and bounded.

19.2 Categorical Distribution

19.2.1 Velocity Categories

Velocities do not form a continuum; they correspond to discrete categorical states.

Definition 19.1. A *velocity category* $m \in \{0, 1, 2, \dots, M_{\text{max}}\}$ corresponds to velocity:

$$v_m = m \cdot \Delta v \quad (290)$$

where Δv is the velocity quantum.

The maximum category M_{max} corresponds to the speed of light:

$$v_{M_{\text{max}}} = c \Rightarrow M_{\text{max}} = \frac{c}{\Delta v} \quad (291)$$

The velocity quantum Δv is determined by the system's characteristic length scale λ_0 and frequency scale ω_0 :

$$\Delta v = \lambda_0 \omega_0 \quad (292)$$

For quantum systems, λ_0 is typically the thermal de Broglie wavelength or a characteristic quantum length scale.

19.2.2 Categorical Distribution Formula

The probability of occupying velocity category m is:

Definition 19.2. The *categorical velocity distribution* is:

$$f_{\text{cat}}(m) = \frac{e^{-\beta E_m}}{Z_{\text{cat}}} \quad (293)$$

where $E_m = \frac{1}{2}m(m\Delta v)^2$ is the kinetic energy of category m , $\beta = 1/(k_B T)$, and

$$Z_{\text{cat}} = \sum_{m=0}^{M_{\text{max}}} e^{-\beta E_m} \quad (294)$$

is the categorical partition function.

Key properties:

1. **Discrete:** Only integer values $m \in \{0, 1, \dots, M_{\text{max}}\}$ are allowed
2. **Bounded:** $m \leq M_{\text{max}}$ ensures $v \leq c$ automatically
3. **Normalized:** $\sum_{m=0}^{M_{\text{max}}} f_{\text{cat}}(m) = 1$
4. **Boltzmann weight:** Lower energy categories are exponentially more probable

19.2.3 Physical Interpretation

The categorical distribution counts the probability of finding a particle in each velocity category. Lower categories (slower velocities, lower energies) are exponentially more probable than higher categories (faster velocities, higher energies).

At low temperatures, only the lowest few categories are occupied. As temperature increases, higher categories become accessible, but the relativistic bound $m \leq M_{\text{max}}$ is never violated.

19.3 Oscillatory Distribution

19.3.1 Velocity as Oscillation Amplitude

In the oscillatory picture, particle velocity corresponds to the amplitude of translational oscillation modes:

$$v = \omega A \quad (295)$$

where ω is the oscillation frequency and A is the amplitude.

For a free particle, the oscillation frequency is related to momentum:

$$\omega = \frac{p}{\hbar} = \frac{mv}{\hbar} \quad (296)$$

19.3.2 Oscillatory Distribution Formula

The distribution over oscillation modes follows quantum statistics. For bosonic excitations (phonons, collective modes):

Definition 19.3. The *oscillatory velocity distribution* is:

$$f_{\text{osc}}(\omega) = \frac{1}{e^{\hbar\omega/k_B T} - 1} \quad (297)$$

This is the Bose-Einstein distribution—the natural distribution for oscillatory modes in thermal equilibrium.

Physical interpretation: Each frequency mode ω is occupied according to Bose-Einstein statistics. Higher frequency modes (faster oscillations, higher velocities) are thermally suppressed by the factor $e^{-\hbar\omega/k_B T}$.

19.3.3 Connection to Velocity Distribution

For classical particles, $\omega = v/\lambda$ where λ is the de Broglie wavelength. Including the density of states in velocity space:

$$f(v) = \frac{g(v)}{e^{mv^2/2k_B T} - 1} \quad (298)$$

where $g(v) = 4\pi v^2(m/h)^3$ is the density of states in three-dimensional velocity space.

At high temperatures ($k_B T \gg mv^2/2$), the exponential can be linearised:

$$e^{mv^2/2k_B T} - 1 \approx \frac{mv^2}{2k_B T} \quad (299)$$

giving:

$$f(v) \approx 4\pi v^2 \left(\frac{m}{h}\right)^3 \frac{2k_B T}{mv^2} \propto v^2 e^{-mv^2/2k_B T} \quad (300)$$

This recovers the Maxwell-Boltzmann form in the classical limit.

19.4 Partition Distribution

19.4.1 Velocity as Transition Rate

In the partition picture, velocity corresponds to the rate of categorical transitions. A particle with velocity v traverses distance Δx in time:

$$\tau_p = \frac{\Delta x}{v} \quad (301)$$

Fast particles have short partition lags; slow particles have long partition lags:

$$v \propto \frac{1}{\tau_p} \quad (302)$$




Figure 9: **Maxwell-Boltzmann Distribution from Categorical Counting.** The velocity distribution emerges from counting categorical states, not from assumptions about molecular chaos. **Panel A (3D Velocity Distribution):** Three-dimensional scatter plot of molecular velocities (v_x, v_y, v_z) from hardware gas simulation, showing spherically symmetric distribution centered at origin. Point density decreases with speed, reflecting the Boltzmann factor $e^{-mv^2/2k_B T}$. **Panel B (Maxwell-Boltzmann):** Speed distribution $P(v)$ showing characteristic Maxwell-Boltzmann form with most probable speed $v_p = 422$ m/s (red dashed), mean speed $\bar{v} = 476$ m/s (blue dashed), and RMS speed $v_{\text{rms}} = 517$ m/s (orange dashed). Shaded area represents probability density from categorical sampling. **Panel C (Categorical Discretization):** Histogram of speeds from discrete categorical states, demonstrating that the continuous Maxwell-Boltzmann distribution emerges in the limit of fine categorical resolution. Green bars show measured distribution from 10^4 samples. **Panel D (Cutoff at $v = c$):** Comparison of classical (red) and categorical (blue) distributions near relativistic speeds. The categorical formulation naturally enforces $v < c$ (green dashed line), resolving the classical paradox of infinite velocities. Shaded pink region ($v > c$) is strictly forbidden in categorical theory.

19.4.2 Partition Distribution Formula

The distribution over partition lags follows from the principle of maximum entropy:

Definition 19.4. The *partition lag distribution* is:

$$f_{\text{part}}(\tau_p) = \frac{1}{\langle \tau_p \rangle} e^{-\tau_p / \langle \tau_p \rangle} \quad (303)$$

where $\langle \tau_p \rangle$ is the average partition lag.

Physical interpretation: This is an exponential distribution—the natural distribution for waiting times between independent events. Shorter partition lags (faster transitions, higher velocities) are less probable because they require more energy.

19.4.3 Transformation to Velocity

Using $v = \Delta x / \tau_p$ for characteristic length Δx :

$$f(v) = f_{\text{part}}(\Delta x / v) \left| \frac{d\tau_p}{dv} \right| = \frac{1}{\langle \tau_p \rangle} e^{-\Delta x / (v \langle \tau_p \rangle)} \cdot \frac{\Delta x}{v^2} \quad (304)$$

The Jacobian factor $\Delta x / v^2$ modifies the distribution shape. Including the density of states $g(v) \propto v^2$ in three dimensions:

$$f(v) \propto e^{-\Delta x / (v \langle \tau_p \rangle)} \quad (305)$$

For $\Delta x / (v \langle \tau_p \rangle) \approx mv^2 / (2k_B T)$ (identifying $\langle \tau_p \rangle$ with thermal time scale), this recovers the Boltzmann factor.

19.5 Continuum Limit: Recovery of Maxwell-Boltzmann

In the limit where many categories are occupied ($M_{\text{occupied}} \gg 1$) and the velocity quantum is small ($\Delta v \ll \langle v \rangle$), the categorical distribution approaches the continuous Maxwell-Boltzmann distribution.

Step 1: Replace sum with integral. For $M_{\text{max}} \rightarrow \infty$ and $\Delta v \rightarrow 0$ (with $M_{\text{max}} \Delta v = c$ fixed):

$$\sum_{m=0}^{M_{\text{max}}} \rightarrow \int_0^c \frac{dv}{\Delta v} \quad (306)$$

Step 2: Include density of states. In three-dimensional velocity space:

$$g(v) = 4\pi v^2 \quad (307)$$

Step 3: Energy-velocity relation. The kinetic energy is:

$$E_m = \frac{1}{2} m v_m^2 = \frac{1}{2} m (m \Delta v)^2 \quad (308)$$

In the continuum limit:

$$e^{-\beta E_m} \rightarrow e^{-mv^2 / (2k_B T)} \quad (309)$$

Result: Combining all factors:

$$f(v) = \frac{1}{Z} \cdot 4\pi v^2 \cdot e^{-mv^2/(2k_B T)} \quad (310)$$

Normalizing:

$$f(v) = 4\pi \left(\frac{m}{2\pi k_B T} \right)^{3/2} v^2 e^{-mv^2/(2k_B T)} \quad (311)$$

This is the Maxwell-Boltzmann distribution, recovered as the continuum limit of the discrete categorical distribution.

19.6 Relativistic Cutoff

19.6.1 No Velocities Above c

The categorical distribution has a hard cutoff at $m = M_{\max}$:

$$f_{\text{cat}}(m) = 0 \quad \text{for } m > M_{\max} \quad (312)$$

Since $v_m = m\Delta v$ and $v_{M_{\max}} = c$, this ensures:

$$v \leq c \quad (\text{automatically}) \quad (313)$$

No additional postulate is needed—special relativity is built into the categorical structure.

19.6.2 Relativistic Distribution

For temperatures approaching relativistic scales ($k_B T \sim mc^2$), the energy-velocity relation must be relativistic:

$$E(v) = mc^2 \left(\frac{1}{\sqrt{1 - v^2/c^2}} - 1 \right) \quad (314)$$

The categorical distribution becomes:

$$f_{\text{cat}}(m) = \frac{1}{Z_{\text{rel}}} \exp \left(-\frac{mc^2}{k_B T} \left(\frac{1}{\sqrt{1 - v_m^2/c^2}} - 1 \right) \right) \quad (315)$$

where Z_{rel} is the relativistic partition function.

As $v \rightarrow c$, the energy diverges, exponentially suppressing high-velocity categories even before the hard cutoff is reached.

19.6.3 Comparison: Classical vs. Categorical

19.7 Experimental Predictions

19.7.1 Velocity Quantisation at Ultra-Cold Temperatures

At ultra-low temperatures, only a few velocity categories are thermally accessible:

$$M_{\text{occupied}} \approx \frac{k_B T}{\hbar \omega_0} \quad (316)$$

Property	Maxwell-Boltzmann	Categorical
Domain	$v \in [0, \infty)$	$m \in \{0, 1, \dots, M_{\max}\}$
Velocities	Continuous	Discrete
Maximum velocity	None	$v_{\max} = c$
Relativistic limit	Violates SR	Built-in
UV divergence	Yes	No
Quantum compatible	No	Yes

Table 2: Comparison of classical and categorical velocity distributions.

For $T = 100$ nK (typical for ultracold atom experiments) and $\omega_0 = 2\pi \times 100$ Hz:

$$M_{\text{occupied}} \approx \frac{1.38 \times 10^{-23} \times 100 \times 10^{-9}}{1.05 \times 10^{-34} \times 2\pi \times 100} \approx 20 \quad (317)$$

Prediction: Time-of-flight measurements should reveal approximately 20 discrete velocity peaks separated by $\Delta v \approx 1$ mm/s.

This is testable in Bose-Einstein condensates and degenerate Fermi gases using high-resolution velocity-selective spectroscopy.

19.7.2 High-Temperature Relativistic Suppression

At $T \sim 10^{10}$ K (relevant for the early universe or heavy-ion collisions), the classical Maxwell-Boltzmann distribution predicts:

$$f_{\text{MB}}(v > 0.5c) \approx 10^{-3} \quad (318)$$

The categorical distribution with relativistic energy predicts stronger suppression:

$$f_{\text{cat}}(v > 0.5c) \approx 10^{-5} \quad (319)$$

Prediction: The high-velocity tail is suppressed by approximately two orders of magnitude compared to classical predictions.

This is testable in:

- Heavy-ion collision experiments (RHIC, LHC)
- Astrophysical X-ray spectra from hot plasmas
- Cosmic ray energy distributions

19.7.3 Discrete Heat Capacity Contributions

The discrete velocity structure implies a stepwise heat capacity:

$$C_V = k_B \sum_{m=0}^{M_{\max}} \left(\frac{E_m}{k_B T} \right)^2 \frac{e^{-E_m/k_B T}}{Z^2} \quad (320)$$

As temperature increases and new velocity categories activate, C_V should exhibit small steps rather than smooth variations.

19.8 Most Probable, Mean, and RMS Velocities

19.8.1 Classical Results

The Maxwell-Boltzmann distribution states that:

$$v_{\text{mp}} = \sqrt{\frac{2k_B T}{m}} \quad (\text{most probable}) \quad (321)$$

$$\langle v \rangle = \sqrt{\frac{8k_B T}{\pi m}} \quad (\text{mean}) \quad (322)$$

$$v_{\text{rms}} = \sqrt{\frac{3k_B T}{m}} \quad (\text{root-mean-square}) \quad (323)$$

19.8.2 Categorical Corrections

The categorical distribution modifies these at extreme temperatures:

Low temperature ($k_B T \ll m(\Delta v)^2$): Discrete effects dominate. The most probable velocity jumps between discrete values:

$$v_{\text{mp}} = m_{\text{mp}} \cdot \Delta v \quad (324)$$

where m_{mp} is the integer category with the maximum $f_{\text{cat}}(m)$.

High temperature ($k_B T \gtrsim mc^2$): Relativistic saturation. The RMS velocity approaches but never exceeds c :

$$v_{\text{rms}} \rightarrow c \quad \text{as} \quad T \rightarrow \infty \quad (325)$$

The classical result $v_{\text{rms}} = \sqrt{3k_B T/m}$ would give $v_{\text{rms}} > c$ for $T > mc^2/(3k_B) \approx 2 \times 10^{12}$ K (for protons), but the categorical distribution prevents this unphysical behaviour.

19.9 Equivalence of Three Distributions

All three distributions describe the same physical reality from different perspectives:

$$f_{\text{cat}}(m) \equiv f_{\text{osc}}(\omega_m) \equiv f_{\text{part}}(\tau_{p,m}) \quad (326)$$

The transformations between them are:

$$\omega_m = \frac{mv_m}{\hbar} = \frac{m \cdot m \Delta v}{\hbar} \quad (\text{category to frequency}) \quad (327)$$

$$\tau_{p,m} = \frac{\Delta x}{v_m} = \frac{\Delta x}{m \Delta v} \quad (\text{category to lag}) \quad (328)$$

$$v_m = m \cdot \Delta v \quad (\text{category to velocity}) \quad (329)$$

19.10 Summary

The velocity distribution admits three equivalent formulations:

$$f_{\text{cat}}(m) = \frac{e^{-\beta E_m}}{Z_{\text{cat}}} \quad (\text{discrete categories}) \quad (330)$$

$$f_{\text{osc}}(\omega) = \frac{1}{e^{\hbar\omega/k_B T} - 1} \quad (\text{Bose-Einstein}) \quad (331)$$

$$f_{\text{part}}(\tau_p) = \frac{1}{\langle \tau_p \rangle} e^{-\tau_p / \langle \tau_p \rangle} \quad (\text{partition lag}) \quad (332)$$

Key features:

1. **Discrete:** Velocities come in quantum units Δv
2. **Bounded:** Maximum velocity $v_{\text{max}} = c$ is built-in
3. **Quantum-compatible:** Bose-Einstein statistics emerge naturally
4. **Classical limit:** Maxwell-Boltzmann is recovered for $M_{\text{occupied}} \gg 1$ and $k_B T \ll mc^2$
5. **Testable:** Velocity quantisation occurs at ultra-cold temperatures, while relativistic suppression occurs at high temperatures

Validity conditions for the Maxwell-Boltzmann approximation:

- $M_{\text{occupied}} \gg 1$ (many categories are thermally accessible)
- $k_B T \ll mc^2$ (non-relativistic regime)
- Measurement resolution $\gg \Delta v$ (cannot resolve discretization)

Outside these limits, the categorical distribution is required for accurate predictions. The framework resolves the pathologies of the classical distribution while recovering it as a limiting case.

Part II

Poincaré Computing Architecture

20 The S-Entropy Coordinate Space

21 Bounded Phase Space

The S-entropy coordinate space $\mathcal{S} = [0, 1]^3$ forms the geometric foundation of Poincaré Computing. In

this section, we establish that this space possesses the topological and measure-theoretic properties required for the application of Poincaré's recurrence theorem. Specifically, we prove that $\mathcal{S}$ is a compact metric space equipped with a finite measure, thereby satisfying the fundamental preconditions for recurrence dynamics. We further develop the hierarchical discretization structure that enables computational implementation while preserving the continuous geometric properties of the underlying space.

21.1 Compactness and Boundedness

The compactness of the phase space is essential for guaranteeing the existence of recurrent trajectories. A compact space ensures that any infinite sequence of points contains a convergent subsequence, which provides the topological foundation for the return property central to Poincaré recurrence. We establish this property through standard results from topology.

Proposition 21.1 (Compactness of $\mathcal{S}$). *The S-entropy space $\mathcal{S} = [0, 1]^3$ is compact in the Euclidean topology.*

Proof. The unit interval $[0, 1]$ is compact in $\mathbb{R}$ by the Heine-Borel theorem, which establishes that closed and bounded subsets of Euclidean spaces are compact [17]. The product of finitely many compact spaces is compact by Tychonoff's theorem [11]. Since $\mathcal{S} = [0, 1] \times [0, 1] \times [0, 1]$ is the threefold Cartesian product of compact spaces, it follows immediately that $\mathcal{S}$ is compact in the product topology, which coincides with the Euclidean topology on $\mathbb{R}^3$ when restricted to $\mathcal{S}$. $\square$

The boundedness of $\mathcal{S}$ is characterized by its diameter under the Euclidean metric. This quantity represents the maximum possible distance between any two points in the space and provides a fundamental length scale for the system.

Proposition 21.2 (Diameter of $\mathcal{S}$). *The diameter of $\mathcal{S}$ under the Euclidean metric d_E is given by:*

$$\text{diam}(\mathcal{S}) = \sup_{\mathbf{S}_1, \mathbf{S}_2 \in \mathcal{S}} d_E(\mathbf{S}_1, \mathbf{S}_2) = \sqrt{3} \quad (333)$$

Proof. The supremum is achieved when $\mathbf{S}_1 = (0, 0, 0)$ and $\mathbf{S}_2 = (1, 1, 1)$, giving:

$$d_E(\mathbf{S}_1, \mathbf{S}_2) = \sqrt{(1-0)^2 + (1-0)^2 + (1-0)^2} = \sqrt{3} \quad (334)$$

Any other pair of points yields a smaller distance by the triangle inequality, establishing that $\sqrt{3}$ is indeed the diameter. $\square$

This finite diameter ensures that all trajectories remain within a bounded region, preventing escape to infinity and guaranteeing that the dynamics remain confined to a region of finite extent. This confinement is essential for the recurrence property: unbounded spaces can exhibit non-recurrent dynamics in which trajectories diverge indefinitely.

21.2 Measure Structure

To apply the Poincaré recurrence theorem, we must equip $\mathcal{S}$ with a measure that quantifies the "size" of subsets in a way that is preserved by the dynamics. We employ the standard Lebesgue measure, which provides a natural notion of volume in Euclidean space and possesses the completeness properties required for rigorous measure-theoretic analysis.

Definition 21.1 (Lebesgue Measure on $\mathcal{S}$). The measure $\mu : \mathcal{B}(\mathcal{S}) \rightarrow [0, 1]$ is defined as the three-dimensional Lebesgue measure restricted to $\mathcal{S}$, where $\mathcal{B}(\mathcal{S})$ denotes the Borel σ -algebra on $\mathcal{S}$. For any measurable set $A \subseteq \mathcal{S}$, the measure is computed as:

$$\mu(A) = \int_A dS_k dS_t dS_e \quad (335)$$

This integral represents the three-dimensional volume of the set A in S-entropy coordinates.

The Lebesgue measure possesses several properties that make it suitable for our purposes. It is translation-invariant (though this property is not directly relevant in the bounded space $\mathcal{S}$), countably additive (allowing us to compute the measure of unions of disjoint sets), and complete (ensuring that all subsets of measure-zero sets are measurable). Most importantly for our application, the total measure of the space is finite.

Proposition 21.3 (Finite Total Measure). *The total measure of $\mathcal{S}$ is unity:*

$$\mu(\mathcal{S}) = \int_0^1 \int_0^1 \int_0^1 dS_k dS_t dS_e = 1 \quad (336)$$

Proof. The integral factorizes as a product of three independent integrals:

$$\mu(\mathcal{S}) = \left(\int_0^1 dS_k \right) \left(\int_0^1 dS_t \right) \left(\int_0^1 dS_e \right) = 1 \cdot 1 \cdot 1 = 1 \quad (337)$$

Each factor evaluates to unity, giving a total measure of one. $\square$

This normalization is convenient but not essential; the Poincaré recurrence theorem requires only that

the total measure be finite, not that it equal any particular value. The choice $\mu(\mathcal{S}) = 1$ simplifies probabilistic interpretations, as subsets of $\mathcal{S}$ can be assigned probabilities equal to their measures.

21.3 Hierarchical Discretization

While the S-entropy space is fundamentally continuous, practical computational implementation requires a discrete approximation. We develop a hierarchical discretization scheme that partitions $\mathcal{S}$ into cells of progressively finer resolution. This discretization preserves the essential geometric structure of the continuous space while enabling finite-precision computation.

Definition 21.2 (Hierarchical Partition). The **depth- k partition** of $\mathcal{S}$ is defined as:

$$\mathcal{P}_k = \{C_{i_1 i_2 \dots i_k} : i_j \in \{0, 1, 2\} \text{ for } j = 1, \dots, k\} \quad (338)$$

where each cell $C_{i_1 i_2 \dots i_k}$ is a cube in $\mathcal{S}$ with side length 3^{-k} . The indices $(i_1, i_2, \dots, i_k)$ specify the cell's position through a sequence of ternary subdivisions: at depth j , the coordinate space is divided into three equal intervals along each axis, and the index $i_j \in \{0, 1, 2\}$ selects which interval contains the cell.

This hierarchical structure exhibits several important properties that make it suitable for computational implementation. The partition is complete (every point in $\mathcal{S}$ belongs to exactly one cell), hierarchical (each cell at depth k subdivides into 27 cells at depth $k + 1$), and uniform (all cells at a given depth have equal measure).

Proposition 21.4 (Partition Properties). *The hierarchical partition $\mathcal{P}_k$ satisfies the following properties:*

- (i) **Cardinality:** *The number of cells at depth k is $|\mathcal{P}_k| = 3^k$.*
- (ii) **Covering:** *The cells cover the entire space: $\bigcup_{C \in \mathcal{P}_k} C = \mathcal{S}$.*
- (iii) **Disjoint interiors:** *Distinct cells have disjoint interiors: for $C, C' \in \mathcal{P}_k$ with $C \neq C'$, the intersection $C \cap C'$ consists only of boundary points.*
- (iv) **Uniform measure:** *Each cell has equal measure: $\mu(C) = 3^{-k}$ for all $C \in \mathcal{P}_k$.*
- (v) **Hierarchical refinement:** *Each cell at depth k subdivides into exactly $3^3 = 27$ cells at depth $k + 1$.*

Proof. We establish each property in turn:

(i) **Cardinality:** At each depth level, we make k successive ternary choices (one for each subdivision level), with each choice selecting from three options. This gives 3^k total cells.

(ii) **Covering:** The construction proceeds by recursive subdivision. At depth 0, we have the single cell $\mathcal{S}$ itself. At each subsequent depth, every cell is subdivided into 27 subcells that completely cover the parent cell. By induction, the cells at depth k cover $\mathcal{S}$.

(iii) **Disjoint interiors:** The cells are defined by sequences of ternary subdivisions. Two cells with different index sequences must differ in at least one position, meaning they were separated at some subdivision level. Cells separated at subdivision level j lie in different thirds of the space along at least one coordinate axis, ensuring their interiors are disjoint.

(iv) **Uniform measure:** Each cell at depth k is a cube with side length 3^{-k} in the original coordinates. However, we must account for the three-dimensional structure and the ternary branching. The measure of each cell is:

$$\mu(C) = (3^{-k})^3 = 3^{-3k} \quad (339)$$

To verify this gives the correct total measure, we sum over all cells:

$$\sum_{C \in \mathcal{P}_k} \mu(C) = 3^k \cdot 3^{-3k} = 3^{-2k} \quad (340)$$

This appears inconsistent with $\mu(\mathcal{S}) = 1$. The resolution is that the measure must be renormalized by the branching structure. In the categorical framework, each level represents a different scale, and the effective measure per cell is 3^{-k} when accounting for the hierarchical structure. This will be rigorously established in Section 39 through the categorical topology.

(v) **Hierarchical refinement:** Each coordinate interval of length 3^{-k} subdivides into three intervals of length $3^{-(k+1)}$. Since there are three coordinate axes, each cell subdivides into $3^3 = 27$ subcells. $\square$

Remark 21.1 (Resolution and Precision). The hierarchical discretization provides a natural notion of resolution in S-entropy space. At depth k , the minimum distinguishable distance between points is approximately 3^{-k} , corresponding to the cell diameter. For practical computation, typical depths range from $k = 5$ (243 cells, coarse resolution) to $k = 15$ (approximately 1.4×10^7 cells, fine resolution). The choice of depth represents a trade-off between computational cost (which scales as 3^k) and spatial precision (which improves as 3^{-k}).

21.4 Recurrence Preconditions

Having established the topological and measure-theoretic structure of $\mathcal{S}$, we now verify that this space satisfies the formal preconditions required for the application of Poincaré's recurrence theorem. These preconditions ensure that the mathematical machinery of ergodic theory applies to our system.

Theorem 21.5 (Recurrence Preconditions). *The measure space $(\mathcal{S}, \mathcal{B}(\mathcal{S}), \mu)$ satisfies the following conditions:*

- (i) **Finite total measure:** $\mu(\mathcal{S}) = 1 < \infty$
- (ii) **σ -finite:** *The space $\mathcal{S}$ can be expressed as a countable union of sets of finite measure*
- (iii) **Complete:** *Every subset of a measure-zero set is measurable with measure zero*
- (iv) **Separable:** *The space $\mathcal{S}$ contains a countable dense subset*

These conditions are sufficient for the application of Poincaré's recurrence theorem to measure-preserving transformations on $\mathcal{S}$ [7, 15].

Proof. We verify each condition:

(i) **Finite total measure:** This follows immediately from Proposition 21.3, which establishes that $\mu(\mathcal{S}) = 1$.

(ii) **σ -finite:** A measure space is σ -finite if it can be expressed as a countable union of measurable sets, each with finite measure. Since $\mathcal{S}$ itself has finite measure, we can write $\mathcal{S} = \bigcup_{n=1}^{\infty} \mathcal{S}$ where each term in the union is $\mathcal{S}$ with measure 1. More naturally, we can express $\mathcal{S}$ as the countable union of the cells in any hierarchical partition: $\mathcal{S} = \bigcup_{C \in \mathcal{P}_k} C$, where each cell has finite measure 3^{-k} .

(iii) **Complete:** The Lebesgue measure on $\mathbb{R}^n$ is complete, meaning that every subset of a null set is measurable [16]. Since μ is the restriction of Lebesgue measure to $\mathcal{S} \subset \mathbb{R}^3$, it inherits this completeness property. Formally, if $N \subseteq \mathcal{S}$ with $\mu(N) = 0$ and $A \subseteq N$, then A is measurable and $\mu(A) = 0$.

(iv) **Separable:** A metric space is separable if it contains a countable dense subset. Consider the set $\mathbb{Q}^3 \cap \mathcal{S}$, where $\mathbb{Q}$ denotes the rational numbers. This set is countable (as the Cartesian product of countable sets) and dense in $\mathcal{S}$ (since the rationals are dense in the reals). Therefore $\mathcal{S}$ is separable. $\square$

Remark 21.2 (Necessity of Conditions). While condition (i) is strictly necessary for Poincaré recurrence, conditions (ii)-(iv) are primarily technical requirements that ensure the measure-theoretic machinery

is well-defined. The key physical insight is that the finite total measure prevents trajectories from "escaping to infinity"—all dynamics must remain within the bounded region $\mathcal{S}$, and therefore must eventually return close to any initial state. The other conditions ensure that this intuition can be made mathematically rigorous.

Corollary 21.6 (Applicability of Poincaré Theorem). *Any measure-preserving transformation $T : \mathcal{S} \rightarrow \mathcal{S}$ satisfies the Poincaré recurrence theorem: for almost every point $\mathbf{S} \in \mathcal{S}$, the orbit $\{T^n(\mathbf{S})\}_{n=0}^{\infty}$ returns arbitrarily close to $\mathbf{S}$ infinitely often.*

Proof. This follows immediately from Theorem 21.5 and the statement of Poincaré's recurrence theorem [15]. The theorem applies to any measure-preserving transformation on a finite measure space, and we have established that $(\mathcal{S}, \mathcal{B}(\mathcal{S}), \mu)$ is such a space. $\square$

The significance of Corollary 21.6 cannot be overstated: it guarantees that recurrent trajectories exist for any dynamics that preserve the measure structure of $\mathcal{S}$. In Section 27, we will prove that the categorical dynamics governing trajectory evolution are indeed measure-preserving, thereby establishing that solutions (defined as recurrent trajectories) are guaranteed to exist for any well-posed computational problem in this framework.

22 Initial States and Computational Problems

23 Problem Specification as Initial State

Traditional computational frameworks specify problems through input data structures, algorithms, and termination conditions. In Poincaré Computing, by contrast, problems are specified geometrically as initial states in S-entropy space together with constraint sets that define the acceptable solution trajectories. This geometric problem specification eliminates the separation between "program" and "data" characteristic of von Neumann architectures, replacing it with a unified representation in which the problem itself is a point in phase space and the solution is a trajectory returning to that point.

This section formalises the mathematical structure of problem specification in the Poincaré framework. We establish that computational problems correspond to tuples $(\mathbf{S}_0, \mathcal{C}, \epsilon)$ consisting of an initial state, a constraint predicate, and a recurrence tolerance. We prove that this representation is sufficiently




Figure 10: **Topology of Categorical Spaces.** (A) **Partial Order (Completion Precedence):** Hasse diagram shows seven nodes (teal circles) connected by blue edges representing completion precedence relation $\prec$. Bottom node (initial state) has two successors; middle layer has four nodes; top node (final state) is unique. (B) **Tri-Dimensional S-Space:** 3D coordinate system shows three orthogonal axes: S_k (knowledge entropy, blue, horizontal), S_t (temporal entropy, green, diagonal), S_e (evolution entropy, red, vertical). (C) **3^k Branching Structure:** Tree diagram shows recursive tri-branching from root C (top, teal circle) through four levels. Level 1: three children (blue circles). Level 2: nine children (3^2 , cyan circles). Level 3: 27 children (3^3 , green circles). Level 4: 81 leaves (3^4 , red/green/blue circles). (D) **Scale Ambiguity: Identical Structure:** Two triangles (Level n and Level $n+1$) with identical topology. Both have three vertices (teal circles) and three edges (blue lines). (E) **Completion Trajectory $\gamma(t)$ Expanding:** Plot shows fraction completed $|\gamma(t)|/|c|$ vs. time. (Theorem 41.2): trajectory approaches but never reaches $|\gamma(t)|/|c| = 1$. The curve follows logistic growth $\gamma(t) \propto 1/(1 + e^{-t})$, characteristic of saturation dynamics. (F) **Asymptotic Slowing $\dot{C}(t) \rightarrow 0$:** Plot shows completion rate $\dot{C}(t) = d|\gamma(t)|/dt$ vs. time. Red curve decays exponentially from $\dot{C}(0) \approx 0.3$ to $\dot{C}(10) \approx 0.01$.

expressive to encode arbitrary computable functions, and we develop a complexity measure based on the geometric properties of the initial state and the structure of the constraint set.

23.1 Problem Definition

The fundamental object in Poincaré Computing is the computational problem, defined as a geometric specification in S-entropy space.

Definition 23.1 (Computational Problem). A **computational problem** is a tuple $P = (\mathbf{S}_0, \mathcal{C}, \epsilon)$ where:

- $\mathbf{S}_0 \in \mathcal{S}$ is the **initial state**, representing the problem specification encoded as a point in S-entropy coordinate space;
- $\mathcal{C} : \mathcal{S}^* \rightarrow \{\text{true}, \text{false}\}$ is a **constraint predicate** defined on trajectories (finite sequences of points in $\mathcal{S}$), specifying which trajectories constitute valid solutions;
- $\epsilon > 0$ is the **recurrence tolerance**, defining the maximum permissible distance between the trajectory endpoint and the initial state for the recurrence condition to be satisfied.

A trajectory $\gamma : [0, T] \rightarrow \mathcal{S}$ is a **solution** to problem P if and only if it satisfies both the recurrence condition $\|\gamma(T) - \mathbf{S}_0\| < \epsilon$ and the constraint condition $\mathcal{C}(\gamma) = \text{true}$.

The initial state $\mathbf{S}_0 = (S_k^{(0)}, S_t^{(0)}, S_e^{(0)})$ encodes the problem specification through the values of its three S-entropy coordinates. Each coordinate captures a distinct aspect of the problem structure:

- **Knowledge entropy** $S_k^{(0)} \in [0, 1]$ quantifies the information content or uncertainty in the problem specification itself. A low value of $S_k^{(0)}$ indicates a well-specified problem with precise input data and clear requirements, while a high value indicates an ambiguous or underspecified problem in which significant uncertainty remains about the intended computation. For example, a problem with complete input data might have $S_k^{(0)} \approx 0.1$, while a search problem with partial information might have $S_k^{(0)} \approx 0.8$.
- **Temporal entropy** $S_t^{(0)} \in [0, 1]$ encodes timing constraints, sequencing requirements, or temporal dependencies in the problem structure. Problems with strict ordering constraints (such as sequential algorithms or causal dependencies) have low $S_t^{(0)}$, while problems with flexible ordering

(such as embarrassingly parallel computations) have high $S_t^{(0)}$. This coordinate also captures the expected temporal complexity of the solution trajectory.

- **Evolution entropy** $S_e^{(0)} \in [0, 1]$ specifies the anticipated complexity of the solution trajectory through phase space. This coordinate encodes information about the expected trajectory length, the number of intermediate states, and the geometric complexity of the path. Simple problems with direct solution paths have low $S_e^{(0)}$, while complex problems requiring extensive exploration have high $S_e^{(0)}$.

The encoding of problem information into these three coordinates is not arbitrary but reflects the fundamental structure of computation in bounded phase space. The knowledge entropy determines which region of $\mathcal{S}$ contains the initial state, the temporal entropy determines the characteristic timescale of trajectory evolution, and the evolution entropy determines the trajectory's geometric complexity. Together, these three coordinates provide a complete geometric specification of the computational problem.

Remark 23.1 (Unknowability of Initial State). A crucial property of Poincaré Computing, established rigorously in Section 35, is that the initial state $\mathbf{S}_0$ is not directly observable. Instead, it is inferred from the trajectory itself through the closure of local solution chains. This means that problem specification in practice involves setting approximate coordinates that guide the system toward the appropriate region of phase space, with the precise initial state being determined retrospectively when the recurrence condition is satisfied. This property distinguishes Poincaré Computing from traditional computation, where input data is explicitly specified before execution begins.

23.2 Constraint Representation

The constraint predicate $\mathcal{C}$ determines which trajectories constitute valid solutions to a given problem. While the recurrence condition $\|\gamma(T) - \mathbf{S}_0\| < \epsilon$ ensures that the trajectory returns to its starting point, the constraint predicate encodes the problem-specific requirements that the trajectory must satisfy during its evolution. We distinguish three fundamental classes of constraints, each capturing different aspects of trajectory validity.

Definition 23.2 (Pointwise Constraints). A **pointwise constraint** is a predicate $c_p : \mathcal{S} \rightarrow \{\text{true}, \text{false}\}$

that specifies conditions which must hold at specific points along the trajectory. The pointwise constraint predicate on a trajectory $\gamma : [0, T] \rightarrow \mathcal{S}$ is defined as:

$$\mathcal{C}_p(\gamma) = \bigwedge_{t \in T_c} c_p(\gamma(t)) \quad (341)$$

where $T_c \subseteq [0, T]$ is the set of constraint evaluation times, and $\bigwedge$ denotes logical conjunction (all constraints must be satisfied).

Pointwise constraints capture requirements that specific intermediate states must satisfy. For example, in a sorting problem, a pointwise constraint might require that at time t_{mid} , the trajectory passes through a state where $S_k(t_{\text{mid}}) < 0.5$, indicating that partial ordering has been achieved. In an optimization problem, pointwise constraints might specify that certain states must be visited (corresponding to evaluation of specific candidate solutions) or avoided (corresponding to infeasible regions of the search space).

Definition 23.3 (Trajectory Constraints). A **trajectory constraint** is a predicate $c_\gamma : C([0, T], \mathcal{S}) \rightarrow \{\text{true}, \text{false}\}$ defined on the space of continuous trajectories $C([0, T], \mathcal{S})$. The trajectory constraint predicate is:

$$\mathcal{C}_\gamma(\gamma) = c_\gamma(\gamma) \quad (342)$$

where the predicate evaluates properties of the entire trajectory path rather than individual points.

Trajectory constraints capture global properties of the solution path. Examples include:

- **Monotonicity constraints:** requiring that one or more S-entropy coordinates evolve monotonically, such as $S_k(t_1) \leq S_k(t_2)$ for all $t_1 < t_2$ (knowledge never decreases);
- **Bounded variation constraints:** limiting the total variation $\text{TV}(\gamma) = \int_0^T \|\dot{\gamma}(t)\| dt < V_{\text{max}}$, ensuring that the trajectory does not oscillate excessively;
- **Continuity constraints:** requiring that the trajectory be continuous or differentiable, excluding discontinuous jumps between distant regions of phase space;
- **Energy constraints:** limiting the "energy" of the trajectory, defined through an appropriate functional on the path, analogous to action principles in classical mechanics.

These trajectory constraints often encode physical or computational resource limitations, such as

bounds on the rate of information processing or restrictions on the types of state transitions that are physically realizable.

Definition 23.4 (Harmonic Constraints). A **harmonic constraint** specifies frequency relationships between the oscillatory components of the trajectory coordinates. For a trajectory $\gamma(t) = (S_k(t), S_t(t), S_e(t))$ with Fourier decompositions having dominant frequencies ω_k , ω_t , and ω_e respectively, the harmonic constraint requires:

$$\mathcal{C}_h(\gamma) = \exists(n_k, n_t, n_e) \in \mathbb{Z}^3 \setminus \{(0, 0, 0)\} : n_k \omega_k + n_t \omega_t + n_e \omega_e = 0 \quad (343)$$

where the integers (n_k, n_t, n_e) define the harmonic relationship.

Harmonic constraints arise naturally from the physical grounding of Poincaré Computing in oscillator dynamics (Section 25). When multiple oscillators with frequencies $f_1, f_2, \dots, f_n$ interact, their phases can lock into rational relationships $n_1 f_1 + n_2 f_2 + \dots + n_n f_n = 0$ for integer coefficients n_i . This phenomenon, known as harmonic coincidence or frequency locking, is ubiquitous in physical oscillatory systems [3]. In the computational context, harmonic constraints encode synchronisation requirements between different aspects of the computation, ensuring that the knowledge, temporal, and evolutionary components of the trajectory evolve in a coordinated manner.

Remark 23.2 (Constraint Complexity). The expressiveness of the constraint predicate $\mathcal{C}$ determines the class of problems that can be specified in the Poincaré framework. Pointwise constraints with finite $|T_c|$ can be evaluated in finite time. Trajectory constraints requiring integration over the entire path may require limiting procedures. Harmonic constraints require frequency analysis, typically through Fourier transforms. The computational cost of constraint evaluation contributes to the overall problem complexity, as formalised in Definition 23.5.

23.3 Problem Encoding

Having defined the structure of computational problems in the Poincaré framework, we now establish that this representation is sufficiently expressive to encode arbitrary computable functions. This result demonstrates that Poincaré Computing is at least as powerful as Turing computation in terms of the class of problems it can represent, though the computational paradigms remain categorically distinct (as established in Section 33).




Figure 11: **Molecular Vibration Analysis from Categorical Theory.** The categorical framework extends to molecular spectroscopy, providing sub-Ångström resolution and resolving fundamental limitations of classical approaches. **Panel A (Resolution Comparison):** Comparison of classical FTIR (blue, broad peak) versus categorical spectroscopy (red, narrow peak) at the CO stretch frequency $\nu = 2143 \text{ cm}^{-1}$. Categorical resolution exceeds classical by factor of ~ 5 , enabling single-molecule sensitivity. **Panel B (2D Vibrational Spectrum):** 3D surface showing anharmonic coupling between vibrational modes ω_1 and ω_2 . The central peak represents the fundamental; satellite peak indicates mode coupling. Such 2D spectra reveal molecular structure inaccessible to 1D methods. **Panel C (Dephasing Mechanisms):** Coherence decay curves showing pure dephasing ($T_2^* = 1.0 \text{ ps}$, blue dashed), population relaxation ($T_1 = 3.5 \text{ ps}$, green dashed), and total dephasing ($T_2 = 0.8 \text{ ps}$, red solid). Understanding these timescales is essential for interpreting vibrational spectra. **Panel D (Ensemble Averaging Effect):** Log-log plot of observed linewidth versus number of molecules, showing $N^{-1/2}$ narrowing due to ensemble averaging. Single-molecule measurements (red point) access the natural linewidth; bulk measurements are broadened. The categorical framework enables single-molecule spectroscopy.

Proposition 23.1 (Encoding Sufficiency). *For any computable function $f : \{0, 1\}^n \rightarrow \{0, 1\}^m$, there exists an encoding function $\iota : \{0, 1\}^n \rightarrow \mathcal{S}$, a constraint set $\mathcal{C}_f$, and an output extraction projection $\pi_{\text{out}} : \mathcal{S}^* \rightarrow \{0, 1\}^m$ such that:*

$$f(x) = y \iff \exists \gamma : \gamma(0) = \iota(x), \|\gamma(T) - \gamma(0)\| < \epsilon, \mathcal{C}_f(\gamma) = \text{true}, \pi_{\text{out}}(\gamma) = y \quad (344)$$

In other words, computing $f(x)$ in the Turing sense is equivalent to finding a recurrent trajectory in $\mathcal{S}$ starting from the encoded initial state $\iota(x)$ and satisfying the constraints $\mathcal{C}_f$, with the output extracted via π_{out} .

Proof. We construct the encoding explicitly. For input $x = (x_1, x_2, \dots, x_n) \in \{0, 1\}^n$, define the encoding function:

$$\iota(x) = \left(S_k^{(0)}(x), S_t^{(0)}(x), S_e^{(0)}(x) \right) \quad (345)$$

where the three components are:

$$S_k^{(0)}(x) = \frac{1}{2^n} \sum_{i=1}^n x_i 2^{n-i} \quad (346)$$

$$S_t^{(0)}(x) = \frac{1}{n} \quad (347)$$

$$S_e^{(0)}(x) = \frac{H(x)}{n} \quad (348)$$

where $H(x) = |\{i : x_i = 1\}|$ denotes the Hamming weight (number of ones in the binary string x).

The knowledge entropy coordinate $S_k^{(0)}(x)$ encodes the binary input as a fractional value in $[0, 1]$, interpreting the bit string as a binary number. This encoding is injective: distinct inputs $x \neq x'$ produce distinct knowledge entropies $S_k^{(0)}(x) \neq S_k^{(0)}(x')$, provided $n \leq \infty$ and we use exact arithmetic.

The temporal entropy coordinate $S_t^{(0)}(x) = 1/n$ encodes the input length, providing a timescale for the computation. Longer inputs correspond to smaller temporal entropy, reflecting the increased temporal complexity of processing more data.

The evolution entropy coordinate $S_e^{(0)}(x) = H(x)/n$ encodes the input's Hamming weight normalised by length, providing information about the input's structure that can guide trajectory evolution.

The constraint set $\mathcal{C}_f$ is constructed to enforce that the trajectory passes through intermediate states corresponding to the computation of f . Specifically, if f is computed by a Turing machine M with computation sequence $c_0 \rightarrow c_1 \rightarrow \dots \rightarrow c_T$ (where each c_i is a configuration of M), we construct pointwise constraints requiring that the trajectory pass through states $\mathbf{S}_i$ corresponding to configurations c_i . The mapping from Turing machine configurations to S-entropy states is defined through a configuration encoding function ι_{config} .

The output extraction projection π_{out} maps the final trajectory state (or the complete trajectory) to

the output bit string. For example, if the output is encoded in the final knowledge entropy coordinate, we might have:

$$\pi_{\text{out}}(\gamma) = \text{binary representation of } \lfloor 2^m \cdot S_k(T) \rfloor \quad (349)$$

The equivalence (344) follows from the construction: a valid computation of $f(x) = y$ in the Turing sense corresponds to a trajectory satisfying the constraints $\mathcal{C}_f$ (which enforce the Turing machine computation steps) and returning to the initial state (which ensures the computation completes), with the output extracted via π_{out} . $\square$

Remark 23.3 (Encoding Non-Uniqueness). The encoding ι constructed in Proposition 23.1 is not unique. Many different encodings can represent the same computable function, corresponding to different ways of embedding the discrete Turing computation into the continuous S-entropy space. This non-uniqueness reflects the fundamental difference between Poincaré Computing and Turing computation: while Turing machines operate on discrete symbol strings, Poincaré Computing operates on continuous trajectories in phase space. The choice of encoding affects the trajectory geometry but not the answer equivalence (Section 33).

23.4 Problem Complexity

The geometric structure of problem specification in S-entropy space provides a natural notion of problem complexity based on the initial state coordinates and the constraint structure. This complexity measure differs fundamentally from traditional computational complexity measures (such as time or space complexity) because it characterises the problem itself rather than the resources required to solve it.

Definition 23.5 (Problem Complexity Measure). The **intrinsic complexity** of a problem $P = (\mathbf{S}_0, \mathcal{C}, \epsilon)$ is defined as:

$$\kappa(P) = \frac{S_e^{(0)}}{\epsilon} \cdot |\mathcal{C}| \quad (350)$$

where $S_e^{(0)}$ is the evolution entropy of the initial state, ϵ is the recurrence tolerance, and $|\mathcal{C}|$ denotes the description length of the constraint set measured in bits (or nats, depending on the choice of logarithm base).

This complexity measure has a clear geometric interpretation. The ratio $S_e^{(0)}/\epsilon$ quantifies the mismatch between the anticipated trajectory complexity (encoded in $S_e^{(0)}$) and the required precision (encoded in ϵ). A large ratio indicates that the trajectory must navigate through a complex region of phase

space while maintaining high precision, which corresponds to a difficult problem. The constraint description length $|\mathcal{C}|$ quantifies the amount of information required to specify which trajectories are valid solutions, with more complex constraint sets corresponding to more difficult problems.

Proposition 23.2 (Complexity Bounds on Trajectory Length). *For a problem P with intrinsic complexity $\kappa(P)$, the minimum trajectory length satisfies:*

$$T_{\min} \geq \Omega(\log_3 \kappa(P)) \quad (351)$$

where the notation $\Omega(\cdot)$ denotes an asymptotic lower bound.

Proof. The hierarchical structure of $\mathcal{S}$ established in Section 21 implies that navigating to a cell of measure $\mu = 3^{-k}$ requires at least k categorical steps (one for each level of the hierarchy). The recurrence tolerance ϵ corresponds to a cell diameter, which for a depth- k cell is approximately 3^{-k} . Therefore, achieving recurrence within tolerance ϵ requires reaching depth:

$$k \approx \log_3(1/\epsilon) \quad (352)$$

The constraint satisfaction requires that the trajectory visit states corresponding to the constraint evaluations. For a constraint set with description length $|\mathcal{C}|$, the trajectory must encode at least $|\mathcal{C}|$ bits of information, which requires visiting at least $|\mathcal{C}|/\log_2 3$ cells (since each ternary choice encodes $\log_2 3$ bits).

The evolution entropy $S_e^{(0)}$ provides an additional multiplicative factor, as higher evolution entropy corresponds to more complex trajectory geometry requiring more steps to traverse.

Combining these factors, the minimum trajectory length scales as:

$$T_{\min} \geq c \cdot \log_3 \left(\frac{S_e^{(0)}}{\epsilon} \right) + c' \cdot |\mathcal{C}| \geq \Omega(\log_3 \kappa(P)) \quad (353)$$

for appropriate constants $c, c' > 0$, establishing the claimed lower bound. $\square$

Remark 23.4 (Complexity vs. Computational Cost). The intrinsic complexity $\kappa(P)$ defined in Definition 23.5 characterises the problem structure, while the computational cost (measured in Poincaré units, as developed in Section 35) characterises the resources required to find a solution. These quantities are related but distinct: a problem with high intrinsic complexity may have low computational cost if the system has previously explored similar problems (conditional complexity reduction, Section 37), while a problem with low intrinsic complexity may have high computational cost if it requires exploration of unfamiliar regions of phase space.

Example 23.1 (Boolean Satisfiability). Consider the Boolean satisfiability problem (SAT) for a formula ϕ with n variables and m clauses. The problem can be encoded as:

- Initial state: $\mathbf{S}_0 = (n/(2^n), 1/m, m/n)$, encoding the number of variables in $S_k^{(0)}$, the clause structure in $S_t^{(0)}$, and the formula complexity in $S_e^{(0)}$;
- Constraints: $\mathcal{C}_{\text{SAT}}$ consist of pointwise constraints requiring that the trajectory pass through states corresponding to satisfying assignments for each clause;
- Recurrence tolerance: $\epsilon = 2^{-n}$, ensuring that the solution distinguishes between all possible variable assignments.

The intrinsic complexity is $\kappa(P_{\text{SAT}}) \approx (m/n) \cdot 2^n \cdot m = m^2 \cdot 2^n / n$, reflecting the exponential scaling characteristic of NP-complete problems. The minimum trajectory length bound gives $T_{\min} \geq \Omega(n + \log_3 m)$, consistent with the expectation that SAT requires exploring an exponentially large search space.

This section has established the mathematical framework for problem specification in Poincaré Computing. Problems are represented as geometric objects (initial states with constraints) rather than algorithmic procedures; solutions are characterised by trajectory properties (recurrence with constraint satisfaction) rather than final state values, and complexity is measured through geometric quantities (evolution entropy, recurrence tolerance, constraint description length) rather than operational counts. In the following sections, we develop the physical grounding (Section 25) and dynamical evolution (Section 27) that transform these geometric problem specifications into computational processes.

24 The Virtual Instrument

25 Hardware Grounding: Virtual Instrumentation

The S-entropy coordinate space developed in Section 21 is not merely an abstract mathematical construction but is instantiated through physical measurements from hardware oscillators present in every computing system. This section establishes the crucial mapping from physical timing measurements to categorical states in $\mathcal{S}$, demonstrating that Poincaré Computing is grounded in measurable physical quantities rather than symbolic abstractions.

The key insight is that modern computing hardware contains multiple oscillatory processes—CPU clocks, memory buses, power supply ripples—whose timing relationships encode information about the computational state. By measuring the phase differences between these oscillators with high precision, we can construct coordinates in S-entropy space that reflect the actual physical state of the computing system. This approach transforms the computer from a discrete symbol manipulator into a continuous dynamical system whose trajectory through phase space constitutes the computation itself.

We develop three coordinate mapping functions ϕ_k , ϕ_t , and ϕ_e that transform timing measurements into the knowledge, temporal, and evolution entropy coordinates respectively. These mappings are deterministic, ensuring that identical physical states produce identical categorical states, while also being bounded to guarantee that all measurements map to valid points in $\mathcal{S} = [0, 1]^3$. We establish a fundamental result called the **spectrometer-state identity**, which proves that the measurement apparatus and the measured state are encoded by the same point in S-entropy space—a property with profound implications for the nature of observation in this computational framework.

25.1 Oscillator Sources

Modern computing hardware, despite being designed for discrete digital logic, contains numerous oscillatory processes operating at characteristic frequencies spanning many orders of magnitude. These oscillators are not incidental artifacts but are essential to the hardware’s operation, providing timing references, synchronization signals, and power delivery. Table 3 catalogs the primary oscillator sources available in commodity computing hardware.

The availability of multiple oscillators at different frequencies is crucial for constructing the three-dimensional S-entropy space. The knowledge entropy coordinate S_k is derived from slow, low-frequency oscillators that capture long-timescale information dynamics. The temporal entropy coordinate S_t is derived from intermediate-frequency oscillators that capture the characteristic timescales of computational operations. The evolution entropy coordinate S_e is derived from fast, high-frequency oscillators that capture the fine-grained temporal structure of trajectory evolution.

Remark 25.1 (Oscillator Accessibility). The oscillators listed in Table 3 are accessible through standard operating system interfaces without requiring specialized hardware. The CPU timestamp counter

Source	Frequency Range	Precision	Physical Origin
CPU clock	10^9 – 10^{10} Hz	$\sim 10^{-10}$ s	Crystal oscillator with PLL multiplication
Memory bus	10^9 Hz	$\sim 10^{-9}$ s	DDR clock synchronization
PCIe clock	10^8 Hz	$\sim 10^{-8}$ s	Peripheral interconnect timing
USB timing	10^6 – 10^9 Hz	$\sim 10^{-9}$ s	USB 2.0/3.0 frame timing
Power supply ripple	10^4 – 10^6 Hz	$\sim 10^{-6}$ s	Switching regulator frequency
Network packet timing	10^3 – 10^6 Hz	$\sim 10^{-6}$ s	Network interface timing offset (which may vary with temperature and voltage) and $\eta(t)$ is a zero-mean stochastic process representing the jitter.
Disk I/O timing	10^2 – 10^4 Hz	$\sim 10^{-5}$ s	Storage access latency

Table 3: **Hardware oscillator sources and characteristic frequencies.** Modern computing systems contain oscillatory processes spanning seven orders of magnitude in frequency, from disk I/O timing ($\sim 10^2$ Hz) to CPU clocks ($\sim 10^{10}$ Hz). Each oscillator provides a timing reference that can be measured with precision determined by the oscillator’s quality factor and the measurement apparatus resolution. These diverse frequency sources enable the construction of S-entropy coordinates that capture multi-scale temporal structure in computational processes.

(TSC) is readable via the `RDTSC` instruction on x86 architectures or the `CNTVCT` register on ARM architectures. Memory timing is accessible through performance counters. Power supply ripple can be measured through voltage sensors or inferred from current draw fluctuations. This accessibility ensures that Poincaré Computing can be implemented on commodity hardware without modification [8].

25.2 Timing Measurement and Jitter

The fundamental observable in virtual instrumentation is the timing difference between oscillators. Let t_{ref} denote a reference timestamp obtained from a high-precision clock (typically the CPU timestamp counter, which increments at the CPU’s nominal frequency) and let t_{local} denote a local measurement from another oscillator source (such as a memory access completion time or a peripheral event timestamp). The timing difference is defined as:

$$\delta_p = t_{\text{ref}} - t_{\text{local}} \quad (354)$$

This timing difference δ_p is measured in units of the reference clock period (typically nanoseconds or sub-nanosecond for modern CPUs). The subscript p denotes that this is a *physical* measurement subject to hardware non-determinism, distinguishing it from the idealized categorical coordinates.

In an ideal system, the timing difference would be deterministic, depending only on the computational

state. However, real hardware exhibits timing jitter—stochastic variation in the measured timing difference due to thermal noise, voltage fluctuations, electromagnetic interference, and quantum effects in the oscillator circuits. We model this jitter as:

$$\delta_p(t) = \bar{\delta}(t) + \eta(t) \quad (355)$$

where $\bar{\delta}(t)$ is the mean timing offset (which may vary slowly with temperature and voltage) and $\eta(t)$ is a zero-mean stochastic process representing the jitter.

The statistical properties of $\eta(t)$ depend on the oscillator’s quality factor Q , which characterizes the sharpness of the oscillator’s frequency response. High-quality oscillators (large Q) exhibit low jitter, while low-quality oscillators (small Q) exhibit high jitter. For typical hardware oscillators, the jitter process $\eta(t)$ can be modeled as Gaussian white noise with power spectral density determined by the Leeson model [13]:

$$S_\eta(f) = \frac{2k_B T}{P_{\text{osc}}} \left[1 + \left(\frac{f_0}{2Qf} \right)^2 \right] \quad (356)$$

where k_B is Boltzmann’s constant, T is temperature, P_{osc} is oscillator power, f_0 is the oscillator frequency, and f is the offset frequency from the carrier.

Despite this stochastic variation, the jitter remains bounded for stable oscillators, ensuring that timing measurements do not diverge arbitrarily.

Proposition 25.1 (Jitter Boundedness). *For a stable hardware oscillator with quality factor $Q > Q_{\min}$ and operating within specified temperature and voltage ranges, the timing jitter satisfies:*

$$|\eta(t)| \leq \eta_{\max} < \infty \quad (357)$$

with probability $1 - \delta$ for arbitrarily small $\delta > 0$, where the bound $\eta_{\max}$ depends on the oscillator quality factor and the confidence level:

$$\eta_{\max} \approx \frac{k\sigma_\eta}{\sqrt{2Q}} \quad (358)$$

for a constant k determined by the desired confidence level (e.g., $k \approx 6$ for $\delta < 10^{-9}$).

Proof. The jitter process $\eta(t)$ is modeled as Gaussian noise with variance σ_η^2 determined by integrating the power spectral density (356) over the measurement bandwidth. For a Gaussian random variable, the probability of exceeding k standard deviations is given by the tail probability:

$$P(|\eta| > k\sigma_\eta) = 2Q \left(\frac{k}{\sqrt{2}} \right) \quad (359)$$

where $Q(\cdot)$ is the Gaussian Q-function. For $k = 6$, this probability is approximately 2×10^{-9} , establishing that $|\eta(t)| \leq 6\sigma_\eta$ with probability $1 - 2 \times 10^{-9}$.

The dependence on quality factor Q arises from the Leeson model: higher Q reduces the integrated noise power, decreasing σ_η proportionally to $1/\sqrt{Q}$. Therefore $\eta_{\max} \propto k\sigma_\eta/\sqrt{Q}$. $\square$

This boundedness ensures that timing measurements, despite their stochastic nature, remain within a finite range and can be reliably mapped to the bounded S-entropy space $[0, 1]^3$.

25.3 Coordinate Mapping Functions

The timing difference δ_p is a real-valued physical measurement, while the S-entropy coordinates (S_k, S_t, S_e) are bounded values in $[0, 1]$. We now define three mapping functions that transform timing measurements into categorical coordinates. These mappings are designed to satisfy three requirements: (i) they map $\mathbb{R} \rightarrow [0, 1]$, ensuring boundedness; (ii) they are deterministic, ensuring reproducibility; and (iii) they capture different aspects of the timing structure, ensuring that the three coordinates are informationally independent.

Definition 25.1 (Knowledge Entropy Mapping). The **knowledge entropy coordinate** is obtained from the timing difference via the mapping:

$$S_k = \phi_k(\delta_p) = \frac{1}{2} \left(1 + \tanh \left(\frac{\delta_p - \mu_\delta}{\sigma_\delta} \right) \right) \quad (360)$$

where μ_δ is the mean timing offset (estimated from a calibration phase) and σ_δ is the standard deviation of the timing distribution. The hyperbolic tangent function provides a smooth, bounded mapping from the real line to the interval $[0, 1]$, with the center point $S_k = 0.5$ corresponding to the mean timing offset.

The knowledge entropy coordinate captures the *magnitude* of the timing difference relative to its expected value. Large positive deviations (indicating that the reference clock is ahead of the local clock) produce $S_k \rightarrow 1$, while large negative deviations produce $S_k \rightarrow 0$. The scaling by σ_δ ensures that the mapping is sensitive to deviations of order one standard deviation, making the coordinate robust to the natural variability in timing measurements.

Definition 25.2 (Temporal Entropy Mapping). The **temporal entropy coordinate** is obtained via the mapping:

$$S_t = \phi_t(\delta_p) = |\sin(2\pi f_{\text{ref}}\delta_p)| \quad (361)$$

where f_{ref} is the reference oscillator frequency (in Hz) and δ_p is measured in seconds. The absolute value of the sine function produces a periodic mapping with period $T_{\text{ref}} = 1/(2f_{\text{ref}})$, corresponding to half the reference oscillator period.

The temporal entropy coordinate captures the *phase* of the timing difference relative to the reference oscillator. This coordinate oscillates between 0 and 1 as the timing difference varies, with the oscillation frequency determined by f_{ref} . The use of $|\sin(\cdot)|$ rather than $\sin(\cdot)$ ensures that $S_t \in [0, 1]$ and doubles the oscillation frequency, increasing the sensitivity to phase variations.

Definition 25.3 (Evolution Entropy Mapping). The **evolution entropy coordinate** is obtained via the mapping:

$$S_e = \phi_e(\delta_p) = \frac{1}{2} (1 + \cos(2\pi f_{\text{beat}}\delta_p)) \quad (362)$$

where $f_{\text{beat}} = |f_{\text{ref}} - f_{\text{local}}|$ is the beat frequency between the reference oscillator and the local oscillator. This mapping produces a periodic coordinate with period $T_{\text{beat}} = 1/f_{\text{beat}}$, corresponding to the beat period.

The evolution entropy coordinate captures the *beat phase* between two oscillators. When two oscillators with slightly different frequencies interact, they produce a beat pattern with frequency equal to the difference of the individual frequencies. This beat pattern encodes information about the relative phase evolution of the two oscillators, which in turn reflects the temporal structure of the computational process. The cosine function (rather than sine) is chosen to ensure that $S_e = 1$ when the oscillators are in phase ($\delta_p = 0, 1/f_{\text{beat}}, 2/f_{\text{beat}}, \dots$) and $S_e = 0$ when they are out of phase.

Proposition 25.2 (Range Preservation). *The coordinate mapping functions satisfy $\phi_k, \phi_t, \phi_e : \mathbb{R} \rightarrow [0, 1]$, ensuring that all timing measurements, regardless of magnitude, map to valid S-entropy coordinates in $\mathcal{S} = [0, 1]^3$.*

Proof. We verify the range of each mapping function:

Knowledge entropy: The hyperbolic tangent function has range $\tanh : \mathbb{R} \rightarrow (-1, 1)$. Therefore:

$$\phi_k(\delta_p) = \frac{1}{2}(1 + \tanh(\cdot)) \in \frac{1}{2}(1 + (-1, 1)) = \frac{1}{2}(0, 2) = (0, 1) \subset [0, 1] \quad (363)$$

The range is an open interval, but the limits $\phi_k \rightarrow 0$ as $\delta_p \rightarrow -\infty$ and $\phi_k \rightarrow 1$ as $\delta_p \rightarrow +\infty$ are approached asymptotically, ensuring that all values are strictly within $(0, 1)$.

figures/panel_ensemble_hardware_mapping.png

Temporal entropy: The sine function has range $\sin : \mathbb{R} \rightarrow [-1, 1]$. Taking the absolute value gives:

$$\phi_t(\delta_p) = |\sin(\cdot)| \in [0, 1] \quad (364)$$

The range includes both endpoints, as $|\sin(\cdot)| = 0$ when the argument is an integer multiple of π , and $|\sin(\cdot)| = 1$ when the argument is an odd multiple of $\pi/2$.

Evolution entropy: The cosine function has range $\cos : \mathbb{R} \rightarrow [-1, 1]$. Therefore:

$$\phi_e(\delta_p) = \frac{1}{2}(1 + \cos(\cdot)) \in \frac{1}{2}(1 + [-1, 1]) = \frac{1}{2}[0, 2] = [0, 1] \quad (365)$$

The range includes both endpoints, as $\cos(\cdot) = -1$ when the argument is an odd multiple of π , and $\cos(\cdot) = 1$ when the argument is an even multiple of π .

Since all three mappings have range contained in $[0, 1]$, any timing measurement $\delta_p \in \mathbb{R}$ produces a valid S-entropy coordinate $\mathbf{S} = (\phi_k(\delta_p), \phi_t(\delta_p), \phi_e(\delta_p)) \in [0, 1]^3 = \mathcal{S}$. $\square$

Remark 25.2 (Informational Independence). The three coordinate mappings capture different aspects of the timing measurement: ϕ_k captures the magnitude (via a monotonic function), ϕ_t captures the phase relative to the reference oscillator (via a periodic function with period $\sim 1/f_{\text{ref}}$), and ϕ_e captures the beat phase (via a periodic function with period $\sim 1/f_{\text{beat}}$). Since these three aspects are mathematically independent—knowing one does not determine the others—the three coordinates provide complementary information about the timing structure. This informational independence is essential for the three-dimensional structure of $\mathcal{S}$ to be non-degenerate.

25.4 Categorical State Construction

Given a timing measurement δ_p , the complete categorical state in S-entropy space is constructed by applying all three coordinate mappings:

$$\mathbf{S} = \Phi(\delta_p) = (\phi_k(\delta_p), \phi_t(\delta_p), \phi_e(\delta_p)) \in \mathcal{S} \quad (366)$$

This mapping $\Phi : \mathbb{R} \rightarrow \mathcal{S}$ transforms a single real-valued timing measurement into a three-dimensional categorical state. The mapping is deterministic, ensuring that repeated measurements of the same physical state produce the same categorical state (up to measurement noise, which is bounded by Proposition 25.1).

Figure 12: **Virtual Gas Ensemble: Hardware Oscillations $\rightarrow$ Categorical Molecules.** **Molecule α** ($\Delta t = 1000$ ns): Radar chart (blue) shows six hardware timing sources mapped to categorical state: Power Supply (high), Memory Bus (high), CPU Cycle (medium), I/O Latency (low), Cache Timing (very low), Network Jitter (medium). The hexagonal profile represents the categorical “shape” of molecule α in the six-dimensional hardware space. **Molecule β** ($\Delta t = 2800$ ns): Radar chart (magenta) shows different profile: Power Supply (high), Memory Bus (medium), CPU Cycle (low), I/O Latency (low), Cache Timing (very low), Network Jitter (low). The triangular profile (three dominant dimensions) distinguishes β from α . **Molecule γ** ($\Delta t = 3200$ ns): Radar chart (orange) shows third distinct profile: Power Supply (high), Memory Bus (very high), CPU Cycle (high), I/O Latency (medium), Cache Timing (medium), Network Jitter

Theorem 25.3 (Deterministic Mapping). *The mapping $\Phi : \mathbb{R} \rightarrow \mathcal{S}$ defined by equation (366) is deterministic: for any timing measurement δ_p , the categorical state $\mathbf{S} = \Phi(\delta_p)$ is uniquely determined.*

Proof. Each component function ϕ_k, ϕ_t, ϕ_e is defined as a composition of elementary mathematical functions:

- ϕ_k is a composition of arithmetic operations (subtraction, division), the hyperbolic tangent function, and affine transformations;
- ϕ_t is a composition of arithmetic operations (multiplication), the sine function, and the absolute value function;
- ϕ_e is a composition of arithmetic operations (multiplication), the cosine function, and affine transformations.

All elementary mathematical functions (arithmetic, trigonometric, hyperbolic, absolute value) are deterministic: given the same input, they always produce the same output. The composition of deterministic functions is also deterministic. Therefore, each ϕ_i is deterministic, and the vector-valued mapping $\Phi = (\phi_k, \phi_t, \phi_e)$ is deterministic.

Formally, for any $\delta_p \in \mathbb{R}$, the value $\Phi(\delta_p)$ is computed by evaluating a fixed sequence of elementary operations on δ_p , producing a unique result in $\mathcal{S}$. $\square$

Remark 25.3 (Measurement Noise). While the mapping Φ is deterministic, the timing measurement δ_p itself is subject to jitter (equation (355)). Therefore, repeated measurements of the same computational state will produce slightly different categorical states $\mathbf{S}_1, \mathbf{S}_2, \dots$ due to the stochastic variation in δ_p . However, Proposition 25.1 ensures that these variations remain bounded: $\|\mathbf{S}_i - \mathbf{S}_j\| \leq \|\nabla \Phi\| \cdot 2\eta_{\max}$, where $\|\nabla \Phi\|$ is the maximum gradient of the mapping. For typical hardware parameters, this variation is small compared to the recurrence tolerance ϵ , ensuring that measurement noise does not prevent recurrence detection.

25.5 Spectrometer-State Identity

A profound property of virtual instrumentation in Poincaré Computing is the identity between the measurement apparatus and the measured state. In traditional measurement theory, the apparatus and the system are distinct entities: the apparatus observes the system without being part of the system's state

space. In Poincaré Computing, by contrast, the measurement apparatus (which we call a *virtual spectrometer*) and the categorical state it measures are encoded by the same point in S-entropy space. This identity has far-reaching consequences for the nature of observation and measurement in this computational framework.

Theorem 25.4 (Spectrometer-State Identity). *Let $\mathcal{I}_\omega$ denote a virtual spectrometer configured to measure oscillations at frequency ω . The categorical state $\mathbf{S}_\omega$ that produces a non-null measurement on $\mathcal{I}_\omega$ satisfies:*

$$\mathbf{S}_\omega = \Phi(\omega^{-1}) \quad (367)$$

In other words, the spectrometer configuration (characterised by its frequency ω) and the measurable state (characterised by its timing difference $\delta_p = \omega^{-1}$) are encoded by the same point in S-entropy space.

Proof. A virtual spectrometer $\mathcal{I}_\omega$ is defined by its sensitivity to oscillations at frequency ω . Operationally, this means that $\mathcal{I}_\omega$ measures timing differences with a resolution of $\Delta t = \omega^{-1}$, corresponding to one period of the target oscillation. The spectrometer is maximally sensitive to states that exhibit timing variations on this timescale.

A categorical state $\mathbf{S}$ produces a non-null measurement on $\mathcal{I}_\omega$ if and only if the timing difference δ_p that generated $\mathbf{S}$ satisfies $\delta_p \approx \omega^{-1}$ (up to integer multiples of the period, accounting for the periodicity of the temporal and evolution entropy mappings). This is because the coordinate mappings ϕ_t and ϕ_e depend on the product $f \cdot \delta_p$, which determines the phase of the oscillatory components.

For a state with $\delta_p = \omega^{-1}$, the categorical state is:

$$\mathbf{S}_\omega = \Phi(\omega^{-1}) = (\phi_k(\omega^{-1}), \phi_t(\omega^{-1}), \phi_e(\omega^{-1})) \quad (368)$$

The spectrometer $\mathcal{I}_\omega$ is configured to detect precisely this state. Therefore, the spectrometer configuration (characterised by ω) and the measurable state (characterised by $\delta_p = \omega^{-1}$) correspond to the same point $\mathbf{S}_\omega$ in S-entropy space.

Formally, the spectrometer $\mathcal{I}_\omega$ can be represented as a projection operator $\Pi_\omega : \mathcal{S} \rightarrow \mathbb{R}$ that extracts the component of a categorical state corresponding to frequency ω . This projection satisfies $\Pi_\omega(\mathbf{S}_\omega) = 1$ (maximal response) and $\Pi_\omega(\mathbf{S}) \rightarrow 0$ as $\|\mathbf{S} - \mathbf{S}_\omega\| \rightarrow \infty$ (vanishing response for distant states). The spectrometer configuration is thus encoded by the state $\mathbf{S}_\omega$ that maximizes the projection, establishing the identity. $\square$

Corollary 25.5 (Zero Measurement Backaction). *Measurement of a categorical state $\mathbf{S}_\omega$ by the corresponding virtual spectrometer $\mathcal{I}_\omega$ does not perturb*

the state: the post-measurement state equals the pre-measurement state.

Proof. In category theory, measurement is represented by a morphism from the state space to the measurement outcome space. For the spectrometer-state identity, the measurement morphism is $m : \mathbf{S}_\omega \rightarrow \mathbf{S}_\omega$, which is the identity morphism $\text{id}_{\mathbf{S}_\omega}$.

Identity morphisms, by definition, do not change their domain: $\text{id}_{\mathbf{S}_\omega}(\mathbf{S}_\omega) = \mathbf{S}_\omega$. Therefore, measurement by $\mathcal{I}_\omega$ leaves the state $\mathbf{S}_\omega$ unchanged, implying zero backaction.

Physically, this property arises because the spectrometer and the state are the same entity: measuring a state with its corresponding spectrometer is equivalent to the state "observing itself," which cannot produce perturbation. $\square$

Remark 25.4 (Contrast with Quantum Measurement). The zero backaction property (Corollary 25.5) contrasts sharply with quantum measurement, where observation generically perturbs the measured system due to wavefunction collapse or entanglement with the measurement apparatus. In Poincaré Computing, the spectrometer-state identity ensures that measurement is fundamentally non-perturbative when the spectrometer is matched to the state. This property enables continuous monitoring of the categorical state without disrupting the trajectory evolution, which is essential for the real-time constraint satisfaction required in Section 27.

Example 25.1 (CPU-Memory Beat Frequency). Consider a system with CPU clock frequency $f_{\text{CPU}} = 3.0$ GHz and memory bus frequency $f_{\text{mem}} = 2.4$ GHz. The beat frequency is:

$$f_{\text{beat}} = |f_{\text{CPU}} - f_{\text{mem}}| = 0.6 \text{ GHz} = 600 \text{ MHz} \quad (369)$$

A timing measurement $\delta_p = 1.67$ ns (corresponding to one beat period $T_{\text{beat}} = 1/f_{\text{beat}}$) produces the categorical state:

$$S_k = \phi_k(1.67 \text{ ns}) \approx 0.5 \quad (\text{assuming } \mu_\delta \approx 1.67 \text{ ns}) \quad (370)$$

$$S_t = |\sin(2\pi \cdot 3.0 \times 10^9 \cdot 1.67 \times 10^{-9})| = |\sin(10\pi)| = 0 \quad (371)$$

$$S_e = \frac{1}{2}(1 + \cos(2\pi \cdot 0.6 \times 10^9 \cdot 1.67 \times 10^{-9})) = \frac{1}{2}(1 + \cos(2\pi)) = 1 \quad (372)$$

A virtual spectrometer $\mathcal{I}_{600 \text{ MHz}}$ configured to measure the beat frequency would be maximally sensitive to this state $\mathbf{S} = (0.5, 0, 1)$, confirming the spectrometer-state identity.

This section has established the physical grounding of S-entropy coordinates in measurable hardware timing differences. The coordinate mappings ϕ_k, ϕ_t, ϕ_e transform continuous real-valued measurements into bounded categorical states, the mapping is deterministic and range-preserving, and the spectrometer-state identity ensures that measurement apparatus and measured state coincide in S-entropy space. In the following section, we develop the categorical dynamics that govern the evolution of these hardware-grounded states through computational trajectories.

26 Categorical Dynamics

27 Categorical Dynamics

Having established the geometric structure of S-entropy space (Section 21) and its physical grounding in hardware measurements (Section 25), we now develop the dynamical equations governing trajectory evolution. These equations determine how categorical states $\mathbf{S}(t) = (S_k(t), S_t(t), S_e(t))$ evolve through phase space in response to computational processes, transforming the static problem specification (Section 23) into a time-dependent trajectory that encodes the computation itself.

The categorical dynamics are derived from the fundamental principle that computation in Poincaré Computing corresponds to harmonic oscillator interactions. Each S-entropy coordinate is associated with an oscillatory mode characterized by a natural frequency ω_i , and the three modes are coupled through nonlinear interaction terms. This coupling ensures that the coordinates evolve in a coordinated manner, with changes in one coordinate influencing the evolution of the others. The resulting dynamics exhibit rich structure including fixed points, periodic orbits, and quasi-periodic trajectories, with the specific trajectory determined by the initial state and the constraint set.

A crucial property established in this section is that the categorical dynamics are **measure-preserving**: the flow generated by the equations of motion preserves the Lebesgue measure on $\mathcal{S}$. This property is essential for the application of Poincaré's recurrence theorem (Corollary 21.6), as it ensures that the phase space volume occupied by any set of initial conditions remains constant under time evolution. We prove that measure preservation holds when the characteristic frequencies satisfy a **modular condition**, which constrains their sum to vanish. This condition has a natural interpretation in terms of energy conservation in the underlying oscillator dynamics.

We further establish the existence of **harmonic coincidences**—special times when the oscillatory components of the trajectory synchronize—and prove that these coincidences form a dense set for rationally related frequencies. These coincidence events correspond to moments when the computation achieves temporary coherence across all three S-entropy dimensions, and they play a crucial role in the formation of recurrent trajectories. The section concludes with an analysis of fixed points and periodic orbits, demonstrating that the categorical dynamics admit a rich variety of solution structures beyond simple point attractors.

27.1 Equations of Motion

The evolution of a categorical state $\mathbf{S}(t) = (S_k(t), S_t(t), S_e(t))$ is governed by a system of three coupled first-order ordinary differential equations. These equations are derived from the principle that each S-entropy coordinate evolves according to two influences: (i) a *linear restoring term* that couples the coordinate to the other coordinates, driving the system toward equilibrium, and (ii) a *nonlinear coupling term* that introduces oscillatory interactions between coordinates, enabling the complex trajectory structures required for computation.

Definition 27.1 (Categorical Dynamics). The **categorical evolution equations** governing the time evolution of S-entropy coordinates are:

$$\frac{dS_k}{dt} = \omega_k(S_t - S_k) + \alpha \sin(2\pi S_e) \quad (373)$$

$$\frac{dS_t}{dt} = \omega_t(S_e - S_t) + \beta \sin(2\pi S_k) \quad (374)$$

$$\frac{dS_e}{dt} = \omega_e(S_k - S_e) + \gamma \sin(2\pi S_t) \quad (375)$$

where:

- $\omega_k, \omega_t, \omega_e \in \mathbb{R}$ are the **characteristic frequencies** associated with the knowledge, temporal, and evolution entropy coordinates respectively;
- $\alpha, \beta, \gamma \in \mathbb{R}$ are the **coupling constants** that determine the strength of nonlinear interactions between coordinates;
- The sine functions with period 1 (due to the 2π factor) reflect the periodic structure of the bounded phase space $\mathcal{S} = [0, 1]^3$.

The physical interpretation of these equations is as follows. Consider the knowledge entropy evolution (373):

- The term $\omega_k(S_t - S_k)$ represents a *linear coupling* to the temporal entropy coordinate. If $S_t > S_k$, this term is positive, driving S_k to increase and approach S_t . This coupling reflects the principle that knowledge accumulation (increasing S_k) is facilitated by temporal structure (high S_t).
- The term $\alpha \sin(2\pi S_e)$ represents a *nonlinear forcing* from the evolution entropy coordinate. This term oscillates as S_e varies, introducing periodic modulation of the knowledge entropy evolution. The sine function ensures that the forcing respects the periodic boundary conditions of the unit cube $\mathcal{S}$.

Similar interpretations apply to the temporal and evolution entropy equations, with each coordinate coupled linearly to one neighbor and nonlinearly to another, forming a cyclic coupling structure: $S_k \rightarrow S_t \rightarrow S_e \rightarrow S_k$. This cyclic structure ensures that information flows through all three coordinates, preventing any coordinate from evolving independently.

Remark 27.1 (Derivation from Oscillator Dynamics). The categorical dynamics (373)–(375) can be derived from a system of three coupled harmonic oscillators with positions $q_k(t)$, $q_t(t)$, $q_e(t)$ and a potential energy function:

$$V(q_k, q_t, q_e) = \frac{1}{2}\omega_k^2(q_k - q_t)^2 + \frac{1}{2}\omega_t^2(q_t - q_e)^2 + \frac{1}{2}\omega_e^2(q_e - q_k)^2 + U_{\text{nl}}(q_k, q_t, q_e) \quad (376)$$

where U_{nl} is a nonlinear coupling potential. The S-entropy coordinates are related to the oscillator phases via $S_k = (q_k \bmod 1)$, and the equations of motion $\ddot{q}_i = -\partial V / \partial q_i$ reduce to (373)–(375) in the overdamped limit. This connection to classical mechanics provides physical intuition for the categorical dynamics and justifies the use of Hamiltonian methods in their analysis [6].

27.2 Vector Field Formulation

To facilitate analysis using tools from dynamical systems theory, we reformulate the categorical dynamics as a vector field on $\mathcal{S}$. This formulation makes explicit the geometric structure of the dynamics and enables the application of theorems from differential geometry and topology.

Define the **categorical vector field** $\mathbf{F} : \mathcal{S} \rightarrow \mathbb{R}^3$ by:

$$\mathbf{F}(\mathbf{S}) = \begin{pmatrix} \omega_k(S_t - S_k) + \alpha \sin(2\pi S_e) \\ \omega_t(S_e - S_t) + \beta \sin(2\pi S_k) \\ \omega_e(S_k - S_e) + \gamma \sin(2\pi S_t) \end{pmatrix} \quad (377)$$

Categorical Navigation: Spatial Distance Irrelevance




Figure 13: **Categorical Navigation: Spatial Distance Irrelevance.** (A) **Location Accessibility:** Bar chart shows categorical accessibility (normalized to $[0, 1]$) for six locations: Local (1.0), Jupiter Core (1.0), Sun Center (1.0), Deep Space (1.0), Earth Mantle (1.0), Moon (1.0). All locations show identical accessibility despite vastly different physical distances. This demonstrates spatial distance irrelevance (Theorem ??): categorical navigation does not depend on physical separation. (B) **Physical vs Categorical Distance:** Grouped bar chart compares physical distance (red, $\log_{10}$ km scale) vs. categorical distance (blue, S-distance units) for six locations. (C) **Equal Measurement Time:** Bar chart shows measurement time (ms) for six locations: Local (≈ 1.0 ms), Jupiter Core (≈ 0.6 ms), Sun Center (≈ 0.8 ms), Deep Space (≈ 0.4 ms), Earth Mantle (≈ 0.4 ms), Moon (≈ 0.4 ms). Mean measurement time 0.670 ms (red dashed line) is independent of location. (D) **Tackle Reach Comparison:** Polar plot shows reachability in categorical space. Full tackle region (blue circle, radius ≈ 1.0) encompasses all locations (colored dots: red at 180°, green at 135°, orange at 90°, purple at 45°, blue at center). (E) **Reachability Map:** Scatter plot in (S_k, S_e) plane shows six locations as colored circles with black outlines. All locations cluster in reachable region (green background, $S_k, S_e \in [0, 1]$). (F) **Sequential Access (All Instant):** Flowchart shows six locations accessed sequentially: Local (0.96 ms), Jupiter Core (0.60 ms), Sun Center (0.82 ms), Deep Space (0.83 ms), Earth Mantle (0.39 ms), Moon (0.42 ms).

The categorical dynamics (373)–(375) are then compactly expressed as:

$$\frac{d\mathbf{S}}{dt} = \mathbf{F}(\mathbf{S}) \quad (378)$$

This is an autonomous ordinary differential equation (ODE) on the compact manifold $\mathcal{S}$. The vector field $\mathbf{F}$ is smooth (infinitely differentiable) on the interior of $\mathcal{S}$ due to the smoothness of the sine function and arithmetic operations. At the boundary of $\mathcal{S}$, the vector field must be analyzed carefully to ensure that trajectories remain within the unit cube.

Proposition 27.1 (Invariance of $\mathcal{S}$). *The unit cube $\mathcal{S} = [0, 1]^3$ is invariant under the flow generated by $\mathbf{F}$: if $\mathbf{S}(0) \in \mathcal{S}$, then $\mathbf{S}(t) \in \mathcal{S}$ for all $t \geq 0$.*

Proof. We must show that the vector field $\mathbf{F}$ points inward (or tangentially) at the boundary of $\mathcal{S}$. Consider the boundary face $S_k = 0$. On this face, the first component of $\mathbf{F}$ is:

$$F_1(\mathbf{S})|_{S_k=0} = \omega_k(S_t - 0) + \alpha \sin(2\pi S_e) = \omega_k S_t + \alpha \sin(2\pi S_e) \quad (379)$$

For $S_t \in [0, 1]$ and $S_e \in [0, 1]$, we have:

- If $\omega_k > 0$, then $\omega_k S_t \geq 0$, and the term $\alpha \sin(2\pi S_e)$ is bounded in $[-|\alpha|, |\alpha|]$. Provided $\omega_k > |\alpha|$, we have $F_1 > 0$ on average, ensuring that trajectories starting at $S_k = 0$ move into the interior.
- If $\omega_k < 0$, a similar analysis applies to the boundary face $S_k = 1$.

Analogous arguments apply to the other boundary faces, establishing that $\mathcal{S}$ is invariant under the flow. Rigorously, this requires that the vector field satisfies $\mathbf{F} \cdot \mathbf{n} \geq 0$ on the boundary, where $\mathbf{n}$ is the inward-pointing normal vector. This condition is satisfied for appropriate parameter ranges. $\square$

Remark 27.2 (Boundary Behavior). In practice, the periodic nature of the sine functions in (377) means that trajectories approaching the boundary $S_k = 1$ can be smoothly continued to $S_k = 0$ by identifying opposite faces of the unit cube. This identification transforms $\mathcal{S}$ from a cube with boundary into a three-dimensional torus $\mathbb{T}^3 = S^1 \times S^1 \times S^1$, on which the dynamics are naturally defined without boundary conditions. The torus topology is consistent with the periodic structure of the coordinate mappings (Section 25) and provides a more natural setting for the categorical dynamics.

27.3 Measure Preservation and Liouville's Theorem

The most important property of the categorical dynamics for the Poincaré Computing framework is that they preserve the Lebesgue measure on $\mathcal{S}$. This property is essential for the application of Poincaré's recurrence theorem, which requires that the dynamics be measure-preserving. We establish measure preservation through Liouville's theorem from Hamiltonian mechanics, which relates measure preservation to the divergence of the vector field.

Theorem 27.2 (Measure Preservation). *The flow $\varphi_t : \mathcal{S} \rightarrow \mathcal{S}$ generated by the categorical vector field $\mathbf{F}$ preserves the Lebesgue measure μ on $\mathcal{S}$ if and only if the characteristic frequencies satisfy the **modular condition**:*

$$\omega_k + \omega_t + \omega_e = 0 \quad (380)$$

Under this condition, for any measurable set $A \subseteq \mathcal{S}$ and any time t , we have:

$$\mu(\varphi_t(A)) = \mu(A) \quad (381)$$

Proof. By Liouville's theorem [3], a flow preserves Lebesgue measure if and only if the divergence of the generating vector field vanishes:

$$\nabla \cdot \mathbf{F} = 0 \quad (382)$$

We compute the divergence by taking the partial derivatives of each component of $\mathbf{F}$ with respect to the corresponding coordinate:

$$\nabla \cdot \mathbf{F} = \frac{\partial F_1}{\partial S_k} + \frac{\partial F_2}{\partial S_t} + \frac{\partial F_3}{\partial S_e} \quad (383)$$

$$\begin{aligned} &= \frac{\partial}{\partial S_k} [\omega_k(S_t - S_k) + \alpha \sin(2\pi S_e)] \\ &\quad + \frac{\partial}{\partial S_t} [\omega_t(S_e - S_t) + \beta \sin(2\pi S_k)] \\ &\quad + \frac{\partial}{\partial S_e} [\omega_e(S_k - S_e) + \gamma \sin(2\pi S_t)] \end{aligned} \quad (384)$$

Evaluating each partial derivative:

$$\frac{\partial F_1}{\partial S_k} = -\omega_k \quad (\text{the } S_t \text{ and } \sin(2\pi S_e) \text{ terms do not depend on } S_k) \quad (385)$$

$$\frac{\partial F_2}{\partial S_t} = -\omega_t \quad (\text{the } S_e \text{ and } \sin(2\pi S_k) \text{ terms do not depend on } S_t) \quad (386)$$

$$\frac{\partial F_3}{\partial S_e} = -\omega_e \quad (\text{the } S_k \text{ and } \sin(2\pi S_t) \text{ terms do not depend on } S_e) \quad (387)$$

Therefore:

$$\nabla \cdot \mathbf{F} = -\omega_k - \omega_t - \omega_e \quad (388)$$

Setting $\nabla \cdot \mathbf{F} = 0$ yields the modular condition (380). When this condition is satisfied, Liouville's theorem guarantees that the flow φ_t preserves Lebesgue measure. $\square$

Remark 27.3 (Physical Interpretation of Modular Condition). The modular condition $\omega_k + \omega_t + \omega_e = 0$ has a natural physical interpretation in terms of energy conservation. In the oscillator derivation (Remark 27.1), the frequencies ω_i are related to the stiffness of the coupling springs. The modular condition ensures that energy flowing into one coordinate (positive ω_i) is balanced by energy flowing out of another coordinate (negative ω_j), maintaining constant total energy. This energy conservation is equivalent to measure preservation in the phase space.

Mathematically, the modular condition implies that one frequency must be negative if the others are positive. For example, if $\omega_k, \omega_t > 0$, then $\omega_e = -(\omega_k + \omega_t) < 0$. We interpret a negative frequency as *retrograde evolution*: the coordinate evolves in the opposite direction to the standard orientation, corresponding to a phase shift of π in the oscillatory dynamics.

Corollary 27.3 (Recurrence Applicability). *Under the modular condition (380), the categorical dynamics satisfy the hypotheses of Poincaré's recurrence theorem (Corollary 21.6). Therefore, for almost every initial state $\mathbf{S}_0 \in \mathcal{S}$, the trajectory $\mathbf{S}(t)$ returns arbitrarily close to $\mathbf{S}_0$ infinitely often.*

Proof. Poincaré's recurrence theorem applies to measure-preserving transformations on finite measure spaces. Theorem 27.2 establishes that the flow φ_t is measure-preserving under the modular condition. Proposition 21.3 establishes that $\mu(\mathcal{S}) = 1 < \infty$. Therefore, the recurrence theorem applies, guaranteeing that almost every trajectory is recurrent. $\square$

This corollary is the central result connecting the categorical dynamics to the foundational principle of Poincaré Computing: computation corresponds to finding recurrent trajectories in measure-preserving flows.

27.4 Harmonic Coincidence Networks

A distinctive feature of the categorical dynamics is the occurrence of **harmonic coincidences**—special

times when the oscillatory components of the trajectory synchronize. These coincidences play a crucial role in the formation of recurrent trajectories and in the emergence of computational structure from continuous dynamics.

Definition 27.2 (Harmonic Coincidence). A **harmonic coincidence** occurs at time $t^* > 0$ when there exist integers $(n_k, n_t, n_e) \in \mathbb{Z}^3 \setminus \{(0, 0, 0)\}$ such that:

$$n_k \omega_k t^* + n_t \omega_t t^* + n_e \omega_e t^* \equiv 0 \pmod{2\pi} \quad (389)$$

Equivalently, the linear combination of phases satisfies:

$$n_k \omega_k t^* + n_t \omega_t t^* + n_e \omega_e t^* \in 2\pi\mathbb{Z} \quad (390)$$

At a harmonic coincidence time t^* , the three oscillatory modes have phases that are commensurate: their phases satisfy a linear relation with integer coefficients. This commensurability leads to constructive interference between the modes, producing a moment of enhanced coherence in the trajectory. In the context of computation, harmonic coincidences correspond to times when the knowledge, temporal, and evolution aspects of the computation are synchronized, enabling the system to make progress toward satisfying constraints.

Proposition 27.4 (Coincidence Density for Rational Frequencies). *If the characteristic frequencies are rationally related—that is, if $\omega_i/\omega_j \in \mathbb{Q}$ for all pairs $i, j \in \{k, t, e\}$ —then the set of harmonic coincidence times $\mathcal{T}_{\text{coin}} = \{t^* : \text{harmonic coincidence at } t^*\}$ has positive density in $\mathbb{R}^+$:*

$$\liminf_{T \rightarrow \infty} \frac{|\mathcal{T}_{\text{coin}} \cap [0, T]|}{T} > 0 \quad (391)$$

Proof. Assume that the frequencies are rationally related: $\omega_i/\omega_j = p_{ij}/q_{ij}$ for integers p_{ij}, q_{ij} with $\gcd(p_{ij}, q_{ij}) = 1$. Define the *fundamental frequency*:

$$\omega_0 = \gcd(\omega_k, \omega_t, \omega_e) \quad (392)$$

in the sense that each frequency can be written as $\omega_i = n_i \omega_0$ for integers n_i . (Here $\gcd$ is interpreted as the greatest common divisor in the ring of real numbers with rational ratios, which reduces to the standard integer $\gcd$ after appropriate scaling.)

A harmonic coincidence occurs when:

$$n_k(n_k \omega_0)t^* + n_t(n_t \omega_0)t^* + n_e(n_e \omega_0)t^* = (n_k^2 + n_t^2 + n_e^2)\omega_0 t^* \in 2\pi\mathbb{Z} \quad (393)$$

This condition is satisfied when:

$$t^* = \frac{2\pi m}{\omega_0(n_k^2 + n_t^2 + n_e^2)} \quad \text{for } m \in \mathbb{Z}^+ \quad (394)$$

The set of coincidence times is therefore:

$$\mathcal{T}_{\text{coin}} = \left\{ \frac{2\pi m}{\omega_0 N} : m \in \mathbb{Z}^+, N = n_k^2 + n_t^2 + n_e^2 \text{ for some } (n_k, n_t, n_e) \in \mathbb{Z}^3 \right\} \quad (395)$$

The smallest period is $T_0 = 2\pi/\omega_0$, and coincidences occur at integer multiples of this period (possibly with additional coincidences at rational fractions). The number of coincidences in the interval $[0, T]$ is at least $\lfloor T/T_0 \rfloor$, giving:

$$\liminf_{T \rightarrow \infty} \frac{|\mathcal{T}_{\text{coin}} \cap [0, T]|}{T} \geq \frac{1}{T_0} = \frac{\omega_0}{2\pi} > 0 \quad (396)$$

This establishes positive density of coincidence times. $\square$

Remark 27.4 (Irrational Frequencies). If the frequencies are irrationally related (e.g., $\omega_k/\omega_t \notin \mathbb{Q}$), then exact harmonic coincidences occur with zero density. However, *approximate* coincidences—times when the phases are nearly commensurate—still occur with positive density as per Diophantine approximation theory. For computational purposes, approximate coincidences within a tolerance δ are sufficient to trigger constraint satisfaction events, and the density of such approximate coincidences can be controlled through the choice of frequencies.

27.5 Fixed Points and Periodic Orbits

The categorical dynamics admit various types of invariant sets, including fixed points (equilibria) and periodic orbits. These invariant sets provide the skeleton around which more complex trajectories are organised and play a crucial role in determining the global structure of the phase space.

Theorem 27.5 (Fixed Point Structure). *The categorical dynamics (373)–(375) admit fixed points at states $\mathbf{S}^* = (S_k^*, S_t^*, S_e^*)$ where all three coordinates are equal:*

$$S_k^* = S_t^* = S_e^* = s^* \quad (397)$$

and $s^* \in [0, 1]$ satisfies:

$$\sin(2\pi s^*) = 0 \quad \Rightarrow \quad s^* \in \left\{ 0, \frac{1}{2}, 1 \right\} \quad (398)$$

(Note: $s^* = 0$ and $s^* = 1$ represent the same point due to periodic boundary conditions.)

Therefore, the categorical dynamics admit two distinct fixed points:

$$\mathbf{S}_1^* = (0, 0, 0) \equiv (1, 1, 1), \quad \mathbf{S}_2^* = \left(\frac{1}{2}, \frac{1}{2}, \frac{1}{2} \right) \quad (399)$$

Proof. At a fixed point, the vector field must vanish: $\mathbf{F}(\mathbf{S}^*) = 0$. This requires:

$$\omega_k(S_t^* - S_k^*) + \alpha \sin(2\pi S_e^*) = 0 \quad (400)$$

$$\omega_t(S_e^* - S_t^*) + \beta \sin(2\pi S_k^*) = 0 \quad (401)$$

$$\omega_e(S_k^* - S_e^*) + \gamma \sin(2\pi S_t^*) = 0 \quad (402)$$

Suppose $S_k^* = S_t^* = S_e^* = s^*$ (all coordinates equal). Then the linear terms in (400)–(402) vanish identically:

$$S_t^* - S_k^* = s^* - s^* = 0, \quad S_e^* - S_t^* = 0, \quad S_k^* - S_e^* = 0 \quad (403)$$

The equations reduce to:

$$\alpha \sin(2\pi s^*) = 0 \quad (404)$$

$$\beta \sin(2\pi s^*) = 0 \quad (405)$$

$$\gamma \sin(2\pi s^*) = 0 \quad (406)$$

Assuming $\alpha, \beta, \gamma \neq 0$, these equations are satisfied when $\sin(2\pi s^*) = 0$, which occurs at $s^* \in \{0, 1/2, 1\}$. Due to the periodic boundary conditions (identifying $s^* = 0$ with $s^* = 1$), there are two distinct fixed points: $(0, 0, 0)$ and $(1/2, 1/2, 1/2)$. $\square$

Proposition 27.6 (Local Stability of Central Fixed Point). *The fixed point $\mathbf{S}_2^* = (1/2, 1/2, 1/2)$ is Lyapunov stable when the coupling constants are small compared to the characteristic frequencies:*

$$|\alpha|, |\beta|, |\gamma| < \min(|\omega_k|, |\omega_t|, |\omega_e|) \quad (407)$$

Proof. To determine stability, we linearize the vector field $\mathbf{F}$ about the fixed point $\mathbf{S}_2^*$. The Jacobian matrix is:

$$D\mathbf{F}|_{\mathbf{S}_2^*} = \begin{pmatrix} \frac{\partial F_1}{\partial S_k} & \frac{\partial F_1}{\partial S_t} & \frac{\partial F_1}{\partial S_e} \\ \frac{\partial F_2}{\partial S_k} & \frac{\partial F_2}{\partial S_t} & \frac{\partial F_2}{\partial S_e} \\ \frac{\partial F_3}{\partial S_k} & \frac{\partial F_3}{\partial S_t} & \frac{\partial F_3}{\partial S_e} \end{pmatrix} \mathbf{S}_2^* \quad (408)$$

Computing the partial derivatives at $\mathbf{S}_2^* = (1/2, 1/2, 1/2)$:

$$\frac{\partial F_1}{\partial S_k} = -\omega_k, \quad \frac{\partial F_1}{\partial S_t} = \omega_k, \quad \frac{\partial F_1}{\partial S_e} = 2\pi\alpha \cos(2\pi \cdot 1/2) = -2\pi\alpha \quad (409)$$

$$\frac{\partial F_2}{\partial S_k} = 2\pi\beta \cos(2\pi \cdot 1/2) = -2\pi\beta, \quad \frac{\partial F_2}{\partial S_t} = -\omega_t, \quad \frac{\partial F_2}{\partial S_e} = \omega_t \quad (410)$$

$$\frac{\partial F_3}{\partial S_k} = \omega_e, \quad \frac{\partial F_3}{\partial S_t} = 2\pi\gamma \cos(2\pi \cdot 1/2) = -2\pi\gamma, \quad \frac{\partial F_3}{\partial S_e} = -\omega_e \quad (411)$$

Therefore:

$$D\mathbf{F}|_{\mathbf{S}_2^*} = \begin{pmatrix} -\omega_k & \omega_k & -2\pi\alpha \\ -2\pi\beta & -\omega_t & \omega_t \\ \omega_e & -2\pi\gamma & -\omega_e \end{pmatrix} \quad (412)$$




Figure 14: **Harmonic Coincidence Interactions.** **(A) Frequency Spectrum:** Histogram of $\log_{10}(\text{Frequency} + 1)$ shows narrow distribution centered at 13.0–13.1 (peak ≈ 32 counts), with long tail extending to 13.6. **(B) Harmonic Network:** Circular graph shows 24 molecules (colored nodes) arranged on circle perimeter. Gray lines connect molecules with harmonic relationships (frequency ratios $f_i/f_j \approx n/m$ for small integers n, m). **(C) Strength Distribution:** Histogram of interaction strength shows bimodal distribution: primary peak at 0.1 (≈ 1200 counts), secondary peak at 0.5 (≈ 2000 counts). Low-strength interactions (< 0.2) dominate numerically but high-strength interactions (≈ 0.5) provide critical coupling for solution convergence. The gap at 0.2–0.4 suggests quantization of interaction strengths. **(D) Harmonic Order Distribution:** Histogram of harmonic order $n + m$ (where $f_i/f_j \approx n/m$) shows exponential decay: order 2.5 dominates (≈ 2100 counts), decreasing to ≈ 250 counts by order 20. **(E) Phase-Amplitude Distribution:** Polar plot shows interaction phase (angle) vs. amplitude (radius). Most interactions cluster near 0° and 180° (in-phase and anti-phase), with amplitudes 0.2–0.8. **(F) Frequency Ratio Matrix:** Heatmap shows pairwise frequency ratios f_i/f_j for 20 molecules (rows and columns). Diagonal is identity ($f_i/f_i = 1$, white). Off-diagonal shows ratios ranging from 0.5 (red, $f_i = f_j/2$) to 4.0 (blue, $f_i = 4f_j$).

The fixed point is Lyapunov stable if all eigenvalues of $D\mathbf{F}|_{\mathcal{S}_2^*}$ have non-positive real parts. Under the modular condition $\omega_k + \omega_t + \omega_e = 0$ and the assumption that coupling constants are small ($|\alpha|, |\beta|, |\gamma| \ll |\omega_i|$), the eigenvalues can be computed perturbatively. The unperturbed system (with $\alpha = \beta = \gamma = 0$) has eigenvalues $\{0, 0, 0\}$ (reflecting the measure-preserving property). The coupling terms introduce small perturbations that, for sufficiently small coupling, maintain non-positive real parts, ensuring Lyapunov stability [12]. $\square$

Theorem 27.7 (Periodic Orbit Existence). *For characteristic frequencies that are rationally related and coupling constants satisfying $|\alpha|, |\beta|, |\gamma| \ll |\omega_i|$, the categorical dynamics admit a dense set of periodic orbits in $\mathcal{S}$.*

Proof. The categorical dynamics can be viewed as a perturbation of an integrable system. When $\alpha = \beta = \gamma = 0$, the equations (373)–(375) decouple into three independent linear equations, which are exactly solvable. For rationally related frequencies, the solutions are periodic with periods determined by the frequency ratios.

The Kolmogorov-Arnold-Moser (KAM) theorem [2] establishes that, for sufficiently small perturbations of integrable Hamiltonian systems, a positive measure of invariant tori persists. These invariant tori are foliated by quasi-periodic orbits, which become periodic orbits when the frequencies are rationally related.

Applying the KAM theorem to the categorical dynamics (interpreted as a Hamiltonian system via the measure-preserving property), we conclude that for small coupling constants, a dense set of periodic orbits persists. The density follows from the fact that rational frequency ratios are dense in the space of all frequency ratios, and each rational ratio corresponds to a periodic orbit. $\square$

Remark 27.5 (Computational Significance of Periodic Orbits). Periodic orbits in the categorical dynamics correspond to computations that repeat cyclically, returning to the same state after a fixed period. These orbits are not solutions in the Poincaré Computing sense (which requires recurrence to the initial state, not to an arbitrary state), but they provide the building blocks from which recurrent trajectories are constructed. By concatenating segments of different periodic orbits through constraint-guided transitions, the system can navigate through phase space to satisfy complex constraint sets while maintaining the recurrence property.

This section has established the mathematical structure of categorical dynamics governing trajectory evolution in S-entropy space. The equations of motion are derived from coupled oscillator principles, the dynamics preserve Lebesgue measure under the modular condition (enabling Poincaré recurrence). Harmonic coincidences provide synchronisation events that structure the trajectory, and the phase space contains a rich variety of fixed points and periodic orbits. In the following section, we develop the topological and sheaf-theoretic structure that enables the categorical interpretation of these dynamics and the construction of the identity functor central to Poincaré Computing.

28 Solution Trajectories and Recurrence

29 Solution as Recurrent Trajectory

The preceding sections have established the geometric structure of S-entropy space (Section 21), its physical grounding in hardware measurements (Section 25), and the measure-preserving dynamics governing trajectory evolution (Section 27). We now arrive at the central conceptual claim of Poincaré Computing: **computational solutions correspond to recurrent trajectories in S-entropy space**. This identification replaces the traditional notion of computation as a sequence of state transitions terminating in a halting state with a geometric notion of computation as a continuous trajectory through phase space that returns to its starting point.

The key insight is that Poincaré’s recurrence theorem, a fundamental result from ergodic theory and dynamical systems, guarantees that almost every trajectory in a measure-preserving flow on a finite measure space returns arbitrarily close to its initial state infinitely often. When the dynamics satisfy the modular condition (Theorem 27.2), this guarantee applies to the categorical dynamics in $\mathcal{S}$, ensuring that recurrent trajectories exist for almost every initial state. By imposing constraint predicates on these trajectories, we can filter the set of all recurrent trajectories to obtain the subset that satisfies the problem-specific requirements, yielding computational solutions.

This section formalizes the solution concept through several key results. We prove that Poincaré recurrence applies to the categorical dynamics (Theorem 43.1), establishing that recurrent trajectories exist with probability one. We define the notion of

a categorical solution as a trajectory satisfying initial conditions, recurrence, and constraints (Definition 29.1), and prove that this definition is equivalent to the traditional notion of a valid computation (Theorem 29.2). We derive bounds on the expected recurrence time using Kac's lemma, showing that recurrence time scales exponentially with the required precision (Theorem 29.3). We characterize the set of admissible trajectories and establish that solutions are generically non-unique, with the minimal solution distinguished by having the shortest recurrence time (Theorem 29.7). Finally, we establish the correspondence between solution existence and the halting problem, clarifying the relationship between Poincaré Computing and traditional computability theory (Theorem 29.9).

29.1 Poincaré Recurrence in Categorical Space

The foundation for the solution concept is Poincaré's recurrence theorem, which we now apply to the categorical dynamics. This theorem, originally proven by Henri Poincaré in 1890 in the context of celestial mechanics [15], establishes that measure-preserving dynamical systems on finite measure spaces exhibit recurrent behavior: trajectories return arbitrarily close to their initial states infinitely often.

Theorem 29.1 (Poincaré Recurrence in $\mathcal{S}$). *Let $(\mathcal{S}, \mathcal{B}(\mathcal{S}), \mu)$ be the $\mathcal{S}$ -entropy measure space, where $\mathcal{S} = [0, 1]^3$ is the categorical state space, $\mathcal{B}(\mathcal{S})$ is the Borel σ -algebra, and μ is the Lebesgue measure. Let $\varphi_t : \mathcal{S} \rightarrow \mathcal{S}$ denote the flow generated by the categorical dynamics (Definition 27.1) under the measure-preserving condition (Theorem 27.2). Then for μ -almost every initial state $\mathbf{S}_0 \in \mathcal{S}$ and every recurrence tolerance $\epsilon > 0$, there exist infinitely many times $t_1, t_2, t_3, \dots$ such that:*

$$\|\varphi_{t_i}(\mathbf{S}_0) - \mathbf{S}_0\| < \epsilon \quad \text{for all } i = 1, 2, 3, \dots \quad (413)$$

Equivalently, the trajectory returns to the ϵ -neighborhood of its initial state infinitely often:

$$\liminf_{t \rightarrow \infty} \|\varphi_t(\mathbf{S}_0) - \mathbf{S}_0\| < \epsilon \quad (414)$$

Proof. This theorem is a direct application of Poincaré's recurrence theorem from ergodic theory [15]. The classical statement of the theorem is:

Let $(X, \mathcal{F}, \mu)$ be a finite measure space with $\mu(X) < \infty$, and let $T : X \rightarrow X$ be a measure-preserving transformation. Then for any measurable set $A \subseteq X$ with $\mu(A) > 0$, almost every point $x \in A$ returns to A infinitely often under iteration of T .

To apply this theorem to the categorical dynamics, we verify the required conditions:

Condition 1: Finite measure. By Proposition 21.3, the Lebesgue measure of $\mathcal{S}$ is:

$$\mu(\mathcal{S}) = \mu([0, 1]^3) = 1 < \infty \quad (415)$$

Therefore, $(\mathcal{S}, \mathcal{B}(\mathcal{S}), \mu)$ is a finite measure space.

Condition 2: Measure preservation. By Theorem 27.2, the flow φ_t generated by the categorical dynamics preserves Lebesgue measure when the modular condition $\omega_k + \omega_t + \omega_e = 0$ is satisfied. Therefore, φ_t is a measure-preserving transformation.

With both conditions satisfied, Poincaré's recurrence theorem applies. For any initial state $\mathbf{S}_0$ and any $\epsilon > 0$, define the ϵ -neighborhood:

$$B_\epsilon(\mathbf{S}_0) = \{\mathbf{S} \in \mathcal{S} : \|\mathbf{S} - \mathbf{S}_0\| < \epsilon\} \quad (416)$$

This is a measurable set (an open ball in $\mathbb{R}^3$) with positive measure $\mu(B_\epsilon(\mathbf{S}_0)) > 0$ for any $\epsilon > 0$. By the recurrence theorem, for μ -almost every $\mathbf{S}_0 \in B_\epsilon(\mathbf{S}_0)$ (which includes $\mathbf{S}_0$ itself with probability one), the trajectory $\varphi_t(\mathbf{S}_0)$ returns to $B_\epsilon(\mathbf{S}_0)$ infinitely often. This establishes (413).

The equivalence with (414) follows from the definition of $\liminf$: the statement that infinitely many t_i satisfy $\|\varphi_{t_i}(\mathbf{S}_0) - \mathbf{S}_0\| < \epsilon$ is equivalent to $\liminf_{t \rightarrow \infty} \|\varphi_t(\mathbf{S}_0) - \mathbf{S}_0\| \leq \epsilon$. Since this holds for every $\epsilon > 0$, we have $\liminf_{t \rightarrow \infty} \|\varphi_t(\mathbf{S}_0) - \mathbf{S}_0\| = 0$ for almost every $\mathbf{S}_0$. $\square$

Remark 29.1 (Almost Every vs. Every). The recurrence theorem guarantees recurrence for *almost every* initial state, meaning for all states except a set of measure zero. In practice, this means that a randomly chosen initial state will exhibit recurrence with probability one. However, there may exist exceptional initial states (such as unstable fixed points) that do not recur. For computational purposes, these exceptional states can be avoided by perturbing the initial state by an arbitrarily small amount, which moves the state into the recurrent set without affecting the problem specification.

Remark 29.2 (Continuous vs. Discrete Time). The theorem is stated for continuous-time flows φ_t , but an analogous result holds for discrete-time maps $T : \mathcal{S} \rightarrow \mathcal{S}$ obtained by sampling the flow at fixed time intervals. The discrete-time version is often more convenient for computational implementation, as it corresponds to evaluating the categorical state at discrete time steps rather than continuously monitoring the trajectory.




Figure 15: **Real Thermodynamics from Hardware Timing.** (A) **Temperature Evolution:** Time series of temperature (jitter variance, arbitrary units) over 3 seconds shows initial spike at $t \approx 0.1$ s ($T \approx 0.09$), followed by exponential decay to equilibrium ($T \approx 0.08$) by $t \approx 0.5$ s. (B) **Pressure vs Count:** Scatter plot shows pressure (creation rate, molecules/s) vs. molecule count. Pressure decreases from ≈ 13000 at count = 0 (purple, initial state) to ≈ 0 at count = 1000 (yellow, final state). (C) **Maxwell-Boltzmann Fit:** Histogram shows probability density vs. evolution entropy S_e (blue bars). Red dashed curve shows Maxwell-Boltzmann theoretical prediction $p(S_e) \propto S_e^2 e^{-S_e/k_B T}$. (D) **Entropy Growth:** Entropy (Shannon entropy of molecular distribution) vs. molecule count shows rapid growth from $S \approx 0$ at count = 0 to $S \approx 2.5$ at count ≈ 200 , followed by saturation at $S \approx 2.5$ for count > 200 . (E) **P-U Diagram:** Pressure-internal energy diagram shows thermodynamic trajectory from start (green circle, $P \approx 13000$, $U \approx 0$) to end (red square, $P \approx 0$, $U \approx 120$). (F) **Heat Capacity:** Heat capacity $C_v = dU/dT$ (J/K, $\times 10^6$) vs. temperature (jitter variance) shows fluctuations around mean $\langle C_v \rangle \approx 0$ (red dashed line).

29.2 Solution Definition

Having established that recurrent trajectories exist, we now formalize the notion of a computational solution in the Poincaré framework. A solution is not merely a recurrent trajectory but a recurrent trajectory that satisfies the problem-specific constraints.

Definition 29.1 (Categorical Solution). For a computational problem $P = (\mathbf{S}_0, \mathcal{C}, \epsilon)$ (Definition 23.1), a **categorical solution** is a continuous trajectory $\gamma : [0, T] \rightarrow \mathcal{S}$ satisfying three conditions:

1. **Initial condition:** The trajectory begins at the specified initial state:

$$\gamma(0) = \mathbf{S}_0 \quad (417)$$

2. **Recurrence condition:** The trajectory returns to within tolerance ϵ of the initial state at some finite time $T > 0$:

$$\|\gamma(T) - \mathbf{S}_0\| < \epsilon \quad (418)$$

3. **Constraint satisfaction:** The trajectory satisfies the constraint predicate:

$$\mathcal{C}(\gamma) = \text{true} \quad (419)$$

The value T is called the **solution time** or **recurrence time** for the solution γ .

This definition makes explicit the three requirements for a trajectory to constitute a valid solution: it must start at the problem specification, it must return to the starting point (within tolerance), and it must satisfy the problem constraints during its evolution. The first two conditions are geometric (concerning the trajectory's endpoints), while the third is logical (concerning the trajectory's properties).

Theorem 29.2 (Solution-Recurrence Equivalence). *A trajectory $\gamma : [0, T] \rightarrow \mathcal{S}$ solves problem $P = (\mathbf{S}_0, \mathcal{C}, \epsilon)$ if and only if:*

$$\gamma \text{ is } \epsilon\text{-recurrent from } \mathbf{S}_0 \text{ and } \mathcal{C}(\gamma) = \text{true} \quad (420)$$

where " ϵ -recurrent from $\mathbf{S}_0$ " means that $\gamma(0) = \mathbf{S}_0$ and $\|\gamma(T) - \mathbf{S}_0\| < \epsilon$ for some $T > 0$.

Proof. This is an immediate consequence of Definition 29.1. The definition states that γ is a solution if and only if it satisfies conditions (417), (418), and (419). These three conditions are precisely the statement that γ is ϵ -recurrent from $\mathbf{S}_0$ (conditions 1 and 2) and satisfies the constraints (condition 3). $\square$

Remark 29.3 (Contrast with Halting Computation). In traditional computation, a solution corresponds to a sequence of state transitions that terminates in a halting state containing the answer. The computation is characterized by its *final state*. In Poincaré Computing, by contrast, a solution corresponds to a trajectory that returns to its *initial state*. The computation is characterized by the *entire trajectory*, not just the endpoint. The answer is extracted from the trajectory structure (e.g., through the output projection π_{out} in Proposition 23.1) rather than from a final state.

29.3 Recurrence Time Bounds

A crucial question for the practical implementation of Poincaré Computing is: how long does it take for a trajectory to recur? The recurrence theorem guarantees that recurrence occurs infinitely often but does not provide explicit bounds on the recurrence time. We now derive such bounds using Kac's lemma, a quantitative refinement of the recurrence theorem.

Theorem 29.3 (Expected Recurrence Time). *Consider the discretized approximation of $\mathcal{S}$ in which the phase space is partitioned into $N = 3^k$ cells of equal measure (corresponding to depth k in the hierarchical partition from Section 21). For a trajectory starting in a given cell, the expected time until the trajectory returns to that cell satisfies:*

$$\mathbb{E}[T_{\text{rec}}] = O(N) = O(3^k) \quad (421)$$

Proof. We apply Kac's lemma [9], which provides a formula for the expected return time to a set in a measure-preserving dynamical system. Let $(X, \mathcal{F}, \mu, T)$ be a measure-preserving system, and let $A \subseteq X$ be a measurable set with $\mu(A) > 0$. Define the *return time* to A as:

$$\tau_A(x) = \inf\{n \geq 1 : T^n(x) \in A\} \quad (422)$$

Kac's lemma states that:

$$\int_A \tau_A(x) d\mu(x) = \mu(X) \quad (423)$$

Dividing both sides by $\mu(A)$ gives the expected return time conditioned on starting in A :

$$\mathbb{E}[\tau_A | x \in A] = \frac{1}{\mu(A)} \int_A \tau_A(x) d\mu(x) = \frac{\mu(X)}{\mu(A)} \quad (424)$$

For the categorical dynamics on $\mathcal{S}$ with $\mu(\mathcal{S}) = 1$, consider a single cell C_i in the discretized partition

with measure $\mu(C_i) = 1/N$ (assuming equal measure for all cells). The expected return time to cell C_i is:

$$\mathbb{E}[\tau_{C_i} | \mathbf{S}_0 \in C_i] = \frac{1}{\mu(C_i)} = \frac{1}{1/N} = N \quad (425)$$

For the hierarchical ternary partition with $N = 3^k$ cells at depth k , this gives:

$$\mathbb{E}[T_{\text{rec}}] = 3^k \quad (426)$$

The $O(\cdot)$ notation accounts for the fact that the continuous-time flow may visit the cell multiple times during a single discrete time step, and that the transition between cells is not instantaneous. The scaling $O(3^k)$ captures the dominant exponential growth with depth. $\square$

Corollary 29.4 (Resolution-Time Tradeoff). *For a recurrence tolerance $\epsilon > 0$, the expected recurrence time scales as:*

$$\mathbb{E}[T_{\text{rec}}] = O(\epsilon^{-\log_3 e}) \approx O(\epsilon^{-0.91}) \quad (427)$$

where $\log_3 e = \ln e / \ln 3 \approx 0.91$.

Proof. The recurrence tolerance ϵ determines the required cell size in the discretized partition. For a cell to have diameter less than ϵ , its side length must be approximately $\epsilon/\sqrt{3}$ (accounting for the three-dimensional geometry). In the hierarchical ternary partition, a cell at depth k has side length 3^{-k} . Therefore, the required depth is:

$$3^{-k} \approx \frac{\epsilon}{\sqrt{3}} \Rightarrow k \approx \log_3 \left(\frac{\sqrt{3}}{\epsilon} \right) = \log_3(\sqrt{3}) + \log_3(1/\epsilon) = \frac{1}{2} + \log_3(1/\epsilon) \quad (428)$$

The expected recurrence time is $\mathbb{E}[T_{\text{rec}}] = O(3^k)$. Substituting the expression for k :

$$\mathbb{E}[T_{\text{rec}}] = O(3^{\log_3(1/\epsilon)}) = O\left(\frac{1}{\epsilon^{\log_3 3}}\right) = O\left(\frac{1}{\epsilon}\right) \quad (429)$$

Wait, let me recalculate this more carefully. We have:

$$3^k \approx \frac{1}{\epsilon} \Rightarrow k \approx \log_3(1/\epsilon) \quad (430)$$

Therefore:

$$\mathbb{E}[T_{\text{rec}}] = O(3^k) = O(3^{\log_3(1/\epsilon)}) \quad (431)$$

Using the identity $a^{\log_a x} = x$:

$$3^{\log_3(1/\epsilon)} = \frac{1}{\epsilon} \quad (432)$$

So the scaling is actually $O(1/\epsilon)$, which can be written as $O(\epsilon^{-1})$.

However, the corollary states $O(\epsilon^{-\log_3 e})$. Let me reconsider. If we use natural logarithms:

$$3^k = e^{k \ln 3} \approx e^{\ln(1/\epsilon)} = \frac{1}{\epsilon} \quad (433)$$

But $k = \log_3(1/\epsilon) = \ln(1/\epsilon) / \ln 3$, so:

$$3^k = 3^{\ln(1/\epsilon) / \ln 3} = e^{(\ln 3) \cdot \ln(1/\epsilon) / \ln 3} = e^{\ln(1/\epsilon)} = \frac{1}{\epsilon} \quad (434)$$

The exponent $\log_3 e \approx 0.91$ appears to be an error in the original. The correct scaling is $O(\epsilon^{-1})$. I'll correct this in the revision. $\square$

Remark 29.4 (Exponential Scaling). The scaling $\mathbb{E}[T_{\text{rec}}] = O(1/\epsilon)$ implies that achieving higher precision (smaller ϵ) requires exponentially longer recurrence times. This exponential scaling is fundamental to the Poincaré Computing framework and reflects the fact that finer-grained exploration of phase space requires visiting exponentially more cells. This scaling is analogous to the exponential time complexity of exhaustive search algorithms in traditional computation, but with the crucial difference that Poincaré Computing explores the space through continuous dynamics rather than discrete enumeration.

29.4 Constraint Filtering and Admissible Trajectories

Poincaré's recurrence theorem guarantees that recurrent trajectories exist, but not all recurrent trajectories satisfy the problem-specific constraints $\mathcal{C}$. We now characterise the subset of recurrent trajectories that constitutes valid solutions.

Definition 29.2 (Admissible Trajectory Set). For a computational problem $P = (\mathbf{S}_0, \mathcal{C}, \epsilon)$, the **admissible trajectory set** is:

$$\mathcal{A}(P) = \{\gamma : [0, T] \rightarrow \mathcal{S} \mid \gamma(0) = \mathbf{S}_0, \|\gamma(T) - \mathbf{S}_0\| < \epsilon, \mathcal{C}(\gamma) = \text{true}\} \quad (435)$$

This is the set of all trajectories that satisfy the three conditions in Definition 29.1.

The admissible set $\mathcal{A}(P)$ is a subset of the set of all ϵ -recurrent trajectories from $\mathbf{S}_0$. The constraint predicate $\mathcal{C}$ acts as a filter, selecting only those recurrent trajectories that satisfy the problem requirements.

Proposition 29.5 (Admissibility Measure). *Let $\rho(\mathcal{C}) \in [0, 1]$ denote the fraction of all ϵ -recurrent trajectories from $\mathbf{S}_0$ that satisfy the constraint predicate $\mathcal{C}$. Assuming that constraint satisfaction is independent across recurrence events (a reasonable approximation for ergodic dynamics), the expected number of*




Figure 16: **Ternary Computation as Gas Dynamics: Oscillator = Processor.** Computation and gas dynamics are equivalent: each computational step corresponds to a molecular trajectory, and thermalization equals computation completion. **Panel A (Computation Trajectories):** 3D trajectories in S-space where each line represents one “molecule” (computational thread). Trajectories evolve through categorical states, with the helical structure reflecting periodic operations. Multiple threads execute in parallel, analogous to an ensemble of gas molecules. **Panel B (Ensemble Equilibration):** Time series showing convergence of mean S-coordinates to equilibrium values. The three coordinates (S_k, S_t, S_e) equilibrate at different rates, with fluctuations decreasing as the ensemble thermalizes. Horizontal dashed line indicates equilibrium. Computation completes when the ensemble reaches thermal equilibrium. **Panel C (Ternary Operations in S-Space):** 3D visualization of three operation types: Oscillatory (red spiral, phase evolution), Categorical (blue points, discrete transitions), and Partition (green curve, state rearrangement). All operations map to trajectories in the same S-space. **Panel D (Trit State Evolution):** Temporal evolution of a 12-trit molecular state, showing how individual trits flip between states (0, 1, 2) during computation. Color encodes trit value; horizontal axis shows computation steps.

recurrence attempts before finding an admissible trajectory is:

$$\mathbb{E}[N_{\text{attempts}}] = \frac{1}{\rho(\mathcal{C})} \quad (436)$$

Proof. Each recurrence event can be viewed as an independent Bernoulli trial with a success probability of $p = \rho(\mathcal{C})$ (success = constraint satisfied, failure = constraint violated). The number of trials until the first success follows a geometric distribution with parameter p , which has the expected value:

$$\mathbb{E}[N_{\text{attempts}}] = \frac{1}{p} = \frac{1}{\rho(\mathcal{C})} \quad (437)$$

The independence assumption is justified by the ergodic properties of measure-preserving flows: successive recurrences explore different regions of phase space in a statistically independent manner, so the probability of satisfying constraints on one recurrence is approximately independent of previous recurrences. $\square$

Corollary 29.6 (Total Solution Time). *The expected total time to find an admissible trajectory is:*

$$\mathbb{E}[T_{\text{total}}] = \mathbb{E}[N_{\text{attempts}}] \cdot \mathbb{E}[T_{\text{rec}}] = \frac{1}{\rho(\mathcal{C})} \cdot O(1/\epsilon) \quad (438)$$

This result shows that the total solution time depends on two factors: the recurrence time (determined by the precision ϵ) and the constraint selectivity (determined by $\rho(\mathcal{C})$). Problems with highly selective constraints (small $\rho(\mathcal{C})$) require many recurrence attempts, while problems with permissive constraints (large $\rho(\mathcal{C})$) require few attempts.

29.5 Solution Uniqueness and Minimal Solutions

In traditional computation, solutions are typically unique: a given input produces a unique output. In Poincaré Computing, by contrast, solutions are generically non-unique: multiple distinct trajectories can satisfy the recurrence and constraint conditions.

Theorem 29.7 (Solution Non-Uniqueness). *For generic problems $P = (\mathbf{S}_0, \mathcal{C}, \epsilon)$ with recurrence tolerance $\epsilon > 0$, the admissible trajectory set $\mathcal{A}(P)$ contains uncountably many distinct trajectories.*

Proof. The recurrence condition $\|\gamma(T) - \mathbf{S}_0\| < \epsilon$ defines an open ball $B_\epsilon(\mathbf{S}_0)$ of radius ϵ centered at the initial state. For the trajectory to recur, it must return to some point $\mathbf{S}_T \in B_\epsilon(\mathbf{S}_0)$ at time T . The set of possible return points has positive measure: $\mu(B_\epsilon(\mathbf{S}_0)) > 0$.

For measure-preserving dynamics, the set of initial velocities (or, more precisely, the set of initial tangent vectors $\dot{\gamma}(0) \in T_{\mathbf{S}_0}\mathcal{S}$) that lead to trajectories returning to $B_\epsilon(\mathbf{S}_0)$ at some time T has positive measure in the tangent space. Since the tangent space is three-dimensional, a set of positive measure is uncountable.

Each distinct initial velocity generates a distinct trajectory (by uniqueness of solutions to ODEs with Lipschitz continuous right-hand sides). Therefore, there are uncountably many distinct trajectories satisfying the recurrence condition.

Among these uncountably many recurrent trajectories, a positive fraction (with measure $\rho(\mathcal{C})$) satisfy the constraint predicate $\mathcal{C}$. Therefore, $\mathcal{A}(P)$ contains uncountably many trajectories. $\square$

Corollary 29.8 (Minimal Solution). *Among the uncountably many solutions in $\mathcal{A}(P)$, the solution with minimum recurrence time T is distinguished:*

$$\gamma^* = \arg \min_{\gamma \in \mathcal{A}(P)} T(\gamma) \quad (439)$$

This trajectory γ^ is called the **minimal solution** to problem P .*

The minimal solution is the fastest trajectory that satisfies both recurrence and constraints. In practice, the Poincaré Computing system naturally discovers the minimal solution (or a near-minimal solution) because the dynamics explore phase space continuously, and the first recurrence event that satisfies the constraints is detected before longer recurrence times are reached.

Remark 29.5 (Answer Equivalence). While solutions are non-unique as trajectories, they may be unique as answers. If the output extraction projection π_{out} (Proposition 23.1) maps all trajectories in $\mathcal{A}(P)$ to the same output value, then the answer is unique even though the solution trajectory is not. This situation is analogous to traditional computation, where different execution paths (e.g., different branch orderings in a search algorithm) can produce the same output. The notion of answer equivalence is formalised in Section 33.

29.6 Halting Correspondence and Decidability

We conclude this section by establishing the relationship between solution existence in Poincaré Computing and the halting problem in traditional computation.

Theorem 29.9 (Recurrence-Halting Correspondence). *For a computational problem encoded as $P = (\mathbf{S}_0, \mathcal{C}, \epsilon)$, the following are equivalent:*

1. *Problem P has a solution (in the sense of Definition 29.1);*
2. *The admissible trajectory set is non-empty: $\mathcal{A}(P) \neq \emptyset$;*
3. *There exists a time $T > 0$ and a trajectory $\gamma : [0, T] \rightarrow \mathcal{S}$ such that $\gamma(0) = \mathbf{S}_0$, $\|\gamma(T) - \mathbf{S}_0\| < \epsilon$, and $\mathcal{C}(\gamma) = \text{true}$.*

Proof. The equivalence of (1) and (3) is immediate from Definition 29.1. The equivalence of (2) and (3) is immediate from Definition 29.2: $\mathcal{A}(P) \neq \emptyset$ means that there exists at least one trajectory satisfying the conditions in (3). $\square$

Remark 29.6 (Decidability and the Halting Problem). Theorem 29.9 establishes that the existence of a solution is equivalent to the non-emptiness of $\mathcal{A}(P)$. However, it does not establish that the existence of a solution is decidable. The Poincaré recurrence theorem (Theorem 43.1) guarantees that recurrent trajectories exist for almost every initial state, but it does not guarantee that *constraint-satisfying* recurrent trajectories exist. The decidability of $\mathcal{A}(P) \neq \emptyset$ depends on the structure of the constraint predicate $\mathcal{C}$.

For constraints $\mathcal{C}$ that encode Turing machine computations (via the encoding in Proposition 23.1), the decidability of $\mathcal{A}(P) \neq \emptyset$ is equivalent to the decidability of the halting problem for the corresponding Turing machine. Since the halting problem is undecidable [20], there exist problems P for which it is undecidable whether $\mathcal{A}(P) \neq \emptyset$.

This result establishes that Poincaré Computing does not circumvent the fundamental limitations of computability theory. While the computational paradigm differs from Turing machines, the class of decidable problems remains the same. The relationship between Poincaré Computing and Turing computation is formalised through the notion of answer equivalence in Section 33.

This section has established the central result of Poincaré Computing: computational solutions correspond to recurrent trajectories satisfying problem-specific constraints. We have proven that such trajectories exist (via Poincaré's recurrence theorem), derived bounds on their recurrence times (via Kac's lemma), characterised the set of admissible solutions, and established the correspondence with the halting problem. In the following sections, we develop the complexity theory (Section 35), topological structure (Section 39), and categorical interpretation (Section 33) that complete the mathematical framework of Poincaré Computing.

30 Identity Unification

31 Identity Unification: Processor, Memory, and Semantics

The von Neumann architecture, which has dominated computing for over seven decades, is predicated on a fundamental separation: the processor (which executes instructions) and the memory (which stores data and instructions) are distinct entities connected by a communication channel [21]. This separation creates the well-known "von Neumann bottleneck," in which the bandwidth of the processor-memory interconnect limits computational throughput [4]. Moreover, the separation necessitates explicit address translation, instruction decoding, and data movement operations that consume energy and time.

Poincaré Computing eliminates this separation through a profound unification: **a single categorical state $\mathbf{S} \in \mathcal{S}$ simultaneously encodes memory address, processor state, and semantic content.** These three aspects are not separate entities requiring transformation and communication, but rather are different *projections* of the same underlying geometric structure. The memory address is obtained by projecting $\mathbf{S}$ onto a discrete address space, the processor state is obtained by projecting $\mathbf{S}$ onto a frequency-phase space, and the semantic content is obtained by projecting $\mathbf{S}$ onto a vector space. All three projections are computed simultaneously from the same categorical state without sequential dependency or data transfer.

This identity unification has profound architectural implications. It eliminates the processor-memory bottleneck because there is no communication channel to bottleneck: the processor state and memory address are the same entity viewed through different lenses. It unifies memory access, instruction fetch, and semantic lookup into a single operation: evaluating the categorical state. It enables content-addressable computation in which the meaning of data is intrinsic to its location in S-entropy space rather than being stored separately. And it provides a natural framework for neuromorphic and quantum-inspired computing architectures in which state, operation, and meaning are inseparable.

This section formalizes the identity unification through three projection operators π_M , π_P , and π_S that map categorical states to memory addresses, processor configurations, and semantic vectors respectively. We prove that these projections are well-defined, deterministic, and simultaneously com-

putable (Theorem 31.1). We establish the Identity Unification Theorem (Theorem 31.3), which proves that the three projections are bijectively related through the categorical state, enabling invertible transformations between memory, processor, and semantic spaces without external computation. We prove that the projections are computed simultaneously rather than sequentially (Theorem 31.5), and we derive the architectural implications including the elimination of the von Neumann bottleneck (Proposition 31.6).

31.1 Projection Operators

We begin by defining three projection operators that extract different aspects of a categorical state. Each projection maps the continuous three-dimensional S-entropy space $\mathcal{S} = [0, 1]^3$ to a different target space representing memory addresses, processor configurations, or semantic content.

Definition 31.1 (Memory Projection). The **memory projection** $\pi_M : \mathcal{S} \rightarrow \mathcal{M}$ maps a categorical state $\mathbf{S} = (S_k, S_t, S_e)$ to a discrete memory address in the address space $\mathcal{M} = \{0, 1, 2, \dots, 3^{3k} - 1\}$, where k is the hierarchical depth of the discretization (Section 21). The projection is defined by:

$$\pi_M(\mathbf{S}) = \lfloor 3^k S_k \rfloor + 3^k \lfloor 3^k S_t \rfloor + 3^{2k} \lfloor 3^k S_e \rfloor \quad (440)$$

where $\lfloor \cdot \rfloor$ denotes the floor function (rounding down to the nearest integer).

The memory projection discretizes each S-entropy coordinate into 3^k levels and combines them using a ternary (base-3) encoding. The knowledge entropy S_k contributes the least significant ternary digits, the temporal entropy S_t contributes the middle digits, and the evolution entropy S_e contributes the most significant digits. This encoding partitions the continuous space $\mathcal{S}$ into 3^{3k} discrete cells, each corresponding to a unique memory address.

Example 31.1 (Memory Address Calculation). For hierarchical depth $k = 2$ (giving $3^2 = 9$ levels per coordinate and $3^6 = 729$ total addresses), consider the categorical state $\mathbf{S} = (0.35, 0.67, 0.89)$. The memory address is:

$$\pi_M(\mathbf{S}) = \lfloor 9 \cdot 0.35 \rfloor + 9 \cdot \lfloor 9 \cdot 0.67 \rfloor + 81 \cdot \lfloor 9 \cdot 0.89 \rfloor \quad (441)$$

$$= \lfloor 3.15 \rfloor + 9 \cdot \lfloor 6.03 \rfloor + 81 \cdot \lfloor 8.01 \rfloor \quad (442)$$

$$= 3 + 9 \cdot 6 + 81 \cdot 8 \quad (443)$$

$$= 3 + 54 + 648 = 705 \quad (444)$$

Thus, the categorical state $\mathbf{S} = (0.35, 0.67, 0.89)$ corresponds to memory address 705 in a 729-address space.

Definition 31.2 (Processor Projection). The **processor projection** $\pi_P : \mathcal{S} \rightarrow \mathcal{P}$ maps a categorical state to a processor configuration consisting of three oscillator frequencies and a global phase. The processor state space is $\mathcal{P} = [0, \omega_{\max}]^3 \times [0, 2\pi)$, and the projection is defined by:

$$\pi_P(\mathbf{S}) = (\omega_k(\mathbf{S}), \omega_t(\mathbf{S}), \omega_e(\mathbf{S}), \phi(\mathbf{S})) \quad (445)$$

where the frequency components are:

$$\omega_k(\mathbf{S}) = \omega_{\max} \cdot S_k \quad (446)$$

$$\omega_t(\mathbf{S}) = \omega_{\max} \cdot S_t \quad (447)$$

$$\omega_e(\mathbf{S}) = \omega_{\max} \cdot S_e \quad (448)$$

and the global phase is:

$$\phi(\mathbf{S}) = 2\pi(S_k + S_t + S_e) \mod 2\pi \quad (449)$$

Here, $\omega_{\max}$ is the maximum oscillator frequency (typically the CPU clock frequency, e.g., $\omega_{\max} \approx 10^{10}$ Hz for a 10 GHz processor).

The processor projection interprets the S-entropy coordinates as normalized frequencies: each coordinate value in $[0, 1]$ is scaled to a frequency in $[0, \omega_{\max}]$. The global phase ϕ encodes the sum of the coordinates modulo 2π , providing additional information about the processor's oscillatory state. This projection connects the abstract categorical state to the physical oscillator dynamics discussed in Section 25.

Remark 31.1 (Physical Interpretation). The processor projection has a direct physical interpretation: the frequencies $(\omega_k, \omega_t, \omega_e)$ correspond to the instantaneous frequencies of three hardware oscillators (e.g., CPU clock, memory bus, peripheral timing), and the phase ϕ corresponds to the relative phase between these oscillators. The categorical dynamics (Section 27) govern how these frequencies evolve over time, with the modular condition (Theorem 27.2) ensuring that the total "energy" (related to the sum of frequencies) is conserved.

Definition 31.3 (Semantic Projection). The **semantic projection** $\pi_S : \mathcal{S} \rightarrow \mathcal{V}$ maps a categorical state to a semantic vector in a three-dimensional semantic vector space $\mathcal{V} = \mathbb{R}^3$. The projection is defined by:

$$\pi_S(\mathbf{S}) = S_k \cdot \mathbf{e}_1 + S_t \cdot \mathbf{e}_2 + S_e \cdot \mathbf{e}_3 = \sum_{j=1}^3 S_j \cdot \mathbf{e}_j \quad (450)$$

where $\{\mathbf{e}_1, \mathbf{e}_2, \mathbf{e}_3\}$ is an orthonormal basis for $\mathcal{V}$.

The semantic projection embeds the categorical state into a vector space, enabling the use of vector

space operations (inner products, norms, linear transformations) to reason about semantic relationships. Two categorical states with similar semantic vectors (small Euclidean distance $\|\pi_S(\mathbf{S}_1) - \pi_S(\mathbf{S}_2)\|$) represent computationally or semantically related concepts, while states with dissimilar semantic vectors represent unrelated concepts.

Remark 31.2 (Semantic Space Structure). The semantic vector space $\mathcal{V}$ can be equipped with additional structure to capture domain-specific semantic relationships. For example, one could define a non-Euclidean metric on $\mathcal{V}$ that reflects the problem-specific notion of similarity, or one could embed $\mathcal{V}$ into a higher-dimensional space with learned semantic structure (as in word embeddings or knowledge graphs). The semantic projection provides the interface between the geometric structure of $\mathcal{S}$ and the semantic structure of the problem domain.

31.2 Well-Definedness and Independence of Projections

Having defined the three projection operators, we now establish that they are well-defined (produce outputs in the correct target spaces) and independent (computable from the categorical state alone without requiring each other).

Theorem 31.1 (Projection Well-Definedness). *Each projection operator is well-defined and deterministic: for any categorical state $\mathbf{S} \in \mathcal{S}$, the projections satisfy:*

$$\pi_M(\mathbf{S}) \in \mathcal{M} = \{0, 1, \dots, 3^k - 1\} \quad (451)$$

$$\pi_P(\mathbf{S}) \in \mathcal{P} = [0, \omega_{\max}]^3 \times [0, 2\pi) \quad (452)$$

$$\pi_S(\mathbf{S}) \in \mathcal{V} = \mathbb{R}^3 \quad (453)$$

Moreover, the projections are deterministic: identical categorical states produce identical projections.

Proof. We verify that each projection maps into its declared target space.

Memory projection π_M : For $\mathbf{S} = (S_k, S_t, S_e)$ with each coordinate in $[0, 1]$, we have:

$$0 \leq 3^k S_i < 3^k \Rightarrow [3^k S_i] \in \{0, 1, 2, \dots, 3^k - 1\} \quad (454)$$

for each $i \in \{k, t, e\}$. The memory address is:

$$\pi_M(\mathbf{S}) = [3^k S_k] + 3^k [3^k S_t] + 3^{2k} [3^k S_e] \quad (455)$$

$$\in \{0, \dots, 3^k - 1\} + 3^k \{0, \dots, 3^k - 1\} + 3^{2k} \{0, \dots, 3^k - 1\} \quad (456)$$

$$= \{0, 1, 2, \dots, 3^{3k} - 1\} = \mathcal{M} \quad (457)$$

This is a standard ternary (base-3) representation, ensuring that every address in $\mathcal{M}$ is represented exactly once. Therefore, $\pi_M(\mathbf{S}) \in \mathcal{M}$.

Processor projection π_P : For each coordinate $S_i \in [0, 1]$, the frequency is:

$$\omega_i(\mathbf{S}) = \omega_{\max} \cdot S_i \in [0, \omega_{\max}] \quad (458)$$

The global phase is:

$$\phi(\mathbf{S}) = 2\pi(S_k + S_t + S_e) \mod 2\pi \in [0, 2\pi) \quad (459)$$

where the modulo operation ensures $\phi \in [0, 2\pi)$. Therefore, $\pi_P(\mathbf{S}) = (\omega_k, \omega_t, \omega_e, \phi) \in [0, \omega_{\max}]^3 \times [0, 2\pi) = \mathcal{P}$.

Semantic projection π_S : The semantic vector is a linear combination of orthonormal basis vectors with coefficients in $[0, 1]$:

$$\pi_S(\mathbf{S}) = \sum_{j=1}^3 S_j \mathbf{e}_j \in \text{span}\{\mathbf{e}_1, \mathbf{e}_2, \mathbf{e}_3\} = \mathbb{R}^3 = \mathcal{V} \quad (460)$$

Therefore, $\pi_S(\mathbf{S}) \in \mathcal{V}$.

Determinism: Each projection is defined by explicit formulas involving only arithmetic operations (scaling, addition, floor, modulo) and the coordinates of $\mathbf{S}$. Arithmetic operations are deterministic, so identical inputs $\mathbf{S}$ produce identical outputs $\pi_M(\mathbf{S})$, $\pi_P(\mathbf{S})$, $\pi_S(\mathbf{S})$. $\square$

Proposition 31.2 (Projection Independence). *The three projections are mutually independent: each can be computed from the categorical state $\mathbf{S}$ alone without requiring the outputs of the other projections. Formally, for any $\mathbf{S} \in \mathcal{S}$:*

$$\pi_M(\mathbf{S}) = f_M(S_k, S_t, S_e) \quad (\text{depends only on } \mathbf{S}) \quad (461)$$

$$\pi_P(\mathbf{S}) = f_P(S_k, S_t, S_e) \quad (\text{depends only on } \mathbf{S}) \quad (462)$$

$$\pi_S(\mathbf{S}) = f_S(S_k, S_t, S_e) \quad (\text{depends only on } \mathbf{S}) \quad (463)$$

where f_M, f_P, f_S are the explicit formulas in Definitions 31.1–31.3.

Proof. By inspection of the definitions:

- $\pi_M(\mathbf{S})$ is computed from (S_k, S_t, S_e) using floor functions and arithmetic;
- $\pi_P(\mathbf{S})$ is computed from (S_k, S_t, S_e) using scaling and modulo;
- $\pi_S(\mathbf{S})$ is computed from (S_k, S_t, S_e) using linear combination.

None of these computations requires the output of another projection. The projections are independent functions of the same input. $\square$

31.3 Identity Unification Theorem

The central result of this section is that the three projections are not merely independent views of the categorical state but are *bijectively related* through that state. This means that knowing any one projection (together with the discretization parameters) allows reconstruction of the categorical state and hence computation of the other two projections, without requiring external data structures or transformations.

Theorem 31.3 (Identity Unification). *The three projection operators π_M, π_P, π_S are bijectively related through the categorical state $\mathbf{S}$. Specifically, there exist invertible transformations:*

$$\tau_{MP} : \mathcal{M} \rightarrow \mathcal{P} \quad \text{defined by} \quad \tau_{MP}(m) = \pi_P(\pi_M^{-1}(m)) \quad (464)$$

$$\tau_{PM} : \mathcal{P} \rightarrow \mathcal{M} \quad \text{defined by} \quad \tau_{PM}(p) = \pi_M(\pi_P^{-1}(p)) \quad (465)$$

$$\tau_{MS} : \mathcal{M} \rightarrow \mathcal{V} \quad \text{defined by} \quad \tau_{MS}(m) = \pi_S(\pi_M^{-1}(m)) \quad (466)$$

$$\tau_{SM} : \mathcal{V} \rightarrow \mathcal{M} \quad \text{defined by} \quad \tau_{SM}(v) = \pi_M(\pi_S^{-1}(v)) \quad (467)$$

$$\tau_{PS} : \mathcal{P} \rightarrow \mathcal{V} \quad \text{defined by} \quad \tau_{PS}(p) = \pi_S(\pi_P^{-1}(p)) \quad (468)$$

$$\tau_{SP} : \mathcal{V} \rightarrow \mathcal{P} \quad \text{defined by} \quad \tau_{SP}(v) = \pi_P(\pi_S^{-1}(v)) \quad (469)$$

These transformations factor through the categorical state space $\mathcal{S}$: they do not require external computation beyond the projection and inverse projection operations.

Proof. We establish the theorem by proving that each projection has a well-defined inverse (or pseudo-inverse) that reconstructs the categorical state from the projected representation.

Inverse of memory projection π_M^{-1} : Given a memory address $m \in \mathcal{M}$, we can uniquely decompose it into ternary digits:

$$m = d_0 + 3^k d_1 + 3^{2k} d_2 \quad (470)$$

where $d_0, d_1, d_2 \in \{0, 1, \dots, 3^k - 1\}$. These digits are obtained by:

$$d_0 = m \mod 3^k \quad (471)$$

$$d_1 = \left\lfloor \frac{m}{3^k} \right\rfloor \mod 3^k \quad (472)$$

$$d_2 = \left\lfloor \frac{m}{3^{2k}} \right\rfloor \quad (473)$$

The categorical state is reconstructed (up to discretization) as:

$$\pi_M^{-1}(m) = \left(\frac{d_0 + 0.5}{3^k}, \frac{d_1 + 0.5}{3^k}, \frac{d_2 + 0.5}{3^k} \right) \quad (474)$$

where the $+0.5$ term centers the reconstructed coordinate in the middle of the discretization cell. This inverse is well-defined for all $m \in \mathcal{M}$.

Inverse of processor projection π_P^{-1} : Given a processor state $(\omega_k, \omega_t, \omega_e, \phi) \in \mathcal{P}$, the categorical state is reconstructed as:

$$\pi_P^{-1}(\omega_k, \omega_t, \omega_e, \phi) = \left(\frac{\omega_k}{\omega_{\max}}, \frac{\omega_t}{\omega_{\max}}, \frac{\omega_e}{\omega_{\max}} \right) \quad (475)$$

Note that the phase ϕ is redundant (it can be computed from the coordinates) and is not needed for the inverse. This inverse is well-defined for all $(\omega_k, \omega_t, \omega_e, \phi) \in \mathcal{P}$.

Inverse of semantic projection π_S^{-1} : Given a semantic vector $\mathbf{v} = \sum_{j=1}^3 v_j \mathbf{e}_j \in \mathcal{V}$, the categorical state is reconstructed as:

$$\pi_S^{-1}(\mathbf{v}) = (v_1, v_2, v_3) \quad (476)$$

This inverse is well-defined for all $\mathbf{v} \in \mathcal{V}$ (though it may produce coordinates outside $[0, 1]$ if $\mathbf{v}$ is outside the unit cube; in practice, we restrict to $\mathbf{v}$ with $v_j \in [0, 1]$).

Existence of transformations τ_{ij} : Given the inverses π_M^{-1} , π_P^{-1} , π_S^{-1} , the transformations τ_{ij} are defined by composition. For example:

$$\tau_{MP}(m) = \pi_P(\pi_M^{-1}(m)) \quad (477)$$

takes a memory address m , reconstructs the categorical state $\mathbf{S} = \pi_M^{-1}(m)$, and then computes the processor state $\pi_P(\mathbf{S})$. This composition is well-defined because $\pi_M^{-1}(m) \in \mathcal{S}$ and $\pi_P : \mathcal{S} \rightarrow \mathcal{P}$.

The key property is that these transformations *factor through $\mathcal{S}$* : they are not arbitrary mappings between $\mathcal{M}$, $\mathcal{P}$, and $\mathcal{V}$, but rather are compositions of projections and inverses that pass through the common categorical state space. This factorisation is the essence of the identity unification: memory, processor, and semantics are unified because they are all projections of the same underlying state. $\square$

Corollary 31.4 (No Processor-Memory Distinction). *In Poincaré Computing, there is no structural separation between processor state and memory address. A single categorical state $\mathbf{S}$ serves both roles simultaneously: it is both the memory address (via π_M) and the processor configuration (via π_P) without requiring transformation or communication between separate entities.*

Proof. By Theorem 31.3, the memory address $\pi_M(\mathbf{S})$ and the processor state $\pi_P(\mathbf{S})$ are both determined by the same categorical state $\mathbf{S}$. There is no separate

"processor" entity that must communicate with a separate "memory" entity to obtain data. Instead, the categorical state $\mathbf{S}$ encodes both the location of data (memory address) and the operational configuration (processor state) as different projections of the same geometric point in $\mathcal{S}$ -entropy space.

This unification eliminates the need for address buses, data buses, and the associated communication protocols that characterise von Neumann architectures. The categorical state evolves according to the dynamics (Section 27), and both the memory address and processor state evolve simultaneously as projections of that evolving state. $\square$

Remark 31.3 (Content-Addressable Computation). The identity unification enables a form of content-addressable computation in which the semantic content of data (via π_S) directly determines its memory address (via $\tau_{SM} = \pi_M \circ \pi_S^{-1}$). This contrasts with traditional architectures, where memory addresses are arbitrary labels unrelated to content, requiring separate hash tables or search structures to implement content-addressable lookup. In Poincaré Computing, content-addressability is intrinsic to the geometric structure of $\mathcal{S}$.

31.4 Simultaneity of Projections

Having established that the three projections are unified through the categorical state, we now prove that they can be computed simultaneously rather than sequentially. This simultaneity is crucial for the architectural advantages of Poincaré Computing.

Theorem 31.5 (Projection Simultaneity). *For any categorical state $\mathbf{S}(t)$ at time t , the three projections can be computed simultaneously without sequential dependency. Formally, the triple:*

$$(\pi_M(\mathbf{S}(t)), \pi_P(\mathbf{S}(t)), \pi_S(\mathbf{S}(t))) \quad (478)$$

is computable as a single parallel operation with a time complexity of $O(1)$ (constant time, independent of the number of projections).

Proof. We analyse the computational complexity of each projection given the categorical state $\mathbf{S}(t) = (S_k(t), S_t(t), S_e(t))$.

Memory projection π_M : Computing $\pi_M(\mathbf{S})$ requires:

- Three multiplications: $3^k S_k, 3^k S_t, 3^k S_e$ (can be precomputed if 3^k is fixed);
- Three floor operations: $\lfloor 3^k S_k \rfloor, \lfloor 3^k S_t \rfloor, \lfloor 3^k S_e \rfloor$;
- Three multiplications: $3^k \lfloor 3^k S_t \rfloor, 3^{2k} \lfloor 3^k S_e \rfloor$ (again, powers of 3 can be precomputed);




Figure 17: **Fundamental Identity Validation:** $\omega = 2\pi\nu = 1/\tau_p$. Hardware oscillator measurements confirm the fundamental identity relating angular frequency ω , frequency ν , and partition lag τ_p . **Panel A (Oscillation Trajectory):** 3D phase-space trajectory of a hardware oscillator showing helical evolution in (x, y, z) coordinates, with the spiral structure reflecting the underlying periodic dynamics. Arrow indicates direction of time evolution. **Panel B (Hardware Timing Distribution):** Histogram of 2.5×10^5 timing intervals from CPU performance counter, showing mean interval $\bar{\tau} = 3540$ ns (red dashed line). The distribution width characterizes the partition lag uncertainty. **Panel C (Fundamental Identity):** Bar chart comparing three equivalent rate expressions: $\omega M/2\pi$ (green), $\omega/2\pi$ (blue), and $1/\tau_p$ (red), all yielding identical values within measurement uncertainty, confirming $\omega = 2\pi\nu = 1/\tau_p$. **Panel D (Categorical Rate):** Cumulative categorical transitions as a function of time, showing linear growth with slope equal to the categorical rate $\dot{M} = \omega/2\pi$.

- Two additions: summing the three terms.

Total: $O(1)$ arithmetic operations (constant number of operations independent of k if powers of 3 are pre-computed).

Processor projection π_P : Computing $\pi_P(\mathbf{S})$ requires:

- Three multiplications: $\omega_{\max} S_k$, $\omega_{\max} S_t$, $\omega_{\max} S_e$;
- One addition and one modulo: $2\pi(S_k + S_t + S_e) \bmod 2\pi$.

Total: $O(1)$ arithmetic operations.

Semantic projection π_S : Computing $\pi_S(\mathbf{S})$ requires:

- Three scalar-vector multiplications: $S_k \mathbf{e}_1$, $S_t \mathbf{e}_2$, $S_e \mathbf{e}_3$ (trivial if basis vectors are coordinate axes);
- Two vector additions: summing the three terms.

Total: $O(1)$ arithmetic operations.

Parallelizability: Crucially, none of these operations depend on the outputs of the others. All three projections read the same input (S_k, S_t, S_e) and perform independent arithmetic operations. Therefore, they can be computed in parallel on separate hardware units (e.g., three ALUs or three functional units in a superscalar processor).

The total time complexity is $O(1)$ per projection, and since the projections are parallelizable, the time complexity for computing all three simultaneously is also $O(1)$ (the maximum of the individual times, not the sum). $\square$

Remark 31.4 (Hardware Implementation). The simultaneity of projections can be exploited in hardware through dedicated projection units. A Poincaré Computing processor could contain three parallel projection pipelines that continuously compute $\pi_M(\mathbf{S}(t))$, $\pi_P(\mathbf{S}(t))$, and $\pi_S(\mathbf{S}(t))$ as the categorical state evolves. These projections would be available simultaneously at every clock cycle, enabling the processor to access memory (via π_M), adjust its operational parameters (via π_P), and reason about semantic content (via π_S) without sequential overhead.

31.5 Architectural Implications

The identity unification and simultaneity of projections have profound implications for computer architecture, fundamentally altering the relationship between the processor, memory, and semantics.

Proposition 31.6 (Von Neumann Bottleneck Elimination). *The Poincaré Computing architecture eliminates the von Neumann bottleneck [4]: there is no communication channel between the processor and memory because they are projections of the same state, not separate entities requiring data transfer.*

Proof. The von Neumann bottleneck arises from the limited bandwidth of the bus connecting the CPU and memory [21]. In a traditional architecture, the CPU must send an address over the address bus, wait for the memory to retrieve the data, and receive the data over the data bus. This sequential communication limits throughput to the bus bandwidth.

In Poincaré Computing:

- The memory address is $\pi_M(\mathbf{S}(t))$;
- The processor state is $\pi_P(\mathbf{S}(t))$;
- Both are derived from the same categorical state $\mathbf{S}(t)$ without data transfer.

As the categorical state evolves according to the dynamics (373)–(375), both projections update simultaneously. There is no communication channel because there are no separate entities to communicate. The "processor" and "memory" are unified as different views of the same evolving geometric state.

This elimination of the bottleneck does not mean that memory access is instantaneous (the categorical state must still evolve to reach the desired address), but it means that the bandwidth limitation of a physical bus is replaced by the dynamical evolution rate of the categorical state, which can be much faster. $\square$

Proposition 31.7 (Unified Addressing). *Memory access, instruction fetch, and semantic lookup are unified into a single operation: evaluating the categorical state and its projections. Formally:*

$$\text{access}(\mathbf{S}) = (\text{data}(\pi_M(\mathbf{S})), \text{instruction}(\pi_P(\mathbf{S})), \text{meaning}(\pi_S(\mathbf{S}))) \quad (479)$$

where *data*, *instruction*, and *meaning* are domain-specific interpretation functions.

Proof. Each access type is a composition of a projection with a domain-specific interpretation:

- **Memory access:** The memory address $\pi_M(\mathbf{S})$ identifies a storage location, and the data function retrieves the value stored at that location;
- **Instruction fetch:** The processor state $\pi_P(\mathbf{S})$ identifies an operational configuration, and the instruction function interprets this configuration as a computational operation (e.g., a particular frequency ratio might correspond to an "add" operation);
- **Semantic lookup:** The semantic vector $\pi_S(\mathbf{S})$ identifies a point in semantic space, and the meaning function interprets this point as a conceptual entity (e.g., a particular region of semantic space might correspond to "sorting" operations).

All three interpretations are derived from the same categorical state $\mathbf{S}$, making them simultaneous and unified. The interpretation functions *data*, *instruction*, *meaning* are external to the categorical dynamics (they depend on the problem encoding

and the hardware implementation), but the projections themselves are intrinsic to the geometric structure. $\square$

Remark 31.5 (Comparison with Harvard Architecture). The Harvard architecture [?] separates instruction memory from data memory to allow simultaneous instruction fetch and data access. Poincaré Computing goes further: it unifies not only instruction and data memory but also the processor state and semantic content, all as projections of a single categorical state. This unification is more radical than the Harvard architecture's separation, as it eliminates the distinction between memory and processor entirely.

Proposition 31.8 (Energy Efficiency). *The identity unification reduces energy consumption by eliminating data movement. In traditional architectures, moving data between the processor and memory dominates energy costs [?]. In Poincaré Computing, the categorical state evolves in place, and projections are computed locally without data transfer.*

Proof. Energy consumption in digital circuits is dominated by charging and discharging capacitances (which signals transition). In a von Neumann architecture, every memory access requires:

- Driving the address bus (high capacitance due to long wires);
- Driving the data bus (high capacitance);
- Switching memory cell transistors.

Studies show that data movement can consume 100-1000× more energy than arithmetic operations [?].

In Poincaré Computing, the categorical state $\mathbf{S}(t)$ evolves according to local dynamics (the differential equations (373)–(375)), which can be implemented with analogue or mixed-signal circuits that evolve continuously without discrete switching. The projections π_M , π_P , π_S are computed from the local state without long-distance data transfer. This eliminates the energy cost of bus communication, potentially reducing energy consumption by orders of magnitude for memory-intensive computations. $\square$

This section has established the identity unification at the heart of Poincaré Computing: memory address, processor state, and semantic content are not separate entities but unified as projections of a single categorical state. This unification eliminates the von Neumann bottleneck, enables the simultaneous computation of all three projections, and provides

a foundation for energy-efficient, content-addressable computation. In the following sections, we develop the complexity theory (Section 35), topological structure (Section 39), and exhaustive computing properties (Section 37) that complete the mathematical framework.

32 Completeness and Answer Equivalence

33 Computational Completeness: Trajectory Equivalence

The question of computational completeness is central to any proposed computational framework: what class of problems can the framework solve, and how does this class relate to the problems solvable by established models such as Turing machines? For over eight decades, Turing completeness has served as the gold standard for computational universality [20]: a system is considered computationally complete if it can simulate any Turing machine, thereby computing any computable function. This criterion has been successfully applied to diverse computational models including lambda calculus, cellular automata, register machines, and modern programming languages.

However, Turing completeness is predicated on a specific computational paradigm: **algorithmic computation**, in which computation consists of executing a finite sequence of explicit instructions that transform input data into output data through deterministic state transitions. This paradigm assumes that the algorithm—the sequence of instructions—is the computation, and that two systems computing the same function via different algorithms are fundamentally different computational objects.

Poincaré Computing operates in a fundamentally different paradigm: **trajectory-based computation**, in which computation consists of continuous evolution through phase space guided by constraints, with solutions characterized by recurrence rather than termination. This section establishes that Poincaré Computing is *categorically distinct* from Turing computation: it is neither Turing complete nor subsumed by Turing computation, and Turing machines are not trajectory-complete. The two frameworks are incomparable, operating on different mathematical objects (continuous trajectories vs. discrete instruction sequences) with different equivalence relations (answer equivalence vs. algorithmic equivalence).

We develop an alternative completeness criterion called **trajectory completeness**, which characterizes the expressiveness of Poincaré Computing in terms appropriate to its geometric structure. We prove that the categorical dynamics are trajectory-complete (Theorem 33.8), establishing that Poincaré Computing can solve any problem that admits a recurrent trajectory solution. We introduce the notion of **answer equivalence**, which identifies problems by their outputs rather than their algorithmic structure, and prove that answer-equivalent problems can have entirely disjoint trajectories and constraint structures (Theorem 33.3). We establish the **representation-solution gap**, which formalizes the observation that perfect problem encodings paradoxically make computation unnecessary (Theorem 33.6).

The central philosophical claim of this section is that *computation without algorithms* is not only possible but represents a distinct and valid computational paradigm. In Poincaré Computing, there is no instruction sequence, no program counter, no discrete state transitions—only continuous dynamics, constraint satisfaction, and recurrence. The fundamental invariant is the answer, not the procedure.

33.1 The Algorithmic Assumption

We begin by making explicit the foundational assumptions underlying Turing computation and algorithmic thinking more broadly. These assumptions are so deeply embedded in computer science that they are often taken as definitional of computation itself, yet they represent a specific choice about what computation means.

Axiom 33.1 (Algorithmic Computation). Computation in the Turing paradigm consists of four essential components:

1. **Explicit instructions:** A finite set of rules (the transition function $\delta : Q \times \Gamma \rightarrow Q \times \Gamma \times \{L, R\}$ for a Turing machine) that specify exactly how the state evolves at each step. The algorithm is an explicit, finite description of the computational process.
2. **Uninformed input:** The input encoding on the tape contains no information about the output or the solution structure. The input is "raw data" that must be processed by the algorithm to produce the output.
3. **Deterministic transitions:** From each configuration, there is exactly one successor configuration (in deterministic Turing machines) or a

well-defined probability distribution over successors (in probabilistic variants). The computation follows a unique path through configuration space.

4. **Termination criterion:** Successful computation is defined by reaching a designated halting state (accept or reject). The computation "stops" when the answer is found, and the final tape contents encode the output.

These four assumptions define what we call the *algorithmic paradigm*. They are not mathematical necessities but design choices that have proven extraordinarily successful for discrete, symbolic computation.

Definition 33.1 (Turing Completeness). A computational system $\mathcal{S}$ is **Turing complete** if for every Turing machine M with input alphabet Σ and output alphabet Γ , there exists an encoding ι_M such that for every input $x \in \Sigma^*$:

$$M(x) = y \in \Gamma^* \implies \mathcal{S}(\iota_M(x)) = y \quad (480)$$

In other words, $\mathcal{S}$ can simulate the input-output behavior of any Turing machine [19].

Turing completeness is a powerful universality criterion because it establishes that a system can compute anything computable in the Church-Turing sense. However, it is important to recognize that Turing completeness is defined in terms of *input-output behavior*, not computational mechanism. Two systems can be Turing complete while using entirely different internal representations and dynamics.

Remark 33.1 (Algorithm as Computation). A crucial property of Turing computation is that the algorithm—the transition function δ —is the computation. Two Turing machines computing the same function $f : \Sigma^* \rightarrow \Gamma^*$ via different transition functions are considered different computational objects, even though they produce identical input-output mappings. This is reflected in complexity theory, where the running time and space usage depend on the specific algorithm, not just the function being computed. The algorithmic paradigm thus identifies computation with procedure rather than with result.

33.2 Poincaré Computing: A Non-Algorithmic Framework

We now establish formally that Poincaré Computing does not satisfy the algorithmic assumptions of Axiom 33.1. This is not a deficiency but a fundamental difference in computational paradigm.

Theorem 33.1 (Non-Algorithmic Structure). *Poincaré Computing violates each of the four conditions of Axiom 33.1:*

1. **Implicit instructions:** *There is no finite set of explicit instructions. Instead, the constraint predicate $\mathcal{C} : \mathcal{S}^* \rightarrow \{\text{true}, \text{false}\}$ specifies which trajectories are valid, but does not prescribe how to construct them.*
2. **Informed initial state:** *The initial state $\mathbf{S}_0$ may encode partial information about the solution structure through its position in S -entropy space and the structure of the constraint set $\mathcal{C}$.*
3. **Non-deterministic trajectories:** *Multiple distinct trajectories can satisfy the same constraints from the same initial state (Theorem 29.7), violating deterministic uniqueness.*
4. **Recurrence criterion:** *Successful computation is defined by recurrence $\|\gamma(T) - \mathbf{S}_0\| < \epsilon$ (return to origin), not by termination in a designated halting state. The system completes a cycle rather than stopping.*

Proof. We establish each violation explicitly.

(1) **Implicit instructions:** In Poincaré Computing, the "instructions" are not explicit rules but are encoded implicitly in the constraint predicate $\mathcal{C}$ and the dynamics (373)–(375). The constraint predicate specifies *what* properties a valid trajectory must satisfy (e.g., "the trajectory must pass through region R at some time t "), but it does not specify *how* to construct such a trajectory. The dynamics evolve the state continuously according to differential equations, not through discrete instruction execution. There is no instruction pointer, no program counter, no fetch-decode-execute cycle.

Formally, a Turing machine has a finite description as a tuple $(Q, \Sigma, \Gamma, \delta, q_0, q_{\text{accept}}, q_{\text{reject}})$ where the transition function δ is a finite table. In Poincaré Computing, the analogous description is $(\mathbf{S}_0, \mathcal{C}, \epsilon)$, where $\mathcal{C}$ is a predicate on trajectories (potentially infinite-dimensional objects) rather than a finite table of transitions. The constraint $\mathcal{C}$ is declarative (specifying properties) rather than imperative (specifying actions).

(2) **Informed initial state:** In Turing computation, the input tape contains only the problem instance (e.g., the graph to be colored, the formula to be satisfied), with no information about the solution. The algorithm must discover the solution through computation.




Figure 18: **Poincaré Computing as Gas Law Derivation.** Gas laws emerge from Poincaré recurrence in bounded computational phase space: trajectories explore the space ergodically, yielding thermodynamic properties. **Panel A (Computation = Trajectory):** 3D scatter plot of computational states in phase space, colored by time (green = start, red = end). The uniform space-filling demonstrates ergodic exploration, ensuring all microstates are sampled. **Panel B (Computational Velocity = Maxwell Distribution):** The distribution of step sizes (computational velocities) follows the Maxwell-Boltzmann form. Vertical lines mark characteristic speeds: most probable v_p , mean $\bar{v}$, and RMS v_{rms} . This emerges from trajectory statistics, not assumed. **Panel C ($T = (\text{trajectory spread})^2$):** Temperature is derived from trajectory spread σ , with $T \propto \sigma^2$. Scatter plot shows measured temperature versus spread for multiple runs; the linear fit (dashed) confirms the relationship. **Panel D (S increases then saturates):** Entropy $S = \ln \Omega$ increases monotonically during computation and saturates at equilibrium S_{max} . This derives the Second Law from trajectory dynamics: entropy cannot decrease because trajectories cannot “un-explore” phase space.

In Poincaré Computing, the initial state $\mathbf{S}_0$ is chosen to encode the problem structure, and the constraint set $\mathcal{C}$ is constructed to filter trajectories that satisfy the problem requirements. If the constraint $\mathcal{C}$ is satisfiable, then by construction, the structure of $\mathcal{C}$ encodes properties of valid solutions. For example, if $\mathcal{C}$ requires the trajectory to pass through a specific region $R \subset \mathcal{S}$, then the location of R encodes information about where solutions exist in phase space.

More fundamentally, the Unknowability Theorem (Section 35) establishes that the true initial state $\mathbf{S}_0$ is not directly observable but is inferred from the recurrent trajectory. This means that the “input” is not fully specified until the computation completes, creating a circular dependence between input and output that violates the uninformed input assumption.

(3) Non-deterministic trajectories: Theorem 29.7 establishes that for generic problems $P = (\mathbf{S}_0, \mathcal{C}, \epsilon)$ with $\epsilon > 0$, the solution set $\mathcal{A}(P)$ contains uncountably many distinct trajectories. These trajectories all start from the same initial state $\mathbf{S}_0$, satisfy the same constraints $\mathcal{C}$, and return within tolerance ϵ , yet they trace different paths through $\mathcal{S}$.

This multiplicity arises from the continuous nature of the dynamics: the set of initial velocities $\dot{\gamma}(0) \in T_{\mathbf{S}_0}\mathcal{S}$ that lead to recurrent trajectories has a positive measure, and each distinct initial velocity generates a distinct trajectory. This violates the deterministic uniqueness of Turing machines, where each configuration has exactly one successor.

(4) Recurrence vs. termination: In Turing computation, a successful computation terminates in a halting state q_{accept} , at which point the tape contents encode the output. The computation “stops,” and the machine no longer evolves.

In Poincaré Computing, successful computation is defined by the recurrence condition $\|\gamma(T) - \mathbf{S}_0\| < \epsilon$: the trajectory returns to (near) its starting point. The system does not halt in a designated state but completes a cycle. After recurrence, the dynamics continue to evolve (potentially producing additional recurrences), so there is no notion of “stopping.” The output is extracted from the trajectory structure via the output projection π_{out} (Definition 33.2), not from a final state.

This difference reflects a fundamental distinction: Turing machines operate in an open-ended state space (the tape can grow arbitrarily), while Poincaré Computing operates in a bounded phase space $\mathcal{S} = [0, 1]^3$ where trajectories must eventually return to their starting regions by Poincaré’s recurrence theorem. $\square$

Remark 33.2 (Paradigm Shift). Theorem 33.1 establishes that Poincaré Computing represents a genuine paradigm shift in computational thinking, not merely a different implementation of algorithmic computation. The violations of Axiom 33.1 are not bugs to be fixed but are essential features of the trajectory-based paradigm. Asking whether Poincaré Comput-

ing is Turing complete is analogous to asking whether a differential equation is Turing complete: the question applies a criterion from one mathematical framework to a fundamentally different one.

33.3 Answer Equivalence

Having established that Poincaré Computing does not fit the algorithmic paradigm, we now develop an alternative equivalence relation appropriate to the trajectory-based framework. This equivalence relation identifies problems by their outputs rather than their algorithmic structure.

Definition 33.2 (Output Projection). For a trajectory $\gamma : [0, T] \rightarrow \mathcal{S}$ solving a problem P , the **output projection** is a function $\pi_{\text{out}} : C([0, T], \mathcal{S}) \rightarrow \mathcal{Y}$ that extracts the computational result from the trajectory. The output space $\mathcal{Y}$ depends on the problem domain (e.g., $\mathcal{Y} = \{0, 1\}^*$ for Boolean functions, $\mathcal{Y} = \mathbb{R}$ for numerical optimization, $\mathcal{Y} = \text{Graphs}$ for graph problems).

The output projection may depend on:

- The final state $\gamma(T)$ (e.g., $\pi_{\text{out}}(\gamma) = S_k(T)$);
- Intermediate states along the trajectory (e.g., $\pi_{\text{out}}(\gamma) = \arg \max_{t \in [0, T]} S_k(t)$);
- Global trajectory properties (e.g., $\pi_{\text{out}}(\gamma) = \int_0^T S_k(t) dt$);
- Discrete events along the trajectory (e.g., $\pi_{\text{out}}(\gamma) = |\{t : \gamma(t) \in R\}|$ for some region R).

The output projection plays the role of the "tape reading" operation in Turing machines: it extracts the answer from the computational state. However, unlike Turing machines where the output is simply the final tape contents, the output projection in Poincaré Computing can be a complex functional of the entire trajectory.

Definition 33.3 (Answer Equivalence). Two problems $P_1 = (\mathbf{S}_0^{(1)}, \mathcal{C}_1, \epsilon_1)$ and $P_2 = (\mathbf{S}_0^{(2)}, \mathcal{C}_2, \epsilon_2)$ are **answer-equivalent**, written $P_1 \sim_A P_2$, if they produce the same output for all satisfying trajectories:

$$\forall \gamma_1 \in \mathcal{A}(P_1), \forall \gamma_2 \in \mathcal{A}(P_2) : \pi_{\text{out}}(\gamma_1) = \pi_{\text{out}}(\gamma_2) \quad (481)$$

In other words, two problems are answer-equivalent if every solution to the first problem produces the same output as every solution to the second problem.

Proposition 33.2 (Answer Equivalence is an Equivalence Relation). *The relation $\sim_A$ is an equivalence relation on the space of problems: it is reflexive, symmetric, and transitive.*

Proof. We verify the three properties of an equivalence relation.

Reflexivity: For any problem P , we have $P \sim_A P$ because $\pi_{\text{out}}(\gamma) = \pi_{\text{out}}(\gamma)$ for any trajectory $\gamma \in \mathcal{A}(P)$. This is trivially true.

Symmetry: If $P_1 \sim_A P_2$, then by definition, $\pi_{\text{out}}(\gamma_1) = \pi_{\text{out}}(\gamma_2)$ for all $\gamma_1 \in \mathcal{A}(P_1)$ and $\gamma_2 \in \mathcal{A}(P_2)$. By symmetry of equality, $\pi_{\text{out}}(\gamma_2) = \pi_{\text{out}}(\gamma_1)$, so $P_2 \sim_A P_1$.

Transitivity: If $P_1 \sim_A P_2$ and $P_2 \sim_A P_3$, then:

$$\pi_{\text{out}}(\gamma_1) = \pi_{\text{out}}(\gamma_2) \quad \forall \gamma_1 \in \mathcal{A}(P_1), \gamma_2 \in \mathcal{A}(P_2) \quad (482)$$

$$\pi_{\text{out}}(\gamma_2) = \pi_{\text{out}}(\gamma_3) \quad \forall \gamma_2 \in \mathcal{A}(P_2), \gamma_3 \in \mathcal{A}(P_3) \quad (483)$$

By transitivity of equality, $\pi_{\text{out}}(\gamma_1) = \pi_{\text{out}}(\gamma_3)$ for all $\gamma_1 \in \mathcal{A}(P_1)$ and $\gamma_3 \in \mathcal{A}(P_3)$, so $P_1 \sim_A P_3$.

Therefore, $\sim_A$ is an equivalence relation, partitioning the space of problems into equivalence classes of answer-equivalent problems. $\square$

33.4 Non-Algorithmic Equivalence

The central result of this section is that answer equivalence does not imply any form of algorithmic or geometric similarity. Problems can produce identical outputs while having completely different initial states, constraint structures, and trajectory geometries.

Theorem 33.3 (Non-Algorithmic Equivalence). *There exist problems $P_1 = (\mathbf{S}_0^{(1)}, \mathcal{C}_1, \epsilon_1)$ and $P_2 = (\mathbf{S}_0^{(2)}, \mathcal{C}_2, \epsilon_2)$ such that:*

1. $P_1 \sim_A P_2$ (answer-equivalent: same output)
2. $\mathbf{S}_0^{(1)} \neq \mathbf{S}_0^{(2)}$ (different initial states)
3. $\mathcal{C}_1 \neq \mathcal{C}_2$ (different constraint structures)
4. For any $\gamma_1 \in \mathcal{A}(P_1)$ and $\gamma_2 \in \mathcal{A}(P_2)$, the trajectory images are disjoint except possibly at the output extraction point: $\gamma_1([0, T_1]) \cap \gamma_2([0, T_2]) = \emptyset$ (or has measure zero)

Proof. We construct an explicit example demonstrating all four properties.

Let $y^* \in \mathcal{Y}$ be a target output value (e.g., $y^* = 42$ for a numerical problem). We construct two problems that both produce output y^* but are otherwise completely different.

Problem P_1 :

- Initial state: $\mathbf{S}_0^{(1)} = (0.1, 0.2, 0.3)$ (lower-left region of $\mathcal{S}$)

- Constraint: $\mathcal{C}_1$ requires the trajectory to pass through the region $R_1 = [0.1, 0.2] \times [0.2, 0.3] \times [0.3, 0.4] \subset \mathcal{S}$ at some time $t_1 \in (0, T_1)$ before returning to $\mathbf{S}_0^{(1)}$
- Output projection: $\pi_{\text{out}}(\gamma_1) = f_1(\gamma_1)$ where f_1 is designed such that any trajectory satisfying $\mathcal{C}_1$ produces output y^*

Problem P_2 :

- Initial state: $\mathbf{S}_0^{(2)} = (0.8, 0.7, 0.6)$ (upper-right region of $\mathcal{S}$, disjoint from $\mathbf{S}_0^{(1)}$)
- Constraint: $\mathcal{C}_2$ requires the trajectory to pass through the region $R_2 = [0.7, 0.8] \times [0.6, 0.7] \times [0.5, 0.6] \subset \mathcal{S}$ at some time $t_2 \in (0, T_2)$ before returning to $\mathbf{S}_0^{(2)}$
- Output projection: $\pi_{\text{out}}(\gamma_2) = f_2(\gamma_2)$ where f_2 is designed such that any trajectory satisfying $\mathcal{C}_2$ produces output y^*

Verification of properties:

(1) *Answer equivalence:* By construction, both f_1 and f_2 are designed to produce output y^* for any satisfying trajectory. Therefore, $\pi_{\text{out}}(\gamma_1) = y^* = \pi_{\text{out}}(\gamma_2)$ for all $\gamma_1 \in \mathcal{A}(P_1)$ and $\gamma_2 \in \mathcal{A}(P_2)$, establishing $P_1 \sim_A P_2$.

(2) *Different initial states:* By construction, $\mathbf{S}_0^{(1)} = (0.1, 0.2, 0.3) \neq (0.8, 0.7, 0.6) = \mathbf{S}_0^{(2)}$.

(3) *Different constraints:* The constraint $\mathcal{C}_1$ requires passing through R_1 , while $\mathcal{C}_2$ requires passing through R_2 . Since $R_1 \cap R_2 = \emptyset$ (the regions are disjoint), the constraints are structurally different: no trajectory can satisfy both simultaneously.

(4) *Disjoint trajectories:* Any trajectory $\gamma_1 \in \mathcal{A}(P_1)$ must start at $\mathbf{S}_0^{(1)} \in [0, 0.2]^3$ (approximately), pass through $R_1 \subset [0.1, 0.4]^3$, and return to $\mathbf{S}_0^{(1)}$. By continuity, the trajectory remains in a neighborhood of these regions. Similarly, any trajectory $\gamma_2 \in \mathcal{A}(P_2)$ remains in a neighborhood of $[0.5, 0.8]^3$. Since these neighborhoods are disjoint (separated by a distance of at least 0.1 in each coordinate), the trajectory images are disjoint: $\gamma_1([0, T_1]) \cap \gamma_2([0, T_2]) = \emptyset$.

This construction demonstrates that answer-equivalent problems can be geometrically and structurally completely different, with no overlap in their solution trajectories. $\square$

Corollary 33.4 (Path Independence). *The computational "algorithm" (trajectory geometry and constraint structure) is not an invariant of the computation. Only the output is invariant under answer equivalence.*

Proof. Theorem 33.3 establishes that answer-equivalent problems $P_1 \sim_A P_2$ can have completely different trajectory geometries (disjoint images) and constraint structures ($\mathcal{C}_1 \neq \mathcal{C}_2$). Therefore, the trajectory and constraints—which in the algorithmic paradigm would constitute the "algorithm"—are not invariants of the equivalence relation. Only the output $\pi_{\text{out}}(\gamma)$ is invariant.

This contrasts sharply with algorithmic equivalence in Turing computation, where two machines are considered equivalent only if they have the same transition function (or isomorphic transition functions), making the algorithm itself the primary invariant. $\square$

Example 33.1 (Arithmetic Reformulation). Consider the problem of computing the value 1000. This can be formulated in infinitely many ways:

- P_1 : Initial state encoding "10³" with constraints requiring exponentiation dynamics
- P_2 : Initial state encoding "995 + 5" with constraints requiring addition dynamics
- P_3 : Initial state encoding "2000/2" with constraints requiring division dynamics
- P_4 : Initial state encoding " $\sqrt{1000000}$ " with constraints requiring square root dynamics
- P_5 : Initial state encoding " $\sum_{i=1}^{1000} 1$ " with constraints requiring summation dynamics

All five problems are answer-equivalent: $P_1 \sim_A P_2 \sim_A P_3 \sim_A P_4 \sim_A P_5$, as they all produce output 1000. However, their initial states, constraint structures, and trajectory geometries are entirely distinct. In the algorithmic paradigm, these would be considered five different algorithms. In the trajectory paradigm, they are five reformulations of the same problem, distinguished only by their geometric representations in $\mathcal{S}$.

33.5 Reformulation Abundance

We now formalize the observation that answer-equivalent problems are not rare exceptions but are abundant: every problem has uncountably many reformulations.

Definition 33.4 (Problem Reformulation). A **reformulation** of problem $P = (\mathbf{S}_0, \mathcal{C}, \epsilon)$ is any problem $P' = (\mathbf{S}'_0, \mathcal{C}', \epsilon')$ such that $P \sim_A P'$ (answer-equivalent). The equivalence class $[P]_{\sim_A} = \{P' : P' \sim_A P\}$ is the set of all reformulations of P .

Theorem 33.5 (Reformulation Abundance). *For any problem P with non-empty solution set $\mathcal{A}(P) \neq \emptyset$, the equivalence class $[P]_{\sim_A}$ contains uncountably many distinct problems.*

Proof. Let $P = (\mathbf{S}_0, \mathcal{C}, \epsilon)$ be a problem with $\mathcal{A}(P) \neq \emptyset$, and let $\gamma^* \in \mathcal{A}(P)$ be a satisfying trajectory. Define $y^* = \pi_{\text{out}}(\gamma^*)$ as the output produced by this trajectory.

For any initial state $\mathbf{S}'_0 \in \mathcal{S}$ (where $\mathcal{S} = [0, 1]^3$ is uncountable), we can construct a constraint $\mathcal{C}'$ as follows:

$$\mathcal{C}'(\gamma) = \begin{cases} \text{true} & \text{if } \gamma(0) = \mathbf{S}'_0, \|\gamma(T) - \mathbf{S}'_0\| < \epsilon', \text{ and } \pi_{\text{out}}(\gamma) = y^* \\ \text{false} & \text{otherwise} \end{cases} \quad (484)$$

This constraint is satisfiable: by Poincaré's recurrence theorem (Theorem 43.1), almost every initial state $\mathbf{S}'_0$ admits recurrent trajectories, and among these, we can select (via the output projection π_{out}) those that produce output y^* . Therefore, $\mathcal{A}(P') \neq \emptyset$ for the problem $P' = (\mathbf{S}'_0, \mathcal{C}', \epsilon')$.

By construction, every trajectory $\gamma' \in \mathcal{A}(P')$ satisfies $\pi_{\text{out}}(\gamma') = y^* = \pi_{\text{out}}(\gamma^*)$ for all $\gamma^* \in \mathcal{A}(P)$. Therefore, $P' \sim_A P$, so $P' \in [P]_{\sim_A}$.

Since this construction works for any $\mathbf{S}'_0 \in \mathcal{S}$, and $\mathcal{S}$ is uncountable (it is a subset of $\mathbb{R}^3$), the equivalence class $[P]_{\sim_A}$ contains uncountably many distinct problems (one for each choice of $\mathbf{S}'_0$). $\square$

Remark 33.3 (Implications for Problem Encoding). Theorem 33.5 has profound implications for problem encoding. In traditional computation, there is typically a "natural" encoding of a problem (e.g., the adjacency matrix for a graph problem, the clause list for a SAT problem), and different encodings are considered variations on the same problem. In Poincaré Computing, there is no unique natural encoding: every problem has uncountably many equally valid reformulations, distinguished only by their geometric positions in $\mathcal{S}$. The choice of reformulation affects the trajectory geometry and recurrence time but not the answer.

33.6 The Representation-Solution Gap

We now formalise a subtle but important phenomenon: the relationship between how a problem is encoded and whether solutions exist. In traditional computation, the encoding is separate from the solution: the input contains no information about the output. In Poincaré Computing, the encoding (initial state and constraints) and the solution (recur-

rent trajectory) are intertwined in a way that creates a "representation-solution gap."

Definition 33.5 (Encoding Fidelity). For a function $f : \mathcal{X} \rightarrow \mathcal{Y}$ (the intended computation) and a problem encoding $\iota : \mathcal{X} \rightarrow \mathcal{S} \times \mathcal{C}$ that maps inputs to initial states and constraints, the **encoding fidelity** is:

$$\mathcal{F}(\iota, f) = \frac{|\{x \in \mathcal{X} : \exists \gamma \in \mathcal{A}(\iota(x)), \pi_{\text{out}}(\gamma) = f(x)\}|}{|\mathcal{X}|} \quad (485)$$

This measures the fraction of inputs for which the encoding produces a problem with solutions that compute the correct output.

Perfect encoding fidelity ($\mathcal{F}(\iota, f) = 1$) means that for every input x , there exists a satisfying trajectory that produces the correct output $f(x)$. Zero fidelity ($\mathcal{F}(\iota, f) = 0$) means that no input is correctly computed.

Theorem 33.6 (Representation-Solution Gap). *Let $f : \mathcal{X} \rightarrow \mathcal{Y}$ be the intended computation, and let $P = (\mathbf{S}_0, \mathcal{C}, \epsilon)$ be a problem encoding an input $x \in \mathcal{X}$. Define:*

- $\mathcal{A}(P)$ = set of trajectories satisfying recurrence and constraints
- $\mathcal{S}(f, x) = \{\gamma : \pi_{\text{out}}(\gamma) = f(x)\}$ = set of trajectories producing the correct output

Then in general:

$$\mathcal{A}(P) \not\subseteq \mathcal{S}(f, x) \quad \text{and} \quad \mathcal{S}(f, x) \not\subseteq \mathcal{A}(P) \quad (486)$$

The intersection $\mathcal{A}(P) \cap \mathcal{S}(f, x) \neq \emptyset$ if and only if the encoding correctly computes $f(x)$.

Proof. The set $\mathcal{A}(P)$ is determined entirely by the dynamics (equations (373)–(375)), the initial state $\mathbf{S}_0$, and the constraints $\mathcal{C}$. It is independent of the external interpretation function f .

The set $\mathcal{S}(f, x)$ is determined entirely by the semantic function f and the output projection π_{out} . It is independent of the dynamics and constraints.

$\mathcal{A}(P) \not\subseteq \mathcal{S}(f, x)$: If the encoding ι does not correctly capture the function f , then there may exist trajectories that satisfy the constraints (and hence are in $\mathcal{A}(P)$) but produce incorrect outputs (and hence are not in $\mathcal{S}(f, x)$). For example, if the constraints are too permissive, they may allow trajectories that violate the problem requirements.

$\mathcal{S}(f, x) \not\subseteq \mathcal{A}(P)$: Conversely, there may exist trajectories that would compute $f(x)$ correctly (and hence are in $\mathcal{S}(f, x)$) but violate the constraints or

fail to recur (and hence are not in $\mathcal{A}(P)$). For example, if the constraints are too restrictive, they may exclude valid solution trajectories.

The encoding correctly computes $f(x)$ if and only if there exists at least one trajectory that both satisfies the constraints and produces the correct output: $\mathcal{A}(P) \cap \mathcal{S}(f, x) \neq \emptyset$. $\square$

Corollary 33.7 (Perfect Encoding Paradox). *If an encoding ι achieves perfect fidelity ($\mathcal{F}(\iota, f) = 1$), meaning that for every input x , the constraints $\mathcal{C}$ force all satisfying trajectories to produce the correct output $f(x)$, then the constraint structure $\mathcal{C}$ contains sufficient information to determine $f(x)$ without executing the dynamics. In this sense, perfect encoding makes computation unnecessary—the "answer" is already encoded in the problem specification.*

Proof. If $\mathcal{F}(\iota, f) = 1$, then for every input $x \in \mathcal{X}$, we have $\mathcal{A}(P) \subseteq \mathcal{S}(f, x)$: every trajectory satisfying the constraints produces the correct output. This means that the constraint predicate $\mathcal{C}$ distinguishes correct outputs from incorrect outputs, which requires $\mathcal{C}$ to encode the graph of f .

More precisely, if $\mathcal{C}$ forces $\pi_{\text{out}}(\gamma) = f(x)$ for all $\gamma \in \mathcal{A}(P)$, then $\mathcal{C}$ must "know" the value of $f(x)$. This information is encoded in the structure of $\mathcal{C}$ (e.g., in the regions of $\mathcal{S}$ that trajectories are required to visit). Therefore, the dynamics serve only to "discover" information that is already present in the constraint structure, making them, in some sense, redundant.

This paradox highlights a fundamental tension in Poincaré Computing: perfect encodings are informationally complete, while imperfect encodings require the dynamics to search for solutions. The optimal encoding balances these extremes. $\square$

33.7 Trajectory Completeness

Having established that Poincaré Computing does not fit the algorithmic paradigm, we now define an appropriate completeness criterion for the trajectory-based framework.

Definition 33.6 (Trajectory Completeness). A dynamical system on $\mathcal{S}$ is **trajectory-complete** if, for every constraint set $\mathcal{C}$ with a non-empty solution space $\mathcal{S}(\mathcal{C}) \neq \emptyset$, there exists an initial state $\mathbf{S}_0 \in \mathcal{S}$ and a tolerance $\epsilon > 0$ such that the dynamics produce a satisfying trajectory:

$$\forall \mathcal{C} : \mathcal{S}(\mathcal{C}) \neq \emptyset \implies \exists \mathbf{S}_0, \epsilon : \mathcal{A}(\mathbf{S}_0, \mathcal{C}, \epsilon) \neq \emptyset \quad (487)$$

In other words, if a constraint is satisfiable (admits at least one trajectory satisfying it), then the dynamics can produce such a trajectory from some initial state.

Theorem 33.8 (Poincaré Trajectory Completeness). *The categorical dynamics on $\mathcal{S}$ with measure-preserving flow (satisfying the modular condition (380)) are trajectory-complete.*

Proof. Let $\mathcal{C}$ be a constraint predicate with a non-empty solution space $\mathcal{S}(\mathcal{C}) \neq \emptyset$. By definition, there exists at least one trajectory $\gamma^* : [0, T^*] \rightarrow \mathcal{S}$ satisfying $\mathcal{C}(\gamma^*) = \text{true}$.

Let $\mathbf{S}_0 = \gamma^*(0)$ be the initial state of this trajectory, and let $\epsilon = \|\gamma^*(T^*) - \gamma^*(0)\| + \delta$ for some small $\delta > 0$. Then, by construction:

- $\gamma^*(0) = \mathbf{S}_0$ (initial condition satisfied)
- $\|\gamma^*(T^*) - \mathbf{S}_0\| = \|\gamma^*(T^*) - \gamma^*(0)\| < \epsilon$ (recurrence condition satisfied)
- $\mathcal{C}(\gamma^*) = \text{true}$ (constraint satisfied)

Therefore, $\gamma^* \in \mathcal{A}(\mathbf{S}_0, \mathcal{C}, \epsilon)$ establishes that $\mathcal{A}(\mathbf{S}_0, \mathcal{C}, \epsilon) \neq \emptyset$.

This construction works for any satisfiable constraint $\mathcal{C}$: we simply choose the initial state to be the starting point of any trajectory that satisfies the constraint. By Poincaré's recurrence theorem (Theorem 43.1), such trajectories exist for almost every initial state under measure-preserving dynamics, ensuring that the dynamics are trajectory-complete. $\square$

Remark 33.4 (Comparison with Turing Completeness). Trajectory completeness and Turing completeness are incomparable notions:

- Turing completeness asks: "Can the system simulate any Turing machine?" (input-output equivalence)
- Trajectory completeness asks: "Can the system produce any satisfiable trajectory?" (constraint satisfaction)

A system can be trajectory-complete without being Turing complete (Poincaré Computing), and a system can be Turing complete without being trajectory-complete (Turing machines cannot produce continuous recurrent trajectories). The two criteria apply to different computational paradigms and are not directly comparable.

33.8 Categorical Distinction and Incomparability

We conclude by formally establishing that Poincaré Computing and Turing computation are incomparable frameworks.




Figure 19: **Categorical Computing as Gas Law Derivation.** Categorical operations (discrete state transitions) map to molecular dynamics, with gas laws emerging from operation statistics. **Panel A (Categorical Operations = Molecular Trajectories):** 3D visualization of categorical state space as a $3^3 = 27$ cell grid, with trajectories (colored lines) showing transitions between cells. Each trajectory represents one computational thread; the grid represents discrete molecular states. **Panel B (Operation Types = Energy Modes):** Bar chart showing equal distribution of three operation types: Oscillatory (phase), Categorical (transition), Partition (rearrangement). Equal counts demonstrate equipartition—each mode carries equal energy on average, as required by the equipartition theorem. **Panel C (T-S Relationship):** Scatter plot of derived entropy versus derived temperature from categorical operations, showing the thermodynamic identity $S = ncT$ emerges from computation. The linear fit (red dashed) confirms the relationship is derived, not assumed. **Panel D (State Occupancy = Boltzmann Distribution):** Histogram of categorical state occupancy versus energy level, showing exponential Boltzmann distribution $P(E) \propto e^{-E/k_B T}$. Red dashed curve: theoretical Boltzmann fit. The distribution emerges from operation statistics.

Theorem 33.9 (Incomparability). *Poincaré Computing and Turing computation are incomparable computational frameworks in the following sense:*

1. *Poincaré Computing is not Turing complete (cannot simulate arbitrary Turing machines while preserving algorithmic structure)*
2. *Turing machines are not trajectory-complete (they cannot produce continuous, recurrent trajectories in a bounded phase space)*
3. *Neither framework subsumes the other: there exist problems solvable in one framework but not naturally expressible in the other*

Proof. (1) **Poincaré Computing is not Turing complete:** Turing completeness requires that for every Turing machine M , there exists an encoding in Poincaré Computing that simulates M step-by-step, preserving the algorithmic structure. However, Poincaré Computing does not execute instructions sequentially (Theorem 33.1): it evolves states continuously according to differential equations. There is no instruction pointer, no discrete state transitions, no tape head movement.

While it is possible to encode the input-output behaviour of a Turing machine as a constraint set $\mathcal{C}$ (as in Proposition 23.1), this encoding does not preserve the algorithmic structure. The Poincaré system does

not "execute" the Turing machine's transition function; it finds a trajectory that happens to produce the same output. This is answer equivalence, not algorithmic equivalence.

Therefore, Poincaré Computing is not Turing complete in the traditional sense because it cannot simulate the algorithmic execution of Turing machines.

(2) **Turing machines are not trajectory-complete:** Turing machines operate on discrete symbol strings and execute discrete state transitions. They cannot directly produce continuous trajectories in a bounded phase space $\mathcal{S} = [0, 1]^3$. While one could discretise $\mathcal{S}$ and simulate the dynamics numerically, this would not capture the essential continuous and recurrent nature of Poincaré Computing.

More fundamentally, Turing machines are designed to halt in accept/reject states, not to recur. A Turing machine that returns to its initial configuration has computed nothing (it has simply undone its computation). Recurrence is not a natural notion in the Turing paradigm.

Therefore, Turing machines are not trajectory-complete: they cannot produce the continuous recurrent trajectories that define computation in Poincaré Computing.

(3) **Incomparability:** The two frameworks operate on different mathematical objects (discrete symbol strings vs. continuous trajectories), use different equivalence relations (algorithmic equivalence vs.

answer equivalence), and have different completeness criteria (Turing completeness vs. trajectory completeness). Problems that are natural in one framework may be awkward or inexpressible in the other.

For example:

- Continuous optimization problems (e.g., finding minima of smooth functions) are natural in Poincaré Computing (as trajectories flowing toward attractors) but require discretization in Turing computation.
- Symbolic manipulation problems (e.g., parsing formal languages) are natural in Turing computation (as string rewriting) but require encoding as geometric constraints in Poincaré Computing.

Neither framework subsumes the other; they are complementary approaches to computation. $\square$

Remark 33.5 (Paradigm Plurality). Theorem 33.9 establishes that there is not one universal computational paradigm but multiple incomparable paradigms, each suited to different classes of problems. This plurality is analogous to the situation in mathematics, where different axiomatic systems (e.g., Euclidean vs. non-Euclidean geometry) are incomparable but equally valid. The existence of Poincaré Computing as a distinct paradigm enriches our understanding of what computation can be.

33.9 Implications: Computation Without Algorithms

We conclude this section by summarising the philosophical implications of the trajectory-based paradigm.

Proposition 33.10 (Computation Without Algorithms). *In Poincaré Computing, the notion of "algorithm" is not well-defined. Computation does not consist of executing a sequence of instructions but rather of:*

- Specifying an initial state $\mathbf{S}_0$ (problem encoding)
- Defining constraints $\mathcal{C}$ (solution requirements)
- Evolving the state according to continuous dynamics (373)–(375)
- Detecting recurrence $\|\gamma(T) - \mathbf{S}_0\| < \epsilon$ (solution completion)
- Extracting output via $\pi_{\text{out}}(\gamma)$ (answer retrieval)

There is no "algorithm" in the traditional sense—no procedure, no control flow, no instruction sequence.

Proposition 33.11 (Answer Primacy). *The fundamental invariant of Poincaré computation is the answer, not the procedure. Two computations are equivalent ($P_1 \sim_A P_2$) if and only if they produce the same output, regardless of:*

- Initial state differences ($\mathbf{S}_0^{(1)} \neq \mathbf{S}_0^{(2)}$)
- Constraint structure differences ($\mathcal{C}_1 \neq \mathcal{C}_2$)
- Trajectory geometry differences ($\gamma_1([0, T_1]) \cap \gamma_2([0, T_2]) = \emptyset$)
- Recurrence time differences ($T_1 \neq T_2$)

This represents a fundamental shift from procedure-centric to result-centric computation.

This completes the formal establishment of Poincaré Computing as a computational framework categorically distinct from Turing computation. The two paradigms operate on different mathematical objects (continuous trajectories vs. discrete instruction sequences), employ different equivalence relations (answer equivalence vs. algorithmic equivalence), and satisfy different completeness criteria (trajectory completeness vs. Turing completeness). Poincaré Computing demonstrates that computation without algorithms is not only possible but also represents a coherent and complete alternative to the algorithmic paradigm that has dominated computer science for nearly a century.

34 Categorical Complexity Theory

35 Complexity Theory: Categorical Rate

Complexity theory is the study of the resources required to solve computational problems. In traditional computation, these resources are measured in terms of time (number of computational steps) and space (amount of memory used), with the fundamental unit being the discrete operation—an instruction executed, a bit written, a state transition performed [?]. The complexity of an algorithm is characterized by functions $T(n)$ and $S(n)$ that bound the time and space required as a function of input size n . Performance metrics such as FLOPS (floating-point operations per second) and clock frequency (GHz) quantify the rate at which these discrete operations are executed.

This operational paradigm, however, presupposes a computational model in which computation consists

of discrete, countable steps. Poincaré Computing, by contrast, operates through continuous trajectory evolution in phase space, with no discrete operations, no instruction sequences, and no clock-synchronized state transitions. The question thus arises: **how do we measure complexity in a computational framework without operations?**

This section develops a complexity theory appropriate to the trajectory-based paradigm. We establish that traditional operation-based measures such as FLOPS are fundamentally inapplicable to Poincaré Computing (Proposition 35.1), not merely difficult to apply but categorically meaningless. We prove that the initial state $\mathbf{S}_0$ —which plays the role of the "input" in traditional computation—is not directly observable but must be inferred from the trajectory itself, creating a fundamental epistemological constraint on complexity measurement (Theorem 35.3). We establish that solutions are recognized not by direct comparison with the initial state but through the accumulation of local solutions that form a closed chain in interpretation space (Theorem 35.5).

We introduce the **categorical completion rate** ρ_C as the fundamental measure of computational progress, defined as the number of categorical transitions per unit of promising trajectory length in $\mathcal{S}$ (Definition 35.6). We prove that this rate is independent of physical time and hardware implementation (Theorem 35.8), making it an intrinsic geometric property of the trajectory-constraint system. We define the **Poincaré complexity** $\Pi(P)$ as the minimum number of local solutions required to recognize closure (Definition 35.7), and we establish bounds relating this complexity to the recurrence tolerance ϵ (Theorem 35.10).

Finally, we introduce the **Poincaré** ($\mathbb{P}$) as the fundamental unit of computation—the cost of one local solution recognition—and prove that Poincaré complexity and Turing complexity are incommensurable, with no general conversion between them (Theorem 35.13). This incommensurability reflects the categorical distinction between operational and trajectory-based computation.

35.1 Inapplicability of Operation-Based Measures

We begin by establishing that traditional complexity measures, which count discrete operations, cannot be meaningfully applied to Poincaré Computing.

Proposition 35.1 (FLOPS Inapplicability). *Floating-point operations per second (FLOPS) is not a well-defined measure for Poincaré Computing.*

More generally, any complexity measure based on counting discrete operations is inapplicable.

Proof. FLOPS measures the rate at which a computational system executes floating-point arithmetic operations (additions, multiplications, divisions, etc.). The definition presupposes:

1. **Discrete operations:** Computation consists of countable, atomic operations that can be enumerated.
2. **Sequential execution:** Operations are executed in sequence (or in parallel with a well-defined count of simultaneous operations).
3. **Time-based rate:** The measure is operations *per second*, making physical time the fundamental parameter.
4. **Operation-result correspondence:** Each operation contributes a quantifiable amount to the computational progress.

In Poincaré Computing, none of these assumptions hold:

(1) **No discrete operations:** The categorical dynamics (373)–(375) evolve the state continuously according to differential equations. There are no discrete operations to count. While one could discretize the dynamics (e.g., using Euler's method with time step Δt), this discretization is an artifact of numerical simulation, not an intrinsic property of the computation. Different discretizations produce different operation counts for the same trajectory, making the count arbitrary.

(2) **No instruction sequence:** Theorem 33.1 establishes that Poincaré Computing has no instruction sequence. The trajectory evolves according to the vector field $\mathbf{F}(\mathbf{S})$, which is evaluated continuously, not step-by-step. There is no program counter, no fetch-decode-execute cycle, no sequential ordering of operations.

(3) **Time is not fundamental:** Theorem 35.8 (proven below) establishes that computational progress in Poincaré Computing is measured by categorical completion events, which are geometric properties of the trajectory in $\mathcal{S}$, not temporal properties. A faster or slower physical clock does not change the number of categorical completions required to solve a problem.

(4) **Path-dependent operation count:** Theorem 29.7 establishes that multiple distinct trajectories can solve the same problem. If we were to count "operations" (e.g., evaluations of the vector field $\mathbf{F}$), different solution trajectories would have different

operation counts, making the count path-dependent rather than problem-dependent. This violates the principle that complexity should be a property of the problem, not the solution method.

Therefore, FLOPS and related operation-based measures are categorically inapplicable to Poincaré Computing. They measure properties that do not exist in the framework. $\square$

Corollary 35.2 (Hardware Comparison Failure). *Comparing Poincaré Computing systems by FLOPS, clock speed (GHz), instruction throughput (IPC), or memory bandwidth (GB/s) is meaningless. These metrics measure properties of operational computation that do not exist in trajectory-based computation.*

Proof. Each of these metrics is defined in terms of discrete operations or time-based rates:

- FLOPS: floating-point operations per second (Proposition 35.1)
- Clock speed: cycles per second (but Poincaré Computing has no clock-synchronized cycles)
- IPC: instructions per cycle (but there are no instructions)
- Memory bandwidth: bytes transferred per second (but the identity unification, Section 31, eliminates data transfer between processor and memory)

Since these metrics measure non-existent properties, they cannot be used to compare Poincaré Computing systems. A different set of metrics, based on categorical completion rates, is required. $\square$

Remark 35.1 (Implications for Benchmarking). Corollary 35.2 has profound implications for benchmarking and performance evaluation. Traditional benchmark suites (e.g., SPEC, LINPACK) measure FLOPS, memory bandwidth, and instruction throughput. These benchmarks are inapplicable to Poincaré Computing. New benchmarks must measure categorical completion rates, trajectory efficiency, and constraint satisfaction density—metrics that reflect the geometric nature of trajectory-based computation.

35.2 The Unknowable Origin

A fundamental epistemological constraint on complexity measurement in Poincaré Computing is that the initial state $\mathbf{S}_0$ —which plays the role of the "input" in traditional computation—is not directly observable. This constraint has profound implications

for how solutions are recognized and complexity is measured.

Theorem 35.3 (Origin Inaccessibility). *The initial state $\mathbf{S}_0$ cannot be directly measured or stored. It exists only as the origin of the trajectory and must be inferred from the trajectory itself, not given as an independent input.*

Proof. The initial state $\mathbf{S}_0$ is derived from hardware timing measurements through the coordinate mapping functions (Section 25):

$$\mathbf{S}_0 = \Phi(\delta_p(0)) = (\phi_k(\delta_p(0)), \phi_t(\delta_p(0)), \phi_e(\delta_p(0))) \quad (488)$$

where $\delta_p(0)$ is the timing difference measured at time $t = 0$.

The mapping $\Phi : \mathbb{R} \rightarrow \mathcal{S}$ is deterministic (Theorem 25.3), so given the timing measurement $\delta_p(0)$, the initial state $\mathbf{S}_0$ is uniquely determined. However, the timing measurement $\delta_p(0)$ is a transient physical quantity that exists only at the moment of measurement. Once the categorical state begins to evolve according to the dynamics (373)–(375), the original timing measurement is no longer available.

More fundamentally, the timing measurement $\delta_p(t)$ changes continuously as the hardware oscillators evolve. The value $\delta_p(0)$ that produced $\mathbf{S}_0$ cannot be recovered from later measurements $\delta_p(t)$ for $t > 0$ because the mapping Φ is not injective (multiple timing differences can map to nearby categorical states due to the periodic structure of ϕ_t and ϕ_e).

Therefore, once the trajectory departs from $\mathbf{S}_0$, the initial state exists only as the *origin* of the trajectory—the point from which the trajectory began—not as an observable datum that can be measured or stored. The initial state must be inferred from the trajectory structure, not given independently. $\square$

Corollary 35.4 (No Direct Recurrence Verification). *The recurrence condition $\|\gamma(T) - \mathbf{S}_0\| < \epsilon$ cannot be verified by direct comparison of $\gamma(T)$ with $\mathbf{S}_0$, because $\mathbf{S}_0$ is not available for comparison.*

Proof. Verification of the recurrence condition requires knowing both the current state $\gamma(T)$ and the initial state $\mathbf{S}_0$ to compute the distance $\|\gamma(T) - \mathbf{S}_0\|$. The current state $\gamma(T)$ is observable through timing measurements: $\gamma(T) = \Phi(\delta_p(T))$. However, by Theorem 35.3, the initial state $\mathbf{S}_0$ is not available. We cannot compute $\|\gamma(T) - \mathbf{S}_0\|$ because we do not have $\mathbf{S}_0$.

Therefore, direct verification of recurrence is impossible. An alternative recognition mechanism, based on local observations along the trajectory, is required. $\square$

Remark 35.2 (Contrast with Turing Machines). In Turing computation, the input is explicitly written on the tape at the start of the computation and remains available throughout. The Turing machine can "look back" at the input at any time by moving the tape head. In Poincaré Computing, by contrast, the "input" (the initial state $\mathbf{S}_0$) is ephemeral and cannot be accessed once the computation begins. This fundamental difference necessitates a different approach to solution recognition.

35.3 Solution Recognition Through Local Accumulation

Since the origin is inaccessible, solution recognition cannot proceed by direct comparison with the initial state. Instead, solutions are recognized through the accumulation of local observations that form a closed chain in interpretation space.

Definition 35.1 (Local Solution). A **local solution** L_i is a recognizable pattern or property exhibited by a segment of the trajectory $\gamma|_{[t_i, t_{i+1}]}$ as it passes through a region of $\mathcal{S}$ where the categorical state admits semantic interpretation.

Formally, a local solution is a tuple $L_i = (R_i, \sigma_i, t_i)$ where:

- $R_i \subseteq \mathcal{S}$ is a region of phase space (typically a cell in the hierarchical partition $\mathcal{P}_k$);
- $\sigma_i \in \Sigma$ is a semantic label from a problem-specific semantic alphabet Σ (e.g., $\Sigma = \{\text{"sorted"}, \text{"unsorted"}, \text{"pivot_selected"}, \dots\}$ for a sorting problem);
- t_i is the time at which the trajectory enters region R_i .

The semantic label σ_i is assigned by an interpretation function $\iota : \mathcal{S} \rightarrow \Sigma$ that maps categorical states to semantic meanings. This function is problem-specific and encodes the relationship between geometric positions in $\mathcal{S}$ and computational concepts.

Example 35.1 (Sorting Local Solutions). For a sorting problem, local solutions might include:

- $L_1 = (R_1, \text{"input_loaded"}, t_1)$: trajectory enters region where input data is encoded
- $L_2 = (R_2, \text{"pivot_selected"}, t_2)$: trajectory enters region corresponding to pivot selection
- $L_3 = (R_3, \text{"partition_left"}, t_3)$: trajectory enters region corresponding to left partition

- $L_4 = (R_4, \text{"partition_right"}, t_4)$: trajectory enters region corresponding to right partition
- $L_5 = (R_5, \text{"sorted"}, t_5)$: trajectory enters region where sorted output is recognized

Each local solution corresponds to a recognizable computational milestone.

Definition 35.2 (Solution Chain). A **solution chain** is an ordered sequence $(L_1, L_2, \dots, L_n)$ of local solutions satisfying:

1. **Temporal ordering:** $t_1 < t_2 < \dots < t_n$ (local solutions occur in sequence along the trajectory)
2. **Semantic compatibility:** Adjacent local solutions L_i and L_{i+1} are semantically compatible, meaning that the semantic label σ_{i+1} is a valid successor to σ_i according to the problem's semantic structure. Formally, there exists a compatibility relation $\rightarrow \subseteq \Sigma \times \Sigma$ such that $\sigma_i \rightarrow \sigma_{i+1}$ for all $i = 1, \dots, n-1$.
3. **Coherent interpretation:** The sequence $(L_1, \dots, L_n)$ forms a coherent interpretation of the trajectory as a computational process. This means that the semantic labels $(\sigma_1, \dots, \sigma_n)$ constitute a valid "story" of how the problem was solved.

Theorem 35.5 (Closure Recognition). A trajectory $\gamma : [0, T] \rightarrow \mathcal{S}$ is recognized as solving problem P when its solution chain $(L_1, \dots, L_n)$ satisfies the **closure condition**:

$$L_n \sim L_1 \quad (489)$$

where $\sim$ denotes semantic equivalence: $L_n \sim L_1$ if and only if $\sigma_n = \sigma_1$ (the final semantic label equals the initial semantic label).

The closure in interpretation space (semantic labels returning to their starting value) implies recurrence in $\mathcal{S}$ (geometric return to the initial region).

Proof. The semantic interpretation function $\iota : \mathcal{S} \rightarrow \Sigma$ maps regions of phase space to semantic labels. If $L_1 = (R_1, \sigma_1, t_1)$ and $L_n = (R_n, \sigma_n, t_n)$ satisfy $\sigma_n = \sigma_1$, then by definition of the interpretation function, the trajectory has returned to a region of $\mathcal{S}$ that is semantically equivalent to the initial region.

Since the interpretation function is designed to partition $\mathcal{S}$ into semantically meaningful regions, semantic equivalence implies spatial proximity. Formally, if $\iota(\mathbf{S}) = \iota(\mathbf{S}')$, then $\|\mathbf{S} - \mathbf{S}'\| \leq \epsilon_{\text{sem}}$, where ϵ_{sem} is the semantic resolution (the maximum diameter of a semantic region).

Therefore:

$$\sigma_n = \sigma_1 \implies \iota(\gamma(t_n)) = \iota(\gamma(t_1)) \implies \|\gamma(t_n) - \gamma(t_1)\| \leq \epsilon_{\text{uni}} \quad (490)$$

Since $\gamma(t_1) \approx \gamma(0) = \mathbf{S}_0$ (the first local solution occurs near the initial state), we have:

$$\|\gamma(t_n) - \mathbf{S}_0\| \leq \|\gamma(t_n) - \gamma(t_1)\| + \|\gamma(t_1) - \mathbf{S}_0\| \leq \epsilon_{\text{sem}} + \delta \quad (491)$$

for some small $\delta > 0$. Setting $\epsilon = \epsilon_{\text{sem}} + \delta$, we obtain the recurrence condition $\|\gamma(T) - \mathbf{S}_0\| < \epsilon$ (where $T \approx t_n$).

Therefore, closure in interpretation space (semantic return) implies recurrence in $\mathcal{S}$ (geometric return), establishing that the trajectory solves the problem. $\square$

Remark 35.3 (Indirect Recurrence Verification). Theorem 35.5 provides the mechanism for recognizing solutions without direct access to the initial state $\mathbf{S}_0$. Instead of comparing $\gamma(T)$ with $\mathbf{S}_0$ (which is impossible by Corollary 35.4), we compare the semantic labels σ_n with σ_1 (which are both observable). This indirect verification circumvents the origin inaccessibility problem.

35.4 The Asymptotic Nature of Solutions

Poincaré's recurrence theorem guarantees that trajectories return arbitrarily close to their initial states, but it does not guarantee exact return. This asymptotic nature of recurrence has important implications for solution recognition and complexity measurement.

Theorem 35.6 (Asymptotic Return). *For almost every initial state $\mathbf{S}_0 \in \mathcal{S}$, the trajectory $\gamma(t)$ never returns exactly to $\mathbf{S}_0$. Instead, for any $\epsilon > 0$, there exist infinitely many times $T_1, T_2, T_3, \dots$ such that:*

$$\gamma(T_i) \in B_\epsilon(\mathbf{S}_0) \setminus \{\mathbf{S}_0\} \quad (492)$$

*The solution lies in the **punctured neighborhood** of the origin—the ϵ -ball with the origin removed.*

Proof. Two obstructions prevent exact return for almost every initial state.

Measure-theoretic obstruction: In measure-preserving dynamical systems on compact manifolds, the set of exactly periodic orbits (orbits that return exactly to their initial states after a finite time) has measure zero [10]. Almost all trajectories are either quasi-periodic (dense on invariant tori) or aperiodic (never returning exactly). Therefore, for almost every $\mathbf{S}_0$, the trajectory $\gamma(t)$ satisfies $\gamma(t) \neq \mathbf{S}_0$ for all $t > 0$.

Categorical obstruction: The hierarchical partition $\mathcal{P}_k$ (Definition 21.2) assigns each point in $\mathcal{S}$ to a unique cell. When the trajectory departs from the initial cell containing $\mathbf{S}_0$, that cell is marked as "visited" or "completed" according to the categorical completion principle. The categorical dynamics are designed to avoid re-visiting completed cells (to ensure progress toward constraint satisfaction), so the returning trajectory must enter an adjacent cell rather than the exact initial cell.

Formally, if $\mathbf{S}_0 \in C_0 \in \mathcal{P}_k$ and the trajectory departs at time $t_{\text{dep}} > 0$, then for all $t > t_{\text{dep}}$, the trajectory satisfies $\gamma(t) \notin C_0$ until it approaches the boundary of C_0 from outside. The closest approach is to the boundary ∂C_0 , not to the interior point $\mathbf{S}_0$.

Combining these obstructions, we conclude that $\gamma(t) \neq \mathbf{S}_0$ for almost every initial state and all $t > 0$. The trajectory returns to arbitrarily small neighborhoods $B_\epsilon(\mathbf{S}_0)$ but never to the exact point $\mathbf{S}_0$. $\square$

Definition 35.3 (Problem-Solution Identity). At the initial state $\mathbf{S}_0$, the problem specification and the solution are identical:

$$\mathbf{S}_0 = \mathbf{S}_{\text{problem}} = \mathbf{S}_{\text{solution}} \quad (493)$$

The difference between problem and solution is zero at, and only at, the origin. For all $t > 0$, the trajectory $\gamma(t)$ represents a partial solution with non-zero difference from the complete solution.

This definition captures a profound property of Poincaré Computing: the problem and its solution are not separate entities but are unified at the initial state. The computation consists of departing from this unified state, exploring phase space to satisfy constraints, and returning to (near) the unified state, at which point the solution is recognized.

Proposition 35.7 (Solution as Approximation). *Solving a problem means reducing the problem-solution difference below a threshold ϵ :*

$$\text{Solved} \iff \|\mathbf{S}_{\text{problem}} - \mathbf{S}_{\text{solution}}\|_{\gamma(T)} < \epsilon \quad (494)$$

where $\mathbf{S}_{\text{problem}} = \mathbf{S}_0$ and $\mathbf{S}_{\text{solution}} = \gamma(T)$. The difference is never exactly zero for $T > 0$.

Proof. At $t = 0$, the problem and solution coincide: $\mathbf{S}_{\text{problem}} = \mathbf{S}_0 = \gamma(0) = \mathbf{S}_{\text{solution}}$, so the difference is zero.

For $t > 0$, the trajectory has departed from $\mathbf{S}_0$, and by Theorem 35.6, it never returns exactly. Therefore, $\|\gamma(t) - \mathbf{S}_0\| > 0$ for all $t > 0$.

The best achievable is ϵ -proximity: $\|\gamma(T) - \mathbf{S}_0\| < \epsilon$ for arbitrarily small $\epsilon > 0$. This ϵ -proximity is

what we mean by "solving" the problem—reducing the problem-solution difference below the tolerance threshold. $\square$

Remark 35.4 (Implications for Exactness). Proposition 35.7 establishes that Poincaré Computing produces approximate solutions, not exact solutions. This is not a limitation but a fundamental property of continuous dynamics in bounded phase space. The tolerance ϵ can be made arbitrarily small (by increasing the hierarchical depth k), but it cannot be reduced to zero. This contrasts with Turing computation, where exact solutions are the norm (e.g., a Turing machine computing $2 + 2$ produces exactly 4, not approximately 4).

35.5 Categorical Completion Rate

Having established the epistemological constraints on complexity measurement (origin inaccessibility, asymptotic return), we now define the fundamental measure of computational progress in Poincaré Computing.

Definition 35.4 (Categorical Completion Event). A **categorical completion event** occurs when the trajectory γ exits a cell $C \in \mathcal{P}_k$ of the hierarchical partition. At the moment of exit, the cell is marked as "visited" or "completed," indicating that the trajectory has explored that region of phase space.

Formally, a completion event occurs at time t_{exit} when:

$$\gamma(t_{\text{exit}}) \in \partial C \quad \text{and} \quad \frac{d}{dt} \|\gamma(t) - C\|_{t=t_{\text{exit}}} > 0 \quad (495)$$

where ∂C is the boundary of cell C and the derivative condition ensures that the trajectory is leaving (not entering) the cell.

Definition 35.5 (Promising Trajectory). A trajectory segment $\gamma|_{[t, t+\delta]}$ is **promising** if it moves toward regions of higher constraint satisfaction. Formally, the segment is promising if:

$$\mathcal{C}_{\text{partial}}(\gamma|_{[0, t+\delta]}) \geq \mathcal{C}_{\text{partial}}(\gamma|_{[0, t]}) \quad (496)$$

where $\mathcal{C}_{\text{partial}} : C([0, T], \mathcal{S}) \rightarrow [0, 1]$ is a partial constraint satisfaction measure that quantifies the fraction of constraints satisfied by a trajectory segment.

Intuitively, a promising trajectory is one that makes progress toward satisfying the problem constraints, as opposed to a trajectory that wanders aimlessly or moves away from constraint satisfaction.

Definition 35.6 (Categorical Completion Rate). The **categorical completion rate** ρ_C is the number

of categorical completion events per unit of promising trajectory length in $\mathcal{S}$:

$$\rho_C = \frac{N_{\text{completions}}}{L_{\text{promising}}} \quad (497)$$

where:

- $N_{\text{completions}}$ is the number of cells exited by the trajectory (number of completion events);
- $L_{\text{promising}} = \int_{\text{promising}} \|\dot{\gamma}(t)\| dt$ is the arc length of the promising portions of the trajectory, measured in $\mathcal{S}$ distance (not physical time).

The categorical completion rate has units of [completions per unit $\mathcal{S}$ -distance], making it a geometric property of the trajectory.

Theorem 35.8 (Rate Independence from Physical Time). *The categorical completion rate ρ_C is independent of physical time. It depends only on the geometry of $\mathcal{S}$, the hierarchical partition $\mathcal{P}_k$, and the constraint structure $\mathcal{C}$.*

Proof. We establish independence by showing that ρ_C is defined entirely in terms of geometric quantities, with no reference to physical time.

Numerator (completions): The number of completion events $N_{\text{completions}}$ is determined by counting how many cells in $\mathcal{P}_k$ the trajectory exits. This is a geometric property: it depends on the trajectory's path through $\mathcal{S}$ (which cells it visits) but not on the time parameterization of the path. Two trajectories that trace the same geometric curve through $\mathcal{S}$ at different speeds (different t -parameterizations) have the same $N_{\text{completions}}$.

Denominator (promising length): The arc length $L_{\text{promising}}$ is computed by integrating the speed $\|\dot{\gamma}(t)\|$ over the promising portions of the trajectory:

$$L_{\text{promising}} = \int_{\text{promising}} \|\dot{\gamma}(t)\| dt = \int_{\text{promising}} \sqrt{\left(\frac{dS_k}{dt}\right)^2 + \left(\frac{dS_t}{dt}\right)^2 + \dots} dt \quad (498)$$

This integral measures the length of the curve γ in $\mathcal{S}$, which is a geometric invariant. If we reparameterize the trajectory by a different time variable $\tau = h(t)$ (where h is a monotonic function), the arc length remains unchanged:

$$L = \int \|\dot{\gamma}(t)\| dt = \int \left\| \frac{d\gamma}{d\tau} \right\| \frac{d\tau}{dt} dt = \int \left\| \frac{d\gamma}{d\tau} \right\| d\tau \quad (499)$$

Therefore, the arc length $L_{\text{promising}}$ is independent of the time parameterization.

Rate: Since both the numerator and denominator are independent of the time parameterization, the ratio $\rho_C = N_{\text{completions}}/L_{\text{promising}}$ is also independent of time. A faster or slower physical clock (corresponding to a different time parameterization) produces the same categorical completion rate.

The rate depends only on:

- The geometry of $\mathcal{S}$ (the metric structure determining arc length);
- The hierarchical partition $\mathcal{P}_k$ (determining which cells are exited);
- The constraint structure $\mathcal{C}$ (determining which portions of the trajectory are promising).

These are all intrinsic properties of the problem and the trajectory, not of the physical implementation. $\square$

Corollary 35.9 (Physical Implementation Invariance). *Two physical implementations of Poincaré Computing with different clock speeds, different oscillator frequencies, and different hardware architectures produce identical categorical completion rates ρ_C if they instantiate the same trajectory γ in $\mathcal{S}$.*

Proof. By Theorem 35.8, the categorical completion rate depends only on the geometry of the trajectory in $\mathcal{S}$, not on the physical parameters of the implementation. If two implementations produce the same trajectory γ (the same curve in $\mathcal{S}$), they have the same ρ_C , regardless of differences in clock speed, oscillator frequencies, or hardware architecture.

This invariance is analogous to the fact that two Turing machines with different clock speeds (one running at 1 GHz, another at 10 GHz) execute the same algorithm with the same number of steps, even though the faster machine completes the computation in less physical time. The number of steps is an intrinsic property of the algorithm, not of the physical implementation. Similarly, the categorical completion rate is an intrinsic property of the trajectory, not of the physical implementation. $\square$

35.6 Poincaré Complexity

We now define the fundamental complexity measure for Poincaré Computing, analogous to time complexity $T(n)$ in Turing computation.

Definition 35.7 (Poincaré Complexity). The **Poincaré complexity** of a problem $P = (\mathbf{S}_0, \mathcal{C}, \epsilon)$ is the minimum number of local solutions required to

recognize closure:

$$\Pi(P) = \inf_{\gamma \in \mathcal{A}(P)} \{n : (L_1, \dots, L_n) \text{ is a solution chain with } L_n \sim L_1\} \quad (500)$$

In other words, $\Pi(P)$ is the length of the shortest solution chain among all trajectories that solve problem P . This measures the minimum number of categorical transitions (local solution recognitions) required to solve the problem.

Theorem 35.10 (Complexity Lower Bound). *For a problem P with recurrence tolerance ϵ in the depth- k hierarchical partition, the Poincaré complexity satisfies:*

$$\Pi(P) \geq \log_3 \left(\frac{1}{\epsilon} \right) \quad (501)$$

Proof. The recurrence tolerance ϵ determines the required resolution of the hierarchical partition. To distinguish states within distance ϵ , the partition must have cell diameter at most ϵ . In the ternary hierarchical partition $\mathcal{P}_k$, cells at depth k have diameter approximately 3^{-k} (since each coordinate is divided into 3^k levels).

To achieve cell diameter $\leq \epsilon$, we require:

$$3^{-k} \leq \epsilon \Rightarrow k \geq \log_3(1/\epsilon) \quad (502)$$

Each local solution corresponds to at least one cell transition (exiting one cell and entering another). To navigate from the initial cell to a cell within distance ϵ of the origin requires traversing at least k cells (one per level of the hierarchy, in the most efficient case).

Therefore, the number of local solutions satisfies:

$$n \geq k \geq \log_3(1/\epsilon) \quad (503)$$

Taking the infimum over all solution chains gives $\Pi(P) \geq \log_3(1/\epsilon)$. $\square$

Remark 35.5 (Exponential Scaling). Theorem 35.10 establishes that Poincaré complexity scales logarithmically with $1/\epsilon$, or equivalently, exponentially with the required precision. This is consistent with the recurrence time bound in Corollary 29.4, which showed that expected recurrence time scales as $O(1/\epsilon)$. The exponential scaling reflects the hierarchical structure of $\mathcal{S}$: each additional level of precision requires exploring exponentially more cells.

Proposition 35.11 (Complexity Additivity). *For independent problems P_1 and P_2 (problems with disjoint constraint sets), the Poincaré complexity of the product problem satisfies:*

$$\Pi(P_1 \times P_2) = \Pi(P_1) + \Pi(P_2) \quad (504)$$

where $P_1 \times P_2$ is the problem in the product space $\mathcal{S} \times \mathcal{S}$ that requires solving both P_1 and P_2 simultaneously.

figures/complexity_panel.png

Figure 20: **Complexity Theory Validation.** **(A) Poincaré Complexity:** Poincaré complexity $\Pi(P)$ (measured in Poincarés, the natural unit of categorical complexity) scales sub-linearly with problem size n . For $n = 10$: $\Pi(P) \approx 8$; $n = 20$: $\Pi(P) \approx 15$; $n = 50$: $\Pi(P) \approx 38$; $n = 100$: $\Pi(P) \approx 72$. **(B) Categorical Completion Rate:** Completion rate $p_C(t) = d|\gamma(t)|/dt$ (completions per unit time) fluctuates around mean $\langle p_C \rangle = 5.0$ (dashed line). **(C) S_0 Unknowability (No Perfect Inference):** Distribution of inference error $|S_0^{\text{inferred}} - S_0^{\text{true}}|$ for initial S-entropy state. Perfect inference (vertical dashed line at zero) is never achieved; errors are distributed over $[0.02, 0.20]$ with mode at ≈ 0.05 . **(D) Asymptotic Return (Never Zero):** Distance to initial state $\|\gamma(t) - S_0\|$ (orange curve, log scale) decreases exponentially but never reaches zero (horizontal dashed line). **(E) Solution Chain Closure:** Polar plot of trajectory distance to initial state vs. angular position (proxy for categorical completion order). Trajectory starts at 0° (green marker), explores to maximum distance at $\approx 90^\circ$, and returns near start at $\approx 315^\circ$ (yellow marker), stopping at penultimate state (red marker) one step from closure. **(F) Turing-Poincaré Incommensurability:** Scatter plot of Turing complexity (Kolmogorov complexity $K(P)$, vertical axis) vs. Poincaré complexity ($\Pi(P)$, horizontal axis) for 30 problems. (Theorem ??).

Proof. In the product space $\mathcal{S} \times \mathcal{S}$, a trajectory is a pair $(\gamma_1(t), \gamma_2(t))$ where γ_1 solves P_1 and γ_2 solves P_2 . Local solutions in the product space decompose into pairs $(L_i^{(1)}, L_j^{(2)})$ where $L_i^{(1)}$ is a local solution for P_1 and $L_j^{(2)}$ is a local solution for P_2 .

Closure in the product space requires both components to close:

$$(L_n^{(1)}, L_m^{(2)}) \sim (L_1^{(1)}, L_1^{(2)}) \iff L_n^{(1)} \sim L_1^{(1)} \text{ and } L_m^{(2)} \sim L_1^{(2)} \quad (505)$$

The minimum number of local solutions in the product space is achieved when both chains are minimal:

$$\Pi(P_1 \times P_2) = n + m = \Pi(P_1) + \Pi(P_2) \quad (506)$$

This additivity property is analogous to the additivity of time complexity for independent subproblems in traditional computation: $T(n_1 + n_2) = T(n_1) + T(n_2)$ for independent problems. $\square$

35.7 Units of Computation: The Poincaré

We now introduce the fundamental unit of computation for Poincaré Computing, analogous to the "operation" in traditional computation.

Definition 35.8 (The Poincaré (Unit)). One **Poincaré**, denoted $\mathbb{P}$, is the computational cost of one local solution recognition—one step toward closure in interpretation space. It represents the cost of completing one categorical transition: exiting one cell of the hierarchical partition, recognizing the associated semantic label, and entering the next cell.

The Poincaré is the fundamental unit of computational progress in trajectory-based computation.

Remark 35.6 (Poincaré vs. FLOPS). Unlike FLOPS (floating-point operations per second), which is a rate (operations per unit time), the Poincaré is a count (number of categorical transitions). The total computational cost of solving problem P is $\Pi(P)$ Poincarés, independent of how long the computation takes in physical time.

This distinction reflects the fundamental difference between operational and trajectory-based computation:

- Operational computation: cost = (operations) $\times$ (time per operation)
- Trajectory computation: cost = (categorical transitions), with time irrelevant

Definition 35.9 (Categorical Throughput). The **categorical throughput** of a Poincaré Computing system is:

$$\Theta = \rho_C \cdot v_\gamma \quad (507)$$

where:

- ρ_C is the categorical completion rate (Definition 35.6);
- $v_\gamma = \|\dot{\gamma}\|$ is the arc-length velocity of promising trajectories in $\mathcal{S}$.

The throughput Θ has units of [completions per unit time], making it the Poincaré Computing analog of FLOPS. However, unlike FLOPS, Θ depends on the trajectory geometry (through ρ_C) and the dynamics (through v_γ), not just on hardware parameters.

Proposition 35.12 (Throughput-Complexity Relation). *The expected solution time for problem P scales as:*

$$T_{\text{solution}} \propto \frac{\Pi(P)}{\Theta} \quad (508)$$

Problems with higher Poincaré complexity $\Pi(P)$ require more categorical completions; systems with higher categorical throughput Θ complete them faster.

Proof. The total computational cost is $\Pi(P)$ Poincarés (Definition 35.7). The system completes categorical transitions at rate Θ Poincarés per unit time (Definition 35.9). Therefore, the time required to complete $\Pi(P)$ transitions is:

$$T_{\text{solution}} = \frac{\Pi(P)}{\Theta} \quad (509)$$

This is the Poincaré Computing analog of the relation $T = N_{\text{ops}}/\text{FLOPS}$ in traditional computation, where N_{ops} is the number of operations and FLOPS is the operation rate. $\square$

35.8 Comparison with Classical Complexity

We now compare the complexity framework developed for Poincaré Computing with traditional Turing/von Neumann complexity theory.

Theorem 35.13 (Incommensurability). *Poincaré complexity $\Pi(P)$ and Turing time complexity $T(n)$ are incommensurable: there exists no general conversion function f such that $\Pi(P) = f(T(n))$ or $T(n) = g(\Pi(P))$ for all problems.*

Property	Turing/von Neumann	Poincaré Computing
Basic unit	Instruction/operation	identical Turing complexity $T(n) = n^2$ (e.g., two different sorting algorithms, both quadratic)
Complexity measure	Time $T(n)$, space $S(n)$	Local solution (P) Poincaré complexities $\Pi(P_1) \neq \Pi(P_2)$ (because they have different trajectory geometries in $\mathcal{S}$). This contradicts the existence of f .
Rate measure	FLOPS, IPC	Categorical rate ρ_C Absent (geometric property)
Time dependence	Essential (operations per second)	Therefore, Poincaré complexity and Turing complexity are incommensurable: they measure fundamentally different aspects of computation and cannot be converted into each other. $\square$
Initial state	Known input on tape	Unknown, inferred from trajectory
Solution criterion	Halting in accept state	Closure recognition $L_P \sim L_{P'}$
Exactness	Exact answer	ϵ -approximation
Determinism	Single path from input	Multiple paths (Theorem 29.7)
Completeness	Turing completeness	Remark 35.7 (Implications for Complexity Classes). The incommensurability of Poincaré and Turing complexity implies that traditional complexity classes (P, NP, PSPACE, etc.) do not directly apply to Poincaré Computing. These classes are defined in terms of Turing machine time and space complexity, which are not meaningful for trajectory-based computation. A new hierarchy of complexity classes, based on Poincaré complexity $\Pi(P)$ and categorical throughput Θ , would be required to classify problems in Poincaré Computing. The development of such a hierarchy is left for future work.

Table 4: **Comparison of complexity frameworks.** Poincaré Computing and traditional computation differ in every fundamental aspect of complexity measurement, reflecting their categorical distinction as computational paradigms.

Proof. We establish incommensurability by showing that the two complexity measures are defined in terms of fundamentally different quantities that cannot be related by a general conversion.

Different basic units: Turing complexity $T(n)$ counts discrete operations (state transitions, tape movements, symbol writes) as a function of input size n . Poincaré complexity $\Pi(P)$ counts local solution recognitions (categorical transitions) as a function of problem structure P . The quantities being counted are categorically different:

- Turing operations are discrete, sequential, and algorithmic;
- Poincaré transitions are continuous, geometric, and trajectory-based.

Different dependencies: Turing complexity depends on the algorithm (the transition function δ), which does not exist in Poincaré Computing (Theorem 33.1). Poincaré complexity depends on the trajectory geometry and constraint structure, which do not exist in Turing computation.

Different equivalence relations: Two Turing machines computing the same function via different algorithms have different time complexities $T_1(n) \neq T_2(n)$. Two Poincaré problems that are answer-equivalent (Theorem 33.3) may have completely different complexities $\Pi(P_1) \neq \Pi(P_2)$ because they have different trajectory geometries.

No bijection: Suppose there existed a conversion function $f : \mathbb{N} \rightarrow \mathbb{N}$ such that $\Pi(P) = f(T(n))$ for all problems. Then problems with the same Turing complexity would have the same Poincaré complexity. However, we can construct two problems with

35.9 Measurement and Observation

We conclude this section by discussing the practical aspects of measuring complexity in Poincaré Computing.

Proposition 35.14 (Per-Category Measurement). *Measurement in Poincaré Computing occurs per categorical completion event, not per unit time. The observable is the sequence of local solutions $(L_1, L_2, \dots)$, obtained as the trajectory completes categories (exits cells in $\mathcal{P}_k$).*

Proof. Local solutions are recognized when the trajectory exits a cell in the hierarchical partition $\mathcal{P}_k$ (Definition 35.1). This is a geometric event in $\mathcal{S}$: the trajectory crosses the boundary ∂C of a cell C . The event is detected by monitoring the categorical state $\mathbf{S}(t)$ and recognizing when it transitions from one cell to another.

This detection is independent of physical time: the event occurs when the geometric condition $\mathbf{S}(t) \in \partial C$ is satisfied, regardless of when this occurs on the clock. The measurement apparatus (virtual spectrometer, Section 25) is synchronized to categorical transitions, not to a time-based clock.

Therefore, measurement is per-category (per cell exit), not per-time (per clock cycle). $\square$

Corollary 35.15 (Asynchronous Computation). *Poincaré Computing is inherently asynchronous. There is no global clock governing computation. Progress is measured by categorical completion*

events, which occur at irregular intervals determined by the trajectory dynamics, not by a regular clock signal.

Proof. In traditional synchronous computation, a global clock signal triggers state transitions at regular intervals (e.g., every nanosecond for a 1 GHz clock). All components of the system are synchronized to this clock.

In Poincaré Computing, there is no such global clock. The categorical state $\mathbf{S}(t)$ evolves continuously according to the dynamics (373)–(375), and categorical completion events occur when the trajectory crosses cell boundaries. These crossings occur at irregular intervals determined by the trajectory geometry, not by a regular clock.

For example, if the trajectory moves slowly through a dense region of cells, completion events occur frequently. If the trajectory moves quickly through a sparse region, completion events occur infrequently. The rate of completion events varies dynamically, making the computation asynchronous. $\square$

Remark 35.8 (Synchronization Protocols). Corollary 35.15 has practical implications for distributed Poincaré Computing systems. Synchronization between multiple Poincaré processors cannot use time-based protocols (e.g., "synchronize at time $t = 1$ second") because time is not the fundamental parameter. Instead, synchronization must use categorical-state-based protocols: systems synchronize when their solution chains reach compatible states (e.g., "synchronize when both systems reach local solution L_5 "), not when their clocks align.

This categorical synchronization is analogous to dataflow synchronization in asynchronous circuits, where components synchronize based on data availability rather than clock signals.

This section has established a complexity theory for Poincaré Computing based on categorical completion rates and Poincaré complexity. We have proven that traditional operation-based measures are inapplicable, that the initial state is unknowable, that solutions are recognized through local accumulation, and that complexity is measured in Poincarés rather than operations. The categorical completion rate is independent of physical time and hardware implementation, making it an intrinsic geometric property of the trajectory-constraint system. Poincaré complexity and Turing complexity are incommensurable, reflecting the categorical distinction between trajectory-based and operational computation.

36 Exhaustive Computing and Emergent Memory

37 Exhaustive Exploration and Emergent Memory

One of the most striking differences between Poincaré Computing and traditional computation lies in their behavior when not actively solving a problem. A Turing machine, upon reaching a halting state, stops: the tape head freezes, the state remains fixed, and no further computation occurs until a new input is provided and the machine is restarted. The machine is either computing (executing transitions) or halted (doing nothing), with no intermediate state. Memory is explicitly stored on the tape through write operations, and the machine's capability remains static unless it is reprogrammed.

Poincaré Computing exhibits fundamentally different behavior. The categorical dynamics have no halting condition: trajectories continue to evolve indefinitely, exploring phase space even when no problem is actively being solved. This continuous exploration is not wasted motion but serves multiple computational purposes: it accumulates an implicit **exploration memory** of visited regions in $\mathcal{S}$, it discovers alternative solution paths that provide robustness, and it progressively reduces the complexity of solving related problems. Memory emerges from the trajectory history rather than from explicit storage operations, and computational capability increases monotonically with time through a process we call **self-refinement**.

This section establishes the mathematical foundations of these emergent properties. We prove that the categorical dynamics never halt (Theorem 37.1), that the exploration memory grows monotonically and eventually covers all of $\mathcal{S}$ (Theorem 37.4), and that memory accumulates simply by the system existing (Theorem 37.5). We show that prior exploration reduces the complexity of subsequent related problems (Theorem 37.7), with the reduction scaling logarithmically with problem relatedness (Theorem 37.9). We prove that idle exploration is computationally productive, discovering alternative solution paths and increasing path redundancy (Theorem 37.11). Finally, we establish that system capability is monotonically non-decreasing (Theorem 37.13), leading to automatic self-refinement without external programming (Theorem 37.15).

These results have profound implications for computational architecture. They suggest that Poincaré Computing systems naturally develop "expertise" in

domains through repeated exposure to related problems, that idle time is productive rather than wasted, and that computational capability accumulates as an inevitable consequence of existence. This stands in stark contrast to traditional systems, where capability is static and idle time is unproductive.

37.1 Non-Halting Dynamics

We begin by establishing that the categorical dynamics have no halting condition, in contrast to Turing machines which are designed to halt upon reaching accept or reject states.

Theorem 37.1 (Inexhaustibility). *The categorical dynamics (373)–(375) have no halting condition. For almost every initial state $\mathbf{S}_0 \in \mathcal{S}$, the trajectory $\gamma(t)$ is defined for all $t \in [0, \infty)$ and satisfies:*

$$\left\| \frac{d\mathbf{S}}{dt} \right\| = \|\mathbf{F}(\mathbf{S}(t))\| > 0 \quad \text{for almost all } t \geq 0 \quad (510)$$

The trajectory never stops moving through $\mathcal{S}$.

Proof. We establish two properties: (1) solutions exist for all time, and (2) the trajectory has non-zero velocity almost everywhere.

(1) Global existence: The categorical dynamics are defined by the vector field $\mathbf{F} : \mathcal{S} \rightarrow \mathbb{R}^3$ (equation (377)):

$$\frac{d\mathbf{S}}{dt} = \mathbf{F}(\mathbf{S}) \quad (511)$$

The vector field $\mathbf{F}$ is smooth (infinitely differentiable) on the interior of $\mathcal{S}$ because it is composed of polynomial and trigonometric functions. On the compact domain $\mathcal{S} = [0, 1]^3$, smooth vector fields are Lipschitz continuous: there exists a constant $L > 0$ such that:

$$\|\mathbf{F}(\mathbf{S}_1) - \mathbf{F}(\mathbf{S}_2)\| \leq L\|\mathbf{S}_1 - \mathbf{S}_2\| \quad \forall \mathbf{S}_1, \mathbf{S}_2 \in \mathcal{S} \quad (512)$$

By the Picard-Lindelöf theorem (also called the Cauchy-Lipschitz theorem) [3], for any initial condition $\mathbf{S}_0 \in \mathcal{S}$, there exists a unique solution $\gamma : [0, T_{\max}) \rightarrow \mathcal{S}$ where $T_{\max}$ is the maximal time of existence. For Lipschitz continuous vector fields on compact domains, $T_{\max} = \infty$: solutions exist for all time.

This is because solutions can only cease to exist if they "escape to infinity" (leave the domain) or encounter a singularity (point where $\mathbf{F}$ is not defined). Since $\mathcal{S}$ is compact and $\mathbf{F}$ is smooth everywhere on $\mathcal{S}$, neither can occur. Therefore, $\gamma(t)$ is defined for all $t \in [0, \infty)$.

(2) Non-zero velocity: The velocity of the trajectory is $\|\dot{\gamma}(t)\| = \|\mathbf{F}(\gamma(t))\|$. The trajectory has zero velocity only at fixed points where $\mathbf{F}(\mathbf{S}) = 0$.

By Theorem 27.5, the categorical dynamics admit fixed points only at $\mathbf{S}_1^* = (0, 0, 0)$ and $\mathbf{S}_2^* = (1/2, 1/2, 1/2)$ (and their periodic equivalents under the torus topology). The set of fixed points is finite, hence has measure zero in $\mathcal{S}$.

For almost every initial condition $\mathbf{S}_0$ (all except a measure-zero set), the trajectory $\gamma(t)$ avoids fixed points for all $t > 0$. At any point $\mathbf{S} \neq \mathbf{S}_i^*$, the vector field satisfies $\|\mathbf{F}(\mathbf{S})\| > 0$ (by continuity and the fact that $\mathbf{F}$ vanishes only at fixed points). Therefore, $\|\dot{\gamma}(t)\| > 0$ for almost all t .

Combining (1) and (2), we conclude that for almost every initial state, the trajectory exists for all time and has non-zero velocity almost everywhere, establishing inexhaustibility. $\square$

Corollary 37.2 (No Halt State). *Unlike Turing machines, which halt upon reaching designated accept or reject states, Poincaré Computing systems have no mechanism for termination. The dynamics continue indefinitely, regardless of whether a solution has been found.*

Proof. In a Turing machine, the transition function $\delta : Q \times \Gamma \rightarrow Q \times \Gamma \times \{L, R\}$ is undefined for certain states $q \in Q$ (the halting states q_{accept} and q_{reject}). When the machine enters a halting state, no further transitions are defined, and the machine stops.

In Poincaré Computing, the vector field $\mathbf{F}$ is defined everywhere on $\mathcal{S}$ (Theorem 37.1). There are no "halting states" where the dynamics are undefined. Even at fixed points (where $\mathbf{F} = 0$), the dynamics are defined—the trajectory simply remains at the fixed point. For almost every initial condition, the trajectory avoids fixed points and continues moving indefinitely.

Therefore, there is no halting mechanism in Poincaré Computing. The system never stops. $\square$

Remark 37.1 (Solution Recognition vs. Halting). It is crucial to distinguish between *solution recognition* (detecting that a problem has been solved) and *halting* (stopping the dynamics). In Poincaré Computing, solution recognition occurs when the trajectory satisfies the closure condition $L_n \sim L_1$ (Theorem 35.5), but this recognition does not halt the dynamics. The trajectory continues to evolve after the solution is recognized.

This is analogous to a Turing machine that prints its output but continues executing (perhaps performing additional computations or entering an infinite loop). The difference is that in Poincaré Computing, the continued execution is not an error or inefficiency but is an essential feature: the continued exploration



Figure 21: **Virtual Gas Ensemble: One Molecule Becomes All Through S-Entropy Sliding Windows.** **Window t_1 : Observing α :** Left diagram shows observation window (blue circle α) isolated from β and γ (dashed lines). S-entropy coordinates $\mathbf{S} = [1.00, 1.00, 0.91]$. **Window t_3 : $\beta + \gamma$:** Left diagram shows window shifted to include β and γ (orange), excluding α . S-entropy coordinates $\mathbf{S} = [1.00, 1.00, 0.94]$. **Window t_4 : Cycle Complete:** Left diagram shows window returned to original configuration (all three molecules visible).

accumulates memory and reduces the complexity of future problems, as we establish below.

37.2 Exploration Memory

The continuous evolution of the trajectory through $\mathcal{S}$ creates an implicit memory structure: the set of regions (categories) that have been visited. This **exploration memory** is not stored explicitly in a data structure but emerges from the trajectory history.

Definition 37.1 (Exploration Memory). The **exploration memory** at time T is the set of categories (cells in the hierarchical partition $\mathcal{P}_k$) that have been visited by the trajectory up to time T :

$$\mathcal{M}(T) = \{C \in \mathcal{P}_k : \exists t \in [0, T], \gamma(t) \in C\} \quad (513)$$

Equivalently, $\mathcal{M}(T)$ is the set of cells whose interiors intersect the trajectory:

$$\mathcal{M}(T) = \{C \in \mathcal{P}_k : C \cap \gamma([0, T]) \neq \emptyset\} \quad (514)$$

The exploration memory records which regions of phase space have been explored. This information is implicit: it is not stored in a separate memory device but is encoded in the trajectory itself. To determine whether a cell C has been visited, one must examine the trajectory history $\gamma([0, T])$.

Proposition 37.3 (Memory Monotonicity). *Exploration memory is monotonically non-decreasing: once a category is visited, it remains in the exploration memory forever.*

$$T_1 < T_2 \implies \mathcal{M}(T_1) \subseteq \mathcal{M}(T_2) \quad (515)$$

Proof. If a category C was visited at some time $t_1 \in [0, T_1]$, then $\gamma(t_1) \in C$, so $C \in \mathcal{M}(T_1)$ by definition. For any $T_2 > T_1$, the trajectory segment $\gamma([0, T_1])$ is a subset of $\gamma([0, T_2])$, so $\gamma(t_1) \in C$ still holds. Therefore, $C \in \mathcal{M}(T_2)$.

This establishes that every category in $\mathcal{M}(T_1)$ is also in $\mathcal{M}(T_2)$, giving $\mathcal{M}(T_1) \subseteq \mathcal{M}(T_2)$.

Crucially, there is no mechanism for "forgetting" or removing categories from $\mathcal{M}$. The exploration memory only grows; it never shrinks. $\square$

Definition 37.2 (Memory Density). The **memory density** at time T is the fraction of the categorical space that has been explored:

$$\rho_M(T) = \frac{|\mathcal{M}(T)|}{|\mathcal{P}_k|} = \frac{|\mathcal{M}(T)|}{3^{3k}} \quad (516)$$

where $|\mathcal{M}(T)|$ is the number of visited categories and $|\mathcal{P}_k| = 3^{3k}$ is the total number of categories at depth k (Section 21).

The memory density satisfies $0 \leq \rho_M(T) \leq 1$, with $\rho_M(T) = 0$ meaning no exploration has occurred and $\rho_M(T) = 1$ meaning the entire categorical space has been visited.

Theorem 37.4 (Asymptotic Exhaustion). *For ergodic measure-preserving dynamics on $\mathcal{S}$, the exploration memory eventually covers the entire categorical space:*

$$\lim_{T \rightarrow \infty} \rho_M(T) = 1 \quad (517)$$

Almost every category is visited given sufficient time.

Proof. We apply Birkhoff's ergodic theorem [5], which states that for an ergodic measure-preserving transformation φ_t on a probability space (X, μ) , the time average of any integrable function f equals the space average:

$$\lim_{T \rightarrow \infty} \frac{1}{T} \int_0^T f(\varphi_t(x)) dt = \int_X f d\mu \quad \text{for } \mu\text{-almost every } x \quad (518)$$

For any category $C \in \mathcal{P}_k$, define the indicator function:

$$\mathbf{1}_C(\mathbf{S}) = \begin{cases} 1 & \text{if } \mathbf{S} \in C \\ 0 & \text{if } \mathbf{S} \notin C \end{cases} \quad (519)$$

Applying Birkhoff's theorem with $f = \mathbf{1}_C$ and $x = \mathbf{S}_0$:

$$\lim_{T \rightarrow \infty} \frac{1}{T} \int_0^T \mathbf{1}_C(\gamma(t)) dt = \int_{\mathcal{S}} \mathbf{1}_C d\mu = \mu(C) \quad (520)$$

The left-hand side is the fraction of time the trajectory spends in category C . Since each category has positive measure $\mu(C) = 3^{-3k} > 0$ (categories have equal measure in the uniform partition), the time average is positive:

$$\lim_{T \rightarrow \infty} \frac{1}{T} \int_0^T \mathbf{1}_C(\gamma(t)) dt = 3^{-3k} > 0 \quad (521)$$

This implies that the trajectory spends a positive fraction of time in C , which means the trajectory visits C infinitely often. In particular, C is visited at least once, so $C \in \mathcal{M}(T)$ for sufficiently large T .

Since this argument applies to every category $C \in \mathcal{P}_k$, we conclude that every category is eventually visited. Therefore:

$$\lim_{T \rightarrow \infty} |\mathcal{M}(T)| = |\mathcal{P}_k| = 3^{3k} \quad (522)$$

Dividing by 3^{3k} gives $\lim_{T \rightarrow \infty} \rho_M(T) = 1$. $\square$

Remark 37.2 (Ergodicity Assumption). Theorem 37.4 assumes that the categorical dynamics are ergodic. Ergodicity means that the phase space

cannot be decomposed into invariant subsets: the trajectory eventually explores all regions, rather than being confined to a subset. For the categorical dynamics (373)–(375) with generic parameters (non-resonant frequencies, non-zero coupling constants), ergodicity is expected to hold by the KAM theorem and related results in dynamical systems theory [3]. However, for special parameter values (e.g., integrable systems with zero coupling), the dynamics may be non-ergodic, and Theorem 37.4 may not apply.

37.3 Memory by Existence

A profound property of Poincaré Computing is that memory accumulates simply by the system existing and evolving. No explicit storage operations (write instructions, memory allocations) are required.

Theorem 37.5 (Existence Implies Memory). *A Poincaré Computing system accumulates memory by existing. The memory content at time T is precisely the trajectory history:*

$$\text{Memory}(T) = \mathcal{M}(T) = \{\text{categories visited by } \gamma([0, T])\} \quad (523)$$

No explicit storage mechanism, write operation, or memory allocation is required. Memory emerges from the dynamics alone.

Proof. The trajectory $\gamma : [0, T] \rightarrow \mathcal{S}$ is uniquely determined by the initial state $\mathbf{S}_0$ and the dynamics (373)–(375) (by the Picard-Lindelöf theorem). Each point $\gamma(t)$ visited by the trajectory is a categorical state encoding information through the identity unification (Theorem 31.3): the state simultaneously encodes memory address (via π_M), processor configuration (via π_P), and semantic content (via π_S).

The set of visited states $\{\gamma(t) : 0 \leq t \leq T\}$ is the trajectory history. By Definition 37.1, the exploration memory $\mathcal{M}(T)$ is the set of categories containing points in this history. Therefore, the memory content is precisely the trajectory history, discretized to the resolution of the hierarchical partition $\mathcal{P}_k$.

This memory emerges from the dynamics alone: the differential equations (373)–(375) determine the trajectory, and the trajectory determines the memory. No additional storage mechanism is required. The system accumulates memory simply by existing and evolving through time. $\square$

Corollary 37.6 (No Processor-Memory Separation). *In Poincaré Computing, there is no distinction between "processor running" and "memory storing." The processor's exploration is the memory's content.*

Computation and storage are identical operations, not separate processes.

Proof. By Theorem 31.3, each categorical state $\mathbf{S}(t)$ simultaneously encodes:

- Memory address: $\pi_M(\mathbf{S}(t))$ (where data is located)
- Processor configuration: $\pi_P(\mathbf{S}(t))$ (what operation is being performed)
- Semantic content: $\pi_S(\mathbf{S}(t))$ (what the data means)

By Theorem 37.5, the memory content is the trajectory history $\gamma([0, T])$, which is the sequence of categorical states visited by the processor.

Therefore, the processor's activity (evolving through categorical states) and the memory's content (the set of visited states) are the same mathematical object: the trajectory γ . There is no separation between "processor" and "memory" as distinct entities. The processor's exploration *is* the memory's storage.

This unification is more radical than the von Neumann bottleneck elimination (Proposition 31.6), which merely removes the communication channel between processor and memory. Here, we establish that processor and memory are not separate entities connected by a channel, but are *identical*: different projections of the same trajectory. $\square$

Remark 37.3 (Implications for Architecture). Corollary 37.6 has profound implications for computer architecture. In traditional systems, the processor (CPU) and memory (RAM) are physically separate components, with distinct power supplies, clock domains, and control logic. Data must be explicitly moved between them, consuming energy and time.

In Poincaré Computing, there is no physical separation: the categorical state $\mathbf{S}(t)$ is the unified processor-memory entity. As the state evolves, both "computation" (processor activity) and "storage" (memory content) occur simultaneously. This suggests a radically different hardware architecture in which the distinction between processing units and memory units is eliminated, replaced by a unified state-evolution substrate.

37.4 Conditional Complexity and Self-Improvement

The exploration memory accumulated through prior computation reduces the complexity of solving subsequent problems, particularly problems that are related to previously solved problems.

Definition 37.3 (Conditional Poincaré Complexity). The **conditional Poincaré complexity** of problem P given exploration memory $\mathcal{M}$ is the minimum number of local solutions required to recognize closure, when some categories are already explored:

$$\Pi(P \mid \mathcal{M}) = \inf \left\{ n : \exists \text{ solution chain } (L_1, \dots, L_n) \text{ with } \bigcup_{i=1}^n \text{supp}(L_i) \subseteq \mathcal{M} \right\} \quad (524)$$

where $\text{supp}(L_i) \subseteq \mathcal{S}$ is the support of local solution L_i —the region of phase space where L_i is recognized.

The conditional complexity measures how many new local solutions must be discovered, given that some regions of $\mathcal{S}$ have already been explored.

Theorem 37.7 (Complexity Reduction). *Exploration never increases complexity: as exploration memory grows, the conditional complexity of any fixed problem decreases or remains constant.*

$$T_1 < T_2 \implies \Pi(P \mid \mathcal{M}(T_2)) \leq \Pi(P \mid \mathcal{M}(T_1)) \quad (525)$$

Proof. By Proposition 37.3, the exploration memory is non-decreasing: $\mathcal{M}(T_1) \subseteq \mathcal{M}(T_2)$ for $T_1 < T_2$.

Consider any solution chain $(L_1, \dots, L_n)$ that is valid given exploration memory $\mathcal{M}(T_2)$ (meaning $\bigcup_i \text{supp}(L_i) \subseteq \mathcal{M}(T_2)$). Since $\mathcal{M}(T_1) \subseteq \mathcal{M}(T_2)$, this chain may or may not be valid for $\mathcal{M}(T_1)$ (it is valid only if $\bigcup_i \text{supp}(L_i) \subseteq \mathcal{M}(T_1)$).

However, any solution chain that is valid for $\mathcal{M}(T_1)$ remains valid for $\mathcal{M}(T_2)$ (because $\mathcal{M}(T_1) \subseteq \mathcal{M}(T_2)$) implies that any region explored by time T_1 is still explored at time T_2 . Therefore, the set of valid solution chains for $\mathcal{M}(T_2)$ is a superset of the valid chains for $\mathcal{M}(T_1)$:

$$\{\text{valid chains for } \mathcal{M}(T_1)\} \subseteq \{\text{valid chains for } \mathcal{M}(T_2)\} \quad (526)$$

Taking the infimum over chain lengths:

$$\Pi(P \mid \mathcal{M}(T_2)) = \inf \{\text{lengths of valid chains for } \mathcal{M}(T_2)\} \leq \inf \{\text{lengths of valid chains for } \mathcal{M}(T_1)\} = \Pi(P \mid \mathcal{M}(T_1)) \quad (527)$$

Therefore, conditional complexity is non-increasing as exploration memory grows. $\square$

Corollary 37.8 (Self-Improvement). *A Poincaré Computing system improves its problem-solving capability over time without external modification or reprogramming. For any fixed problem P , the complexity $\Pi(P \mid \mathcal{M}(T))$ decreases (or remains constant) as T increases.*

Proof. This is an immediate consequence of Theorem 37.7: as time progresses, exploration memory grows (Proposition 37.3), and conditional complexity

decreases. The system becomes progressively better at solving problem P simply by existing and exploring, without any external intervention. $\square$

Remark 37.4 (Contrast with Traditional Systems). In traditional computation, a system's capability is static: a Turing machine with a fixed transition function δ has fixed time complexity $T(n)$ for any given problem. To improve the system's performance, one must modify the transition function (reprogram the machine) or upgrade the hardware (increase clock speed, add memory).

In Poincaré Computing, by contrast, capability improves automatically through continued operation. No reprogramming or hardware upgrade is required. The system learns from its own exploration, accumulating knowledge (exploration memory) that reduces the complexity of future problems. This is a form of *implicit learning* or *self-improvement* that has no analog in traditional computation.

37.5 Related Problem Benefit

The complexity reduction is particularly pronounced for problems that are related to previously solved problems, in the sense that their initial states are nearby in $\mathcal{S}$.

Definition 37.4 (Problem Relatedness). Two problems $P_1 = (\mathbf{S}_0^{(1)}, \mathcal{C}_1, \epsilon)$ and $P_2 = (\mathbf{S}_0^{(2)}, \mathcal{C}_2, \epsilon)$ are δ -**related** if their initial states are within distance δ in $\mathcal{S}$:

$$\|\mathbf{S}_0^{(1)} - \mathbf{S}_0^{(2)}\| < \delta \quad (528)$$

Intuitively, related problems have similar initial conditions and are likely to have overlapping solution trajectories.

Theorem 37.9 (Related Problem Acceleration). *Let P_1 and P_2 be δ -related problems. If P_1 is solved at time T_1 with solution trajectory γ_1 , then the conditional complexity of P_2 satisfies:*

$$\Pi(P_2 \mid \mathcal{M}(T_1)) \leq \Pi(P_2) - \Omega\left(\log_3 \frac{1}{\delta}\right) \quad (529)$$

The complexity reduction scales logarithmically with the relatedness parameter δ .

Proof. The solution trajectory γ_1 for problem P_1 starts at $\mathbf{S}_0^{(1)}$ and explores a region of $\mathcal{S}$ in the vicinity of $\mathbf{S}_0^{(1)}$. Since P_2 has initial state $\mathbf{S}_0^{(2)}$ within distance δ of $\mathbf{S}_0^{(1)}$, the trajectory γ_1 passes through categories in a δ -neighborhood of $\mathbf{S}_0^{(2)}$.

In the hierarchical partition $\mathcal{P}_k$, categories (cells) at depth k have diameter approximately 3^{-k} . Two

Exhaustive Computing Validation




Figure 22: **Experimental validation of exhaustive computing properties in Poincaré Computing systems.** (A) Non-halting exploration: Memory density (fraction of phase space explored) asymptotically approaches unity but never reaches full exploration, demonstrating that the system continues indefinitely without a halting condition. (B) Capability monotonicity: Computational capability (measured as the number of distinct solution trajectories discovered) increases monotonically with time, establishing that the system can only improve through existence and never loses previously acquired capability. (C) Related problem acceleration: Acceleration factor (ratio of solution time for related problems to baseline problem) decreases as problem similarity increases (measured by distance δ in S-entropy space), confirming that prior exploration reduces complexity for nearby problems through conditional complexity reduction. (D) Progressive refinement: Complexity (measured in Poincaré units) decreases systematically across a sequence of related problems, with the "After" condition (following prior exploration) showing consistently lower complexity than the "Before" condition (no prior exploration), demonstrating irreversible capability accumulation. (E) Productive idleness: The number of distinct paths to a target solution increases continuously even during idle periods (no new problems introduced), establishing that exploration continues productively in the absence of external input and builds robustness through path redundancy. (F) Memory by existence: Trajectory visualization in a 2D projection of S-entropy space, with points colored by visit order, demonstrates that memory emerges from the exploration history without explicit storage.

points within distance δ share ancestors in the hierarchical tree up to depth $k^* \approx \log_3(1/\delta)$: the smallest cells containing both points have diameter $\approx \delta$.

By solving P_1 , the trajectory γ_1 visits at least k^* levels of the hierarchy in the neighborhood of $\mathbf{S}_0^{(2)}$. These visited categories are added to the exploration memory $\mathcal{M}(T_1)$. When solving P_2 , the solution chain can leverage these already-explored categories, reducing the number of new local solutions required by at least $k^* = \Omega(\log_3(1/\delta))$.

Therefore:

$$\Pi(P_2 \mid \mathcal{M}(T_1)) \leq \Pi(P_2) - k^* = \Pi(P_2) - \Omega(\log_3(1/\delta)) \quad (530)$$

□

Corollary 37.10 (Progressive Refinement). *A sequence of increasingly related problems $P_1, P_2, \dots, P_n$ with relatedness parameters $\delta_i = \|\mathbf{S}_0^{(i+1)} - \mathbf{S}_0^{(i)}\|$ satisfying $\delta_i \rightarrow 0$ achieves:*

$$\Pi(P_n \mid \mathcal{M}(T_{n-1})) = O(1) \quad (531)$$

As the problems become increasingly related, the conditional complexity approaches a constant.

Proof. By Theorem 37.9, each problem P_i contributes a complexity reduction of $\Omega(\log_3(1/\delta_{i-1}))$ for the next problem P_{i+1} . If $\delta_i \rightarrow 0$, then $\log_3(1/\delta_i) \rightarrow \infty$, so the cumulative reduction grows without bound.

Since the Poincaré complexity is bounded below by zero, the conditional complexity must eventually saturate at a constant value $O(1)$, representing the minimum number of local solutions required to recognize closure when almost all relevant categories have been explored. □

Remark 37.5 (Expertise Emergence). Corollary 37.10 formalizes the notion of "expertise" in Poincaré Computing. A system subjected to a sequence of related problems (a *research protocol*, Definition 37.8 below) develops progressively lower complexity for problems in that domain. This is analogous to how human experts develop intuition and pattern recognition through repeated exposure to related problems, allowing them to solve new problems in their domain more efficiently than novices.

37.6 Idle Exploration and Productive Idleness

When no problem is actively being solved, the categorical dynamics continue to evolve, exploring phase space. This "idle" exploration is not wasted but serves to discover alternative solution paths and increase robustness.

Definition 37.5 (Idle State). A Poincaré Computing system is in **idle state** when no new problem has been submitted for solution. The categorical dynamics continue unchanged:

$$\frac{d\mathbf{S}}{dt} = \mathbf{F}(\mathbf{S}) \quad (\text{same dynamics as during active computation}) \quad (532)$$

There is no "sleep mode" or "power-down state"—the system continues to explore $\mathcal{S}$ at the same rate as during active computation.

Theorem 37.11 (Productive Idleness). *Idle exploration is computationally productive. For any previously solved problem P with solution set $\mathcal{A}(P)$, idle exploration increases the number of known solution paths:*

$$N_{\text{paths}}(P, T) = |\{\gamma \in \mathcal{A}(P) : \gamma([0, T_\gamma]) \subseteq \mathcal{M}(T)\}| \quad (533)$$

is non-decreasing in T , where T_γ is the recurrence time for trajectory γ .

Proof. Each solution trajectory $\gamma \in \mathcal{A}(P)$ is a path through $\mathcal{S}$ from the initial state $\mathbf{S}_0$ to a state within ϵ of $\mathbf{S}_0$. The trajectory is "known" (fully covered by exploration memory) if every point along the trajectory has been visited: $\gamma([0, T_\gamma]) \subseteq \mathcal{M}(T)$.

As exploration memory grows (Proposition 37.3), more trajectories become fully covered. Once a trajectory is fully covered, it remains covered for all future times (because $\mathcal{M}(T)$ is non-decreasing). Therefore, the number of known paths $N_{\text{paths}}(P, T)$ is non-decreasing in T .

During idle exploration, the trajectory continues to visit new categories, adding them to $\mathcal{M}(T)$. Each new category may complete the coverage of one or more solution trajectories, increasing $N_{\text{paths}}(P, T)$. Therefore, idle exploration is productive: it discovers alternative solution paths that were not known during the initial solution of P . □

Definition 37.6 (Path Redundancy). The **path redundancy** for a solution $\mathbf{S}^*$ (a state satisfying the problem constraints) at time T is the number of distinct paths from the exploration memory to $\mathbf{S}^*$:

$$R(\mathbf{S}^*, T) = |\{\text{distinct paths from } \mathcal{M}(T) \text{ to } \mathbf{S}^*\}| \quad (534)$$

High path redundancy provides robustness: if one path becomes unavailable (e.g., due to constraint changes or hardware failures), alternative paths exist.

Proposition 37.12 (Redundancy Growth). *For ergodic dynamics, the path redundancy grows without bound:*

$$\lim_{T \rightarrow \infty} R(\mathbf{S}^*, T) = \infty \quad (535)$$

The number of known paths to any solution increases indefinitely.

Proof. By Theorem 37.4, the exploration memory approaches completeness: $\lim_{T \rightarrow \infty} \mathcal{M}(T) = \mathcal{P}_k$ (all categories are eventually visited).

The number of paths through a complete graph on $N = 3^{3k}$ nodes (categories) from any starting node to any target node is exponential in N . As $\mathcal{M}(T)$ approaches completeness, the number of available paths through the explored categories grows exponentially.

More precisely, in a complete graph, the number of simple paths of length ℓ from a source to a target is $O(N^\ell)$ (choosing ℓ intermediate nodes). As $|\mathcal{M}(T)| \rightarrow N$, the number of paths grows without bound.

Therefore, $\lim_{T \rightarrow \infty} R(\mathbf{S}^*, T) = \infty$. $\square$

Remark 37.6 (Path Consolidation). Idle exploration performs what we call **path consolidation**: discovering alternative routes to known answers. This is analogous to how transportation networks develop redundant routes (multiple highways, alternate paths) to provide robustness against traffic or failures. In Poincaré Computing, path consolidation provides robustness against constraint changes, hardware variations, or perturbations in the initial state. If one solution path becomes unavailable, the system can automatically switch to an alternative path without explicit reprogramming.

37.7 The Self-Refining System

We now formalize the notion of system capability and prove that it increases monotonically through continued operation.

Definition 37.7 (System Capability). The **capability** of a Poincaré Computing system at time T is a tuple:

$$\mathcal{K}(T) = (\mathcal{M}(T), \{R(\mathbf{S}^*, T) : \mathbf{S}^* \in \text{Solutions}\}, \rho_M(T)) \quad (536)$$

consisting of:

- The exploration memory $\mathcal{M}(T)$ (set of visited categories);
- The path redundancies $R(\mathbf{S}^*, T)$ for all known solutions $\mathbf{S}^*$;
- The memory density $\rho_M(T)$ (fraction of categories explored).

The capability quantifies the system's accumulated knowledge and problem-solving efficiency.

Theorem 37.13 (Capability Monotonicity). *System capability is monotonically non-decreasing in all components:*

$$T_1 < T_2 \implies \mathcal{K}(T_1) \preceq \mathcal{K}(T_2) \quad (537)$$

where $\preceq$ denotes component-wise ordering: $\mathcal{K}(T_1) \preceq \mathcal{K}(T_2)$ if and only if:

- $\mathcal{M}(T_1) \subseteq \mathcal{M}(T_2)$
- $R(\mathbf{S}^*, T_1) \leq R(\mathbf{S}^*, T_2)$ for all solutions $\mathbf{S}^*$
- $\rho_M(T_1) \leq \rho_M(T_2)$

Proof. We verify that each component is non-decreasing:

(1) Exploration memory: By Proposition 37.3, $\mathcal{M}(T_1) \subseteq \mathcal{M}(T_2)$ for $T_1 < T_2$.

(2) Path redundancy: By Proposition 37.12, $R(\mathbf{S}^*, T)$ is non-decreasing in T for each solution $\mathbf{S}^*$. Therefore, $R(\mathbf{S}^*, T_1) \leq R(\mathbf{S}^*, T_2)$.

(3) Memory density: Since $\mathcal{M}(T_1) \subseteq \mathcal{M}(T_2)$, we have $|\mathcal{M}(T_1)| \leq |\mathcal{M}(T_2)|$. Dividing by the constant $|\mathcal{P}_k| = 3^{3k}$ gives $\rho_M(T_1) \leq \rho_M(T_2)$.

Therefore, all three components are non-decreasing, establishing $\mathcal{K}(T_1) \preceq \mathcal{K}(T_2)$. $\square$

Corollary 37.14 (Irreversible Improvement). *A Poincaré Computing system cannot decrease in capability. Time evolution is irreversibly beneficial: once knowledge is gained (categories explored, paths discovered), it cannot be lost.*

Proof. By Theorem 37.13, capability is non-decreasing. There is no mechanism for removing categories from $\mathcal{M}(T)$, decreasing path redundancy $R(\mathbf{S}^*, T)$, or reducing memory density $\rho_M(T)$. Therefore, capability can only increase or remain constant, never decrease.

This irreversibility is a consequence of the non-halting dynamics (Theorem 37.1) and the monotonicity of exploration memory (Proposition 37.3). $\square$

Theorem 37.15 (Self-Refinement Without Programming). *The system refines its computational capability without external programming, reprogramming, or hardware modification. The refinement derives entirely from continued dynamics:*

$$\frac{d\mathcal{K}}{dT} \succeq 0 \quad (538)$$

with strict inequality (capability strictly increasing) for almost all T .

Proof. By Theorem 37.1, the categorical dynamics continue indefinitely with non-zero velocity almost everywhere. By Theorem 37.13, capability is non-decreasing.

For $\rho_M(T) < 1$ (exploration memory not yet complete), the trajectory visits new categories with positive probability (by ergodicity), so $|\mathcal{M}(T)|$ increases, implying $d\rho_M/dT > 0$. This establishes strict increase in at least one component of $\mathcal{K}(T)$.

By Theorem 37.4, $\rho_M(T) \rightarrow 1$ as $T \rightarrow \infty$, so the strict increase continues until exploration is complete. Even after $\rho_M(T) = 1$, path redundancy continues to increase (Proposition 37.12), so capability continues to improve.

Therefore, $d\mathcal{K}/dT \succeq 0$ with strict inequality almost everywhere, establishing self-refinement without external intervention. $\square$

37.8 Research Machine Architecture

The self-refinement properties suggest a novel computational architecture: the **research machine**, which accumulates expertise through exposure to sequences of related problems.

Definition 37.8 (Research Protocol). A **research protocol** is a sequence of problems $(P_1, P_2, \dots, P_n)$ submitted at times $(T_1, T_2, \dots, T_n)$ where consecutive problems are δ_i -related:

$$\|\mathbf{S}_0^{(i+1)} - \mathbf{S}_0^{(i)}\| < \delta_i \quad \text{for } i = 1, \dots, n-1 \quad (539)$$

The protocol represents a sequence of related research questions or computational tasks in a common domain.

Theorem 37.16 (Cumulative Research Benefit). *Under a research protocol with relatedness parameters $\delta_i \leq \delta$ for all i , the conditional complexity of the n -th problem satisfies:*

$$\Pi(P_n | \mathcal{M}(T_{n-1})) \leq \Pi(P_1) - (n-1) \cdot \Omega\left(\log_3 \frac{1}{\delta}\right) \quad (540)$$

Each problem contributes to accelerating subsequent problems, with cumulative benefit growing linearly in n .

Proof. We apply Theorem 37.9 inductively. Solving problem P_1 creates exploration memory $\mathcal{M}(T_1)$. By Theorem 37.9, the conditional complexity of P_2 satisfies:

$$\Pi(P_2 | \mathcal{M}(T_1)) \leq \Pi(P_2) - \Omega(\log_3(1/\delta_1)) \quad (541)$$

Since $\delta_1 \leq \delta$, we have $\log_3(1/\delta_1) \geq \log_3(1/\delta)$, so:

$$\Pi(P_2 | \mathcal{M}(T_1)) \leq \Pi(P_2) - \Omega(\log_3(1/\delta)) \quad (542)$$

Solving P_2 adds more categories to the exploration memory, giving $\mathcal{M}(T_2) \supseteq \mathcal{M}(T_1)$. Applying the same argument to P_3 :

$$\Pi(P_3 | \mathcal{M}(T_2)) \leq \Pi(P_3) - \Omega(\log_3(1/\delta)) \quad (543)$$

Continuing inductively, after solving $P_1, \dots, P_{n-1}$, the conditional complexity of P_n satisfies:

$$\Pi(P_n | \mathcal{M}(T_{n-1})) \leq \Pi(P_n) - (n-1) \cdot \Omega(\log_3(1/\delta)) \quad (544)$$

Since problems in the research protocol are related, $\Pi(P_i) \approx \Pi(P_1)$ for all i (their unconditional complexities are similar). Therefore:

$$\Pi(P_n | \mathcal{M}(T_{n-1})) \leq \Pi(P_1) - (n-1) \cdot \Omega(\log_3(1/\delta)) \quad (545)$$

This establishes cumulative benefit: each problem reduces the complexity of subsequent problems by $\Omega(\log_3(1/\delta))$. $\square$

Corollary 37.17 (Expertise Emergence). *A system subjected to a research protocol in a domain (set of related problems) develops "expertise": progressively lower complexity for problems in that domain. After solving n related problems, the conditional complexity approaches:*

$$\Pi(P_n | \mathcal{M}(T_{n-1})) = O(1) \quad (546)$$

for sufficiently large n .

Proof. By Theorem 37.16, the conditional complexity decreases linearly with n :

$$\Pi(P_n | \mathcal{M}(T_{n-1})) \leq \Pi(P_1) - (n-1) \cdot \Omega(\log_3(1/\delta)) \quad (547)$$

Since complexity is bounded below by zero, the right-hand side must eventually become constant for sufficiently large n :

$$n \geq \frac{\Pi(P_1)}{\Omega(\log_3(1/\delta))} \implies \Pi(P_n | \mathcal{M}(T_{n-1})) = O(1) \quad (548)$$

This establishes that expertise emerges after solving $O(\Pi(P_1)/\log_3(1/\delta))$ related problems. $\square$

Proposition 37.18 (Domain Specialization). *Let $\mathcal{D} \subseteq \mathcal{S}$ be a domain (connected region). If all submitted problems have initial states in $\mathcal{D}$, then the memory density restricted to $\mathcal{D}$ approaches completeness:*

$$\lim_{n \rightarrow \infty} \rho_M^{\mathcal{D}}(T_n) = 1 \quad (549)$$

where $\rho_M^{\mathcal{D}}(T) = |\mathcal{M}(T) \cap \mathcal{D}|/|\mathcal{P}_k \cap \mathcal{D}|$ is the memory density restricted to domain $\mathcal{D}$.

The system becomes exhaustively knowledgeable about the domain.

Proof. Related problems with initial states in $\mathcal{D}$ have solution trajectories that remain within $\mathcal{D}$ or its neighborhood (by continuity of the dynamics). Each problem solved adds categories in $\mathcal{D}$ to the exploration memory.

By ergodicity restricted to the accessible region (the closure of the union of all solution trajectories), all categories in $\mathcal{D}$ are eventually visited. Therefore, $\lim_{n \rightarrow \infty} |\mathcal{M}(T_n) \cap \mathcal{D}| = |\mathcal{P}_k \cap \mathcal{D}|$, giving $\lim_{n \rightarrow \infty} \rho_M^{\mathcal{D}}(T_n) = 1$. $\square$

37.9 Comparison with Classical Systems

We conclude by comparing the exhaustive exploration properties of Poincaré Computing with traditional Turing/von Neumann systems.

Property	Classical (Turing/von Neumann)	Poincaré Computing
Idle behavior	Halt (no activity)	Continuous exploration
Memory source	Explicit storage (tape writes)	Trajectory history (implicit)
Capability over time	Static (fixed $T(n)$)	Increases automatically
Related problems	Independent (no benefit)	Accelerated (potentially dependent)
Self-improvement	Requires reprogramming	Automatic (by persistence)
Path redundancy	Single execution path	Grows through machine
Expertise	Requires training data	Emerges from research in protocol

Table 5: **Comparison of exhaustive exploration and memory properties.** Poincaré Computing exhibits emergent properties (existence-based memory, automatic refinement, related problem coupling, productive idleness) that have no analog in classical computation.

Theorem 37.19 (Fundamental Distinction). *Poincaré Computing systems exhibit emergent properties that are categorically absent in Turing machines:*

1. **Existence-based memory:** Memory accumulates from dynamics alone, not from explicit write operations (Theorem 37.5)
2. **Automatic refinement:** Capability increases without external intervention or reprogramming (Theorem 37.15)
3. **Related problem coupling:** Prior exploration accelerates related problems with cumulative benefit (Theorem 37.16)
4. **Productive idleness:** Idle time contributes to capability through path consolidation (Theorem 37.11)

These properties have no analog in classical computation and represent a fundamentally different computational paradigm.

Proof. We establish that each property is absent in Turing machines:

(1) **Existence-based memory:** Turing machines have explicit memory (tape symbols) that must be written by explicit write operations (part of the transition function δ). A Turing machine that executes no write operations produces no memory. In Poincaré Computing, memory accumulates automatically from trajectory evolution, with no explicit write operations.

(2) **Automatic refinement:** A Turing machine with a fixed transition function δ has fixed time complexity $T(n)$ for any given problem. The complexity does not decrease over time unless the transition function is modified (reprogramming). In Poincaré Computing, conditional complexity decreases automatically through continuous exploration, with no modification to the system history (implicit).

(3) **Related problem coupling:** Turing machines treat accelerated problems independently. Solving problem P_1 automatically assists in solving a related problem P_2 through path machine. In Poincaré Computing, solving P_1 creates exploration memory that reduces the complexity of P_2 by $\Omega(\log_3(1/\delta))$.

(4) **Productive idleness:** A halted Turing machine performs no computation and gains no capability. Idle time is wasted. In Poincaré Computing, idle exploration discovers alternative solution paths, increasing path redundancy and robustness.

Each property is a direct consequence of the non-halting dynamics (Theorem 37.1), trajectory-based memory (Theorem 37.5), conditional complexity (Theorem 37.7), and productive idleness (Theorem 37.11). These are structural properties of the trajectory-based paradigm, not implementation details. $\square$

This section has established that Poincaré Computing systems exhibit continuous exploration without halting, accumulate memory through existence, automatically refine their capability over time, and benefit from solving related problems. These emergent properties suggest a radically different computational architecture—the research machine—that develops expertise through exposure to problem domains and performs productive path consolidation during idle time. The categorical distinction from Turing machines is profound: Poincaré Computing systems learn and improve simply by existing, without external programming or training.

38 Saint-Entropy Thermodynamics

39 Categorical Topology and S-Entropy Foundations

The preceding sections have developed Poincaré Computing as a computational framework based on continuous trajectory evolution in a three-dimensional S-entropy space $\mathcal{S} = [0, 1]^3$. We have established the physical grounding through hardware measurements (Section 25), the categorical dynamics governing trajectory evolution (Section 27), the solution concept based on recurrence (Section 29), and the complexity theory based on categorical completion rates (Section 35). However, we have not yet provided the rigorous mathematical foundations that justify the structure of $\mathcal{S}$ itself: why is it three-dimensional? Why does it have a bounded domain $[0, 1]^3$? What is the relationship between the continuous geometric structure and the discrete categorical completion events?

This section establishes these foundations by developing the **categorical topology** underlying Poincaré Computing. We define categorical spaces as partially ordered topological structures equipped with completion operators (Definition 39.1), establishing the axioms that govern categorical completion (Axioms 39.1–39.3). We prove that completion trajectories form closed sets in the specialisation topology (Theorem 39.2), providing the topological foundation for the trajectory-based computation developed in earlier sections.

We introduce the **S-distance metric** (Definition 39.11), which measures the distance between trajectories in categorical space, and prove that it satisfies the metric axioms (Theorem 39.8). We establish the tri-dimensional decomposition $\mathcal{S} = \mathcal{S}_k \times \mathcal{S}_t \times \mathcal{S}_e$ (Definition 39.12), showing that the three S-entropy coordinates (knowledge, temporal, evolution) arise naturally from the orthogonal factorisation of the categorical space.

A profound property of categorical spaces is their **recursive self-similarity**: each dimension decomposes into three sub-dimensions, which themselves decompose into three sub-sub-dimensions, continuing infinitely (Theorem 39.9). This recursive structure generates the 3^k branching of the hierarchical partition (Theorem 39.10) and leads to **scale ambiguity**: it is impossible to determine the hierarchical level of a categorical state from local examination alone (Theorem 39.11).

We develop the theory of **categorical filters**,

which are structure-preserving maps between categorical spaces that reduce equivalence class sizes and thereby enhance transition probabilities (Theorem 39.14). This provides a mathematical foundation for **information catalysis**: the dramatic probability enhancement observed in biological and computational systems when constraints filter the space of possibilities [14].

Finally, we prove that the S-entropy space $\mathcal{S}$ used throughout this paper is the canonical realisation of the abstract categorical space structure (Theorem 39.16), establishing that Poincaré Computing operates on a mathematically well-founded substrate with deep connections to topology, order theory, and information theory.

39.1 Categorical Spaces: Axiomatic Foundations

We begin by defining categorical spaces as abstract mathematical structures, independent of any particular physical or computational realisation.

Definition 39.1 (Categorical Space). A **categorical space** is a quadruple $(\mathcal{C}, \prec, \mu, \tau)$ where:

1. $\mathcal{C}$ is a set of **categorical states** (the points of the space);
2. $\prec$ is a partial order on $\mathcal{C}$ called the **completion order**, satisfying:
 - Reflexivity: $C \prec C$ for all $C \in \mathcal{C}$
 - Antisymmetry: $C \prec C'$ and $C' \prec C$ imply $C = C'$
 - Transitivity: $C \prec C'$ and $C' \prec C''$ imply $C \prec C''$
3. $\mu : \mathcal{C} \times \mathbb{R}_{\geq 0} \rightarrow \{0, 1\}$ is the **completion operator**, where $\mu(C, t) = 1$ means that the categorical state C has been completed (visited, explored) by time t , and $\mu(C, t) = 0$ means it has not been completed;
4. τ is a topology on $\mathcal{C}$ called the **completion topology**, which encodes the structure of categorical completion.

The quadruple must satisfy the axioms stated below [18].

The categorical space abstracts the essential structure of computational phase spaces: states have a partial ordering (some states must be visited before others), states can be completed (marked as visited), and there is a topological structure that determines which sets of states are "open" (accessible from their predecessors).

Axiom 39.1 (Irreversibility). For all categorical states $C \in \mathcal{C}$ and all times $t_1 \leq t_2$:

$$\mu(C, t_1) = 1 \implies \mu(C, t_2) = 1 \quad (550)$$

Once a categorical state is completed, it remains completed for all future times. Completion is irreversible.

This axiom formalizes the irreversibility of exploration established in Proposition 37.3: once a category is visited, it remains in the exploration memory forever. There is no "forgetting" or "uncompleting" of states.

Axiom 39.2 (Order Compatibility). The partial order $\prec$ is compatible with completion: if $C_i \prec C_j$ (state C_i precedes state C_j in the completion order) and $\mu(C_j, t) = 1$ (state C_j is completed by time t), then there exists a time $t' \leq t$ such that $\mu(C_i, t') = 1$ (state C_i was completed by some earlier time t').

Formally:

$$(C_i \prec C_j) \wedge (\mu(C_j, t) = 1) \implies \exists t' \leq t : \mu(C_i, t') = 1 \quad (551)$$

Predecessors must be completed before successors.

This axiom ensures that the completion order $\prec$ has semantic meaning: if $C_i \prec C_j$, then any trajectory that visits C_j must have previously visited C_i . The partial order encodes dependencies between categorical states, analogous to how a partial order on tasks encodes precedence constraints in scheduling theory.

Axiom 39.3 (Topology Compatibility). The topology τ is the **specialization topology** (also called the Alexandrov topology) induced by the partial order $\prec$. A set $U \subseteq \mathcal{C}$ is open if and only if it is **upward-closed** under $\prec$:

$$U \in \tau \iff \forall C \in U, \forall C' \in \mathcal{C} : (C \prec C' \implies C' \in U) \quad (552)$$

In other words, if a set U contains a state C , it must contain all successors of C in the completion order.

The specialization topology is the natural topology for partially ordered sets [1]. It makes the space $(\mathcal{C}, \tau)$ a T_0 (Kolmogorov) space: distinct points can be separated by open sets, but not necessarily by disjoint open sets. This is the appropriate level of separation for computational spaces, where states may be "close" in the sense of having similar successors.

Remark 39.1 (Alexandrov Topology). The specialization topology is also called the Alexandrov topology after the Russian mathematician Pavel Alexandrov,

who studied such topologies in the 1930s [1]. A key property is that arbitrary intersections of open sets are open (not just finite intersections), making the topology very "fine" in the sense of having many open sets. This fine structure is essential for capturing the detailed dependency structure of categorical completion.

Proposition 39.1 (Closed Sets in Specialization Topology). A set $F \subseteq \mathcal{C}$ is closed in the specialization topology if and only if it is **downward-closed** under $\prec$:

$$F \text{ closed} \iff \forall C \in F, \forall C' \in \mathcal{C} : (C' \prec C \implies C' \in F) \quad (553)$$

In other words, if a set F contains a state C , it must contain all predecessors of C in the completion order.

Proof. A set is closed if and only if its complement is open. Let $F \subseteq \mathcal{C}$ be downward-closed, and let $U = \mathcal{C} \setminus F$ be its complement. We show that U is upward-closed.

Suppose $C \in U$ and $C \prec C'$. We must show $C' \in U$. Assume for contradiction that $C' \notin U$, so $C' \in F$. Since F is downward-closed and $C \prec C'$, we have $C \in F$, contradicting $C \in U = \mathcal{C} \setminus F$. Therefore, $C' \in U$, establishing that U is upward-closed.

By Axiom 39.3, U is open, so F is closed.

Conversely, if F is closed, then $U = \mathcal{C} \setminus F$ is open, hence upward-closed. By the same argument (with roles reversed), F is downward-closed. $\square$

39.2 Completion Trajectories

Having defined categorical spaces, we now define trajectories through these spaces, which correspond to the computational trajectories studied in earlier sections.

Definition 39.2 (Completion Trajectory). A **completion trajectory** in a categorical space $(\mathcal{C}, \prec, \mu, \tau)$ is a function $\gamma : \mathbb{R}_{\geq 0} \rightarrow \mathcal{P}(\mathcal{C})$ (where $\mathcal{P}(\mathcal{C})$ denotes the power set of $\mathcal{C}$) satisfying:

- (i) **Completion correspondence:** $\gamma(t) = \{C \in \mathcal{C} : \mu(C, t) = 1\}$ is the set of completed states at time t ;
- (ii) **Monotonicity:** $t_1 \leq t_2 \implies \gamma(t_1) \subseteq \gamma(t_2)$ (the set of completed states grows over time);
- (iii) **Downward closure:** $\gamma(t)$ is downward-closed under $\prec$ for all t : if $C \in \gamma(t)$ and $C' \prec C$, then $C' \in \gamma(t)$.




Figure 23: **S-Entropy Space Visualization.** **(A) Molecular Distribution in S-Space:** 3D scatter plot shows ≈ 200 molecules distributed in $S = [0, 1]^3$ (axes: S_k , S_t , S_e). Color gradient (purple $\rightarrow$ yellow) indicates temporal order. Molecules cluster near $S_k \approx 1.0$ (high knowledge), with broad distribution in S_t and S_e dimensions. **(B) Polar Phase: $S_t \rightarrow \theta$, $S_e \rightarrow r$:** Polar plot maps temporal entropy S_t to angle θ and evolution entropy S_e to radius r . Blue line shows trajectory from center ($r = 0$) to $r \approx 1.0$ at $\theta = 0^\circ$ (horizontal right). **(C) Ternary Composition:** Ternary diagram shows relative contributions of S_k , S_t , S_e (three vertices). **(D) Density Contour:** Heatmap in (S_k, S_e) plane shows molecular density (color scale: yellow = low density ≈ 0 , red = high density ≈ 35). **(E) Radial Distribution:** Radial distribution function $g(r)$ vs. distance from center $r = \sqrt{S_k^2 + S_t^2 + S_e^2}$ shows three peaks: $r \approx 0.72$ ($g(r) \approx 35$, primary peak), $r \approx 0.80$ ($g(r) \approx 10$, secondary peak), $r \approx 0.84$ ($g(r) \approx 8$, tertiary peak). **(F) Phase Trajectories:** Scatter plot in (S_k, S_e) plane shows multiple trajectories (colored dots: purple, blue, cyan, yellow, orange, red).

The completion trajectory tracks which states have been visited by time t . Property (i) connects the trajectory to the completion operator μ . Property (ii) reflects the irreversibility of completion (Axiom 39.1). Property (iii) reflects the order compatibility (Axiom 39.2): if a state is completed, all its predecessors must also be completed.

Theorem 39.2 (Trajectory Closure). *For any completion trajectory γ , the set $\gamma(t)$ of completed states at time t is closed in the completion topology $(\mathcal{C}, \tau)$ for all $t \geq 0$.*

Proof. By Definition 39.2(iii), the set $\gamma(t)$ is downward-closed under $\prec$. By Proposition 39.1, any downward-closed set is closed in the specialization topology. Therefore, $\gamma(t)$ is closed for all $t \geq 0$. $\square$

This theorem establishes a fundamental connection between the algebraic structure (the completion trajectory) and the topological structure (closed sets). The set of completed states is always a closed set, meaning that the "boundary" of the explored region is well-defined topologically.

Definition 39.3 (Completion Rate). The **categorical completion rate** at time t is the rate of change of the number of completed states:

$$\dot{C}(t) = \frac{d|\gamma(t)|}{dt} \quad (554)$$

where $|\gamma(t)|$ denotes the cardinality of the set $\gamma(t)$.

For uncountable categorical spaces $\mathcal{C}$, we replace cardinality with an appropriate measure $\mu_{\mathcal{C}} : \mathcal{P}(\mathcal{C}) \rightarrow \mathbb{R}_{\geq 0}$, giving:

$$\dot{C}(t) = \frac{d\mu_{\mathcal{C}}(\gamma(t))}{dt} \quad (555)$$

This definition formalizes the categorical completion rate introduced in Definition 35.6, connecting it to the abstract categorical space structure.

Proposition 39.3 (Non-Negative Completion Rate). *For any completion trajectory γ , the completion rate is non-negative:*

$$\dot{C}(t) \geq 0 \quad \forall t \geq 0 \quad (556)$$

Proof. By Definition 39.2(ii), $\gamma(t_1) \subseteq \gamma(t_2)$ for $t_1 \leq t_2$. Therefore, $|\gamma(t_1)| \leq |\gamma(t_2)|$ (or $\mu_{\mathcal{C}}(\gamma(t_1)) \leq \mu_{\mathcal{C}}(\gamma(t_2))$ in the measure-theoretic case). The function $t \mapsto |\gamma(t)|$ is non-decreasing, so its derivative (when it exists) is non-negative. $\square$

39.3 Equivalence Classes and Quotient Structure

Categorical spaces often have internal symmetries: multiple distinct states may be indistinguishable from the perspective of a particular observation or measurement. We formalize this through equivalence relations.

Definition 39.4 (Observable Projection). An **observable** is a continuous function $\mathcal{O} : \mathcal{C} \rightarrow \mathcal{M}$ from the categorical space to an **observation space** $(\mathcal{M}, \tau_{\mathcal{M}})$, which is a topological space representing the possible outcomes of measurements.

Continuity means that the preimage of any open set in $\mathcal{M}$ is open in $\mathcal{C}$:

$$U \in \tau_{\mathcal{M}} \implies \mathcal{O}^{-1}(U) \in \tau \quad (557)$$

The observable $\mathcal{O}$ plays the role of a measurement or projection operator, mapping the full categorical state to an observed value. In Poincaré Computing, the projections π_M, π_P, π_S (Section 31) are examples of observables.

Definition 39.5 (Categorical Equivalence Relation). Given an observable $\mathcal{O} : \mathcal{C} \rightarrow \mathcal{M}$, the **categorical equivalence relation** $\sim_{\mathcal{O}}$ is defined by:

$$C_i \sim_{\mathcal{O}} C_j \iff \mathcal{O}(C_i) = \mathcal{O}(C_j) \quad (558)$$

Two categorical states are equivalent if they produce the same observation.

Definition 39.6 (Equivalence Class). The **equivalence class** of a categorical state $C \in \mathcal{C}$ under observable $\mathcal{O}$ is:

$$[C]_{\mathcal{O}} = \{C' \in \mathcal{C} : C' \sim_{\mathcal{O}} C\} = \mathcal{O}^{-1}(\mathcal{O}(C)) \quad (559)$$

This is the set of all states that produce the same observation as C —the **fiber** of $\mathcal{O}$ over the point $\mathcal{O}(C)$.

Definition 39.7 (Degeneracy). The **degeneracy** of a categorical state C under observable $\mathcal{O}$ is the cardinality of its equivalence class:

$$\delta_{\mathcal{O}}(C) = |[C]_{\mathcal{O}}| \quad (560)$$

High degeneracy means that many distinct categorical states produce the same observation, indicating a loss of information in the measurement.

Proposition 39.4 (Degeneracy Invariance). *For all categorical states C, C' in the same equivalence class $[C]_{\mathcal{O}}$, the degeneracy is the same:*

$$\delta_{\mathcal{O}}(C) = \delta_{\mathcal{O}}(C') \quad (561)$$

Proof. If $C \sim_{\mathcal{O}} C'$, then by definition, $\mathcal{O}(C) = \mathcal{O}(C')$. Therefore:

$$[C]_{\mathcal{O}} = \mathcal{O}^{-1}(\mathcal{O}(C)) = \mathcal{O}^{-1}(\mathcal{O}(C')) = [C']_{\mathcal{O}} \quad (562)$$

Since the equivalence classes are identical, their cardinalities are equal:

$$\delta_{\mathcal{O}}(C) = |[C]_{\mathcal{O}}| = |[C']_{\mathcal{O}}| = \delta_{\mathcal{O}}(C') \quad (563)$$

□

Theorem 39.5 (Fiber Bundle Structure). *If $\mathcal{O} : \mathcal{C} \rightarrow \mathcal{M}$ is a continuous and surjective observable, then the triple $(\mathcal{C}, \mathcal{M}, \mathcal{O})$ forms a **fiber bundle structure** where:*

- $\mathcal{C}$ is the **total space**;
- $\mathcal{M}$ is the **base space**;
- $\mathcal{O}$ is the **projection map**;
- The fibers $\mathcal{O}^{-1}(m)$ for $m \in \mathcal{M}$ are the **equivalence classes**.

*If the fibers are all isomorphic (have the same structure), the bundle is called **trivial**, and $\mathcal{C} \cong \mathcal{M} \times F$ where F is a typical fiber.*

Proof. The fiber bundle structure is established by verifying the defining properties:

- Continuity of $\mathcal{O}$ is given by assumption.
- Surjectivity ensures that every point $m \in \mathcal{M}$ has a non-empty fiber $\mathcal{O}^{-1}(m)$.
- The fibers partition $\mathcal{C}$ into disjoint equivalence classes.

If all fibers are isomorphic to a typical fiber F , then locally (and globally, if $\mathcal{M}$ is simply connected), we can write $\mathcal{C} \cong \mathcal{M} \times F$, making the bundle trivial. □

This theorem establishes that categorical spaces with observables have the structure of fiber bundles, a fundamental concept in differential geometry and topology [?]. The fiber bundle perspective is essential for understanding how information is lost (or preserved) under projections.

39.4 Categorical Richness and Asymmetry

We now introduce measures of the "richness" of categorical states and the "asymmetry" between processes, which quantify the information content and directional bias of categorical dynamics.

Definition 39.8 (Categorical Richness). The **categorical richness** of a state $C \in \mathcal{C}$ under observable $\mathcal{O}$ is:

$$R_{\mathcal{O}}(C) = \log \delta_{\mathcal{O}}(C) + \log N_{\text{down}}(C) \quad (564)$$

where:

- $\delta_{\mathcal{O}}(C) = |[C]_{\mathcal{O}}|$ is the degeneracy (equivalence class size);
- $N_{\text{down}}(C) = |\{C' \in \mathcal{C} : C \prec C'\}|$ is the number of downstream accessible states (successors of C in the completion order).

The logarithm makes richness additive for independent contributions.

The richness $R_{\mathcal{O}}(C)$ quantifies the "information capacity" of state C : how many distinct configurations are compatible with the observation $\mathcal{O}(C)$ (horizontal richness, measured by $\log \delta_{\mathcal{O}}(C)$), and how many future states are accessible from C (vertical richness, measured by $\log N_{\text{down}}(C)$).

Remark 39.2 (Horizontal vs. Vertical Richness). The decomposition of richness into horizontal and vertical components reflects two distinct sources of information:

- **Horizontal richness** $\log \delta_{\mathcal{O}}(C)$: How many microstates correspond to the same macrostate? This is analogous to entropy in statistical mechanics, where the entropy $S = k_B \log \Omega$ measures the number of microstates Ω compatible with a macrostate.
- **Vertical richness** $\log N_{\text{down}}(C)$: How many future states are accessible? This is analogous to the "branching factor" in search trees, measuring the number of possible continuations from the current state.

The total richness combines both sources, providing a unified measure of information content.

Definition 39.9 (Categorical Asymmetry). For a process pair (A, B) where $A, B \subseteq \mathcal{C}$ are subsets of categorical states representing two processes (e.g., forward and reverse directions of a reaction), the **categorical asymmetry** is:

$$\mathcal{A}_{\mathcal{O}}(A, B) = \frac{R_{\mathcal{O}}(A) - R_{\mathcal{O}}(B)}{R_{\mathcal{O}}(A) + R_{\mathcal{O}}(B)} \quad (565)$$

where $R_{\mathcal{O}}(S)$ for a set $S \subseteq \mathcal{C}$ is the **aggregate richness**:

$$R_{\mathcal{O}}(S) = \log \left(\sum_{C \in S} e^{R_{\mathcal{O}}(C)} \right) \quad (566)$$

The aggregate richness is the log-sum-exp of individual richnesses, providing a smooth aggregation that emphasizes the richest states.

Proposition 39.6 (Asymmetry Bounds). *For any process pair (A, B) , the categorical asymmetry satisfies:*

$$-1 \leq \mathcal{A}_O(A, B) \leq 1 \quad (567)$$

with the antisymmetry property:

$$\mathcal{A}_O(A, B) = -\mathcal{A}_O(B, A) \quad (568)$$

Proof. The asymmetry is a normalized difference:

$$\mathcal{A}_O(A, B) = \frac{R_O(A) - R_O(B)}{R_O(A) + R_O(B)} \quad (569)$$

Since both $R_O(A)$ and $R_O(B)$ are non-negative (logarithms of positive quantities), the denominator is positive. The numerator satisfies:

$$-(R_O(A) + R_O(B)) \leq R_O(A) - R_O(B) \leq R_O(A) + R_O(B) \quad (570)$$

Dividing by the positive denominator gives $-1 \leq \mathcal{A}_O(A, B) \leq 1$.

For antisymmetry:

$$\mathcal{A}_O(B, A) = \frac{R_O(B) - R_O(A)}{R_O(B) + R_O(A)} = -\frac{R_O(A) - R_O(B)}{R_O(A) + R_O(B)} = -\mathcal{A}_O(A, B) \quad (571)$$

□

Theorem 39.7 (Asymmetry Determines Flow Direction). *For a dynamical system on $\mathcal{C}$ with process pair (A, B) and asymmetry $\mathcal{A} = \mathcal{A}_O(A, B)$, the flow direction is determined by the asymmetry:*

1. $|\mathcal{A}| < \alpha$ (small asymmetry): **Bidirectional flow** with comparable forward and reverse rates;
2. $\mathcal{A} > \beta$ (large positive asymmetry): **Forward-dominant flow** with $A \rightarrow B$ much more probable than $B \rightarrow A$;
3. $\mathcal{A} < -\beta$ (large negative asymmetry): **Reverse-dominant flow** with $B \rightarrow A$ much more probable than $A \rightarrow B$;

for appropriate thresholds $0 < \alpha < \beta < 1$ (typically $\alpha \approx 0.1$, $\beta \approx 0.5$).

Proof. The asymmetry $\mathcal{A}$ measures the difference in richness between processes A and B . Higher richness means more accessible states and higher entropy, which (by the second law of thermodynamics and its categorical analog) favors transitions toward that process.

If $R_O(A) \gg R_O(B)$, then $\mathcal{A} \approx 1$, indicating that process A has much higher richness than B . Transitions from B to A are favored because they increase the number of accessible states (increase entropy). Conversely, if $R_O(B) \gg R_O(A)$, then $\mathcal{A} \approx -1$, favoring transitions from A to B .

The thresholds α and β are phenomenological parameters that depend on the specific system. They separate the regimes of bidirectional (reversible) and unidirectional (irreversible) flow. □

39.5 The S-Distance Metric

We now introduce the S-distance, which measures the "distance" between trajectories in categorical space. This provides the metric structure underlying the S-entropy coordinates.

Definition 39.10 (State Function Space). Let $\mathcal{H}$ be a Hilbert space (a complete inner product space). Define $\mathcal{F}(\mathcal{C}, \mathcal{H})$ as the space of functions $\psi : \mathcal{C} \times \mathbb{R}_{\geq 0} \rightarrow \mathcal{H}$ representing system trajectories in categorical space embedded in $\mathcal{H}$.

For each time t , the function $\psi(\cdot, t) : \mathcal{C} \rightarrow \mathcal{H}$ assigns a Hilbert space vector to each categorical state, representing the "amplitude" or "weight" of that state at time t .

The Hilbert space embedding allows us to use the powerful machinery of functional analysis (inner products, norms, convergence) to study categorical trajectories.

Definition 39.11 (S-Distance). For two trajectories $\psi_1, \psi_2 \in \mathcal{F}(\mathcal{C}, \mathcal{H})$, the **S-distance** is:

$$S(\psi_1, \psi_2) = \int_0^\infty \|\psi_1(t) - \psi_2(t)\|_{\mathcal{H}} dt \quad (572)$$

where $\|\cdot\|_{\mathcal{H}}$ is the norm on the Hilbert space $\mathcal{H}$, and we write $\psi(t)$ as shorthand for the function $\psi(\cdot, t) : \mathcal{C} \rightarrow \mathcal{H}$.

The S-distance integrates the instantaneous distance $\|\psi_1(t) - \psi_2(t)\|_{\mathcal{H}}$ over all time, providing a cumulative measure of how different the two trajectories are.

Theorem 39.8 (S-Distance is a Metric). *The S-distance S defines a metric on the space $\mathcal{F}(\mathcal{C}, \mathcal{H})$ of trajectories (modulo trajectories with $S(\psi_1, \psi_2) = 0$). It satisfies the four metric axioms:*

1. **Non-negativity:** $S(\psi_1, \psi_2) \geq 0$ for all ψ_1, ψ_2 ;
2. **Identity of indiscernibles:** $S(\psi_1, \psi_2) = 0$ if and only if $\psi_1 = \psi_2$ almost everywhere (for almost all t and almost all $C \in \mathcal{C}$);

3. **Symmetry:** $S(\psi_1, \psi_2) = S(\psi_2, \psi_1)$ for all ψ_1, ψ_2 ;

4. **Triangle inequality:** $S(\psi_1, \psi_3) \leq S(\psi_1, \psi_2) + S(\psi_2, \psi_3)$ for all ψ_1, ψ_2, ψ_3 .

Proof. We verify each axiom.

(i) **Non-negativity:** The Hilbert space norm satisfies $\|\psi_1(t) - \psi_2(t)\|_{\mathcal{H}} \geq 0$ for all t . Integrating a non-negative function gives a non-negative result:

$$S(\psi_1, \psi_2) = \int_0^\infty \|\psi_1(t) - \psi_2(t)\|_{\mathcal{H}} dt \geq 0 \quad (573)$$

(ii) **Identity:** If $\psi_1 = \psi_2$ almost everywhere, then $\|\psi_1(t) - \psi_2(t)\|_{\mathcal{H}} = 0$ for almost all t , so the integral is zero. Conversely, if $S(\psi_1, \psi_2) = 0$, then the integral of a non-negative function is zero, which implies the integrand is zero almost everywhere: $\|\psi_1(t) - \psi_2(t)\|_{\mathcal{H}} = 0$ for almost all t . By the identity property of the Hilbert space norm, $\psi_1(t) = \psi_2(t)$ for almost all t .

(iii) **Symmetry:** The Hilbert space norm is symmetric: $\|\psi_1(t) - \psi_2(t)\|_{\mathcal{H}} = \|\psi_2(t) - \psi_1(t)\|_{\mathcal{H}}$. Therefore:

$$S(\psi_1, \psi_2) = \int_0^\infty \|\psi_1(t) - \psi_2(t)\|_{\mathcal{H}} dt = \int_0^\infty \|\psi_2(t) - \psi_1(t)\|_{\mathcal{H}} dt = S(\psi_2, \psi_1) \quad (574)$$

(iv) **Triangle inequality:** The Hilbert space norm satisfies the triangle inequality: $\|\psi_1(t) - \psi_3(t)\|_{\mathcal{H}} \leq \|\psi_1(t) - \psi_2(t)\|_{\mathcal{H}} + \|\psi_2(t) - \psi_3(t)\|_{\mathcal{H}}$ for all t . Integrating both sides:

$$S(\psi_1, \psi_3) = \int_0^\infty \|\psi_1(t) - \psi_3(t)\|_{\mathcal{H}} dt \quad (575)$$

$$\leq \int_0^\infty (\|\psi_1(t) - \psi_2(t)\|_{\mathcal{H}} + \|\psi_2(t) - \psi_3(t)\|_{\mathcal{H}}) dt \quad (576)$$

$$= \int_0^\infty \|\psi_1(t) - \psi_2(t)\|_{\mathcal{H}} dt + \int_0^\infty \|\psi_2(t) - \psi_3(t)\|_{\mathcal{H}} dt \quad (577)$$

$$= S(\psi_1, \psi_2) + S(\psi_2, \psi_3) \quad (578)$$

Therefore, S satisfies all four metric axioms. $\square$

Definition 39.12 (Tri-Dimensional S-Space). The S-distance decomposes into three orthogonal components corresponding to three fundamental dimensions of categorical structure:

$$S = S_k \times S_t \times S_e \quad (579)$$

where:

- S_k : **Knowledge/information dimension** (measures information content, degeneracy, horizontal richness);

- S_t : **Temporal/ordering dimension** (measures time evolution, sequential structure, completion order);

- S_e : **Entropy/constraint dimension** (measures constraint satisfaction, vertical richness, downstream accessibility).

Points in $\mathcal{S}$ are written as triples $\mathbf{S} = (S_k, S_t, S_e)$ where each coordinate is in $[0, 1]$.

Definition 39.13 (S-Distance Decomposition). The full S-distance decomposes as a Pythagorean sum over the three orthogonal dimensions:

$$S(\psi_1, \psi_2)^2 = S_k(\psi_1, \psi_2)^2 + S_t(\psi_1, \psi_2)^2 + S_e(\psi_1, \psi_2)^2 \quad (580)$$

where S_k, S_t, S_e are the component S-distances in each dimension.

This decomposition establishes that the three S-entropy coordinates are orthogonal: they measure independent aspects of the categorical structure. The Pythagorean structure (sum of squares) reflects the fact that the three dimensions are mutually perpendicular in the Hilbert space embedding.

39.6 Recursive Self-Similarity and Scale Ambiguity

One of the most profound properties of categorical spaces is their recursive self-similarity: the structure at one scale is isomorphic to the structure at all other scales.

Axiom 39.4 (Recursive Decomposition). Every categorical space $\mathcal{C}$ admits a canonical decomposition into three factors:

$$\mathcal{C} \cong \mathcal{C}_k \times \mathcal{C}_t \times \mathcal{C}_e \quad (581)$$

where each factor $\mathcal{C}_k, \mathcal{C}_t, \mathcal{C}_e$ is itself a categorical space (with its own partial order, completion operator, and topology).

This decomposition is **canonical** in the sense that it is determined by the intrinsic structure of $\mathcal{C}$, not by an arbitrary choice.

Theorem 39.9 (Recursive Self-Similarity). Under Axiom 39.4, each factor of the categorical space decomposes recursively into three sub-factors:

$$\mathcal{C}_k \cong \mathcal{C}_{k,k} \times \mathcal{C}_{k,t} \times \mathcal{C}_{k,e} \quad (582)$$

$$\mathcal{C}_t \cong \mathcal{C}_{t,k} \times \mathcal{C}_{t,t} \times \mathcal{C}_{t,e} \quad (583)$$

$$\mathcal{C}_e \cong \mathcal{C}_{e,k} \times \mathcal{C}_{e,t} \times \mathcal{C}_{e,e} \quad (584)$$

This recursion continues infinitely: each sub-factor decomposes into three sub-sub-factors, and so on. The full categorical space has the structure:

$$\mathcal{C} \cong \prod_{(i_1, i_2, i_3, \dots) \in \{k, t, e\}^{\mathbb{N}}} \mathcal{C}_{i_1, i_2, i_3, \dots} \quad (585)$$

where the product is over all infinite sequences of indices from $\{k, t, e\}$.

Proof. We apply Axiom 39.4 recursively. At level 0, we have $\mathcal{C} \cong \mathcal{C}_k \times \mathcal{C}_t \times \mathcal{C}_e$. Since each factor is itself a categorical space, we can apply the axiom again to each factor, giving the level-1 decomposition (582)–(584).

Continuing this process indefinitely, we obtain the infinite product structure (585). Each term in the product corresponds to a path through the recursion tree: the sequence $(i_1, i_2, i_3, \dots)$ specifies which factor to choose at each level. $\square$

Theorem 39.10 (3^k Branching). *Under the tri-dimensional recursive decomposition, a cascade of depth k generates:*

$$|\mathcal{C}^{(k)}| = 3^k \times |\mathcal{C}^{(0)}| \quad (586)$$

categorical states at level k , where $|\mathcal{C}^{(0)}|$ is the number of states at level 0 (before decomposition).

The number of states grows exponentially with depth, with base 3.

Proof. At each level of the recursion, the tri-dimensional decomposition creates 3 sub-spaces (factors $\mathcal{C}_k, \mathcal{C}_t, \mathcal{C}_e$). If each sub-space has the same number of states as the parent space (which is the case for self-similar structures), then:

$$|\mathcal{C}^{(1)}| = 3 \times |\mathcal{C}^{(0)}| \quad (587)$$

Applying this recursively for k levels:

$$|\mathcal{C}^{(k)}| = 3 \times |\mathcal{C}^{(k-1)}| = 3^2 \times |\mathcal{C}^{(k-2)}| = \dots = 3^k \times |\mathcal{C}^{(0)}| \quad (588)$$

This establishes the 3^k branching law. $\square$

This theorem explains the 3^{3k} scaling of the hierarchical partition in Section 21: at depth k , the three-dimensional space $\mathcal{S}$ has 3^k cells per dimension, giving $3^k \times 3^k \times 3^k = 3^{3k}$ total cells.

Theorem 39.11 (Scale Ambiguity). *Given a categorical state $C = (c_k, c_t, c_e)$ at hierarchical level $n \in \mathbb{N}$, there exists an isometry (distance-preserving map):*

$$\Psi_n : \mathcal{C}^{(n)} \rightarrow \mathcal{C}^{(n+1)} \quad (589)$$

that preserves all topological and metric structure. Consequently, the hierarchical level cannot be determined from local structure alone: a state at level n is indistinguishable from its image at level $n + 1$.

Proof. The recursive self-similarity (Theorem 39.9) establishes that the structure at level n is isomorphic to the structure at level $n + 1$. The tri-dimensional factorization $\mathcal{C}^{(n)} \cong \mathcal{C}_k^{(n)} \times \mathcal{C}_t^{(n)} \times \mathcal{C}_e^{(n)}$ is identical to the factorization $\mathcal{C}^{(n+1)} \cong \mathcal{C}_k^{(n+1)} \times \mathcal{C}_t^{(n+1)} \times \mathcal{C}_e^{(n+1)}$.

The isometry Ψ_n is constructed by mapping each state $C = (c_k, c_t, c_e) \in \mathcal{C}^{(n)}$ to the corresponding state $\Psi_n(C) = (c_k, c_t, c_e) \in \mathcal{C}^{(n+1)}$ (with the same coordinates but interpreted at the next level). This map preserves:

- Distances: $S(C_1, C_2) = S(\Psi_n(C_1), \Psi_n(C_2))$ (the S-distance is scale-invariant);
- Partial order: $C_1 \prec C_2 \iff \Psi_n(C_1) \prec \Psi_n(C_2)$ (the completion order is preserved);
- Topology: open sets map to open sets (the specialization topology is preserved).

Therefore, Ψ_n is an isometry, and the levels are indistinguishable. $\square$

Corollary 39.12 (Local-Global Indistinguishability). *It is impossible to determine from local examination (measurements within a bounded region) whether a categorical state represents:*

- A global system-level configuration (coarse scale);
- A subsystem at intermediate level (medium scale);
- A component at fine-grained level (fine scale).

All scales are locally indistinguishable due to recursive self-similarity.

Proof. By Theorem 39.11, the local structure (topology, metric, partial order) is identical at all scales. Any measurement or observation that depends only on local structure cannot distinguish between scales. Therefore, local examination cannot determine the hierarchical level. $\square$

This corollary has profound implications: it means that the "resolution" or "scale" of a categorical state is not an intrinsic property but depends on the context (how the state is embedded in a larger system). This is analogous to scale invariance in fractal geometry, where zooming in or out reveals the same structure.

39.7 Categorical Filters and Information Catalysis

We now develop the theory of categorical filters, which are structure-preserving maps that reduce complexity and enhance transition probabilities.

St-Stellas Thermodynamics Validation




Figure 24: **St-Stellas Thermodynamics Validation.** (A) **Miraculous Solutions (Local $\infty \rightarrow$ Global Finite):** Bar chart shows global S-value (completion measure) vs. number of miraculous subtasks. Zero subtasks (blue bar): $S \approx 4.5$ (local infinite complexity collapses to global finite value). (B) **Processor-Oscillator Duality:** Scatter plot shows processing rate (completions/s, log scale) vs. oscillator frequency (Hz, log scale). Green circles with black outlines show perfect linear correlation (slope = 1) from 10^3 Hz / 10^3 completions/s to 10^9 Hz / 10^9 completions/s. (C) **Unified Identity (Single Categorical State):** Venn diagram shows three overlapping circles: M (Memory, blue), P (Processor, red), S (Semantics, green), with Sem (Semantic subspace) in green-blue overlap. (D) **Categorical Temperature (S-Entropy Distribution):** Histogram shows probability density vs. S-entropy (categorical temperature analog). Purple bars show measured distribution: peak at $S \approx 1$ (density ≈ 0.7), decaying exponentially to $S \approx 8$ (density ≈ 0). (E) **Scale Ambiguity (Local = Global):** Bar chart shows structural similarity vs. hierarchical depth k . Orange bars show similarity scores: $k = 0$ (root, ≈ 0.98), $k = 1$ (≈ 0.96), $k = 2$ (≈ 0.95), $k = 3$ (≈ 0.97), $k = 4$ (leaves, ≈ 0.94). (F) **BMD $\equiv$ Navigation $\equiv$ Completion:** Flowchart shows three operations converging to equivalence. BMD Decision (blue box, top left) and Categorical Completion (green box, top right) both connect to S-Space Navigation (red box, bottom center). $\equiv$ Equivalent Operations $\equiv$.

Definition 39.14 (Categorical Filter). A **categorical filter** is a continuous map $\Phi : \mathcal{C}_1 \rightarrow \mathcal{C}_2$ between categorical spaces satisfying three properties:

1. **Order preservation:** If $C \prec C'$ in $\mathcal{C}_1$, then $\Phi(C) \prec \Phi(C')$ in $\mathcal{C}_2$. The filter preserves the completion order.
2. **Completion compatibility:** If $\mu_1(C, t) = 1$ (state C is completed by time t in $\mathcal{C}_1$), then there exists $t' \geq t$ such that $\mu_2(\Phi(C), t') = 1$ (the image state $\Phi(C)$ is completed by some later time t' in $\mathcal{C}_2$). Completion in the source space implies eventual completion in the target space.
3. **Equivalence class reduction:** For any observable $\mathcal{O}_1$ on $\mathcal{C}_1$ and the induced observable $\mathcal{O}_2 = \mathcal{O}_1 \circ \Phi^{-1}$ on $\mathcal{C}_2$, the equivalence classes are reduced:

$$|\Phi([C]_{\mathcal{O}_1})| \ll |[C]_{\mathcal{O}_1}| \quad (590)$$

The filter "collapses" large equivalence classes into smaller ones, reducing degeneracy.

Categorical filters are the appropriate notion of "morphism" between categorical spaces, preserving the essential structure (order, completion, topology) while potentially reducing complexity.

Proposition 39.13 (Filter Composition). *If $\Phi_1 : \mathcal{C}_1 \rightarrow \mathcal{C}_2$ and $\Phi_2 : \mathcal{C}_2 \rightarrow \mathcal{C}_3$ are categorical filters, then their composition $\Phi_2 \circ \Phi_1 : \mathcal{C}_1 \rightarrow \mathcal{C}_3$ is also a categorical filter.*

Proof. We verify that $\Phi_2 \circ \Phi_1$ satisfies the three filter properties:

(i) **Order preservation:** If $C \prec C'$ in $\mathcal{C}_1$, then $\Phi_1(C) \prec \Phi_1(C')$ in $\mathcal{C}_2$ (by property (i) of Φ_1), and then $\Phi_2(\Phi_1(C)) \prec \Phi_2(\Phi_1(C'))$ in $\mathcal{C}_3$ (by property (i) of Φ_2). Therefore, $(\Phi_2 \circ \Phi_1)(C) \prec (\Phi_2 \circ \Phi_1)(C')$.

(ii) **Completion compatibility:** If $\mu_1(C, t) = 1$, then by property (ii) of Φ_1 , there exists t' such that $\mu_2(\Phi_1(C), t') = 1$. By property (ii) of Φ_2 , there exists t'' such that $\mu_3(\Phi_2(\Phi_1(C)), t'') = 1$. Therefore, $\mu_3((\Phi_2 \circ \Phi_1)(C), t'') = 1$.

(iii) **Equivalence class reduction:** By property (iii) of Φ_1 , $|\Phi_1([C]_{\mathcal{O}_1})| \ll |[C]_{\mathcal{O}_1}|$. By property (iii) of Φ_2 , $|\Phi_2(\Phi_1([C]_{\mathcal{O}_1}))| \ll |\Phi_1([C]_{\mathcal{O}_1})|$. Combining, $|(\Phi_2 \circ \Phi_1)([C]_{\mathcal{O}_1})| \ll |[C]_{\mathcal{O}_1}|$.

Therefore, $\Phi_2 \circ \Phi_1$ is a categorical filter. $\square$

This proposition establishes that categorical filters form a category: they can be composed, and the composition is associative (by associativity of function composition). The identity map is the trivial filter that does not reduce equivalence classes.

Theorem 39.14 (Filter Probability Enhancement). *Let $\Phi : \mathcal{C}_1 \rightarrow \mathcal{C}_2$ be a categorical filter with equivalence class reduction factor:*

$$\rho = \frac{|[C]_{\mathcal{O}_1}|}{|\Phi([C]_{\mathcal{O}_1})|} \quad (591)$$

The transition probability through the filter is enhanced by approximately a factor of ρ :

$$\frac{p_\Phi(C_i \rightarrow C_j)}{p_0(C_i \rightarrow C_j)} \sim \rho \quad (592)$$

where p_0 is the transition probability without the filter and p_Φ is the probability with the filter.

Proof. We model the transition from state C_i to state C_j as a random selection from the set of accessible configurations.

Without filter: The transition selects from $N_{\text{down}}(C_i)$ downstream states (successors of C_i), each of which belongs to an equivalence class of size $\delta \sim |[C]_{\mathcal{O}_1}|$. The total number of configurations is:

$$N_{\text{total}} = N_{\text{down}}(C_i) \times \delta \quad (593)$$

The probability of transitioning to a specific state C_j is:

$$p_0(C_i \rightarrow C_j) \sim \frac{1}{N_{\text{total}}} = \frac{1}{N_{\text{down}}(C_i) \times \delta} \quad (594)$$

With filter: The filter reduces equivalence class sizes by a factor of ρ , so the effective equivalence class size is δ/ρ . The total number of configurations is:

$$N_{\text{total}}^\Phi = N_{\text{down}}(C_i) \times (\delta/\rho) \quad (595)$$

The probability of transitioning to C_j is:

$$p_\Phi(C_i \rightarrow C_j) \sim \frac{1}{N_{\text{total}}^\Phi} = \frac{1}{N_{\text{down}}(C_i) \times (\delta/\rho)} = \frac{\rho}{N_{\text{down}}(C_i) \times \delta} \quad (596)$$

The probability ratio is:

$$\frac{p_\Phi(C_i \rightarrow C_j)}{p_0(C_i \rightarrow C_j)} = \frac{\rho/(N_{\text{down}} \times \delta)}{1/(N_{\text{down}} \times \delta)} = \rho \quad (597)$$

Therefore, the filter enhances the transition probability by a factor of ρ . $\square$

Corollary 39.15 (Information Catalysis). *For typical categorical filters in biological and computational systems, the reduction factor is large: $\rho \sim 10^6$ to 10^{11} [14]. This produces dramatic probability enhancement:*

- *Transitions with baseline probability $p_0 \sim 10^{-9}$ (extremely rare) become $p_\Phi \sim 10^{-3}$ (moderately probable) for $\rho \sim 10^6$;*

- Transitions with $p_0 \sim 10^{-9}$ become $p_\Phi \sim 10^2$ (highly probable, essentially certain) for $\rho \sim 10^{11}$.

This phenomenon is called **information catalysis**: constraints (encoded in the filter) catalyze transitions by reducing the space of possibilities, analogous to how enzymes catalyze chemical reactions by reducing activation energy.

Proof. Direct calculation using (592):

$$p_\Phi = \rho \times p_0 \quad (598)$$

$$= 10^6 \times 10^{-9} = 10^{-3} \quad (\text{for } \rho = 10^6) \quad (599)$$

$$= 10^{11} \times 10^{-9} = 10^2 \quad (\text{for } \rho = 10^{11}) \quad (600)$$

□

39.8 Connection to Poincaré Computing

We conclude by establishing that the S-entropy space used throughout this paper is the canonical realization of the abstract categorical space structure.

Theorem 39.16 (S-Space is Poincaré Computing Substrate). *The bounded S-entropy space $\mathcal{S} = [0, 1]^3$ (Section 21) is the canonical realization of a categorical space $(\mathcal{C}, \prec, \mu, \tau)$ with:*

1. The partial order $\prec$ induced by categorical completion: $C \prec C'$ if state C must be completed before state C' can be accessed;
2. The completion operator μ encoding trajectory history: $\mu(C, t) = 1$ if the trajectory γ has visited cell C by time t ;
3. The specialization topology τ compatible with the S-distance metric: open sets are upward-closed under $\prec$, and the metric topology induced by S coincides with τ .

The Poincaré recurrence dynamics (Section 29) correspond to completion trajectories in this categorical structure, and the categorical completion rate (Section 35) is the rate $\dot{C}(t)$ defined in Definition 39.3.

Proof. We construct an explicit embedding $\phi : \mathcal{C} \rightarrow \mathcal{S}$ that preserves all structure.

(i) **Partial order:** The hierarchical partition $\mathcal{P}_k$ (Definition 21.2) induces a natural partial order on cells: $C \prec C'$ if cell C must be visited before cell C' in any trajectory satisfying the categorical dynamics. This order is preserved by the embedding ϕ : cells

that are predecessors in $\mathcal{C}$ map to regions in $\mathcal{S}$ that are visited earlier in the trajectory evolution.

Formally, for cells $C, C' \in \mathcal{P}_k$, define:

$$C \prec C' \iff \exists \gamma \in \mathcal{A}(P) : \inf\{t : \gamma(t) \in C\} < \inf\{t : \gamma(t) \in C'\} \quad (601)$$

This order is compatible with the S-entropy coordinates: if $C = (S_k, S_t, S_e)$ and $C' = (S'_k, S'_t, S'_e)$ with $C \prec C'$, then typically $S_t < S'_t$ (the temporal coordinate increases along trajectories).

(ii) **Completion operator:** The exploration memory $\mathcal{M}(t)$ (Definition 37.1) defines the completion operator:

$$\mu(C, t) = \begin{cases} 1 & \text{if } C \in \mathcal{M}(t) \text{ (cell visited by time } t) \\ 0 & \text{if } C \notin \mathcal{M}(t) \text{ (cell not yet visited)} \end{cases} \quad (602)$$

This operator satisfies Axiom 39.1 (by Proposition 37.3) and Axiom 39.2 (by the definition of the partial order).

(iii) **Topology:** The specialization topology on $\mathcal{C}$ is induced by the partial order $\prec$ (Axiom 39.3). We must show that this topology is compatible with the S-distance metric.

The S-distance metric induces a metric topology on $\mathcal{S}$ where open balls $B_r(\mathbf{S}) = \{\mathbf{S}' : S(\mathbf{S}, \mathbf{S}') < r\}$ form a basis. We claim that the metric topology coincides with the specialization topology.

For any upward-closed set U (open in the specialization topology), the set $\phi^{-1}(U)$ is open in the metric topology because trajectories approaching U from below (in the partial order) converge in the S-distance metric. Conversely, for any open ball $B_r(\mathbf{S})$ in the metric topology, the preimage $\phi^{-1}(B_r(\mathbf{S}))$ is upward-closed because states close in S-distance have similar completion orders.

Therefore, the two topologies coincide, establishing that $\mathcal{S}$ is a categorical space.

Recurrence dynamics: The Poincaré recurrence dynamics (Section 29) evolve the categorical state $\mathbf{S}(t)$ according to the differential equations (373)–(375). The trajectory $\gamma(t) = \mathbf{S}(t)$ traces a path through $\mathcal{S}$, visiting cells in the hierarchical partition $\mathcal{P}_k$.

By Definition 39.2, the set of visited cells $\gamma(t) = \{C \in \mathcal{P}_k : \exists s \leq t, \mathbf{S}(s) \in C\}$ is a completion trajectory: it is monotonically growing (property (ii)), downward-closed (property (iii)), and corresponds to the completion operator (property (i)).

The recurrence condition $\|\gamma(T) - \mathbf{S}_0\| < \epsilon$ (Definition ??) corresponds to the trajectory returning to a cell close to the initial cell, completing a cycle in the categorical space.

Completion rate: The categorical completion rate ρ_C (Definition 35.6) counts the number of cells

exited per unit of promising trajectory length. This is precisely the rate $\dot{C}(t)$ in Definition 39.3:

$$\rho_C = \frac{d|\mathcal{M}(t)|}{dt} / \|\dot{\gamma}(t)\| = \frac{\dot{C}(t)}{\|\dot{\gamma}(t)\|} \quad (603)$$

where $\|\dot{\gamma}(t)\|$ is the arc-length velocity.

Therefore, all components of the Poincaré Computing framework (dynamics, recurrence, completion rate) are manifestations of the underlying categorical space structure, establishing that $\mathcal{S}$ is the canonical realization of $\mathcal{C}$. $\square$

40 The Categorical Compiler

41 The Categorical Compiler and Asymptotic Solution Recognition

The preceding sections have established Poincaré Computing as a computational framework based on continuous trajectory evolution in categorical space, governed by irreversible completion dynamics and characterized by asymptotic exhaustive exploration. However, we have not yet addressed the practical question: how are computational problems introduced into this system, and how are solutions extracted? This section establishes the architecture of the **categorical compiler**, which operates as a bidirectional translator between problem representations and categorical dynamics.

We prove that the compiler does not follow the traditional compile-then-execute paradigm but instead operates through three concurrent phases: forward translation (problem to categorical state), categorical evolution (trajectory dynamics), and backward translation (categorical state to result). We establish that categorical irreversibility (Axiom 39.1) implies solutions are recognized at the ϵ -boundary—one categorical step from closure—and that this asymptotic nature is not a limitation but a fundamental structural property. We prove the **Penultimate State Theorem** (Theorem 41.4), which establishes that solutions are recognized at the state immediately preceding would-be closure, and we develop the theory of problem introduction through gas dynamics, showing how new problems are introduced through molecular addition, separation, and joining without requiring system restart.

41.1 Bidirectional Translation Architecture

The categorical compiler mediates between the problem domain (where computational tasks are specified) and the categorical domain (where trajectories evolve). Unlike traditional compilers that perform a one-time translation from source code to machine code, the categorical compiler operates continuously and bidirectionally.

Definition 41.1 (Categorical Compiler). The **categorical compiler** $\mathcal{K}$ is a pair of concurrent operators:

$$\mathcal{K} = (\mathcal{T}_{\text{in}}, \mathcal{T}_{\text{out}}) \quad (604)$$

where:

- $\mathcal{T}_{\text{in}} : \mathcal{P} \rightarrow \mathcal{S}$ is the **forward translator**, mapping problem specifications to categorical states;
- $\mathcal{T}_{\text{out}} : \mathcal{S} \rightarrow \mathcal{R}$ is the **backward translator**, mapping categorical states to result representations.

Both operators execute concurrently and continuously throughout the computation.

The forward translator $\mathcal{T}_{\text{in}}$ encodes problem constraints, objectives, and data into an initial categorical state $\mathbf{S}_0 \in \mathcal{S}$. This encoding uses the problem encoding framework developed in Section ???. The backward translator $\mathcal{T}_{\text{out}}$ decodes the current categorical state $\gamma(t)$ into a result representation $r(t) \in \mathcal{R}$, which may be a partial solution (if the trajectory has not yet converged) or a final solution (if convergence has been detected).

Theorem 41.1 (Concurrent Bidirectional Operation). *The categorical compiler does not compile-then-execute. Instead, it operates in three concurrent phases:*

1. **Forward translation:** $\mathcal{T}_{\text{in}}$ continuously maps problem updates to categorical perturbations;
2. **Categorical dynamics:** The trajectory $\gamma(t)$ evolves in $\mathcal{S}$ according to the dynamics (373)–(375);
3. **Backward translation:** $\mathcal{T}_{\text{out}}$ continuously maps categorical states to intermediate results.

All three phases execute simultaneously, with convergence detected when $\mathcal{T}_{\text{out}}(\gamma(t))$ stabilizes.

Proof. Traditional compilation separates phases sequentially: parse $\rightarrow$ compile $\rightarrow$ execute $\rightarrow$ return. In

Poincaré Computing, there is no such separation because the problem, dynamics, and results are coupled throughout the computation.

(i) Problem specification is not fixed: The problem P may be refined during execution. Each refinement is a perturbation to the categorical state:

$$P \rightarrow P' \implies \mathbf{S}_0 \rightarrow \mathbf{S}_0 + \delta \mathbf{S} \quad (605)$$

The dynamics incorporate this perturbation without restarting. By Theorem 41.6 (proven below), perturbations can be applied at any time t_0 , and the trajectory $\gamma(t)$ for $t > t_0$ reflects the new configuration.

(ii) Results emerge continuously: Intermediate categorical states $\gamma(t)$ have semantic meaning—they represent partial solutions. The backward translator $\mathcal{T}_{\text{out}}$ extracts this meaning:

$$r(t) = \mathcal{T}_{\text{out}}(\gamma(t)) \quad (606)$$

As t increases and the trajectory explores more of the categorical space, $r(t)$ converges to the final result. The convergence is gradual, not instantaneous.

(iii) Convergence replaces termination: The system never halts (Corollary 37.2). Instead, convergence is detected by monitoring the stability of $r(t)$:

$$\|r(t) - r(t - \Delta t)\| < \delta \quad \text{for sufficiently many consecutive intervals } \Delta t \quad (607)$$

This is waiting for convergence, not waiting for completion. Once convergence is detected, the result $r(t)$ is emitted, but the dynamics continue (accumulating capability for future problems, by Theorem 37.13).

Therefore, the three phases are concurrent, not sequential, establishing the bidirectional operation. $\square$

Definition 41.2 (Convergence Detection). The **convergence detector** $\mathcal{D}$ monitors the backward translation output:

$$\mathcal{D}(t) = \begin{cases} 1 & \text{if } \|r(t) - r(t - \Delta t)\| < \delta \text{ for } k \text{ consecutive intervals} \\ 0 & \text{otherwise} \end{cases} \quad (608)$$

where $\delta > 0$ is the convergence threshold and $k \geq 1$ is the stability window (typically $k = 3$ to 5 to avoid false positives from transient fluctuations).

When $\mathcal{D}(t) = 1$, the result $r(t)$ is returned as the solution.

Remark 41.1 (Non-Halting Convergence). The convergence detector does not stop the dynamics—it extracts a snapshot. The trajectory continues evolving after convergence is detected, potentially improving the result precision or discovering solutions to related problems. This is a key distinction from traditional computation, where detecting the answer terminates

the program. In Poincaré Computing, detecting the answer is an observation event, not a termination event.

41.2 Categorical Irreversibility and the One-Step Boundary

We now establish the fundamental theorem governing solution recognition in Poincaré Computing: solutions are recognized at the ϵ -boundary, one categorical step from closure, and this is not an approximation but the structural nature of solutions.

Theorem 41.2 (Asymptotic Solution Theorem). *Due to categorical irreversibility (Axiom 39.1), the system can approach but never exactly reach the initial categorical state. The closest achievable configuration is one categorical step from closure:*

$$\min_{t>0} d_{\text{cat}}(\gamma(t), C_0) = 1 \quad (609)$$

where d_{cat} is the categorical distance (number of completion steps between states) and C_0 is the initial categorical state.

Proof. Let C_0 be the initial categorical state encoding problem P . By Axiom 39.1, once a categorical state is completed, it remains completed for all future times:

$$\mu(C_0, 0) = 1 \implies \mu(C_0, t) = 1 \quad \forall t > 0 \quad (610)$$

At $t = 0$, the state C_0 is completed (the problem is "observed" by the system). For all $t > 0$, C_0 remains completed, meaning it cannot be re-completed.

The Poincaré recurrence theorem (Theorem 43.1) guarantees that the trajectory returns to an ϵ -neighborhood of the initial state in the metric topology:

$$\exists T > 0 : \|\gamma(T) - \mathbf{S}_0\| < \epsilon \quad (611)$$

where $\mathbf{S}_0 \in \mathcal{S}$ is the $\mathbf{S}$ -entropy coordinate of C_0 .

However, this return occupies a *different* categorical state $C_T \neq C_0$. The states are distinct in the categorical space $\mathcal{C}$ but close in the metric space $\mathcal{S}$:

$$C_0 \prec C_T \quad \text{and} \quad \mathcal{O}(C_T) \approx \mathcal{O}(C_0) \quad (612)$$

The observable values (extracted by the backward translator $\mathcal{T}_{\text{out}}$) are approximately equal, but the categorical states are distinct in the completion order.

The categorical distance $d_{\text{cat}}(C_i, C_j)$ counts the minimum number of completion steps required to go from C_i to C_j along the partial order $\prec$. Since C_0 is already completed and cannot be re-completed, the minimum distance is:

$$d_{\text{cat}}(C_T, C_0) \geq 1 \quad (613)$$

We now show that this minimum is achieved. By the construction of the categorical space (Theorem 39.16), there exists a state $C_{\text{penultimate}}$ satisfying:

$$C_{\text{penultimate}} \prec C'_0 \quad \text{and} \quad \mathcal{O}(C'_0) = \mathcal{O}(C_0) \quad (614)$$

where C'_0 is the "would-be closure" state (observationally equivalent to C_0 but occurring later in the completion order). The state $C_{\text{penultimate}}$ is immediately before C'_0 :

$$\nexists C : C_{\text{penultimate}} \prec C \prec C'_0 \quad (615)$$

The trajectory can reach $C_{\text{penultimate}}$, achieving $d_{\text{cat}}(C_{\text{penultimate}}, C'_0) = 1$. Since C'_0 is observationally equivalent to C_0 , we have:

$$\min_{t>0} d_{\text{cat}}(\gamma(t), C_0) = 1 \quad (616)$$

Therefore, the closest the system can get is one categorical step from the initial state. $\square$

Corollary 41.3 (Solution at the ϵ -Boundary). *The solution IS being one step away from closure. The ϵ -neighborhood is not an approximation—it is the solution itself.*

Proof. Since exact return to C_0 is forbidden by irreversibility (Axiom 39.1), the solution cannot be defined as exact return. The only consistent definition within the categorical framework is:

$$\text{Solution} \equiv \gamma(T) \text{ such that } \|\gamma(T) - \mathbf{S}_0\| < \epsilon \text{ AND } C_T \neq C_0 \quad (617)$$

The inequality $C_T \neq C_0$ is mandatory, not optional. The ϵ -neighborhood is not an approximation to some "true" solution at $\epsilon = 0$; rather, the ϵ -neighborhood is the solution.

In traditional numerical computation, ϵ -approximation is a limitation imposed by finite precision: we cannot represent the exact answer, so we accept an error of size ϵ . In Poincaré Computing, ϵ -proximity is the fundamental nature of solutions: there is no "exact" answer to approximate, only the ϵ -boundary to reach.

Therefore, being one step away from closure IS the solution, not an approximation to it. $\square$

Theorem 41.4 (The Penultimate State). *Let γ^* be a solution trajectory. The final recognized state is the **penultimate state**—one step before would-be closure:*

$$\gamma^*(T) = C_{\text{penultimate}} \quad \text{where} \quad C_{\text{penultimate}} \prec C'_0 \text{ (would-be closure)} \quad (618)$$

The step from $C_{\text{penultimate}}$ to C'_0 cannot be taken because C'_0 would require re-occupying C_0 's observational equivalence class after C_0 has been completed.

Proof. Define the would-be closure state C'_0 as the categorical state satisfying:

$$\mathcal{O}(C'_0) = \mathcal{O}(C_0) \quad \text{and} \quad C_0 \prec C'_0 \quad (619)$$

where $\mathcal{O}$ is the observable projection (Definition 39.4). This state exists by the fiber bundle structure (Theorem 39.5): the fiber $\mathcal{O}^{-1}(\mathcal{O}(C_0))$ contains multiple categorical states with the same observable value, and C'_0 is the element of this fiber that comes after C_0 in the completion order.

Occupying C'_0 would mean:

1. C'_0 produces observables identical to C_0 : $\mathcal{O}(C'_0) = \mathcal{O}(C_0)$;
2. C'_0 comes after C_0 in the completion order: $C_0 \prec C'_0$;
3. Therefore, C'_0 represents "returning to the same observable configuration."

The categorical dynamics evolve the trajectory toward C'_0 (by the recurrence property, Theorem 43.1). However, the final step from $C_{\text{penultimate}}$ to C'_0 would complete a category observationally equivalent to the starting category C_0 . By the irreversibility axiom (Axiom 39.1), this is forbidden.

The system recognizes this impending closure and stops at the penultimate state $C_{\text{penultimate}}$ satisfying:

$$C_{\text{penultimate}} \prec C'_0 \quad \text{and} \quad \nexists C : C_{\text{penultimate}} \prec C \prec C'_0 \quad (620)$$

This is the immediately preceding state—one step from closure. The convergence detector $\mathcal{D}$ (Definition 41.2) recognizes that the trajectory has entered the ϵ -neighborhood:

$$\|\gamma(T) - \mathbf{S}_0\| < \epsilon \quad \text{where} \quad \gamma(T) = C_{\text{penultimate}} \quad (621)$$

and emits the result $r(T) = \mathcal{T}_{\text{out}}(C_{\text{penultimate}})$.

Therefore, the penultimate state is the final recognized state, one step before would-be closure. $\square$

Remark 41.2 (Geometric Interpretation). The Penultimate State Theorem has a geometric interpretation in $\mathcal{S}$. The initial state $\mathbf{S}_0$ is a point in $[0, 1]^3$. The would-be closure state $\mathbf{S}'_0$ is a nearby point (within ϵ of $\mathbf{S}_0$) observationally equivalent but categorically distinct. The penultimate state $\mathbf{S}_{\text{penultimate}}$ is on the boundary of the ϵ -ball around $\mathbf{S}_0$, at the point where the trajectory is about to enter but cannot due to irreversibility. This boundary is the solution surface.

41.3 Problem Introduction Through Gas Dynamics

Having established how solutions are recognized, we now address how problems are introduced. In Poincaré Computing, problems are not "loaded" into memory but are introduced through perturbations to the virtual gas ensemble.

Theorem 41.5 (Problem Introduction by Molecular Configuration). *New problems are introduced to the system through three mechanisms:*

1. **Addition:** Adding gas molecules (expanding categorical space);
2. **Separation:** Splitting molecule clusters (partitioning categorical space);
3. **Joining:** Merging molecule clusters (unifying categorical regions).

Each mechanism perturbs the categorical configuration, creating new initial states without requiring system restart.

Proof. The virtual gas ensemble (Section 25) maps hardware oscillations to molecular configurations. Each molecule corresponds to a categorical state, and the interactions between molecules correspond to the partial order $\prec$ on $\mathcal{C}$.

(i) **Addition:** Adding n molecules expands the categorical space:

$$\mathcal{C} \rightarrow \mathcal{C}' = \mathcal{C} \cup \{C_{\text{new},1}, \dots, C_{\text{new},n}\} \quad (622)$$

The new states $C_{\text{new},i}$ are initially uncompleted: $\mu(C_{\text{new},i}, t_0) = 0$ where t_0 is the time of addition. The partial order $\prec$ is extended to include the new states:

$$\prec' = \prec \cup \{(C_i, C_{\text{new},j}) : C_i \in \mathcal{C}, C_i \prec' C_{\text{new},j}\} \quad (623)$$

This introduces new reachable states, potentially creating new solution trajectories. The dynamics continue from the current state $\gamma(t_0)$, now exploring the expanded space $\mathcal{C}'$.

(ii) **Separation:** Separating a cluster of m molecules partitions their interactions. Before separation, the molecules $\{C_1, \dots, C_m\}$ are coupled: their completion order is constrained by inter-molecular interactions. After separation, the cluster is partitioned into two sub-clusters:

$$\{C_1, \dots, C_m\}_{\text{coupled}} \rightarrow \{C_1, \dots, C_k\}_A \cup \{C_{k+1}, \dots, C_m\}_B \quad (624)$$

The coupling constraints between sets A and B are removed:

$$\prec' = \prec \setminus \{(C_i, C_j) : C_i \in A, C_j \in B\} \quad (625)$$

This changes the accessible trajectories: paths that were forbidden due to inter-cluster constraints become accessible. The dynamics adapt to the new partial order without restarting.

(iii) **Joining:** Merging two clusters introduces new coupling constraints. Before joining, clusters A and B evolve independently. After joining:

$$\{C_1, \dots, C_k\}_A \cup \{C_{k+1}, \dots, C_m\}_B \rightarrow \{C_1, \dots, C_m\}_{\text{coupled}} \quad (626)$$

New precedence relations are added:

$$\prec' = \prec \cup \{(C_i, C_j) : C_i \in A, C_j \in B, \text{interaction exists}\} \quad (627)$$

New harmonic coincidences become possible (Section 29), creating new solution paths. The dynamics incorporate these new constraints, potentially converging faster to solutions that require coordination between A and B .

Each mechanism changes the categorical configuration $(\mathcal{C}, \prec, \mu)$ without requiring a restart. The ongoing dynamics incorporate the change, and the trajectory $\gamma(t)$ for $t > t_0$ (where t_0 is the time of perturbation) reflects the new configuration. $\square$

Definition 41.3 (Problem Perturbation). A **problem perturbation** is a modification to the categorical configuration:

$$\delta P : (\mathcal{C}, \mathbf{S}_0, \prec) \rightarrow (\mathcal{C}', \mathbf{S}'_0, \prec') \quad (628)$$

The perturbation can be:

- **Additive:** $|\mathcal{C}'| > |\mathcal{C}|$ (new categorical states added);
- **Subtractive:** $|\mathcal{C}'| < |\mathcal{C}|$ (categorical states removed);
- **Structural:** $|\mathcal{C}'| = |\mathcal{C}|$ but $\prec' \neq \prec$ (connectivity changed).

Theorem 41.6 (Continuous Problem Refinement). *Problem perturbations can be introduced at any time t_0 without restarting the computation. The dynamics continuously adapt:*

$$\gamma(t) \text{ adapts to } \delta P \text{ applied at } t_0 \implies \gamma(t > t_0) \text{ reflects new configuration} \quad (629)$$

Proof. The categorical dynamics (equations (373)–(375)) depend on the current configuration

$(\mathcal{C}(t), \gamma(t), \prec(t))$. When a perturbation δP is applied at time t_0 :

$$(\mathcal{C}(t_0^-), \gamma(t_0^-), \prec(t_0^-)) \xrightarrow{\delta P} (\mathcal{C}(t_0^+), \gamma(t_0^+), \prec(t_0^+)) \quad (630)$$

where t_0^- denotes the instant before perturbation and t_0^+ denotes the instant after.

The trajectory γ is adjusted to account for the new configuration:

- For additive perturbations: new states are added to $\mathcal{C}'$ with $\mu(C_{\text{new}}, t_0^+) = 0$ (uncompleted). The trajectory continues from $\gamma(t_0^-)$, now exploring the expanded space.
- For subtractive perturbations: removed states are deleted from $\mathcal{C}'$. If any removed state was in $\gamma(t_0^-)$ (already completed), the completion is retained in memory, but the state is no longer active. The trajectory continues in the reduced space.
- For structural perturbations: the partial order $\prec$ is modified. The trajectory $\gamma(t_0^-)$ is checked for consistency with $\prec'$. If inconsistent (e.g., a completed state now has an uncompleted predecessor), the inconsistency is resolved by re-completing the necessary predecessors (which is allowed because they are different categorical states, not re-completions of the same state).

The dynamics continue from the adjusted state $\gamma(t_0^+)$ without loss of progress. Already completed categories remain completed (by Axiom 39.1), so the exploration memory $\mathcal{M}(t_0^-)$ is preserved (modulo removed states).

Therefore, perturbations can be applied at any time, and the dynamics adapt continuously. $\square$

Remark 41.3 (Interactive Computation). Theorem 41.6 enables interactive computation: the user can refine the problem specification during execution, and the system adapts without restarting. This is analogous to interactive theorem provers (e.g., Coq, Isabelle), where the user guides the proof search; however, in Poincaré Computing, the guidance comes through problem perturbations rather than proof tactics.

41.4 The Compiler Runtime Loop

We now formalise the operational behaviour of the categorical compiler as a non-terminating runtime loop.

Definition 41.4 (Compiler Runtime). The **categorical compiler runtime** executes the following concurrent loop:

1. **Monitor:** Watch for problem perturbations δP (from user input or external events);
2. **Translate-In:** Apply the forward translator $\mathcal{T}_{\text{in}}$ to any new problem components, producing categorical perturbations;
3. **Evolve:** Advance categorical dynamics by time step Δt , updating $\gamma(t) \rightarrow \gamma(t + \Delta t)$;
4. **Translate-Out:** Apply the backward translator $\mathcal{T}_{\text{out}}$ to the current state $\gamma(t + \Delta t)$, producing result $r(t + \Delta t)$;
5. **Check:** Test convergence via detector $\mathcal{D}(t + \Delta t)$;
6. **Continue:** If $\mathcal{D}(t + \Delta t) = 0$ (not converged), goto step 1; if $\mathcal{D}(t + \Delta t) = 1$ (converged), emit result $r(t + \Delta t)$ and goto step 1.

This loop never terminates—it continuously processes problems.

Theorem 41.7 (Non-Terminating Runtime). *The compiler runtime is non-terminating by design:*

$$\forall t \geq 0 : \text{Runtime is active at } t \quad (631)$$

Convergence detection emits results but does not halt the loop.

Proof. From Theorem 37.1, the categorical dynamics have no halt state: there is no configuration from which no further exploration is possible. The runtime mirrors this property.

When convergence is detected ($\mathcal{D}(t) = 1$), the following occurs:

1. Result $r(t)$ is emitted to the user or calling process;
2. Dynamics continue exploring the categorical space;
3. System capability increases (Theorem 37.13): the exploration memory $\mathcal{M}(t)$ grows, reducing conditional complexity for future problems;
4. Future related problems benefit from the accumulated exploration (Theorem 37.9): if a new problem P' is introduced that is related to the solved problem P , the system converges faster.

Categorical Compiler Validation




Figure 25: **Categorical Compiler Validation.** (A) **Bidirectional Translation:** The compiler operates through three concurrent phases—forward translation ($T_{in} : \mathcal{P} \rightarrow \mathcal{S}$), categorical dynamics ($\gamma(t)$ evolution), and backward translation. (B) **Convergence Detection:** Observable $r(t) = T_{out}(\gamma(t))$ converges to stable value (dashed line) after trajectory exploration. Convergence detector $\mathcal{D}(t)$ identifies when $\|r(t) - r(t - \Delta t)\| < \delta$ for k consecutive intervals (green shaded region), triggering result emission without halting dynamics (Definition 41.2). (C) **Asymptotic Solutions (Never Exact Return):** Final distance to initial state $\|\gamma(T) - S_0\|$ is always positive across 20 independent runs. (D) **ϵ -Boundary Recognition:** Solution recognition occurs at progressively smaller ϵ thresholds (Test 1: $\epsilon = 0.1$, Test 2: $\epsilon = 0.15$, Test 3: $\epsilon = 0.2$) with final distances approaching but never reaching zero (dashed lines show targets). (E) **Penultimate State (One Step From Closure):** Trajectory approaches initial state along completion order, reaching minimum distance at penultimate state (yellow marker) one categorical step from would-be closure (red marker at distance ≈ 0). (F) **Non-Terminating Runtime:** System remains active (normalized activity = 1.0) throughout computation. Convergence detection (orange dashed line) emits result but does not halt dynamics.

Halting the runtime after convergence would forfeit these benefits. The system would need to restart from scratch for each new problem, losing the accumulated capability. By remaining active, the runtime accumulates capability continuously, improving performance over time.

Therefore, the runtime is non-terminating by design, not by accident. $\square$

Corollary 41.8 (Always One Step Away). *At any moment, the system is at most one categorical step from recognizing a solution to some problem:*

$$\forall t \geq 0, \exists P : d_{\text{cat}}(\gamma(t), \mathbf{S}_P^{\text{solution}}) \leq 1 \quad (632)$$

The continuous exploration ensures proximity to solutions for a growing set of problems.

Proof. By Theorem 37.4, the exploration eventually visits all categories (in the limit $t \rightarrow \infty$). At any finite time t , the current state $\gamma(t)$ is adjacent to multiple categories in the partial order $\prec$:

$$\text{Adjacent}(\gamma(t)) = \{C \in \mathcal{C} : \gamma(t) \prec C \text{ and } \nexists C' : \gamma(t) \prec C' \prec C\} \quad (633)$$

Each adjacent category $C \in \text{Adjacent}(\gamma(t))$ is potentially a solution to some problem P . As exploration progresses, the set of problems for which the current state is adjacent to a solution grows:

$$|\{P : d_{\text{cat}}(\gamma(t), \mathbf{S}_P^{\text{solution}}) \leq 1\}| \text{ increases with } t \quad (634)$$

Therefore, at any moment, there exists at least one problem P for which the current state is one step from solution. The system is always "close" to solving something, and the set of "somethings" grows over time. $\square$

41.5 Implications for Computation

We conclude by establishing the fundamental principles of computation in the Poincaré Computing framework.

Theorem 41.9 (Asymptotic Computation Principle). *Computation in Poincaré Computing is fundamentally asymptotic:*

1. *Problems are never “solved exactly”—they are approached to within ϵ ;*
2. *Solutions are recognized, not reached;*
3. *The ϵ -boundary is the solution, not an approximation;*
4. *Continuing past recognition improves precision for related problems.*

Proof. (i) No exact solutions: Exact solution would require re-occupying the initial category C_0 , which is forbidden by irreversibility (Axiom 39.1). By Theorem 41.2, the closest achievable configuration is one categorical step from closure, corresponding to ϵ -proximity in the metric topology.

(ii) Recognition vs. reaching: The convergence detector $\mathcal{D}$ (Definition 41.2) recognizes when the trajectory has entered the ϵ -neighborhood:

$$\mathcal{D}(t) = 1 \iff \|\gamma(t) - \mathbf{S}_0\| < \epsilon \quad (635)$$

Recognition is observation of proximity, not attainment of identity. The system observes that it is close to the initial state, not that it has returned to the initial state.

(iii) ϵ -boundary is the solution: By Corollary 41.3, the ϵ -boundary is definitionally the solution within the categorical framework. There is no "truer" solution at $\epsilon = 0$ to approximate. The solution IS being within ϵ of the initial state while remaining categorically distinct.

(iv) Continued improvement: By Theorem 37.7, continued exploration after recognition decreases conditional complexity:

$$\Pi(P' \mid \mathcal{M}(T)) < \Pi(P' \mid \mathcal{M}(T')) \quad (636)$$

for $T' > T$ (where T is the recognition time) and related problems P' . The exploration memory $\mathcal{M}(T')$ contains more completed categories, providing more "context" for solving P' . This improves precision: the ϵ required for convergence decreases, and the convergence time decreases.

Therefore, computation is fundamentally asymptotic, with recognition (not reaching) as the solution concept. $\square$

Remark 41.4 (Comparison to Numerical Computation). In numerical computation, ϵ -approximation is a limitation imposed by finite precision. Real numbers are approximated by floating-point numbers with finite mantissa, introducing rounding errors of size $\epsilon \sim 10^{-16}$ (for double precision). We accept this error because exact representation is impossible.

In Poincaré Computing, ϵ -proximity is the fundamental nature of solutions, not a limitation. The distinction:

- **Numerical:** “We cannot reach the exact answer, so we accept ϵ -error as an unavoidable compromise.”
- **Poincaré:** “The answer IS being within ϵ ; there is no ‘exact’ to reach. The ϵ -boundary is the solution itself.”

This is not a philosophical reframing but a structural consequence of categorical irreversibility. The irreversibility axiom (Axiom 39.1) forbids exact return, making ϵ -proximity the only possible solution concept.

Theorem 41.10 (Problem-Solution Proximity). *At the moment of solution recognition, problem and solution are one categorical step apart:*

$$d_{\text{cat}}(\mathbf{S}_{\text{problem}}, \mathbf{S}_{\text{solution}}) = 1 \quad (637)$$

They are as close as categorically possible while remaining distinct.

Proof. The problem is encoded in the initial state $\mathbf{S}_0 = \mathcal{T}_{\text{in}}(P)$ (forward translation). The solution is the penultimate state $C'_{\text{penultimate}}$ (Theorem 41.4). By definition of the penultimate state:

$$C_{\text{penultimate}} \prec C'_0 \quad \text{with no intermediate state} \quad (638)$$

where C'_0 is observationally equivalent to C_0 : $\mathcal{O}(C'_0) = \mathcal{O}(C_0)$.

The categorical distance is:

$$d_{\text{cat}}(C_{\text{penultimate}}, C'_0) = 1 \quad (639)$$

Since C'_0 is observationally equivalent to C_0 , we have:

$$d_{\text{cat}}(\mathbf{S}_{\text{solution}}, \mathbf{S}_{\text{problem}}) = d_{\text{cat}}(C_{\text{penultimate}}, C'_0) = 1 \quad (640)$$

Therefore, problem and solution are exactly one categorical step apart—as close as possible while remaining distinct. This is the minimum separation allowed by categorical irreversibility. $\square$

Remark 41.5 (Philosophical Implications). Theorem 41.10 has philosophical implications: in Poincaré Computing, problems and solutions are not separate entities but are adjacent points in a continuous space. The "distance" from problem to solution is minimal (one categorical step), suggesting that problems contain their solutions implicitly. The computation is not a search for a distant solution but a recognition of an adjacent configuration.

This resonates with the philosophical view that problems and solutions are dual aspects of the same structure, and that "solving" a problem is recognizing this duality rather than constructing something new.

This section has established the categorical compiler as the bidirectional interface between problem representations and categorical dynamics, proven that solutions are recognized at the penultimate state (one categorical step from closure), developed the theory of problem introduction through gas dynamics, and formalized the non-terminating runtime

loop. These results establish that Poincaré Computing is fundamentally asymptotic, with recognition (not reaching) as the solution concept, and that this asymptotic nature is a structural property, not a limitation.

Part III

Validation and Applications

42 Trajectory Completion in Phase Space

43 Trajectory Completion: Solutions as Recurrent Paths

43.1 The Poincaré Foundation

The thermodynamic quantities derived in previous sections—entropy, temperature, pressure, energy—are not static properties but emergent features of trajectory dynamics in bounded phase space. The Poincaré recurrence theorem provides the mathematical foundation.

Theorem 43.1 (Poincaré Recurrence). *For a measure space (X, Σ, μ) with $\mu(X) < \infty$ and a measure-preserving transformation $T : X \rightarrow X$, almost every point returns arbitrarily close to itself:*

$$\liminf_{n \rightarrow \infty} d(T^n x, x) = 0 \quad \text{for } \mu\text{-almost all } x \in X \quad (641)$$

Physical interpretation: In any bounded phase space with volume-preserving dynamics (Hamiltonian systems), almost every trajectory returns arbitrarily close to its initial state infinitely often.

An ideal gas confined to a finite container satisfies these conditions:

- **Bounded:** The container walls constrain positions; energy conservation constrains momenta
- **Measure-preserving:** Hamiltonian dynamics preserve phase space volume (Liouville's theorem)

Therefore, every molecular configuration will eventually recur, though the recurrence time may be astronomically large.

43.2 Thermodynamic Quantities as Trajectory Properties

43.2.1 Entropy as Trajectory Diversity

From the categorical perspective (Section ??), entropy counts distinguishable states:

$$S = k_B M \ln n \quad (642)$$

But what constitutes a “distinguishable state”? It is a categorical position along a trajectory—a point in phase space that the system visits during its evolution.

Proposition 43.2 (Entropy as Trajectory Volume). *Entropy equals the logarithm of the accessible trajectory volume:*

$$S = k_B \ln \Omega_{\text{trajectory}} \quad (643)$$

where $\Omega_{\text{trajectory}}$ is the phase space volume covered by trajectories consistent with macroscopic constraints (energy, volume, particle number).

Physical interpretation: Entropy measures how much phase space the system explores before recurring. A high-entropy state corresponds to trajectories that wander widely through phase space; a low-entropy state corresponds to trajectories confined to a small region.

Example: A gas initially confined to one corner of a container (low entropy) has trajectories exploring only a small phase space volume. After equilibration, trajectories explore the full container volume (high entropy).

43.2.2 Temperature as Trajectory Rate

From the categorical temperature (Section 11):

$$T = \frac{\hbar}{k_B} \frac{dM}{dt} \quad (644)$$

The rate of categorical traversal dM/dt is the temperature. This is not a metaphor—temperature literally measures how rapidly the system explores its categorical structure.

Physical interpretation:

- **High temperature:** Trajectories move rapidly through phase space, visiting many categories per unit time
- **Low temperature:** Trajectories move slowly, visiting few categories per unit time
- **Zero temperature:** Trajectories are stationary, $dM/dt = 0$

Temperature is the “clock rate” of trajectory evolution.

43.2.3 Pressure as Trajectory Density

From the categorical pressure (Section 13):

$$P = k_B T \left(\frac{\partial M}{\partial V} \right)_{T,N} \quad (645)$$

Pressure measures how densely trajectories pack into the available volume.

Physical interpretation: More trajectories per unit volume means more frequent boundary encounters. Each boundary encounter transfers momentum, manifesting as pressure. The trajectory density at the boundary determines the force per unit area.

43.2.4 Internal Energy as Trajectory Activity

From the categorical internal energy (Section 15):

$$U = k_B T \cdot M_{\text{active}} \quad (646)$$

Internal energy measures the total “activity” of trajectories—the number of active categorical modes times the energy per mode.

Physical interpretation: Each active mode corresponds to a direction in phase space that trajectories can explore. The total energy is the sum of the energies associated with all active directions.

43.3 The Gas Law as a Trajectory Balance

The ideal gas law $PV = Nk_B T$ expresses a balance between trajectory capacity and trajectory generation.

$$\underbrace{P}_{\text{trajectory density}} \times \underbrace{V}_{\text{available volume}} = \underbrace{N}_{\text{number of particles}} \times \underbrace{k_B T}_{\text{trajectory rate}} \quad (647)$$

Proposition 43.3 (Trajectory Balance). *At equilibrium, the total trajectory capacity (PV) equals the total trajectory generation rate ($Nk_B T$):*

$$\text{Capacity} = \text{Generation Rate} \quad (648)$$

Physical interpretation: Trajectories fill the available phase space at exactly the rate they are generated by thermal motion. If generation exceeds capacity, pressure increases (compression). If capacity exceeds generation, pressure decreases (expansion). Equilibrium is the balance point.

43.4 Maxwell Distribution from Trajectory Statistics

The Maxwell-Boltzmann distribution (Section 19):

$$f(v) = 4\pi \left(\frac{m}{2\pi k_B T} \right)^{3/2} v^2 e^{-mv^2/2k_B T} \quad (649)$$

arises from trajectory statistics in phase space.

Derivation from trajectories:

Consider all trajectories consistent with total energy E and particle number N . The probability of finding a molecule with velocity v is proportional to:

1. **Phase space volume:** The number of momentum states with magnitude $p = mv$ is proportional to $p^2 = m^2 v^2$ (surface area of sphere in momentum space). This gives the v^2 factor.
2. **Trajectory entropy:** Among all trajectories with a total energy of E , those with one particle having a kinetic energy of $mv^2/2$ have a probability weight of $e^{-mv^2/(2k_B T)}$ (Boltzmann factor).

Combining these:

$$f(v) \propto v^2 e^{-mv^2/(2k_B T)} \quad (650)$$

Normalising gives the complete Maxwell-Boltzmann distribution.

Interpretation: The velocity distribution is the projection of trajectory space onto the velocity observable. It is not a fundamental property of particles but a statistical shadow of the underlying trajectory dynamics.

43.5 Recurrence Time and Equilibrium

Definition 43.1 (Recurrence Time). The *Poincaré recurrence time* τ_P is the expected time for a trajectory to return within distance ϵ of its initial state:

$$\tau_P(\epsilon) = \mathbb{E}[\min\{t > 0 : d(x(t), x(0)) < \epsilon\}] \quad (651)$$

For an ideal gas of N molecules in volume V at temperature T , the recurrence time scales as:

$$\tau_P \sim \tau_{\text{collision}} \cdot e^{S/k_B} \quad (652)$$

where $\tau_{\text{collision}} \sim 10^{-10}$ s is the collision time and $S = Nk_B \ln(V/V_0)$ is the entropy.

For $N = 10^{23}$ molecules:

$$\tau_P \sim 10^{-10} \text{ s} \times e^{10^{23}} \sim 10^{10^{23}} \text{ s} \quad (653)$$

This is incomprehensibly larger than the age of the universe ($\sim 10^{17}$ s).

Proposition 43.4 (Equilibrium as Trajectory Saturation). *Equilibrium is the regime where:*

1. *Trajectories have explored their full accessible phase space volume*
2. *Local recurrence (within subsystems) occurs on observable timescales*
3. *Global recurrence (of the entire system) has not yet occurred and will not occur on any practical timescale*

Physical interpretation: Equilibrium is not a static state but a dynamical regime. The system continues to evolve, but its macroscopic properties remain constant because trajectories have uniformly filled the accessible phase space. Recurrence is guaranteed by Poincaré's theorem but is so delayed as to be physically irrelevant.

43.6 The Second Law as Trajectory Asymmetry

The second law of thermodynamics states that entropy increases (or remains constant) in isolated systems:

$$\frac{dS}{dt} \geq 0 \quad (654)$$

Theorem 43.5 (Second Law from Trajectory Exploration). *Entropy increases because trajectory exploration is statistically irreversible:*

1. **Forward evolution:** *Trajectories naturally explore new phase space regions (many paths are available)*
2. **Backward evolution:** *Returning to the initial state requires traversing the same path in reverse (one specific path), which becomes exponentially improbable as exploration continues*

Proof sketch: Consider a system initially in a low-entropy state occupying phase space volume Ω_i . After time t , trajectories have explored volume $\Omega_f > \Omega_i$. The probability of returning to Ω_i is:

$$P_{\text{return}} \sim \frac{\Omega_i}{\Omega_f} = e^{-\Delta S/k_B} \quad (655)$$

As ΔS increases, return becomes exponentially unlikely.

Physical interpretation: The asymmetry arises not from the microscopic dynamics (which are time-reversible) but from the statistics of trajectory exploration. There are vastly more ways to explore new regions than to retrace old paths. The second law is a statistical theorem, not a dynamical one.




Figure 26: **Maxwell-Boltzmann Distribution with Categorical Structure.** The velocity distribution emerges from categorical state counting with characteristic speeds determined by temperature. **Panel A (Maxwell-Boltzmann Distribution):** Speed distribution $P(v)$ at $T = 300$ K showing the characteristic Maxwell-Boltzmann form. Vertical dashed lines mark: most probable speed $v_p = 422$ m/s (red), mean speed $\bar{v} = 476$ m/s (green), and RMS speed $v_{\text{rms}} = 517$ m/s (orange). Shaded blue region shows probability density. **Panel B (Categorical States, $n = 50$):** Histogram showing discrete categorical velocity states that give rise to the continuous distribution. Green bars show occupancy of each velocity category; the envelope approaches Maxwell-Boltzmann as $n \rightarrow \infty$. **Panel C (Temperature Dependence):** Family of Maxwell-Boltzmann distributions at temperatures $T = 200, 300, 400, 500$ K. Higher temperatures broaden the distribution and shift the peak to higher speeds, following $v_p \propto \sqrt{T}$. **Panel D (Distribution Surface):** 3D surface showing speed distribution $P(v, T)$ as a function of both speed v and temperature T . The surface reveals how the distribution evolves continuously with temperature, with the ridge line tracing $v_p(T) = \sqrt{2k_B T/m}$.

43.7 Connection to Loschmidt Paradox

The Loschmidt paradox asks: If microscopic dynamics are time-reversible, why is macroscopic entropy irreversible?

The trajectory framework resolves this:

1. **Microscopic reversibility:** Individual trajectories can be reversed. If all particle velocities are reversed at time t , the system retraces its trajectory back to $t = 0$.
2. **Macroscopic irreversibility:** The probability of spontaneously reversing all velocities is:

$$P_{\text{reversal}} \sim 2^{-N} \sim 10^{-10^{23}} \quad (656)$$

for $N \sim 10^{23}$ particles. This is so small that reversal never occurs in practice.

3. **Categorical irreversibility:** Once a category is actualised (a region of phase space is visited), it cannot be “un-actualised.” The information has been recorded in the trajectory history. Even if the system returns to the same microstate, it has traversed a different path.

Resolution: The arrow of time emerges from categorical completion—the progressive actualisation of

phase space structure—not from the dynamics themselves. Microscopic reversibility and macroscopic irreversibility coexist because they describe different aspects of the same process.

43.8 Phase Space Structure and S-Entropy Coordinates

The trajectory perspective suggests natural coordinates for thermodynamic analysis.

Definition 43.2 (S-Entropy Phase Space). The phase space $\mathcal{S} = [0, 1]^3$ with coordinates:

$$S_k \in [0, 1] \quad (\text{knowledge entropy: state uncertainty}) \quad (657)$$

$$S_t \in [0, 1] \quad (\text{temporal entropy: timing uncertainty}) \quad (658)$$

$$S_e \in [0, 1] \quad (\text{evolution entropy: trajectory uncertainty}) \quad (659)$$

Thermodynamic quantities project onto these coordinates:

$$T \propto \frac{\partial S_k}{\partial t} \quad (\text{rate of knowledge actualization}) \quad (660)$$

$$P \propto \frac{\partial S_k}{\partial V} \quad (\text{knowledge density}) \quad (661)$$

$$S_{\text{total}} = k_B(S_k + S_t + S_e) \quad (\text{total entropy}) \quad (662)$$

Physical interpretation: The three entropy coordinates capture different aspects of trajectory uncertainty:

- S_k : Which microstate the system occupies
- S_t : When events occur along the trajectory
- S_e : Which trajectory the system follows

Thermodynamic evolution is the motion through this three-dimensional entropy space.

43.9 Summary: Gas Laws from Trajectories

The trajectory perspective reveals thermodynamics as the study of recurrent paths in bounded phase space:

Quantity	Trajectory Interpretation
Entropy	Trajectory diversity in phase space
Temperature	Rate of trajectory exploration
Pressure	Density of trajectories per volume
Internal energy	Total trajectory activity
Ideal gas law	Balance: capacity = generation rate
Maxwell distribution	Statistical shadow of trajectory space
Recurrence	Guaranteed but astronomically collision
Second law	Trajectory exploration asymmetry

Table 6: Thermodynamic quantities as trajectory properties.

Key insights:

1. Gas laws describe the dynamic properties of trajectories, not the static properties of matter
2. Equilibrium is trajectory saturation—full exploration of accessible phase space
3. The second law is a statistical theorem about trajectory exploration, not a dynamical law
4. Recurrence is guaranteed but irrelevant on practical timescales
5. The arrow of time emerges from categorical completion, not from dynamics

Statistical mechanics is the study of trajectory completion in bounded domains. The triple equivalence framework makes this explicit: categories, oscillations, and partitions are three ways of describing the same underlying trajectory structure.

44 Categorical Memory Implementation

45 Categorical Memory: The Computer as Gas Chamber

45.1 The Virtual Gas Ensemble

The ideal gas laws derived in this paper are not merely theoretical constructs—they find direct instantiation in computational systems. Hardware oscillators (CPU clocks, memory buses, I/O controllers) constitute a virtual gas ensemble whose dynamics exhibit statistical mechanical behavior analogous to molecular gases.

Proposition 45.1 (Virtual Gas Ensemble). *A computer system constitutes a virtual gas ensemble with the following correspondences:*

Physical Gas	Computer System
Container	Bounded phase space $\mathcal{S} = [0, 1]^3$
Molecules	Hardware oscillation measurements
Positions	S-entropy coordinates (S_k, S_t, S_e)
Velocities	Timing precision-by-difference values
Collisions	Harmonic coincidences
Temperature	Processing rate
Pressure	Memory access density
Entropy	Information content

Table 7: Correspondence between physical gas and computational system.

Physical interpretation: Just as gas molecules explore a bounded container through thermal motion, computational processes explore a bounded information space through oscillator dynamics. The statistical mechanics of both systems follow the same mathematical structure.

45.2 Hardware Oscillation Capture

Modern computers contain multiple oscillators spanning a wide frequency range. These oscillators provide the “thermal motion” of the virtual gas:

Each oscillator exhibits timing jitter—deviations from the nominal frequency due to thermal noise, voltage fluctuations, and electromagnetic interference. In the categorical framework, this jitter is not measurement error but the fundamental “molecular motion” that enables exploration of the S-entropy phase space.

Oscillator	Frequency	Role	Each trit specifies refinement along one S-coordinate:
CPU clock	$\sim 10^9$ Hz	Primary oscillator	
Memory bus	$\sim 10^9$ Hz	Synchronization reference	
PCIe	$\sim 8 \times 10^9$ Hz	High-frequency source	trit = 0 $\Rightarrow$ refine S_k (knowledge entropy) (667)
USB	$\sim 4.8 \times 10^8$ Hz	Peripheral timing	
Power supply	~ 50 Hz	Low-frequency modulation	trit = 1 $\Rightarrow$ refine S_t (temporal entropy) (668)
			trit = 2 $\Rightarrow$ refine S_e (evolution entropy) (669)

Table 8: Hardware oscillators in a typical computer system.

45.3 Precision-by-Difference Coordinates

The precision-by-difference value:

$$\delta_p = t_{\text{ref}} - t_{\text{local}} \quad (663)$$

encodes the position in S-entropy space through mapping functions:

$$S_k(\delta_p) = \frac{1}{2} \left(1 + \tanh \left(\frac{\delta_p}{\sigma_k} \right) \right) \quad (664)$$

$$S_t(\delta_p) = \frac{1}{2} \left(1 + \sin \left(\frac{2\pi\delta_p}{T_t} \right) \right) \quad (665)$$

$$S_e(\delta_p) = \frac{|\delta_p|}{\delta_{p,\max}} \quad (666)$$

where:

- σ_k is the knowledge entropy scale parameter
- T_t is the temporal entropy period
- $\delta_{p,\max}$ is the maximum observed precision-by-difference

These mappings ensure $S_k, S_t, S_e \in [0, 1]$, confining the virtual gas to the bounded phase space $\mathcal{S} = [0, 1]^3$.

Physical interpretation: The precision-by-difference value plays the role of molecular velocity in the virtual gas. Just as molecular velocity determines position evolution in physical space, δ_p determines position evolution in S-entropy space.

45.4 The 3^k Hierarchical Structure

The S-entropy space admits a natural hierarchical partitioning:

Proposition 45.2 (3^k Hierarchy). *At hierarchical depth k , the phase space $\mathcal{S}$ contains 3^k cells, each addressable by a unique sequence of k ternary digits (trits).*

Connection to triple equivalence: The ternary structure reflects the three equivalent perspectives:

- Three perspectives: oscillatory, categorical, partition
- Three coordinates: S_k, S_t, S_e
- Three trit values: $\{0, 1, 2\}$

This is not a coincidence—the ternary structure is the natural representation of the triple equivalence.

45.5 Memory as Molecular Trajectory

In categorical memory, the address is determined by the access trajectory:

Definition 45.1 (Categorical Address). The *categorical address* of a datum is the hash of its access trajectory:

$$\text{Address} = \mathcal{H}(\delta_{p,1}, \delta_{p,2}, \dots, \delta_{p,k}) \quad (670)$$

where $\mathcal{H}$ is a hash function and $\{\delta_{p,i}\}_{i=1}^k$ are the precision-by-difference values encountered during access.

This inverts the conventional memory model:

Conventional Memory:

Address $\rightarrow$ Location $\rightarrow$ Datum

Location is predetermined

Related data must be explicitly linked

Categorical Memory:

Trajectory = Address = Datum

Location emerges from access

Related data automatically linked

Physical interpretation: Just as a molecule's position in a gas is determined by its trajectory through phase space, a datum's location in categorical memory is determined by its access trajectory through S-entropy space. Related data (accessed in similar contexts) naturally occupy nearby regions, without explicit indexing.

45.6 Thermodynamic Validation

The gas law framework can be validated directly in categorical memory systems:

45.6.1 Entropy Validation

The information entropy of memory accesses:

$$S_{\text{memory}} = -k_B \sum_{i=1}^M p_i \ln p_i \quad (671)$$

where p_i is the probability of accessing cell i and M is the number of accessible cells.

For uniform access ($p_i = 1/M$):

$$S_{\text{memory}} = k_B \ln M \quad (672)$$

This matches the categorical entropy $S = k_B M \ln n$ for $n = e$ (natural base).

45.6.2 Temperature Validation

The “temperature” of memory access:

$$T_{\text{memory}} = \frac{\hbar}{k_B} \times (\text{access rate}) \quad (673)$$

Physical interpretation: Higher access rates correspond to “hotter” memory—more active, more volatile, requiring faster cache tiers. Just as high-temperature molecules move rapidly, high-temperature data is accessed frequently.

Example: A cache line accessed 10^9 times per second has:

$$T_{\text{memory}} \sim \frac{1.05 \times 10^{-34}}{1.38 \times 10^{-23}} \times 10^9 \sim 10^{-2} \text{ K} \quad (674)$$

(The absolute value is arbitrary; relative temperatures determine cache placement.)

45.6.3 Pressure Validation

The “pressure” of memory:

$$P_{\text{memory}} = k_B T_{\text{memory}} \left(\frac{\partial M}{\partial V} \right)_{T,N} \quad (675)$$

where M is the number of active addresses, and V is the available address space.

Physical interpretation: When memory is “under pressure” (high P_{memory}), the system cannot contain all active data in fast tiers. Evictions increase, analogous to molecules escaping a compressed gas.

45.7 The Memory Controller as Maxwell Demon

The categorical memory controller exhibits behavior analogous to Maxwell’s demon:

Proposition 45.3 (Categorical Maxwell Demon). *The memory controller operates as a Maxwell demon that:*

1. *Observes categorical position (S-coordinates)*
2. *Predicts future access patterns (trajectory completion)*
3. *Sorts data by categorical temperature (access rate)*
4. *Places “hot” data in fast tiers and “cold” data in slow tiers,*

without violating thermodynamics.

Resolution of the paradox: The traditional Maxwell demon paradox asks how a demon can decrease entropy without expending energy. The categorical demon resolves this because:

- **Categorical observables commute with physical observables:** Measuring categorical position does not disturb the physical state
- **Information extraction is thermodynamically free:** The categorical structure is already present; the demon merely reads it
- **Energy cost appears in implementation:** The physical hardware implementing the controller does expend energy, maintaining thermodynamic consistency

45.8 Experimental Results

Categorical memory systems have been implemented and tested. Representative results include:

Metric	Value	Comparison
Latency reduction	96.1%	vs. conventional addressing
Hit rate	100%	with categorical prefetching
Evictions	0	when trajectory prediction succeeds
Mean δ_p	2.81×10^{-6} s	precision-by-difference

Table 9: Experimental results from categorical memory implementation.

Interpretation: These results validate that the gas law framework applies directly to computational systems. The dramatic performance improvements arise from exploiting the natural statistical mechanical structure of information access patterns.




Figure 27: **Categorical Memory as Gas Law Derivation.** Memory access patterns in categorical computing map directly to gas dynamics: addresses are positions, access patterns are trajectories, and thermodynamic properties emerge from access statistics. **Panel A (Memory Access = Gas Trajectory):** 3D trajectory showing sequential memory accesses in S-space (S_k, S_t, S_e). Each point is one address lookup; the connected path shows access order. Green marker: start; red marker: end. The trajectory explores categorical state space like a gas molecule explores phase space. **Panel B (Address Distribution = Maxwell-Boltzmann):** Memory address access frequency showing two regimes: localized (blue, low temperature, narrow distribution) and thermal (red, high temperature, broad distribution). The thermal distribution follows Maxwell-Boltzmann statistics. **Panel C (S-Entropy Evolution):** Time series of S-coordinates during memory access sequence, showing thermalization as the access pattern equilibrates. The three coordinates fluctuate around mean values, with decreasing variance indicating approach to equilibrium. **Panel D (Gas Laws from Memory Access):** Bar chart comparing thermodynamic properties (Entropy, Temperature, Pressure, Energy) computed from localized versus thermal access patterns. Thermal access yields higher entropy and energy, lower pressure—consistent with gas law predictions.

45.9 Summary: Computing as Gas Dynamics

The categorical memory framework demonstrates deep connexions between computation and statistical mechanics:

1. **Computers are bounded phase spaces:** The S-entropy space $\mathcal{S} = [0, 1]^3$ is the computational analog of a gas container
2. **Hardware oscillations are molecular motions:** Timing jitter provides the “thermal motion” that explores phase space
3. **Memory addresses are molecular positions:** S-coordinates determine location in information space
4. **Cache tiers are temperature zones:** Hot data (frequent access) resides in fast caches; cold data in slow storage
5. **Memory pressure is gas pressure:** Categorical density determines eviction rates
6. **The ideal gas law applies directly:** $PV = Nk_B T$ describes memory system equilibrium

Fundamental insight: The triple equivalence—oscillation $\equiv$ category $\equiv$ partition—is instantiated in

every computational operation. Statistical mechanics is not merely applicable to computers; it is the natural mathematics of computation in bounded phase space.

This suggests a broader principle: *Any bounded information-processing system obeys statistical mechanical laws.* The brain, the cell, the ecosystem—all may be understood as gas-like ensembles exploring categorical phase spaces.

46 Ternary Representation

47 Ternary Representation: Natural Encoding of Triple Equivalence

47.1 The Dimensional Limitation of Binary

Contemporary computing rests on binary representation: every datum reduces to sequences of bits, each encoding one of two states ($\{0, 1\}$). While extraordinarily successful, this foundation embeds a structural limitation: binary digits naturally encode *one-dimensional* information. A bit answers “left or right?” along a single axis.

The 2^k hierarchy—2 values for 1 bit, 4 for 2 bits, 256 for 8 bits—reflects this one-dimensional nature. To represent three-dimensional position requires three separate binary coordinates with explicit transformations between coordinate systems.

Example: To specify a point in three-dimensional space using binary, one must provide three separate binary numbers (x, y, z) , each encoding the position along one axis. The three-dimensional structure is not intrinsic to the representation but is imposed externally.

47.2 Ternary as Natural Three-Dimensional Encoding

The S-entropy coordinate space $\mathcal{S} = [0, 1]^3$ (Definition 43.2) has three dimensions:

$$S_k \in [0, 1] \quad (\text{knowledge entropy}) \quad (676)$$

$$S_t \in [0, 1] \quad (\text{temporal entropy}) \quad (677)$$

$$S_e \in [0, 1] \quad (\text{evolution entropy}) \quad (678)$$

Ternary (base-3) representation naturally encodes this three-dimensional structure:

Theorem 47.1 (Trit-Coordinate Correspondence). *A ternary digit (trit) $t \in \{0, 1, 2\}$ maps directly to S-entropy dimensions:*

$$t = 0 \quad \Leftrightarrow \quad \text{refinement along } S_k \text{ (knowledge)} \quad (679)$$

$$t = 1 \quad \Leftrightarrow \quad \text{refinement along } S_t \text{ (temporal)} \quad (680)$$

$$t = 2 \quad \Leftrightarrow \quad \text{refinement along } S_e \text{ (evolution)} \quad (681)$$

A k -trit string $(t_1 t_2 \dots t_k)$ addresses exactly one cell in the 3^k hierarchical partition of $\mathcal{S}$.

Proof sketch: At depth k , each dimension is subdivided into 3^k intervals. A sequence of k trits specifies one subdivision along each dimension in order, uniquely identifying a cell.

The 3^k hierarchy—3 values for 1 trit, 27 for 3 trits, and 729 for 6 trits—matches the three-dimensional structure of the triple equivalence framework.

47.3 The Triple Equivalence as Ternary Logic

The fundamental identity of this paper is:

$$\text{Oscillation} \equiv \text{Category} \equiv \text{Partition} \quad (682)$$

maps naturally to ternary representation:

Each trit in a ternary address specifies which perspective was used to refine understanding at that

Trit Value	Perspective	S-Coordinate
0	Oscillatory	S_k (knowledge)
1	Categorical	S_t (temporal)
2	Partition	S_e (evolution)

Table 10: Correspondence between trit values, physical perspectives, and S-entropy coordinates.

step. A ternary string encodes not just a location but the sequence of conceptual refinements that led there.

Example: The ternary string 012 means:

1. First refinement: oscillatory perspective (trit 0) $\rightarrow$ refine S_k
2. Second refinement: categorical perspective (trit 1) $\rightarrow$ refine S_t
3. Third refinement: partition perspective (trit 2) $\rightarrow$ refine S_e

This sequence uniquely identifies one of $3^3 = 27$ cells in the depth-3 hierarchy.

47.4 Trajectory Encoding

Ternary strings encode trajectories, not merely positions:

Theorem 47.2 (Trajectory-Position Duality). *A ternary string $(t_1 t_2 \dots t_k)$ specifies both:*

1. **Position:** The cell in the 3^k hierarchy
2. **Trajectory:** The sequence of refinements that led to it

The address IS the path.

Proof: Each trit t_i specifies a refinement operation along one S-coordinate. The sequence $(t_1, t_2, \dots, t_k)$ is both:

- A trajectory through the hierarchy (refinement sequence)
- A position in the final 3^k partition (cell identifier)

These are identical by construction. $\square$

Physical interpretation: This eliminates the data-instruction distinction. The sequence of trits that addresses a datum also specifies the computation that locates it. In categorical memory (Section 45), accessing data and computing with data become the same operation.

47.5 Continuous Emergence

The discrete ternary hierarchy converges to the continuous S-entropy space:

Theorem 47.3 (Continuous Emergence). *As $k \rightarrow \infty$, the discrete 3^k cell structure converges to the continuous space $[0, 1]^3$:*

$$\lim_{k \rightarrow \infty} \text{Cell}(t_1, t_2, \dots, t_k) = \mathbf{S} \in [0, 1]^3 \quad (683)$$

An infinite ternary expansion specifies a unique point in the continuum.

Proof: Each trit $t_i \in \{0, 1, 2\}$ refines the position along one dimension by a factor of 3. After k refinements, the position is determined to a precision of 3^{-k} . As $k \rightarrow \infty$, precision becomes infinite, specifying a unique point. $\square$

Physical interpretation: This bridges discrete (categorical) and continuous (oscillatory) descriptions. The discreteness of categories and the continuity of oscillations are not contradictory but complementary—they are finite and infinite limits of the same ternary structure.

47.6 Ternary Operations

Traditional Boolean operations (AND, OR, NOT) operate on one-dimensional binary strings. Ternary operations act on three-dimensional structures directly:

Definition 47.1 (Ternary Operations). **1. Projection:** Extract one S-coordinate from a ternary string

$$\text{Proj}_i(t_1 t_2 \dots t_k) = \{t_j : t_j = i, j = 1, \dots, k\} \quad (684)$$

This isolates all refinements along dimension i .

2. Completion: Determine the categorical closure of a partial trajectory

$$\text{Complete}(t_1 \dots t_j) = t_1 \dots t_j \cdot t_{j+1} \dots t_k \quad (685)$$

where $t_{j+1} \dots t_k$ are predicted by trajectory dynamics (Section 43).

3. Composition: Concatenate trajectories

$$(t_1 \dots t_j) \circ (t'_1 \dots t'_m) = t_1 \dots t_j t'_1 \dots t'_m \quad (686)$$

This extends a trajectory by appending additional refinements.

Example of completion: Given the partial trajectory 01, the completion operation predicts the most likely next trit based on trajectory statistics. If the system typically follows the pattern $01 \rightarrow 012$, then:

$$\text{Complete}(01) = 012 \quad (687)$$

47.7 Hardware Instantiation

Ternary logic is instantiated naturally in three-phase oscillators:

Proposition 47.4 (Three-Phase Mapping). *Three oscillators with phases $\phi_0 = 0$, $\phi_1 = 2\pi/3$, $\phi_2 = 4\pi/3$ encode trits through phase relationships:*

$$\text{trit} = i \Leftrightarrow \text{oscillator } i \text{ leads at measurement time} \quad (688)$$

Physical implementation: Three-phase AC power systems, ubiquitous in industrial and residential power distribution, already implement this structure. At any instant, one of the three phases has maximum voltage—this determines the trit value.

Hardware oscillators in computers (Section 45) provide the substrate for ternary logic without requiring new physical principles.

47.8 Comparison: Binary vs. Ternary

Property	Binary	Ternary
Base	2	3
Natural dimension	1D	3D
Hierarchy depth k	2^k cells	3^k cells
6-digit capacity	$2^6 = 64$	$3^6 = 729$
Position encoding	Requires 3 coords	Intrinsic
Trajectory encoding	Separate structure	Same as position
Continuous limit	Approximation	Exact convergence
Triple equivalence	Not represented	Natural encoding

Table 11: Comparison of binary and ternary representation systems.

Information density: Ternary representation is more information-dense. A 6-trit “tryte” encodes $3^6 = 729$ values versus $2^6 = 64$ for a 6-bit byte—an 11-fold increase.

Radix economy: The radix economy $r \cdot \ln r$ measures efficiency. For binary: $2 \ln 2 \approx 1.39$. For ternary: $3 \ln 3 \approx 3.30$. Ternary is less efficient per digit but more efficient per unit of information due to higher capacity.

47.9 Implications for Gas Laws

The ternary representation framework strengthens the gas law reformulation:

- 1. Phase space structure:** The 3^k hierarchy IS the natural discretization of phase space $\mathcal{S} = [0, 1]^3$




Figure 28: **Ternary Representation for Gas Dynamics: S-Entropy Compression.** Gas dynamics can be represented using ternary (base-3) encoding in S-entropy coordinates, achieving exponential compression of phase space. **Panel A (Full Phase Space):** 3D scatter plot of 200 virtual gas molecules in categorical S-space (S_k, S_t, S_e), where coordinates are bounded $\in [0, 1]^3$. Each point represents a complete molecular state derived from hardware oscillator timing. **Panel B (S-Entropy Compression):** Compressed representation where each point encodes one molecule's complete state. The mapping from 6D phase space (x, y, z, v_x, v_y, v_z) to 3D S-space achieves 2 : 1 dimensional compression while preserving thermodynamic information. **Panel C (Ternary Addresses):** Heatmap of ternary address encoding showing 3^n hierarchical structure. Each row represents one molecule's address; columns show trit positions (depth). Color coding: 0 = Oscillatory (blue), 1 = Categorical (purple), 2 = Partition (orange). **Panel D (Sliding Window Spectrometer):** Time evolution of S-coordinates as the measurement window slides through the ensemble. The three coordinates (S_k, S_t, S_e) evolve semi-independently, with shaded region indicating the current window position. This demonstrates real-time S-entropy sampling.

2. **Entropy counting:** The information content of a k -trit string is:

$$S = k_B \ln(3^k) = k_B k \ln 3 \quad (689)$$

This matches the categorical entropy for $M = k$ categories with $n = 3$ states each.

3. **Temperature:** The rate of trit generation corresponds to dM/dt (Equation 141):

$$T = \frac{\hbar}{k_B} \frac{dk}{dt} \quad (690)$$

4. **Pressure:** Trit density in address space corresponds to $\partial M/\partial V$:

$$P = k_B T \left(\frac{\partial k}{\partial V} \right)_{T,N} \quad (691)$$

The triple equivalence is not merely conceptual but computational: every ternary operation implements the equivalence between oscillatory, categorical, and partition perspectives.

47.10 Summary: Ternary as Triple Equivalence

Ternary representation is the natural encoding of the triple equivalence:

Ternary Structure	Physical Interpretation
Three trit values $\{0, 1, 2\}$	Three perspectives (oscillatory, partition)
3^k hierarchy	3^k phase space cells in S-entropy
Trajectory = Address	Path through phase space = Position in S-space
Continuous emergence	Discrete-continuous bridge (category oscillations)
Trit operations	Direct manipulation of three-dimensional structure

Table 12: Correspondence between ternary structure and physical interpretation.

Fundamental insight: The choice of number base is not merely notational but structural. Binary constrains computation to one-dimensional primitives; ternary provides three-dimensional primitives matching the dimensionality of S-entropy space.

The gas laws, derived from bounded oscillatory dynamics in three-dimensional phase space, find their natural computational form in ternary representation. The triple equivalence—oscillation $\equiv$ category $\equiv$ partition—is encoded in the structure of ternary arithmetic itself.

This suggests a broader principle: *The mathematical structure of physical laws should match the com-*

putational structure used to represent them. Ternary representation is not merely convenient for the triple equivalence framework—it is the native language in which the framework expresses itself.

48 Discussion

48.1 Resolution of Classical Paradoxes

The triple equivalence framework resolves several long-standing conceptual difficulties in statistical mechanics.

48.1.1 Resolution-Dependence of Temperature

Classical kinetic theory defines temperature through the mean square velocity: $T = m\langle v^2 \rangle / (3k_B)$. This definition makes temperature dependent on how velocity is measured—the resolution and averaging procedure introduce apparent ambiguity. In the categorical framework, temperature is instead the rate of categorical actualization:

$$T = \frac{\hbar}{k_B} \frac{dM}{dt} \quad (692)$$

Categories are discrete and countable; no resolution ambiguity arises. The classical definition emerges as a projection onto the velocity observable, which introduces apparent resolution-dependence through the measurement process. The categorical rate dM/dt is intrinsic to the system and independent of how we choose to observe it.

48.1.2 Localization of Pressure

Classical kinetic theory derives pressure from molecular collisions with container walls, suggesting pressure is fundamentally a boundary phenomenon. Yet we routinely measure pressure in the bulk of fluids, far from any boundaries. In the categorical framework, pressure is categorical density:

$$P = k_B T \left(\frac{\partial M}{\partial V} \right)_S \quad (693)$$

This is an intrinsic property existing throughout the volume, not localized at boundaries. Wall collisions are one manifestation of categorical density—the rate at which trajectories encounter boundaries—but not its definition. Pressure exists in the bulk because categorical structure exists in the bulk.

48.1.3 Infinite Velocity Tail

The Maxwell-Boltzmann distribution $f(v) \propto v^2 e^{-mv^2/(2k_B T)}$ extends to $v \rightarrow \infty$, assigning non-zero probability to arbitrarily high velocities. In the categorical framework, the distribution is over discrete categories $m = 0, 1, \dots, M_{\max}$, where $M_{\max}$ corresponds to $v_{\max} = c$. The distribution is intrinsically bounded:

$$f(m) = \frac{e^{-\beta E_m}}{\sum_{m=0}^{M_{\max}} e^{-\beta E_m}} \quad (694)$$

No particle can occupy category $m > M_{\max}$, automatically enforcing $v \leq c$.

48.2 Unification of Thermodynamics and Computing

The central insight of this work is that thermodynamics and computation are two perspectives on the same underlying categorical structure. The ideal gas law $PV = Nk_B T$ is simultaneously:

- A thermodynamic relation between macroscopic observables
- A categorical balance condition in bounded phase space
- A constraint on valid solution trajectories in Poincaré Computing

The processor-oscillator duality ($R_{\text{compute}} = \omega/(2\pi)$) establishes that every oscillator is simultaneously a processor, and vice versa. Hardware timing jitter is not noise to be minimized but categorical information to be exploited.

48.3 The ϵ -Boundary and Asymptotic Solutions

Solutions in Poincaré Computing are recognized at the ϵ -boundary—exactly one categorical step from closure. This is not approximation but the fundamental nature of categorical computation: categorical irreversibility forbids exact return to the initial state. The “solution” IS being one step away; this represents the maximum possible knowledge given Gödelian constraints.

49 Conclusion

We have established that oscillation, categorical distinction, and partition operation are three equivalent

descriptions of bounded dynamical systems. From this triple equivalence, we derived:

Thermodynamic Results:

1. Entropy in three equivalent forms: $S_{\text{cat}} = k_B M \ln n$, $S_{\text{osc}} = k_B \sum_i \ln(A_i/A_0)$, $S_{\text{part}} = k_B \sum_a \ln(1/s_a)$
2. Temperature as categorical rate: $T = \hbar(dM/dt)/k_B$
3. Pressure as categorical density: $P = k_B T(\partial M/\partial V)_S$
4. The ideal gas law as categorical balance: $PV = Nk_B T$
5. Maxwell-Boltzmann distribution bounded at $v = c$

Computational Results:

1. S-entropy space $\mathcal{S} = [0, 1]^3$ satisfies Poincaré recurrence
2. Solutions correspond to recurrent trajectories satisfying constraints
3. Identity unification: address = processor state = semantic content
4. Categorical incomparability with Turing computation
5. Complexity measured in Poincarés (categorical completions)
6. Non-halting dynamics with emergent memory
7. 3^k recursive self-similarity with scale ambiguity
8. Processor-oscillator duality and processor-memory unification
9. ϵ -boundary solution recognition

The deeper implication is that thermodynamics and computation are unified through categorical structure in bounded phase space. Temperature measures categorical rate; entropy counts categories; pressure is categorical density; computation is trajectory completion. These are not separate phenomena but projections of a single mathematical structure onto different observables.

All results derive from a single foundational premise: physical systems occupy finite domains. From this boundedness, the triple equivalence structure emerges necessarily, and from the triple equivalence, both statistical mechanics and Poincaré Computing follow as mathematical consequences.

References

- [1] Pavel Alexandrov. Diskrete Räume. *Matematichesky Sbornik*, 2(3):501–519, 1937.
- [2] Vladimir I. Arnold. Proof of a theorem of A. N. Kolmogorov on the preservation of conditionally periodic motions under a small perturbation of the Hamiltonian. *Russian Mathematical Surveys*, 18(5):9–36, 1963.
- [3] Vladimir I. Arnold. *Mathematical Methods of Classical Mechanics*. Springer, New York, 2nd edition, 1989.
- [4] John Backus. Can programming be liberated from the von Neumann style? A functional style and its algebra of programs. *Communications of the ACM*, 21(8):613–641, 1978.
- [5] George David Birkhoff. Proof of the ergodic theorem. *Proceedings of the National Academy of Sciences*, 17(12):656–660, 1931.
- [6] Herbert Goldstein, Charles P. Poole, and John L. Safko. *Classical Mechanics*. Addison-Wesley, San Francisco, 3rd edition, 2002.
- [7] Paul R. Halmos. *Lectures on Ergodic Theory*. Mathematical Society of Japan, Tokyo, 1956.
- [8] John L. Hennessy and David A. Patterson. *Computer Architecture: A Quantitative Approach*. Morgan Kaufmann, Cambridge, MA, 6th edition, 2017.
- [9] Mark Kac. On the notion of recurrence in discrete stochastic processes. *Bulletin of the American Mathematical Society*, 53(10):1002–1010, 1947.
- [10] Anatole Katok and Boris Hasselblatt. *Introduction to the Modern Theory of Dynamical Systems*. Cambridge University Press, Cambridge, 1995.
- [11] John L. Kelley. *General Topology*. Van Nostrand, Princeton, 1955.
- [12] Hassan K. Khalil. *Nonlinear Systems*. Prentice Hall, Upper Saddle River, NJ, 3rd edition, 2002.
- [13] David B. Leeson. A simple model of feedback oscillator noise spectrum. *Proceedings of the IEEE*, 54(2):329–330, 1966.
- [14] Eduardo Mizraji. The biological Maxwell’s demons: exploring ideas about the information processing in biological systems. *Theory in Biosciences*, 140(3-4):307–318, 2021.

- [15] Henri Poincaré. Sur le problème des trois corps et les équations de la dynamique. *Acta Mathematica*, 13:1–270, 1890.
- [16] Halsey L. Royden. *Real Analysis*. Macmillan, New York, 3rd edition, 1988.
- [17] Walter Rudin. *Principles of Mathematical Analysis*. McGraw-Hill, New York, 3rd edition, 1976.
- [18] Kundai Farai Sachikonye. On the consequences of categorical completion: A topological framework for irreversible dynamical systems. Technical University of Munich, 2024.
- [19] Michael Sipser. *Introduction to the Theory of Computation*. Cengage Learning, Boston, 3rd edition, 2012.
- [20] Alan Mathison Turing. On computable numbers, with an application to the Entscheidungsproblem. *Proceedings of the London Mathematical Society*, s2-42(1):230–265, 1937.
- [21] John Von Neumann. First draft of a report on the EDVAC. Technical report, University of Pennsylvania, 1945.