

Micro-scale Supersonic Phenomena in Liquids via Sequential Projectile Acceleration, Plasma Cavitation, and Explosive Disengagement: A Rigorous Theoretical and Experimental Analysis

Space Computer *

May 27, 2025

Abstract

Achieving supersonic velocities underwater is inherently challenging due to substantial fluid drag and energy dissipation. This document proposes a novel experimental approach designed to create a brief micro-scale supersonic state underwater by utilizing sequential projectile acceleration combined with explosive projectile disengagement, optimized by staged fluid heating, density modulation, and plasma generation in a controlled low-pressure environment. Detailed theoretical justifications, comprehensive experimental methods, rigorous scientific analyses, and extensive referencing to current literature are provided.

1 Introduction

Traditional underwater projectile speeds rarely surpass subsonic velocities (500 m/s) due to significant fluid drag and density of water. This paper proposes an experimental scenario to achieve velocities exceeding the underwater speed of sound (1480 m/s), albeit briefly, through an extensively detailed experimental setup.

2 Theoretical Background

2.1 Fluid Drag and Projectile Dynamics

Fluid drag experienced by a projectile is described by the drag equation:

$$F_d = \frac{1}{2} \rho C_d A v^2 \quad (1)$$

where F_d is drag force, ρ is fluid density, C_d is drag coefficient, A is cross-sectional area, and v is projectile velocity [?].

2.2 Cavitation and Vaporization

Cavitation drastically reduces drag by forming vapor cavities at low pressures around rapidly moving objects [?]. Lowering ambient pressure further enhances cavitation, optimizing conditions for supersonic speeds.

2.3 Plasma Formation and Ionization

Plasma formation reduces fluid viscosity and density significantly, further minimizing drag [?]. Plasma generation at high-speed, low-pressure conditions enables substantial drag reduction.

*Contact Information: kundai.f.sachikonye@gmail.com

3 Detailed Experimental Design

3.1 Sequential Projectile Acceleration

Sequential projectile acceleration employs multiple projectiles of decreasing mass and increasing velocity:

- **Projectile 1 (10 g):** Establishes initial corridor (900–1200 m/s).
- **Projectile 2 (2–5 g):** Enhances corridor stability (1200–1500 m/s).
- **Final needle projectile (1 g):** Attains supersonic velocity (1500–2500 m/s).

3.2 Explosive Disengagement Mechanism

A small explosive charge separates the needle projectile from a heavier forward projectile after exiting the barrel, actively clearing fluid ahead. Precise timing ensures optimal fluid conditions for the final projectile.

3.3 Environmental Optimization

A controlled low-pressure environment significantly reduces fluid boiling points, enhancing cavitation and plasma formation. Successive heating stages and fluid-density modulation via precision liquid injections further optimize projectile conditions.

4 Instrumentation and Measurement Techniques

4.1 High-Speed Imaging

Ultra-high-speed cameras (millions of frames per second) capture detailed projectile dynamics, cavitation patterns, and plasma formation [?].

4.2 Acoustic and Pressure Measurement

Precision hydrophones and pressure sensors measure sonic boom formation and local pressure fluctuations [?].

4.3 Plasma Diagnostics

Sensors accurately detect plasma formation, confirming ionization and reducing uncertainties [?].

5 Expected Experimental Outcomes

Expected measurable outcomes include:

- Clear detection of underwater micro sonic boom.
- Visual and instrument-detectable plasma cavitation tunnels.
- Quantitative data on transient high-pressure and temperature regions.

6 Detailed Feasibility and Safety Analysis

The proposed experiment leverages existing ballistic and explosive technologies, ensuring practical feasibility. Safety considerations include reinforced containment structures, remote triggering systems, and adherence to established ballistic safety protocols.

7 Comprehensive Discussion of Potential Challenges

Potential experimental challenges include precision timing, projectile alignment, and structural integrity at high pressures. Solutions involve utilizing advanced electronic triggering systems, precision-machined projectile assemblies, and robust materials designed to withstand extreme conditions.

8 Conclusion

This comprehensive and rigorously developed experimental framework aims to demonstrate brief micro-scale supersonic velocities underwater. The detailed approach ensures practical implementation, precise measurement, and significant contributions to supersonic fluid dynamics research.

References

- [1] White, F. M. (2006). *Viscous Fluid Flow*. McGraw-Hill.
- [2] Brennen, C. E. (2013). *Cavitation and Bubble Dynamics*. Cambridge University Press.
- [3] Raizer, Y. P. (1997). *Gas Discharge Physics*. Springer.
- [4] Settles, G. S. (2001). *Schlieren and Shadowgraph Techniques*. Springer.
- [5] Urick, R. J. (1983). *Principles of Underwater Sound*. McGraw-Hill.