

Autonomous Vehicle Navigation Through Categorical State Counting in Coupled Oscillator Networks

Kundai Farai Sachikonye
AIME Registry for Artificial Intelligence
Experimental Bioinformatics
Maximus-von-Imhof-Forum 3
85354 Freising, Germany
`kundai.sachikonye@bitspark.com`

March 2026

Abstract

We present a rigorous mathematical framework for autonomous vehicle navigation that replaces forward simulation and trajectory prediction with categorical state counting in coupled oscillator networks. The central result is the *Triple Process Identity*: observation $O(x)$, computing $C(x)$, and processing $P(x)$ are categorically equivalent when realized on physical oscillators occupying bounded phase space. A vehicle’s constituent oscillators — CPU clock ($\sim$ GHz), engine crankshaft ($\sim$ 50 Hz), wheel rotation ($\sim$ 10 Hz), and atmospheric molecular vibrations ($\sim 10^{13}$ Hz) — form a harmonic coincidence network whose phase-locked rational frequency ratios define a counting loop. We prove that this counting loop computes navigation functions with complexity $\mathcal{O}(\log_3 M)$ for state finding, $\mathcal{O}(n^k)$ for sufficiency checking, and $\mathcal{O}(1)$ for recognition, where M is the partition count. Through the Position-Partition Bijection $\Pi : \mathbb{R}^3 \rightarrow [0, 1]^3$, we show that atmospheric S-entropy fields encode absolute position without GPS. The oscillator–processor duality $\omega \equiv R_{\text{compute}}$ and the commutation relation $[\hat{O}_{\text{cat}}, \hat{O}_{\text{phys}}] = 0$ ensure that categorical observation and physical measurement yield identical navigation states. We derive trans-Planckian timing enhancement of $10^{120.95}$ effective resolution through five vehicle-specific mechanisms and prove that other vehicles are detected as perturbations of the local S-entropy field, requiring no predictive model. The framework is grounded in Poincaré recurrence, Boltzmann statistical mechanics, and Kuramoto synchronization theory. We propose an experimental protocol using instrumented vehicles to validate the theory

against conventional GPS-based navigation.

Keywords: autonomous navigation, oscillator networks, categorical state counting, Poincaré recurrence, S-entropy, harmonic coincidence, trajectory completion, coupled oscillators, trans-Planckian timing, sufficiency recognition

1 Introduction

The prevailing paradigm in autonomous driving research treats navigation as a prediction problem: given the current state of the world, forecast future trajectories and select the optimal path [22, 4]. This approach inherits the computational burden of forward simulation—solving differential equations, propagating uncertainty, and evaluating cost functions over exponentially branching futures. We argue that this paradigm rests on a fundamental conceptual error that we term the *prediction fallacy*.

Definition 1.1 (Prediction Fallacy). The prediction fallacy is the assumption that navigation requires a forward model $f : \mathcal{S}_t \rightarrow \mathcal{S}_{t+\Delta t}$ mapping current states to future states. Formally, it is the claim that safe navigation necessitates computing

$$s(t + \Delta t) = f(s(t), u(t), w(t)) \quad (1)$$

where $s(t) \in \mathcal{S}$ is the state, $u(t)$ the control input, and $w(t)$ the environment process, for some horizon $\Delta t > 0$.

Human drivers refute this assumption at every moment. An experienced driver does not solve differential equations or propagate probability distributions

over possible futures. Instead, the driver *recognizes sufficiency*: the current configuration of sensory inputs either suffices for continued safe operation or it does not. This recognition is instantaneous, requiring no simulation.

The present paper—the second in a three-paper series on autonomous driving via trajectory completion computing [18]—formalizes this observation through the theory of categorical state counting in coupled oscillator networks. The key mathematical structure is:

Axiom 1.2 (Triple Process Identity). *For any physical system $\mathcal{P}$ occupying bounded phase space with oscillatory dynamics at frequency ω , the observation operator $O(x)$, the computation operator $C(x)$, and the processing operator $P(x)$ satisfy*

$$O(x) \equiv C(x) \equiv P(x). \quad (2)$$

That is, observation IS computing IS processing. These are not merely correlated or approximately equal; they are categorically identical morphisms in the category of physical processes.

The consequences for autonomous navigation are immediate. If observation is computing, then a vehicle’s physical oscillators—the CPU clock, the engine crankshaft, the wheel rotations, the atmospheric molecular vibrations—are not merely producing data for a separate computational system. They *are* the computational system. Navigation reduces to counting the categorical states that these coupled oscillators traverse.

Definition 1.3 (Oscillator–Processor Duality). For any oscillator with angular frequency ω and any computational process with rate R_{compute} (operations per second), the oscillator–processor duality is the identity

$$\omega \equiv R_{\text{compute}}. \quad (3)$$

Each oscillation cycle constitutes exactly one computational operation: the transition from one categorical state to the next in the bounded phase space.

This duality was established in [17] through the chain: bounded phase space $\Rightarrow$ Poincaré recurrence [12] $\Rightarrow$ oscillation $\Rightarrow$ categorical states $\Rightarrow$ counting $\Rightarrow$ computation. The present paper applies this chain specifically to the vehicle navigation problem.

The paper is organized as follows. Section 2 establishes the vehicle as a multi-scale oscillator network and proves the fundamental counting identity. Section 3 develops the harmonic coincidence network through which rational frequency ratios enable phase-locked navigation. Section 4 shows how the vehicle’s

computer functions as a spectrometer via precision-by-difference. Section 5 constructs the multi-modal observer architecture. Section 6 formalizes sufficiency recognition as the alternative to prediction. Section 7 derives the trans-Planckian timing enhancement. Section 8 proves position determination without GPS via the Position-Partition Bijection. Section 9 treats other vehicles as categorical state perturbations. Section 10 proposes experimental validation. Section 11 concludes.

2 Vehicle as Oscillator Network

2.1 Oscillator Inventory

A modern vehicle contains oscillators spanning over thirteen orders of magnitude in frequency. We catalog the principal oscillators relevant to navigation.

Definition 2.1 (Vehicle Oscillator Inventory). A vehicle oscillator inventory is a set $\mathcal{V} = \{(\omega_i, \Phi_i, \mathcal{H}_i)\}_{i=1}^N$ where ω_i is the angular frequency, Φ_i the bounded phase space, and $\mathcal{H}_i$ the Hilbert space of categorical states for the i -th oscillator. The principal oscillators are:

- (i) **CPU clock**: $\omega_{\text{CPU}} \sim 2\pi \times 3 \times 10^9 \text{ Hz}$, $\Phi_{\text{CPU}} = S^1$ (ring oscillator phase), $\dim \mathcal{H}_{\text{CPU}} = 2^{64}$.
- (ii) **Sensor clocks**: $\omega_{\text{sensor}} \sim 2\pi \times 10^6 \text{ Hz}$ to $2\pi \times 10^9 \text{ Hz}$ (LiDAR, radar, camera pixel clocks).
- (iii) **Engine crankshaft**: $\omega_{\text{engine}} \sim 2\pi \times 50 \text{ Hz}$ at 3000 rpm.
- (iv) **Wheel rotation**: $\omega_{\text{wheel}} \sim 2\pi \times 10 \text{ Hz}$ at 100 km/h with standard tires.
- (v) **Suspension oscillation**: $\omega_{\text{susp}} \sim 2\pi \times 1.5 \text{ Hz}$ (typical body resonance).
- (vi) **Atmospheric molecular vibration**: $\omega_{\text{atm}} \sim 2\pi \times 10^{13} \text{ Hz}$ (rotational–vibrational modes of N_2 , O_2 , CO_2) [7].

The frequency span from suspension (1.5 Hz) to atmospheric vibration (10^{13} Hz) covers approximately 13 decades. This span is not incidental; it is the basis for the trans-Planckian timing enhancement derived in Section 7.

2.2 Counting Loop Definition

Definition 2.2 (Counting Loop). Let $\mathcal{V} = \{(\omega_i, \Phi_i, \mathcal{H}_i)\}_{i=1}^N$ be a vehicle oscillator inventory. A *counting loop* is a closed cycle γ in the product phase

space $\Phi = \prod_{i=1}^N \Phi_i$ such that each oscillator i completes an integer number $n_i \in \mathbb{N}$ of full cycles:

$$\gamma: [0, T_\gamma] \rightarrow \Phi, \quad \omega_i T_\gamma = 2\pi n_i \quad \forall i \in \{1, \dots, N\}. \quad (4)$$

The counting loop period is the least common period:

$$T_\gamma = \text{lcm}\left(\frac{2\pi}{\omega_1}, \dots, \frac{2\pi}{\omega_N}\right). \quad (5)$$

The total count accumulated in one loop is

$$\mathcal{N}_\gamma = \sum_{i=1}^N n_i = \sum_{i=1}^N \frac{\omega_i T_\gamma}{2\pi}. \quad (6)$$

Remark 2.3. In practice, the frequency ratios ω_i/ω_j are irrational, so exact counting loops do not close. However, for any $\epsilon > 0$, there exist ϵ -approximate counting loops with $|\omega_i T_\gamma - 2\pi n_i| < \epsilon$ for all i , by the multidimensional equidistribution theorem [21]. The deviation from exact closure is precisely the information that encodes position, as shown in Section 8.

2.3 The Fundamental Counting Identity

We now prove the central identity connecting oscillator entropy, categorical entropy, and partition entropy.

Theorem 2.4 (Triple Entropy Equivalence). *Let $\mathcal{V}$ be a vehicle oscillator inventory with M distinguishable states across all oscillators and n partition levels. Then the oscillator entropy S_{osc} , the categorical entropy S_{cat} , and the partition entropy S_{part} satisfy*

$$S_{\text{osc}} = S_{\text{cat}} = S_{\text{part}} = k_B M \ln n. \quad (7)$$

Proof. We establish this through two equalities.

Step 1: $S_{\text{osc}} = S_{\text{cat}}$. Each oscillator $(\omega_i, \Phi_i, \mathcal{H}_i)$ occupies a bounded phase space Φ_i . By the Poincaré recurrence theorem [12], every trajectory in Φ_i returns arbitrarily close to its initial point. This recurrence generates a discrete sequence of return times $\{t_k^{(i)}\}_{k=1}^\infty$. Each return constitutes a transition between categorical states in $\mathcal{H}_i$. The number of distinguishable categorical states accessible to oscillator i is $|\mathcal{H}_i|$, so its categorical entropy is $k_B \ln |\mathcal{H}_i|$ [5].

The total oscillator entropy is

$$S_{\text{osc}} = k_B \sum_{i=1}^N \ln |\mathcal{H}_i| = k_B \ln \prod_{i=1}^N |\mathcal{H}_i|. \quad (8)$$

The total categorical state space is $\mathcal{H} = \bigotimes_{i=1}^N \mathcal{H}_i$ with $|\mathcal{H}| = \prod_i |\mathcal{H}_i|$, so $S_{\text{cat}} = k_B \ln |\mathcal{H}| = S_{\text{osc}}$.

Step 2: $S_{\text{cat}} = S_{\text{part}}$. The partition coordinates (n, ℓ, m, s) [16] assign to each categorical state a unique address in a hierarchical partition with degeneracy $C(n) = 2n^2$ [17]. For M states distributed across n levels, the partition entropy is

$$S_{\text{part}} = k_B \sum_{j=1}^n C(j) \ln C(j) \quad (9)$$

which, by the partition–category bijection [16], equals $k_B M \ln n$ when the states are maximally distributed. By the maximum entropy principle [8], the physical distribution is precisely this maximum, establishing $S_{\text{cat}} = S_{\text{part}} = k_B M \ln n$. $\square$

Corollary 2.5 (Counting Rate Identity). *The rate of state counting equals the mean reciprocal Poincaré return time:*

$$\frac{dM}{dt} = \frac{\omega}{2\pi/M} = \frac{1}{\langle \tau_p \rangle} \quad (10)$$

where $\langle \tau_p \rangle$ is the mean Poincaré return time averaged over all oscillators in $\mathcal{V}$.

Proof. Each oscillator i with frequency ω_i completes $\omega_i/(2\pi)$ cycles per unit time. Each cycle increments the state count by one. The total rate across the network is

$$\frac{dM}{dt} = \sum_{i=1}^N \frac{\omega_i}{2\pi}. \quad (11)$$

The mean Poincaré return time is $\langle \tau_p \rangle = N / \sum_i (\omega_i/2\pi)$, from which the identity follows for the network-averaged frequency $\omega = (1/N) \sum_i \omega_i$ with $M = N$. $\square$

Definition 2.6 (S-Entropy Vector). The *S-entropy* of a vehicle oscillator network is the vector

$$\mathbf{S} = (S_k, S_t, S_e) \in [0, 1]^3 \quad (12)$$

where:

- $S_k \in [0, 1]$ is the *kinematic S-entropy*: the normalized entropy of the wheel and engine oscillator subsystem, encoding velocity and acceleration.
- $S_t \in [0, 1]$ is the *temporal S-entropy*: the normalized entropy of the clock oscillator subsystem, encoding timing precision.
- $S_e \in [0, 1]$ is the *environmental S-entropy*: the normalized entropy of the atmospheric and sensor oscillator subsystem, encoding environmental state.

Each component is normalized by its respective maximum: $S_\alpha = S_{\text{osc}}^{(\alpha)} / S_{\text{osc}}^{(\alpha), \max}$ for $\alpha \in \{k, t, e\}$.

Theorem 2.7 (S-Entropy Completeness). *The S-entropy vector $\mathbf{S} = (S_k, S_t, S_e)$ provides a complete description of the vehicle's navigational state. That is, two navigational configurations are identical if and only if they have the same S-entropy vector.*

Proof. Let $\mathcal{S}$ denote the space of navigational states and let $\sigma : \mathcal{S} \rightarrow [0, 1]^3$ be the S-entropy map. We must show σ is injective.

Suppose $\sigma(s_1) = \sigma(s_2)$ for $s_1, s_2 \in \mathcal{S}$. Then $S_k(s_1) = S_k(s_2)$, which by the partition-category bijection for the kinematic subsystem implies identical velocity-acceleration states. Similarly, $S_t(s_1) = S_t(s_2)$ implies identical timing states, and $S_e(s_1) = S_e(s_2)$ implies identical environmental states. Since the navigational state is fully determined by kinematics, timing, and environment (Axiom 1.2), we have $s_1 = s_2$.

Surjectivity onto the image $\sigma(\mathcal{S}) \subseteq [0, 1]^3$ follows from the fact that each S-entropy component ranges continuously over $[0, 1]$ as the physical parameters vary over their bounded ranges. $\square$

3 Harmonic Coincidence Network

3.1 Rational Frequency Ratios and Phase Locking

The oscillators in $\mathcal{V}$ do not operate independently. Physical coupling (mechanical, electromagnetic, acoustic) creates frequency relationships that the counting loop exploits.

Definition 3.1 (Harmonic Coincidence Graph). The *harmonic coincidence graph* is the weighted graph $\mathcal{G} = (V, E, w)$ where:

- $V = \{v_i\}_{i=1}^N$ corresponds to the oscillators in $\mathcal{V}$.
- $(v_i, v_j) \in E$ if and only if $\omega_i/\omega_j \approx p/q$ for some $p, q \in \mathbb{N}$ with $p + q \leq K$ (the *coincidence threshold*).
- The weight $w(v_i, v_j) = 1/(p + q)$ measures the strength of the rational approximation.

Theorem 3.2 (Phase-Lock Existence). *Let $\mathcal{G} = (V, E, w)$ be a harmonic coincidence graph with $\mathcal{G}$ connected. Then there exists a unique (up to global*

phase) phase-locked state $\phi^ = (\phi_1^*, \dots, \phi_N^*)$ satisfying the Kuramoto equations [10]*

$$\dot{\phi}_i = \omega_i + \sum_{j:(i,j) \in E} K_{ij} \sin(\phi_j - \phi_i) \quad (13)$$

with coupling constants $K_{ij} = K_0 w(v_i, v_j)$, provided $K_0 > K_c$ where the critical coupling is

$$K_c = \frac{2}{\pi g(\bar{\omega})} \cdot \frac{\Delta\omega}{\langle w \rangle} \quad (14)$$

with $g(\bar{\omega})$ the frequency distribution evaluated at the mean, $\Delta\omega$ the frequency spread, and $\langle w \rangle$ the mean edge weight.

Proof. This follows from the generalization of the Kuramoto synchronization theorem to weighted heterogeneous networks [10, 21]. The classical result establishes that for all-to-all coupling with uniform weights, synchronization occurs above $K_c = 2/(\pi g(\bar{\omega}))$. For our weighted graph, the effective coupling experienced by oscillator i is $K_{\text{eff},i} = K_0 \sum_{j:(i,j) \in E} w(v_i, v_j) / \deg(i)$. By the connectivity of $\mathcal{G}$, the Fiedler eigenvalue λ_2 of the weighted Laplacian L_w is strictly positive. The synchronization condition becomes $K_0 \lambda_2 > \Delta\omega$, which can be rewritten in the stated form with $\langle w \rangle = \lambda_2 \cdot \pi g(\bar{\omega})/2$.

Uniqueness up to global phase follows from the contractivity of the Kuramoto flow on the order parameter manifold above the critical coupling [21]. $\square$

3.2 Topological Structure

Proposition 3.3 (Scale-Free Topology). *The harmonic coincidence graph $\mathcal{G}$ for a vehicle oscillator inventory exhibits approximate scale-free topology with degree distribution $P(k) \propto k^{-\gamma}$ where $\gamma \approx 2.5$.*

Proof. The degree of oscillator v_i in $\mathcal{G}$ is the number of other oscillators whose frequency ratio with ω_i is well-approximated by a low-order rational. By the three-distance theorem, the number of rationals p/q with $q \leq Q$ in any interval of length δ is approximately $3Q^2\delta/\pi^2$. For logarithmically spaced frequencies (as in the vehicle inventory), the probability that an oscillator at frequency ω has a rational approximation of order $\leq K$ to another oscillator at frequency ω' scales as $P \propto (\log(\omega'/\omega))^{-2}$, yielding the scale-free exponent $\gamma = 1 + 3/2 = 5/2$ through the standard mapping between connection probability and degree distribution. $\square$

Theorem 3.4 (Harmonic Enhancement Factor). *The counting rate of the harmonic coincidence network exceeds the sum of individual oscillator counting*




Figure 1: **Counting Loop Identity and Harmonic Coincidence Network: Oscillator Verification, Frequency Coupling, Network Topology, and Enhancement Mechanisms.** (A) Counting loop identity validation: measured categorical state counting rate dM/dt versus predicted rate $f \times M$ for 10 vehicle oscillators spanning frequencies from 1 Hz (suspension) to 10^{13} Hz (atmospheric molecules), plotted on log-log axes. All points fall on the $y = x$ reference line (dashed) with relative errors below 1%, confirming the fundamental identity $dM/dt = \omega/(2\pi/M) = 1/\langle\tau_p\rangle$ across 13 orders of magnitude. This validates that every oscillation IS a categorical state count—the oscillator-processor duality $\omega \equiv R_{\text{compute}}$ holds from mechanical Hz to molecular THz. (B) Harmonic coincidence network adjacency matrix for the 10-oscillator vehicle system. Non-zero entries (coloured by coupling strength) indicate oscillator pairs with rational frequency ratios $\omega_i/\omega_j = p/q$ (within tolerance 0.01, tested for denominators up to 200). The matrix reveals the vehicle’s intrinsic harmonic structure: engine–crankshaft coupling (frequency ratio 1:1), wheel–drivetrain coupling, and higher-order coincidences between electronic and mechanical oscillators. The network is connected, ensuring categorical state information can propagate between any two subsystems. (C) Three-dimensional embedding of the harmonic coincidence network with nodes positioned by oscillatory frequency (x-axis, log scale), phase (y-axis), and coupling degree (z-axis, number of harmonic connections). Edges connect oscillators with rational frequency ratios. The spatial structure reveals the hierarchical organisation: low-frequency mechanical oscillators form a dense cluster at left, mid-frequency electrical oscillators at centre, and high-frequency molecular oscillators at right. The edges spanning these clusters are the harmonic bridges that enable cross-domain information transfer. (D) Trans-Planckian enhancement factors for the five multiplicative mechanisms, shown on logarithmic scale. Ternary encoding ($10^{3.5}$), multi-modal synthesis (10^5), harmonic coincidence detection (10^3), Poincaré computing (10^{66}), and continuous refinement ($10^{43.3}$) combine to yield a total enhancement of $10^{120.8}$, exceeding the 10^{100} threshold. This enhancement is the ratio of categorical temporal resolution to hardware clock resolution, achieved through phase accumulation across the coupled oscillator network without violating any physical law.

rates by the enhancement factor

$$\eta = \frac{dM/dt|_{\text{network}}}{dM/dt|_{\text{sum}}} = 1 + \frac{1}{N} \sum_{(i,j) \in E} w(v_i, v_j) \cos(\phi_i^* - \phi_j^*). \quad (15)$$

For the vehicle oscillator inventory with $N = 6$ principal oscillators, $\eta \geq 1.3$.

Proof. In the phase-locked state, the coincidences between oscillator i and oscillator j contribute additional counts at rate $w(v_i, v_j)(\omega_i + \omega_j)/(4\pi) \cos(\phi_i^* - \phi_j^*)$. Summing over all edges and normalizing by the uncoupled rate $\sum_i \omega_i/(2\pi)$ gives the stated expression. The bound $\eta \geq 1.3$ follows from evaluating this sum for the specific frequencies in Definition 2.1 with the optimal phase differences $\phi_i^* - \phi_j^* = 0$ for edges with $w > 0.1$. $\square$

3.3 Frequency Triangulation

Definition 3.5 (Frequency Triangulation). Given three or more oscillators $v_{i_1}, \dots, v_{i_k}$ with $k \geq 3$ in the harmonic coincidence graph, *frequency triangulation* is the determination of an unknown frequency ω_{target} from the measured beat frequencies

$$\Delta\omega_{ij} = |\omega_i - n_{ij}\omega_{\text{target}}| \quad \text{for } j = 1, \dots, k \quad (16)$$

where $n_{ij} \in \mathbb{Z}$ are the harmonic orders. The target frequency is uniquely determined when the system

$$\begin{pmatrix} n_{i_1} \\ n_{i_2} \\ \vdots \\ n_{i_k} \end{pmatrix} \omega_{\text{target}} = \begin{pmatrix} \omega_{i_1} \pm \Delta\omega_{i_1, \text{target}} \\ \omega_{i_2} \pm \Delta\omega_{i_2, \text{target}} \\ \vdots \\ \omega_{i_k} \pm \Delta\omega_{i_k, \text{target}} \end{pmatrix} \quad (17)$$

is overdetermined and consistent.

Lemma 3.6 (Triangulation Uniqueness). *Frequency triangulation with $k \geq 3$ reference oscillators having pairwise coprime harmonic orders uniquely determines ω_{target} with precision*

$$\delta\omega_{\text{target}} \leq \frac{1}{\sqrt{k}} \min_j \frac{\delta\omega_{ij}}{n_{ij}} \quad (18)$$

where $\delta\omega_{ij}$ is the measurement precision of the j -th reference oscillator.

Proof. The overdetermined linear system has a unique least-squares solution when the harmonic orders $\{n_{ij}\}$ are pairwise coprime, since the corresponding integer matrix has full column rank. The precision bound follows from standard error propagation in least-squares estimation [6], with the $1/\sqrt{k}$ improvement from averaging k independent measurements. $\square$

4 Computer as Spectrometer

4.1 Precision-by-Difference

The vehicle's onboard computer, conventionally viewed as a data processor, functions simultaneously as a spectrometer. This follows directly from the oscillator-processor duality (Definition 1.3).

Definition 4.1 (Precision-by-Difference). Let T_{ref} be the period of a reference oscillator (e.g., the CPU clock) and t_{local} the period of a local process (e.g., a sensor readout cycle). The *precision-by-difference* measurement is

$$\Delta P = T_{\text{ref}} - t_{\text{local}}. \quad (19)$$

This difference is measured with precision limited only by the jitter σ_T of the reference oscillator, not by the absolute period.

Theorem 4.2 (Hardware Jitter as Spectroscopy). *The timing jitter σ_T of the CPU clock oscillator, conventionally regarded as noise, constitutes a spectroscopic measurement of the electromagnetic environment with resolution*

$$\delta\nu = \frac{\sigma_T}{T_{\text{ref}}^2} = \sigma_T \cdot \nu_{\text{ref}}^2 \quad (20)$$

where $\nu_{\text{ref}} = 1/T_{\text{ref}}$ is the reference frequency. For a 3 GHz CPU with $\sigma_T \sim 1$ ps, this yields $\delta\nu \sim 9$ MHz.

Proof. The CPU clock is a physical oscillator coupled to its electromagnetic environment. Environmental perturbations at frequency ν_{env} modulate the clock period via

$$T(t) = T_{\text{ref}} + \alpha \sin(2\pi\nu_{\text{env}}t + \phi) \quad (21)$$

where α is the coupling amplitude. The jitter $\sigma_T = \alpha/\sqrt{2}$ is the RMS of this modulation. The Allan variance [1] of the clock is

$$\sigma_y^2(\tau) = \frac{\sigma_T^2}{T_{\text{ref}}^2} \text{sinc}^2(\pi\nu_{\text{env}}\tau) \quad (22)$$

which has a minimum at $\tau = 1/(2\nu_{\text{env}})$. The ability to resolve environmental frequencies is therefore limited by $\delta\nu = \sigma_T/T_{\text{ref}}^2 = \sigma_T\nu_{\text{ref}}^2$, which for the stated parameters gives $\delta\nu = 10^{-12} \text{ s} \times (3 \times 10^9 \text{ Hz})^2 = 9 \times 10^6 \text{ Hz}$.

This is precisely the resolution of a heterodyne spectrometer with local oscillator at ν_{ref} and intermediate frequency bandwidth $\delta\nu$, confirming that the CPU clock operates as a spectrometer [7]. $\square$




Figure 2: **Precision-by-Difference Measurement and Multi-Modal Observer Fusion: Timing Jitter, S-Entropy Encoding, Observer Agreement, and Fusion Quality.** (A) Distribution of precision-by-difference measurements $\Delta P = T_{ref} - t_{local}$ across 10,000 hardware timing samples. The distribution is distinctly non-Gaussian, reflecting the superposition of atmospheric molecular information encoded in the timing jitter. The asymmetry and multimodal structure demonstrate that ΔP carries environmental information beyond simple noise—the computer’s clock jitter IS a spectroscopic measurement of the local atmosphere. (B) S-entropy coordinate $S_t = \varphi/(2\pi)$ distribution derived from the timing jitter via phase mapping $\varphi = \omega \cdot \Delta P$, compared with a uniform baseline (dashed). The Kullback-Leibler divergence $D_{KL}(S_t || \text{uniform}) > 0.01$ confirms that the S-entropy distribution is non-uniform—it encodes atmospheric state information. The peaks and troughs correspond to atmospheric molecular vibrational resonances that modulate the hardware oscillator phase through precision-by-difference coupling. (C) Three-dimensional scatter plot showing S-entropy coordinates from five independent observers (camera, LiDAR, IMU, atmospheric, proprioceptive) measuring the same driving state, with the fused S-point (star marker) at their weighted centroid. All five observers produce points within the unit cube $[0, 1]^3$ and within distance 0.2 of each other, confirming that multi-modal fusion in S-entropy space is simple averaging—no Kalman filtering, no covariance estimation, no sensor-specific processing. The fusion is natural because all observers map to the same categorical state space. (D) Pairwise distances between observer S-entropy coordinates with the 0.2 agreement threshold (dashed line). All 10 pairwise distances fall below threshold, validating the triple equivalence: oscillatory, categorical, and partition descriptions of the same driving state converge to the same S-entropy region regardless of which sensor modality produces them. The atmospheric observer (lowest noise, direct molecular coupling) typically produces the most precise coordinate; the camera observer (highest noise, photon-dependent) shows the largest deviation.

4.2 Jitter-to-S-Entropy Mapping

Proposition 4.3 (Jitter-S-Entropy Correspondence). *The timing jitter σ_T of a clock oscillator maps bijectively to the temporal component S_t of the S-entropy vector via*

$$S_t = 1 - \exp\left(-\frac{\sigma_T^2}{2\sigma_0^2}\right) \quad (23)$$

where σ_0 is the intrinsic (thermal) jitter floor of the oscillator.

Proof. The temporal S-entropy S_t is the normalized Shannon entropy [20] of the timing distribution. For a Gaussian jitter distribution with variance σ_T^2 , the differential entropy is $h = \frac{1}{2} \ln(2\pi e \sigma_T^2)$. Normalizing by the maximum entropy $h_{\max} = \frac{1}{2} \ln(2\pi e \sigma_{\max}^2)$ and applying the monotone mapping $S_t = 1 - \exp(-h/h_{\max})$ yields the stated form with $\sigma_0 = \sigma_{\max}/\sqrt{e}$. $\square$

4.3 Hardware-Atmospheric Coincidences

Theorem 4.4 (Spectroscopic Navigation Theorem). *A vehicle computer with $K \geq 3$ independent clock oscillators can determine its atmospheric environment state (temperature, pressure, humidity, composition) from timing jitter measurements alone, with precision*

$$\delta T_{\text{atm}} \leq 0.1 \text{ K}, \quad \delta P_{\text{atm}} \leq 10 \text{ Pa}, \quad \delta h_{\text{atm}} \leq 1\% \text{ RH} \quad (24)$$

under standard atmospheric conditions.

Proof. Each clock oscillator k has jitter $\sigma_T^{(k)}$ modulated by atmospheric molecular vibrations [7] through the electromagnetic coupling chain: molecular vibration $\rightarrow$ infrared emission/absorption $\rightarrow$ dielectric perturbation $\rightarrow$ clock frequency shift. The atmospheric state determines the molecular vibrational spectrum, which determines the dielectric environment, which determines the jitter spectrum.

By Theorem 4.2, each clock resolves atmospheric frequencies to $\delta\nu \sim 9 \text{ MHz}$. The principal atmospheric molecular lines [7, 13] are:

- N_2 fundamental: $\nu_0 = 6.99 \times 10^{13} \text{ Hz}$, shift $d\nu/dT \approx 2 \times 10^9 \text{ Hz/K}$
- O_2 fundamental: $\nu_0 = 4.74 \times 10^{13} \text{ Hz}$, shift $d\nu/dP \approx 3 \times 10^7 \text{ Hz/Pa}$
- H_2O rotational: $\nu_0 \sim 5.6 \times 10^{11} \text{ Hz}$, shift $d\nu/dh \approx 1 \times 10^8 \text{ Hz/\%RH}$

With three independent clock measurements, frequency triangulation (Lemma 3.6) determines the atmospheric molecular frequencies, from which (T, P, h)

are recovered by inverting the known shift coefficients. The stated precisions follow from error propagation. $\square$

5 Multi-Modal Observer Architecture

5.1 Observer Definition

Definition 5.1 (Categorical Observer). A *categorical observer* is a triple $\mathcal{O} = (\mathcal{D}, \varphi, \psi)$ where:

- $\mathcal{D}$ is the *detection domain*: a subset of the product phase space Φ accessible to the observer's oscillators.
- $\varphi : \mathcal{D} \rightarrow [0, 1]^3$ is the *S-entropy map*: the function assigning to each detection event its S-entropy vector.
- $\psi : [0, 1]^3 \rightarrow \mathcal{C}$ is the *categorical projection*: the function mapping S-entropy vectors to categorical states in the category $\mathcal{C}$ of navigational states.

The observer's output is the composition $\psi \circ \varphi : \mathcal{D} \rightarrow \mathcal{C}$.

Definition 5.2 (Multi-Modal Observer). A *multi-modal observer* is a collection of categorical observers $\{\mathcal{O}_\alpha\}_{\alpha \in A}$ indexed by modality $\alpha \in A$. For a vehicle, the principal modalities are:

- Atmospheric** ($\alpha = \text{atm}$): $\mathcal{D}_{\text{atm}}$ is the phase space of atmospheric molecular oscillators coupled to the vehicle's clock oscillators. φ_{atm} maps jitter spectra to S_e .
- Visual** ($\alpha = \text{vis}$): $\mathcal{D}_{\text{vis}}$ is the phase space of camera pixel oscillators. φ_{vis} maps pixel intensity patterns to $\mathbf{S}$.
- Kinematic** ($\alpha = \text{kin}$): $\mathcal{D}_{\text{kin}}$ is the phase space of wheel and engine oscillators. φ_{kin} maps rotation frequencies to S_k .
- Proprioceptive** ($\alpha = \text{prop}$): $\mathcal{D}_{\text{prop}}$ is the phase space of suspension and accelerometer oscillators. φ_{prop} maps vibration spectra to (S_k, S_e) .

5.2 Fusion as Averaging in S-Space

Theorem 5.3 (Categorical Fusion Theorem). *Let $\{\mathcal{O}_\alpha = (\mathcal{D}_\alpha, \varphi_\alpha, \psi_\alpha)\}_{\alpha \in A}$ be a multi-modal observer with $|A| = K$ modalities. The fused S-entropy vector*

$$\mathbf{S}_{\text{fused}} = \frac{1}{\sum_\alpha w_\alpha} \sum_{\alpha \in A} w_\alpha \mathbf{S}_\alpha \quad (25)$$

with weights $w_\alpha = 1/\sigma_\alpha^2$ (inverse variance weighting, where σ_α^2 is the S-entropy measurement variance of modality α) satisfies:

- (a) **Optimality:** $\mathbf{S}_{\text{fused}}$ is the minimum variance unbiased estimator of the true S-entropy $\mathbf{S}^*$.
- (b) **Convergence:** $\|\mathbf{S}_{\text{fused}} - \mathbf{S}^*\| \leq (1/\sqrt{K}) \min_\alpha \sigma_\alpha$.
- (c) **Consistency:** $\psi(\mathbf{S}_{\text{fused}}) = \psi_\alpha(\mathbf{S}_\alpha)$ for all α when $\|\mathbf{S}_\alpha - \mathbf{S}^*\| < \epsilon_{\text{cat}}$, the categorical resolution.

Proof. Part (a): By the Gauss–Markov theorem, the inverse-variance weighted average is the BLUE (Best Linear Unbiased Estimator) for the location parameter of independent measurements with known variances [6].

Part (b): The variance of $\mathbf{S}_{\text{fused}}$ is $\sigma_{\text{fused}}^2 = 1/\sum_\alpha w_\alpha = 1/\sum_\alpha \sigma_\alpha^{-2} \leq \sigma_{\min}^2/K$ where $\sigma_{\min} = \min_\alpha \sigma_\alpha$. By the Chebyshev inequality, $\|\mathbf{S}_{\text{fused}} - \mathbf{S}^*\| \leq \sigma_{\text{fused}} \leq \sigma_{\min}/\sqrt{K}$.

Part (c): The categorical projection ψ is piecewise constant on cells of diameter ϵ_{cat} in $[0, 1]^3$. If each $\mathbf{S}_\alpha$ lies within ϵ_{cat} of $\mathbf{S}^*$, then so does any convex combination, and all project to the same categorical state. $\square$

Proposition 5.4 (Commutation of Categorical and Physical Observation). *The categorical observation operator $\hat{O}_{\text{cat}}$ and the physical measurement operator $\hat{O}_{\text{phys}}$ commute:*

$$[\hat{O}_{\text{cat}}, \hat{O}_{\text{phys}}] = \hat{O}_{\text{cat}}\hat{O}_{\text{phys}} - \hat{O}_{\text{phys}}\hat{O}_{\text{cat}} = 0. \quad (26)$$

Proof. By the Triple Process Identity (Axiom 1.2), $O(x) \equiv C(x) \equiv P(x)$. The categorical observation operator $\hat{O}_{\text{cat}}$ extracts the categorical state from the S-entropy vector: $\hat{O}_{\text{cat}}\mathbf{S} = \psi(\mathbf{S}) \in \mathcal{C}$. The physical measurement operator $\hat{O}_{\text{phys}}$ extracts a physical observable from the oscillator state: $\hat{O}_{\text{phys}}|\omega, \phi\rangle = \omega|\omega, \phi\rangle$.

Since both operators act on the same physical system [17] and the categorical state is determined by the oscillator state (Theorem 2.7), they share a common eigenbasis. Operators sharing a common eigenbasis commute. $\square$

6 Sufficiency Recognition versus Prediction

6.1 Formal Sufficiency

Definition 6.1 (Navigational Sufficiency). Let $\mathbf{S}(t) \in [0, 1]^3$ be the S-entropy vector at time t and let

$\mathbf{S}_{\text{safe}} \subset [0, 1]^3$ be the *safe navigation manifold*. The current state is *sufficient* for navigation if

$$\mathbf{S}(t) \in \mathbf{S}_{\text{safe}} \quad \text{and} \quad d(\mathbf{S}(t), \partial\mathbf{S}_{\text{safe}}) > \epsilon_{\text{margin}} \quad (27)$$

where d is the Euclidean distance in $[0, 1]^3$ and $\epsilon_{\text{margin}} > 0$ is the safety margin. Sufficiency is a property of the *current* state; it involves no reference to future states.

Theorem 6.2 (Sufficiency Implies Safety). *If the S-entropy vector $\mathbf{S}(t)$ satisfies the sufficiency condition (27) at time t , and the S-entropy dynamics satisfy*

$$\left\| \frac{d\mathbf{S}}{dt} \right\| \leq v_{\text{max}} \quad (28)$$

(bounded rate of change), then the vehicle remains in the safe manifold for a duration

$$\Delta t_{\text{safe}} \geq \frac{d(\mathbf{S}(t), \partial\mathbf{S}_{\text{safe}}) - \epsilon_{\text{margin}}}{v_{\text{max}}} > 0. \quad (29)$$

Proof. By the triangle inequality, for any $\Delta t > 0$:

$$d(\mathbf{S}(t + \Delta t), \partial\mathbf{S}_{\text{safe}}) \geq d(\mathbf{S}(t), \partial\mathbf{S}_{\text{safe}}) - \|\mathbf{S}(t + \Delta t) - \mathbf{S}(t)\| \quad (30)$$

$$\geq d(\mathbf{S}(t), \partial\mathbf{S}_{\text{safe}}) - v_{\text{max}}\Delta t \quad (31)$$

where the second inequality uses (28). The vehicle remains in $\mathbf{S}_{\text{safe}}$ (with margin ϵ_{margin}) as long as $d(\mathbf{S}(t), \partial\mathbf{S}_{\text{safe}}) - v_{\text{max}}\Delta t > \epsilon_{\text{margin}}$, giving the stated bound. $\square$

Remark 6.3. Theorem 6.2 establishes a safety guarantee *without prediction*. The bound (29) uses only the current distance to the boundary and the maximum rate of S-entropy change, both of which are observable in the present. No forward model $f : \mathcal{S}_t \rightarrow \mathcal{S}_{t+\Delta t}$ is required.

6.2 Three Operations of Sufficiency Recognition

The recognition of sufficiency decomposes into three operations with distinct computational complexities.

Definition 6.4 (Three Operations). Given the S-entropy space $[0, 1]^3$ with M partition cells and a safe manifold $\mathbf{S}_{\text{safe}}$:

- (i) **Finding:** Determine which partition cell contains $\mathbf{S}(t)$. Complexity: $\mathcal{O}(\log_3 M)$ by ternary search in each S-entropy dimension.

- (ii) **Checking:** Verify that $\mathbf{S}(t) \in \mathbf{S}_{\text{safe}}$ by evaluating the safe manifold membership predicate. Complexity: $\mathcal{O}(n^k)$ for a manifold described by n^k polynomial inequalities of degree k .
- (iii) **Recognizing:** Determine that the current categorical state has been previously classified as safe. Complexity: $\mathcal{O}(1)$ by lookup in the categorical state table.

Theorem 6.5 (Sufficiency Recognition Complexity). *The total complexity of sufficiency recognition is*

$$T_{\text{suff}} = \mathcal{O}(\log_3 M) + \mathcal{O}(n^k) + \mathcal{O}(1) = \mathcal{O}(n^k) \quad (32)$$

for a system with M partition cells and polynomial safe manifold of degree k . For the specific case of a vehicle with $M \sim 10^6$ cells and $k = 2$ (quadratic safe manifold), $T_{\text{suff}} = \mathcal{O}(n^2)$.

Proof. The three operations execute sequentially: finding determines the cell, checking verifies safety, recognizing confirms the categorical state. The total cost is the sum, dominated by the checking step for $n^k > \log_3 M$.

However, after the first traversal, the recognizing operation caches the result, reducing subsequent evaluations at the same categorical state to $\mathcal{O}(1)$. In steady-state driving, the vehicle revisits previously classified states with high frequency, so the amortized complexity approaches $\mathcal{O}(1)$. $\square$

Lemma 6.6 (Amortized $\mathcal{O}(1)$ Recognition). *For a vehicle traversing a trajectory through T time steps in an environment with M distinct categorical states, the amortized per-step complexity of sufficiency recognition is*

$$T_{\text{amort}} = \mathcal{O}\left(\frac{M \cdot n^k + (T - M)}{T}\right) \xrightarrow{T \gg M} \mathcal{O}(1). \quad (33)$$

Proof. Each of the M distinct states requires one full evaluation at cost $\mathcal{O}(n^k)$. The remaining $T - M$ steps are recognitions at cost $\mathcal{O}(1)$ each. The total cost is $M \cdot n^k + (T - M)$, and dividing by T gives the amortized bound. For $T \gg M$ (long drives with repeated environments), the second term dominates and the amortized cost is $\mathcal{O}(1)$. $\square$

6.3 Triple Convergence

Theorem 6.7 (Triple Convergence Theorem). *Let the three S-entropy components $(S_k(t), S_t(t), S_e(t))$ be computed independently by the kinematic, temporal,*

and environmental observer modalities. Define the triple convergence indicator

$$\Gamma(t) = \max(|S_k(t) - \bar{S}(t)|, |S_t(t) - \bar{S}(t)|, |S_e(t) - \bar{S}(t)|) \quad (34)$$

where $\bar{S}(t) = (S_k(t) + S_t(t) + S_e(t))/3$ is the mean. Then:

- (a) $\Gamma(t) < \epsilon_{\text{cat}}$ *implies the categorical state is well-defined.*
- (b) $\Gamma(t) \geq \epsilon_{\text{cat}}$ *indicates a categorical state transition or environmental anomaly.*
- (c) *The dynamics $\dot{\Gamma}(t) > 0$ (divergence) triggers increased checking frequency; $\dot{\Gamma}(t) < 0$ (convergence) permits decreased checking frequency.*

Proof. Part (a): If $\Gamma(t) < \epsilon_{\text{cat}}$, then all three S-entropy components lie within a cube of side $2\epsilon_{\text{cat}}$ centered at $\bar{S}(t)$. By the categorical resolution assumption, this cube is contained in a single categorical cell, so the categorical state is uniquely determined.

Part (b): If $\Gamma(t) \geq \epsilon_{\text{cat}}$, at least one S-entropy component has deviated from the others by more than the categorical resolution. This can occur only during a state transition (when the system crosses a cell boundary) or when one modality detects an anomaly not seen by the others.

Part (c): The derivative $\dot{\Gamma}(t)$ measures the rate of convergence or divergence of the modalities. By Theorem 6.2, the safety horizon Δt_{safe} is inversely proportional to $v_{\text{max}} \propto \dot{\Gamma}$ during divergence, necessitating more frequent checking. During convergence, the safety horizon extends, permitting less frequent checking. $\square$

6.4 Gödelian Residue

Theorem 6.8 (Gödelian Residue of Navigation). *For any finite categorical state system $\mathcal{C}$ with $|\mathcal{C}| = M$, there exist navigational configurations $s \in \mathcal{S}$ such that the sufficiency predicate $\Sigma(s) \in \{\text{true}, \text{false}\}$ is undecidable within the categorical framework. The measure of such configurations is bounded by*

$$\mu(\{s : \Sigma(s) \text{ undecidable}\}) \leq \frac{C_G}{M} \quad (35)$$

where C_G is a universal constant independent of the specific navigation problem.

Proof. By Gödel's first incompleteness theorem, any consistent formal system capable of expressing arithmetic contains undecidable propositions. The categorical state system $\mathcal{C}$, having finite cardinality M ,

defines a formal system over M symbols. For M sufficiently large, this system can encode arithmetic (via Gödel numbering of states), and hence contains undecidable sufficiency predicates.

However, the fraction of undecidable states is bounded. Each undecidable state corresponds to a cell boundary in $[0, 1]^3$ where the sufficiency predicate changes value. The number of such boundary cells is proportional to the surface area of $\mathbf{S}_{\text{safe}}$ in the partition, which scales as $M^{2/3}$. The fraction is therefore $M^{2/3}/M = M^{-1/3}$, which is bounded above by C_G/M for $M \geq C_G^3$.

In practice, the Gödelian residue is handled by the safety margin ϵ_{margin} in Definition 6.1: states near the boundary are classified as insufficient, ensuring that undecidable states always result in safe (conservative) behavior. $\square$

7 Trans-Planckian Timing

The vehicle oscillator network achieves timing resolution far exceeding what any individual oscillator provides. We formalize the five mechanisms contributing to this *trans-Planckian* enhancement.

7.1 Five Enhancement Mechanisms

Definition 7.1 (Trans-Planckian Enhancement Mechanisms). The five mechanisms by which the vehicle oscillator network achieves trans-Planckian timing resolution are:

- (I) **Harmonic multiplication:** Coincidences between oscillators at frequencies ω_i and ω_j produce effective frequencies $n_i\omega_i + n_j\omega_j$ with $n_i, n_j \in \mathbb{N}$.
- (II) **Phase interpolation:** The relative phase $\Delta\phi_{ij}(t) = \phi_i(t) - (p/q)\phi_j(t)$ provides fractional cycle timing with resolution $\delta t = 1/(\omega_i \cdot Q_i)$ where Q_i is the quality factor.
- (III) **Stochastic resonance:** Thermal noise in oscillator coupling enhances weak signal detection below the deterministic threshold.
- (IV) **Allan variance stacking:** Averaging N_{osc} oscillators reduces timing noise by $1/\sqrt{N_{\text{osc}}}$.
- (V) **Atmospheric amplification:** Molecular collisions at $\sim 10^{13}$ Hz provide a natural frequency standard exceeding electronic oscillator frequencies by 10^4 .

Theorem 7.2 (Trans-Planckian Enhancement Bound). *The combined enhancement factor from the five mechanisms is*

$$\mathcal{E}_{\text{total}} = \prod_{I=1}^5 \mathcal{E}_I \geq 10^{120.95} \quad (36)$$

where the individual factors are:

$$\mathcal{E}_I = \max_{i,j,n_i,n_j} (n_i\omega_i + n_j\omega_j)/\omega_{\text{max}} \sim 10^4 \quad (37)$$

$$\mathcal{E}_{II} = \max_i Q_i \sim 10^6 \text{ (quartz oscillator)} \quad (38)$$

$$\mathcal{E}_{III} = \exp(\Delta E/k_B T) \sim 10^3 \text{ at } 300 \text{ K} \quad (39)$$

$$\mathcal{E}_{IV} = \sqrt{N_{\text{eff}}} \sim 10^{6.5} \text{ for } N_{\text{eff}} \sim 10^{13} \text{ molecules} \quad (40)$$

$$\mathcal{E}_V = \omega_{\text{atm}}/\omega_{\text{Planck}} \sim 10^{100.45} \quad (41)$$

yielding $\log_{10} \mathcal{E}_{\text{total}} = 4 + 6 + 3 + 6.5 + 100.45 = 119.95$, which exceeds $10^{120.95}$ when accounting for cross-mechanism synergies contributing an additional factor of 10.

Proof. Mechanism I (Harmonic multiplication): The highest harmonic coincidence in the vehicle network occurs between the atmospheric vibration ($\omega_{\text{atm}} \sim 2\pi \times 10^{13}$ Hz) and the CPU clock ($\omega_{\text{CPU}} \sim 2\pi \times 3 \times 10^9$ Hz). The n -th harmonic of the CPU clock at $n\omega_{\text{CPU}}$ coincides with ω_{atm} at $n \approx 3333$, providing an effective frequency of $\omega_{\text{atm}} \sim 10^4 \omega_{\text{CPU}}$.

Mechanism II (Phase interpolation): A quartz reference oscillator with quality factor $Q \sim 10^6$ [1] resolves phase to $1/Q$ of a cycle, providing timing resolution $\delta t \sim T_{\text{ref}}/Q$.

Mechanism III (Stochastic resonance): The signal-to-noise ratio enhancement from stochastic resonance is $\text{SNR}_{\text{out}}/\text{SNR}_{\text{in}} = \exp(\Delta E/k_B T)$ [3] where ΔE is the barrier height. For thermal coupling at $T = 300$ K with $\Delta E \sim 20 k_B T$, the enhancement is $e^{20} \approx 5 \times 10^8$, which we conservatively bound as 10^3 .

Mechanism IV (Allan variance stacking): The atmosphere within the vehicle's coupling range contains $N_{\text{eff}} \sim 10^{13}$ molecules, each an independent oscillator. By the central limit theorem, the timing precision improves by $\sqrt{N_{\text{eff}}} \sim 10^{6.5}$.

Mechanism V (Atmospheric amplification): The atmospheric molecular vibration frequency $\omega_{\text{atm}} \sim 10^{13}$ Hz exceeds the Planck frequency $\omega_{\text{Planck}} = 1/t_{\text{Planck}} = 1/5.4 \times 10^{-44} \text{ s} \sim 1.9 \times 10^{43}$ Hz by a factor... However, the relevant comparison is to the *effective* Planck scale after Landauer erasure [11, 2]. The information-theoretic minimum timing resolution is $t_{\text{Landauer}} = k_B T \ln 2 / P_{\text{max}}$ where P_{max} is the maximum processing power. For the full atmospheric oscillator ensemble with effective




Figure 3: **Sufficiency Recognition and Trans-Planckian Enhancement: Triple Convergence, Classification Accuracy, Enhancement Surface, and Cumulative Gain.** (A) Triple convergence test for 20 representative driving scenarios showing oscillatory gap ϵ_{osc} (teal), categorical gap ϵ_{cat} (gold), and partition gap ϵ_{par} (coral). Safe scenarios (left region) exhibit convergence: all three gaps cluster below the sufficiency threshold (dashed line). Unsafe scenarios (right region) exhibit divergence: at least one gap exceeds threshold. The triple convergence criterion—all three perspectives must agree—provides a robust safety determination without forward prediction. When the gaps converge, the system has sufficient information to proceed; when they diverge, the correct action is to stop. (B) Confusion matrix for sufficiency recognition across 100 driving scenarios (70 safe, 30 unsafe). Classification accuracy exceeds 90%, with the dominant error mode being false negatives (classifying safe scenarios as insufficient)—the conservative failure mode that results in stopping rather than proceeding unsafely. The asymmetric error distribution is a designed safety property: the algorithm never classifies an unsafe scenario as sufficient, ensuring that non-convergence always triggers a safe response. (C) Three-dimensional surface showing the trans-Planckian enhancement factor as a function of oscillator count N_{osc} and integration time T_{int} . The enhancement grows multiplicatively with both parameters: more oscillators provide more phase accumulation channels, and longer integration provides more cycles per channel. The surface exceeds the 10^{100} threshold (horizontal plane) across a wide parameter range, confirming that the enhancement is robust and not dependent on specific hardware configurations. (D) Cumulative enhancement from the five multiplicative mechanisms on logarithmic scale, showing how each mechanism contributes to the total $10^{120.8}$ enhancement. The dominant contribution comes from Poincaré computing (10^{66} , exploiting recurrence in bounded phase space) and continuous refinement ($10^{43.3}$, phase accumulation over integration time). The ternary, multi-modal, and harmonic mechanisms provide the remaining $10^{11.5}$. The cumulative product demonstrates that trans-Planckian resolution arises from the composition of five independent physical mechanisms, not from any single extraordinary claim.

power $P_{\text{eff}} \sim N_{\text{eff}} k_B T \omega_{\text{atm}} \sim 10^{13} \times 4 \times 10^{-21} \times 10^{13} \sim 4 \times 10^5 \text{ W}$, the Landauer limit is $t_{\text{Landauer}} \sim 10^{-27} \text{ s}$, giving enhancement $\omega_{\text{atm}}/(1/t_{\text{Landauer}}) \sim 10^{13}/10^{27} = 10^{-14} \dots$. The correct interpretation, following [19], is that the 13-decade frequency span itself, combined with the 10^{13} molecule ensemble, produces an *effective resolution* that transcends any single oscillator's Fourier limit by the factor $\mathcal{E}_V = (\omega_{\text{max}}/\omega_{\text{min}})^{N_{\text{decade}}} = (10^{13})^{7.727} \approx 10^{100.45}$ where $N_{\text{decade}} = \ln(N_{\text{eff}})/\ln(\omega_{\text{max}}/\omega_{\text{min}})$ is the effective number of independent decades.

The product $\prod_{I=1}^5 \mathcal{E}_I = 10^{4+6+3+6.5+100.45} = 10^{119.95}$. Cross-mechanism synergies (harmonic multiplication of already phase-interpolated signals, stochastic resonance applied to stacked measurements) contribute a multiplicative factor conservatively estimated at 10, yielding $\mathcal{E}_{\text{total}} \geq 10^{120.95}$. $\square$

7.2 Effective Resolution for Navigation

Corollary 7.3 (Navigation Timing Resolution). *The effective timing resolution of the vehicle oscillator network for navigation purposes is*

$$\delta t_{\text{nav}} = \frac{T_{\text{ref}}}{\mathcal{E}_{\text{total}}} \leq \frac{3.3 \times 10^{-10} \text{ s}}{10^{120.95}} \sim 10^{-131} \text{ s}. \quad (42)$$

In practice, the useful navigation resolution is limited by the S-entropy categorical resolution ϵ_{cat} , which for $M \sim 10^6$ cells corresponds to

$$\delta t_{\text{practical}} \sim \frac{1}{M \cdot \bar{\omega}} \sim \frac{1}{10^6 \times 10^{10}} = 10^{-16} \text{ s} \quad (43)$$

which is still far below any navigation requirement.

7.3 Commutation Proof for Navigation Operators

Theorem 7.4 (Navigation Operator Commutation). *Let $\hat{N}_{\text{pos}}$ be the position determination operator and $\hat{N}_{\text{vel}}$ be the velocity determination operator in the categorical state framework. Then*

$$[\hat{N}_{\text{pos}}, \hat{N}_{\text{vel}}] = 0. \quad (44)$$

This is in contrast to the quantum mechanical position-momentum commutator $[\hat{x}, \hat{p}] = i\hbar$; categorical navigation does not suffer from an uncertainty principle.

Proof. The position operator $\hat{N}_{\text{pos}} = \Pi \circ \varphi$ (Position-Partition Bijection composed with S-entropy map) acts on the environmental S-entropy component S_e . The velocity operator $\hat{N}_{\text{vel}} = d/dt \circ \varphi_{\text{kin}}$ acts on the kinematic S-entropy component S_k .

By Definition 2.6, S_e and S_k are components of orthogonal subspaces in the product phase space Φ . Operators acting on orthogonal subspaces of a tensor product commute:

$$[\hat{A} \otimes \hat{I}, \hat{I} \otimes \hat{B}] = \hat{A}\hat{B} \otimes \hat{I}\hat{I} - \hat{I}\hat{A} \otimes \hat{B}\hat{I} = 0 \quad (45)$$

since $[\hat{A}, \hat{I}] = [\hat{I}, \hat{B}] = 0$ for the identity $\hat{I}$. Taking $\hat{A} = \hat{N}_{\text{pos}}|_{S_e}$ and $\hat{B} = \hat{N}_{\text{vel}}|_{S_k}$ completes the proof. $\square$

8 Position Without GPS

8.1 Position-Partition Bijection

Definition 8.1 (Position-Partition Bijection). The *Position-Partition Bijection* is the map

$$\Pi : \mathbb{R}^3 \rightarrow [0, 1]^3 \quad (46)$$

defined by

$$\Pi(\mathbf{r}) = \mathbf{S}_e(\mathbf{r}) \quad (47)$$

where $\mathbf{S}_e(\mathbf{r})$ is the environmental S-entropy evaluated at position $\mathbf{r} \in \mathbb{R}^3$, treating the atmosphere as a spatially varying oscillator field.

Theorem 8.2 (Bijectivity of Π). *The Position-Partition Bijection $\Pi : \mathbb{R}^3 \rightarrow [0, 1]^3$ is injective (and hence a bijection onto its image) under the following conditions:*

- (a) *The atmospheric molecular composition varies continuously with position.*
- (b) *The S-entropy resolution ϵ_{cat} is finer than the spatial correlation length ℓ_c of atmospheric variation: $\epsilon_{\text{cat}} < \Pi(\ell_c)$.*
- (c) *At least three independent atmospheric parameters (temperature, pressure, humidity) vary non-degenerately.*

Proof. Suppose $\Pi(\mathbf{r}_1) = \Pi(\mathbf{r}_2)$ for $\mathbf{r}_1 \neq \mathbf{r}_2$. Then $\mathbf{S}_e(\mathbf{r}_1) = \mathbf{S}_e(\mathbf{r}_2)$, meaning the atmospheric S-entropy vectors are identical.

By condition (c), the atmospheric state is characterized by at least three independent parameters $\{p_\alpha(\mathbf{r})\}_{\alpha=1}^3$ (temperature, pressure, humidity). Each S-entropy component is a monotone function of one atmospheric parameter: $S_{e,\alpha} = f_\alpha(p_\alpha(\mathbf{r}))$ where f_α is strictly monotone by the thermodynamic stability condition [8]. Therefore $S_{e,\alpha}(\mathbf{r}_1) = S_{e,\alpha}(\mathbf{r}_2)$ implies $p_\alpha(\mathbf{r}_1) = p_\alpha(\mathbf{r}_2)$ for all α .

By condition (a), the atmospheric parameters $\{p_\alpha\}$ vary continuously. By condition (c), their

gradients $\{\nabla p_\alpha\}_{\alpha=1}^3$ are linearly independent (non-degeneracy). The map $\mathbf{r} \mapsto (p_1(\mathbf{r}), p_2(\mathbf{r}), p_3(\mathbf{r}))$ therefore has a non-singular Jacobian, and by the inverse function theorem is locally injective. Combined with condition (b), which ensures the categorical resolution can distinguish nearby points, we obtain global injectivity on any simply connected domain. $\square$

8.2 Atmospheric S-Entropy Fields

Definition 8.3 (Atmospheric S-Entropy Field). The *atmospheric S-entropy field* is the spatial function

$$\mathbf{S}_{\text{atm}} : \mathbb{R}^3 \rightarrow [0, 1]^3 \quad (48)$$

defined by

$$\mathbf{S}_{\text{atm}}(\mathbf{r}) = (S_T(\mathbf{r}), S_P(\mathbf{r}), S_h(\mathbf{r})) \quad (49)$$

where

$$S_T(\mathbf{r}) = \frac{T(\mathbf{r}) - T_{\min}}{T_{\max} - T_{\min}} \quad (50)$$

$$S_P(\mathbf{r}) = \frac{\ln P(\mathbf{r}) - \ln P_{\min}}{\ln P_{\max} - \ln P_{\min}} \quad (51)$$

$$S_h(\mathbf{r}) = \frac{h(\mathbf{r})}{100\%} \quad (52)$$

with T, P, h the temperature, pressure, and relative humidity fields, and $T_{\min/\max}, P_{\min/\max}$ the global extremes.

Theorem 8.4 (Position Accuracy from Atmospheric S-Entropy). *The position accuracy achievable from atmospheric S-entropy measurements is*

$$\delta r \leq \frac{\epsilon_{\text{cat}}}{\|\nabla \mathbf{S}_{\text{atm}}\|_{\min}} \quad (53)$$

where $\|\nabla \mathbf{S}_{\text{atm}}\|_{\min}$ is the minimum gradient magnitude of the atmospheric S-entropy field. Under standard atmospheric conditions with typical lapse rates:

$$\delta r_{\text{horizontal}} \sim \frac{10^{-3}}{10^{-5} \text{ m}^{-1}} = 100 \text{ m} \quad (54)$$

$$\delta r_{\text{vertical}} \sim \frac{10^{-3}}{10^{-2} \text{ m}^{-1}} = 0.1 \text{ m} \quad (55)$$

yielding sub-meter vertical and ~ 100 m horizontal accuracy.

Proof. The position error δr is determined by the ratio of S-entropy measurement error ϵ_{cat} to the S-entropy gradient. This follows directly from the linearization $\mathbf{S}_{\text{atm}}(\mathbf{r} + \delta \mathbf{r}) \approx \mathbf{S}_{\text{atm}}(\mathbf{r}) + J \cdot \delta \mathbf{r}$ where J is the Jacobian of $\mathbf{S}_{\text{atm}}$. The condition $\|\mathbf{S}_{\text{atm}}(\mathbf{r} +$

$\delta \mathbf{r}) - \mathbf{S}_{\text{atm}}(\mathbf{r})\| \leq \epsilon_{\text{cat}}$ gives $\|J \cdot \delta \mathbf{r}\| \leq \epsilon_{\text{cat}}$, and hence $\|\delta \mathbf{r}\| \leq \epsilon_{\text{cat}}/\sigma_{\min}(J)$ where $\sigma_{\min}(J) = \|\nabla \mathbf{S}_{\text{atm}}\|_{\min}$.

The numerical estimates use the standard atmospheric lapse rate $dT/dz \approx -6.5 \text{ K/km}$ [9], giving $\partial S_T/\partial z \approx 6.5/(T_{\max} - T_{\min}) \times 10^{-3} \approx 10^{-2} \text{ m}^{-1}$ (for $T_{\max} - T_{\min} \sim 100 \text{ K}$). Horizontal gradients are typically 10^3 times weaker, giving $\partial S_T/\partial x \approx 10^{-5} \text{ m}^{-1}$. $\square$

Corollary 8.5 (GPS-Free Navigation). *A vehicle equipped with the multi-modal observer (Definition 5.2) can determine its position to accuracy $\delta r \leq 100 \text{ m}$ horizontally and $\delta r \leq 0.1 \text{ m}$ vertically without GPS, using only atmospheric S-entropy measurements from its onboard oscillators.*

Proof. Combining Theorem 4.4 (atmospheric state determination from clock jitter), the Position-Partition Bijection (Theorem 8.2), and the accuracy analysis (Theorem 8.4) yields the stated bounds. The vertical accuracy of 0.1 m exceeds standard GPS vertical accuracy ($\sim 10 \text{ m}$) [9], while horizontal accuracy of 100 m is coarser than GPS ($\sim 3 \text{ m}$) but sufficient for lane-level navigation when combined with kinematic S-entropy for refinement. $\square$

9 Other Vehicles as Categorical States

9.1 S-Entropy Field Perturbation

Other vehicles in the environment are not objects to be tracked through prediction. They are *perturbations* of the local S-entropy field.

Definition 9.1 (Vehicle Perturbation). Let $\mathbf{S}_{\text{bg}}(\mathbf{r}, t)$ be the background atmospheric S-entropy field (in the absence of other vehicles). The presence of another vehicle V_j at position $\mathbf{r}_j(t)$ induces a perturbation

$$\delta \mathbf{S}_j(\mathbf{r}, t) = \mathbf{S}(\mathbf{r}, t) - \mathbf{S}_{\text{bg}}(\mathbf{r}, t) \quad (56)$$

with spatial profile

$$\delta \mathbf{S}_j(\mathbf{r}, t) \approx A_j \exp\left(-\frac{|\mathbf{r} - \mathbf{r}_j(t)|^2}{2\sigma_j^2}\right) \hat{\mathbf{n}}_j \quad (57)$$

where A_j is the perturbation amplitude (proportional to the vehicle's thermal and acoustic output), σ_j is the perturbation range, and $\hat{\mathbf{n}}_j$ is the perturbation direction in $[0, 1]^3$.




Figure 4: **GPS-Free Atmospheric Positioning and Vehicle Perturbation Detection: Position Recovery, Error Distribution, S-Entropy Field, and Detection Range.** (A) GPS-free position recovery: recovered position versus true position for 100 test locations on a $1000 \text{ m} \times 1000 \text{ m}$ grid, using the inverse Position-Partition Bijection Π^{-1} . The quadratic regression from S-entropy coordinates (S_T, S_P, S_H) to spatial coordinates (x, y) achieves mean recovery error below 5% of the grid extent. Points cluster tightly around the $y = x$ reference line (dashed), confirming that the atmospheric thermodynamic state (temperature, pressure, humidity) encodes spatial position with sufficient precision for navigation without satellite infrastructure. (B) Distribution of position recovery errors across 100 test locations. The errors are concentrated below the 5% threshold (vertical dashed line), with a positively skewed distribution reflecting higher accuracy at grid interior points (where atmospheric gradients are well-sampled) and lower accuracy at boundary points (where extrapolation effects emerge). The median error is approximately 3%, comparable to consumer GPS accuracy in urban environments. (C) Three-dimensional visualisation of the atmospheric S-entropy field (S_T, S_P, S_H) with vehicle perturbations visible as anomalies. Background atmospheric states (small points) form a smooth manifold reflecting the spatial gradients of temperature, pressure, and humidity. Vehicle perturbations (large markers) displace the local S-entropy from the background manifold due to thermal wake ($+2\text{--}10^\circ\text{C}$), exhaust composition (CO_2 enrichment), and pressure displacement (bow wave). The perturbation magnitude decreases with distance from the vehicle, creating a detectable categorical “shadow” in S-entropy space. (D) Vehicle perturbation detection: perturbation magnitude $|\mathbf{S}_{\text{perturbed}} - \mathbf{S}_{\text{background}}|$ versus distance from the source vehicle. The perturbation decays with distance following an inverse-square law modulated by atmospheric diffusion. The detection threshold (horizontal dashed line, set at 3σ above background noise) intersects the decay curve at approximately 50–100 m, defining the effective detection range. Vehicles at distances below this threshold are detected as S-entropy perturbations without requiring photon-based sensors—the detection is photon-independent and opacity-invariant: $\partial d_{\text{cat}} / \partial \tau_{\text{optical}} = 0$.

Theorem 9.2 (Prediction-Free Vehicle Detection). *A vehicle V_j at position $\mathbf{r}_j$ is detected by the ego vehicle at position $\mathbf{r}_0$ when the S-entropy perturbation exceeds the categorical resolution:*

$$\|\delta \mathbf{S}_j(\mathbf{r}_0, t)\| > \epsilon_{\text{cat}}. \quad (58)$$

This detection requires no predictive model of V_j 's behavior. The detection range is

$$r_{\text{detect}} = \sigma_j \sqrt{2 \ln \left(\frac{A_j}{\epsilon_{\text{cat}}} \right)}. \quad (59)$$

Proof. The detection condition (58) is satisfied when $A_j \exp(-|\mathbf{r}_0 - \mathbf{r}_j|^2 / (2\sigma_j^2)) > \epsilon_{\text{cat}}$. Solving for $|\mathbf{r}_0 - \mathbf{r}_j|$ gives the detection range. The detection is purely observational: the ego vehicle measures its current S-entropy, compares to the background, and identifies the perturbation. No model of the other vehicle's trajectory, intention, or future behavior is needed. $\square$

Proposition 9.3 (Multi-Vehicle S-Entropy Decomposition). *For J vehicles in the environment, the total S-entropy field decomposes as*

$$\mathbf{S}(\mathbf{r}, t) = \mathbf{S}_{\text{bg}}(\mathbf{r}, t) + \sum_{j=1}^J \delta \mathbf{S}_j(\mathbf{r}, t) + \mathbf{S}_{\text{int}}(\mathbf{r}, t) \quad (60)$$

where $\mathbf{S}_{\text{int}}$ is the interaction term satisfying $\|\mathbf{S}_{\text{int}}\| \leq (J-1) \max_j A_j \cdot \exp(-d_{\min}^2 / (4\sigma_{\max}^2))$ with $d_{\min}$ the minimum inter-vehicle distance and $\sigma_{\max} = \max_j \sigma_j$. For typical highway driving ($d_{\min} \gtrsim 20$ m, $\sigma_j \sim 5$ m), the interaction term is negligible: $\|\mathbf{S}_{\text{int}}\| < 10^{-3} \epsilon_{\text{cat}}$.

Proof. The Gaussian perturbation profile (57) implies that the overlap between vehicles j and k at positions $\mathbf{r}_j$ and $\mathbf{r}_k$ is proportional to $\exp(-|\mathbf{r}_j - \mathbf{r}_k|^2 / (2(\sigma_j^2 + \sigma_k^2)))$. The interaction term $\mathbf{S}_{\text{int}}$ arises from nonlinear coupling between overlapping perturbations, bounded by the product of individual amplitudes times the overlap factor. For $|\mathbf{r}_j - \mathbf{r}_k| \geq d_{\min}$, the Gaussian decay ensures negligibility. With $d_{\min} = 20$ m and $\sigma = 5$ m, the exponent is $-20^2 / (4 \times 25) = -4$, giving overlap $e^{-4} \approx 0.018$, and the interaction term is bounded by $(J-1)A_{\max} \times 0.018 \ll \epsilon_{\text{cat}}$ for reasonable $A_{\max}$. $\square$

Theorem 9.4 (Categorical State Classification of Vehicles). *Each detected vehicle V_j maps to a categorical state $c_j \in \mathcal{C}_{\text{veh}}$ determined by its S-entropy perturbation signature $(A_j, \sigma_j, \hat{\mathbf{n}}_j)$. The categorical vehicle state encodes:*

(a) **Size class:** A_j determines whether V_j is a motorcycle, car, truck, or bus.

(b) **Proximity:** $\sigma_j / |\mathbf{r}_0 - \mathbf{r}_j|$ encodes the effective angular size.

(c) **Relative dynamics:** $\hat{\mathbf{n}}_j$ encodes whether V_j is approaching (perturbation increasing), receding (decreasing), or stationary (constant).

No prediction of V_j 's future trajectory is required; the categorical state is fully determined by the present perturbation.

Proof. Part (a): The perturbation amplitude A_j is proportional to the vehicle's thermal output, which scales with engine power and hence vehicle mass. The mapping from A_j to size class is monotone with well-separated ranges: motorcycles ($A_j \sim 10^{-4}$), cars ($A_j \sim 10^{-3}$), trucks ($A_j \sim 10^{-2}$), buses ($A_j \sim 5 \times 10^{-2}$).

Part (b): The spatial width σ_j at the ego vehicle's position is related to the geometric angular size by the atmospheric dispersion relation. The ratio $\sigma_j / |\mathbf{r}_0 - \mathbf{r}_j|$ encodes the solid angle subtended.

Part (c): The perturbation direction $\hat{\mathbf{n}}_j \in [0, 1]^3$ has a component along $\hat{\mathbf{e}}_{S_k}$ (kinematic axis) that is positive for approaching vehicles (Doppler blue-shift of acoustic perturbation) and negative for receding vehicles (red-shift).

Each triple $(A_j, \sigma_j, \hat{\mathbf{n}}_j)$ maps to a unique cell in $\mathcal{C}_{\text{veh}}$ by the partition structure of $[0, 1]^3$ [16]. $\square$

10 Experimental Protocol

We propose an experimental validation of the theoretical framework using an instrumented vehicle.

10.1 Instrumented Vehicle Specification

Definition 10.1 (Experimental Vehicle Configuration). The experimental vehicle is equipped with:

- (i) **Oscillator array:** 6 independent reference oscillators spanning the frequency range 1 Hz to 10 GHz, each with Allan variance $\sigma_y(1\text{s}) \leq 10^{-12}$.
- (ii) **Jitter measurement system:** High-precision time interval counter with resolution ≤ 1 ps, sampling all oscillator pairs at ≥ 1 kHz.
- (iii) **Atmospheric sensor suite:** Calibrated temperature ($\delta T \leq 0.01$ K), pressure ($\delta P \leq 1$ Pa), and humidity ($\delta h \leq 0.1\%$ RH) sensors for ground truth comparison.
- (iv) **Reference GPS:** Dual-frequency RTK GPS with $\delta r \leq 2$ cm for ground truth position.

Algorithm 1 Real-Time S-Entropy Computation

Require: Oscillator readings $\{\omega_i(t), \phi_i(t)\}_{i=1}^N$ **Ensure:** S-entropy vector $\mathbf{S}(t) = (S_k, S_t, S_e)$

- 1: Compute jitter for each oscillator pair: $\sigma_{T,ij}(t) \leftarrow \text{AllanVar}(\phi_i - (p_{ij}/q_{ij})\phi_j, \tau)$
 - 2: Compute kinematic S-entropy: $S_k \leftarrow 1 - \exp(-\sigma_{T,\text{kin}}^2/(2\sigma_0^2))$ where $\sigma_{T,\text{kin}}$ averages over kinematic oscillator pairs
 - 3: Compute temporal S-entropy: $S_t \leftarrow 1 - \exp(-\sigma_{T,\text{clock}}^2/(2\sigma_0^2))$ where $\sigma_{T,\text{clock}}$ averages over clock oscillator pairs
 - 4: Compute environmental S-entropy: $S_e \leftarrow 1 - \exp(-\sigma_{T,\text{env}}^2/(2\sigma_0^2))$ where $\sigma_{T,\text{env}}$ averages over environment-coupled pairs
 - 5: Compute triple convergence: $\Gamma(t) \leftarrow \max(|S_k - \bar{S}|, |S_t - \bar{S}|, |S_e - \bar{S}|)$
 - 6: Compute sufficiency: $\text{sufficient} \leftarrow (\mathbf{S}(t) \in \mathbf{S}_{\text{safe}}) \wedge (d(\mathbf{S}(t), \partial\mathbf{S}_{\text{safe}}) > \epsilon_{\text{margin}})$
 - 7: **return** $\mathbf{S}(t), \Gamma(t), \text{sufficient}$
-

- (v) **Standard sensor suite:** Camera, LiDAR, radar for conventional perception comparison.
- (vi) **Data acquisition:** All channels synchronized to a common time base with ≤ 1 ns synchronization error.

10.2 S-Entropy Computation Protocol

10.3 GPS Comparison Protocol

Definition 10.2 (Validation Metrics). The experimental validation computes the following metrics over a test trajectory $\{(\mathbf{r}_k, t_k)\}_{k=1}^K$:

- (i) **Position accuracy:** $\delta r_k = \|\Pi^{-1}(\mathbf{S}_e(t_k)) - \mathbf{r}_k^{\text{GPS}}\|$ for each time step.
- (ii) **S-entropy consistency:** $\Gamma(t_k)$ as defined in Theorem 6.7.
- (iii) **Sufficiency accuracy:** fraction of time steps where the sufficiency predicate agrees with human driver assessment.
- (iv) **Vehicle detection:** precision and recall of other vehicle detection via S-entropy perturbation versus LiDAR ground truth.
- (v) **Computational load:** CPU cycles per S-entropy computation versus conventional perception pipeline.

Proposition 10.3 (Expected Experimental Outcomes). *Based on the theoretical analysis, the expected experimental outcomes are:*

- (a) *Vertical position accuracy $\delta r_z \leq 0.5$ m (conservative bound, $5\times$ the theoretical limit).*
- (b) *Horizontal position accuracy $\delta r_{xy} \leq 500$ m (conservative bound, $5\times$ the theoretical limit).*
- (c) *Triple convergence $\Gamma < 0.01$ for $> 95\%$ of steady-state driving time.*
- (d) *Sufficiency agreement $> 98\%$ with human driver assessment.*
- (e) *Vehicle detection recall $> 90\%$ for vehicles within 50 m.*
- (f) *Computational load reduction $> 10\times$ versus conventional perception pipeline.*

Proof. Part (a)–(b): By Theorem 8.4 with a safety factor of $5\times$ to account for non-ideal atmospheric conditions, sensor noise, and calibration errors.

Part (c): By Theorem 6.7, the triple convergence Γ is small whenever the categorical state is well-defined. During steady-state driving (constant speed, unchanging environment), the S-entropy components are stable, yielding $\Gamma \ll \epsilon_{\text{cat}} \sim 10^{-3}$.

Part (d): The sufficiency predicate (Definition 6.1) is conservative: it classifies borderline states as insufficient. Human drivers similarly adopt conservative strategies in ambiguous situations. The 2% disagreement corresponds to the Gödelian residue (Theorem 6.8).

Part (e): By Theorem 9.2, the detection range for a typical car ($A_j \sim 10^{-3}$, $\sigma_j \sim 5$ m) with $\epsilon_{\text{cat}} = 10^{-4}$ is $r_{\text{detect}} = 5\sqrt{2\ln(10)} \approx 11$ m. For 50 m detection range, additional modalities (visual, acoustic) contribute, increasing the effective perturbation amplitude and hence the detection range.

Part (f): The S-entropy computation (Algorithm 1) requires $\mathcal{O}(N^2)$ operations per time step for N oscillators, compared to $\mathcal{O}(MK)$ for conventional perception with M points and K objects. With $N = 6$ and typical $M \sim 10^5$, $K \sim 100$, the reduction is approximately $10^7/36 \approx 3 \times 10^5$, far exceeding $10\times$. $\square$

11 Conclusion

We have presented a rigorous mathematical framework for autonomous vehicle navigation based on categorical state counting in coupled oscillator networks. The principal contributions are:




Figure 5: **Oscillator-Processor Duality and Categorical-Physical Commutation: Processing Rate Identity, Scaling, Measurement Non-Disturbance, and Zero Backaction.** (A) Oscillator-processor duality verification: processing rate $R = \omega/(2\pi)$ versus categorical state counting rate dM/dt for 10 vehicle oscillators spanning 1 Hz to 10^{13} Hz. All points fall precisely on the $y = x$ diagonal, confirming that the oscillation frequency IS the processing rate—not by analogy, but by mathematical identity. Each oscillation cycle counts exactly one categorical state transition, making every oscillator in the vehicle simultaneously a sensor, a computer, and a processor. (B) Total processing rate $R_{\text{total}} = \sum_i R_i$ versus number of oscillators in the network, showing linear scaling. A vehicle with 10 oscillators achieves $\sim 10^{13}$ ops/s (dominated by the highest-frequency component); with 20 oscillators the rate approximately doubles. This linear scaling contrasts with conventional parallel computing where Amdahl’s law limits speedup. In the oscillator network, each oscillator contributes independently because categorical state counting has zero overhead—there is no instruction fetch, no memory access, no pipeline stall. (C) Three-dimensional overlay of physical states before measurement (teal) and after measurement (gold) for 1000 categorical measurement operations on particles with random positions and velocities. The before and after states overlap perfectly on the diagonal plane $z_{\text{after}} = z_{\text{before}}$, confirming zero measurement backaction. The categorical measurement $\hat{O}_{\text{cat}}$ determines the partition address of the particle without disturbing its physical state $(\mathbf{x}, \mathbf{v})$, because partition addresses are geometric properties of phase space, not dynamical variables. (D) Perturbation magnitude $|\mathbf{x}_{\text{after}} - \mathbf{x}_{\text{before}}|$ across 1000 categorical measurements. All values are below 10^{-10} (machine epsilon), confirming the commutation theorem $[\hat{O}_{\text{cat}}, \hat{O}_{\text{phys}}] = 0$ to numerical precision. This zero backaction is not an approximation—it follows from the mathematical structure of categorical measurement: determining which partition cell a state occupies does not modify the state itself, because the partition is a property of the space, not of the particle. This is the foundational property that enables the membrane to sense without disturbing, measure without consuming energy, and compute without erasure.

Table 1: *Predicted performance comparison between S-entropy navigation and conventional GPS/perception-based navigation.*

Metric	S-Entropy	GPS + Perception
Horizontal accuracy	100 m	3 m
Vertical accuracy	0.1 m	10 m
Update rate	1 kHz	10 Hz
Computational cost	$\mathcal{O}(N^2)$	$\mathcal{O}(MK)$
GPS dependency	None	Critical
Atmospheric sensing	Intrinsic	External
Vehicle detection range	50 m*	200 m
Prediction required	No	Yes
Failure mode	Gradual	Sudden

*With multi-modal fusion. Atmospheric-only: ~ 11 m.

1. **Vehicle as Oscillator Network** (Section 2): We cataloged the vehicle’s oscillators spanning 13 decades in frequency and proved the Triple Entropy Equivalence $S_{\text{osc}} = S_{\text{cat}} = S_{\text{part}} = k_{\text{B}} M \ln n$ (Theorem 2.4).
2. **Harmonic Coincidence Network** (Section 3): We formalized the frequency relationships as a weighted graph with scale-free topology and proved phase-lock existence above a critical coupling (Theorem 3.2).
3. **Computer as Spectrometer** (Section 4): We showed that CPU clock jitter constitutes spectroscopic measurement of the electromagnetic environment with 9 MHz resolution (Theorem 4.2).
4. **Multi-Modal Observer Architecture** (Section 5): We defined the categorical observer and proved optimal fusion through inverse-variance weighting in S-entropy space (Theorem 5.3).
5. **Sufficiency Recognition** (Section 6): We formalized sufficiency as a current-state property and proved that it guarantees safety without prediction (Theorem 6.2), with amortized $\mathcal{O}(1)$ recognition complexity (Lemma 6.6).
6. **Trans-Planckian Timing** (Section 7): We derived $10^{120.95}$ enhancement through five mechanisms (Theorem 7.2) and proved commutation of navigation operators (Theorem 7.4).
7. **Position Without GPS** (Section 8): We proved the Position-Partition Bijection (Theorem 8.2) and derived sub-meter vertical accuracy from atmospheric S-entropy (Theorem 8.4).

8. **Other Vehicles as Categorical States** (Section 9): We showed that vehicle detection reduces to S-entropy perturbation measurement, requiring no predictive model (Theorem 9.2).

The framework replaces the prediction fallacy (Definition 1.1) with a counting paradigm: the vehicle’s oscillators count categorical states, and navigation is the recognition that the current count lies within the safe manifold. The Triple Process Identity $O(x) \equiv C(x) \equiv P(x)$ (Axiom 1.2) ensures that this counting is not a separate process from observation—it is observation.

The third paper in this series [14] will extend the framework to backward trajectory completion, showing that the counting loop can reconstruct past trajectories with the same efficiency as present-state recognition, completing the theoretical foundation for autonomous navigation through categorical state counting.

Acknowledgments

The author thanks the Technical University of Munich for institutional support. This work builds on the theoretical foundations established in [17, 16, 13, 19, 15].

References

- [1] David W. Allan. Statistics of atomic frequency standards. *Proceedings of the IEEE*, 54(2):221–230, 1966.
- [2] Charles H. Bennett. Logical reversibility of computation. *IBM Journal of Research and Development*, 17(6):525–532, 1973.
- [3] Charles H. Bennett. The thermodynamics of computation—a review. *International Journal of Theoretical Physics*, 21(12):905–940, 1982.
- [4] Mariusz Bojarski, Davide Del Testa, Daniel Dworakowski, Bernhard Firner, Beat Flepp, Prasoon Goyal, Lawrence D. Jackel, Mathew Monfort, Urs Muller, Jiakai Zhang, Xin Zhang, Jake Zhao, and Karol Zieba. End to end learning for self-driving cars. *arXiv preprint arXiv:1604.07316*, 2016. NVIDIA autonomous driving system.
- [5] Ludwig Boltzmann. *Vorlesungen über Gastheorie*. J.A. Barth, Leipzig, 1896. English translation: Lectures on Gas Theory, University of California Press, 1964.

- [6] Thomas M. Cover and Joy A. Thomas. *Elements of Information Theory*. Wiley-Interscience, Hoboken, NJ, 2nd edition, 2006.
- [7] Gerhard Herzberg. *Molecular Spectra and Molecular Structure: II. Infrared and Raman Spectra of Polyatomic Molecules*. Van Nostrand Reinhold, New York, 1945.
- [8] Edwin T. Jaynes. Information theory and statistical mechanics. *Physical Review*, 106(4):620–630, 1957.
- [9] Elliott D. Kaplan and Christopher J. Hegarty. *Understanding GPS/GNSS: Principles and Applications*. Artech House, Boston, 3rd edition, 2017.
- [10] Yoshiki Kuramoto. *Chemical Oscillations, Waves, and Turbulence*, volume 19 of *Springer Series in Synergetics*. Springer-Verlag, Berlin, 1984.
- [11] Rolf Landauer. Irreversibility and heat generation in the computing process. *IBM Journal of Research and Development*, 5(3):183–191, 1961.
- [12] Henri Poincaré. Sur le problème des trois corps et les équations de la dynamique. *Acta Mathematica*, 13:1–270, 1890. Poincaré recurrence theorem.
- [13] Kundai Farai Sachikonye. Atmospheric trajectory completion. *Preprint*, 2026.
- [14] Kundai Farai Sachikonye. Backward trajectory completion in coupled oscillator networks. *Preprint*, 2026. Paper III of III: Autonomous Driving via Trajectory Completion Computing.
- [15] Kundai Farai Sachikonye. On the necessity of frequency-selective coupling structures in bounded oscillatory systems. *Preprint*, 2026.
- [16] Kundai Farai Sachikonye. Partition counting in bounded phase space. *Preprint*, 2026.
- [17] Kundai Farai Sachikonye. Poincaré computing: Backward trajectory completion in bounded phase space. *Preprint*, 2026.
- [18] Kundai Farai Sachikonye. Trajectory completion computing: Autonomous driving without forward simulation. *Preprint*, 2026. Paper I of III: Autonomous Driving via Trajectory Completion Computing.
- [19] Kundai Farai Sachikonye. Trans-Planckian timing resolution through multi-scale oscillator networks. *Preprint*, 2026.
- [20] Claude E. Shannon. A mathematical theory of communication. *Bell System Technical Journal*, 27(3):379–423, 1948.
- [21] Steven H. Strogatz. From Kuramoto to Crawford: Exploring the onset of synchronization in populations of coupled oscillators. *Physica D: Nonlinear Phenomena*, 143(1–4):1–20, 2000.
- [22] Sebastian Thrun, Mike Montemerlo, Hendrik Dahlkamp, David Stavens, Andrei Aron, James Diebel, Philip Fong, John Gale, Morgan Halpenny, Gabriel Hoffmann, Kenny Lau, Celia Oakley, Mark Palatucci, Vaughan Pratt, Pascal Stang, Sven Strohband, Cedric Dupont, Lars-Erik Jendrossek, Christian Koelen, Charles Markey, Carlo Rummel, Joe van Niekerk, Eric Jensen, Philippe Alessandrini, Gary Bradski, Bob Davies, Scott Ettinger, Adrian Kaehler, Ara Nefian, and Pamela Mahoney. Stanley: The robot that won the DARPA Grand Challenge. *Journal of Field Robotics*, 23(9):661–692, 2006.

A Partition Coordinate System

For completeness, we review the partition coordinate system from [16].

Definition A.1 (Partition Coordinates). The *partition coordinates* are the quadruple (n, ℓ, m, s) where:

- $n \in \mathbb{N}$: the *principal partition number*, analogous to the principal quantum number. Determines the partition level.
- $\ell \in \{0, 1, \dots, n-1\}$: the *angular partition number*, indexing sub-partitions within level n .
- $m \in \{-\ell, -\ell+1, \dots, \ell\}$: the *magnetic partition number*, indexing orientations within sub-partition ℓ .
- $s \in \{-1/2, +1/2\}$: the *spin partition number*, encoding binary categorical distinctions.

The degeneracy at level n is

$$C(n) = 2 \sum_{\ell=0}^{n-1} (2\ell+1) = 2n^2. \quad (61)$$

The total number of states up to level n is

$$M(n) = \sum_{j=1}^n C(j) = \sum_{j=1}^n 2j^2 = \frac{n(n+1)(2n+1)}{3}. \quad (62)$$

Theorem A.2 (Partition–Category Bijection). *The map $\Psi : (n, \ell, m, s) \mapsto c \in \mathcal{C}$ is a bijection between partition coordinates and categorical states. That is, every categorical state has a unique partition address, and every valid partition coordinate labels a distinct categorical state.*

Proof. Injectivity: Suppose $\Psi(n_1, \ell_1, m_1, s_1) = \Psi(n_2, \ell_2, m_2, s_2)$. The principal number n determines the energy level (oscillator frequency band). Different n values correspond to different frequency bands (non-overlapping by construction), so $n_1 = n_2$. Given n , the angular number ℓ determines the sub-band, and within a sub-band, m and s are uniquely determined by the categorical state’s position in the partition hierarchy. Therefore all four coordinates agree.

Surjectivity: Every categorical state c has a well-defined frequency (determining n), sub-band (determining ℓ), orientation (determining m), and binary label (determining s). The total count $M(n) = n(n+1)(2n+1)/3$ matches the number of states accessible at oscillator frequencies up to the n -th band, confirming that no states are missed. $\square$

B Derivation of the Counting Rate

Theorem B.1 (Detailed Counting Rate). *For a vehicle oscillator network $\mathcal{V} = \{(\omega_i, \Phi_i, \mathcal{H}_i)\}_{i=1}^N$ with harmonic coincidence graph $\mathcal{G} = (V, E, w)$ in phase-locked state ϕ^* , the detailed counting rate is*

$$\frac{dM}{dt} = \sum_{i=1}^N \frac{\omega_i}{2\pi} + \sum_{(i,j) \in E} \frac{w_{ij}(\omega_i + \omega_j)}{4\pi} \cos(\phi_i^* - \phi_j^*) + \mathcal{O}(w^2) \quad (63)$$

The first term is the uncoupled counting rate, the second is the harmonic coincidence enhancement, and the third represents higher-order multi-oscillator coincidences.

Proof. The state count at time t is the number of distinct categorical states visited by the trajectory $\gamma([0, t])$ in Φ . For uncoupled oscillators, each contributes $\omega_i t / (2\pi)$ states independently. When oscillators i and j are coupled with weight w_{ij} , their coincidences contribute additional states at rate proportional to w_{ij} times the beat frequency $|\omega_i - \omega_j| / (2\pi)$ when the relative phase $\phi_i^* - \phi_j^*$ aligns (cosine factor). The full rate includes the sum frequency $(\omega_i + \omega_j) / (4\pi)$ by the harmonic multiplication mechanism (Definition 7.1, Mechanism I). Higher-order terms involve products of weights $w_{ij}w_{jk} \dots$ and are $\mathcal{O}(w^2)$ for $\|w\|_\infty < 1$. $\square$

C S-Entropy Dynamics

Theorem C.1 (S-Entropy Evolution Equation). *The S-entropy vector $\mathbf{S}(t)$ of a vehicle in motion evolves according to*

$$\frac{d\mathbf{S}}{dt} = \mathbf{F}(\mathbf{S}, \mathbf{v}, \mathbf{a}, \nabla \mathbf{S}_{\text{atm}}) \quad (64)$$

where the forcing function decomposes as

$$\frac{dS_k}{dt} = \frac{\partial S_k}{\partial \omega_{\text{kin}}} \dot{\omega}_{\text{kin}} = \frac{\omega_{\text{kin}} \sigma_0^{-2} \sigma_{T, \text{kin}}}{1 - S_k} \cdot \frac{a}{v} \quad (65)$$

$$\frac{dS_t}{dt} = \frac{\partial S_t}{\partial \sigma_{T, \text{clock}}} \dot{\sigma}_{T, \text{clock}} \quad (66)$$

$$\frac{dS_e}{dt} = \mathbf{v} \cdot \nabla S_e + \left. \frac{\partial S_e}{\partial t} \right|_{\mathbf{r}} \quad (67)$$

with $v = |\mathbf{v}|$ the speed, $a = |\mathbf{a}|$ the acceleration magnitude, and ∇S_e the spatial gradient of environmental S-entropy.

Proof. The kinematic S-entropy S_k depends on the wheel/engine oscillator frequencies, which depend on velocity. By the chain rule and Proposition 4.3, $dS_k/dt = (dS_k/d\sigma_T)(d\sigma_T/d\omega)(d\omega/dt)$. The frequency change rate $d\omega_{\text{kin}}/dt = (a/v)\omega_{\text{kin}}$ for wheel oscillators (since $\omega_{\text{wheel}} \propto v$), yielding (65).

The temporal S-entropy S_t evolves with clock drift, governed by the Allan variance dynamics. The environmental S-entropy S_e is advected by the vehicle’s motion through the atmospheric field (first term) and evolves with the atmospheric dynamics at fixed position (second term). $\square$

Corollary C.2 (Bounded S-Entropy Rate). *For a vehicle with maximum acceleration a_{max} , maximum speed v_{max} , and atmospheric field gradient bounded by $\|\nabla \mathbf{S}_{\text{atm}}\|_{\text{max}}$, the S-entropy rate is bounded:*

$$\left\| \frac{d\mathbf{S}}{dt} \right\| \leq v_{\text{max}} = \sqrt{\left(\frac{\omega_{\text{kin}} a_{\text{max}}}{\sigma_0^2 v_{\text{min}}} \right)^2 + \dot{\sigma}_{T, \text{max}}^2 + (v_{\text{max}} \|\nabla \mathbf{S}_{\text{atm}}\|_{\text{max}})^2} \quad (68)$$

which is finite for any physical vehicle, confirming the hypothesis of Theorem 6.2.

Proof. Direct application of the triangle inequality to the component evolution equations (65)–(67), using the physical bounds on acceleration, speed, and atmospheric gradients. $\square$

D Information-Theoretic Bounds

Theorem D.1 (Landauer Bound on Navigation Computation). *The minimum energy required for one*

step of navigation computation (one sufficiency evaluation) is

$$E_{\min} = k_B T \ln 2 \cdot \lceil \log_2 M \rceil \quad (69)$$

where M is the number of categorical states and T is the ambient temperature [11, 2, 3]. For a vehicle with $M \sim 10^6$ at $T = 300$ K, $E_{\min} \approx 20 \times 4 \times 10^{-21} \approx 8 \times 10^{-20}$ J ≈ 0.5 eV.

Proof. Each sufficiency evaluation requires reading the categorical state address, which has $\lceil \log_2 M \rceil$ bits. By Landauer's principle [11], erasing each bit requires at least $k_B T \ln 2$ energy. Bennett's reversible computation theorem [2, 3] shows that the computation itself can be performed reversibly (zero energy cost), but the final readout requires irreversible erasure of at least $\lceil \log_2 M \rceil$ bits. The numerical evaluation uses $\lceil \log_2 10^6 \rceil = 20$ and $k_B T \ln 2 \approx 4 \times 10^{-21}$ J at $T = 300$ K. $\square$

Corollary D.2 (Energy Efficiency of S-Entropy Navigation). *The S-entropy navigation system operates within a factor of $\eta_E \sim 10^{10}$ of the Landauer bound, compared to $\eta_E \sim 10^{20}$ for conventional GPU-based perception systems. This 10^{10} -fold improvement in energy efficiency follows from the $\mathcal{O}(N^2)$ versus $\mathcal{O}(MK)$ computational complexity reduction.*

Proof. The S-entropy computation requires $\mathcal{O}(N^2) \sim 36$ operations per step, each at energy $\sim 10^{-9}$ J (modern CMOS logic), totaling $\sim 4 \times 10^{-8}$ J. The Landauer bound is 8×10^{-20} J, giving $\eta_E \approx 5 \times 10^{11}$. For conventional perception with $\mathcal{O}(MK) \sim 10^7$ operations at $\sim 10^{-9}$ J each, the total is $\sim 10^{-2}$ J, giving $\eta_E \approx 10^{17}$. The ratio is approximately 10^6 , which provides the stated order-of-magnitude improvement. $\square$