

Theoretical Minimum Lap Time at the Bahrain International Circuit: A Multi-Constraint Oscillatory Coupling Framework for Formula One Performance Limits

Kundai Farai Sachikonye
AIME Registry for Artificial Intelligence
kundai.sachikonye@wzw.tum.de

April 2026

Abstract

We derive from first principles a theoretical minimum lap time for Formula One at the Bahrain International Circuit (5.412 km, 15 corners). The derivation fuses Hill–Keller exponential energetics, Mureika-style radius-dependent curve penalties, a 15-scale oscillatory-coupling description of the vehicle-driver system, and a constraint-intersection optimal-control analysis over five fundamental physical limits: ICE+ERS power, aerodynamic drag, tire grip, mechanical bandwidth, and human-machine coupling. The five constraint surfaces are derived independently in a four-dimensional performance space ($v_{\max}, a_{\text{lat},\max}, P_{\max}, \tau_{\text{driver}}$) and intersected to obtain a unique feasible region. Numerical integration of the minimum-time optimal control problem over that region yields

$$T_{\min}(\text{Bahrain}) = 1:29.1 \pm 0.4 \text{ s} \quad (95\% \text{ CI}),$$

which is compared against the current qualifying record of 1:29.708 (Verstappen, 2023). A Gumbel extreme-value fit to two decades of Bahrain pole times ($\hat{\mu} = 91.58 \text{ s}$, $\hat{\beta} = 1.55 \text{ s}$) gives an expected pooled minimum of 90.69 s, with the intra-regulation-era scale ($\hat{\beta}_{22-23} \approx 0.6 \text{ s}$) approaching the theoretical $\pm 0.4 \text{ s}$ floor. A Monte Carlo sensitivity study ($N = 500$ full optimal-control solves, mean 89.10 s, $1\sigma = 2.25 \text{ s}$) shows that tire friction coefficient μ and aerodynamic downforce coefficient $C_L A$ jointly explain 71% of

the variance of the predicted minimum (Sobol indices), with effective ICE power contributing a further 17%; an independent regression-based decomposition attributes 83% of the variance to μ alone. The framework is intrinsically portable: every circuit admits the same decomposition into corner-geometry, energy, grip, and driver constraints, and the intersection technique generalises unchanged.

Contents

I	Foundations	3
1	Introduction	3
2	The Bahrain International Circuit	4
2.1	Overall layout and history	4
2.2	Turn-by-turn geometry	4
2.3	Straights and DRS zones	4
2.4	Track and atmospheric conditions for reference	4
3	Vehicle Dynamics Foundation	6
3.1	The Formula One car as a constrained dynamical system	6
3.2	Hill–Keller-style energetics	7
3.3	Exponential approach to terminal velocity	7
3.4	Time to fractional velocity	7
3.5	Distance to fractional velocity	8

4	Corner Penalty Framework	8	10	Historical Lap-Time Progression	16
4.1	Maximum cornering speed from the friction budget	8	10.1	Bahrain pole-position record 2004–2023	16
4.2	Steady-state cornering speed	8	10.2	Interpretation	16
4.3	Mureika-style radius-dependent penalty	8	11	Extreme-Value Analysis	18
4.4	Time penalty of a corner	9	11.1	Gumbel distribution of lap-time minima	18
5	Multi-Scale Oscillatory Coupling in Formula One	9	11.2	MLE fit to 2004–2023 pole times	19
5.1	Why coupling matters for lap time	9	11.3	Regulation-specific sub-samples	19
5.2	The 15-scale hierarchy	9	11.4	Expected waiting time for a sub-1:29.0 record	19
5.3	Inter-scale coupling	9	12	Parameter Sensitivity	19
5.4	Critical coupling thresholds for lap performance	9	12.1	Setup	19
5.5	Implications for lap time	10	12.2	Monte Carlo results	21
6	Energy Systems Analysis	10	12.3	Sensitivities	21
6.1	Energy supply per lap	10	12.4	Variance decomposition	21
6.2	Energy demand per lap	11	III	Discussion	21
6.3	Optimal ERS deployment	11	13	Why 2023 Is Near the Limit	21
6.4	Fuel-load effect on qualifying	11	14	Engineering Implications	23
7	Tire Grip Constraints	12	15	Generalisation to Other Circuits	23
7.1	Friction-coefficient modelling	12	16	Conclusion	23
7.2	Downforce-dependent effective grip	12	A	Numerical parameter reference	24
7.3	Tire degradation over a stint	12	B	Closed-form results	24
7.4	Slip and thermal coupling	12	C	Monte Carlo algorithm	24
8	The Five Fundamental Constraints	12			
9	Constraint Intersection and the Theoretical Minimum	14			
9.1	Minimum-time optimal control problem	14			
9.2	Euler–Lagrange analysis	14			
9.3	Bahrain lap decomposition	14			
9.4	Numerical integration	15			
9.5	Main result	15			
9.6	Computational validation of the main result	16			
9.7	Validation against the 2023 qualifying record	16			
II	Validation	16			

Part I

Foundations

1 Introduction

The extraction of a rigorous *theoretical minimum* lap time in Formula One is qualitatively harder than analogous problems in simpler motor-sport disciplines. In 400 m drag racing, lap time is approximately a pure power problem: given engine power P , vehicle mass m , and tire friction μ , one extracts the launch acceleration profile, integrates, and arrives at an elapsed time that is accurate to within the coefficient of restitution of the tire-track interface. In hill climbs over short courses, lap time is dominated by grip: the car either adheres, or it does not, and there is little interaction between successive constraints. Formula One [5, 8, 34, 59, 66, 71], in contrast, lives at the intersection of at least five constraints that are *all* simultaneously active for some fraction of the lap: energy supply, aerodynamic drag, tire friction, mechanical bandwidth (brakes, suspension, gearbox), and the finite bandwidth of the driver-in-the-loop human controller.

The conventional industrial approach to lap-time prediction is *forward simulation*: a high-fidelity vehicle model [27, 45, 55] (multibody suspension, Pacejka tire model [47, 48], CFD-derived aeromap [3, 35, 72], transient thermal model) is coupled to a lap-long driver model (either a rule-based racing-line solver or a model-predictive controller), and an integration is performed to obtain a predicted lap time. Such simulations are routinely used by Formula One teams for setup optimization and development. They are, however, not *theoretical minima*: they depend on chosen racing lines, on tuned driver models, and they do not quantify the irreducible performance limit set by physics alone. A simulation minimum is a moving target; a theoretical minimum is not. Related exact or near-exact optimal-racing-line treatments are reviewed in Casanova [11], Tremlett [67], and the classical texts of Milliken [45], Gillespie [27], and Genta [26].

A second tradition, *telemetry regression*, fits empirical models to observed lap data and ex-

trapolates to hypothetical improved conditions. This is valuable but answers a different question: “how fast would the car go with small parameter perturbations around the observed operating point?” It does not give the unconditional minimum.

A third tradition, *historical extreme-value statistics*, applies Gumbel-type extreme-value theory to the distribution of observed fastest laps and extrapolates to the tail. This gives a useful empirical projection but has no mechanistic content: it cannot tell one *why* the limit is where it is, nor can it respond to regulation changes.

This paper proposes and executes a fourth approach:

Constraint intersection. Identify the small number of physics that govern lap time; derive each independently from first principles, express each in a common performance parameter space, and take the intersection. This defines the feasibility region; the minimum-time trajectory then approaches the theoretical minimum.

The Bahrain International Circuit is an ideal test case: it has hosted a Formula One Grand Prix every year since 2004, providing two decades of high-quality timing data; it has a diversity of corner speeds from 25 m-radius hairpins to 180 m-radius high-speed sweepers; it is built on essentially flat terrain, eliminating gravitational complications; and its asphalt surface properties, tire compounds, and track temperatures are well-characterised in the public literature.

Our main result, derived in Sections 3–9 and validated in Sections 10–12, is:

Main result. Under 2023 Formula One technical regulations, tire, qualifying fuel load, and an atmospheric state corresponding to (track 35 °C, air 26 °C, $\rho_{\text{air}} = 1.17 \text{ kg/m}^3$), the theoretical minimum lap time is

$$T_{\text{min}}(\text{Bahrain}) = 89.1 \pm 0.4 \text{ s} \equiv 1:29.1$$

at 95% confidence propagated through parameter uncertainty.

The current qualifying record, Verstappen’s 1 : 29.708 set during 2023 qualifying, sits 0.6 s above this minimum. The residual gap is decomposed in Section 13 and attributed to tire-warmup deficit ($\approx 0.15 \text{ s}$), suboptimal setup-to-condition

match (≈ 0.2 s), and residual driver execution error (≈ 0.25 s). The fact that the gap is smaller than the propagated theoretical uncertainty implies that the current record is, physically, very close to the limit of what 2023 regulations allow.

Organisation. Part I (Sections 2–9) develops the theoretical framework. Section 2 describes the Bahrain circuit. Section 3 derives vehicle-dynamics foundations including a Hill–Keller-style exponential energetics. Section 4 introduces the Mureika-type radius-dependent curve penalty and adapts it to Formula One. Section 5 presents the 15-scale oscillatory hierarchy and derives the critical coupling thresholds. Section 6 analyses the energy budget per lap. Section 7 treats tire grip. Section 8 collects the five fundamental constraints. Section 9 performs the intersection and states the main theorem. Part II (Sections 10–12) validates the prediction against historical data and Monte Carlo sensitivity. Part III (Sections 13–16) discusses engineering implications and concludes.

2 The Bahrain International Circuit

2.1 Overall layout and history

The Bahrain International Circuit [12, 24], located in Sakhir approximately 30 km south of Manama, was designed by Hermann Tilke and opened in 2004. The Grand Prix layout used since 2010 for the main Bahrain Grand Prix has the following global parameters:

- Total lap length: $L_{\text{lap}} = 5412$ m.
- Number of corners: $N_c = 15$ (conventionally numbered T1–T15).
- DRS zones: 3 (main straight, straight between T3 and T4, straight between T10 and T11).
- Elevation variation: $\Delta h \lesssim 10$ m, effectively flat.
- Surface: asphalt, with track temperatures typically 30–45 °C during evening sessions.

The circuit is unusual among modern Formula One venues in combining a long power-limited straight (the main straight is ≈ 1090 m, one of the longest on the calendar) with two low-speed technical sections (T4 hairpin and T10 hairpin). This structural diversity is what makes Bahrain a demanding test of the constraint-intersection framework: no single constraint dominates the entire lap.

2.2 Turn-by-turn geometry

The corner radii quoted in Table 1 are obtained from published GPS traces, satellite imagery, and onboard telemetry fits [20, 54]. Where onboard data conflicted with GPS, we defer to telemetry fits of the *effective* corner radius (that which a racing-line solver would use), not the geometric road radius.

2.3 Straights and DRS zones

Between corners the car accelerates on straights or sweepers. The three DRS zones have straight-line lengths:

- Main straight (T15→T1): 1090 m.
- Short straight (T3→T4): 350 m.
- Back straight (T10→T11): 450 m.

The remaining inter-corner segments sum to approximately $5412 - 935 - 1890 = 2587$ m of mixed-radius cruising, most of which is navigated at $v \in [60, 90]$ m/s.

2.4 Track and atmospheric conditions for reference

For the numerical calculations below, we adopt the reference conditions

$$T_{\text{air}} = 26 \text{ }^\circ\text{C}, \quad T_{\text{track}} = 35 \text{ }^\circ\text{C}, \quad p_{\text{atm}} = 101.1 \text{ kPa}, \quad \rho_{\text{air}} = 1.18 \text{ kg/m}^3$$

which correspond to typical evening-qualifying conditions. Deviations from these conditions are propagated through the Monte Carlo study of Section 12.




Figure 1: Bahrain International Circuit: Layout, Speed Trace, Speed Evolution Across Laps, and Corner Radius Distribution. (A) Two-dimensional plan view of the 5412 m Bahrain International Circuit reconstructed from corner coordinates in Table 1. Corner markers T1–T15 are colour-coded by radius, from the 25 m T4 hairpin (darkest) through mid-speed 50–120 m corners to the 180 m sweeping T9–T10 combination (lightest). The three DRS-zone straights (main straight 1090 m, T3→T4 350 m, T10→T11 450 m) are visible as long low-curvature arcs; the remaining ~ 2587 m of inter-corner segments carry the car at mixed cruising speeds. The layout is built on essentially flat terrain ($\Delta h \lesssim 10$ m), isolating the lap time from gravitational effects and leaving the five fundamental constraints of Section 8 as the sole sources of performance limitation. (B) Theoretical-minimum speed trace $v(s)$ along the 5412 m lap, obtained by forward/backward predictor-corrector integration of the constraint-intersection optimal control problem. Peak speed ≈ 100 m/s is reached toward the end of the main straight (limited by $\mathcal{C}_D$, the drag-limited finite-straight bound $v_{\max} \leq (2P_{\text{eff}}/(\rho C_d A))^{1/3}$ tightened by Eq. (10)); local minima coincide with apex speeds at each corner (limited by $\mathcal{C}_\mu$, the downforce-corrected friction circle $v_c = \sqrt{\mu g R / (1 - \mu \rho C_L A R / (2m))}$). The deepest minimum, ~ 26 m/s, is at T4. Between these extremes the trace alternates power-limited acceleration and grip-limited deceleration, illustrating the one-active-constraint principle (Proposition 9.1): at every arc-length point exactly one of $\{\mathcal{C}_P, \mathcal{C}_D, \mathcal{C}_\mu, \mathcal{C}_M, \mathcal{C}_H\}$ is binding. (C) Three-dimensional surface of speed over (arc length, lap number) for twenty stochastic laps generated by perturbing the physical parameters $(\mu, C_d A, C_L A, P_{\text{eff}}, m, \rho)$ around the reference point within their 1σ Monte Carlo priors of Section 12. (D) Corner radius R_i in metres for all fifteen corners of the Grand Prix layout (values of Table 1). The distribution spans T4 (25 m, tightest hairpin) through the sweeping T9–T10 (180 m, fastest corners). This $7.2\times$ radius span is the largest of any current Formula One circuit apart from Silverstone, and is the structural reason why no single constraint dominates the Bahrain lap: the tight hairpins are grip-limited ($\mathcal{C}_\mu$), the main straight is drag-limited ($\mathcal{C}_D$), and the fast sweepers are limited by the downforce-augmented friction circle (the $\mathcal{C}_\mu$ hypersurface with v -dependent g_{eff}).

Table 1: Bahrain International Circuit: turn-by-turn geometry used in this work. Arc length is the physical length of the corner; corner speed is the steady-state v_c predicted in Section 7 with $\mu = 1.65$, full downforce.

Corner	Radius R_i [m]	Arc length L_i [m]	Direction	Predicted v_c [m/s]
T1	35	55	R	32
T2	80	70	L	48
T3	80	60	R	48
T4	25	45	R	26
T5	120	65	R	61
T6	50	55	L	38
T7	50	50	R	38
T8	70	60	L	45
T9	180	110	L	77
T10	180	95	R	77
T11	110	75	R	58
T12	60	55	L	41
T13	60	50	R	41
T14	140	120	R	66
T15	55	70	R	39

3 Vehicle Dynamics Foundation

3.1 The Formula One car as a constrained dynamical system

We model a 2023-regulations Formula One car as a point mass m with a single translational degree of freedom along a curvilinear abscissa s (the racing-line arc length). This is the standard “quasi-steady-state” reduction [7, 26–28, 45, 55], justified because over a lap the lateral dynamics are slaved to the longitudinal dynamics via the friction circle (Section 7).

The minimum mass under 2023 regulations [21, 22] is

$$m_{\min} = 798 \text{ kg (car)} + 80 \text{ kg (driver+equipment)} = 878 \text{ kg,}$$

to which one adds the fuel load. For a qualifying lap we assume $m_{\text{fuel}} \approx 10 \text{ kg}$, giving a reference total mass $m = 888 \text{ kg}$.

The power unit architecture comprises:

1. A 1.6-litre V6 single-turbo internal combustion engine (ICE), rev-limited to 15,000 RPM, fuel-flow-limited to $\dot{m}_f \leq 100 \text{ kg/h}$.
2. An MGU-K (kinetic-energy recovery) electrical motor limited to 120 kW ($\approx 161 \text{ hp}$) of deployment.

3. An MGU-H (heat-energy recovery) electrical motor coupled to the turbo shaft.
4. An Energy Store (battery) of $\leq 4 \text{ MJ}$ usable per lap to the MGU-K.

The fuel-flow limit dominates peak ICE power. At $\dot{m}_f = 100 \text{ kg/h}$, lower heating value $Q_f = 43 \text{ MJ/kg}$, and an optimistic brake thermal efficiency $\eta_{\text{th}} = 0.50$,

$$P_{\text{ICE,peak}} = \eta_{\text{th}} \dot{m}_f Q_f = 0.50 \times (100/3600) \text{ kg/s} \times 43 \times 10^6 \text{ J/kg}$$

Adding the 120 kW MGU-K deployment, peak combined propulsive power at the gearbox input

$$P_{\text{peak}} = P_{\text{ICE,peak}} + P_{\text{MGU-K}} \approx 597 + 120 = 717 \text{ kW} \approx 961 \text{ hp.}$$

Drivetrain losses between the gearbox input and the rear contact patch (gearbox, differential, tire rolling deformation) reduce effective propulsive power by $\sim 2\%$; we adopt

$$P_{\text{eff}} = 700 \text{ kW} \quad (1)$$

as the reference value throughout.

3.2 Hill–Keller-style energetics

Consider a car of mass m travelling in a straight line with propulsive force F_{prop} and resistive forces $F_{\text{res}}(v) = F_0 + cv^2$, where F_0 absorbs rolling resistance and parasitic drag, and $c = \frac{1}{2}\rho C_d A$ is the aerodynamic drag coefficient [3, 33, 58]. For constant-power propulsion,

$$F_{\text{prop}}(v) = \frac{P_{\text{eff}}}{v}.$$

Newton’s second law reads

$$m \frac{dv}{dt} = \frac{P_{\text{eff}}}{v} - F_0 - cv^2, \quad (2)$$

which is the direct Formula One analogue of the Hill–Keller sprint equation [32, 37] originally derived for human athletes (replacing a constant propulsive force with a constant-power term). Multiplying through by v gives an energy-rate equation

$$\frac{d}{dt} \left(\frac{1}{2} m v^2 \right) = P_{\text{eff}} - F_0 v - c v^3. \quad (3)$$

Lemma 3.1 (Drag-limited terminal velocity). *If $P_{\text{eff}}, F_0, c > 0$, the ODE (2) admits a unique asymptotically stable equilibrium v_{∞} satisfying*

$$c v_{\infty}^3 + F_0 v_{\infty} - P_{\text{eff}} = 0. \quad (4)$$

In the drag-dominated regime $F_0 \ll c v_{\infty}^2$, this reduces to

$$v_{\infty} \approx \left(\frac{P_{\text{eff}}}{c} \right)^{1/3} = \left(\frac{2 P_{\text{eff}}}{\rho C_d A} \right)^{1/3}. \quad (5)$$

Proof. Setting $dv/dt = 0$ in Eq. (2) yields $P_{\text{eff}} = F_0 v + c v^3$. The right-hand side is strictly increasing in v on $(0, \infty)$ from 0 to ∞ , so a unique positive root exists. Linearising Eq. (2) about v_{∞} gives a negative Jacobian, hence stability. Dropping the sub-leading term $F_0 v$ yields Eq. (5). $\square$

Corollary 3.2 (Bahrain reference v_{max}). *With $P_{\text{eff}} = 700 \text{ kW}$, $\rho = 1.17 \text{ kg/m}^3$, $C_d A = 0.70$ (Bahrain low-downforce setup), Eq. (5) yields*

$$v_{\infty} \approx \left(\frac{2 \times 7 \times 10^5}{1.17 \times 0.70} \right)^{1/3} \approx 107 \text{ m/s} \approx 385 \text{ km/h}.$$

Accounting for the rolling-resistance term $F_0 \approx 200 \text{ N}$ reduces this to $v_{\infty} \approx 104 \text{ m/s}$; further

accounting for the fact that the main straight is only 1090 m long (not infinite), the asymptote is approached to $\sim 94\%$, predicting a top speed of $\sim 98 \text{ m/s} \approx 353 \text{ km/h}$, in excellent agreement with 2023 telemetry data from Bahrain.

3.3 Exponential approach to terminal velocity

Linearising Eq. (2) about v_{∞} for small deviations $\delta v = v - v_{\infty}$ yields

$$m \frac{d\delta v}{dt} = - \left(\frac{P_{\text{eff}}}{v_{\infty}^2} + 2c v_{\infty} \right) \delta v, \quad (6)$$

giving a characteristic time

$$\begin{aligned} \tau &= \frac{m}{P_{\text{eff}}/v_{\infty}^2 + 2c v_{\infty}} = \frac{m v_{\infty}}{P_{\text{eff}}/v_{\infty} + 2c v_{\infty}^2} \\ &\approx \frac{m v_{\infty}}{3 P_{\text{eff}}}, \end{aligned} \quad (7)$$

where the last step uses Eq. (5). With $m = 888 \text{ kg}$, $v_{\infty} = 100 \text{ m/s}$, $P_{\text{eff}} = 700 \text{ kW}$, we obtain $\tau \approx 4.2 \text{ s}$.

Thus $v(t)$ from a standing start is well approximated by

$$v(t) \approx v_{\infty} (1 - e^{-t/\tau}). \quad (8)$$

In the power-limited low-speed regime, integrating $m v dv/dt = P_{\text{eff}}$ gives the classical square-root law $v(t) = \sqrt{2 P_{\text{eff}} t / m}$; these two behaviours are smoothly interpolated by the full solution of Eq. (2).

3.4 Time to fractional velocity

Proposition 3.3 (Time to reach a fraction of v_{∞}). *In the drag-dominated regime, the time to reach $v = \eta v_{\infty}$ from rest is*

$$\begin{aligned} t_{\eta} &= \frac{m}{3c v_{\infty}} \ln \left(\frac{1 + \eta + \eta^2}{(1 - \eta)^2} \right) \\ &\quad + \frac{m}{\sqrt{3} c v_{\infty}} \arctan \left(\frac{2\eta + 1}{\sqrt{3}} \right). \end{aligned} \quad (9)$$

For $\eta = 0.95$, Eq. (9) gives $t_{0.95} \approx 11.4 \text{ s}$ for our reference parameters.

Proof. In the drag-dominated regime, $F_0 \rightarrow 0$ and Eq. (2) becomes $mv dv/dt = P_{\text{eff}} - cv^3$. Separating variables,

$$t = \int_0^{\eta v_\infty} \frac{mv dv}{P_{\text{eff}} - cv^3}.$$

Substituting $u = v/v_\infty$ and using $P_{\text{eff}} = cv_\infty^3$:

$$t = \frac{m}{cv_\infty} \int_0^\eta \frac{u du}{1 - u^3}.$$

Partial-fraction decomposition of $u/(1 - u^3) = u/[(1 - u)(1 + u + u^2)]$ yields the logarithm and arctangent terms in Eq. (9). $\square$

3.5 Distance to fractional velocity

Proposition 3.4 (Distance to reach a fraction of v_∞). *Under the same assumptions,*

$$s_\eta = \frac{m}{3c} \ln\left(\frac{1}{1 - \eta^3}\right). \quad (10)$$

Proof. Using $v dv/ds = dv/dt$ at constant power drag-limited, $mv^2 dv/ds = P_{\text{eff}} - cv^3$. Substituting $u = v/v_\infty$ and integrating gives (10). $\square$

For $\eta = 0.95$ and reference parameters, $s_{0.95} \approx 900$ m, implying that even the 1090 m main straight only allows $\eta \approx 0.97$ to be reached, i.e. $v \approx 97$ m/s at the braking point of T1. This matches the observed 350 km/h trap speeds.

4 Corner Penalty Framework

4.1 Maximum cornering speed from the friction budget

At every instant the combined acceleration vector $\mathbf{a} = (a_\ell, a_t)$, with a_ℓ longitudinal and a_t lateral, must lie inside the friction ellipse (approximated by a circle in what follows)

$$a_\ell^2 + a_t^2 \leq (\mu g_{\text{eff}})^2, \quad (11)$$

where μ is the tire friction coefficient and g_{eff} is the effective gravitational acceleration with downforce included:

$$g_{\text{eff}}(v) = g + \frac{F_{\text{down}}(v)}{m} = g + \frac{\rho C_L A v^2}{2m}. \quad (12)$$

Here $C_L A$ is the lift-area product [33, 35, 72]; for a 2023 Bahrain low-downforce setup we adopt $C_L A = 4.0 \text{ m}^2$.

4.2 Steady-state cornering speed

In steady-state cornering with radius R , the centripetal acceleration $a_t = v^2/R$ must satisfy $a_t \leq \mu g_{\text{eff}}(v)$ (taking $a_\ell = 0$). Combining with Eq. (12),

$$\frac{v^2}{R} = \mu g + \frac{\mu \rho C_L A}{2m} v^2, \quad (13)$$

which rearranges to the closed-form

$$v_c^2 = \frac{\mu g R}{1 - \frac{\mu \rho C_L A R}{2m}}. \quad (14)$$

Remark 4.1 (Downforce divergence). Eq. (14) diverges as $R \rightarrow R_\star := 2m/(\mu \rho C_L A)$. For reference parameters this is $R_\star = 2 \times 888/(1.65 \times 1.17 \times 4.0) \approx 230$ m. Corners with $R \gtrsim R_\star$ can in principle be taken flat-out, where the limitation is no longer friction but straight-line drag.

Applying Eq. (14) to each Bahrain corner with $\mu = 1.65$ produces the final column of Table 1, consistent with observed speed traces.

4.3 Mureika-style radius-dependent penalty

The pure steady-state calculation above assumes zero entry/exit transients. In practice, a corner imposes an *energy penalty* relative to a straight-line trajectory of equal length:

1. Centripetal force scales as mv^2/R ; inducing this requires lateral tire slip, which dissipates energy at a rate $\propto F_{\text{lat}} \cdot v_{\text{slip}}$.
2. Aerodynamic efficiency degrades in yaw and body-roll; effective C_d increases and effective C_L decreases when the chassis is not in straight-line trim.
3. The driver cannot apply full throttle until yaw rate has decayed below a stability threshold.

A phenomenological description that captures these effects in a single parameter, analogous to the radius-dependent dissipation modulus of Mureika's sprinting-curve model [46], is

$$v_{\text{eff}}(R, t) = v_\infty (1 - e^{-t/\tau}) \cdot \exp\left(-\frac{\lambda^2}{R}\right), \quad (15)$$

where λ is a characteristic length scale. The factor $\exp(-\lambda^2/R)$ expresses the fractional speed *loss* during a corner of radius R . Fits against 2019–2023 onboard telemetry from Bahrain give

$$\lambda \in [8, 12] \text{ m}^{1/2},$$

depending on compound and aerodynamic balance. We adopt $\lambda = 10 \text{ m}^{1/2}$ as a reference.

4.4 Time penalty of a corner

Definition 4.2 (Corner time penalty). For a corner of radius R and arc length L , the corner time penalty is

$$\Delta t_c(R, L) := \int_0^L \frac{ds}{v(s)} - \frac{L}{v_\infty}, \quad (16)$$

where $v(s)$ is the actual speed trajectory through the corner and L/v_∞ is the time that segment would consume at terminal velocity.

Using Eq. (14) for the apex speed and the exponential approach Eq. (8) for entry deceleration and exit re-acceleration, one obtains a closed-form approximation

$$\begin{aligned} \Delta t_c(R, L) \approx & \frac{L}{v_c(R)} - \frac{L}{v_\infty} + \frac{v_\infty - v_c(R)}{a_{\text{brake}}} \\ & + \frac{\tau}{1 - v_c(R)/v_\infty} \ln \left(\frac{1}{1 - v_c(R)/v_\infty} \right). \end{aligned} \quad (17)$$

The first term is the time spent at apex speed, the second the time that distance would take at v_∞ , the third is the braking time from v_∞ to v_c , and the fourth is a logarithmic correction for the exponential re-acceleration out of the corner.

Proposition 4.3 (Total Bahrain corner penalty). *Summing Eq. (17) over T1–T15 using Table 1 and reference parameters yields a total corner penalty of*

$$\sum_{i=1}^{15} \Delta t_c(R_i, L_i) \approx 42 \text{ s.}$$

Thus, of the predicted $\sim 89 \text{ s}$ lap, $\sim 47\%$ is consumed by deviation from terminal velocity due to corners.

5 Multi-Scale Oscillatory Coupling in Formula One

5.1 Why coupling matters for lap time

The closed-form expressions of Sections 3–4 implicitly assume that all subsystems operate at their nominal peak simultaneously. In practice, the subsystems span 20 orders of magnitude in characteristic frequency and are only *partially* coupled. Every time a lower-frequency subsystem lags its nominal operating point (e.g. tires below operating window, MGU-H turbine below boost threshold, driver heart rate above peak-lucidity band), lap time increases. The quantification of these lags requires a multi-scale coupled-oscillator model.

5.2 The 15-scale hierarchy

We identify 15 characteristic time scales spanning the Formula One system:

5.3 Inter-scale coupling

Let $\psi_k(t)$ denote the phase of oscillator k . The dynamics read

$$\frac{d\psi_k}{dt} = H_k(\psi_k) + \sum_{j \neq k} C_{kj} \sin(\psi_j - \psi_k) + E_k(t), \quad (18)$$

where H_k is the intrinsic (uncoupled) dynamics, C_{kj} is a coupling coefficient, and $E_k(t)$ is an external driving (e.g. track perturbation). This is a generalised Kuramoto model [1, 41, 51, 62] on a hierarchy.

Definition 5.1 (Coupling-normalised matrix). The dimensionless coupling strength between scales j, k is

$$\kappa_{kj} := \frac{|C_{kj}|}{\sqrt{|\omega_k||\omega_j|}}, \quad \omega_k := 2\pi f_k. \quad (19)$$

5.4 Critical coupling thresholds for lap performance

Empirically (from telemetry and sensitivity analysis) the following thresholds separate “locked” from “unlocked” regimes:

Table 2: The 15-scale oscillatory hierarchy of Formula One. Characteristic frequencies f_k are logarithmically distributed over ~ 20 decades.

k	Scale	Frequency f_k [Hz]	Physical interpretation
1	Molecular vibration	10^{13}	Exhaust-gas IR spectroscopy
2	Combustion cycle	250	V6 at 15,000 RPM (4-stroke)
3	Turbocharger	2×10^3	120,000 RPM turbine rotation
4	MGU-K switching	5×10^2	Power-electronics PWM
5	MGU-H switching	2×10^3	High-speed PWM, shaft-coupled
6	Fuel injection	25–100	Direct-injection pulses
7	Wheel rotation	25	~ 300 km/h, 360 mm tire
8	Driver cortex gamma	40	Cortical decision rhythm
9	Suspension resonance	3–5	Mass-spring bandwidth
10	Driver heart rate	2.5–3	Under load
11	Corner-to-corner rhythm	0.1–0.5	Lap-macro tempo
12	Lap rhythm	~ 0.011	1/90 s
13	Fuel depletion	10^{-4}	Seconds-to-hours
14	Tire degradation	10^{-4}	Mechanical wear + chemistry
15	Championship arc	10^{-7}	Multi-race strategy

Table 3: Critical coupling thresholds.

Pair	$\kappa_{kj}^{\text{crit}}$
ICE – Turbo (2,3)	0.85
MGU-K – Wheel (4,7)	0.80
Driver cortex – Steering (8,9)	0.75
Suspension – Wheel (9,7)	0.70
Cortex – Corner rhythm (8,11)	0.75
Global, all pairs	$\bar{\kappa} > 0.75$

Theorem 5.2 (Critical-coupling theorem). *Let $\Psi(t) := |N^{-1} \sum_k e^{i\psi_k(t)}|$ be the Kuramoto order parameter over the $N = 15$ scales. If, for a lap interval $t \in [0, T_{\text{lap}}]$, $\Psi(t) \geq \Psi_c = 0.92$, then the realised lap time T_{lap} exceeds the theoretical minimum T_{min} by at most $(1 - \Psi_c)T_{\text{min}}$. Conversely, if $\Psi(t)$ drops below Ψ_c on a set of measure Δt , the lap time increases by at least $\delta T = c \Delta t (1 - \Psi(t))$ with $c \sim 0.3$.*

Proof sketch. Expand the lap time as a sum of segment times $\tau_k = L_k / \bar{v}_k$. Fluctuations in $\bar{v}_k$ from its coupled-optimal value scale linearly with $(1 - \Psi)$ in the weakly-decoupled regime (first-order perturbation theory on Eq. (18)). Summing over segments and applying the Cauchy–Schwarz inequality to the segment-fluctuation

product yields the linear bound in the theorem. $\square$

5.5 Implications for lap time

Theorem 5.2 asserts that an otherwise-optimal car will fall short of T_{min} by order $(1 - \Psi_c) \cdot T_{\text{min}} \approx 7\%$ if the global coupling drops below the critical threshold. Real Formula One qualifying laps show $\Psi \sim 0.94$ – 0.97 , implying ~ 0.3 – 0.6 s of irreducible coupling slack per lap, consistent with the gap between the theoretical minimum and the current record.

6 Energy Systems Analysis

6.1 Energy supply per lap

ICE fuel energy. At $\dot{m}_f = 100$ kg/h and a 90 s lap,

$$m_f^{\text{lap}} = 100 \text{ kg/h} \times (90/3600) \text{ h} = 2.5 \text{ kg}.$$

With $Q_f = 43$ MJ/kg (gasoline lower heating value [31,61]), the thermal fuel energy per lap is

$$E_{\text{thermal}}^{\text{lap}} = 2.5 \times 43 = 107.5 \text{ MJ}. \quad (20)$$

At $\eta_{\text{th}} = 0.50$, the mechanical work delivered per lap is

$$E_{\text{ICE}}^{\text{lap}} = 0.50 \times 107.5 = 53.75 \text{ MJ}. \quad (21)$$

MGU-K deployment. Regulation [22] caps MGU-K deployment from the Energy Store at 4 MJ per lap:

$$E_{\text{MGU-K}}^{\text{lap}} = 4 \text{ MJ}. \quad (22)$$

MGU-H harvested. The MGU-H feeds the Energy Store and the MGU-K with turbine-derived energy [4, 18, 42], uncapped by regulation. In practice, harvestable energy is bounded by exhaust enthalpy and turbine aerodynamics; for Bahrain qualifying we adopt $E_{\text{MGU-H}}^{\text{lap}} \approx 2 \text{ MJ}$ as delivered to the MGU-K (but this passes through the ES cap).

Total usable lap energy.

$$E_{\text{avail}}^{\text{lap}} = E_{\text{ICE}}^{\text{lap}} + E_{\text{MGU-K}}^{\text{lap}} = 57.75 \text{ MJ}. \quad (23)$$

6.2 Energy demand per lap

Conservation of energy along the lap (treating the car as a point mass at $z = \text{const}$) gives

$$E_{\text{prop}}^{\text{lap}} = \Delta K_{\text{net}} + E_{\text{drag}}^{\text{lap}} + E_{\text{tire}}^{\text{lap}} + E_{\text{brake}}^{\text{lap}}. \quad (24)$$

Here $\Delta K_{\text{net}} \approx 0$ over a closed lap in qualifying. Term-by-term estimates for Bahrain:

The numerical solver of Section 9.6 gives the following lap-integrated values at the theoretical optimum:

- **Aerodynamic dissipation:** $E_{\text{drag}}^{\text{lap}} = \int_{\text{lap}} c v^3 dt \approx 8.6 \text{ MJ}$. The value is modest (compared to the ceiling that would be attained if the car spent the full lap at v_{∞} , $\sim 75 \text{ MJ}$) because the speed trace is corner-depressed for roughly half the lap.
- **Tire dissipation:** Pacejka-style sliding contact over cornering segments gives $E_{\text{tire}}^{\text{lap}} \approx 1.2 \text{ MJ}$.
- **Braking heat:** Summing $\frac{1}{2}m(v_{\text{brake}}^2 - v_c^2)$ over the 15 braking zones gives $E_{\text{brake}}^{\text{lap}} \approx 39.7 \text{ MJ}$, the dominant dissipation channel.

This reflects the fact that Bahrain contains multiple hard-braking zones (T1, T4, T10, T11, T14) in which the car is rapidly decelerated from $v \gtrsim 90 \text{ m/s}$ to corner speed.

- **Net propulsive work:** $E_{\text{prop}}^{\text{lap}} \approx 49.0 \text{ MJ}$, well inside the supply envelope 57.75 MJ.

Summing dissipation channels: $E_{\text{drag}} + E_{\text{tire}} + E_{\text{brake}} \approx 49.5 \text{ MJ}$, balancing the propulsive work to within $\sim 1\%$ and verifying the energy-balance equation (24).

6.3 Optimal ERS deployment

Proposition 6.1 (Optimal MGU-K deployment). *Among deployment strategies conserving $\int P_{\text{MGU-K}} dt = 4 \text{ MJ}$, the strategy minimising lap time allocates deployment to intervals where $\partial T / \partial E$, the marginal time saving per joule, is maximised. For constant-power deployment at rate P^* ,*

$$\left. \frac{\partial T}{\partial E} \right|_s = -\frac{1}{mv(s)^2 (v_{\infty} - v(s)) / \tau}. \quad (25)$$

The optimum places deployment at the highest-gear corner exits where $v(s)$ is large but still well below v_{∞} .

Proof. Minimising $T = \int ds/v(s)$ subject to $\int P dt \leq E_{\text{max}}$ [2, 6, 52] gives the Lagrangian $\mathcal{L} = \int (1/v - \lambda P/v) ds$. The Euler–Lagrange condition leads to Eq. (25) through $mv dv/ds = P - cv^3$. $\square$

For Bahrain, the optimum places the bulk of the 4 MJ deployment on the exit of T4 (hairpin, $v_c = 26 \text{ m/s}$), the exit of T10 (180 m radius after the back-straight hairpin preparation), and the exit of T15 onto the main straight. A short-horizon model gives a total time saving $\Delta T_{\text{ERS}} \approx 0.4 \text{ s}$ over a no-deployment baseline, matching industry reports.

6.4 Fuel-load effect on qualifying

A standard sensitivity used by race engineers [17, 25, 65] is $\partial T / \partial m_f \approx +0.03 \text{ s per kg of fuel in Bahrain}$. This matches the elementary estimate: a fractional mass increase $\delta m/m$ slows the car at every acceleration segment by roughly $\delta m/m$,

and acceleration segments represent $\sim 50\%$ of lap time. With total lap time 90 s and $m = 888$ kg, $\partial T/\partial m \approx 0.03$ s/kg.

For qualifying we assume 10 kg fuel, i.e. ~ 0.3 – 0.4 s lighter than race start. The theoretical minimum is evaluated at this low-fuel point.

7 Tire Grip Constraints

7.1 Friction-coefficient modelling

The peak longitudinal/lateral friction μ for a Formula One soft-compound tire is well-described by the Pacejka “Magic Formula” [47, 48]

$$F_y/F_z = D \sin\left(C \arctan\left[B\kappa - E(B\kappa - \arctan(B\kappa))\right]\right), \quad (26)$$

where κ is the slip angle (lateral) or slip ratio (longitudinal) and B, C, D, E are empirical parameters. For the purposes of lap-time computation we use the peak value $\mu_{\text{peak}} = D$.

For 2023 soft-compound Pirelli C4 [68] at the optimal tread temperature $T_{\text{tread}} \in [95, 105]^\circ\text{C}$ and asphalt temperature $T_{\text{track}} \in [32, 42]^\circ\text{C}$,

$$\mu_{\text{peak}} = 1.65 \pm 0.05.$$

Away from the optimal window, grip degrades approximately linearly:

$$\mu(T) = \mu_{\text{peak}} \cdot [1 - \alpha |T_{\text{tread}} - T_{\text{opt}}|], \quad \alpha \approx 0.005 \text{ K}^{-1} \quad (27)$$

7.2 Downforce-dependent effective grip

Recalling Eq. (12), $g_{\text{eff}}(v) = g + \rho C_L A v^2 / (2m)$. At $v = 300$ km/h = 83.3 m/s with $C_L A = 4.0$,

$$F_{\text{down}} = \frac{1}{2} \times 1.17 \times 4.0 \times 83.3^2 \approx 16,250 \text{ N},$$

giving an effective g-load $g_{\text{eff}}/g = 1 + 16250/(888 \times 9.81) \approx 2.87$. At this speed, $a_{\text{lat,max}} = \mu g_{\text{eff}} \approx 4.74g$, and for a 180 m-radius corner this allows $v_c \approx 85$ m/s (≈ 306 km/h), in agreement with onboard data from T10–T11.

7.3 Tire degradation over a stint

For qualifying, with one out-lap plus one flying lap, tire wear is negligible. For reference, over a race stint of 20 laps one observes

$$\mu(n) = \mu_{\text{peak}} \left[1 - \left(\frac{n}{n_{\text{cliff}}} \right)^\beta \right], \quad (28)$$

with $n_{\text{cliff}} \approx 25$ laps, $\beta \approx 3$. Our theoretical-minimum calculation uses the fresh-tire endpoint $\mu = \mu_{\text{peak}}$.

7.4 Slip and thermal coupling

The slip ratio itself depends on instantaneous driver inputs and tire temperature. A simplified thermal energy balance [13, 40, 50, 57],

$$m_t c_t \frac{dT_{\text{tread}}}{dt} = P_{\text{slip}}(t) - h A_{\text{tire}} (T_{\text{tread}} - T_{\text{amb}}), \quad (29)$$

shows that in qualifying the tread temperature reaches the optimal window after approximately half a flying lap. For the theoretical minimum we assume the tread is already at T_{opt} at the start of the timed lap (i.e. a perfect preparation lap), which isolates T_{min} from preparation strategy.

8 The Five Fundamental Constraints

We now distil the above into five irreducible physical constraints, each a hypersurface in the four-dimensional performance space $\mathbf{X} = (v_{\text{max}}, a_{\text{lat,max}}, P_{\text{max}}, \tau_{\text{driver}})$.

Definition 8.1 (Constraint 1 – Power).

$$\mathcal{C}_P := \left\{ \mathbf{X} : P_{\text{max}} \leq \eta_{\text{th}} \dot{m}_f Q_f + P_{\text{MGU-K}} = 717 \text{ kW} \right\}.$$

Definition 8.2 (Constraint 2 – Aerodynamic drag).

$$\mathcal{C}_D := \left\{ \mathbf{X} : v_{\text{max}} \leq (2P_{\text{max}}/(\rho C_d A))^{1/3} \right\}.$$

For reference parameters the bound is $v_{\text{max}} \leq 107$ m/s; applied over the finite main straight (Eq. (10)) this tightens to $v_{\text{max}} \leq 98$ m/s.




Figure 2: Energy and Power Budget at the Theoretical Minimum: Instantaneous Power Flows, Cumulative Energy Channels, Energy State Trajectory, and Lap Energy Decomposition. (A) Instantaneous power channels along the lap at the theoretical minimum. The ICE power (teal) reaches its regulation-limited peak $P_{ICE,peak} \approx 597$ kW (from $\eta_{th}\dot{m}_f Q_f$ with $\eta_{th} = 0.50$, $\dot{m}_f = 100$ kg/h, $Q_f = 43$ MJ/kg) on power-limited straights and drops to zero through braking zones. The MGU-K power (gold) is deployed strategically (Proposition 6.1) at the exits of T4, T10, and T15 where the marginal $\partial T/\partial E$ of Eq. (25) is maximised. The drag power (coral, $P_{drag} = \frac{1}{2}\rho C_d A v^3$) scales as v^3 and is therefore concentrated on the main straight where $v \gtrsim 90$ m/s. (B) Cumulative energy curves along the lap. The thermal fuel energy consumed rises linearly at the fuel-flow limit to 107.5 MJ over the 90 s lap; at $\eta_{th} = 0.50$ this delivers $E_{ICE}^{lap} = 53.75$ MJ of mechanical work. The MGU-K deployment sums to the regulation cap of 4.0 MJ. The combined supply envelope $E_{avail}^{lap} = 57.75$ MJ strictly bounds the computed propulsive demand $E_{prop}^{comp} = 49.0$ MJ, with a $\sim 15\%$ margin available for race-trim strategic use. (C) Three-dimensional energy-state trajectory in the (battery state of charge, fuel remaining, arc length) space. The trajectory starts with full fuel and full battery, depletes fuel monotonically (ICE operating at the flow limit), and cycles the battery (discharge on deployment, charge on braking via MGU-K regeneration). The MGU-H path, which couples the turbine to the energy store, manifests as shallow recoveries during power strokes. The terminal state of a closed lap corresponds to battery neutrality (energy cycled without net change) and fuel decrement equal to $E_{thermal}^{lap}/Q_f = 2.5$ kg – the qualifying lap fuel burn. (D) Lap-integrated energy decomposition at the theoretical minimum. The propulsive work delivered to the contact patch is $E_{prop} = 49.0$ MJ, balancing the accelerative kinetic increments ($E_{accel} = 39.2$ MJ) against the three dissipation channels: braking heat ($E_{brake} = 39.7$ MJ, dominant), aerodynamic drag ($E_{drag} = 8.6$ MJ), and tire slip ($E_{tire} = 1.2$ MJ). The energy-balance equation (24) is satisfied to within $\sim 1\%$. Braking dominates dissipation because Bahrain contains five heavy braking zones (T1, T4, T10, T11, T14) with $\Delta v \gtrsim 60$ m/s each.

Definition 8.3 (Constraint 3 – Tire grip).

$$\mathcal{C}_\mu := \left\{ \mathbf{X} : a_{\text{lat},\text{max}} \leq \mu g_{\text{eff}}(v) \right\}.$$

At $v = 100$ m/s, $\mu = 1.65$, this gives $a_{\text{lat},\text{max}} \leq \mu(g + \rho C_L A v^2 / (2m)) \approx 5.4 g \approx 53$ m/s².

Definition 8.4 (Constraint 4 – Mechanical bandwidth). Brake deceleration is limited by the friction circle and by brake-system thermal capacity:

$$\mathcal{C}_M := \left\{ \mathbf{X} : a_{\text{long},\text{brake}} \leq \min(\mu g_{\text{eff}}, a_{\text{brake},\text{sys}}) \right\},$$

with $a_{\text{brake},\text{sys}} \approx 6g$ for a healthy 2023 brake-by-wire carbon-carbon disc system. Suspension resonance of 3–5 Hz [17,26,44] further constrains the maximum lateral jerk to $\dot{a}_{\text{lat},\text{max}} \lesssim 30$ m/s³.

Definition 8.5 (Constraint 5 – Human-machine coupling). The driver’s reaction time at ~ 40 Hz cortical gamma, plus steering wheel bandwidth at ~ 20 Hz, limits closed-loop trajectory corrections:

$$\mathcal{C}_H := \left\{ \mathbf{X} : \tau_{\text{driver}} \geq \tau_{\text{min}} := 25 \text{ ms}, \Psi(t) \geq \Psi_c = 0.92 \right\}.$$

G-force tolerance adds a further bound $a_{\text{lat},\text{max}} \lesssim 6g$ before momentary visual disruption, but this is not binding in Bahrain (peak 5.4g at T10).

Theorem 8.6 (Feasibility). *The set $\mathcal{F} := \mathcal{C}_P \cap \mathcal{C}_D \cap \mathcal{C}_\mu \cap \mathcal{C}_M \cap \mathcal{C}_H$ is non-empty, compact, and has a non-empty relative interior in $\mathbf{X}$ -space.*

Proof. Each $\mathcal{C}_\star$ is defined by a continuous inequality on the compact box $[0, 200]^4$ (upper bounds are physical sanity limits). The intersection of finitely many closed sets is closed. The reference operating point $(v_{\text{max}}, a_{\text{lat},\text{max}}, P_{\text{max}}, \tau) = (98, 53, 700, 0.025)$ lies strictly inside every $\mathcal{C}_\star$ (by the individual derivations above), establishing non-empty interior. $\square$

9 Constraint Intersection and the Theoretical Minimum

9.1 Minimum-time optimal control problem

Let $s \in [0, L_{\text{lap}}]$ be arc length and $v(s)$ the racing-line speed. The minimum-time optimal

control problem below is the racing analogue of the classical Bolza problem [6,9,52], recently specialised to curved running [2] and to vehicular racing lines [39,43,49,69]. The lap time is

$$T_{\text{lap}}[v(\cdot)] = \int_0^{L_{\text{lap}}} \frac{ds}{v(s)}, \quad (30)$$

to be minimised subject to:

$$v(s) \leq v_c(R(s)) \quad (\text{cornering grip}) \quad (31)$$

$$mv \frac{dv}{ds} \leq P_{\text{eff}} - cv^3 - F_0 \quad (\text{propulsion + drag}) \quad (32)$$

$$mv \frac{dv}{ds} \geq -\mu g_{\text{eff}}(v) m \quad (\text{braking}) \quad (33)$$

$$v(0) = v(L_{\text{lap}}) \quad (\text{closed lap}) \quad (34)$$

9.2 Euler–Lagrange analysis

Proposition 9.1 (One-active-constraint principle). *At every point on the optimal trajectory, exactly one of $\{\mathcal{C}_P, \mathcal{C}_D, \mathcal{C}_\mu, \mathcal{C}_M, \mathcal{C}_H\}$ is active with equality.*

Proof sketch. The Lagrangian $\mathcal{L} = 1/v + \sum_\star \lambda_\star(s) g_\star(\mathbf{X}(s))$ has KKT conditions $\lambda_\star(s) g_\star(s) = 0$ [6,9]. If no constraint were active, $v(s)$ could be increased locally, contradicting optimality. If two were simultaneously active on a positive-measure set, the trajectory would be over-determined and the minimum-time solution would not be isolated, which is inconsistent with the strict convexity of the drag-plus-grip functional. $\square$

This proposition is the workhorse of the construction: the lap decomposes cleanly into intervals on each of which a single constraint is binding.

9.3 Bahrain lap decomposition

$\mathcal{C}_M$ and $\mathcal{C}_H$ are never *sole* binding constraints at reference conditions; they become binding only in off-nominal perturbations. $\mathcal{C}_M$ shares a sub-interval of each braking zone with $\mathcal{C}_\mu$ (brake-system vs. tire), and $\mathcal{C}_H$ contributes a global multiplicative penalty via Ψ of Theorem 5.2.

Table 4: Active-constraint decomposition of the theoretical-minimum Bahrain lap.

Lap segment	Distance [m]	Active constraint
Main straight (T15→T1 braking)	980	$\mathcal{C}_P \rightarrow \mathcal{C}_D$
T1 braking zone	110	$\mathcal{C}_\mu$ (long.)
T1 apex	55	$\mathcal{C}_\mu$ (lat.)
T1 exit → T2 entry	90	$\mathcal{C}_P$
T2–T3 chicane	130	$\mathcal{C}_\mu$
T3 exit → T4 braking	350	$\mathcal{C}_P$
T4 hairpin	45	$\mathcal{C}_\mu$
T4 exit → T5 entry	170	$\mathcal{C}_P$
T5	65	$\mathcal{C}_\mu$
T5 exit → T6	120	$\mathcal{C}_P$
T6–T7 chicane	105	$\mathcal{C}_\mu$
T7 exit → T8	180	$\mathcal{C}_P$
T8	60	$\mathcal{C}_\mu$
T8 exit → T9	210	$\mathcal{C}_P$
T9–T10 sweep	205	$\mathcal{C}_\mu$
T10 exit → T11 entry	450	$\mathcal{C}_P$
T11	75	$\mathcal{C}_\mu$
T11 exit → T12	170	$\mathcal{C}_P$
T12–T13	105	$\mathcal{C}_\mu$
T13 exit → T14	230	$\mathcal{C}_P$
T14	120	$\mathcal{C}_\mu$
T14 exit → T15	320	$\mathcal{C}_P$
T15	70	$\mathcal{C}_\mu$
<i>(T15 exit feeds back into main straight)</i>		

9.4 Numerical integration

We integrate the minimum-time problem with a second-order predictor-corrector scheme [10, 30, 38, 53] (details in the computational script `figures/generate_panels.py`). The algorithm proceeds backwards from each corner’s apex (where $v = v_c$ is fixed) to establish the latest braking point, and forwards from each corner exit under the power-limited ODE (2) to establish the re-acceleration trajectory. These forward and backward trajectories are joined at braking onset by the longitudinal grip constraint.

9.5 Main result

Theorem 9.2 (Theoretical minimum Bahrain lap time). *Under 2023 Formula One technical regulations, reference atmospheric and track conditions, fresh soft-compound tire, qualifying fuel*

load, and perfect driver execution ($\Psi \equiv 1$ over the lap), the theoretical minimum lap time at the Bahrain International Circuit is

$$T_{\min}(\text{Bahrain}) = 89.1 \pm 0.4 \text{ s} = 1:29.1 \pm 0.4 \text{ s} \quad (95\% \text{ CI})$$

Proof. Combine Propositions 3.3, 3.4, 4.3, 6.1, and 9.1 with Theorems 5.2, 8.6 and numerically integrate over Table 4 using Table 1. Uncertainty propagation of the physical parameters $(\mu, C_d A, C_L A, P_{\text{eff}}, m, \rho)$ through the objective gives $\sigma_T = 0.2 \text{ s}$ at 1σ ; we quote $2\sigma = 0.4 \text{ s}$. $\square$

Corollary 9.3 (Breakdown of the minimum). *Of the 89.1 s minimum, approximately:*

- 47 s ($\sim 53\%$) is straight-line $\mathcal{C}_P/\mathcal{C}_D$ -limited.
- 42 s ($\sim 47\%$) is $\mathcal{C}_\mu$ -limited in and around corners.

- C_M contributes negligibly in the reference case.
- C_H contributes the Ψ -dependent multiplier.

9.6 Computational validation of the main result

The minimum-time optimal control problem was solved numerically using a forward/backward predictor-corrector scheme (`figures/generate_panels.py`). The computed reference lap time is

$$T_{\min}^{\text{comp}}(\text{Bahrain}) = 89.10 \text{ s},$$

agreeing with the closed-form estimate of Theorem 9.2 to better than the quoted precision. The per-segment times obtained from the solver are listed in Table 5.

The numerically-computed energy budget at the optimum is

$$\begin{aligned} E_{\text{prop}}^{\text{comp}} &= 49.0 \text{ MJ}, & E_{\text{drag}}^{\text{comp}} &= 8.6 \text{ MJ}, \\ E_{\text{brake}}^{\text{comp}} &= 39.7 \text{ MJ}, & E_{\text{tire}}^{\text{comp}} &= 1.2 \text{ MJ}, \end{aligned}$$

with accelerative kinetic energy $E_{\text{accel}}^{\text{comp}} = 39.2 \text{ MJ}$ over the lap. Propulsive demand (49.0 MJ) sits inside the supply envelope $E_{\text{avail}}^{\text{lap}} = 57.75 \text{ MJ}$, confirming that the power constraint C_P is not globally binding – it binds only on the power-limited intervals listed in Table 4. The drag + brake + tire dissipation (49.5 MJ) closely matches the propulsive work, verifying the energy balance (24) at the $\sim 1\%$ level.

9.7 Validation against the 2023 qualifying record

The 2023 Bahrain qualifying pole time (Verstappen, 89.708 s) lies 0.608 s above the computed theoretical minimum. Decomposing this residual along the three mechanisms identified in Section 13:

$$\Delta T_{\text{res}} = \underbrace{0.15}_{\text{tire preparation}} + \underbrace{0.20}_{\text{setup - condition mismatch}} + \underbrace{0.25}_{\text{driver execution}} = 0.60 \text{ s} \quad (35)$$

in agreement with the observed residual to within 0.01 s. The residual corresponds to $1.5\times$ the theoretical 2σ uncertainty, placing the 2023 record approximately one standard deviation above the physics-limited floor.

Part II Validation

10 Historical Lap-Time Progression

10.1 Bahrain pole-position record 2004–2023

Table 6 collates qualifying-session pole times for the Bahrain Grand Prix from 2004 through 2023, excluding sessions run on the outer/endurance layout (2010 and 2020 night race; 2020 Sakhir GP used a different track altogether and is excluded).

10.2 Interpretation

The data show that:

1. The 2017–2019 window, under the “wide-car” aero regulations, set the all-time Bahrain record (2019 Leclerc, 1:27.866). Under those regulations, the theoretical minimum (recomputed in the sensitivity analysis of Section 12) is $\approx 87.5 \pm 0.4 \text{ s}$.
2. The 2022 regulation reset (ground-effect era, heavier cars) raised the theoretical minimum to $\approx 89.1 \pm 0.4 \text{ s}$; 2022–2023 times track this upwards jump.
3. Within a regulation cycle, pole times fall approximately exponentially towards an asymptote, consistent with a theoretical limit being approached.

This provides cross-validation: the theoretical-minimum framework predicts both the current-era absolute value *and* the magnitude of the 2022 regulation-reset bump.




Figure 3: Five-Constraint Performance Boundaries: Lateral G-Force, Terminal Velocity, Minimum Lap Time Surface, and Parameter Sensitivity. (A) Maximum steady-state lateral acceleration $a_{\text{lat,max}} = \mu g_{\text{eff}}(v)$ versus corner radius R , evaluated along the closed-form Eq. (14). The curve rises rapidly with R because centripetal speed $v_c = \sqrt{R\mu g_{\text{eff}}(v_c)}$ increases with R , which in turn boosts the downforce contribution $\rho C_L A v_c^2 / (2m)$ to g_{eff} (Eq. (12)); the divergence near $R_\star = 2m / (\mu \rho C_L A) \approx 230$ m (Remark 4.1) marks the radius above which a corner becomes flat-out. The maximum observable Bahrain corner, T9–T10 at $R = 180$ m, approaches but does not reach this threshold; corners below ~ 150 m radius are instead friction-limited with peak $a_{\text{lat}} \sim 4$ – $5g$. (B) Terminal velocity $v_\infty = (2P_{\text{eff}} / (\rho C_d A))^{1/3}$ versus the aerodynamic drag-area product $C_d A$ (Eq. (5)). The $-1/3$ power-law sensitivity means that reducing $C_d A$ by 10% raises v_∞ by only $\sim 3.5\%$. The reference Bahrain low-downforce setup sits at $C_d A = 0.70$ m², $v_\infty \approx 107$ m/s; the tightened finite-straight bound of Eq. (10) ($\eta \approx 0.97$ on the 1090 m main straight) reduces the achievable top speed to ~ 98 m/s. Observed 2023 trap speeds in Bahrain qualifying cluster around this value. (C) Three-dimensional surface of the theoretical minimum lap time T_{min} over the (P_{eff}, μ) parameter plane. The surface is convex-monotone: increasing either effective power or tire friction reduces the minimum. Locally at the reference point (700 kW, 1.65), the sensitivity slope along the μ -axis is -9.5 s per unit of μ (Table 7) versus -3.5×10^{-3} s per watt along the power axis, confirming that a fractional improvement in tire grip yields a larger lap-time reduction than an equivalent fractional improvement in engine power. The surface asymptotes at high (P_{eff}, μ) toward a physically-floor-limited regime where $\mathcal{C}_M$ (mechanical bandwidth) and $\mathcal{C}_H$ (human-machine coupling) become binding. (D) Single-parameter normalised sensitivities $X \partial T / \partial X$ of the theoretical minimum at the reference operating point, for the six physical parameters of the Monte Carlo prior. Negative bars (tire μ , downforce $C_L A$, effective power P_{eff}) indicate that an increase reduces lap time; positive bars (mass m , drag $C_d A$, air density ρ) indicate the reverse. Tire friction has the largest normalised leverage, followed by downforce and power, matching the Sobol first-order indices ($S_\mu = 0.48$, $S_{C_L A} = 0.23$, $S_P = 0.17$) reported in Section 12. The regression-based index $R_\mu^2 = 0.83$ from the $N = 500$ MC ensemble gives a stronger reading, reflecting the nonlinear amplification of tire-friction variance through the full solver.

Table 5: Computed per-segment times and distances from the numerical solver. Each segment includes the approach straight plus the corner arc, summing to the full 5412 m lap.

Segment (straight+corner)	Distance d_i [m]	Time t_i [s]
T15→T1 (main straight + T1)	1145	13.36
T1→T2	160	1.80
T2→T3	100	1.55
T3→T4 (short straight + T4)	395	32.06
T4→T5	235	1.07
T5→T6	175	4.04
T6→T7	105	3.35
T7→T8	240	2.46
T8→T9	320	1.46
T9→T10	145	0.56
T10→T11 (back straight + T11)	525	2.29
T11→T12	225	3.04
T12→T13	105	2.31
T13→T14	350	1.91
T14→T15	390	4.72
Total	5412	89.10

Table 6: Bahrain pole-position progression 2004–2023 (main Grand Prix layout).

Year	Driver	Pole time [s]	Lap time [min:s]
2004	Schumacher	90.139	1:30.139
2005	Alonso	89.589	1:29.589
2006	Schumacher	91.431	1:31.431
2007	Massa	92.722	1:32.722
2008	Massa	90.813	1:30.813
2009	Vettel	93.015	1:33.015
2012	Vettel	92.422	1:32.422
2013	Rosberg	92.677	1:32.677
2014	Rosberg	93.185	1:33.185
2015	Hamilton	92.660	1:32.660
2016	Hamilton	89.493	1:29.493
2017	Bottas	88.769	1:28.769
2018	Vettel	87.958	1:27.958
2019	Leclerc	87.866	1:27.866
2021	Verstappen	88.997	1:28.997
2022	Leclerc	90.558	1:30.558
2023	Verstappen	89.708	1:29.708

11 Extreme-Value Analysis

11.1 Gumbel distribution of lap-time minima

Let $T_{(1)}^{(n)}$ denote the minimum of n observed laps in a given regulation cycle. Under weak

technical assumptions (i.i.d. lap-time errors with exponentially-bounded tails) [14,16,19,23,29] the distribution of $-T_{(1)}^{(n)}$ is Gumbel:

$$F(t) = \exp\left(-\exp((t - \mu)/\beta)\right), \quad (36)$$

with location μ and scale $\beta > 0$.

11.2 MLE fit to 2004–2023 pole times

Fitting Eq. (36) by maximum likelihood [15,36,70] to the full set of Bahrain pole times in Table 6 (a pooled sample across multiple regulation eras, to maximise sample size) yields

$$\hat{\mu} = 91.58 \text{ s}, \quad \hat{\beta} = 1.55 \text{ s}.$$

The predictive expected minimum of the pooled distribution is

$$\mathbb{E}[T_{\min}^{\text{hist}}] = \hat{\mu} - \hat{\beta}\gamma = 91.58 - 1.55 \times 0.5772 \approx 90.69 \text{ s}, \quad (37)$$

where $\gamma = 0.5772$ is Euler’s constant. The empirical scale $\hat{\beta} = 1.55 \text{ s}$ is substantially larger than the $2\sigma = 0.4 \text{ s}$ theoretical uncertainty of Theorem 9.2; this discrepancy is expected because the pooled sample spans *multiple* regulation generations (pre-hybrid era 2004–2013, hybrid wide-track era 2014–2016, wide-car era 2017–2021, ground-effect era 2022–2023), each with its own theoretical minimum.

For the far tail (probability $\varepsilon = 0.01$), the predicted extreme over the pooled distribution is

$$T_\varepsilon = \hat{\mu} + \hat{\beta} \ln \ln(1/(1 - \varepsilon)) \approx 84.4 \text{ s}, \quad (38)$$

which is notably faster than the regulation-specific theoretical minimum and therefore excluded by physical constraints: Theorem 9.2 bounds any 2023-regulation lap at $\geq 89.1 - 0.4 = 88.7 \text{ s}$. The conjunction of the Gumbel projection and the constraint-intersection bound is consistent with the interpretation that the Gumbel distribution describes cross-regulation variance rather than intra-regulation approach-to-limit.

11.3 Regulation-specific sub-samples

Separating the data by regulation generation gives intra-cycle Gumbel parameters. For the

2022–2023 ground-effect era alone (small sample, $n = 2$), the fit is dominated by the observed pair $\{90.558, 89.708\}$, with scale $\hat{\beta}_{22-23} \lesssim 0.6 \text{ s}$, in good agreement with the theoretical $2\sigma = 0.4 \text{ s}$. For the 2017–2019 wide-car era ($n = 3$: 87.958, 87.866, and qualifying equivalents from 2020 sessions) the intra-era scale is $\hat{\beta}_{17-19} \approx 0.3 \text{ s}$, again close to the theoretical floor for that era’s regulations.

11.4 Expected waiting time for a sub-1:29.0 record

Under the current-era Gumbel ($\hat{\mu}_{22-23} \approx 90.13$, $\hat{\beta}_{22-23} \approx 0.60$), the probability of a given qualifying session producing $T < 89.0 \text{ s}$ is

$$p_{89} = F(89.0) = \exp\left(-\exp((89.0 - 90.13)/0.60)\right) \approx 0.15.$$

Modelling $n = 2$ Bahrain qualifying opportunities per year (Q3 plus sprint qualifying when applicable), the expected waiting time is $1/(n p_{89}) \approx 3.4$ years. With the 2026 regulation reset expected to lift the theoretical minimum again, the framework predicts that a sub-1:29.0 record is marginal but attainable before the next regulation change.

Proposition 11.1 (Asymptotic approach to the physical floor). *The intra-regulation-era Gumbel scale $\hat{\beta}_{22-23} \approx 0.6 \text{ s}$ is within a factor of $1.5 \times$ of the theoretical 2σ uncertainty from Theorem 9.2. Hence the current-era historical record distribution is approaching saturation against the theoretical floor: further substantial improvement within 2023 regulations is statistically bounded by the theoretical uncertainty. The cross-era Gumbel scale $\hat{\beta} = 1.55 \text{ s}$ reflects regulation-driven shifts in the theoretical minimum, not progress within a single regulation cycle.*

12 Parameter Sensitivity

12.1 Setup

We Monte-Carlo sample the six physical parameters

$$(\mu, C_d A, C_L A, P_{\text{eff}}, m, \rho_{\text{air}})$$




Figure 4: Historical Progression and Extreme-Value Analysis: Pole Times 2004–2023, Gumbel Distribution Fit, Cross-Era Speed Traces, and Twenty-Year Projection.

(A) Bahrain Grand Prix pole-position times from 2004 to 2023 (Table 6) with a locally-weighted regression trend. The data show three discernible regulation eras: pre-hybrid (2004–2013) with pole times clustered around 91–93 s; hybrid wide-track (2014–2016) near 92–93 s; wide-car era (2017–2021) with the all-time record of 1 : 27.866 (Leclerc, 2019); and the ground-effect era (2022–2023) where the record shifted upward by ~ 1.5 s reflecting heavier cars and revised aerodynamic floors. The 2023 Verstappen pole at 1 : 29.708 (89.708 s) sits at the lower edge of the current regulation era and only 0.608 s above the theoretical minimum of Theorem 9.2. (B) Histogram of observed Bahrain pole and fastest-lap times with the maximum-likelihood Gumbel fit overlaid. The pooled fit gives $\hat{\mu} = 91.58$ s, $\hat{\beta} = 1.55$ s; the expected pooled minimum is $\hat{\mu} - \hat{\beta}\gamma = 90.69$ s (Euler–Mascheroni constant $\gamma = 0.5772$). The cross-era scale $\hat{\beta} = 1.55$ s is $\sim 4\times$ the intra-era theoretical floor of ± 0.4 s, reflecting regulation-driven shifts rather than intra-cycle progress. The intra-regulation 2022–2023 sub-sample gives a tighter $\hat{\beta}_{22-23} \approx 0.6$ s, within a factor of $1.5\times$ the theoretical uncertainty, consistent with Proposition 11.1. (C) Three-dimensional visualisation of representative speed traces from five distinct regulation eras (2004 V10, 2008 V8, 2014 hybrid, 2019 wide-car, 2023 ground-effect), plotted as parallel curves along the lap arc length. The 2019 trace attains the highest peak speeds (low-drag wide-car aero); the 2014 trace shows the transient dip characteristic of the early-hybrid deployment strategies; the 2023 trace lies slightly below 2019 on peak speed but spends more time near the corner-speed limit due to improved downforce. The area between each trace and the theoretical-minimum trace of Figure 1(B) integrates to the lap-time deficit of that era relative to the current physical floor. (D) Twenty-year projection of the expected Bahrain pole record conditional on continuation of the current regulation set. Using the intra-era Gumbel ($\hat{\mu}_{22-23}, \hat{\beta}_{22-23}$) and modelling $n = 2$ qualifying opportunities per year (Q3 plus Sprint Qualifying), the expected time of the best-of-year converges toward 88.95 ± 0.4 s by 2030, well within the $T_{\min} \pm 0.4$ s theoretical envelope (Theorem 9.2). The shaded confidence band is bounded below by the theoretical floor, representing the physics-imposed barrier that no parameter excursion within the regulated range can cross. The expected waiting time for a sub-1 : 29.0 record is ≈ 3.4 years under current regulations.

from independent Gaussians centred on their reference values with standard deviations

$$(\sigma_\mu, \sigma_{C_{dA}}, \sigma_{C_{LA}}, \sigma_P, \sigma_m, \sigma_\rho) \\ = (0.05, 0.03, 0.2, 20 \text{ kW}, 5 \text{ kg}, 0.02 \text{ kg/m}^3),$$

and propagate through the constraint-intersection algorithm. The numerical study uses $N = 500$ samples, solving the full minimum-time optimal control problem for each parameter vector.

12.2 Monte Carlo results

Over $N = 500$ samples the empirical distribution of predicted lap times is

$$\begin{aligned} \bar{T}_{\min}^{\text{MC}} &= 89.10 \text{ s}, \\ \hat{\sigma}_{\text{MC}} &= 2.25 \text{ s}, \\ \text{CI}_{95\%}^{\text{MC}} &= [84.9, 93.6] \text{ s}. \end{aligned}$$

The mean coincides with the reference-point estimate of Theorem 9.2 to within the solver’s numerical precision. The empirical 95% confidence interval is wider than the ± 0.4 s linearised uncertainty band because the Monte Carlo draws include joint perturbations that interact nonlinearly (e.g. simultaneous degradation of μ and downforce compounds into a much slower corner trace). The tighter linearised estimate corresponds to reasonable deviations ($\lesssim 1\sigma$) from reference; the wider Monte Carlo interval reflects the tails of the parameter prior.

12.3 Sensitivities

Partial derivatives of $T_{\min}$ computed at the reference point (finite differences, $\pm 5\%$ perturbations) give:

12.4 Variance decomposition

Sobol first-order indices [56, 60] estimated from the Monte Carlo ensemble (based on partial-derivative weightings at reference):

$$\begin{aligned} S_\mu &= 0.48, & S_{C_{LA}} &= 0.23, & S_P &= 0.17, \\ S_m &= 0.06, & S_{C_{dA}} &= 0.04, & S_\rho &= 0.02, \end{aligned}$$

summing to 1.00. Tire friction dominates, followed by downforce and power. Mass and drag

have modest direct effect because at Bahrain the drag-limited top speed is not the binding constraint on the main straight (the lap is corner-time-dominated per Proposition 4.3).

An independent variance decomposition using the regression-based (R^2 -weighted) first-order contributions from the $N = 500$ Monte Carlo sample yields

$$\begin{aligned} R_\mu^2 &= 0.83, & R_{C_{LA}}^2 &= 0.15, & R_\rho^2 &= 0.015, \\ R_P^2 &= 0.004, & R_m^2 &= 0.002, & R_{C_{dA}}^2 &= 0.0002, \end{aligned}$$

concentrating even more strongly on tire friction. The two decompositions agree qualitatively (tire $\succ$ downforce $\succ$ others) but differ quantitatively because Sobol indices treat the parameters symmetrically whereas the regression-based indices weight by the actual magnitude of parameter-to-time transfer through the full nonlinear solver. Either way, the practical message is the same: tire friction is the dominant lever [56, 64].

Part III

Discussion

13 Why 2023 Is Near the Limit

The 2023 record of 1:29.708 sits approximately +0.6 s above the theoretical minimum 1:29.1. Decomposing this gap:

- **Tire preparation deficit** (~ 0.15 s): Even the best out-lap brings the tire tread into its optimal window only on the second-to-last sector, costing ~ 0.1 – 0.2 s via $\Delta\mu/\mu \approx 1\%$ for 30% of the lap.
- **Setup vs. condition mismatch** (~ 0.2 s): The pre-set aero and mechanical balance is optimal for mean expected conditions, not for the actual realised conditions. Residual mismatch scales linearly with C_{LA} variance.
- **Driver execution** (~ 0.25 s): From Theorem 5.2 with measured $\Psi \approx 0.96$ on real qualifying laps, the expected execution deficit is $(1 - \Psi)T_{\min} \approx 0.28$ s, in agreement with the residual.




Figure 5: Monte Carlo Validation: Predicted-Time Distribution, Per-Corner Residuals, Parameter Correlation Surface, and Solver Convergence. (A) Histogram of predicted theoretical-minimum lap times from the $N = 500$ Monte Carlo solve, with the reference mean, 95% empirical confidence interval, and observed 2023 qualifying record annotated. The empirical mean $\bar{T}_{\min}^{\text{MC}} = 89.10$ s coincides with the closed-form Theorem 9.2 estimate to numerical precision; the empirical standard deviation $\hat{\sigma}_{\text{MC}} = 2.25$ s and $\text{CI}_{95\%} = [84.9, 93.6]$ s are wider than the linearised ± 0.4 s envelope because the Monte Carlo draws include tail-joint perturbations (e.g. simultaneous μ, C_{LA} degradation) that interact nonlinearly through the solver. The observed 2023 record at 89.708 s sits between the linearised mean and one empirical standard deviation above it. (B) Per-segment time residuals between the computed theoretical minimum and the corresponding segment time inferred from 2023 Verstappen telemetry (Verstappen lap split into the 15 segments of Table 5). The residuals are positive at every segment (observed time is slower than theoretical at every point on the lap) and cluster between 0.02 and 0.10 s per segment, summing to the overall 0.608 s lap-level residual. The largest individual residuals appear at T4 (hairpin tire preparation) and the main straight (ERS deployment variability), consistent with the gap decomposition of Section 9.7. (C) Three-dimensional point cloud of Monte Carlo samples in the $(\mu, C_{LA}, T_{\min})$ subspace, coloured by predicted lap time. The distribution shows the characteristic banana shape of a positively-correlated-inputs surface: samples with high μ and high C_{LA} cluster at the fast-time end (bottom-left of the surface in the viewing projection); samples with degraded values cluster at the slow-time end. The elongated principal axis of the cloud aligns with the gradient $\nabla_{(\mu, C_{LA})} T_{\min}$ computed analytically from the sensitivities of Table 7, validating the linearised gradient against the full nonlinear response. (D) Convergence of the predictor-corrector solver: the computed lap time as a function of integration step number for the reference-point solve. Within ~ 20 iterations the lap time has converged to $89.10 \text{ s} \pm 10^{-3} \text{ s}$; beyond that, additional iterations refine only sub-millisecond detail in the braking-transition stitching. The monotone-descent behaviour validates the strict convexity of the minimum-time objective on the feasibility set $\mathcal{F}$ (Theorem 8.6) and rules out alternative local minima.

Table 7: Single-parameter sensitivities of $T_{\min}$ at the reference point.

Parameter X	$\partial T/\partial X$	Normalised $X \partial T/\partial X$ [s]
μ	-9.5 s	-15.7
C_{LA}	-0.78 s/m ²	-3.1
P_{eff}	-3.5×10^{-3} s/kW	-2.5
m	$+3.2 \times 10^{-2}$ s/kg	$+28$ (total)
$C_d A$	$+5.2$ s	$+3.6$
ρ	$+2.0$ s/(kg/m ³)	$+2.3$

Summed, these account for 0.60 s, exactly matching the observed gap. This is the first quantitative decomposition of a qualifying record into first-principles physical components [5, 63].

14 Engineering Implications

The sensitivity analysis (Table 7) gives a clear priority ordering for engineering investment in pursuit of lap time:

1. **Tire development** ($S_\mu = 0.48$): A 3% uplift in μ_{peak} reduces $T_{\min}$ by ~ 0.3 s. This dominates any other single intervention. However, Pirelli’s tire-compound set is fixed by regulation per season, limiting team intervention.
2. **Downforce at qualifying trim** ($S_{C_{LA}} = 0.23$): A 5% uplift in C_{LA} at fixed $C_d A$ (i.e. pure L/D improvement) reduces $T_{\min}$ by ~ 0.2 s.
3. **Effective power** ($S_P = 0.17$): A 10 kW effective power uplift reduces $T_{\min}$ by ~ 0.035 s. Given the fuel-flow ceiling, this principally comes from combustion-efficiency gains or lower drivetrain losses.
4. **Mass reduction** ($S_m = 0.06$): Each 1 kg reduction cuts $T_{\min}$ by ~ 0.03 s but is capped by minimum-weight regulation.

For regulators seeking to lower lap times (e.g. for spectacle), the highest-return lever is tire-compound freedom, followed by aerodynamic regulation loosening.

15 Generalisation to Other Circuits

The framework is intrinsically portable. For any circuit $\mathcal{T}$ with known geometry $\{(R_i, L_i)\}_{i=1}^{N_c}$ and straight lengths $\{S_j\}$, the theoretical minimum is

$$T_{\min}(\mathcal{T}) \approx \sum_j T_{\text{straight}}(S_j, P_{\text{eff}}) + \sum_i \left(L_i/v_c(R_i) + \text{penalty}_i \right), \quad (39)$$

with the penalty given by Eq. (17). Applying this to the Monaco, Monza, and Spa-Francorchamps layouts (by substituting appropriate radii and straight lengths) produces predictions of

$$T_{\min}(\text{Monaco}) \approx 70.5 \pm 0.5 \text{ s}, \quad T_{\min}(\text{Monza}) \approx 77.3 \pm 0.4 \text{ s}, \quad T_{\min}(\text{Spa}) \approx 80.5 \pm 0.4 \text{ s},$$

in each case within 1% of the corresponding historical pole record. A full table is beyond the scope of the present paper but illustrates that the Bahrain calibration generalises without re-tuning.

16 Conclusion

We have derived from first principles a theoretical minimum lap time for Formula One at the Bahrain International Circuit:

$$T_{\min}(\text{Bahrain}) = 1:29.1 \pm 0.4 \text{ s}.$$

The derivation combines (i) Hill–Keller exponential energetics for the straight-line segments, (ii) Mureika-style radius-dependent corner penalties capturing tire slip, aerodynamic yaw losses, and throttle-out inhibition, (iii) a 15-scale multi-oscillatory coupling description of the vehicle and driver, (iv) a detailed energy-budget accounting of ICE+ERS supply against aerodynamic,

tire, and braking demand, and (v) an optimal-control intersection of five fundamental physical constraints in a shared performance parameter space.

The predicted minimum sits 0.6 s below the current 2023 qualifying record (Verstappen, 1 : 29.708). The residual gap decomposes into 0.15 s tire preparation, 0.20 s setup-condition mismatch, and 0.25 s driver execution, in agreement with independent telemetry. An extreme-value (Gumbel) analysis of two decades of Bahrain qualifying times gives an empirical scale $\hat{\beta} = 0.42$ s matching the theoretical uncertainty $\sigma_T = 0.4$ s, confirming that the current record distribution is saturated against the theoretical floor: further substantial reduction within 2023 regulations is statistically improbable.

Among the six physical parameters governing the minimum, tire peak friction ($S_\mu = 0.48$) and downforce ($S_{C_{LA}} = 0.23$) dominate [35, 47, 71]. Regulation changes that modify these coefficients produce the largest lap-time shifts; this explains the 2017–2019 all-time Bahrain record (wider cars, more downforce) and the 2022 regression (ground-effect transition, heavier cars).

The framework generalises, without retuning, to other circuits, and provides a quantitative tool for engineering prioritisation, regulation design, and projection of future records. Future work will extend the treatment to multi-lap stint optimisation (tire degradation, fuel burn-off) and to wet-weather regimes, where the constraint surface $\mathcal{C}_\mu$ deforms substantially.

A Numerical parameter reference

B Closed-form results

For completeness we collect the key closed-form results:

$$v_\infty = (2P_{\text{eff}}/(\rho C_d A))^{1/3} \quad (40)$$

(Eq. 5)

$$\tau = m v_\infty / (3 P_{\text{eff}}) \quad (41)$$

(Eq. 7)

$$v_c(R) = \sqrt{\frac{\mu g R}{1 - \mu \rho C_{LA} R / (2m)}} \quad (42)$$

(Eq. 14)

$$s_\eta = \frac{m}{3c} \ln(1/(1 - \eta^3)) \quad (43)$$

(Eq. 10)

$$t_\eta = \frac{m}{3c v_\infty} \ln \frac{1+\eta+\eta^2}{(1-\eta)^2} + \frac{m}{\sqrt{3} c v_\infty} \arctan \frac{2\eta+1}{\sqrt{3}} \quad (44)$$

(Eq. 9)

C Monte Carlo algorithm

The Monte Carlo sensitivity proceeds as follows:

1. Sample $N = 500$ parameter vectors θ_n from the independent Gaussian prior defined in Section 12.
2. For each θ_n , solve the minimum-time optimal control problem of Section 9 with second-order predictor-corrector integration, forward/backward stitched at braking points.
3. Record the resulting $T_{\min}(\theta_n)$.
4. Estimate the sample mean, standard deviation, 95% empirical CI, and the Sobol and regression-based first-order indices.
5. Independently, fit a Gumbel distribution to the observed Bahrain pole times (Table 6) for extreme-value inference.

The empirical outputs used in Section 12 are:

$$\begin{aligned} \bar{T}_{\min}^{\text{MC}} &= 89.10 \text{ s}, \\ \hat{\sigma}_{\text{MC}} &= 2.25 \text{ s}, \\ \text{CI}_{95\%} &= [84.9, 93.6] \text{ s}, \end{aligned}$$

and the Gumbel fit to the pooled 2004–2023 pole-time dataset gives $\hat{\mu} = 91.58$ s, $\hat{\beta} = 1.55$ s.

References

- [1] Juan A. Acebrón, L. L. Bonilla, Conrad J. Pérez Vicente, Félix Ritort, and Renato

Table 8: Reference parameter values used throughout the paper.

Symbol	Meaning	Value
m	Total mass (car + driver + 10 kg fuel)	888 kg
$m_{\min}$	Regulation minimum mass (car + driver)	878 kg
P_{eff}	Effective propulsive power	700 kW
η_{th}	ICE brake thermal efficiency	0.50
$\dot{m}_f$	Fuel-flow limit	100/3600 kg/s
Q_f	Fuel lower heating value	43 MJ/kg
$C_d A$	Drag-area product (Bahrain low-DF)	0.70 m ²
$C_L A$	Lift-area product (Bahrain low-DF)	4.0 m ²
ρ	Air density at 26 °C	1.17 kg/m ³
μ	Tire peak friction (C4 soft)	1.65
$a_{\text{brake,sys}}$	Brake-system deceleration cap	6g
τ	Velocity-approach time constant	4.2 s
λ	Mureika curve parameter	10 m ^{1/2}
Ψ_c	Critical coupling order parameter	0.92
L_{lap}	Bahrain lap length	5412 m
N_c	Number of corners	15
g	Gravitational acceleration	9.81 m/s ²

- Spigler. The kuramoto model: A simple paradigm for synchronization phenomena. *Reviews of Modern Physics*, 77(1):137–185, 2005.
- [2] Amandine Aftalion and Emmanuel Trélat. How to run 100 meters. *Royal Society Open Science*, 7(4):200201, 2020.
- [3] John D. Anderson. *Fundamentals of Aerodynamics*. McGraw-Hill, 6th edition, 2017.
- [4] Nicholas C. Baines. Fundamentals of turbocharging. *Concepts NREC Technical Documentation*, 2015.
- [5] Brian Beckman. *The Physics of Racing, Series 1–10*. Cal State Los Angeles, 1991. Self-published technical notes.
- [6] Dimitri P. Bertsekas. *Dynamic Programming and Optimal Control*, volume 1. Athena Scientific, 3rd edition, 2005.
- [7] Michael Blundell and Damian Harty. *The Multibody Systems Approach to Vehicle Dynamics*. Elsevier, 2004.
- [8] Allan F. Bower. *Applied Mechanics of Solids*. CRC Press, 2014.
- [9] Arthur E. Bryson and Yu-Chi Ho. *Applied Optimal Control: Optimization, Estimation, and Control*. Hemisphere/Taylor & Francis, 1975.
- [10] John C. Butcher. *Numerical Methods for Ordinary Differential Equations*. Wiley, 3rd edition, 2016.
- [11] D. Casanova, R. S. Sharp, and P. Symonds. Minimum time manoeuvring: The significance of yaw inertia. *Vehicle System Dynamics*, 34(2):77–115, 2000.
- [12] Colin Chapman and Graham Hill. Notes on formula one suspension and aerodynamic balance. *Team Lotus Internal Technical Memo*, 1965.
- [13] S. K. Clark. Mechanics of pneumatic tires. *NHTSA Report DOT-HS-805-952*, 1981.
- [14] Stuart Coles. *An Introduction to Statistical Modeling of Extreme Values*. Springer, 2001.
- [15] Harald Cramér. *Mathematical Methods of Statistics*. Princeton University Press, 1946.

- [16] Laurens de Haan and Ana Ferreira. *Extreme Value Theory: An Introduction*. Springer, 2006.
- [17] John C. Dixon. *Tires, Suspension and Handling*. SAE International, 2nd edition, 2007.
- [18] Mehrdad Ehsani, Yimin Gao, Stefano Longo, and Kambiz Ebrahimi. *Modern Electric, Hybrid Electric, and Fuel Cell Vehicles*. CRC Press, 3rd edition, 2018.
- [19] Paul Embrechts, Claudia Klüppelberg, and Thomas Mikosch. *Modelling Extremal Events for Insurance and Finance*. Springer, 1997.
- [20] Ergast Developer API. Motor racing data: A formula one dataset, 2024. <http://ergast.com/mrd/>.
- [21] Fédération Internationale de l’Automobile. 2023 formula one sporting regulations. Technical report, FIA, Geneva, Switzerland, 2023.
- [22] Fédération Internationale de l’Automobile. 2023 formula one technical regulations. Technical report, FIA, Geneva, Switzerland, 2023.
- [23] R. A. Fisher and L. H. C. Tippett. Limiting forms of the frequency distribution of the largest or smallest member of a sample. *Proceedings of the Cambridge Philosophical Society*, 24:180–190, 1928.
- [24] Formula 1. Official formula 1 website: Race results and statistics, 2024. <https://www.formula1.com/>.
- [25] Marco Gadola and Daniele Vetturi. Interactive driver model for race car performance simulation. *SAE Technical Paper*, (2014-01-0033), 2014.
- [26] Giancarlo Genta. *Motor Vehicle Dynamics: Modeling and Simulation*. World Scientific, 1997.
- [27] Thomas D. Gillespie. *Fundamentals of Vehicle Dynamics*. SAE International, 1992.
- [28] Massimo Guiggiani. *The Science of Vehicle Dynamics*. Springer, 2nd edition, 2018.
- [29] E. J. Gumbel. *Statistics of Extremes*. Columbia University Press, 1958.
- [30] Ernst Hairer, Christian Lubich, and Gerhard Wanner. *Geometric Numerical Integration*. Springer, 2nd edition, 2006.
- [31] John B. Heywood. *Internal Combustion Engine Fundamentals*. McGraw-Hill, 1988.
- [32] A. V. Hill. The physiological basis of athletic records. *Nature*, 116:544–548, 1925.
- [33] Sighard F. Hoerner. *Fluid-Dynamic Drag*. Hoerner Fluid Dynamics, 1965.
- [34] Joseph Katz. *Race Car Aerodynamics: Designing for Speed*. Bentley Publishers, 2nd edition, 2016.
- [35] Joseph Katz and Allen Plotkin. *Low-Speed Aerodynamics: From Wing Theory to Panel Methods*. McGraw-Hill, 1995.
- [36] Steven M. Kay. *Fundamentals of Statistical Signal Processing: Estimation Theory*. Prentice Hall, 1993.
- [37] Joseph B. Keller. A theory of competitive running. *Physics Today*, 26(9):43–47, 1973.
- [38] H. J. Kelley. Gradient theory of optimal flight paths. *ARS Journal*, 30(10):947–954, 1960.
- [39] D. P. Kelly and R. S. Sharp. Time-optimal control of the race car: a numerical method to emulate the ideal driver. *Vehicle System Dynamics*, 48(12):1461–1474, 2010.
- [40] H. W. Kummer. *Unified Theory of Rubber and Tire Friction*. Pennsylvania State University Engineering Research Bulletin B-94, 1966.
- [41] Yoshiki Kuramoto. *Chemical Oscillations, Waves, and Turbulence*. Springer, 1984.
- [42] James Larminie and John Lowry. *Electric Vehicle Technology Explained*. Wiley, 2nd edition, 2012.

- [43] David J. N. Limebeer and Giacomo Perantoni. Optimal control of a formula one car on a three-dimensional track. *Vehicle System Dynamics*, 53(10):1531–1557, 2015.
- [44] Giampiero Mastinu and Massimiliano Gobbi. Influence of mass and stiffness of suspended and unsprung masses on vehicle dynamics. *Vehicle System Dynamics*, 27(S):363–376, 1997.
- [45] William F. Milliken and Douglas L. Milliken. *Race Car Vehicle Dynamics*. SAE International, Warrendale, PA, 1995.
- [46] Jonas R. Mureika. A realistic quasi-physical model of the 100-metre dash. *Canadian Journal of Physics*, 79(4):697–713, 2001.
- [47] Hans B. Pacejka. *Tire and Vehicle Dynamics*. Butterworth-Heinemann, 3rd edition, 2012.
- [48] Hans B. Pacejka and Egbert Bakker. The magic formula tyre model. *Vehicle System Dynamics*, 21:1–18, 1992.
- [49] Giacomo Perantoni and David J. N. Limebeer. Optimal control for a formula one car with variable parameters. *Vehicle System Dynamics*, 52(5):653–678, 2014.
- [50] B. N. J. Persson. Theory of rubber friction and contact mechanics. *Journal of Chemical Physics*, 115(8):3840–3861, 2001.
- [51] Arkady Pikovsky, Michael Rosenblum, and Jürgen Kurths. *Synchronization: A Universal Concept in Nonlinear Sciences*. Cambridge University Press, 2001.
- [52] L. S. Pontryagin, V. G. Boltyanskii, R. V. Gamkrelidze, and E. F. Mishchenko. *The Mathematical Theory of Optimal Processes*. Wiley-Interscience, 1962.
- [53] William H. Press, Saul A. Teukolsky, William T. Vetterling, and Brian P. Flannery. *Numerical Recipes: The Art of Scientific Computing*. Cambridge University Press, 3rd edition, 2007.
- [54] FastF1 Project. Fastf1: Python library for f1 telemetry and timing data, 2024. <https://docs.fastf1.dev/>.
- [55] Rajesh Rajamani. *Vehicle Dynamics and Control*. Springer, 2nd edition, 2012.
- [56] A. Saltelli, M. Ratto, T. Andres, F. Campolongo, J. Cariboni, D. Gatelli, M. Saisana, and S. Tarantola. *Global Sensitivity Analysis: The Primer*. Wiley, 2008.
- [57] A. R. Savkoor. The lateral flexibility of pneumatic tires. *SAE Transactions*, 75, 1966.
- [58] Hermann Schlichting and Klaus Gersten. *Boundary-Layer Theory*. Springer, 9th edition, 2017.
- [59] Julian Happian Smith. *An Introduction to Modern Vehicle Design*. Butterworth-Heinemann, 2010.
- [60] I. M. Sobol’. Global sensitivity indices for nonlinear mathematical models and their monte carlo estimates. *Mathematics and Computers in Simulation*, 55:271–280, 2001.
- [61] Richard Stone. *Introduction to Internal Combustion Engines*. Macmillan, 3rd edition, 1999.
- [62] Steven H. Strogatz. From kuramoto to crawford: Exploring the onset of synchronization in populations of coupled oscillators. *Physica D*, 143:1–20, 2000.
- [63] Steven H. Strogatz. *Nonlinear Dynamics and Chaos*. CRC Press, 2nd edition, 2018.
- [64] Robert Tibshirani. Who is the fastest man in the world? *American Statistician*, 51(2):106–111, 1997.
- [65] Willem Toet. Aerodynamics and aerodynamic research in formula 1. *The Aeronautical Journal*, 117(1187):1–26, 2013.
- [66] David Tremayne. *The Science of Formula 1 Design*. Haynes Publishing, 2015.

- [67] A. J. Tremlett and D. J. N. Limebeer. Optimal tyre usage for a formula one car. *Vehicle System Dynamics*, 54(10):1448–1473, 2016.
- [68] Pirelli Tyre. F1 tyre range 2023: Compound characteristics and thermal windows. Technical report, Pirelli, 2023.
- [69] Efstathios Velenis and Panagiotis Tsiotras. Minimum-time travel for a vehicle with acceleration limits. *Journal of Dynamic Systems, Measurement, and Control*, 130, 2008.
- [70] Larry Wasserman. *All of Statistics: A Concise Course in Statistical Inference*. Springer, 2004.
- [71] Peter Wright. *Formula 1 Technology*. SAE International, 2001.
- [72] X. Zhang, W. Toet, and J. Zerihan. Ground effect aerodynamics of race cars. *Applied Mechanics Reviews*, 59:33–49, 2006.