

Fullstack Development

Authentication / Authorization

Part 4: SPA

Setup

- `git clone https://github.com/fullstack-69/auth-spa.git`
- Backend
 - `cd backend`
 - Fill in `.env`
 - `pnpm install`
 - `pnpm run db:reset`
 - `pnpm run dev`

Setup

- Frontend
 - `cd frontend`
 - `pnpm install`
 - `pnpm run dev`

Backend

- Routes now return json / redirect header instead of html.
- Created `GET /me` route for clients to check their `auth` states.
- Apart from that, there is very minimal change, surprisingly.

22 hidden lines

23

app.use(passportIns.session());

24

25

// * Endpoints

26

app.get("/", async (req, res, next) => {

27

const sessions = await formatSession(req);

28

res.render("pages/index", {

29

title: "Home",

30

user: req.user,

31

sessions: sessions,

32

});

33

});

34

35

app.get("/signup", function (req, res) {

34 hidden lines

70

app.post("/login", passportIns.authenticate("local"), function (req, res) {

71

debug("@login handler");

72

setSessionInfoAfterLogin(req, "CREDENTIAL");

73

res.setHeader("HX-Redirect", "/");

74

res.send("<div></div>");

75

});

76

77

app.get("/login/oauth/github", passportIns.authenticate("github"));

20 hidden lines | app.get("/callback/google") callback

98

}

99

);

100

101

app.post("/logout", function (req, res, next) {

102

// req.logout will not delete the session in db. It will generate new one for the

103

// When the user login again, it will generate new session with the user id.

104

req.logout(function (err) {

5 hidden lines | req.session.destroy() callback

110

if (err) {

111

return next(err);

112

}

113

res.setHeader("HX-Redirect", "/");

114

res.send("<div></div>");

115

});

116

});

117

});

22 hidden lines

23

app.use(passportIns.session());

24

25

// * Endpoints

26+

app.get("/me", async (req, res, next) => {

27

const sessions = await formatSession(req);

28+

const user = req?.user ?? null;

29+

res.json({ sessions, user });

30

});

31

32

app.get("/signup", function (req, res) {

34 hidden lines

67

app.post("/login", passportIns.authenticate("local"), function (req, res) {

68

debug("@login handler");

69

setSessionInfoAfterLogin(req, "CREDENTIAL");

70+

res.status(200).json("Login Successful");

71

});

72

73

app.get("/login/oauth/github", passportIns.authenticate("github"));

20 hidden lines | app.get("/callback/google") callback

94

}

95

);

96

97+

app.get("/logout", function (req, res, next) {

98

// req.logout will not delete the session in db. It will generate new one for the alr

99

// When the user login again, it will generate new session with the user id.

100

req.logout(function (err) {

5 hidden lines | req.session.destroy() callback

106

if (err) {

107

return next(err);

108

}

109+

res.redirect("/");

110

});

111

});

112

});

Frontend

- Created (client-side) routing.
- Created logic to query/update `auth`'s state.
- Modified proxy server to take care of `Callback URL` (bypass client-routing).
- Created signup form/login and other UI.

Highlighted packages

```
{  
  "@tanstack/react-query": "^5.85.5",  
  "react-router": "^7.8.2"  
}
```

Client-side routing

src/App.tsx

```
import { RouterProvider } from "react-router-dom";
import { createBrowserRouter } from "react-router";
const router = createBrowserRouter([
  {
    path: "/",
    element: <Layout />,
    children: [
      {
        path: "/",
        element: <Home />,
      },
    ],
  },
]);
```

Client-side routing

src/App.tsx

```
function App() {  
  return (  
    // ...  
    <RouterProvider router={router} />  
    // ...  
  );  
}  
  
export default App;
```

Getting auth state

src/hooks/useAuth.ts

```
import { useQuery } from "@tanstack/react-query";
// ...
function getMe() {
  return axios.get<AuthData>("/api/me");
}

function useAuth() {
  // Queries
  const { data, error, refetch } = useQuery({
    queryFn: getMe,
    // Other options
  });
  return { user: data?.user, sessions: data?.sessions, error, refetch };
}
```

Getting auth state


src/components/Nav.tsx

```
const Nav: FC = () => {  
  const { user } = useAuth(); ➡➡➡  
  // ...  
  return (  
    <nav>  
      // ...  
    </nav>  
  );  
};  
  
export default Nav;
```

Handle Callback URL

vite.config.ts

```
export default defineConfig({
  plugins: [react()],
  server: {
    proxy: {
      "/api": {
        // ...
      },
      "/callback": { ➡➡➡
        target: "http://localhost:5002",
      },
    },
  },
});
```



With proxy server

- The cookie will automatically sent to backend for all requests because it is the "same site".

If you don't have proxy server.

- Cookies are still automatically sent given the same host but different port.
- Need to set `withCredentials` to `true` on any AJAX request (via `fetch` or `axios` APIs)
 - Note that `httpOnly` cookie are sent by this technique.
- Need to allow CORS in the backend.

But we still need more

- More OAuth providers
- Forget password feature
- Email confirmation
- OTP link
- Two factor authentication
- Passkey
- ...

| When can I start building my stuff?

Third-party solution

- *On cloud*
 - Clerk
- *On premise*
 - AuthJS
 - I used this last year
 - Better-Auth

Better-Auth

Design

- `Better-Auth` (and `AuthJS`) **is not a middleware**.
 - Unlike `passport`
- It provides ready-made API endpoints.
- This architecture is more suitable for SPAs and fullstack frameworks (`NextJS`).
 - *Using it with MPA is quite unintuitive.*

Setup

- `git clone https://github.com/fullstack-69/auth-spa-better-auth.git`
- Backend
 - `cd backend`
 - Fill in `.env`
 - `pnpm install`
 - `pnpm run db:reset`
 - `pnpm run dev`

Setup

- Frontend
 - `cd frontend`
 - `pnpm install`
 - `pnpm run dev`

Note

- DB schema
- `npx @better-auth/cli@latest generate`

New routes (backend)

```
16 // Better-Auth
17 app.all("/api/auth/*splat", toNodeHandler(auth)); // Add catch-all
18 app.use(express.json()); // Mount express json middleware after
19
20 // Running app
21 app.listen(PORT, async () => {
22   // ...
23 });
```

PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL PORTS

```
[nodemon] watching path(s): src\**\* db\**\* views\**\* public\**
[nodemon] watching extensions: js,ts,json
[nodemon] starting `tsx src/index.ts`
```

```
fs-auth:index Listening on port 5002: http://localhost:5002 +0m
POST /api/auth/sign-out 200 19.558 ms - -
GET /api/auth/get-session 200 4.931 ms - -
POST /api/auth/sign-in/email 200 170.991 ms - -
GET /api/auth/get-session 200 5.691 ms - -
POST /api/auth/sign-out 200 11.994 ms - -
GET /api/auth/get-session 200 1.368 ms - -
POST /api/auth/sign-in/social 200 22.641 ms - -
GET /api/auth/callback/github?code=133c5432bc10bd79999a&state=2owl
- -
GET /api/auth/get-session 200 4.126 ms - -
[nodemon] restarting due to changes...
[nodemon] starting `tsx src/index.ts`
```

Frontend client

useAuth.ts

```
import { useQuery } from "@tanstack/react-query";
import { authClient } from "../lib/auth-client";
function getMe() {
  return authClient.getSession();
}
```

Sign up

Signup.tsx

```
const res = await authClient.signUp.email({  
  email,  
  password,  
  name,  
  image: "logos/robot.png",  
});
```

Login (email)

```
const res = await authClient.signIn.email({  
  email,  
  password,  
  rememberMe: true,  
});
```

Login (Social)

```
const signInGithub = async () => {  
  const data = await authClient.signIn.social({  
    provider: "github",  
  });  
  console.log({ data });  
};
```

More features

- Forget password
- Email confirmation
- OTP link
- Two factor