

Payload Push Template WABA Converter Gateway

Daftar Isi

Payload Push Template WABA Converter Gateway.....	1
Daftar Isi.....	1
Send message push template.....	2
Penjelasan Parameters untuk payload push message.....	5
Penjelasan Header untuk Payload push Message.....	6
Penjelasan button untuk payload push message.....	7
Inbound message from push template with button.....	8
Response.....	9
Delivery status.....	10
Sign Off.....	10

Send message push template

Template

Template with only Text

```
{
  "channel": "whatsapp",
  "from": "brand",
  "recipient": "whatsapp_id",
  "type": "template",
  "template": {
    "name": "template_name",
    "language_code": "EN",
    "template_params": [
      {
        "value": "David"
      },
      {
        "value": "TN12399512"
      },
      {
        "value": "2020-06-28"
      }
    ]
  }
}
```

*Authentication template could only utilize this payload format

Untuk pengiriman OTP parameternya hanya 1, dan pada penamaan template mengandung unsur "otp" agar dari sisi converter mengenali pengiriman yang dilakukan untuk template Authentication contoh name template : **otp_trakindo**.

Template with Image Header & URL Button

```
{
  "channel": "whatsapp",
  "from": "brand_name",
  "recipient": "phone_number",
  "type": "template",
  "template": {
    "name": "template_name",
    "language_code": "language_code",
    "template_params": [
      { "value": "David" },
      { "value": "MYSEP4DTH20" },
      { "value": "HomeExpo2020" }
    ],
    "header": {
      "type": "image",
      "image": {
        "link": "http://xyz.com/testimage.jpg"
      }
    },
    "template_button": {
      "type": "url",
      "url_button": {
        "index": 0,
        "url_sufix": "url_sufix_value"
      }
    }
  }
}
```

Untuk brand name menggunakan value **Trakindo Alert**

Template with Text Header & Quick Reply Buttons

```
{
  "channel":"whatsapp",
  "from":"brand_name",
  "recipient":"phone_number",
  "type":"template",
  "template": {
    "name":"template_name",
    "language_code":"language_code",
    "template_params":[
      { "value":"David" },
      { "value":"MYSEPDTH20" }
    ],
    "header": {
      "type":"text",
      "params":[
        { "value":"param1" }
      ]
    },
    "template_button":{
      "type":"quick_reply",
      "quick_reply_buttons":[
        {
          "index":0,
          "payload":"User Clicked YES Button"
        },
        {
          "index":1,
          "payload":"User Clicked NO Button"
        },
        {
          "index":2,
          "Payload":"User Clicked CANCEL Button"
        }
      ]
    }
  }
}
```

Penjelasan Parameters untuk payload push message

Parameters

Parameter	Data Type	Mandatory?	Description																
from	string	Yes	Refer to Standard Parameters																
recipient	string	Yes	Refer to Standard Parameters																
type	string	Yes	Refer to Standard Parameters																
template	object	Yes	<table><tr><th>Parameter</th><th>Data Type</th><th>Mandatory?</th><th>Description</th></tr><tr><td>name</td><td>string</td><td>Yes</td><td>The name of the template to be used.</td></tr><tr><td>language_code</td><td>string</td><td>No</td><td>The code of the language or locale to use. Default code value is "en". Refer to the Supported Languages</td></tr><tr><td>template_params</td><td>array</td><td>Yes</td><td>This field is an array of values to apply to variables in the template. Guidelines: 1. Empty array should be appended if the template content has no variable(s) in it. Example: "template_params":[] 2. For "Authentication" template category message:</td></tr></table>	Parameter	Data Type	Mandatory?	Description	name	string	Yes	The name of the template to be used.	language_code	string	No	The code of the language or locale to use. Default code value is "en". Refer to the Supported Languages	template_params	array	Yes	This field is an array of values to apply to variables in the template. Guidelines: 1. Empty array should be appended if the template content has no variable(s) in it. Example: "template_params":[] 2. For "Authentication" template category message:
Parameter	Data Type	Mandatory?	Description																
name	string	Yes	The name of the template to be used.																
language_code	string	No	The code of the language or locale to use. Default code value is "en". Refer to the Supported Languages																
template_params	array	Yes	This field is an array of values to apply to variables in the template. Guidelines: 1. Empty array should be appended if the template content has no variable(s) in it. Example: "template_params":[] 2. For "Authentication" template category message:																

Penjelasan Header untuk Payload push Message

Header

Parameter	Data Type	Mandatory?	Description								
type	string	Yes	Describes the Header Type Values: text , image , video , document								
params	array of objects	No <i>(YES, if the Header type is 'text')</i>	This field is required if the Header Type is text . Maximum 1 param (object) allowed. <table> <tr> <th>Parameter</th><th>Data Type</th><th>Mandatory?</th><th>Description</th></tr> <tr> <td>value</td><td>string</td><td>Yes</td><td>Header text param value</td></tr> </table>	Parameter	Data Type	Mandatory?	Description	value	string	Yes	Header text param value
Parameter	Data Type	Mandatory?	Description								
value	string	Yes	Header text param value								
image	object	No <i>(YES, if the Header type is 'image')</i>	This field is required if Header Type is image <table> <tr> <th>Parameter</th><th>Data Type</th><th>Mandatory?</th><th>Description</th></tr> <tr> <td>link</td><td>string</td><td>Yes</td><td>An Image URL of type http/https</td></tr> </table>	Parameter	Data Type	Mandatory?	Description	link	string	Yes	An Image URL of type http/https
Parameter	Data Type	Mandatory?	Description								
link	string	Yes	An Image URL of type http/https								
video	object	No <i>(YES, if the Header type is 'video')</i>	This field is required if Header Type is video <table> <tr> <th>Parameter</th><th>Data Type</th><th>Mandatory?</th><th>Description</th></tr> <tr> <td>link</td><td>string</td><td>Yes</td><td>A Video URL of type http/https</td></tr> </table>	Parameter	Data Type	Mandatory?	Description	link	string	Yes	A Video URL of type http/https
Parameter	Data Type	Mandatory?	Description								
link	string	Yes	A Video URL of type http/https								
document	object	No <i>(YES, if the Header type is 'document')</i>	This field is required if Header Type is document <table> <tr> <th>Parameter</th><th>Data Type</th><th>Mandatory?</th><th>Description</th></tr> <tr> <td>link</td><td>string</td><td>Yes</td><td>A Document URL of type http/https</td></tr> </table>	Parameter	Data Type	Mandatory?	Description	link	string	Yes	A Document URL of type http/https
Parameter	Data Type	Mandatory?	Description								
link	string	Yes	A Document URL of type http/https								

Page | 34

			filename	string	No	Document Name.
--	--	--	----------	--------	----	----------------

Penjelasan button untuk payload push message

Template Button

Parameter	Data Type	Mandatory?	Description												
type	string	Yes	Describes the Button Type Values: <code>url</code> , <code>quick_reply</code>												
url_button	object	No	This field is required if the Button Type is 'url'. <table> <tr> <th>Parameter</th><th>Data Type</th><th>Mandatory?</th><th>Description</th></tr> <tr> <td>index</td><td>integer</td><td>Yes (No, if URL type is Static)</td><td>Index of the button index values: 0-2</td></tr> <tr> <td>url_suffix</td><td>string</td><td>Yes (No, if URL type is Static)</td><td>Suffix value for the url. Example: <code>www.youtube.com/{url_suffix}</code></td></tr> </table>	Parameter	Data Type	Mandatory?	Description	index	integer	Yes (No, if URL type is Static)	Index of the button index values: 0-2	url_suffix	string	Yes (No, if URL type is Static)	Suffix value for the url. Example: <code>www.youtube.com/{url_suffix}</code>
Parameter	Data Type	Mandatory?	Description												
index	integer	Yes (No, if URL type is Static)	Index of the button index values: 0-2												
url_suffix	string	Yes (No, if URL type is Static)	Suffix value for the url. Example: <code>www.youtube.com/{url_suffix}</code>												
quick_reply_buttons	objects	No	This field is required if the Button Type is 'quick_reply' and if you are sending any payloads. You can ignore this field if no payloads are being sent. Maximum 3 Buttons allowed. <table> <tr> <th>Parameter</th><th>Data Type</th><th>Mandatory?</th><th>Description</th></tr> <tr> <td>index</td><td>integer</td><td>No (Yes, if you include a payload)</td><td>Index of the button index values: 0-2</td></tr> <tr> <td>payload</td><td>string</td><td>No</td><td>Developer-defined payload that will be returned in MO</td></tr> </table>	Parameter	Data Type	Mandatory?	Description	index	integer	No (Yes, if you include a payload)	Index of the button index values: 0-2	payload	string	No	Developer-defined payload that will be returned in MO
Parameter	Data Type	Mandatory?	Description												
index	integer	No (Yes, if you include a payload)	Index of the button index values: 0-2												
payload	string	No	Developer-defined payload that will be returned in MO												

					(Yes, if you include a payload)	when the button is clicked by the user.
--	--	--	--	--	---------------------------------	---

Inbound message from push template with button

Button Reply

```
{
  "message": {
    "name": "sender",
    "from": "60123456789",
    "id": "1000000188223",
    "timestamp": "1585125726",
    "type": "interactive",
    "interactive": {
      "type": "button_reply",
      "button_reply": {
        "id": "2",
        "title": "Reply button 2"
      }
    },
    "reply_to": {
      "id": "1000000147671",
      "display_phone_number": "60198765432"
    }
  }
}
```

"button":{"payload":"AlertMana-223598823-0","text":"Selesai"}

Terdapat penyesuaian pada bagian payload yang diberikan perseg

Berikut full penyesuaiannya

```
{
  "message": {
    "name": "Juneidi Sabputra",
    "from": "628116852615",
    "id": "1000002358762",
    "timestamp": "1749300511",
    "type": "button",
    "button": {
      "payload": "AlertMana-223598823-0",
      "text": "Selesai"
    },
    "reply_to": {
      "id": "6000032132194",
      "display_phone_number": "628111500228"
    }
  }
}
```


Response

Parameter	Data Type	Sample Value	Definition
message_id	long	1000000147671	Unique message ID generated by Chat API

A successful response returns a unique identifier for the newly submitted message along with HTTP status code 200.

```
{  
  "message_id": 1000000000046  
}
```

Unsuccessful response returns the error message along with HTTP status code. Kindly refer to [2.1.2 HTTP Response](#)

```
{  
  "Message": "'From': Invalid value"  
}
```

The successful and unsuccessful responses shown above apply to all the message types.

For response with fallback enabled, kindly refer to [3.2 Response](#) under [3.0 Fallback](#).

Catatan :

Untuk response **failed** tanpa message id. Untuk reason failednya atau invalid sesuai yang ada di Coster.

Delivery status

Example: READ

```
{
  "message_status":
  {
    "message_id":1000000000050,
    "recipient":"60126507170",
    "status":"READ"
  }
}
```

Example: UNDELIVERED (WhatsApp)

```
{
  "message_status":
  {
    "message_id":123456,
    "recipient":"60126789456",
    "status":"UNDELIVERED",
    "description":"Invalid parameter."
  }
}
```

Catatan : Untuk Delivery status yang diberikan dari system jatis sesuai dengan status yang ada di meta, yaitu, **Sent, Delivered, read dan Failed**. Untuk failed pada Converter akan didefinisikan sebagai undelivered dengan reason failed sesuai informasi dari Meta. Sedangkan untuk status Accepted tidak ada pada delivery status yang converter kirimkan. Status Accepted jika didefinisikan adalah status sukses submit pesan ke Platform WABA Jatis (Coster)

Sign Off

Nama	Jabatan	Tanda Tangan
Surya Andika	ICT E-Commerce	

