

NAVV v4.0 Alpha – CLI Example Commands

This document provides copy-pasteable command-line examples that match the actual NAVV v4 CLI implementation. These examples assume use of the standalone **navv** executable built with PyInstaller.

Sanity Check

```
./navv --version
./navv --help
./navv generate --help
```

Pass 1 – Create New Workbook + Run Zeek

```
./navv generate GeekLoungeBaseline \
  --new-workbook \
  -p ~/Projects/pcaps/4SICS-GeekLounge-151022.pcap \
  -o ~/Projects/navv_tests/geeklounge_run1 \
  -z ~/Projects/navv_tests/geeklounge_run1/zeek_logs
```

Pass 2 – Iterate Using Existing Workbook and Zeek Logs

```
./navv generate GeekLoungeBaseline \
  -o ~/Projects/navv_tests/geeklounge_run1 \
  -z ~/Projects/navv_tests/geeklounge_run1/zeek_logs
```

Pass 2 – Refresh Zeek Logs but Preserve Workbook

```
./navv generate GeekLoungeBaseline \
  -p ~/Projects/pcaps/4SICS-GeekLounge-151022.pcap \
  -o ~/Projects/navv_tests/geeklounge_run1 \
  -z ~/Projects/navv_tests/geeklounge_run1/zeek_logs
```

Pass 1 – New Workbook with Guessed Segments

```
./navv generate GeekLoungeBaseline \
  --new-workbook --guess-segments \
  -p ~/Projects/pcaps/4SICS-GeekLounge-151022.pcap \
  -o ~/Projects/navv_tests/geeklounge_guess1 \
  -z ~/Projects/navv_tests/geeklounge_guess1/zeek_logs
```

Merge Guessed Segments into Existing Workbook

```
./navv generate GeekLoungeBaseline \  
  --guess-segments --guess-merge \  
  -o ~/Projects/navv_tests/geeklounge_run1 \  
  -z ~/Projects/navv_tests/geeklounge_run1/zeek_logs
```

Tuning Segment Guessing (Advanced)

```
# Increase confidence threshold for /24 guesses  
./navv generate GeekLoungeBaseline \  
  --new-workbook --guess-segments \  
  --guess-min-ips-24 5 \  
  -p ~/Projects/pcaps/4SICS-GeekLounge-151022.pcap \  
  -o ~/Projects/navv_tests/geeklounge_guess_tuned \  
  -z ~/Projects/navv_tests/geeklounge_guess_tuned/zeek_logs  
  
# Disable /16 roll-ups (recommended for most OT networks)  
./navv generate GeekLoungeBaseline \  
  --new-workbook --guess-segments \  
  --no-guess-enable-16 \  
  -p ~/Projects/pcaps/4SICS-GeekLounge-151022.pcap \  
  -o ~/Projects/navv_tests/geeklounge_guess_no16 \  
  -z ~/Projects/navv_tests/geeklounge_guess_no16/zeek_logs  
  
# Allow conservative /16 roll-ups when density is high  
./navv generate GeekLoungeBaseline \  
  --new-workbook --guess-segments \  
  --guess-enable-16 \  
  --guess-min-ips-16 256 \  
  --guess-min-24s-in-16 8 \  
  -p ~/Projects/pcaps/4SICS-GeekLounge-151022.pcap \  
  -o ~/Projects/navv_tests/geeklounge_guess_16 \  
  -z ~/Projects/navv_tests/geeklounge_guess_16/zeek_logs  
  
# /8 guessing is disabled by default and not recommended  
./navv generate GeekLoungeBaseline \  
  --new-workbook --guess-segments \  
  --guess-enable-8 \  
  -p ~/Projects/pcaps/4SICS-GeekLounge-151022.pcap \  
  -o ~/Projects/navv_tests/geeklounge_guess_8 \  
  -z ~/Projects/navv_tests/geeklounge_guess_8/zeek_logs
```

Notes

- Workbook filename is derived from CUSTOMER_NAME.
- Zeek runs only when -p/--pcap is supplied.
- --new-workbook controls template creation, not Zeek execution.
- Segment guessing is a starting point and must be reviewed.
- Excel is the primary user interface for analysis.