

MEDIUM-VOLTAGE METAL-CLAD SWITCHGEAR

DATA SHEET

Manufacturer: Eaton VacClad-W · Model: VCP-W-1600 · Serial: SG10243 · Standards: IEEE C37.20.2, ANSI C37.06, IEC 62271-200

Parameter	Value
Rated Maximum Voltage	15 kV
Rated Power Frequency	60 Hz
Rated Continuous Current	1600 A
Rated Short-Circuit Current	40 kA RMS sym
Rated Peak Withstand Current	104 kA
Rated Short-Time Withstand	40 kA / 3 s
Rated Lightning Impulse Withstand	95 kV BIL
Rated Power Frequency Withstand	36 kV / 1 min
Rated Closing Time	75 ms max
Rated Opening Time	50 ms max
Rated Total Interrupting Time	5 cycles (83 ms)
Rated Operating Sequence	O-0.3s-CO-15s-CO
Number of Operations (rated load)	10,000
Auxiliary Voltage	125 VDC
Trip Coil Current (125 VDC)	9.2 A
Operating Temperature Range	-30 to +40 °C

Compliance: IEEE C37.20.2-2015 (metal-clad), IEEE C37.04-1999 (rating structure), ANSI C37.06-2009 (preferred ratings), IEC 62271-200 (metal-enclosed MV switchgear). Factory tested per ANSI C37.09.