

# ■ Interview Questions & Answers

## ■ HTML Structure & Semantics

**Q:** Why start with ``?

**A:** It tells the browser to render in standards-compliant mode (HTML5), avoiding quirks mode and ensuring consistent interpretation across browsers.

**Q:** Purpose of ``

**A:** Declares the document language for accessibility tools, search engines, and proper hyphenation or pronunciation by screen readers.

**Q:** Roles of `` and ``

**A:** `` holds metadata, links, and scripts; `` contains content your users actually see and interact with.

**Q:** What does `` do?

**A:** Sets the document character encoding to UTF-8, supporting virtually all characters (emojis, international text) correctly.

**Q:** Why ``?

**A:** Instructs mobile browsers to control layout width and scaling, making designs responsive out of the box.

**Q:** Semantic alternatives to ``

**A:** Use ``, ```, ``, ```, or ``` for meaningful regions—boosts accessibility and SEO.

**Q:** Adding ARIA attributes

**A:** If these boxes represent UI regions or widgets, add ``role="region"``` and ``aria-label="Description"``` to improve screen-reader context.

## ■ CSS Fundamentals

**Q:** Selector specificity

**A:** Inline styles > IDs > classes/attributes > elements. Combining selectors (e.g., ``.parentEnclosureDiv .outerBox``) increases specificity.

**Q:** Units (``px``, ``%``, ``vh``, ``dvh``)

**A:** ``px`` is absolute; ``%`` is relative to parent; ``vh`` is 1% of viewport height (including browser chrome); ``dvh`` is 1% of the visible viewport, adjusting for dynamic browser UI.

**Q:** Percentage sizing calculation

**A:** A child's ``%`` width/height is based on its containing block's content box. Using ``dvh`` avoids jumps when mobile address bars show/hide.

**Q:** Box Model & ``border-box``

**A:** By default, borders/padding add outside the content size. Using ``box-sizing: border-box;`` includes them inside the width/height, simplifying layout math.

## ■ Layout with Flexbox

**Q:** `display: flex` basics

**A:** Turns a container into a flexbox, enabling straightforward alignment and distribution without hacks like absolute positioning.

**Q:** `align-items` vs. `justify-content`

**A:** `align-items: center` centers items along the cross-axis (vertical); `justify-content: center` centers along the main-axis (horizontal).

**Q:** Default flex properties

**A:** `flex-grow: 0` (no expansion), `flex-shrink: 1` (shrinks if needed), `flex-basis: auto` (initial size). Prevent shrinking with `flex-shrink: 0`.

**Q:** Old centering methods vs. Flexbox

**A:** Older tricks (absolute + transform, table/table-cell) were clunky; Flexbox is more semantic, predictable, and robust.

## ■ Viewport Units & Responsiveness

**Q:** `100vh` vs `100dvh`

**A:** `100vh` includes browser chrome's show/hide, causing layout jumps; `100dvh` matches the visible area, smoothing mobile viewport changes.

**Q:** Rotation & responsiveness

**A:** Percentages and viewport units recalculate on orientation change, keeping nested boxes proportional in portrait and landscape.

**Q:** Browser support & fallbacks

**A:** For browsers without `dvh`, fallback to `100vh` or update a CSS variable via JS on `resize` events.

## ■■ Best Practices & Optimization

**Q:** DRY up repeated styles

**A:** Create a utility class: `.centered-flex { display: flex; align-items: center; justify-content: center; }` or use a Sass/LESS mixin.

**Q:** Naming conventions (BEM)

**A:** Example: `.parent-enclosure__outer-box { }` and `.parent-enclosure__inner-box--third { }` clarify hierarchy and purpose.

**Q:** Nesting & performance

**A:** Deep nesting can impact paint times; flatten structure or simplify containers when possible.

**Q:** Preprocessors & utility libraries

**A:** Sass mixins or Tailwind utility classes keep code DRY, maintainable, and consistent.

## ■ Cross-Browser & Future-Proofing

**Q:** Testing legacy browsers

**A:** Use BrowserStack or VMs to verify flex and viewport-unit support; polyfill or provide fallbacks as needed.

**Q:** Progressive enhancement

**A:** Let modern browsers use ``dvh``, and serve fallback layouts (e.g., ``vh`` or JS-driven CSS) for older ones without breaking.

## ■ Additional Angles

**Q:** Flexbox vs CSS Grid

**A:** Use Grid for two-dimensional layouts (rows + columns), and Flexbox for one-dimensional alignment tasks.

**Q:** JavaScript dynamic styling

**A:** Listen to ``window.resize``, measure ``window.innerHeight``, and assign a CSS variable (e.g., ``--vh``) to adapt styles.

**Q:** Visual regression testing

**A:** Integrate tools like Percy or BackstopJS to snapshot and compare rendered components across changes.

**Q:** Accessibility deep dive

**A:** Use ``tabindex`` thoughtfully and maintain DOM order matching visual flow to keep keyboard navigation intuitive.