

http://www.thorlabs.com

Thorlabs GmbH Hans-Boeckler-Str. 6 85221 Dachau Germany

Tel.: +49 8131 5956 0 Fax.: +49 8131 5956 99

Certificate of Calibration

No

19270094207

X New Unit Returned Unit

Result as left:

PASS

Manufacturer

Thorlabs GmbH

Model Number

PM16-120

Serial Number

190927109

Date of Calibration

27-Sep-2019

Calibration Standards

NO	MANUFACTURER	MODEL	SERIAL NO	CERTIFICATION	LAST CAL	
1	Thorlabs	GM10HS	THO508	73324 19 PTB	3-Apr-2019	
2	Hamamatsu	S2281	THO505	73330 19 PTB	16-May-2019	
3	Thoriabs	S148C	15050530	NIST 685/0-79-19/1	31-May-2019	
4	Thorlabs	S180C	190605400	NIST 685/0-79-19/2	17-Jun-2019	

Thorlabs GmbH does hereby certify that the above mentioned equipment has been calibrated in accordance with our quality management system.

Our Quality Management System is certified according to DIN EN ISO 9001.

The measurement equipment used for calibration is traceable to national standards of the 'EUROMET' members (NPL, PTB, BNM etc.), the US 'NIST' or other national metrological institutions.

Measurements which cannot be traced to national standards can be traced to natural constants, other accepted standards or relational measurements.

Additional documentation concerning traceability of the measurement equipment is available and can be examined upon request.

The certificate of calibration may only be forwarded in complete form without any changes.

The recommended calibration interval is 12 months. The calibration period of this instrument / system begins on the date of receipt by the customer.

Calibrated by	Mark Csonka Thorlabs GmbH
Date Received	
Calibrated Due	[mm] filtprotocopil

Test Report - as left

Model PM16-120 Serial No 190927109 Scan CAL1

Temperature 24,5°C Humidity 47% Test Date 27-Sep-2019
Tester Mark Csonka
Result PASS

λ [nm]	η [A/W]	λ [nm]	η [A/W]	λ [nm]	η [A/W]						
400	2,23E-02	585	3,21E-02	770	3,87E-02	955	4,76E-02	113 0	TRUE	11111	3
405	2,28E-02	590	3,23E-02	775	3,90E-02	960	4,76E-02	A STATE OF THE STATE OF			
410	2,33E-02	595	3,24E-02	780	3,93E-02	965	4,76E-02		1		İ
415	2,38E-02	600	3,26E-02	785	3,95E-02	970	4,75E-02		1		İ
420	2,42E-02	605	3,27E-02	790	3,98E-02	975	4,74E-02		19.50		1
425	2,47E-02	610	3,29E-02	795	4,00E-02	980	4,71E-02		Account to the con-	A 1 4 4 5 4 7 1	
430	2,51E-02	615	3,30E-02	800	4,02E-02	985	4,67E-02			212 27	
435	2,54E-02	620	3,32E-02	805	4,05E-02	990	4,62E-02		i		1
440	2,57E-02	625	3,33E-02	810	4,07E-02	995	4,55E-02		i l		
445	2,60E-02	630	3,35E-02	815	4,10E-02	1000	4,47E-02	2.31.68			i
450	2,64E-02	635	3,36E-02	820	4,13E-02	1005	4,37E-02		1		i
455	2,67E-02	640	3,37E-02	825	4,15E-02	1010	4,25E-02				l
460	2,70E-02	645	3,39E-02	830	4,18E-02	1015	4,11E-02				1
465	2,72E-02	650	3,40E-02	835	4,20E-02	1020	3,95E-02	draw.			D 60017
470	2,75E-02	655	3,42E-02	840	4,23E-02	1025	3,76E-02				
475	2,77E-02	660	3,43E-02	845	4,26E-02	1030	3,56E-02				
480	2,79E-02	665	3,45E-02	850	4,28E-02	1035	3,33E-02	61.85.			900 E -
485	2,82E-02	670	3,46E-02	855	4,31E-02	1040	3,09E-02				
490	2,84E-02	675	3,48E-02	860	4,34E-02	1045	2,84E-02	19640			Indiana.
495	2,86E-02	680	3,50E-02	865	4,36E-02	1050	2,59E-02				1
500	2,89E-02	685	3,51E-02	870	4,39E-02	1055	2,32E-02	Later to the			
505	2,91E-02	690	3,53E-02	875	4,41E-02	1060	2,07E-02		1000		C 555 11 14
510	2,93E-02	695	3,54E-02	880	4,44E-02	1065	1,85E-02				į.
515	2,95E-02	700	3,56E-02	885	4,46E-02	1070	1,66E-02				i
520	2,97E-02	705	3,58E-02	890	4,49E-02	1075	1,49E-02		1000		
525	2,99E-02	710	3,61E-02	895	4,51E-02	1080	1,34E-02				
530	3,01E-02	715	3,63E-02	900	4,53E-02	1085	1,21E-02				
535	3,03E-02	720	3,65E-02	905	4,55E-02	1090	1,09E-02				
540	3,05E-02	725	3,67E-02	910	4,57E-02	1095	9,74E-03		adia		
545	3,07E-02	730	3,69E-02	915	4,59E-02	1100	8,67E-03				
550	3,08E-02	735	3,71E-02	920	4,61E-02		, , , , , ,		170		
555	3,10E-02	740	3,73E-02	925	4,63E-02		84To				
560	3,12E-02	745	3,76E-02	930	4,66E-02						
565	3,14E-02	750	3,78E-02	935	4,68E-02		818	100			
570	3,16E-02	755	3,80E-02	940	4,71E-02						
575	3,18E-02	760	3,83E-02	945	4,73E-02						
580	3,19E-02	765	3.85E-02	950	4 74F-02		Land Mark	10.7 CO 7 10	THE PORT P		CHOICE

