

202-450.exam.60q

Number: 202-450
Passing Score: 800
Time Limit: 120 min



Website: <https://vceplus.com>

VCE to PDF Converter: <https://vceplus.com/vce-to-pdf/>

Facebook: <https://www.facebook.com/VCE.For.All.VN/>

Twitter : https://twitter.com/VCE_Plus

<https://www.vceplus.com/>

202-450

Linux Professional Institute

Exam A

QUESTION 1

When the default policy for the netfilter INPUT chain is set to DROP, why should a rule allowing traffic to localhost exist?



<https://www.vceplus.com/>

- A. All traffic to localhost must always be allowed
- B. It doesn't matter; netfilter never affects packets addressed to localhost
- C. Some applications use the localhost interface to communicate with other applications
- D. `syslogd` receives messages on localhost
- E. The `iptables` command communicates with the netfilter management daemon `netfilterd` on localhost to create and change packet filter rules

Correct Answer: C

Section: (none)

Explanation



Explanation/Reference:

QUESTION 2

The content of which local file has to be transmitted to a remote SSH server in order to be able to log into the remote server using SSH keys?

- A. `~/.ssh/authorized_keys`
- B. `~/.ssh/config`
- C. `~/.ssh/id_rsa.pub`
- D. `~/.ssh/id_rsa`
- E. `~/.ssh/known_hosts`

Correct Answer: A

Section: (none)

Explanation

Explanation/Reference:

Reference: <https://www.digitalocean.com/community/tutorials/ssh-essentials-working-with-ssh-servers-clients-and-keys>

QUESTION 3

What is the name of the network security scanner project which, at the core, is a server with a set of network vulnerability tests?

- A. NetMap
- B. OpenVAS
- C. Smartscan
- D. Wireshark

Correct Answer: B

Section: (none)

Explanation

Explanation/Reference:

QUESTION 4

With fail2ban, what is a 'jail'?

- A. A netfilter rules chain blocking offending IP addresses for a particular service
- B. A group of services on the server which should be monitored for similar attack patterns in the log files
- C. A filter definition and a set of one or more actions to take when the filter is matched
- D. The chroot environment in which fail2ban runs

Correct Answer: C

Section: (none)

Explanation

Explanation/Reference:

Reference: <https://docs.plesk.com/en-US/onyx/administrator-guide/server-administration/protection-against-brute-force-attacks-fail2ban/fail2ban-jailsmanagement.73382/>

QUESTION 5

Which of the following Samba configuration parameters is functionally identical to the parameter `read only=yes`?

- A. `browseable=no`

- B. read write=no
- C. writeable=no
- D. write only=no
- E. write access=no

Correct Answer: C

Section: (none)

Explanation

Explanation/Reference:

QUESTION 6

How must Samba be configured such that it can check CIFS passwords against those found in `/etc/passwd` and `/etc/shadow`?

- A. Set the parameters `"encrypt passwords = yes"` and `"password file = /etc/passwd"`
- B. Set the parameters `"encrypt passwords = yes"`, `"password file = /etc/passwd"` and `"password algorithm = crypt"`
- C. Delete the `smbpasswd` file and create a symbolic link to the `passwd` and `shadow` file
- D. It is not possible for Samba to use `/etc/passwd` and `/etc/shadow` directly
- E. Run `smbpasswd` to convert `/etc/passwd` and `/etc/shadow` to a Samba password file

Correct Answer: D

Section: (none)

Explanation

Explanation/Reference:

QUESTION 7

Which of the following statements is true regarding the NFSv4 pseudo file system on the NFS server?

- A. It must be called `/exports`
- B. It usually contains bind mounts of the directory trees to be exported
- C. It must be a dedicated partition on the server
- D. It is defined in the option `Nfsv4-Root` in `/etc/pathmapd.conf`
- E. It usually contains symlinks to the directory trees to be exported

Correct Answer: B

Section: (none)

Explanation

Explanation/Reference:

QUESTION 8



A user requests a “hidden” Samba share, named `confidential`, similar to the Windows Administration Share. How can this be configured?

A.

```
[confidential]
comment = hidden share
path = /srv/smb/hidden
write list = user
create mask = 0700
directory mask = 0700

[$confidential]
comment = hidden share
path = /srv/smb/hidden
write list = user
create mask = 0700
directory mask = 0700

[#confidential]
comment = hidden share
path = /srv/smb/hidden
write list = user
create mask = 0700
directory mask = 0700
```

B.



C.

```
[%confidential]
comment = hidden share
path = /srv/smb/hidden
write list = user
create mask = 0700
directory mask = 0700
[confidential$]
comment = hidden share
path = /srv/smb/hidden
write list = user
create mask = 0700
directory mask = 0700
```

D.



E.

Correct Answer: E

Section: (none)

Explanation

Explanation/Reference:

QUESTION 9

Which of the following options are valid in `/etc/exports`? (Choose two.)



<https://www.vceplus.com/>

- A. `rw`
- B. `ro`
- C. `rootsquash`
- D. `norootsquash`
- E. `uid`



Correct Answer: AB

Section: (none)

Explanation

Explanation/Reference:

QUESTION 10

Which of these tools, without any options, provides the most information when performing DNS queries?

- A. `dig`

- B. nslookup
- C. host
- D. named-checkconf
- E. named-checkzone

Correct Answer: A

Section: (none)

Explanation

Explanation/Reference:

QUESTION 11

Performing a DNS lookup with dig results in this answer:

```
;; QUESTION SECTION:
```

```
5.123.168.192.in-addr.arpa.      IN      PTR
```

```
;; ANSWER SECTION:
```

```
5.123.168.192.in-addr.arpa. 600      IN      PTR linuxerv.example.net.123.168.192.in-addr.arpa.
```

```
;; AUTHORITY SECTION:
```

```
123.168.192.in-addr.arpa. 600      IN      NS      linuxerv.example.net.
```

```
;; ADDITIONAL SECTION:
```

```
linuxerv.example.net. 600      IN      A      192.168.123.5
```

- A. There is no . after linuxerv.example.net in the PTR record in the forward lookup zone file
- B. There is no . after linuxerv in the PTR record in the forward lookup zone file

- C. There is no `.` after `linuserv.example.net` in the PTR record in the reverse lookup zone file
- D. The `.` in the NS definition in the reverse lookup zone has to be removed

Correct Answer: C

Section: (none)

Explanation

Explanation/Reference:

QUESTION 12

What is DNSSEC used for?

- A. Encrypted DNS queries between nameservers
- B. Cryptographic authentication of DNS zones
- C. Secondary DNS queries for local zones
- D. Authentication of the user that initiated the DNS query
- E. Encrypting DNS queries and answers

Correct Answer: B

Section: (none)

Explanation

Explanation/Reference:

QUESTION 13

What word is missing from the following excerpt of a `named.conf` file?



```
_____ friends {  
    10.10.0.0/24; 192.168.1.0/24;  
};  
  
options {  
    allow-query { friends; };  
};
```

- A. networks
- B. net
- C. list
- D. acl
- E. group



Correct Answer: D

Section: (none)

Explanation

Explanation/Reference:

QUESTION 14

Which BIND option should be used to limit the IP addresses from which slave name servers may connect?

- A. allow-zone-transfer
- B. allow-transfer
- C. allow-secondary
- D. allow-slaves
- E. allow-queries

Correct Answer: B

Section: (none)

Explanation

Explanation/Reference:

QUESTION 15

In order to protect a directory on an Apache HTTPD web server with a password, this configuration was added to an `.htaccess` file in the respective directory:

```
AuthType Basic
AuthName "Protected Directory"
AuthUserFile /var/www/dir/.htpasswd
Require valid-user
```

Furthermore, a file `/var/www/dir/.htpasswd` was created with the following content:

```
usera:S3cr3t
```

Given that all these files were correctly processed by the web server processes, which of the following statements is true about requests to the directory?

- A. The user `usera` can access the site using the password `s3cr3t`
- B. Accessing the directory as `usera` raises HTTP error code 442 (User Not Existent)
- C. Requests are answered with HTTP error code 500 (Internal Server Error)
- D. The browser prompts the visitor for a username and password but logins for `usera` do not seem to work
- E. The web server delivers the content of the directory without requesting authentication

Correct Answer: A

Section: (none)

Explanation

Explanation/Reference:

QUESTION 16

Which Apache HTTPD directive enables HTTPS protocol support?

- A. `HTTPSEngine on`
- B. `SSLEngine on`

- C. SSLEnable on
- D. HTTPSEnable on
- E. StartTLS on

Correct Answer: B

Section: (none)

Explanation

Explanation/Reference:

QUESTION 17

Which `http_access` directive for Squid allows users in the ACL named `sales_net` to only access the Internet at times specified in the `time_acl` named `sales_time`?

- A. `http_access deny sales_time sales_net`
- B. `http_access allow sales_net sales_time`
- C. `http_access allow sales_net and sales-time`
- D. `allow http_access sales_net sales_time`
- E. `http_access sales_net sales_time`



Correct Answer: B

Section: (none)

Explanation

Explanation/Reference:

QUESTION 18

Which global option in `squid.conf` sets the port number or numbers that Squid will use to listen for client requests?

- A. `port`
- B. `client_port` C. `http_port`
- D. `server_port`
- E. `squid_port`

Correct Answer: C

Section: (none)

Explanation

Explanation/Reference:

QUESTION 19

Which tool creates a Certificate Signing Request (CSR) for serving HTTPS with Apache HTTPD?



<https://www.vceplus.com/>

- A. apachectl
- B. certgen
- C. cartool
- D. httpsgen
- E. openssl



Correct Answer: E

Section: (none)

Explanation

Explanation/Reference:

QUESTION 20

When trying to reverse proxy a web server through Nginx, what keyword is missing from the following configuration sample?

```
location / {  
    _____ http://proxiedserver:8080;  
}
```

- A. remote_proxy
- B. reverse_proxy
- C. proxy_reverse
- D. proxy_pass
- E. forward_to

Correct Answer: D

Section: (none)

Explanation

Explanation/Reference:



QUESTION 21

If there is no access directive, what is the default setting for OpenLDAP?

```
access to *  
by * read  
access to *  
by anonymous none  
by * read
```

B.

access to *

by anonymous auth

by * read

access to *

by anonymous write

by * read

C.

D.



Correct Answer: B

Section: (none)

Explanation

Explanation/Reference:

QUESTION 22

A host, called `lpi`, with the MAC address `08:00:2b:4c:59:23` should always be given the IP address of `192.168.1.2` by a DHCP server running ISC DHCPD.

Which of the following configurations will achieve this?

```
host lpi {  
    hardware-ethernet 08:00:2b:4c:59:23;  
    fixed-address 192.168.1.2;  
}  
  
host lpi {  
    mac=08:00:2b:4c:59:23;  
    ip=192.168.1.2;  
}
```

A.



B.

C. host lpi = 08:00:2b:4c:59:23 192.168.1.2

```
host lpi {  
    hardware ethernet 08:00:2b:4c:59:23;  
    fixed-address 192.168.1.2;  
}
```

```
host lpi {  
    hardware-address 08:00:2b:4c:59:23;  
    fixed-ip 192.168.1.2;  
}
```

D.



E.

Correct Answer: D

Section: (none)

Explanation

Explanation/Reference:

QUESTION 23

How is the LDAP administrator account configured when the `rootdn` and `rootpw` directives are not present in the `slapd.conf` file?

- A. The default account admin with the password admin are used
- B. The account is defined by an ACL in `slapd.conf`
- C. The default account admin is used without a password
- D. The account is defined in the file `/etc/ldap.secret`
- E. The account is defined in the file `/etc/ldap.root.conf`

Correct Answer: B

Section: (none)

Explanation

Explanation/Reference:

QUESTION 24

Which of the following PAM modules allows the system administrator to use an arbitrary file containing a list of user and group names with restrictions on the system resources available to them?

- A. `pam_filter`
- B. `pam_limits`
- C. `pam_listfile`
- D. `pam_unix`



Correct Answer: B

Section: (none)

Explanation

Explanation/Reference:

QUESTION 25

In a PAM configuration file, which of the following is true about the required control flag?

- A. If the module returns success, no more modules of the same type will be invoked
- B. The success of the module is needed for the module-type facility to succeed. If it returns a failure, control is returned to the calling application
- C. The success of the module is needed for the module-type facility to succeed. However, all remaining modules of the same type will be invoked
- D. The module is not critical and whether it returns success or failure is not important

E. If the module returns failure, no more modules of the same type will be invoked

Correct Answer: C

Section: (none)

Explanation

Explanation/Reference:

QUESTION 26

How are PAM modules organized and stored?

- A. As plain text files in `/etc/security/`
- B. As statically linked binaries in `/etc/pam.d/bin/`
- C. As Linux kernel modules within the respective sub directory of `/lib/modules/`
- D. As shared object files within the `/lib/` directory hierarchy
- E. As dynamically linked binaries in `/usr/lib/pam/sbin/`

Correct Answer: E

Section: (none)

Explanation

Explanation/Reference:

QUESTION 27

FILL BLANK

Which OpenLDAP client command can be used to change the password for an LDAP entry? (Specify ONLY the command without any path or parameters.)

Correct Answer: `ldappasswd`

Section: (none)

Explanation

Explanation/Reference:

QUESTION 28

A company is transitioning to a new DNS domain name and wants to accept e-mail for both domains for all of its users on a Postfix server.

Which configuration option should be updated to accomplish this?

- A. mydomain
- B. mylocations
- C. mydestination
- D. myhosts
- E. mydomains

Correct Answer: C

Section: (none)

Explanation

Explanation/Reference:

QUESTION 29

FILL BLANK

What is the path to the global Postfix configuration file? (Specify the full name of the file, **including path**.)

Correct Answer: etc/postfix/main.cf

Section: (none) **Explanation**

Explanation/Reference:

QUESTION 30

When are Sieve filters usually applied to an email?

- A. When the email is delivered to a mailbox
- B. When the email is relayed by an SMTP server
- C. When the email is received by an SMTP smarthost
- D. When the email is sent to the first server by an MUA
- E. When the email is retrieved by an MUA

Correct Answer: A

Section: (none)

Explanation

Explanation/Reference:

QUESTION 31

After the installation of Dovecot, it is observed that the dovecot processes are shown in ps ax like this:

```
31248 ?      S      0:00 dovecot/imap
31253 ?      S      0:00 dovecot/imap-login
```

In order to associate the processes with users and peers, the username, IP address of the peer and the connection status, which of the following options must be set?

- A. `--with-linux-extprocnames` for `./configure` when building Dovecot
- B. `sys.ps.allow_descriptions = 1` in `sysctl.conf` or `/proc`
- C. `proc.all.show_status = 1` in `sysctl.conf` or `/proc`
- D. `verbose_proctitle = yes` in the Dovecot configuration
- E. `process_format = "%u %I %s"` in the Dovecot configuration

Correct Answer: D

Section: (none)

Explanation

Explanation/Reference:

QUESTION 32

Which Postfix command can be used to rebuild all of the alias database files with a single invocation and without the need for any command line arguments?

- A. `makealiases`
- B. `newaliases`
- C. `postalias`
- D. `postmapbuild`

Correct Answer: B

Section: (none)

Explanation

Explanation/Reference:

QUESTION 33

Which of the following authentication mechanisms are supported by Dovecot? (Choose three.)

- A. ldap
- B. digest-md5
- C. cram-md5
- D. plain
- E. krb5

Correct Answer: BCD

Section: (none)

Explanation

Explanation/Reference:

Reference: <https://wiki2.dovecot.org/Authentication/Mechanisms>

QUESTION 34

Which of the following actions synchronizes UNIX passwords with the Samba passwords when the encrypted Samba password is changed using `smbpasswd`?

- A. There are no actions to accomplish this since it is not possible.
- B. Run `netvamp` regularly, to convert the passwords.
- C. Run `winbind -sync`, to synchronize the passwords.
- D. Add `unix password sync = yes` to `smb.conf`
- E. Add `smb unix password = sync` to `smb.conf`

Correct Answer: D

Section: (none)

Explanation

Explanation/Reference:

Reference: https://www.oreilly.com/openbook/samba/book/ch06_04.html

QUESTION 35

In order to join a file server to the Active Directory domain `intra.example.com`, the following `smb.conf` has been created:

```
[global]
```

```
workgroup = intra.example.com
netbios name = Fileserver
server role = member server
idmap config * : backend = tdb
idmap config * : range = 10000-199999
winbind enum users = yes
winbind enum group = yes
```

The command `net ads join` raises an error and the server is not joined to the domain. What should be done to successfully join the domain?

- A. Change server role to `ad member server` to join an Active Directory domain instead of an NT4 domain.
- B. Add `realm = intra.example.com` to the `smb.conf` and change `workgroup` to the domain's netbios workgroup name.
- C. Manually create a machine account in the Active Directory domain and specify the machine account's name with `-U` when starting `net ads join`.
- D. Remove the `winbind enum users` and `winbind enum groups` since `winbind` is incompatible with Active Directory domains.
- E. Remove all `idmap` configuration stanzas since the id mapping is defined globally in an Active Directory domain and cannot be changed on a member server.

Correct Answer: E

Section: (none)

Explanation

Explanation/Reference:

QUESTION 36

FILL BLANK

In order to export `/usr` and `/bin` via NFSv4, `/exports` was created and contains working bind mounts to `/usr` and `/bin`. The following lines are added to `/etc/exports` on the NFS server:

```
/exports    192.0.1.0/24 (rw, sync, fsid=0, crossmnt, no_subtree_check)

/exports/usr 192.0.2.0/24 (rw, sync, fsid=0, crossmnt, no_subtree_check)

/exports/bin 192.0.2.0/24 (rw, sync, fsid=0, crossmnt, no_subtree_check)
```

After running

```
mount -t nfsv4 server:/ /mnt
```

of an NFS-Client, it is observed that `/mnt` contains the content of the server's `/usr` directory instead of the content of the NFSv4 root folder.

Which option in `/etc/exports` has to be changed or removed in order to make the NFSv4 root folder appear when mounting the highest level of the server? (Specify **ONLY** the option name without any values or parameters.)

Correct Answer: mount

Section: (none)

Explanation

Explanation/Reference:

QUESTION 37

What does the `samba-tool testparm` command confirm regarding the Samba configuration?

- A. The configuration loads successfully.
- B. The service operates as expected.
- C. The Samba services are started automatically when the system boots.
- D. The netfilter configuration on the Samba server does not block any access to the services defined in the configuration.
- E. All running Samba processes use the most recent configuration version.

Correct Answer: A

Section: (none)

Explanation

Explanation/Reference:

Reference: <https://www.samba.org/samba/docs/current/man-html/testparm.1.html>

QUESTION 38

Select the Samba option below that should be used if the main intention is to setup a guest printer service?



<https://www.vceplus.com/>

- A. security = cups
- B. security = ldap
- C. security = pam
- D. security = share
- E. security = printing

Correct Answer: D

Section: (none)

Explanation

Explanation/Reference:

QUESTION 39

The Samba configuration file contains the following lines:

```
host allow = 192.168.1.100 192.168.2.0/255.255.255.0 local host
host deny = 192.168.2.31
interfaces = 192.168.1.0/255.255.255.0 192.168.2.0/255.255.255.0
```

A workstation is on the wired network with an IP address of 192.168.1.177 but is unable to access the Samba server. A wireless laptop with an IP address 192.168.2.93 can access the Samba server. Additional trouble shooting shows that almost every machine on the wired network is unable to access the Samba server.

Which alternate `host allow` declaration will permit wired workstations to connect to the Samba server without denying access to anyone else?

- A. host allow = 192.168.1.1-255
- B. host allow = 192.168.1.100 192.168.2.200 localhost
- C. host deny = 192.168.1.100/255.255.255.0 192.168.2.31 localhost
- D. host deny = 192.168.2.200/255.255.255.0 192.168.2.31 localhost
- E. host allow = 192.168.1.0/255.255.255.0 192.168.2.0/255.255.255.0 localhost

Correct Answer: DE

Section: (none)

Explanation

Explanation/Reference:

QUESTION 40

FILL BLANK

What command displays NFS kernel statistics? (Specify **ONLY** the command without any path or parameters.)

Correct Answer: nfsstat

Section: (none)

Explanation

Explanation/Reference:

Reference: <https://www.systutorials.com/docs/linux/man/8-nfsstat/>

QUESTION 41

Which keyword is used in the Squid configuration to define networks and times used to limit access to the service?

- A. acl
- B. allow
- C. http_allow
- D. permit

Correct Answer: A

Section: (none)

Explanation

Explanation/Reference:

Reference: <https://www.tecmint.com/configure-squid-server-in-linux/>

QUESTION 42

The following Apache HTTPD configuration has been set up to create a virtual host available at www.example.com and www2.example.com:

```
<VirtualHost *:80>

    ServerName www.example.com

    ServerName www2.example.com

    ServerAdmin webmaster@example.com

    DocumentRoot /var/www/

    <Directory /srv/www/>
        Require all granted
    </Directory>

</VirtualHost>
```

Even though Apache HTTPD correctly processed the configuration file, requests to both names are not handled correctly. What should be changed in order to ensure correct operations?

- A. The configuration must be split into two `VirtualHost` sections since each virtual host may only have one name.
- B. The port mentioned in opening `VirtualHost` tag has to be appended to the `ServerName` declaration's values.
- C. Both virtual host names have to be placed as comma separated values in one `ServerName` declaration.
- D. Both virtual host names have to be mentioned in the opening `VirtualHost` tag.
- E. Only one Server name declaration may exist, but additional names can be declared in `ServerAlias` options.

Correct Answer: C

Section: (none)

Explanation

Explanation/Reference:

QUESTION 43

Which Apache HTTPD configuration directive specifies the RSA private key that was used in the generation of the SSL certificate for the server?

- A. SSLCertificateKeyFile
- B. SSLKeyFile
- C. SSLPrivateKeyFile
- D. SSLRSAKeyFile

Correct Answer: A

Section: (none)

Explanation

Explanation/Reference:

Reference: https://httpd.apache.org/docs/2.4/ssl/ssl_faq.html#aboutcerts

QUESTION 44

There is a restricted area in a site hosted by Apache HTTPD, which requires users to authenticate against the file `/srv/www/security/sitepasswd`.

Which command is used to **CHANGE** the password of existing users, without losing data, when Basic authentication is being used?

- A. `htpasswd -c /srv/www/security/sitepasswd user`
- B. `htpasswd /srv/www/security/sitepasswd user`
- C. `htpasswd -n /srv/www/security/sitepasswd user`
- D. `htpasswd -D /srv/www/security/sitepasswd user`

Correct Answer: A

Section: (none)

Explanation

Explanation/Reference:

Reference: <https://httpd.apache.org/docs/2.4/howto/auth.html>

QUESTION 45

Which Apache HTTPD configuration directive is used to specify the method of authentication, e.g. None or Basic?

- A. AuthUser
- B. AllowedAuthUser

- C. AuthType
- D. AllowAuth

Correct Answer: C

Section: (none)

Explanation

Explanation/Reference:

Reference: <https://httpd.apache.org/docs/2.4/howto/auth.html>

QUESTION 46

With Nginx, which of the following directives is used to proxy requests to a FastCGI application?

- A. fastcgi_pass
- B. fastcgi_proxy
- C. proxy_fastcgi
- D. proxy_fastcgi_pass
- E. fastcgi_forward



Correct Answer: A

Section: (none)

Explanation

Explanation/Reference:

QUESTION 47

What is the standard port used by OpenVPN?

- A. 1723
- B. 4500
- C. 500 D. 1194

Correct Answer: D

Section: (none)

Explanation

Explanation/Reference:

Reference: <https://openvpn.net/archive/openvpn-users/2006-04/msg00355.html>

QUESTION 48

Which of the following commands can be used to connect and interact with remote TCP network services? (Choose two.)

- A. nettalk
- B. nc
- C. telnet D. cat
- E. netmap

Correct Answer: BC

Section: (none)

Explanation

Explanation/Reference:

QUESTION 49

To which destination will a route appear in the Linux routing table after activating IPv6 on a router's network interface, even when no global IPv6 addresses have been assigned to the interface?

- A. fe80::/10
- B. 0::/128
- C. 0::/0
- D. fe80::/64
- E. 2000::/3

Correct Answer: A

Section: (none)

Explanation

Explanation/Reference:

QUESTION 50

Which command is used to administer IPv6 netfilter rules?

- A. iptables
- B. iptablesv6
- C. iptables6
- D. ip6tables
- E. ipv6tables

Correct Answer: D

Section: (none)

Explanation

Explanation/Reference:

Reference: https://www.centos.org/docs/5/html/5.1/Deployment_Guide/s1-ip6tables.html

QUESTION 51

Which netfilter table contains built-in chains called INPUT, OUTPUT and FORWARD?

- A. ipconn
- B. filter
- C. nat
- D. default
- E. masq



Correct Answer: B

Section: (none)

Explanation

Explanation/Reference:

Reference: <http://shorewall.org/NetfilterOverview.html>

QUESTION 52

Which of these tools provides DNS information in the following format?

```
www.example.com has address 172.25.25.55
```

```
www.example.com has address 172.25.25.63
```

```
www.example.com has IPv6 address fdb4:8fbc:36e1::101f
```


- A. dig
- B. nslookup
- C. host
- D. named-checkconf
- E. named-checkzone

Correct Answer: C

Section: (none)

Explanation

Explanation/Reference:

QUESTION 53

Which `rndc` sub command can be used in conjunction with the name of a zone in order to make BIND reread the content of the specific zone file without reloading other zones as well?

- A. lookup
- B. reload
- C. fileupdate D. reread
- E. zoneupdate



Correct Answer: AC

Section: (none)

Explanation

Explanation/Reference:

QUESTION 54

Which of the following DNS record types is used for reverse DNS queries?



<https://www.vceplus.com/>

- A. CNAME
- B. IN
- C. PTR
- D. REV
- E. RIN

Correct Answer: C

Section: (none)

Explanation

Explanation/Reference:

Reference: <http://help.dnsmadeeasy.com/managed-dns/dns-record-types/ptr-record/>

QUESTION 55

FILL BLANK

According to the configuration below, what is the full e-mail address of the administrator for this domain?



```
$ORIGIN example.com  
@      IN      SOA  mars.example.com pluto.example.com (  
        2016073142  
        10800  
        3600  
        604800  
        86400 )
```

Correct Answer: admin@mars.example.com

Section: (none)

Explanation

Explanation/Reference:

QUESTION 56

What is the purpose of DANE?

- A. Verify the integrity of name information retrieved via DNS.
- B. Allow secure dynamic DNS updates.
- C. Invalidate name information stored on caching name servers to speed up DNS updates.
- D. Discover which servers within a DNS domain offer a specific service.
- E. Provide a way to verify the association of X 509 certificates to DNS host names.

Correct Answer: E

Section: (none)

Explanation

Explanation/Reference:

Reference: <https://wiki.archlinux.org/index.php/DANE>

QUESTION 57

Which option in `named.conf` specifies which host are permitted to ask for domain name information from the server?

- A. allowed-hosts
- B. accept-query
- C. permit-query
- D. allow-query
- E. query-group

Correct Answer: D

Section: (none)

Explanation

Explanation/Reference:

QUESTION 58

Which of the following statements allow the logical combinations of conditions in Sieve filters? (Choose two.)

- A. allof
- B. anyof
- C. noneof
- D. and
- E. or



Correct Answer: AE

Section: (none)

Explanation

Explanation/Reference:

Reference: <https://kb.vircom.com/kbase/redirfile.asp?id=581&SID=>

QUESTION 59

What is the name of the Dovecot configuration variable that specifies the location of user mail?

- A. mbox
- B. mail_location
- C. user_dir
- D. maildir

E. user_mail_dir

Correct Answer: B

Section: (none)

Explanation

Explanation/Reference:

QUESTION 60

Which of the following commands displays an overview of the Postfix queue content to help identify remote sites that are causing excessive mail traffic?

- A. mailtraf
- B. queuequery
- C. qshape
- D. postmap
- E. poststats

Correct Answer: C

Section: (none)

Explanation

Explanation/Reference:

Reference: <https://easyengine.io/tutorials/mail/postfix-queue/>



<https://www.vceplus.com/>