

202-450.65q

Number: 202-450
Passing Score: 800
Time Limit: 120 min



Website: <https://vceplus.com>
VCE to PDF Converter: <https://vceplus.com/vce-to-pdf/>
Facebook: <https://www.facebook.com/VCE.For.All.VN/>
Twitter : https://twitter.com/VCE_Plus

202-450

Linux Professional Institute

Exam A

QUESTION 1

On a Linux router, packet forwarding for IPv4 has been enabled. After a reboot, the machine no longer forwards IP packets from other hosts. The command:

```
echo 1 > /proc/sys/net/ipv4/ip_forward
```

temporarily resolves this issue.

Which one of the following options is the best way to ensure this setting is saved across system restarts?

- A. Add `echo 1 > /proc/sys/net/ipv4/ip_forward` to the root user login script
- B. Add `echo 1 > /proc/sys/net/ipv4/ip_forward` to any user login script
- C. In `/etc/sysctl.conf` change `net.ipv4.ip_forward` to 1
- D. In `/etc/rc.local` add `net.ipv4.ip_forward = 1`
- E. In `/etc/sysconfig/iptables-config` add `ipv4.ip_forward = 1`

Correct Answer: C

Section: (none)

Explanation

Explanation/Reference:



QUESTION 2

What information can be found in the file specified by the `status` parameter in an OpenVPN server configuration file? (Choose two.)



<https://www.vceplus.com/>

- A. Errors and warnings generated by the `openvpn` daemon
- B. Routing information

- C. Statistical information regarding the currently running `openvpn` daemon
- D. A list of currently connected clients
- E. A history of all clients who have connected at some point

Correct Answer: BD

Section: (none)

Explanation

Explanation/Reference:

QUESTION 3

Which of the following lines in the `sshd` configuration file should, if present, be changed in order to increase the security of the server? (Choose two.)

- A. `Protocol 2, 1`
- B. `PermitEmptyPasswords no`
- C. `Port 22`
- D. `PermitRootLogin yes`
- E. `IgnoreRhosts yes`



Correct Answer: AD

Section: (none)

Explanation

Explanation/Reference:

QUESTION 4

Which of the following `nmap` parameters scans a target for open TCP ports? (Choose two.)

- A. `-sO`
- B. `-sZ`
- C. `-sT`
- D. `-sU`
- E. `-sS`

Correct Answer: CE

Section: (none)

Explanation

Explanation/Reference:

QUESTION 5

What option in the client configuration file would tell OpenVPN to use a dynamic source port when making a connection to a peer?

- A. src-port
- B. remote
- C. source-port
- D. nobind
- E. dynamic-bind

Correct Answer: D

Section: (none)

Explanation



Explanation/Reference:

QUESTION 6

The content of which local file has to be transmitted to a remote SSH server in order to be able to log into the remote server using SSH keys?

- A. ~/.ssh/authorized_keys
- B. ~/.ssh/config
- C. ~/.ssh/id_rsa.pub
- D. ~/.ssh/id_rsa
- E. ~/.ssh/known_hosts

Correct Answer: A

Section: (none)

Explanation

Explanation/Reference:

Reference: <https://www.digitalocean.com/community/tutorials/ssh-essentials-working-with-ssh-servers-clients-and-keys>

QUESTION 7

With fail2ban, what is a 'jail'?

- A. A netfilter rules chain blocking offending IP addresses for a particular service
- B. A group of services on the server which should be monitored for similar attack patterns in the log files
- C. A filter definition and a set of one or more actions to take when the filter is matched
- D. The chroot environment in which fail2ban runs

Correct Answer: C

Section: (none)

Explanation

Explanation/Reference:

Reference: <https://docs.plesk.com/en-US/onyx/administrator-guide/server-administration/protection-against-brute-force-attacks-fail2ban/fail2ban-jailsmanagement.73382/>

QUESTION 8

Which of the following Samba configuration parameters is functionally identical to the parameter `read only=yes`?

- A. `browseable=no`
- B. `read write=no`
- C. `writeable=no`
- D. `write only=no`
- E. `write access=no`

Correct Answer: C

Section: (none)

Explanation

Explanation/Reference:**QUESTION 9**

Which of the following Samba services handles the membership of a file server in an Active Directory domain?

- A. winbindd
- B. nmbd
- C. msadd
- D. admemb
- E. samba

Correct Answer: E

Section: (none)

Explanation

Explanation/Reference:

QUESTION 10

Which of the following statements is true regarding the NFSv4 pseudo file system on the NFS server?

- A. It must be called `/exports`
- B. It usually contains bind mounts of the directory trees to be exported



<https://www.vceplus.com/>

- C. It must be a dedicated partition on the server
- D. It is defined in the option `Nfsv4-Root` in `/etc/pathmapd.conf`
- E. It usually contains symlinks to the directory trees to be exported

Correct Answer: B

Section: (none)

Explanation

Explanation/Reference:

QUESTION 11

Which of the following options are valid in `/etc/exports`? (Choose two.)

- A. `rw`
- B. `ro`
- C. `rootsquash`
- D. `norootsquash`
- E. `uid`

Correct Answer: AB

Section: (none)

Explanation

Explanation/Reference:

QUESTION 12

Which command is used to configure which file systems a NFS server makes available to clients?

- A. `exportfs`
- B. `mkfs.nfs`
- C. `mount`
- D. `nfsservctl`
- E. `telinit`

Correct Answer: A

Section: (none)

Explanation

Explanation/Reference:

QUESTION 13

Which of these tools, without any options, provides the most information when performing DNS queries?

- A. `dig`

- B. nslookup
- C. host
- D. named-checkconf
- E. named-checkzone

Correct Answer: A

Section: (none)

Explanation

Explanation/Reference:

QUESTION 14

Performing a DNS lookup with `dig` results in this answer:

```
;; QUESTION SECTION:
```

```
5.123.168.192.in-addr.arpa.      IN      PTR
```

```
;; ANSWER SECTION:
```

```
5.123.168.192.in-addr.arpa. 600      IN      PTR linuxerv.example.net.123.168.192.in-addr.arpa.
```

```
;; AUTHORITY SECTION:
```

```
123.168.192.in-addr.arpa. 600      IN      NS      linuxerv.example.net.
```

```
;; ADDITIONAL SECTION:
```

```
linuxerv.example.net. 600      IN      A      192.168.123.5
```

- A. There is no `.` after `linuxerv.example.net` in the PTR record in the forward lookup zone file
- B. There is no `.` after `linuxerv` in the PTR record in the forward lookup zone file

- C. There is no `.` after `linuserv.example.net` in the PTR record in the reverse lookup zone file
- D. The `.` in the NS definition in the reverse lookup zone has to be removed

Correct Answer: C

Section: (none)

Explanation

Explanation/Reference:

QUESTION 15

What option for BIND is required in the global options to disable recursive queries on the DNS server by default?

- A. `allow-recursive-query ( none; );`
- B. `allow-recursive-query off;`
- C. `recursion { disabled; };`
- D. `recursion { none; };`
- E. `recursion no;`



Correct Answer: E

Section: (none)

Explanation

Explanation/Reference:

QUESTION 16

What is DNSSEC used for?

- A. Encrypted DNS queries between nameservers
- B. Cryptographic authentication of DNS zones
- C. Secondary DNS queries for local zones
- D. Authentication of the user that initiated the DNS query
- E. Encrypting DNS queries and answers

Correct Answer: B

Section: (none)

Explanation

Explanation/Reference:

QUESTION 17

What word is missing from the following excerpt of a named.conf file?

```
_____ friends {  
    10.10.0.0/24; 192.168.1.0/24;  
};  
  
options {  
    allow-query { friends; };  
};
```



- A. networks
- B. net
- C. list
- D. acl
- E. group

Correct Answer: D

Section: (none)

Explanation

Explanation/Reference:

QUESTION 18

Which BIND option should be used to limit the IP addresses from which slave name servers may connect?

- A. allow-zone-transfer
- B. allow-transfer
- C. allow-secondary
- D. allow-slaves
- E. allow-queries

Correct Answer: B

Section: (none)

Explanation

Explanation/Reference:

QUESTION 19

In order to protect a directory on an Apache HTTPD web server with a password, this configuration was added to an `.htaccess` file in the respective directory:

```
AuthType Basic
AuthName "Protected Directory"
AuthUserFile /var/www/dir/.htpasswd
Require valid-user
```



Furthermore, a file `/var/www/dir/.htpasswd` was created with the following content:

```
usera:S3cr3t
```

Given that all these files were correctly processed by the web server processes, which of the following statements is true about requests to the directory?

- A. The user `usera` can access the site using the password `s3cr3t`
- B. Accessing the directory as `usera` raises HTTP error code 442 (User Not Existent)
- C. Requests are answered with HTTP error code 500 (Internal Server Error)
- D. The browser prompts the visitor for a username and password but logins for `usera` do not seem to work
- E. The web server delivers the content of the directory without requesting authentication

Correct Answer: A

Section: (none)

Explanation

Explanation/Reference:

QUESTION 20

Which Apache HTTPD directive enables HTTPS protocol support?

- A. `HTTPSEngine on`
- B. `SSLEngine on`
- C. `SSLEnable on`
- D. `HTTPSEnable on`
- E. `StartTLS on`

Correct Answer: B

Section: (none)

Explanation

Explanation/Reference:



QUESTION 21

Which `http_access` directive for Squid allows users in the ACL named `sales_net` to only access the Internet at times specified in the `time_acl` named `sales_time`?

- A. `http_access deny sales_time sales_net`
- B. `http_access allow sales_net sales_time`
- C. `http_access allow sales_net and sales-time`
- D. `allow http_access sales_net sales_time`
- E. `http_access sales_net sales_time`

Correct Answer: B

Section: (none)

Explanation

Explanation/Reference:

QUESTION 22

Which global option in `squid.conf` sets the port number or numbers that Squid will use to listen for client requests?

- A. `port`
- B. `client_port`
- C. `http_port`



<https://www.vceplus.com/>



- D. `server_port`
- E. `squid_port`

Correct Answer: C

Section: (none)

Explanation

Explanation/Reference:

QUESTION 23

When using `mod_authz_core`, which of the following strings can be used as an argument to `Require` in an Apache HTTPD configuration file to specify the authentication provider? (Choose three.)

- A. `method`
- B. `all`

- C. regex
- D. header
- E. expr

Correct Answer: ABE

Section: (none)

Explanation

Explanation/Reference:

Reference: https://httpd.apache.org/docs/2.4/mod/mod_authz_core.html

QUESTION 24

When trying to reverse proxy a web server through Nginx, what keyword is missing from the following configuration sample?

```
location / {  
    _____ http://proxiedserver:8080;  
}
```

- A. remote_proxy
- B. reverse_proxy
- C. proxy_reverse
- D. proxy_pass
- E. forward_to

Correct Answer: D

Section: (none)

Explanation

Explanation/Reference:

QUESTION 25



If there is no access directive, what is the default setting for OpenLDAP?

A.

```
access to *  
    by * read  
access to *  
    by anonymous none  
    by * read  
access to *  
    by anonymous auth  
    by * read  
access to *  
    by anonymous write  
    by * read
```

B. C.

D.

Correct Answer: B

Section: (none)

Explanation

Explanation/Reference:

QUESTION 26

A host, called `lpi`, with the MAC address `08:00:2b:4c:59:23` should always be given the IP address of `192.168.1.2` by a DHCP server running ISC DHCPD.

Which of the following configurations will achieve this?

```
host lpi {  
    hardware-ethernet 08:00:2b:4c:59:23;  
    fixed-address 192.168.1.2;  
}  
  
host lpi {  
    mac=08:00:2b:4c:59:23;  
    ip=192.168.1.2;  
}
```

A.



B.

C. `host lpi = 08:00:2b:4c:59:23 192.168.1.2`


```
host lpi {  
    hardware ethernet 08:00:2b:4c:59:23;  
    fixed-address 192.168.1.2;  
}  
  
host lpi {  
    hardware-address 08:00:2b:4c:59:23;  
    fixed-ip 192.168.1.2;  
}
```

D.

E.



Correct Answer: D

Section: (none)

Explanation

Explanation/Reference:

QUESTION 27

How is the LDAP administrator account configured when the `rootdn` and `rootpw` directives are not present in the `slapd.conf` file?

- A. The default account admin with the password admin are used
- B. The account is defined by an ACL in `slapd.conf`
- C. The default account admin is used without a password
- D. The account is defined in the file `/etc/ldap.secret`
- E. The account is defined in the file `/etc/ldap.root.conf`

Correct Answer: B

Section: (none)

Explanation

Explanation/Reference:

QUESTION 28

In a PAM configuration file, which of the following is true about the required control flag?

- A. If the module returns success, no more modules of the same type will be invoked
- B. The success of the module is needed for the module-type facility to succeed. If it returns a failure, control is returned to the calling application
- C. The success of the module is needed for the module-type facility to succeed. However, all remaining modules of the same type will be invoked
- D. The module is not critical and whether it returns success or failure is not important
- E. If the module returns failure, no more modules of the same type will be invoked

Correct Answer: C

Section: (none)

Explanation

Explanation/Reference:

QUESTION 29

How are PAM modules organized and stored?

- A. As plain text files in `/etc/security/`
- B. As statically linked binaries in `/etc/pam.d/bin/`
- C. As Linux kernel modules within the respective sub directory of `/lib/modules/`
- D. As shared object files within the `/lib/` directory hierarchy

E. As dynamically linked binaries in `/usr/lib/pam/sbin/`

Correct Answer: E

Section: (none)

Explanation

Explanation/Reference:

QUESTION 30

Which of the following statements in the ISC DHCPD configuration is used to specify whether or not an address pool can be used by nodes which have a corresponding host section in the configuration?

- A. `identified-nodes`
- B. `unconfigured-hosts`
- C. `missing-peers`
- D. `unmatched-hwaddr`
- E. `unknown-clients`



Correct Answer: E

Section: (none)

Explanation

Explanation/Reference:

QUESTION 31

A company is transitioning to a new DNS domain name and wants to accept e-mail for both domains for all of its users on a Postfix server.

Which configuration option should be updated to accomplish this?

- A. `mydomain`
- B. `mylocations`
- C. `mydestination`
- D. `myhosts`

E. mydomains

Correct Answer: C

Section: (none)

Explanation

Explanation/Reference:

QUESTION 32

It has been discovered that the company mail server is configured as an open relay. Which of the following actions would help prevent the mail server from being used as an open relay while maintaining the possibility to receive company mails? (Choose two.)

- A. Restrict Postfix to only accept e-mail for domains hosted on this server
- B. Configure Dovecot to support IMAP connectivity
- C. Configure netfilter to not permit port 25 traffic on the public network
- D. Restrict Postfix to only relay outbound SMTP from the internal network
- E. Upgrade the mailbox format from mbox to maildir

Correct Answer: CD

Section: (none)

Explanation

Explanation/Reference:

QUESTION 33

After the installation of Dovecot, it is observed that the dovecot processes are shown in ps ax like this:

```
31248 ?      S      0:00 dovecot/imap
31253 ?      S      0:00 dovecot/imap-login
```

In order to associate the processes with users and peers, the username, IP address of the peer and the connection status, which of the following options must be set?

- A. `--with-linux-extprocnames` for `./configure` when building Dovecot
- B. `sys.ps.allow_descriptions = 1` in `sysctl.conf` or `/proc`

- C. `proc.all.show_status = 1` in `sysctl.conf` or `/proc`
- D. `verbose_proctitle = yes` in the Dovecot configuration
- E. `process_format = "%u %I %s"` in the Dovecot configuration

Correct Answer: D

Section: (none)

Explanation

Explanation/Reference:

QUESTION 34

Which of the following services belongs to NFSv4 and does not exist in NFSv3?

- A. `rpc.idmapd`
- B. `rpc.statd`
- C. `nfsd`
- D. `rpc.mountd`



Correct Answer: A

Section: (none)

Explanation

Explanation/Reference:

Reference: https://access.redhat.com/documentation/en-us/red_hat_enterprise_linux/5/html/deployment_guide/ch-nfs

QUESTION 35

Which keyword is used in the Squid configuration to define networks and times used to limit access to the service?

- A. `acl`
- B. `allow`
- C. `http_allow`
- D. `permit`

Correct Answer: A

Section: (none)

Explanation

Explanation/Reference:

Reference: <https://www.tecmint.com/configure-squid-server-in-linux/>

QUESTION 36

The following Apache HTTPD configuration has been set up to create a virtual host available at www.example.com and www2.example.com:

```
<VirtualHost *:80>
```

```
    ServerName www.example.com
```

```
    ServerName www2.example.com
```

```
    ServerAdmin webmaster@example.com
```

```
    DocumentRoot /var/www/
```

```
    <Directory /srv/www/>
```

```
        Require all granted
```

```
    </Directory>
```

```
</VirtualHost>
```



Even though Apache HTTPD correctly processed the configuration file, requests to both names are not handled correctly. What should be changed in order to ensure correct operations?

- A. The configuration must be split into two `VirtualHost` sections since each virtual host may only have one name.
- B. The port mentioned in opening `VirtualHost` tag has to be appended to the `ServerName` declaration's values.
- C. Both virtual host names have to be placed as comma separated values in one `ServerName` declaration.
- D. Both virtual host names have to be mentioned in the opening `VirtualHost` tag.
- E. Only one Server name declaration may exist, but additional names can be declared in `ServerAlias` options.

Correct Answer: C

Section: (none)

Explanation

Explanation/Reference:

QUESTION 37

Given the following Squid configuration excerpt:

```
cache_dir ufs /var/spool/squid3/ 1024 16 256
```

Which of the following directories will exist directly within the directory:

/var/spool/squid3/? (Choose two.)

- A. 0F
- B. A0
- C. 0b
- D. FF
- E. 00

Correct Answer: AC

Section: (none)

Explanation

Explanation/Reference:

**QUESTION 38**

Which of the following statements are true regarding Server Name Indication (SNI)? (Choose two.)

- A. It supports transparent failover of TLS sessions from one web server to another.
- B. It allows multiple SSL/TLS secured virtual HTTP hosts to coexist on the same IP address.
- C. It enables HTTP servers to update the DNS of their virtual hosts' names using the X 509 certificates of the virtual hosts.
- D. It provides a list of available virtual hosts to the client during the TLS handshake.
- E. It submits the host name of the requested URL during the TLS handshake.

Correct Answer: BE

Section: (none)

Explanation

Explanation/Reference:

QUESTION 39

Which Apache HTTPD configuration directive specifies the RSA private key that was used in the generation of the SSL certificate for the server?

- A. SSLCertificateKeyFile
- B. SSLKeyFile
- C. SSLPrivateKeyFile
- D. SSLRSAKeyFile

Correct Answer: A

Section: (none)

Explanation

Explanation/Reference:

Reference: https://httpd.apache.org/docs/2.4/ssl/ssl_faq.html#aboutcerts

QUESTION 40

Which of the following are logging directives in Apache HTTPD? (Choose two.)

- A. TransferLog
- B. CustomLog
- C. ErrorLog
- D. ServerLog
- E. VHostLog



Correct Answer: AB

Section: (none)

Explanation

Explanation/Reference:

Reference: http://httpd.apache.org/docs/current/mod/mod_log_config.html

QUESTION 41

Which option within a Nginx server configuration section defines the file system path from which the content of the server is retrieved?

- A. location
- B. htdocs

- C. DocumentRoot
- D. root



<https://www.vceplus.com/>

- E. base_dir

Correct Answer: D

Section: (none)

Explanation

Explanation/Reference:

Reference: http://nginx.org/en/docs/beginners_guide.html



QUESTION 42

Which of the following information has to be submitted to a certification authority in order to request a web server certificate?

- A. The web server's private key.
- B. The IP address of the web server.
- C. The list of ciphers supported by the web server.
- D. The web server's SSL configuration file.
- E. The certificate signing request.

Correct Answer: E

Section: (none)

Explanation

Explanation/Reference:

Reference: <https://help.ubuntu.com/lts/serverguide/certificates-and-security.html.en>

QUESTION 43

To allow X connections to be forwarded from or through an SSH server, what configuration keyword must be set to `yes` in the `sshd` configuration file?

- A. `AllowForwarding`
- B. `ForwardingAllow`
- C. `X11ForwardingAllow`
- D. `X11Forwarding`

Correct Answer: D

Section: (none)

Explanation

Explanation/Reference:

Reference: <https://help.ubuntu.com/community/SSH/OpenSSH/Configuring>

QUESTION 44

What is the standard port used by OpenVPN?

- A. 1723
- B. 4500
- C. 500
- D. 1194



Correct Answer: D

Section: (none)

Explanation

Explanation/Reference:

Reference: <https://openvpn.net/archive/openvpn-users/2006-04/msg00355.html>

QUESTION 45

Using its standard configuration, how does fail2ban block offending SSH clients?

- A. By rejecting connections due to its role as a proxy in front of SSHD.
- B. By modifying and adjusting the SSHD configuration.
- C. By creating and maintaining netfilter rules.

- D. By creating null routes that drop any answer packets sent to the client.
- E. By modifying and adjusting the TCP Wrapper configuration for SSHD.

Correct Answer: B

Section: (none)

Explanation

Explanation/Reference:

Reference: <https://www.digitalocean.com/community/tutorials/how-to-protect-ssh-with-fail2ban-on-centos-7> **QUESTION 46**

Which FTP names are recognized as anonymous users in vsftp when the option `anonymous_enable` is set to yes in the configuration files? (Choose two.)

- A. `anonymous`
- B. `ftp`
- C. In the described configuration, any username which neither belongs to an existing user nor has another special meaning is treated as anonymous user.
- D. `nobody`
- E. `guest`

Correct Answer: AB

Section: (none)

Explanation

Explanation/Reference:

Reference: http://vsftpd.beasts.org/vsftpd_conf.html#bAE

QUESTION 47

Which of the following commands can be used to connect and interact with remote TCP network services? (Choose two.)

- A. `nettalk`
- B. `nc`
- C. `telnet`
- D. `cat`
- E. `netmap`

Correct Answer: BC

Section: (none)

Explanation

Explanation/Reference:

QUESTION 48

To which destination will a route appear in the Linux routing table after activating IPv6 on a router's network interface, even when no global IPv6 addresses have been assigned to the interface?

- A. fe80::/10
- B. 0::/128
- C. 0::/0
- D. fe80::/64
- E. 2000::/3

Correct Answer: A

Section: (none)

Explanation

Explanation/Reference:



QUESTION 49

Which command is used to administer IPv6 netfilter rules?

- A. iptables
- B. iptablesv6
- C. iptables6
- D. ip6tables
- E. ipv6tables

Correct Answer: D

Section: (none)

Explanation

Explanation/Reference:

Reference: https://www.centos.org/docs/5/html/5.1/Deployment_Guide/s1-ip6tables.html

QUESTION 50

Which netfilter table contains built-in chains called INPUT, OUTPUT and FORWARD?

- A. ipconn
- B. filter
- C. nat
- D. default
- E. masq

Correct Answer: B

Section: (none)

Explanation

Explanation/Reference:

Reference: <http://shorewall.org/NetfilterOverview.html>

QUESTION 51

After running `ssh-keygen` and accepting the default values, which of the following files are changed or created? (Choose two.)

- A. `~/.ssh/id_rsa.key`
- B. `~/.ssh/id_rsa.pub`
- C. `~/.ssh/id_rsa.prv`
- D. `~/.ssh/id_rsa.crt`
- E. `~/.ssh/id_rsa`

Correct Answer: BE

Section: (none)

Explanation

Explanation/Reference:

Reference: <https://www.ssh.com/ssh/keygen/>

QUESTION 52

Which of these tools provides DNS information in the following format?

```
www.example.com has address 172.25.25.55  
www.example.com has address 172.25.25.63  
www.example.com has IPv6 address fdb4:8fbc:36e1::101f
```

- A. dig
- B. nslookup
- C. host
- D. named-checkconf
- E. named-checkzone

Correct Answer: C

Section: (none)

Explanation

Explanation/Reference:



QUESTION 53

Which of the following DNS record types is used for reverse DNS queries?

- A. CNAME
- B. IN
- C. PTR
- D. REV
- E. RIN

Correct Answer: C

Section: (none)

Explanation

Explanation/Reference:

Reference: <http://help.dnsmadeeasy.com/managed-dns/dns-record-types/ptr-record/>

QUESTION 54

What is the purpose of DANE?

- A. Verify the integrity of name information retrieved via DNS.
- B. Allow secure dynamic DNS updates.
- C. Invalidate name information stored on caching name servers to speed up DNS updates.
- D. Discover which servers within a DNS domain offer a specific service.
- E. Provide a way to verify the association of X 509 certificates to DNS host names.

Correct Answer: E

Section: (none)

Explanation

Explanation/Reference:

Reference: <https://wiki.archlinux.org/index.php/DANE>

QUESTION 55

A BIND server should be upgraded to use TSIG. Which configuration parameters should be added if the server should use the algorithm `hmac-md5` and the key `skrKc4DoTzi/takIlPi7JZA==`?



```
TSIG server.example.com. {  
  algorithm hmac-md5;  
  secret "skrKc4DoTzi/takIlPi7JZA==";  
};  
  
key.server.example.com. {  
  algorithm hmac-md5;  
  secret skrKc4DoTzi/takIlPi7JZA==;  
};  
  
key.server.example.com. {  
  algorithm hmac-md5;  
  secret "skrKc4DoTzi/takIlPi7JZA==";  
};  
  
key.server.example.com. {  
  algorithm=hmac-md5;  
  secret="skrKc4DoTzi/takIlPi7JZA==";  
};  
  
key.server.example.com.  
  algorithm hmac-md5  
  secret "skrKc4DoTzi/takIlPi7JZA==";
```

A.

B.

C.

D.



E.

Correct Answer: C

Section: (none)

Explanation

Explanation/Reference:

QUESTION 56

Which option in `named.conf` specifies which host are permitted to ask for domain name information from the server?

- A. `allowed-hosts`
- B. `accept-query`
- C. `permit-query`
- D. `allow-query`

E. query-group

Correct Answer: D

Section: (none)

Explanation

Explanation/Reference:

QUESTION 57

Which configuration parameter on a Postfix server modifies only the sender address and not the recipient address?

- A. alias_maps
- B. alias_rewrite_maps
- C. sender_canonical_maps
- D. sender_rewrite_maps

Correct Answer: C

Section: (none)

Explanation

Explanation/Reference:



QUESTION 58

In the main Postfix configuration file, how are service definitions continued on the next line?

- A. It isn't possible. The service definition must fit on one line.
- B. The initial line must end with a backslash character (\).
- C. The following line must begin with a plus character (+).
- D. The following line must begin with white space indentation.
- E. The service definition continues on the following lines until all of the required fields are specified.

Correct Answer: D

Section: (none)

Explanation

Explanation/Reference:

QUESTION 59

Which of these sets of entries does the following command return?

```
ldapsearch -x "(|(cn=marie) (!(telephoneNumber=9*)))"
```

- A. Entries that don't have a `cn` of `marie` or don't have a `telephoneNumber` that begins with 9.
- B. Entries that have a `cn` of `marie` or don't have a `telephoneNumber` beginning with 9.
- C. Entries that have a `cn` of `marie` and a `telephoneNumber` that ending with 9.
- D. Entries that don't have a `cn` of `marie` and don't have a `telephoneNumber` beginning with 9.
- E. Entries that have a `cn` of `marie` or have a `telephoneNumber` beginning with 9.

Correct Answer: C

Section: (none)

Explanation

Explanation/Reference:



QUESTION 60

Which of the following types of IPv6 address assignments does DHCPv6 support? (Choose three.)

- A. Assignments of normal IPv6 addresses that can be renewed.
- B. Assignments of temporary IPv6 addresses that cannot be renewed.
- C. Assignments of blacklisted IPv6 addresses that should no longer be used.
- D. Assignments of IPv6 prefixes that can be used for routing or further assignments.
- E. Assignments of anonymous IPv6 addresses whose assignment is not logged by the DHCPv6 server.

Correct Answer: ABD

Section: (none)

Explanation

Explanation/Reference:

QUESTION 61

Which of the following commands is used to change user passwords in an OpenLDAP directory?

- A. setent
- B. ldapasswd
- C. olppasswd
- D. ldappasswd
- E. ldapchpw

Correct Answer: D

Section: (none)

Explanation

Explanation/Reference:

Reference: <https://www.digitalocean.com/community/tutorials/how-to-change-account-passwords-on-an-openldap-server>

QUESTION 62

Which of the following is correct about this excerpt from an LDIF file?

```
dn: cn=PrintOperators,ou=Groups,o=IT,DC=mycompany,DC=example,DC=com
```

- A. dn is the domain name.
- B. o is the operator name.
- C. cn is the common name.
- D. dn is the relative distinguished name.
- E. DC is the delegation container.

Correct Answer: D

Section: (none)

Explanation

Explanation/Reference:

Reference: [https://msdn.microsoft.com/en-us/library/aa366101\(v=vs.85\).aspx](https://msdn.microsoft.com/en-us/library/aa366101(v=vs.85).aspx)

QUESTION 63

Which of the following lines is valid in a configuration file in `/etc/pam.d/`?

- A. `auth required pam_unix.so try_first_pass nullok`
- B. `auth try_first_pass nullok, require pam_unix.so`
- C. `auth required:pam_unix.so(try_first_pass nullok)`
- D. `auth pam_unix.so(required try_first_pass nullok)`

Correct Answer: A

Section: (none)

Explanation

Explanation/Reference:

Reference: https://access.redhat.com/documentation/en-us/red_hat_enterprise_linux/6/html/managing_smart_cards/pam_configuration_files

QUESTION 64

Select the alternative that shows the correct way to disable a user login for all users except root.

- A. The use of the `pam_block` module along with the `/etc/login` configuration file.
- B. The use of the `pam_deny` module along with the `/etc/deny` configuration file.
- C. The use of the `pam_pwd` module along with the `/etc/pwdev.conf` configuration file.
- D. The use of the `pam_nologin` module along with the `/etc/nologin` configuration file.

Correct Answer: D

Section: (none)

Explanation

Explanation/Reference:

QUESTION 65

Which of the following values can be used in the OpenLDAP attribute `olcBackend` for any object of the class `olcBackendConfig` to specify a backend? (Choose three.)

- A. `xml`
- B. `bdb`
- C. `passwd`
- D. `ldap`

E. text

Correct Answer: BDE

Section: (none)

Explanation

Explanation/Reference:



<https://www.vceplus.com/>

