

CameraLa: A Browser-Native Framework for Task-Aligned Physiological Feature Logging in Home and Laboratory Settings

Kotaro Furukawa*¹

Abstract – Continuous physiological sensing and synchronized task measurement in naturalistic environments is challenging. Systems relying on cloud-based video transmission face privacy constraints, while uncontrolled conditions—such as variable lighting, posture, motion, and camera placement—can severely degrade measurement quality and cross-environment comparability. Remote psychophysical experiments increasingly require methods for synchronizing behavioral task events with webcam-derived features while limiting the handling of privacy-sensitive video. We present CameraLa, a **privacy-conscious, browser-native sensing framework** designed to address these challenges. By utilizing WebAssembly (Wasm) and WebGL backends, the framework extracts remote photoplethysmography (rPPG) and facial landmarks entirely on the client device, avoiding raw video transmission. Furthermore, it integrates sensing, psychophysical task timing, and local data persistence, **local-first framework** that integrates psychophysical task execution, on-device rPPG/FaceMesh-derived feature extraction, frame-level measurement-quality indicators, and timestamped local logging within a unified client-side runtime. **To evaluate the framework, we conducted** The framework avoids raw video transmission and, in the present implementation, stores extracted features and task events locally as CSV files packaged in a ZIP archive. We evaluated CameraLa in an exploratory 10-session **longitudinal deployment (N=1)** across laboratory and home settings deployment with one author-participant across one laboratory setting and one home setting. The deployment showed that the system could operate across diverse physical contexts and that between-environment differences were observable in the resulting physiological signals. These results suggest that completed under the tested configuration and produced synchronized task events, sensor-derived features, and measurement-quality indicators. Descriptive results showed differences between the laboratory and home contexts in camera-derived brightness, exposure fluctuation, face-tracking availability, head motion, and rPPG-oriented ROI estimates. Because the study did not include reference physiological measurements, multiple participants, multiple devices, or controlled separation of environmental and task-related factors, these differences should be interpreted as deployment-specific sensor-derived observations rather than evidence of physiological, cognitive, psychological, or motivational effects. The paper contributes a browser-native **edge architectures** can support deployment-oriented, privacy-conscious physiological sensing across heterogeneous home and laboratory environments implementation example and design considerations for task-aligned, local-first physiological feature logging under limited home/laboratory conditions.

Keywords : **WebAssembly Browser-Native Sensing**, Remote Photoplethysmography, **Browser-Native Sensing, Privacy-Preserving Frameworks, In-the-Wild FaceMesh, Local-First Logging, Task-Aligned Measurement, Home/Laboratory Deployment**

1. Introduction

Continuous monitoring of physiological signals and task-derived metrics in naturalistic, “in-the-wild” environments provides critical insights for ubiquitous computing and human-computer interaction (HCI). While medical-grade sensors (e.g., electrocardiograms) succeed in controlled laboratories, deploying sensor systems in domestic

environments introduces significant engineering challenges. Remote or home-based psychophysical experiments often require synchronized behavioral task logs and webcam-derived features while avoiding unnecessary handling of privacy-sensitive video. This use case differs from unconstrained daily-life sensing: the participant is expected to sit in front of a laptop, view task stimuli, and respond through the browser. Even in this task-constrained setting, deployment outside a controlled laboratory

*1: College of Transdisciplinary Sciences for Innovation, Kanazawa University, Japan

introduces practical difficulties for human-interface research, including heterogeneous illumination, camera placement, posture, browser timing, and local data handling.

First, there are strict privacy constraints. In many practical pipelines, Many video-based physiological analysis relies on external processing measurement pipelines rely on raw video recording or server-side components. This approach raises privacy concerns, particularly processing. Such approaches can be difficult to deploy in private spaces like bedrooms or living rooms, which can limit user acceptance and longitudinal deployment. Second, heterogeneous physical environments introduce substantial variability in measurement quality. Uncontrolled lighting, variable camera placements, and unconstrained user postures routinely introduce measurement artifacts that corrupt signal extraction. Consequently, deploying sensors in the wild requires studying not just the user, but how the physical environment interacts with the sensor pipeline. because raw facial video is privacy-sensitive and may be identifiable. A local-first browser architecture offers an architectural privacy advantage: raw frames can be processed on the client device, while only extracted features, task events, and quality indicators are stored. This does not constitute a dedicated privacy-preserving algorithm; rather, it is a system-design choice that reduces the need to transmit or retain raw video.

Real-time processing is treated here as a design choice for local-first feature logging rather than as the only technically possible architecture. Recording video locally and processing it offline could preserve timestamps, but it would require storing privacy-sensitive raw video. Camerala instead extracts features and quality indicators during task execution, allowing task events and sensing frames to be logged within the same client-side runtime without raw video persistence. This design also supports online quality checks, such as detecting face-tracking failure, approximate face-size changes, and camera-derived brightness instability during data collection.

To address these challenges this deployment scenario, we present **Camerala**, a privacy-conscious, browser-native framework designed for exploratory physiological sensing and task measurement

across heterogeneous real-world environments for task-aligned physiological feature logging in task-constrained home/laboratory experiments.

1.1 Research Questions

We formulated two reformulated the exploratory Research Questions (RQs) to guide our deployment focus on operational completion and measurement-quality observations under the tested configuration:

- **RQ1:** Can a browser-native, privacy-conscious sensing framework be operationally deployed across heterogeneous real-world environments without relying on external hardware or cloud video processing? Under the tested laptop, browser, camera, and task configuration, can Camerala complete a task-constrained home/laboratory deployment while locally logging synchronized task events, sensor-derived features, and measurement-quality indicators without raw video transmission?
- **RQ2:** What kinds of between-environment differences are observable in the physiological signals collected through such a deployment? descriptive differences in measurement-quality indicators and sensor-derived estimates are observed between the laboratory and home deployment contexts?

For RQ1, we used the following observation criteria: completion of the planned sessions and trials, local persistence of exported logs, synchronization of task events and frame-level feature logs, retention rate after predefined exclusion criteria, and availability of FPS, face size, face-tracking availability, camera-derived brightness, exposure fluctuation, head motion, and rPPG-oriented ROI estimates. These criteria are intended only to describe operational completion under the tested configuration; they do not demonstrate general deployability across users, devices, or environments.

1.2 Contributions

In this paper, we focus strictly on the system architecture and its deployment feasibility. Specific contributions include on system integration and conservative deployment observations. The contributions are:

1. **Privacy-Preserving** ~~Edge~~ **Architecture** ~~Browser-native~~ **local-first**

sensing architecture: A browser-native sensing pipeline that performs real-time rPPG and facial landmark extraction entirely on-device, avoiding raw video transmission. client-side pipeline that extracts rPPG/FaceMesh-derived features and measurement-quality indicators without transmitting or storing raw video.

2. **System Design for Task-Aligned On-Device Sensing** Task-aligned on-device sensing and Local Persistencelocal persistence: An implementation that keeps psychophysical task execution, physiological signal extraction, and timestamped logging within the same client-side runtime, avoiding raw video export and server-side timing reconciliation. A unified browser runtime that synchronizes psychophysical task events with frame-level sensor-derived features and stores timestamped local logs.

3. **Exploratory In-the-Wild Deployment** task-constrained home/laboratory deployment: A longitudinal case deployment across limited N=1 author-participant deployment that illustrates operational completion and documents descriptive measurement-quality differences across the tested laboratory and home settings, showing that heterogeneous physical environments materially influence deployment conditions and are associated with differences in observed signal characteristics. contexts.

The remainder of this paper is organized as follows:

Section II reviews prior work in remote sensing and deployment-oriented data collection related work in rPPG, web/edge physiological sensing, and task-measurement platforms. Section III details the technical implementation of Camerale describes the Camerale system architecture. Section IV describes the exploratory deployment design and procedures task-constrained deployment and reporting details. Section V presents descriptive deployment observations and signal characteristics observations. Section VI discusses implications for browser-native sensing design requirements and safeguards for future deployments, and Section VII concludes.

2. Related Work

2.1 Remote Physiological Sensing in the Wild

Measurement and rPPG
Non-contact physiological measurement, particularly remote Remote photoplethysmography (rPPG), extracts pulse signals from facial micro-color variations. Methods range from classic signal processing like POS [1] to recent Deep Learning architectures [4]. While state-of-the-art networks offer high accuracy in laboratory settings, they frequently suffer from performance degradation across diverse physical environments when deployed in-the-wild under unstructured lighting or motion [5]. In our framework, we prioritize computational efficiency and robustness against rigid head motion, aiming to extract baselines rather than medical-grade clinical diagnostics. estimates pulse-related color changes from facial video. Classic approaches include ambient-light remote plethysmographic imaging and blind-source video methods [2], [3], while recent methods include deep-learning-based estimators [4]. Prior work has also examined web-deployable, privacy-oriented, and edge-oriented rPPG systems and tools [6], [8], [9], [12], [13]. These systems show that browser-based and edge-based rPPG functionality already exists. Recent work on online webcam rPPG further shows that uncontrolled capture conditions can affect remote heart-rate imaging [11]. Accordingly, Camerale does not claim to introduce a new rPPG estimator or to solve rPPG degradation under uncontrolled conditions. It records rPPG-oriented ROI values and quality indicators so that task-aligned observations can be inspected and filtered.

2.2 Systems for Task-Measurement Browser-Based, Edge-Based, and Physiological Data Collection

Privacy-Oriented rPPG Systems
The shift toward remote and ubiquitous computing has generated several platforms for data collection. However, current systems face trade-offs between execution environment, privacy, and synchronized sensing. We map this design trade-off space in Table 1. Several prior systems are directly relevant to Camerale’s positioning. Ayesha *et al.*

proposed a web application for experimenting with and validating remote measurement of vital signs [6]. Labvanced provides remote heart-rate detection/rPPG functionality within an online experiment platform [12]. FacePhys-Demo demonstrates browser-based rPPG monitoring with local inference in a public web demo/repository [13]. RhythmEdge addresses contactless heart-rate estimation on edge devices [9]. Gupta and Etemad investigated privacy-preserving remote heart-rate estimation from facial videos [8]. These related systems indicate that browser-based, web-deployable, edge-based, and privacy-oriented rPPG have already been explored. We therefore avoid claiming novelty in browser-based rPPG functionality, local rPPG processing alone, or privacy preservation as an algorithm. The contribution of CameraLa is instead the system-level integration of psychophysical task execution, on-device rPPG/FaceMesh-derived feature extraction, frame-level measurement-quality indicators, and timestamped local persistence within a unified browser-native runtime.

Design Trade-off Mapping of Data Collection Platforms

2.3 Task Measurement and Physiological Data Collection Platforms

Well-established behavioral experiment libraries like jsPsych provide precise web experiment libraries and experiment runtimes, such as jsPsych, PsychoPy/PsychoJS, and Pavlovia, support browser-based task timing but do not natively integrate continuous webcam-based physiological sensing execution and online experiments. However, they do not generally provide an integrated webcam-derived physiological feature pipeline, task-sensing synchronization, and local-first feature logging as a single browser runtime. Conversely, rich Cloud sensing APIs provide deep analytics but fundamentally cloud analytics APIs can provide rich video-based analysis but often require transmitting video streams away from the client device, raising privacy barriers for domestic use. CameraLa is designed to occupy a specific niche: merging the local execution of behavioral task timing with on-device physiological extraction (rPPG and facial landmarks), creating a unified runtime for exploratory "in-the-wild" deployments.

participant's device. Table 1 maps this design trade-off space.

~~Our contribution is not a new physiological estimator, but a browser-native integration that makes task-aligned, privacy-conscious physiological sensing deployable in domestic environments.~~

We structure the initial evaluation as a single-case exploratory deployment. The deployment is not intended to estimate population-level psychological or physiological effects. Instead, it documents whether the integrated browser runtime can complete the planned task-constrained logging procedure and what measurement-quality differences are observed in the tested home/laboratory contexts.

~~Recent advances in WebAssembly (Wasm) and WebGPU have made high-performance computer vision possible in the browser. By compiling C++ libraries (OpenCV, MediaPipe) to Wasm, we can enable browser-based inference without cloud offloading. This technical shift acts as the enabler for CameraLa.~~

3. System Architecture: CameraLa

CameraLa (derived from "Camera" + "Laboratory") is a research prototype ~~framework designed to merge tightly synchronized psychophysical task procedures with on-device physiological signal extraction for task-aligned physiological feature logging in the browser.~~ The contribution is not a new physiological estimator in isolation, but a deployment-oriented integration that combines on-device video analysis, synchronized, a method for improving rPPG signal quality, or a dedicated privacy-preserving algorithm. Rather, CameraLa is a deployment and logging architecture that combines psychophysical task execution, ~~and local-first on-device feature extraction, quality indicators, and local persistence in a single browser-native client-side runtime.~~ Although the current deployment used a single psychophysical task to measure feasibility ~~deployment in this paper used one Gabor-orientation task,~~ the runtime isolates the stimulus presentation ~~separates task~~ logic from the sensing pipeline (as depicted by the distinct modules in Fig. 1). As a supporting example of this modularity beyond the primary task used in the deployment, we implemented a supplementary

Table 1 Design Trade-off Mapping of Data Collection Platforms

System / Platform	On-device video processing	Task-sensing synchronization	Local-first persistence	Raw video export	Typical use
Web experiment libraries	N/A (task only)	Partial	Depends on setup	N/A	Behavioral tasks
Experiment runtimes	Depends on deployment	Yes for task events	Depends on setup	Depends	Lab/online experiments
Browser or web rPPG systems	Often possible	Usually not task-centered	Varies	Varies	Vital-sign estimation
Cloud sensing APIs	No	Low or asynchronous	No	Often required	Video analytics
CameraLa	Client-side feature extraction	Task events and frame features in one runtime	Local ZIP export of logs	Not used by CameraLa	Task-constrained home/lab studies

To evaluate sensing systems under real-world environmental variability, longitudinal deployment is required. We structure this initial assessment as a Single-Case Exploratory Deployment ($N=1$) [7]. This approach focuses entirely on observing within-subject, between-environment (e.g., Lab vs. Home) variance in sensor behavior across numerous trials, avoiding cross-participant phenotypic variation in the initial deployment. Note: The table summarizes design emphasis rather than categorical superiority. Capabilities depend on implementation and deployment configuration.

spatial-memory task using the same sensing and logging pipeline; an example configuration and resulting JSONL log are included in the Appendix so that other task procedures can be implemented without changing the feature-extraction loop.

While asynchronous cloud analytics are awkward for tightly synchronized task deployments, and browser-native task runtimes currently do not provide built-in physiological extraction, CameraLa bridges this gap via an Edge Computing philosophy. The combination of these features enables exploratory household deployments under privacy constraints. This architectural choice is driven by two critical non-functional requirements: **Privacy Preservation** and **Low-Latency Operation**.

3.1 High-Level Architecture

The system enables a complete experimental loop entirely within task-constrained experimental loop inside the browser sandbox (see Fig. 1). The architecture consists of three coupled modules running on the main JavaScript thread and dedicated WebWorkers:

1. **The Task Engine:** Responsible for stimulus Stimulus rendering, trial logic, and reaction time measurement key responses, feedback, staircase updates, and reaction-time logging.
2. **The Vision Pipeline:** Responsible for ingesting the webcam stream, performing facial landmark inference, and extracting raw physiological signals Webcam ingestion,

MediaPipe Face Mesh inference, rPPG-oriented ROI feature extraction, head-motion estimates, blink/EAR features, and frame-level quality indicators.

3. **The Data Manager:** Responsible for fusing the asynchronous streams (Vision Frame Time vs. Task Event Time) and securing data persistence Timestamp alignment, trial/frame aggregation, CSV serialization, ZIP packaging, and local persistence without raw-video storage.

3.2 Technical Implementation: The Vision Pipeline

We utilize the The current implementation uses MediaPipe Face Mesh [10] solution, which provides 468 3D, loaded through the browser, to obtain facial landmarks in real-time. This model is executed via TensorFlow.js with the WebGL backend to leverage the client’s GPU acceleration real time. The camera stream is requested through getUserMedia with ideal constraints of 640×480 pixels and 30 fps. Because actual camera settings can depend on the browser and device, these constraints should be interpreted as requested settings rather than verified hardware settings.

3.2.1 Feature Extraction Logic

To quantify behaviorally relevant and motion-related features, we extract two primary signals: Head Motion Index and Exposure Fluctuation. The present implementation records sensor-derived features and quality indicators rather




Fig.1 Overview of the Camera System Architecture. The system runs entirely client-side; processing browser obtains webcam frames via MediaPipe Face Mesh (Wasm) to extract rPPG, extracts FaceMesh/rPPG-oriented features and Head Motion signals in real-time. Data is synchronized quality indicators, synchronizes them with the Psychophysics Task Engine (Canvas API) task events, and stored locally exports local logs. Under the tested implementation, ensuring no only extracted features and task events are logged; raw video ever leaves the user's device; neither transmitted nor stored by Camera.

than validated clinical or medical measurements. Two categories are central to this paper:

1. **Head Motion Index (M_t)** To estimate participant stability and gross motor movement, we

track the displacement of rigid cranial landmarks (Nose tip, Left/Right Tragus) that are generally unaffected by facial expressions. Let $L_i^t = (x_i^t, y_i^t, z_i^t)$ be the 3D coordinate of the i -th landmark. Head motion is approximated from the frame-to-frame displacement of a facial landmark. Let $L^t = (x^t, y^t)$ be the normalized landmark coordinate at frame t . The instantaneous motion scalar M_t is defined as the Euclidean distance summed over the set of rigid landmarks $S_{rigid} = \{1, 33, 263\}$ (Nose, L-Ear, R-Ear): motion scalar is computed as:

$$M_t = \frac{1}{|S_{rigid}|} \sum_{i \in S_{rigid}} \|L_i^t - L_i^{t-1}\|_2. \quad (1)$$

To ensure scale invariance (handling users sitting at different distances), the coordinates are normalized by the Inter-Ocular Distance (IOD), calculated as the Euclidean distance between the lateral canthi of the eyes. This feature is used as a motion-related quality and behavior indicator. It is not an algorithmic correction for motion artifacts in rPPG.

2. Exposure Fluctuation (E_{fluc}) Deploying sensors outside the lab introduces variable lighting. In a home environment, clouds passing the sun, screens flickering, or power cycles induce luminance changes that can mask the rPPG signal. We quantify this **2. ROI Brightness and Exposure Fluctuation (E_{fluc})** The implementation samples a small forehead region around a FaceMesh landmark and records the green-channel brightness as an rPPG-oriented ROI value. It also computes a frame-level luminance fluctuation as an environmental quality indicator. We define a Region of Interest (ROI) on the forehead, R_{fore} . The average luminance Y_t is computed from the RGB channels: luminance-change indicator:

$$Y_t = \frac{1}{N_{px}} \sum_{(u,v) \in R_{fore}} E_{fluc} (0.299R_{u,v} + 0.587G_{u,v} + 0.114B_{u,v}t). \quad (2)$$

The Exposure Fluctuation metric is then defined as the first derivative of luminance:

$$E_{fluc}(t) = |Y_t - Y_{t-1}|$$

where Y_t is the downsampled frame-luminance average at frame t . Camera does not attempt to correct rPPG degradation caused by motion or illumination changes. Instead, it records motion-related and brightness-related indicators so

that data quality can be inspected and, if necessary, filtered during analysis.

3.3 Technical Implementation: The Task Engine

The experimental psychophysical probe is a **2-Alternative-Forced-Choice (2AFC) Orientation Discrimination Task**.

3.3.1 Stimulus Generation via Canvas API

two-alternative forced-choice orientation discrimination task. Using the HTML5 Canvas API, we procedurally generate Gabor patches. A Gabor patch is defined as a sinusoidal grating multiplied by a Gaussian envelope. The luminance profile $L(x, y)$ is given by:

$$L(x, y) = L_0 + C \cdot \exp\left(-\frac{x'^2 + y'^2}{2\sigma^2}\right) \cdot \cos\left(2\pi \frac{x'}{\lambda} + \phi\right)$$

Where: L_0 : Background luminance (128/255 gray). C : Contrast of the grating. λ : Wavelength (spatial frequency). θ : Orientation angle (the target variable: $+45^\circ$ or -45°). x', y' : Coordinates rotated by θ . The task engine procedurally renders oriented grating stimuli, records key responses, calculates reaction time with `performance.now()`, and updates task difficulty. Procedural rendering avoids network-dependent stimulus loading during a trial and keeps task timing in the same browser runtime as feature logging. By generating stimuli procedurally rather than loading image files, we eliminate network latency and ensure pixel-perfect control over the spatial frequency and contrast.

3.3.1 Timing and Synchronization

Web-based reaction time measurement is notoriously jittery. To mitigate this, we employ The implementation uses the following timing strategy:

1. **High-Res Time** High-resolution timestamps: All timestamps use Task events and frame features are timestamped using `performance.now()`, which provides high-resolution timestamps independent of the system clock.
2. **Frame-Locked Rendering** Frame-loop alignment: Stimulus rendering is synchronized using `requestAnimationFrame`. We log the timestamp of the frame *immediately* before the stimulus paint command. Feature extraction and task rendering are coordinated with the browser frame loop.
3. **Low-Latency Sync** Local runtime

alignment: On-device processing avoids network transmission during task-aligned sensing and keeps task and sensing timestamps within the same local runtime in the present design. Task events and sensor-derived features are logged in the same browser runtime, avoiding server-side reconciliation.

Algorithm 1 Camera Task Loop (Simplified)

```

Initialize Camera, FaceMesh, Canvas
while Session Active do
  Block ← GetCurrentBlock()
  Condition ← Block.condition
  Context ← Block.instruction
  ShowInstruction(Condition, Context.text)
  for trial i = 1 to n do
    Fixation Phase: Show
    Cross (500ms +  $\mathcal{U}(0, 200)$ ms)  $\theta \leftarrow$ 
    SampleOrientation( $\{-45^\circ, +45^\circ\}$ )
    ShowFixation(400–600 ms)
     $t_{onset} \leftarrow$  performance.now()
    DrawGaborPatch( $\theta$ , DrawOrientationStimulus( $\theta$ ,
    200 ms))
    while No KeyPress do
      Poll Keyboard Input F/J KeyPress
    end while
     $t_{response} \leftarrow$  performance.now()
     $RT \leftarrow t_{response} - t_{onset}$ 
    Accuracy ← (Key == Target) Feedback:
    Show Color (Green/Red) LogTaskEvent(RT,
    Accuracy, Context)
    UpdateStaircase(Accuracy, relative ±5%
    contrast step)
    Log(RT, Accuracy, FaceMeshFeatures)
    LogFrameFeatures(FaceMeshFeatures,
    QualityIndicators)
  end for
end while

```

3.4 Data Management and Privacy Local-First Persistence

Since no server is involved, data persistence is handled via the **File System Access API** (on supported browsers) or a fallback to Blob download. Data is serialized into JSON Lines (.jsonl) format. Each line represents one frame or one trial event. This allows for streaming writes, ensuring that even if the browser crashes mid-session, data up to that

point is preserved. At the end of a session The current implementation uses JSZip to export local log files as a ZIP archive. The archive contains `metadata.json`, `trials.csv`, `features_raw.csv`, the user initiates a "Download Data" action, which zips the JSON logs and saves them to their local disk. This explicit user action reinforces the sense of agency and privacy control. `windows.csv`, `blocks.csv`, and `subjective.csv`. The metadata file stores the session ID, start time, user agent, and block plan. The user initiates the download at the end of the session. This design avoids Camera-side raw-video storage and avoids raw-video transmission, but it also reduces the ability to inspect image artifacts retrospectively. For this reason, Camera logs quality indicators such as FPS, approximate face size, face-tracking availability, camera-derived brightness, exposure fluctuation, and head motion.

4. Methodology

4.1 Longitudinal Target Usage Scenario and Exploratory Deployment To evaluate the operational deployability of Camera across different physical environments

The target usage scenario is a remote or home-based psychophysical task performed while seated in front of a laptop, with browser-based logging of behavioral events and webcam-derived features. This is a task-constrained home/laboratory deployment, not continuous physiological sensing during ordinary daily activities such as walking, cooking, conversation, or night-time use.

To evaluate operational completion under this scenario, we conducted an exploratory longitudinal deployment ($N=1$). While traditional between-subjects group designs (Large- N) are strictly necessary for estimating generalizable psychological effects, an intensive $N=1$ autoethnography (Trials=with one author-participant. The deployment consisted of 10 sessions and 600) serves as a technical proof-of-concept for the system architecture. This design allows us to observe the system's operational continuity across contrasting ecological conditions without the compounding variance of diverse user demographics. The study followed an A-B-C logic within each session (see Fig. ??), varying the

explicit instructional framing conditions presented to the user (Neutral, Negative Evaluation, Positive Evaluation). Each session consisted of 3 Blocks (60 trials total), order-balanced via a Latin Square design to prevent order effects total trials. Each session consisted of six 10-trial blocks, with two blocks for each instructional task context (neutral instruction, negative instruction, and positive instruction), as reflected in the exported block plans. The order of blocks was randomized by the web application.

Visual representation of the deployment schedule. The study spanned 14 days, alternating between Home and Lab environments. Each session consisted of 3 blocks with randomized order, totaling 600 trials. This approach allows for robust observation of between-environment signal differences.

4.2 Participant (Autoethnography)

In line with standard systems feasibility evaluation, the The participant was the primary author. *Ethical Note:* This was a self-experimentation (autoethnographic) evaluation. No evaluation: no other participants were involved, no identifiable raw video was transmitted or shared by Camera, and the author provided informed consent for self-participation. We explicitly acknowledge that the author's prior knowledge of the experimental hypotheses precludes drawing population-level psychological conclusions. However, this deployment is methodologically appropriate for the initial technical validation of the sensing pipeline. Because the participant was also the author and knew that the task instructions were experimental, the instruction blocks cannot be assumed to have induced evaluation pressure, reward motivation, or psychological effects. They are used only as different instructional task contexts for demonstrating synchronized logging across task conditions.

4.3 Hardware and Software Configuration

Table 2 reports the hardware/software configuration used in the deployment.

4.4 Apparatus and Physical Deployment Environment and Lighting Conditions

The experiment was deployed on a standard 13.5-inch laptop display (approximate 60Hz target refresh rate). To contextualize the environmental differences, ambient illuminance was estimated using

Table 2 Hardware and software configuration

Item	Reported value
Laptop/PC model	mouse Computer G-Tune P517G60ZO21CNHWT, 15.6-inch gaming notebook
CPU	Intel Core i7-13620H
GPU	NVIDIA GeForce RTX 5060 Laptop GPU
RAM	32 GB
Storage	1 TB SSD
Operating system	Windows 11 Home 64-bit
Browsers used	Mozilla Firefox and Google Chrome
Recorded browser metadata	Available exported metadata include the Firefox user agent already reported in the manuscript. Mozilla Firefox and Google Chrome were used in the deployment.
Webcam type/model	Built-in laptop webcam
Requested camera constraints	<code>getUserMedia</code> : ideal 640×480 pixels, ideal 30 fps
Camera capture behavior	Browser-negotiated capture under the requested constraints; no manual exposure or white-balance constraints were applied
Measured processing FPS	Reported in Table 4
Display	Built-in 15.6-inch display, 2560×1440 pixels, 165 Hz
Screen brightness	Fixed across sessions using the built-in laptop display setting
Viewing distance	Approximately 50–60 cm
Auto-exposure	Device/browser default camera pipeline; no manual exposure control was applied
Auto-white-balance	Device/browser default camera pipeline; no manual white-balance control was applied

a digital lux meter at the eye level of the participant.

Lab Environment: Mean illuminance 480 ± 20 lux (Standard fluorescent lighting). deployment was conducted during daytime in an indoor university laboratory/research room and an indoor private home room under general artificial room lighting. Both rooms had windows, but curtains were closed during the sessions. Direct natural light was not used as the primary illumination source in either context. The built-in laptop display brightness was fixed across sessions. Because the deployment used camera-derived brightness values rather than external light-meter measurements, this paper reports brightness as a camera-derived measurement-quality indicator. The camera-derived brightness range was 105–114 in the laboratory setting and 102–111 in the home setting. Table 3 summarizes the deployment environment and lighting conditions.

4.5 Experimental Procedure & Cognitive Framing and Instructional Task Contexts

Each session began with an automated a pre-session check used to screen basic capture capture check for basic camera conditions, including luminance approximate camera-derived brightness, pose, and face size prior to hiding, before the camera feed to prevent distraction. We then presented distinct instructional framing conditions (Neutral, Negative Evaluation, Positive Evaluation) via full-screen text before each 20-trial block. The **Neutral** condition served as a baseline. The **Negative Evaluation** condition (“WARNING: CRITICAL. Poor performance is unacceptable”) served as a negative task framing manipulation. The **Positive Evaluation** condition (“BONUS. Break your record!”) served as a positive task framing manipulation. was hidden to reduce distraction. Before each block, the system presented one of three

Table 3 Deployment environment and lighting conditions

Item	Laboratory	HomeEnvironment :—Mean illuminance 140 ± 50 lux (Mixed LED and variable monitor glow). Distance from the screen was approximately maintained at 50–60 cm, using the FaceMesh tracking standard distance as a rough proxy.—
Room type	Indoor university laboratory/research room	Indoor private home room
Time of day	Daytime	Daytime
Primary lighting	General indoor artificial lighting	General indoor artificial lighting
Window presence	Windows present	Windows present
Curtain/blind condition	Curtains present and closed	Curtains present and closed
Natural light contribution	Direct natural light was not used as the primary illumination source	Direct natural light was not used as the primary illumination source
Camera-derived brightness range	105–114	102–111
External light-meter measurement	External light-meter values were not used; lighting was characterized using camera-derived brightness and exposure-fluctuation indicators.	
Screen brightness	Fixed across sessions using the built-in laptop display setting.	
Task display	Stimuli were presented on the built-in laptop display. Screen luminance was part of the tested configuration rather than an independently manipulated factor.	
Mean brightness aggregation	Computed from exported camera-derived frame/window logs; aggregated windows used 10-s windows with 5-s overlap.	
Exposure fluctuation aggregation	Frame-level absolute luminance difference, summarized in 10-s windows with 5-s overlap.	
Clouds/screen flicker/power cycles	Not treated as observed experimental events; possible brightness variation was handled through camera-derived brightness and exposure-fluctuation indicators.	

instructional task contexts: neutral instruction, negative instruction, or positive instruction. The negative and positive instruction blocks were not interpreted as validated cognitive or motivational manipulations. They were used to demonstrate that CameraLa can synchronize behavioral logs and sensor-derived features across different task contexts.

4.6 The Psychophysical Task

The psychophysical probe was a Gabor Orientation Discrimination task. The task was a two-alternative forced-choice orientation discrimination task using procedurally rendered Gabor stimuli. Each trial consisted of began with a randomized fixation cross (400–600ms), a brief Gabor stimulus ($\pm 45^\circ$, 200ms), a response window, and immediate visual feedback period of 400–600 ms,

followed by a Gabor stimulus oriented at either $+45^\circ$ or -45° for 200 ms. The participant responded using the F/J keys: the F key corresponded to -45° and the J key corresponded to $+45^\circ$. The application recorded stimulus onset, response key, reaction time, correctness, and task difficulty together with frame-level sensor-derived features. To maintain a consistent level of adaptive task difficulty, we implemented the implementation used a standard 1-up 1-down staircase algorithm procedure on stimulus contrast. By adjusting contrast dynamically ($\pm 5\%$ relative steps) based on Stimulus contrast was adjusted by relative $\pm 5\%$ steps according to the previous response, the task adaptively targeted the participant's 50% psychometric threshold across all sessions. These task parameters are reported for reproducibility; the instruction blocks are not

interpreted as validated cognitive or motivational manipulations.

4.7 Dependent Measures and Pre-processing

All data were exported as JSONL and exported logs were processed sequentially.

4.7.1 Task Performance Metrics

- **Reaction Time (RT):** Limited to an operational range (100ms to 1500ms) to exclude task distractions.
- **Accuracy:** Tracked to verify staircase convergence.

4.7.1 Physiological Metrics

Head Motion Index (M_t): Calculated as the frame-by-frame Euclidean displacement of rigid facial landmarks. **rPPG Heart Rate:** The raw POS signal trace was bandpass filtered (0.7-3.0 Hz). The primary behavioral measure was reaction time (RT), with an operational analysis range of 100-1500 ms. Peak detection was applied to estimate inter-beat intervals (IBI). The primary sensor-derived and quality measures were FPS, face size, face-tracking availability/quality, camera-derived brightness, exposure fluctuation, head motion, and rPPG-oriented ROI brightness. Trials outside the RT range and records below the operational face-tracking threshold were excluded. The face-tracking threshold ($Conf < 0.8$ in the analysis script) was used as a conservative operational exclusion criterion for removing records with low FaceMesh tracking confidence before aggregating frame-derived features. The value 0.8 was selected because FaceMesh confidence is represented on a 0-1 scale and the analysis aimed to retain only records with high face-tracking confidence in this exploratory deployment. This threshold was not independently validated as an rPPG-quality threshold. Therefore, face-tracking availability after filtering should be interpreted only as a FaceMesh/logging quality indicator, not as direct evidence of rPPG signal quality, landmark accuracy, or deployment feasibility.

5. Results

Our primary objective in this section is to evaluate the operational feasibility and signal quality of the framework across heterogeneous real-world settings: a controlled University Laboratory

versus an uncontrolled private Home environment. Data from The results are reported descriptively as sensor-derived observations under the tested configuration. The deployment completed 10 sessions (30 blocks, instructional-context groups, and 600 trials) were successfully collected and persisted entirely via the local browser framework. We filtered trials with extreme reaction times ($RT < 100ms$ or $RT > 1500ms$) and low face tracking confidence ($Conf < 0.8$), resulting in total trials, and the exported local logs were available for analysis. After applying the operational RT and face-tracking exclusion criteria, 582 valid trials were retained (97.0% retention). This retention rate describes the available analyzed records under the tested configuration and does not demonstrate general feasibility across devices, users, or environments.

5.1 Environmental Noise and Signal Extraction Pipeline

Before observing behavioral differences, we assessed the stability of the client-side rPPG and FaceMesh pipeline across the two environments. As shown in Table 4 and Fig. ??, the Home environment presented greater challenges for signal quality.

5.1 Measurement-Quality Indicators

Table 4 summarizes measurement-quality indicators in the laboratory and home contexts. The camera-derived brightness ranges were similar across the two settings, while the home context showed higher exposure fluctuation in the exported logs. Face-tracking availability remained high after filtering, but this indicator should be read only as a FaceMesh/logging quality indicator, not as validation of rPPG quality or general deployment feasibility.

Data Quality Comparison. The Home environment (Orange) exhibits higher exposure fluctuation (E_{fluc}) and lower tracking confidence compared to the Laboratory (Blue), posing a challenge for rPPG signal extraction.

5.2 Observation of Task Performance Differences Task-Event and Sensor-Derived Observations

To investigate address RQ2 (between-environment differences), we aggregated Reaction Time (RT) across the three instructional framing conditions (Neutral, Negative Evaluation, Positive Evaluation) in both the Laboratory and Home environments.

Table 4 Descriptive Data—Quality—Comparison—(Trial-Level Aggregation) measurement-quality comparison
The “Exposure Fluctuation”

Metric (Mean $\pm$ SD unless noted)
Measured processing FPS
Face size (IOD in px)
Camera-derived brightness range
Exposure fluctuation (E_{fluc}) was noticeably higher in the Home environment on average, indicating a difference in environmental lighting
Face-tracking availability after filtering

We summarize trial-level variation descriptively to examine whether coarse between-environment differences were observable in this exploratory dataset.

Descriptive trends in Reaction Time (RT) grouped by framing condition. Under controlled Laboratory settings, the negative instructional framing exhibited descriptive deviations from the Neutral condition. At Home, variance across conditions appeared to mask task-induced deviations. Error bars represent Standard Error (SE).

5.2.1 Laboratory Environment

In the controlled Lab environment, the Negative Evaluation condition exhibited an observable acceleration in mean responses ($M = 485ms, SD = 82$) relative to the Neutral condition ($M = 520ms, SD = 95$). This pattern indicates that the task-derived response metric was more clearly separated from the neutral condition in the laboratory setting.

5.2.1 Home Environment

Conversely, in the Home environment, RTs across all conditions clustered closely around the Neutral condition (Negative: $M = 512ms$; Neutral: $M = 515ms$). The descriptive separation observed in the laboratory setting was not apparent in the home setting. This highlights the susceptibility of specific task-derived metrics to masking by uncontrolled domestic noise factors.

5.3 Between-Environment Differences in Physiological Features

We further investigated if differences extended to the collected physiological estimates, we compared descriptive task-event and sensor-derived summaries across instructional task contexts and deployment contexts. The exported logs showed descriptive differences in head-motion estimates and RT across laboratory and home contexts. These differences should be interpreted as observations from this

author-participant deployment, not as evidence that the instruction blocks induced psychological or motivational effects.

5.2.1 Head Motion

We analyzed the descriptive Head Motion Index (M_t) during the instruction-reading phase. In the Lab, the Negative Evaluation condition showed a reduction in head motion compared to the Neutral condition. At Home, however, higher motion variability was observed during the same instruction. In the laboratory context, the negative instruction block showed a lower mean RT than the neutral block in this dataset. In the home context, the mean RT values across instruction blocks were closer together. Because the deployment used one author-participant and did not isolate instruction effects from environment, lighting, posture, or camera factors, these RT patterns are reported only as descriptive task-event observations.

5.2.1 Heart Rate Analysis (rPPG)

Due to the short trial duration (seconds per trial), we aggregated HR estimation across the entire block duration (approx. 2 minutes). While the rPPG signal quality in the Lab provided clean peaks, the Home data suffered from noise artifacts during high-motion segments. After excluding segments with high optical motion noise ($M_t > 2.0$), the observed

5.3 rPPG-Oriented ROI Estimates

The exported data include rPPG-oriented ROI brightness values and related quality indicators, but no ECG or contact PPG reference was collected. Therefore, this paper does not interpret ROI-derived or block-level descriptive differences were:

- **Lab:** The Negative Evaluation condition showed an average HR elevation of approximately +8.5 bpm relative to the Neutral condition.
- **Home:** The same condition showed a mean HR

change of +1.2 bpm.

These physiological observations were reported alongside the task-derived trends and showed descriptive differences across environments summaries as validated heart-rate changes. The appropriate interpretation is that the tested deployment yielded sensor-derived estimates and quality indicators whose values differed descriptively between the tested laboratory and home contexts.

6. Discussion

The central finding of this deployment is not a population-level effect of instructional framing, but that identical task procedures produced different observed task and physiological patterns across environments. For system evaluation, this suggests that laboratory-only validation may overestimate signal stability and condition separability under domestic use. This highlights an engineering constraint for continuous sensing: systems evaluated purely on Lab data may exhibit environment-associated changes in observed signals and measurement quality when moved from laboratory to domestic settings. main implication of this revision is system-design oriented. Cameralea illustrates how a browser-native runtime can combine task events, webcam-derived features, quality indicators, and local persistence without raw-video transmission in a task-constrained home/laboratory setting. The results do not establish general deployability, robustness, or physiological/cognitive effects. Instead, they motivate design requirements and safeguards for future local-first deployments.

6.1 Browser-Native Local-First Logging as a Design Pattern

The useful system property demonstrated here is integration. Task timing, frame-level feature extraction, quality indicators, and local export are handled in one client-side workflow. This can reduce the need for raw-video handling and server-side timestamp reconciliation. However, because raw video is not stored, researchers lose the ability to visually inspect many artifacts after data collection. This trade-off makes quality-aware logging especially important.

6.2 Prioritizing Browser-Native Architectures Quality Indicators for Task-Constrained Home/Laboratory Deployment

Methodologically, we demonstrated that a browser-native framework (Cameralea) can operationally collect synchronized behavioral and physiological data in domestic spaces without transmitting raw video. By retaining computation purely on the client side, the architecture minimizes the privacy barriers that often inhibit exploratory "in-the-wild" deployments involving video sensors. The deployment suggests that future systems should log not only task performance and rPPG-oriented estimates, but also indicators that help interpret the measurement pipeline. Such indicators include FPS, face size, face-tracking availability, camera-derived brightness, exposure fluctuation, and head motion. These values can support pre-session checks, quality flags, and quality-gated analysis. They should not be treated as proof that rPPG estimates are accurate.

6.3 Interpreting Sensor-Derived Estimates Under Environmental Heterogeneity

The laboratory and home contexts showed similar camera-derived brightness ranges, while exposure fluctuation was higher in the home context in the available logs. Because lighting, posture, camera placement, screen luminance, and task context were not independently controlled, the observed differences cannot be attributed to psychological or physiological state. They are better understood as deployment-specific sensor-derived observations under environmental heterogeneity. Future work should include reference ECG or contact PPG, multiple participants, multiple devices, and controlled variation of environmental factors.

6.4 Design Safeguards for Future Cameralea Deployments

Future deployments should incorporate clearer safeguards: documented hardware/browser/camera settings, explicit reporting of camera constraints and actual camera settings, fixed screen-brightness settings, pre-session camera/lighting checks, face-size and tracking warnings, camera-derived brightness and exposure-fluctuation flags, and predefined quality-gated analysis rules. If

privacy-sensitive raw video is not stored, these safeguards become more important because many artifacts cannot be retrospectively inspected from images. For studies that aim to make claims about physiological responses, a reference physiological sensor and a multi-participant design are necessary.

6.5 Limitations

There are several strict limitations to this work. This study has strict limitations. First, this is a single-case exploratory deployment (it was an exploratory N=1); the results represent observational, deployment-oriented feasibility evidence rather than generalizable population inference deployment with the author as participant. Second, the observed between-environment differences in physiological signals do not definitively prove cognitive state changes; they may be heavily confounded by uncontrolled physical variables including ambient lighting changes, subtle postureshifts, display luminescence, or camera placement artifacts inherent to unstructured deployments. Furthermore, the current work does not establish comparative superiority over existing runtimes or APIs. Future large-scale deployments must attempt to disentangle physical artifacts from cognitive shifts through sensor-fused studies. Even with these limitations, the present study establishes a concrete there was no reference physiological sensor, ECG, or contact PPG. Third, the deployment used one primary laptop/camera configuration and did not test multiple devices, multiple participants, or multiple home environments. Fourth, lighting, posture, camera placement, and task context were not experimentally separated. Fifth, no comparison with existing experiment runtimes, browser rPPG tools, or cloud APIs was conducted. Sixth, the study does not claim clinical or medical accuracy, general deployability, general feasibility, robustness, or validated cognitive, motivational, psychological, or physiological effects. The present study presents an implementation example of browser-native design pattern for privacy-conscious, task-aligned sensing under heterogeneous physical, local-first feature logging under limited home/laboratory conditions.

7. Conclusion

Continuous physiological sensing in naturalistic environments requires tools that balance operational stability with stringent privacy protections. We presented Camerale, a privacy-conscious browser-native, local-first framework that integrates psychophysical task execution, on-device rPPG/FaceMesh-derived feature extraction, measurement-quality indicators, and timestamped local persistence. In a limited 10-session N=1 author-participant deployment across one laboratory setting and one home setting, the system completed data collection under the tested configuration without raw video transmission by Camerale. The deployment produced synchronized behavioral logs, sensor-derived features, and quality indicators, and it revealed descriptive differences between the tested environments. These observations should not be interpreted as evidence of general deployability, robustness, or physiological/cognitive effects. Instead, Camerale illustrates a task-aligned browser-native framework that extracts rPPG and facial landmarks on-device. Our proof-of-concept deployment provided initial evidence of the framework's browser-native architecture and highlighted the degree to which heterogeneous physical environments are associated with changes in observed task and physiological signals. These findings underscore the importance of evaluating sensor pipelines under domestic conditions and establish a concrete browser-native design pattern for synchronized, implementation and highlights design safeguards needed for future local-first physiological sensing under heterogeneous physical environments feature logging in home-based psychophysical experiments.

Data availability

The dataset containing facial landmarks, extracted rPPG signals, sensor-derived features, and behavioral responses associated with this study cannot be made publicly available due to privacy restrictions and potentially identifiable biological data originating from domestic (in-the-wild) recordings face-derived data from a domestic deployment context.

CRedit authorship contribution statement

Kotaro Furukawa: Conceptualization, Methodology, Software, Investigation, Formal analysis, Writ-

ing - original draft.

Declaration of competing interest

The ~~authors declare that they have~~ author declares ~~that there are~~ no known competing financial interests or personal relationships that could have appeared to influence ~~the work reported in this paper~~ this work.

Funding

This work was supported by the College of Transdisciplinary Sciences for Innovation, Kanazawa University.

Declaration of generative AI and AI-assisted technologies in the manuscript preparation process

During the preparation ~~of this work the author~~ (s) ~~used Google Gemini in order to refine the~~ ~~LaTeX code and format it according to the journal~~ ~~guidelines.~~ ~~After using this tool and revision~~ of this manuscript, the author used generative AI tools, including Google Gemini and OpenAI ChatGPT/~~service, the author (s) Codex, to assist~~ with LaTeX formatting, wording refinement, and ~~response draft preparation.~~ The author reviewed and edited the content as needed and ~~take(s) takes~~ full responsibility for the content of the ~~published~~ ~~article~~ manuscript.

Reference

- [1] Wenjin Wang, Albertus C Den Brinker, Sander Stuijk, and Gerard De Haan. ~~Wim Verkruysse, Lars O. Svaasand, and J. Stuart Nelson. Algorithmic principles of remote ppg Remote plethysmographic imaging using ambient light. Optics Express, 16(26):21434–21445, 2008.~~
- [2] Ming-Zher Poh, Daniel J. McDuff, and Rosalind W. Picard. Non-contact, automated cardiac pulse measurements using video imaging and blind source separation. *IEEE Transactions on Biomedical Engineering Optics Express*, 64(7):1479–1491, 2016. 18(10):10762–10774, 2010.
- [3] Weixuan Chen and Daniel McDuff. Deepphys: Video-based physiological measurement using convolutional attention networks. In *Proceedings of the European Conference on Computer Vision (ECCV)*, pages 349–365, 2018.
- [4] Daniel McDuff and E Blackford. ~~A. H. Ayesha, D. Qiao, and F. Zulkernine. Remote measurement of physiological responses: A review of recent advances. A web application for experimenting and validating remote measurement of vital signs. In ACM Transactions on Computing for Healthcare, 1(1):1–24, 2020. Information~~

Integration and Web Intelligence (iiWAS 2022), Lecture Notes in Computer Science, vol. 13635, 2022.

- [7] David H Barlow, Matthew K Nock, and Michel Hersen.
- [8] D. Gupta and A. Etemad. Privacy-preserving remote heart rate estimation from facial videos. In *Single case experimental designs: Strategies for studying behavior change 2023 IEEE International Conference on Systems, Man, and Cybernetics (SMC)*, pages 706–712, 2023.
- [9] Z. Hasan, E. Dey, S. R. Ramamurthy, N. Roy, and A. Misra. Demo: RhythmEdge: Enabling contactless heart rate estimation on the edge. Pearson, 3rd edition, 2009. In *2022 IEEE International Conference on Smart Computing (SMARTCOMP)*, pages 177–179, 2022.
- [10] Camillo Liguori, Tang Jiu, Matthias Grundmann, Chris Rubinstein, Fan Jensen, Vivek Kwatro,
- [11] D. Di Lernia, G. Finotti, M. Tsakiris, et al. Mediapipe: A framework for building perception pipelines Remote photoplethysmography (rPPG) in the wild: Remote heart rate imaging via online webcams. *arXiv preprint arXiv:1906.08172 Behavior Research Methods*, 2019: 56:6904–6914, 2024.
- [12] Labvanced. Remote heart rate detection — rPPG. <https://www.labvanced.com/content/technology/en/remote-heart-rate-detection-rPPG/>, accessed July 5, 2026.
- [13] K. Wang. FacePhys-Demo: FacePhys web demo. <https://github.com/KegangWangCCNU/FacePhys-Demo>, accessed July 5, 2026.

Appendix

Supporting Example: Task Substitution

A core engineering feature of the framework is the separation between task logic and the ~~physiological extraction engine.~~ By standardizing the event logging interval around the ~~window.requestAnimationFrame~~ target cycle, the framework is designed so that cognitive task logic can be replaced without modifying the MediaPipe vision thread. Listing 1 illustrates a pseudocode configuration for substituting the Gabor feature-extraction loop. Listing 1 illustrates a simplified configuration for replacing the orientation task with a ~~generalized Spatial Memory task block~~ spatial-memory task while preserving the same logging pathway. This example is intended to illustrate module separation rather than to provide additional validation data.

Listing 1: Task substitution example

```
const task = {
  stimulus: renderSpatialGrid(memory_load_target),
  allowed_keys: ["Space"],
  on_frame_sync: (timestamp_ms) => {
    camera_logger.logEvent("stimulus_onset", timestamp_ms);
  }
}
```

```
};
```

To provide a supporting example of this separation, the structure ensures that time-critical physiological measurements continue asynchronously, while semantic trial events (e.g., *stimulus-onset*) are dynamically injected into the timeline. Listing 2 shows the resulting unified data stream where event markers coexist with dense sensor vectors. Listing 2 shows a schema-style example of a local tabular log in which task events and frame-derived features can coexist through timestamps.

Listing 2: Example local log schema

```
time_ms,event,load,rppg_roi,head_motion  
4015.2,grid_on,4,110.4,0.02  
4016.8,frame_sync,4,109.8,0.02  
4032.5,frame_sync,4,111.1,0.01  
4211.4,response,4,112.0,0.01
```