SUPPLEMENTARY MATERIALS

FASTER EXACT METHODS FOR THE SECTIONALIZING SWITCH ALLOCATION PROBLEM

Fábio Luiz Usberti
José Federico Vizcaíno González
Laura Silva de Assis
Celso Cavellucci

October, 2026

Numerical Results

This document presents the complete numerical results obtained from executing the four tate-of-the-art algorithms (*i*) ILP-GALIAS, (*ii*) ILP-IFLOWS, (*iii*) DP-TS, and (*iv*) DP-N2M2, in comparison with two proposal methodologies (*i*) ILP-CUTS and (*ii*) DP-PC). Each row in the following tables represents a switch allocation problem with a specific number of switches. The m column indicates the number of switches to be allocated, **best ENS** represents the optimal energy not supplied value, and the subsequent four columns show the computational time in seconds required by each algorithm to solve the corresponding problem. Each algorithm was executed for each network and we have considered every possible number of switches, starting from $m = 0$ up to $m = n$. Thus, our benchmark comprises a total of 9,995 instances. Therefore, a total of 59,970 computational experiments was performed. For each methodology it was given two hours per network or one hour per instance, halting whenever the first was reached. The original public sources of the three benchmark families used are: (*i*) the REDS networks, available from the Repository of Distribution Systems[1], (*ii*) Poland, and (*iii*) IEEE networks, are available from Galias' Repository[2].

Table 1: ENS optimization - R3.

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
0	11135.20	0.005	0.007	0.000	0.000	0.000	0.000
1	7298.66	0.001	0.006	0.000	0.000	0.001	0.000
2	5559.70	0.011	0.005	0.000	0.000	0.002	0.000
3	4260.74	0.049	0.003	0.000	0.000	0.002	0.000
4	3391.76	0.036	0.003	0.000	0.000	0.002	0.000
5	3031.78	0.089	0.004	0.000	0.000	0.004	0.000
6	2715.24	0.230	0.006	0.000	0.000	0.005	0.000
7	2601.77	1.035	0.013	0.000	0.000	0.005	0.000
8	2505.75	2.311	0.022	0.000	0.000	0.006	0.000
9	2436.24	7.117	0.033	0.000	0.000	0.006	0.000
10	2372.86	13.735	0.045	0.010	0.000	0.006	0.000
11	2333.40	29.362	0.112	0.000	0.000	0.007	0.000
12	2300.69	45.689	0.114	0.000	0.000	0.005	0.000
13	2269.21	81.378	0.146	0.000	0.000	0.007	0.000
14	2238.98	105.767	0.160	0.000	0.000	0.006	0.000
15	2213.58	146.585	0.172	0.000	0.000	0.006	0.000
16	2193.14	165.597	0.172	0.000	0.000	0.005	0.000
17	2175.45	159.426	0.160	0.000	0.000	0.005	0.000
18	2158.37	167.175	0.150	0.000	0.000	0.006	0.000
19	2144.88	166.860	0.164	0.000	0.000	0.005	0.000
20	2132.20	190.745	0.184	0.000	0.000	0.005	0.000
21	2121.00	181.385	0.041	0.000	0.000	0.005	0.000
22	2114.28	195.062	0.050	0.000	0.000	0.005	0.000
23	2107.78	178.212	0.058	0.000	0.000	0.005	0.000
24	2101.43	155.219	0.039	0.000	0.000	0.006	0.000
25	2095.18	241.293	0.018	0.000	0.000	0.004	0.000
26	2089.06	133.895	0.012	0.000	0.000	0.004	0.000
27	2083.60	171.887	0.007	0.010	0.000	0.004	0.000
28	2078.49	129.053	0.004	0.000	0.000	0.003	0.000
29	2073.98	126.038	0.001	0.000	0.000	0.002	0.000
30	2071.62	126.240	0.001	0.000	0.000	0.001	0.000
31	2069.97	224.223	0.000	0.000	0.000	0.000	0.000
32	2069.97	165.916	0.000	0.000	0.000	0.000	0.000
Total		**3494.05**	**1.913**	**0.020**	**0.000**	**0.137**	**0.00**

[1] REDs Repository
[2] Galias' web page

Table 2: ENS optimization - R4.

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
0	42302.40	0.001	0.000	0.000	0.000	0.000	0.000
1	35470.40	0.002	0.004	0.000	0.000	0.005	0.000
2	30373.00	0.012	0.001	0.030	0.000	0.001	0.000
3	25557.90	0.010	0.001	0.630	0.000	0.001	0.000
4	21052.60	0.011	0.001	7.270	0.000	0.001	0.000
5	17272.80	0.012	0.001	53.680	0.000	0.001	0.000
6	14441.20	0.037	0.001	186.280	0.000	0.001	0.000
7	11710.90	0.047	0.001	494.020	0.000	0.001	0.000
8	9568.08	0.094	0.004	1208.170	0.000	0.002	0.000
9	7697.22	0.192	0.004	2582.700	0.000	0.002	0.000
10	5968.14	0.353	0.004	-	0.000	0.002	0.000
11	4242.33	0.757	0.004	-	0.000	0.002	0.000
12	3688.71	4.745	0.019	-	0.000	0.005	0.000
13	3353.53	73.468	0.034	-	0.000	0.005	0.000
14	3130.15	817.892	0.041	-	0.000	0.009	0.000
15	2990.25	-	0.054	-	0.000	0.006	0.000
16	2898.94	-	0.053	-	0.000	0.009	0.000
17	2844.17	-	0.063	-	0.000	0.007	0.000
18	2802.85	-	0.104	-	0.000	0.010	0.000
19	2763.33	-	0.098	-	0.000	0.008	0.000
20	2725.95	-	0.143	-	0.000	0.008	0.000
21	2691.75	-	0.143	-	0.000	0.008	0.000
22	2658.92	-	0.197	-	0.000	0.009	0.000
23	2631.77	-	0.236	-	0.000	0.010	0.000
24	2605.87	-	0.280	-	0.000	0.011	0.000
25	2584.01	-	0.473	-	0.000	0.011	0.000
26	2562.16	-	0.513	-	0.000	0.011	0.000
27	2540.50	-	0.794	-	0.000	0.011	0.000
28	2522.22	-	0.560	-	0.000	0.013	0.000
29	2504.72	-	0.640	-	0.000	0.011	0.000
30	2489.07	-	0.717	-	0.000	0.012	0.000
31	2476.32	-	1.676	-	0.000	0.012	0.000
32	2463.95	-	2.515	-	0.000	0.013	0.000
33	2452.87	-	5.801	-	0.000	0.012	0.000
34	2442.98	-	6.266	-	0.000	0.010	0.000
35	2434.29	-	6.295	-	0.000	0.011	0.000
36	2426.22	-	14.078	-	0.000	0.011	0.000
37	2418.76	-	9.409	-	0.000	0.011	0.000
38	2411.48	-	15.455	-	0.000	0.011	0.000
39	2404.59	-	31.483	-	0.000	0.011	0.000
40	2398.36	-	11.652	-	0.000	0.010	0.000
41	2392.52	-	15.284	-	0.000	0.010	0.000
42	2387.04	-	12.541	-	0.000	0.012	0.000
43	2381.95	-	18.017	-	0.000	0.010	0.000
44	2377.03	-	19.509	-	0.000	0.011	0.000
45	2372.64	-	5.119	-	0.000	0.011	0.000
46	2368.80	-	5.388	-	0.000	0.014	0.000
47	2365.15	-	1.439	-	0.000	0.013	0.000
48	2361.50	-	1.497	-	0.000	0.014	0.000
49	2358.23	-	1.705	-	0.000	0.010	0.000
50	2355.54	-	0.989	-	0.000	0.011	0.000

Continued on next page

Table 2 – continued from previous page - R4

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
51	2353.16	-	0.780	-	0.000	0.012	0.000
52	2350.98	-	7.393	-	0.000	0.010	0.000
53	2348.80	-	0.146	-	0.000	0.011	0.000
54	2347.59	-	1.422	-	0.000	0.010	0.000
55	2346.49	-	0.500	-	0.000	0.011	0.000
56	2345.48	-	0.497	-	0.000	0.011	0.000
57	2344.57	-	0.258	-	0.000	0.014	0.000
58	2343.84	-	0.133	-	0.000	0.012	0.000
59	2343.11	-	0.067	-	0.000	0.009	0.000
60	2342.43	-	0.051	-	0.000	0.010	0.000
61	2341.85	-	0.021	-	0.000	0.011	0.000
62	2341.27	-	0.014	-	0.000	0.006	0.000
63	2340.72	-	0.017	-	0.000	0.006	0.000
64	2340.50	-	0.007	-	0.000	0.005	0.000
65	2340.39	-	0.006	-	0.000	0.005	0.000
66	2340.32	-	0.003	-	0.000	0.003	0.000
67	2340.32	-	0.002	-	0.000	0.002	0.000
68	2340.32	-	0.002	-	0.000	0.002	0.000
69	2340.32	-	0.002	-	0.000	0.002	0.000
70	2340.32	-	0.002	-	0.000	0.002	0.000
71	2340.32	-	0.002	-	0.000	0.002	0.000
72	2340.32	-	0.002	-	0.000	0.002	0.000
73	2340.32	-	0.002	-	0.000	0.002	0.000
74	2340.32	-	0.002	-	0.000	0.002	0.000
75	2340.32	-	0.002	-	0.000	0.002	0.000
76	2340.32	-	0.002	-	0.000	0.002	0.000
77	2340.32	-	0.002	-	0.000	0.002	0.000
78	2340.32	-	0.002	-	0.000	0.002	0.000
79	2340.32	-	0.002	-	0.000	0.002	0.000
80	2340.32	-	0.002	-	0.000	0.002	0.000
81	2340.32	-	0.002	-	0.000	0.002	0.000
82	2340.32	-	0.002	-	0.000	0.002	0.000
83	2340.32	-	0.002	-	0.000	0.002	0.000
84	2340.32	-	0.002	-	0.000	0.002	0.000
85	2340.32	-	0.003	-	0.000	0.002	0.000
86	2340.32	-	0.002	-	0.000	0.002	0.000
87	2340.32	-	0.002	-	0.000	0.002	0.000
88	2340.32	-	0.002	-	0.000	0.002	0.000
89	2340.32	-	0.002	-	0.000	0.002	0.000
90	2340.32	-	0.002	-	0.000	0.002	0.000
91	2340.32	-	0.002	-	0.000	0.002	0.000
92	2340.32	-	0.002	-	0.000	0.002	0.000
93	2340.32	-	0.001	-	0.000	0.001	0.000
Total		**8097.63**	**202.68**	**9673.00**	**0.00**	**0.634**	**0.00**

Table 3: ENS optimization - R5.

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
0	107230.00	0.002	0.000	0.000	0.000	0.000	0.000
1	82358.70	0.004	0.008	0.000	0.000	0.012	0.000
2	66163.10	0.026	0.002	0.010	0.000	0.002	0.000
3	53973.60	0.033	0.003	0.030	0.000	0.003	0.000
4	44745.20	0.055	0.003	0.310	0.000	0.002	0.000
5	35844.70	0.066	0.002	2.300	0.000	0.002	0.000
6	27888.00	0.106	0.002	13.190	0.000	0.002	0.000
7	19933.90	0.127	0.002	59.990	0.000	0.002	0.000
8	14111.00	1.744	0.003	223.680	0.000	0.002	0.000
9	12149.30	63.307	0.017	721.570	0.000	0.007	0.000
10	11096.70	1431.279	0.044	1992.820	0.000	0.007	0.000
11	10156.00	-	0.049	-	0.000	0.009	0.000
12	9629.24	-	0.157	-	0.000	0.014	0.000
13	9156.78	-	0.297	-	0.000	0.012	0.000
14	8791.59	-	0.911	-	0.000	0.013	0.000
15	8428.62	-	7.473	-	0.000	0.016	0.000
16	8066.10	-	5.727	-	0.000	0.014	0.000
17	7751.59	-	5.277	-	0.000	0.014	0.000
18	7468.47	-	25.352	-	0.000	0.015	0.000
19	7237.11	-	2.336	-	0.000	0.015	0.000
20	7025.91	-	12.531	-	0.000	0.015	0.000
21	6815.29	-	2.449	-	0.000	0.014	0.000
22	6614.50	-	6.649	-	0.000	0.016	0.000
23	6418.37	-	2.380	-	0.000	0.017	0.000
24	6224.88	-	8.333	-	0.000	0.022	0.000
25	6039.19	-	5.189	-	0.000	0.018	0.000
26	5893.08	-	7.799	-	0.000	0.017	0.000
27	5755.29	-	10.143	-	0.000	0.017	0.000
28	5618.02	-	10.006	-	0.000	0.018	0.000
29	5488.09	-	9.222	-	0.000	0.018	0.000
30	5371.94	-	5.994	-	0.000	0.018	0.000
31	5257.79	-	11.063	-	0.000	0.021	0.000
32	5144.36	-	14.939	-	0.000	0.018	0.000
33	5056.61	-	32.905	-	0.000	0.018	0.000
34	4970.93	-	47.323	-	0.000	0.017	0.000
35	4885.95	-	67.592	-	0.000	0.019	0.000
36	4801.43	-	54.421	-	0.000	0.017	0.000
37	4729.23	-	123.796	-	0.000	0.017	0.000
38	4669.72	-	282.180	-	0.000	0.018	0.000
39	4613.05	-	661.853	-	0.000	0.019	0.000
40	4558.26	-	1345.134	-	0.000	0.020	0.000
41	4504.61	-	2402.798	-	0.000	0.021	0.000
42	4452.04	-	-	-	0.000	0.024	0.000
43	4407.43	-	-	-	0.000	0.026	0.000
44	4365.06	-	-	-	0.000	0.024	0.000
45	4326.83	-	-	-	0.000	0.024	0.000
46	4293.09	-	-	-	0.000	0.024	0.000
47	4260.94	-	-	-	0.000	0.023	0.000
48	4231.51	-	-	-	0.000	0.023	0.000
49	4204.60	-	-	-	0.000	0.023	0.000
50	4177.97	-	-	-	0.000	0.022	0.000

Continued on next page

Table 3 – continued from previous page - R5

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
51	4153.35	-	-	-	0.000	0.023	0.000
52	4129.61	-	-	-	0.000	0.022	0.000
53	4105.97	-	-	-	0.000	0.020	0.000
54	4082.36	-	-	-	0.000	0.021	0.000
55	4062.37	-	-	-	0.000	0.023	0.000
56	4044.67	-	-	-	0.000	0.023	0.000
57	4028.18	-	-	-	0.000	0.020	0.000
58	4013.74	-	-	-	0.000	0.023	0.000
59	3999.84	-	-	-	0.000	0.021	0.000
60	3986.14	-	-	-	0.000	0.023	0.000
61	3974.03	-	-	-	0.000	0.023	0.000
62	3962.07	-	-	-	0.000	0.018	0.000
63	3950.58	-	-	-	0.000	0.020	0.000
64	3939.30	-	-	-	0.000	0.019	0.000
65	3928.03	-	-	-	0.000	0.019	0.000
66	3917.83	-	-	-	0.000	0.019	0.000
67	3908.14	-	-	-	0.000	0.021	0.000
68	3898.65	-	-	-	0.000	0.020	0.000
69	3889.71	-	-	-	0.000	0.020	0.000
70	3880.89	-	-	-	0.000	0.020	0.000
71	3872.28	-	-	-	0.000	0.021	0.000
72	3864.76	-	-	-	0.000	0.023	0.000
73	3857.84	-	-	-	0.000	0.018	0.000
74	3851.48	-	-	-	0.000	0.020	0.000
75	3845.16	-	-	-	0.000	0.020	0.000
76	3839.06	-	-	-	0.000	0.020	0.000
77	3833.50	-	-	-	0.000	0.018	0.000
78	3828.71	-	-	-	0.000	0.018	0.000
79	3823.94	-	-	-	0.000	0.020	0.000
80	3819.23	-	-	-	0.000	0.019	0.000
81	3815.28	-	-	-	0.000	0.020	0.000
82	3811.40	-	-	-	0.000	0.020	0.000
83	3807.55	-	-	-	0.000	0.018	0.000
84	3803.74	-	-	-	0.000	0.016	0.000
85	3800.13	-	-	-	0.000	0.019	0.000
86	3796.71	-	-	-	0.000	0.019	0.000
87	3793.30	-	-	-	0.000	0.017	0.000
88	3789.95	-	-	-	0.000	0.016	0.000
89	3786.63	-	-	-	0.000	0.018	0.000
90	3783.49	-	-	-	0.000	0.022	0.000
91	3780.40	-	-	-	0.000	0.017	0.000
92	3777.57	-	-	-	0.000	0.017	0.000
93	3774.88	-	-	-	0.000	0.017	0.000
94	3772.21	-	-	-	0.000	0.017	0.000
95	3769.63	-	-	-	0.000	0.019	0.000
96	3767.39	-	-	-	0.000	0.016	0.000
97	3765.24	-	-	-	0.000	0.015	0.000
98	3763.14	-	-	-	0.000	0.021	0.000
99	3761.28	-	-	-	0.000	0.017	0.000
100	3759.45	-	-	-	0.000	0.023	0.000
101	3757.78	-	-	-	0.000	0.019	0.000
102	3756.39	-	-	-	0.000	0.014	0.000

Continued on next page

Table 3 – continued from previous page - R5

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
103	3755.20	-	-	-	0.000	0.020	0.000
104	3754.20	-	-	-	0.000	0.018	0.000
105	3753.27	-	-	-	0.000	0.018	0.000
106	3752.33	-	-	-	0.000	0.013	0.000
107	3751.46	-	-	-	0.000	0.017	0.000
108	3750.62	-	-	-	0.000	0.025	0.000
109	3749.99	-	-	-	0.000	0.018	0.000
110	3749.40	-	-	-	0.000	0.023	0.000
111	3748.85	-	-	-	0.000	0.019	0.000
112	3748.35	-	-	-	0.000	0.011	0.000
113	3747.90	-	-	-	0.000	0.013	0.000
114	3747.69	-	-	-	0.000	0.016	0.000
115	3747.49	-	-	-	0.000	0.010	0.000
116	3747.42	-	-	-	0.000	0.006	0.000
117	3747.42	-	-	-	0.000	0.006	0.000
118	3747.42	-	-	-	0.000	0.005	0.000
119	3747.42	-	-	-	0.000	0.005	0.000
120	3747.42	-	-	-	0.000	0.005	0.000
121	3747.42	-	-	-	0.000	0.005	0.000
122	3747.42	-	-	-	0.000	0.005	0.000
123	3747.42	-	-	-	0.000	0.005	0.000
124	3747.42	-	-	-	0.000	0.005	0.000
125	3747.42	-	-	-	0.000	0.005	0.000
126	3747.42	-	-	-	0.000	0.005	0.000
127	3747.42	-	-	-	0.000	0.005	0.000
128	3747.42	-	-	-	0.000	0.005	0.000
129	3747.42	-	-	-	0.000	0.004	0.000
130	3747.42	-	-	-	0.000	0.004	0.000
131	3747.42	-	-	-	0.000	0.004	0.000
132	3747.42	-	-	-	0.000	0.004	0.000
133	3747.42	-	-	-	0.000	0.004	0.000
134	3747.42	-	-	-	0.000	0.004	0.000
135	3747.42	-	-	-	0.000	0.004	0.000
136	3747.42	-	-	-	0.000	0.004	0.000
137	3747.42	-	-	-	0.000	0.004	0.000
138	3747.42	-	-	-	0.000	0.004	0.000
139	3747.42	-	-	-	0.000	0.004	0.000
140	3747.42	-	-	-	0.000	0.001	0.000
141	3747.42	-	-	-	0.000	0.001	0.000
142	3747.42	-	-	-	0.000	0.001	0.000
Total		**8696.75**	**8224.92**	**8009.00**	**0.00**	**2.118**	**0.00**

Table 4: ENS optimization - R6.

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
0	20806.50	0.011	0.001	0.000	0.000	0.001	0.000
1	15630.60	0.029	0.011	0.010	0.000	0.011	0.000
2	10891.90	0.108	0.006	0.000	0.000	0.005	0.000

Continued on next page

Table 4 – continued from previous page - R6

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
3	6932.57	0.100	0.006	0.010	0.000	0.005	0.000
4	6325.95	10.683	0.035	0.020	0.000	0.007	0.000
5	5864.04	293.232	0.109	0.030	0.000	0.016	0.000
6	5404.43	-	0.115	0.050	0.000	0.017	0.000
7	4947.98	-	0.065	0.070	0.000	0.016	0.000
8	4640.53	-	0.172	0.090	0.000	0.026	0.000
9	4353.60	-	0.143	0.120	0.000	0.022	0.000
10	4075.70	-	0.121	0.160	0.000	0.020	0.000
11	3839.55	-	0.182	0.220	0.000	0.022	0.000
12	3611.17	-	0.147	0.280	0.000	0.021	0.000
13	3388.69	-	0.319	0.340	0.000	0.020	0.000
14	3213.89	-	0.275	0.420	0.000	0.023	0.000
15	3055.73	-	1.288	0.510	0.000	0.023	0.000
16	2921.73	-	0.429	0.610	0.000	0.024	0.000
17	2820.67	-	0.555	0.710	0.000	0.029	0.000
18	2730.54	-	0.922	0.840	0.000	0.044	0.000
19	2640.63	-	1.076	0.940	0.001	0.048	0.000
20	2552.11	-	41.652	1.080	0.000	0.035	0.000
21	2468.27	-	2.328	1.240	0.000	0.029	0.000
22	2391.79	-	2.531	1.410	0.000	0.034	0.000
23	2328.35	-	59.092	1.540	0.000	0.029	0.000
24	2266.18	-	81.517	1.710	0.000	0.030	0.000
25	2205.00	-	90.344	1.910	0.000	0.031	0.000
26	2146.64	-	7.074	2.050	0.000	0.031	0.000
27	2089.25	-	66.394	2.210	0.000	0.031	0.000
28	2038.52	-	10.746	2.360	0.000	0.031	0.000
29	1997.66	-	20.438	2.530	0.000	0.034	0.000
30	1959.61	-	261.623	2.730	0.000	0.034	0.000
31	1925.50	-	43.668	2.840	0.000	0.030	0.000
32	1894.89	-	86.736	3.100	0.000	0.036	0.000
33	1868.14	-	212.019	3.200	0.000	0.039	0.000
34	1843.27	-	533.246	3.340	0.000	0.036	0.000
35	1817.08	-	977.702	3.450	0.000	0.038	0.000
36	1793.97	-	-	3.620	0.000	0.040	0.000
37	1770.88	-	-	3.720	0.000	0.032	0.000
38	1748.80	-	-	3.900	0.000	0.032	0.000
39	1727.42	-	-	3.960	0.000	0.034	0.000
40	1707.27	-	-	4.180	0.000	0.033	0.000
41	1689.58	-	-	4.280	0.000	0.038	0.000
42	1675.16	-	-	4.400	0.000	0.038	0.000
43	1661.86	-	-	4.560	0.000	0.035	0.000
44	1648.66	-	-	4.600	0.000	0.033	0.000
45	1635.70	-	-	4.620	0.000	0.038	0.000
46	1622.78	-	-	4.770	0.000	0.035	0.000
47	1610.19	-	-	4.780	0.000	0.035	0.000
48	1599.13	-	-	4.970	0.000	0.038	0.000
49	1588.22	-	-	5.070	0.000	0.036	0.000
50	1577.59	-	-	5.250	0.000	0.045	0.000
51	1568.09	-	-	5.350	0.000	0.039	0.000
52	1558.70	-	-	5.200	0.000	0.038	0.000
53	1549.42	-	-	5.250	0.000	0.041	0.000
54	1541.13	-	-	5.390	0.000	0.048	0.000

Continued on next page

Table 4 – continued from previous page - R6

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
55	1533.56	-	-	5.410	0.000	0.041	0.000
56	1528.06	-	-	5.510	0.000	0.041	0.000
57	1522.75	-	-	5.540	0.000	0.036	0.000
58	1517.62	-	-	5.690	0.000	0.036	0.000
59	1512.70	-	-	5.780	0.000	0.036	0.000
60	1508.08	-	-	5.740	0.000	0.038	0.000
61	1504.26	-	-	5.800	0.000	0.037	0.000
62	1500.45	-	-	5.850	0.000	0.037	0.000
63	1496.73	-	-	5.950	0.000	0.033	0.000
64	1493.61	-	-	6.070	0.000	0.038	0.000
65	1490.86	-	-	6.080	0.000	0.051	0.000
66	1488.32	-	-	6.130	0.000	0.055	0.000
67	1485.83	-	-	6.140	0.000	0.050	0.000
68	1483.34	-	-	6.220	0.000	0.082	0.000
69	1480.88	-	-	6.370	0.000	0.042	0.000
70	1478.53	-	-	6.540	0.000	0.062	0.000
71	1476.30	-	-	6.660	0.000	0.062	0.000
72	1474.09	-	-	6.440	0.000	0.047	0.000
73	1472.18	-	-	6.410	0.000	0.068	0.000
74	1470.49	-	-	6.410	0.000	0.074	0.000
75	1468.83	-	-	6.400	0.000	0.063	0.000
76	1467.17	-	-	6.350	0.000	0.056	0.000
77	1465.73	-	-	6.340	0.000	0.071	0.000
78	1464.37	-	-	6.350	0.000	0.048	0.000
79	1463.13	-	-	6.300	0.000	0.061	0.000
80	1461.89	-	-	6.370	0.000	0.047	0.000
81	1460.84	-	-	6.370	0.000	0.060	0.000
82	1459.81	-	-	6.220	0.000	0.064	0.000
83	1458.83	-	-	6.170	0.000	0.068	0.000
84	1457.86	-	-	6.030	0.000	0.083	0.000
85	1456.98	-	-	5.980	0.000	0.074	0.000
86	1456.13	-	-	5.870	0.000	0.067	0.000
87	1455.30	-	-	5.970	0.000	0.139	0.000
88	1454.60	-	-	5.780	0.000	0.217	0.000
89	1453.94	-	-	5.710	0.000	0.121	0.000
90	1453.31	-	-	5.560	0.000	0.121	0.000
91	1452.69	-	-	5.420	0.000	0.621	0.000
92	1452.07	-	-	5.350	0.000	0.111	0.000
93	1451.47	-	-	5.260	0.000	0.139	0.000
94	1450.88	-	-	5.200	0.000	0.245	0.000
95	1450.30	-	-	5.000	0.000	0.171	0.000
96	1449.74	-	-	4.920	0.000	0.594	0.000
97	1449.20	-	-	4.770	0.000	0.415	0.000
98	1448.70	-	-	4.750	0.000	0.153	0.000
99	1448.20	-	-	4.550	0.000	0.535	0.000
100	1447.70	-	-	4.420	0.000	0.287	0.000
101	1447.21	-	-	4.370	0.000	0.104	0.000
102	1446.74	-	-	4.290	0.000	0.604	0.000
103	1446.27	-	-	4.170	0.000	0.602	0.000
104	1445.80	-	-	4.030	0.000	0.173	0.000
105	1445.34	-	-	3.890	0.000	0.399	0.000
106	1444.89	-	-	3.820	0.000	0.236	0.000

Continued on next page

Table 4 – continued from previous page - R6

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
107	1444.48	-	-	3.680	0.000	0.522	0.000
108	1444.09	-	-	3.650	0.000	0.712	0.000
109	1443.72	-	-	3.590	0.000	0.584	0.000
110	1443.35	-	-	3.420	0.000	0.393	0.000
111	1442.98	-	-	3.310	0.000	0.514	0.000
112	1442.63	-	-	3.360	0.000	0.312	0.000
113	1442.30	-	-	3.170	0.000	0.237	0.000
114	1441.97	-	-	3.080	0.000	0.271	0.000
115	1441.64	-	-	2.930	0.000	0.233	0.000
116	1441.31	-	-	2.900	0.000	0.446	0.000
117	1441.01	-	-	2.770	0.000	0.355	0.000
118	1440.76	-	-	2.690	0.000	0.475	0.000
119	1440.50	-	-	2.590	0.000	0.265	0.000
120	1440.25	-	-	2.540	0.000	0.399	0.000
121	1440.02	-	-	2.470	0.000	0.264	0.000
122	1439.79	-	-	2.380	0.000	0.436	0.000
123	1439.58	-	-	2.260	0.000	0.429	0.000
124	1439.38	-	-	2.200	0.000	0.381	0.000
125	1439.19	-	-	2.140	0.000	0.498	0.000
126	1439.02	-	-	2.030	0.000	0.374	0.000
127	1438.87	-	-	1.930	0.000	0.556	0.000
128	1438.73	-	-	1.900	0.000	0.408	0.000
129	1438.63	-	-	1.820	0.000	0.245	0.000
130	1438.52	-	-	1.760	0.000	0.388	0.000
131	1438.42	-	-	1.670	0.000	0.291	0.000
132	1438.33	-	-	1.600	0.000	0.246	0.000
133	1438.23	-	-	1.510	0.000	0.324	0.000
134	1438.13	-	-	1.440	0.000	0.190	0.000
135	1438.04	-	-	1.380	0.000	0.117	0.000
136	1437.95	-	-	1.340	0.000	0.078	0.000
137	1437.89	-	-	1.250	0.000	0.064	0.000
138	1437.83	-	-	1.220	0.000	0.030	0.000
139	1437.78	-	-	1.120	0.000	0.020	0.000
140	1437.73	-	-	1.060	0.000	0.015	0.000
141	1437.68	-	-	1.010	0.000	0.007	0.000
142	1437.65	-	-	0.950	0.000	0.006	0.000
143	1437.63	-	-	0.890	0.000	0.005	0.000
144	1437.63	-	-	0.890	0.000	0.005	0.000
145	1437.63	-	-	0.810	0.000	0.005	0.000
146	1437.63	-	-	0.760	0.000	0.005	0.000
147	1437.63	-	-	0.710	0.000	0.005	0.000
148	1437.63	-	-	0.680	0.000	0.005	0.000
149	1437.63	-	-	0.640	0.000	0.005	0.000
150	1437.63	-	-	0.580	0.000	0.005	0.000
151	1437.63	-	-	0.570	0.000	0.005	0.000
152	1437.63	-	-	0.520	0.000	0.005	0.000
153	1437.63	-	-	0.490	0.000	0.005	0.000
154	1437.63	-	-	0.460	0.000	0.005	0.000
155	1437.63	-	-	0.440	0.000	0.005	0.000
156	1437.63	-	-	0.410	0.000	0.005	0.000
157	1437.63	-	-	0.390	0.000	0.005	0.000
158	1437.63	-	-	0.380	0.000	0.005	0.000

Continued on next page

Table 4 – continued from previous page - R6

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
159	1437.63	-	-	0.350	0.000	0.005	0.000
160	1437.63	-	-	0.330	0.000	0.005	0.000
161	1437.63	-	-	0.310	0.000	0.005	0.000
162	1437.63	-	-	0.290	0.000	0.005	0.000
163	1437.63	-	-	0.280	0.000	0.005	0.000
164	1437.63	-	-	0.260	0.000	0.005	0.000
165	1437.63	-	-	0.240	0.000	0.005	0.000
166	1437.63	-	-	0.230	0.000	0.005	0.000
167	1437.63	-	-	0.220	0.000	0.005	0.000
168	1437.63	-	-	0.200	0.000	0.005	0.000
169	1437.63	-	-	0.190	0.000	0.005	0.000
170	1437.63	-	-	0.170	0.000	0.005	0.000
171	1437.63	-	-	0.160	0.000	0.005	0.000
172	1437.63	-	-	0.150	0.000	0.005	0.000
173	1437.63	-	-	0.150	0.000	0.005	0.000
174	1437.63	-	-	0.130	0.000	0.005	0.000
175	1437.63	-	-	0.120	0.000	0.005	0.000
176	1437.63	-	-	0.110	0.000	0.002	0.000
177	1437.63	-	-	0.110	0.000	0.001	0.000
178	1437.63	-	-	0.100	0.000	0.001	0.000
179	1437.63	-	-	0.100	0.000	0.001	0.000
180	1437.63	-	-	0.080	0.000	0.001	0.000
181	1437.63	-	-	0.080	0.000	0.001	0.000
182	1437.63	-	-	0.080	0.000	0.001	0.000
183	1437.63	-	-	0.060	0.000	0.001	0.000
184	1437.63	-	-	0.070	0.000	0.001	0.000
185	1437.63	-	-	0.060	0.000	0.001	0.000
186	1437.63	-	-	0.050	0.000	0.001	0.000
187	1437.63	-	-	0.050	0.000	0.001	0.000
188	1437.63	-	-	0.050	0.000	0.001	0.000
189	1437.63	-	-	0.040	0.000	0.001	0.000
190	1437.63	-	-	0.040	0.000	0.001	0.000
191	1437.63	-	-	0.040	0.000	0.001	0.000
192	1437.63	-	-	0.030	0.000	0.001	0.000
193	1437.63	-	-	0.040	0.000	0.001	0.000
194	1437.63	-	-	0.020	0.000	0.001	0.000
195	1437.63	-	-	0.030	0.000	0.001	0.000
196	1437.63	-	-	0.030	0.000	0.001	0.000
197	1437.63	-	-	0.020	0.000	0.001	0.000
198	1437.63	-	-	0.020	0.000	0.001	0.000
199	1437.63	-	-	0.020	0.000	0.001	0.000
200	1437.63	-	-	0.020	0.000	0.001	0.000
201	1437.63	-	-	0.020	0.000	0.001	0.000
202	1437.63	-	-	0.010	0.000	0.001	0.000
203	1437.63	-	-	0.020	0.000	0.001	0.000
Total		**7504.17**	**9703.26**	**517.71**	**0.03**	**20.63**	**0.00**

Table 5: ENS optimization - R7.

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
0	8974232.50	0.149	0.001	0.000	0.000	0.002	0.000
1	7035772.35	0.453	0.092	0.030	0.000	0.093	0.000
2	5866132.54	1.731	0.017	0.050	0.000	0.017	0.005
3	4726245.09	1.458	0.018	0.250	0.010	0.017	0.004
4	3673006.64	14.682	0.017	4.050	0.000	0.017	0.004
5	2690985.53	44.306	0.018	48.800	0.000	0.018	0.005
6	2100014.02	867.928	0.051	395.550	0.000	0.024	0.004
7	1518308.94	2772.477	0.061	2121.590	0.000	0.025	0.004
8	1318995.66	-	0.367	-	0.010	0.043	0.005
9	1232934.09	-	2.421	-	0.000	0.063	0.003
10	1153227.35	-	3.213	-	0.010	0.074	0.006
11	1093491.80	-	7.155	-	0.000	0.101	0.003
12	1033000.80	-	8.410	-	0.000	0.091	0.003
13	983783.20	-	18.562	-	0.000	0.078	0.003
14	937133.46	-	36.754	-	0.000	0.104	0.003
15	910731.23	-	198.797	-	0.000	0.110	0.003
16	885747.91	-	1667.820	-	0.010	0.088	0.003
17	861508.81	-	-	-	0.010	0.106	0.003
18	836525.49	-	-	-	0.010	0.106	0.003
19	812671.26	-	-	-	0.010	0.096	0.006
20	789429.98	-	-	-	0.010	0.109	0.003
21	768651.09	-	-	-	0.010	0.151	0.003
22	749473.28	-	-	-	0.010	0.102	0.003
23	733077.37	-	-	-	0.010	0.642	0.003
24	717943.07	-	-	-	0.010	0.736	0.003
25	705231.80	-	-	-	0.010	0.974	0.003
26	692795.60	-	-	-	0.010	1.134	0.003
27	680437.23	-	-	-	0.010	0.877	0.003
28	668572.97	-	-	-	0.020	1.067	0.010
29	657167.24	-	-	-	0.010	0.943	0.003
30	646036.50	-	-	-	0.010	0.851	0.003
31	636776.13	-	-	-	0.010	1.034	0.003
32	628099.53	-	-	-	0.010	1.041	0.003
33	620289.81	-	-	-	0.010	1.130	0.003
34	612527.23	-	-	-	0.010	1.049	0.003
35	604965.71	-	-	-	0.010	1.161	0.003
36	597823.54	-	-	-	0.010	0.945	0.002
37	590773.82	-	-	-	0.010	1.116	0.002
38	584107.60	-	-	-	0.010	1.066	0.002
39	577606.50	-	-	-	0.010	0.969	0.002
40	571662.48	-	-	-	0.010	1.179	0.002
41	565982.04	-	-	-	0.010	1.309	0.002
42	560487.47	-	-	-	0.010	1.177	0.002
43	555083.84	-	-	-	0.010	0.976	0.002
44	549871.21	-	-	-	0.010	1.243	0.002
45	544714.85	-	-	-	0.010	1.341	0.002
46	539577.74	-	-	-	0.010	1.220	0.002
47	534490.50	-	-	-	0.010	1.268	0.002
48	529669.53	-	-	-	0.010	1.062	0.002
49	524911.23	-	-	-	0.010	1.579	0.002
50	520262.58	-	-	-	0.010	1.216	0.002

Continued on next page

Table 5 – continued from previous page - R7

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**MILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
51	515671.85	-	-	-	0.010	1.006	0.002
52	511091.94	-	-	-	0.010	1.402	0.002
53	506714.92	-	-	-	0.010	1.007	0.002
54	502359.25	-	-	-	0.010	1.069	0.002
55	498186.11	-	-	-	0.010	1.128	0.002
56	494067.17	-	-	-	0.010	0.995	0.002
57	489973.67	-	-	-	0.010	1.293	0.002
58	485992.49	-	-	-	0.010	0.962	0.002
59	482178.55	-	-	-	0.010	1.207	0.002
60	478375.08	-	-	-	0.020	1.313	0.011
61	474705.94	-	-	-	0.010	1.160	0.002
62	470980.07	-	-	-	0.010	1.263	0.002
63	467310.94	-	-	-	0.010	1.113	0.001
64	463718.55	-	-	-	0.010	1.217	0.001
65	460313.12	-	-	-	0.010	1.416	0.001
66	456924.08	-	-	-	0.010	1.248	0.001
67	453651.27	-	-	-	0.010	1.322	0.001
68	450410.50	-	-	-	0.010	1.162	0.001
69	447175.51	-	-	-	0.010	1.266	0.001
70	444037.87	-	-	-	0.010	1.391	0.001
71	440954.99	-	-	-	0.010	1.488	0.001
72	437985.66	-	-	-	0.010	1.042	0.001
73	435119.59	-	-	-	0.000	1.215	0.001
74	432258.81	-	-	-	0.000	1.143	0.001
75	429487.13	-	-	-	0.000	1.181	0.001
76	426749.32	-	-	-	0.000	1.236	0.001
77	424149.52	-	-	-	0.000	1.322	0.001
78	421561.04	-	-	-	0.000	1.467	0.001
79	418997.85	-	-	-	0.000	1.182	0.001
80	416481.59	-	-	-	0.000	1.231	0.001
81	413993.45	-	-	-	0.010	1.343	0.001
82	411517.66	-	-	-	0.010	1.412	0.001
83	409100.21	-	-	-	0.010	1.369	0.001
84	406749.60	-	-	-	0.010	1.252	0.001
85	404459.02	-	-	-	0.010	1.514	0.001
86	402248.65	-	-	-	0.010	1.304	0.001
87	400214.26	-	-	-	0.010	1.256	0.001
88	398253.98	-	-	-	0.010	1.171	0.001
89	396403.12	-	-	-	0.010	1.396	0.001
90	394560.69	-	-	-	0.010	1.298	0.001
91	392796.69	-	-	-	0.010	1.610	0.001
92	391041.81	-	-	-	0.010	1.387	0.001
93	389300.33	-	-	-	0.010	1.308	0.001
94	387600.79	-	-	-	0.010	1.262	0.001
95	385903.36	-	-	-	0.010	1.340	0.001
96	384236.72	-	-	-	0.020	1.345	0.001
97	382694.21	-	-	-	0.010	1.386	0.001
98	381166.02	-	-	-	0.010	1.327	0.001
99	379690.84	-	-	-	0.010	1.331	0.001
100	378224.25	-	-	-	0.010	1.395	0.001
101	376808.11	-	-	-	0.010	1.408	0.001
102	375400.31	-	-	-	0.010	1.470	0.001

Continued on next page

Table 5 – continued from previous page - R7

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**MILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
103	374000.43	-	-	-	0.010	1.100	0.001
104	372605.20	-	-	-	0.010	1.413	0.001
105	371225.02	-	-	-	0.010	1.211	0.001
106	369844.99	-	-	-	0.010	1.467	0.001
107	368527.42	-	-	-	0.010	1.503	0.001
108	367234.25	-	-	-	0.010	1.375	0.001
109	365999.16	-	-	-	0.010	1.671	0.001
110	364730.11	-	-	-	0.010	1.424	0.001
111	363496.17	-	-	-	0.010	1.537	0.001
112	362270.16	-	-	-	0.010	1.319	0.001
113	361060.98	-	-	-	0.010	1.405	0.001
114	359886.27	-	-	-	0.010	1.701	0.001
115	358737.55	-	-	-	0.010	1.509	0.001
116	357593.07	-	-	-	0.010	1.553	0.001
117	356473.37	-	-	-	0.010	1.541	0.001
118	355403.34	-	-	-	0.010	1.461	0.001
119	354338.57	-	-	-	0.010	1.439	0.001
120	353288.77	-	-	-	0.010	1.402	0.001
121	352248.63	-	-	-	0.010	1.366	0.001
122	351214.01	-	-	-	0.010	1.466	0.001
123	350180.19	-	-	-	0.010	1.399	0.001
124	349164.93	-	-	-	0.010	1.574	0.001
125	348155.67	-	-	-	0.010	1.534	0.001
126	347155.50	-	-	-	0.010	1.515	0.001
127	346162.12	-	-	-	0.010	1.473	0.001
128	345200.06	-	-	-	0.010	1.663	0.001
129	344255.62	-	-	-	0.010	1.554	0.001
130	343293.55	-	-	-	0.010	1.545	0.001
131	342354.79	-	-	-	0.010	1.713	0.001
132	341420.94	-	-	-	0.010	1.769	0.001
133	340482.18	-	-	-	0.010	1.494	0.000
134	339564.27	-	-	-	0.010	1.571	0.000
135	338685.54	-	-	-	0.010	1.835	0.000
136	337812.70	-	-	-	0.010	1.598	0.000
137	336940.03	-	-	-	0.010	1.545	0.000
138	336068.59	-	-	-	0.010	1.737	0.000
139	335207.98	-	-	-	0.010	1.490	0.000
140	334360.09	-	-	-	0.010	1.889	0.000
141	333522.07	-	-	-	0.010	1.659	0.000
142	332690.75	-	-	-	0.010	1.782	0.000
143	331866.06	-	-	-	0.010	1.579	0.000
144	331075.70	-	-	-	0.010	1.722	0.000
145	330307.17	-	-	-	0.010	1.588	0.000
146	329543.60	-	-	-	0.010	1.543	0.000
147	328775.08	-	-	-	0.010	1.541	0.000
148	328024.73	-	-	-	0.010	1.485	0.000
149	327276.00	-	-	-	0.010	1.578	0.000
150	326527.91	-	-	-	0.010	1.534	0.000
151	325798.18	-	-	-	0.010	1.746	0.000
152	325068.81	-	-	-	0.010	1.757	0.000
153	324339.62	-	-	-	0.010	1.742	0.000
154	323624.56	-	-	-	0.010	1.611	0.000

Continued on next page

Table 5 – continued from previous page - R7

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**MILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
155	322912.44	-	-	-	0.010	1.625	0.000
156	322217.13	-	-	-	0.010	1.583	0.000
157	321524.28	-	-	-	0.010	1.671	0.000
158	320834.45	-	-	-	0.010	1.820	0.000
159	320159.68	-	-	-	0.010	1.715	0.000
160	319524.17	-	-	-	0.010	1.814	0.000
161	318844.20	-	-	-	0.010	1.847	0.000
162	318192.50	-	-	-	0.010	1.615	0.000
163	317568.87	-	-	-	0.010	2.234	0.000
164	316950.80	-	-	-	0.010	1.952	0.000
165	316337.94	-	-	-	0.010	2.085	0.000
166	315747.41	-	-	-	0.010	1.689	0.000
167	315174.15	-	-	-	0.010	1.828	0.000
168	314605.07	-	-	-	0.010	1.742	0.000
169	314041.68	-	-	-	0.010	2.208	0.000
170	313492.71	-	-	-	0.010	1.784	0.000
171	312947.18	-	-	-	0.010	1.716	0.000
172	312433.28	-	-	-	0.010	1.959	0.000
173	311927.15	-	-	-	0.000	1.790	0.000
174	311422.60	-	-	-	0.000	2.050	0.000
175	310921.13	-	-	-	0.000	1.737	0.000
176	310423.15	-	-	-	0.000	1.791	0.000
177	309927.07	-	-	-	0.000	1.902	0.000
178	309431.42	-	-	-	0.000	1.952	0.000
179	308953.32	-	-	-	0.000	1.914	0.000
180	308476.15	-	-	-	0.000	1.856	0.000
181	308008.13	-	-	-	0.000	1.957	0.000
182	307542.53	-	-	-	0.000	1.965	0.000
183	307092.99	-	-	-	0.000	1.846	0.000
184	306648.34	-	-	-	0.000	1.643	0.000
185	306226.50	-	-	-	0.000	2.038	0.000
186	305808.42	-	-	-	0.000	2.150	0.000
187	305417.01	-	-	-	0.000	2.065	0.000
188	305007.11	-	-	-	0.000	1.998	0.000
189	304625.06	-	-	-	0.000	2.351	0.000
190	304251.40	-	-	-	0.000	2.493	0.000
191	303879.13	-	-	-	0.000	2.037	0.000
192	303509.49	-	-	-	0.000	2.030	0.000
193	303144.00	-	-	-	0.000	2.759	0.000
194	302780.26	-	-	-	0.000	2.217	0.000
195	302416.88	-	-	-	0.000	2.697	0.000
196	302056.42	-	-	-	0.000	1.847	0.000
197	301701.89	-	-	-	0.000	2.595	0.000
198	301357.79	-	-	-	0.000	2.798	0.000
199	301015.75	-	-	-	0.000	2.440	0.000
200	300679.70	-	-	-	0.000	1.951	0.000
201	300346.68	-	-	-	0.000	2.371	0.000
202	300016.57	-	-	-	0.000	2.101	0.000
203	299687.12	-	-	-	0.000	2.598	0.000
204	299364.61	-	-	-	0.000	2.138	0.000
205	299043.04	-	-	-	0.000	2.202	0.000
206	298726.27	-	-	-	0.000	2.140	0.000

Continued on next page

Table 5 – continued from previous page - R7

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**MILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
207	298404.92	-	-	-	0.000	2.478	0.000
208	298088.16	-	-	-	0.000	2.581	0.000
209	297785.98	-	-	-	0.000	2.289	0.000
210	297486.43	-	-	-	0.000	2.128	0.000
211	297191.09	-	-	-	0.000	2.879	0.000
212	296896.75	-	-	-	0.000	2.467	0.000
213	296610.20	-	-	-	0.000	3.051	0.000
214	296325.28	-	-	-	0.000	2.919	0.000
215	296047.96	-	-	-	0.000	2.319	0.000
216	295771.87	-	-	-	0.000	2.831	0.000
217	295500.65	-	-	-	0.000	2.559	0.000
218	295237.99	-	-	-	0.000	2.631	0.000
219	294978.35	-	-	-	0.000	2.299	0.000
220	294721.56	-	-	-	0.000	2.913	0.000
221	294467.69	-	-	-	0.000	2.503	0.000
222	294214.91	-	-	-	0.000	2.643	0.000
223	293963.38	-	-	-	0.000	2.275	0.000
224	293713.58	-	-	-	0.000	2.531	0.000
225	293464.92	-	-	-	0.000	2.377	0.000
226	293216.81	-	-	-	0.000	2.305	0.000
227	292969.99	-	-	-	0.000	2.325	0.000
228	292731.47	-	-	-	0.000	2.672	0.000
229	292493.77	-	-	-	0.000	2.593	0.000
230	292257.05	-	-	-	0.000	2.352	0.000
231	292021.44	-	-	-	0.000	2.495	0.000
232	291787.47	-	-	-	0.000	2.784	0.000
233	291555.50	-	-	-	0.000	2.401	0.000
234	291325.52	-	-	-	0.000	2.436	0.000
235	291096.99	-	-	-	0.000	2.412	0.000
236	290871.48	-	-	-	0.000	2.282	0.000
237	290654.46	-	-	-	0.000	2.188	0.000
238	290440.96	-	-	-	0.000	2.111	0.000
239	290230.70	-	-	-	0.000	2.684	0.000
240	290024.60	-	-	-	0.000	2.391	0.000
241	289819.61	-	-	-	0.000	2.221	0.000
242	289616.34	-	-	-	0.000	2.639	0.000
243	289414.38	-	-	-	0.000	2.434	0.000
244	289213.28	-	-	-	0.000	2.477	0.000
245	289012.78	-	-	-	0.000	2.355	0.000
246	288814.46	-	-	-	0.000	2.587	0.000
247	288616.76	-	-	-	0.000	2.504	0.000
248	288419.63	-	-	-	0.000	2.187	0.000
249	288226.31	-	-	-	0.000	2.642	0.000
250	288034.11	-	-	-	0.000	2.437	0.000
251	287844.36	-	-	-	0.000	2.302	0.000
252	287654.64	-	-	-	0.000	2.636	0.000
253	287465.58	-	-	-	0.000	2.422	0.000
254	287281.11	-	-	-	0.000	2.546	0.000
255	287100.05	-	-	-	0.000	2.919	0.000
256	286919.75	-	-	-	0.000	2.398	0.000
257	286739.70	-	-	-	0.000	2.545	0.000
258	286560.72	-	-	-	0.000	2.506	0.000

Continued on next page

Table 5 – continued from previous page - R7

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**MILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
259	286381.90	-	-	-	0.000	3.266	0.000
260	286204.54	-	-	-	0.000	2.755	0.000
261	286034.07	-	-	-	0.000	2.614	0.000
262	285863.91	-	-	-	0.000	2.218	0.000
263	285693.86	-	-	-	0.000	2.755	0.000
264	285526.03	-	-	-	0.000	2.993	0.000
265	285360.58	-	-	-	0.000	2.642	0.000
266	285195.47	-	-	-	0.000	2.621	0.000
267	285032.19	-	-	-	0.000	2.271	0.000
268	284869.47	-	-	-	0.000	2.822	0.000
269	284709.84	-	-	-	0.000	2.648	0.000
270	284551.55	-	-	-	0.000	2.540	0.000
271	284393.45	-	-	-	0.000	2.740	0.000
272	284237.52	-	-	-	0.000	2.573	0.000
273	284082.14	-	-	-	0.000	2.809	0.000
274	283929.05	-	-	-	0.000	2.591	0.000
275	283778.85	-	-	-	0.000	3.038	0.000
276	283628.77	-	-	-	0.000	2.495	0.000
277	283478.95	-	-	-	0.000	2.407	0.000
278	283331.39	-	-	-	0.000	2.921	0.000
279	283183.98	-	-	-	0.000	2.434	0.000
280	283037.70	-	-	-	0.000	2.528	0.000
281	282891.82	-	-	-	0.000	2.977	0.000
282	282746.39	-	-	-	0.000	2.708	0.000
283	282602.38	-	-	-	0.000	2.777	0.000
284	282458.78	-	-	-	0.000	2.998	0.000
285	282315.67	-	-	-	0.000	2.801	0.000
286	282172.79	-	-	-	0.000	3.357	0.000
287	282031.39	-	-	-	0.000	2.972	0.000
288	281890.17	-	-	-	0.000	3.126	0.000
289	281749.40	-	-	-	0.000	2.819	0.000
290	281610.26	-	-	-	0.000	2.917	0.000
291	281473.11	-	-	-	0.000	2.911	0.000
292	281337.73	-	-	-	0.000	2.456	0.000
293	281203.59	-	-	-	0.000	2.964	0.000
294	281070.35	-	-	-	0.000	3.104	0.000
295	280938.26	-	-	-	0.000	3.292	0.000
296	280808.55	-	-	-	0.000	2.628	0.000
297	280679.13	-	-	-	0.000	3.082	0.000
298	280551.39	-	-	-	0.000	2.854	0.000
299	280423.79	-	-	-	0.000	3.083	0.000
300	280298.17	-	-	-	0.000	3.181	0.000
301	280174.15	-	-	-	0.000	2.525	0.000
302	280052.30	-	-	-	0.000	2.938	0.000
303	279931.67	-	-	-	0.000	2.787	0.000
304	279811.24	-	-	-	0.000	2.911	0.000
305	279690.88	-	-	-	0.000	2.898	0.000
306	279573.54	-	-	-	0.000	2.835	0.000
307	279459.14	-	-	-	0.000	2.781	0.000
308	279344.79	-	-	-	0.000	2.836	0.000
309	279232.18	-	-	-	0.000	3.031	0.000
310	279120.43	-	-	-	0.000	3.171	0.000

Continued on next page

Table 5 – continued from previous page - R7

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**MILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
311	279008.88	-	-	-	0.000	2.739	0.000
312	278898.57	-	-	-	0.000	3.049	0.000
313	278789.02	-	-	-	0.000	2.792	0.000
314	278683.80	-	-	-	0.000	2.683	0.000
315	278579.36	-	-	-	0.000	2.638	0.000
316	278476.06	-	-	-	0.000	2.712	0.000
317	278372.93	-	-	-	0.000	3.039	0.000
318	278269.89	-	-	-	0.000	2.702	0.000
319	278166.96	-	-	-	0.000	2.934	0.000
320	278065.32	-	-	-	0.000	2.626	0.000
321	277963.72	-	-	-	0.000	3.021	0.000
322	277862.13	-	-	-	0.000	3.308	0.000
323	277761.26	-	-	-	0.000	2.869	0.000
324	277660.88	-	-	-	0.000	3.185	0.000
325	277562.42	-	-	-	0.000	2.860	0.000
326	277463.81	-	-	-	0.000	2.652	0.000
327	277365.34	-	-	-	0.000	3.000	0.000
328	277267.06	-	-	-	0.000	3.237	0.000
329	277170.69	-	-	-	0.000	2.915	0.000
330	277075.86	-	-	-	0.000	3.126	0.000
331	276981.95	-	-	-	0.000	3.248	0.000
332	276888.26	-	-	-	0.000	3.036	0.000
333	276795.17	-	-	-	0.000	3.374	0.000
334	276702.08	-	-	-	0.000	2.961	0.000
335	276611.35	-	-	-	0.000	3.006	0.000
336	276520.99	-	-	-	0.000	2.958	0.000
337	276431.60	-	-	-	0.000	2.905	0.000
338	276344.42	-	-	-	0.000	2.810	0.000
339	276258.71	-	-	-	0.000	2.431	0.000
340	276174.71	-	-	-	0.000	2.517	0.000
341	276090.96	-	-	-	0.000	2.093	0.000
342	276007.25	-	-	-	0.000	2.244	0.000
343	275924.44	-	-	-	0.000	2.422	0.000
344	275842.34	-	-	-	0.000	2.302	0.000
345	275761.38	-	-	-	0.000	2.180	0.000
346	275680.45	-	-	-	0.000	1.995	0.000
347	275599.67	-	-	-	0.000	2.122	0.000
348	275519.84	-	-	-	0.000	2.674	0.000
349	275440.33	-	-	-	0.000	2.634	0.000
350	275363.64	-	-	-	0.000	1.494	0.000
351	275287.15	-	-	-	0.000	2.186	0.000
352	275211.48	-	-	-	0.000	2.534	0.000
353	275135.86	-	-	-	0.000	2.350	0.000
354	275060.48	-	-	-	0.000	2.308	0.000
355	274985.51	-	-	-	0.000	1.282	0.000
356	274910.66	-	-	-	0.000	1.185	0.000
357	274837.92	-	-	-	0.000	1.849	0.000
358	274765.35	-	-	-	0.000	1.741	0.000
359	274693.02	-	-	-	0.000	1.298	0.000
360	274620.78	-	-	-	0.000	0.959	0.000
361	274549.28	-	-	-	0.000	0.995	0.000
362	274477.95	-	-	-	0.000	1.183	0.000

Continued on next page

Table 5 – continued from previous page - R7

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**MILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
363	274406.91	-	-	-	0.000	0.931	0.000
364	274337.22	-	-	-	0.000	1.684	0.000
365	274267.57	-	-	-	0.000	1.386	0.000
366	274198.56	-	-	-	0.000	0.901	0.000
367	274129.55	-	-	-	0.000	1.183	0.000
368	274060.58	-	-	-	0.000	1.025	0.000
369	273992.49	-	-	-	0.000	1.021	0.000
370	273926.36	-	-	-	0.000	0.983	0.000
371	273860.33	-	-	-	0.000	0.890	0.000
372	273795.21	-	-	-	0.000	0.895	0.000
373	273730.14	-	-	-	0.000	0.157	0.000
374	273666.90	-	-	-	0.000	0.175	0.000
375	273603.75	-	-	-	0.000	1.550	0.000
376	273540.60	-	-	-	0.000	0.165	0.000
377	273477.55	-	-	-	0.000	1.797	0.000
378	273415.87	-	-	-	0.000	0.158	0.000
379	273354.59	-	-	-	0.000	1.059	0.000
380	273293.32	-	-	-	0.000	0.181	0.000
381	273232.22	-	-	-	0.000	0.181	0.000
382	273171.87	-	-	-	0.000	0.170	0.000
383	273111.55	-	-	-	0.000	0.157	0.000
384	273051.58	-	-	-	0.000	0.164	0.000
385	272991.67	-	-	-	0.000	0.146	0.000
386	272932.61	-	-	-	0.000	0.153	0.000
387	272874.48	-	-	-	0.000	0.154	0.000
388	272816.41	-	-	-	0.000	0.148	0.000
389	272758.84	-	-	-	0.000	0.149	0.000
390	272702.49	-	-	-	0.000	0.153	0.000
391	272646.26	-	-	-	0.000	0.179	0.000
392	272590.18	-	-	-	0.000	0.153	0.000
393	272536.11	-	-	-	0.000	0.136	0.000
394	272482.20	-	-	-	0.000	0.155	0.000
395	272428.45	-	-	-	0.000	0.146	0.000
396	272375.38	-	-	-	0.000	0.147	0.000
397	272322.58	-	-	-	0.000	0.148	0.000
398	272269.91	-	-	-	0.000	0.145	0.000
399	272217.60	-	-	-	0.000	0.169	0.000
400	272165.52	-	-	-	0.000	0.141	0.000
401	272114.10	-	-	-	0.000	0.177	0.000
402	272062.86	-	-	-	0.000	0.151	0.000
403	272011.68	-	-	-	0.000	0.137	0.000
404	271960.90	-	-	-	0.000	0.145	0.000
405	271910.37	-	-	-	0.000	0.166	0.000
406	271860.12	-	-	-	0.000	0.140	0.000
407	271809.94	-	-	-	0.000	0.167	0.000
408	271759.80	-	-	-	0.000	0.147	0.000
409	271709.68	-	-	-	0.000	0.145	0.000
410	271660.11	-	-	-	0.000	0.146	0.000
411	271610.62	-	-	-	0.000	0.147	0.000
412	271562.96	-	-	-	0.000	0.132	0.000
413	271516.39	-	-	-	0.000	0.128	0.000
414	271470.17	-	-	-	0.000	0.129	0.000

Continued on next page

Table 5 – continued from previous page - R7

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**MILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
415	271426.23	-	-	-	0.000	0.148	0.000
416	271382.92	-	-	-	0.000	0.128	0.000
417	271339.93	-	-	-	0.000	0.127	0.000
418	271297.06	-	-	-	0.000	0.127	0.000
419	271254.24	-	-	-	0.000	0.149	0.000
420	271212.42	-	-	-	0.000	0.132	0.000
421	271170.63	-	-	-	0.000	0.153	0.000
422	271129.22	-	-	-	0.000	0.151	0.000
423	271088.05	-	-	-	0.000	0.136	0.000
424	271047.53	-	-	-	0.000	0.131	0.000
425	271007.46	-	-	-	0.000	0.132	0.000
426	270968.25	-	-	-	0.000	0.143	0.000
427	270929.48	-	-	-	0.000	0.146	0.000
428	270891.08	-	-	-	0.000	0.131	0.000
429	270853.07	-	-	-	0.000	0.135	0.000
430	270815.22	-	-	-	0.000	0.146	0.000
431	270778.09	-	-	-	0.000	0.143	0.000
432	270742.20	-	-	-	0.000	0.131	0.000
433	270706.84	-	-	-	0.000	0.129	0.000
434	270671.68	-	-	-	0.000	0.133	0.000
435	270636.71	-	-	-	0.000	0.137	0.000
436	270601.77	-	-	-	0.000	0.124	0.000
437	270567.10	-	-	-	0.000	0.129	0.000
438	270532.47	-	-	-	0.000	0.123	0.000
439	270497.84	-	-	-	0.000	0.137	0.000
440	270463.46	-	-	-	0.000	0.119	0.000
441	270429.11	-	-	-	0.000	0.136	0.000
442	270394.77	-	-	-	0.000	0.118	0.000
443	270361.22	-	-	-	0.000	0.143	0.000
444	270327.67	-	-	-	0.000	0.131	0.000
445	270295.05	-	-	-	0.000	0.144	0.000
446	270262.76	-	-	-	0.000	0.126	0.000
447	270230.61	-	-	-	0.000	0.140	0.000
448	270198.92	-	-	-	0.000	0.143	0.000
449	270167.75	-	-	-	0.000	0.139	0.000
450	270136.81	-	-	-	0.000	0.131	0.000
451	270105.99	-	-	-	0.000	0.126	0.000
452	270075.78	-	-	-	0.000	0.119	0.000
453	270045.70	-	-	-	0.000	0.126	0.000
454	270015.69	-	-	-	0.000	0.138	0.000
455	269986.01	-	-	-	0.000	0.134	0.000
456	269956.58	-	-	-	0.000	0.112	0.000
457	269927.34	-	-	-	0.000	0.132	0.000
458	269898.24	-	-	-	0.000	0.132	0.000
459	269869.50	-	-	-	0.000	0.121	0.000
460	269840.76	-	-	-	0.000	0.126	0.000
461	269812.02	-	-	-	0.000	0.136	0.000
462	269783.83	-	-	-	0.000	0.131	0.000
463	269755.87	-	-	-	0.000	0.124	0.000
464	269727.96	-	-	-	0.000	0.121	0.000
465	269700.39	-	-	-	0.000	0.127	0.000
466	269672.82	-	-	-	0.000	0.127	0.000

Continued on next page

Table 5 – continued from previous page - R7

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**MILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
467	269645.25	-	-	-	0.000	0.148	0.000
468	269617.73	-	-	-	0.000	0.120	0.000
469	269590.25	-	-	-	0.000	0.127	0.000
470	269562.90	-	-	-	0.000	0.116	0.000
471	269535.63	-	-	-	0.000	0.140	0.000
472	269508.62	-	-	-	0.000	0.114	0.000
473	269482.24	-	-	-	0.000	0.114	0.000
474	269456.16	-	-	-	0.000	0.117	0.000
475	269430.08	-	-	-	0.000	0.108	0.000
476	269404.25	-	-	-	0.000	0.110	0.000
477	269378.48	-	-	-	0.000	0.117	0.000
478	269352.93	-	-	-	0.000	0.102	0.000
479	269327.51	-	-	-	0.000	0.123	0.000
480	269302.29	-	-	-	0.000	0.109	0.000
481	269277.23	-	-	-	0.000	0.114	0.000
482	269252.52	-	-	-	0.000	0.126	0.000
483	269228.02	-	-	-	0.000	0.113	0.000
484	269203.52	-	-	-	0.000	0.110	0.000
485	269179.03	-	-	-	0.000	0.128	0.000
486	269154.86	-	-	-	0.000	0.116	0.000
487	269130.95	-	-	-	0.000	0.114	0.000
488	269107.06	-	-	-	0.000	0.136	0.000
489	269083.24	-	-	-	0.000	0.132	0.000
490	269059.56	-	-	-	0.000	0.119	0.000
491	269036.10	-	-	-	0.000	0.117	0.000
492	269013.32	-	-	-	0.000	0.127	0.000
493	268990.54	-	-	-	0.000	0.122	0.000
494	268968.17	-	-	-	0.000	0.106	0.000
495	268945.81	-	-	-	0.000	0.129	0.000
496	268923.46	-	-	-	0.000	0.110	0.000
497	268901.10	-	-	-	0.000	0.115	0.000
498	268878.75	-	-	-	0.000	0.117	0.000
499	268856.40	-	-	-	0.000	0.111	0.000
500	268834.04	-	-	-	0.000	0.114	0.000
501	268811.69	-	-	-	0.000	0.108	0.000
502	268789.36	-	-	-	0.000	0.129	0.000
503	268767.14	-	-	-	0.000	0.111	0.000
504	268745.05	-	-	-	0.000	0.108	0.000
505	268722.99	-	-	-	0.000	0.114	0.000
506	268700.93	-	-	-	0.000	0.115	0.000
507	268678.90	-	-	-	0.000	0.110	0.000
508	268656.88	-	-	-	0.000	0.124	0.000
509	268634.85	-	-	-	0.000	0.117	0.000
510	268612.89	-	-	-	0.000	0.111	0.000
511	268590.98	-	-	-	0.000	0.119	0.000
512	268569.28	-	-	-	0.000	0.113	0.000
513	268547.68	-	-	-	0.000	0.121	0.000
514	268526.24	-	-	-	0.000	0.102	0.000
515	268505.62	-	-	-	0.000	0.119	0.000
516	268485.17	-	-	-	0.000	0.115	0.000
517	268465.05	-	-	-	0.000	0.122	0.000
518	268445.28	-	-	-	0.000	0.112	0.000

Continued on next page

Table 5 – continued from previous page - R7

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**MILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
519	268425.73	-	-	-	0.000	0.098	0.000
520	268406.82	-	-	-	0.000	0.147	0.000
521	268387.90	-	-	-	0.000	0.132	0.000
522	268369.47	-	-	-	0.000	0.107	0.000
523	268351.07	-	-	-	0.000	0.111	0.000
524	268332.79	-	-	-	0.000	0.105	0.000
525	268314.62	-	-	-	0.000	0.121	0.000
526	268296.44	-	-	-	0.000	0.127	0.000
527	268278.27	-	-	-	0.000	0.117	0.000
528	268260.11	-	-	-	0.000	0.115	0.000
529	268242.18	-	-	-	0.000	0.111	0.000
530	268224.38	-	-	-	0.000	0.123	0.000
531	268206.61	-	-	-	0.000	0.100	0.000
532	268188.84	-	-	-	0.000	0.117	0.000
533	268171.10	-	-	-	0.000	0.119	0.000
534	268153.38	-	-	-	0.000	0.123	0.000
535	268135.66	-	-	-	0.000	0.125	0.000
536	268118.27	-	-	-	0.000	0.114	0.000
537	268100.96	-	-	-	0.000	0.134	0.000
538	268083.67	-	-	-	0.000	0.116	0.000
539	268066.49	-	-	-	0.000	0.122	0.000
540	268049.34	-	-	-	0.000	0.144	0.000
541	268032.38	-	-	-	0.000	0.131	0.000
542	268015.73	-	-	-	0.000	0.143	0.000
543	267999.09	-	-	-	0.000	0.134	0.000
544	267982.56	-	-	-	0.000	0.122	0.000
545	267966.03	-	-	-	0.000	0.117	0.000
546	267949.73	-	-	-	0.000	0.141	0.000
547	267933.44	-	-	-	0.000	0.117	0.000
548	267917.60	-	-	-	0.000	0.136	0.000
549	267901.91	-	-	-	0.000	0.133	0.000
550	267886.61	-	-	-	0.000	0.123	0.000
551	267871.32	-	-	-	0.000	0.130	0.000
552	267856.03	-	-	-	0.000	0.131	0.000
553	267840.85	-	-	-	0.000	0.113	0.000
554	267825.80	-	-	-	0.000	0.124	0.000
555	267810.91	-	-	-	0.000	0.131	0.000
556	267796.01	-	-	-	0.000	0.119	0.000
557	267781.20	-	-	-	0.000	0.130	0.000
558	267766.74	-	-	-	0.000	0.125	0.000
559	267752.32	-	-	-	0.000	0.129	0.000
560	267737.96	-	-	-	0.000	0.119	0.000
561	267723.63	-	-	-	0.000	0.127	0.000
562	267709.69	-	-	-	0.000	0.121	0.000
563	267695.75	-	-	-	0.000	0.153	0.000
564	267681.97	-	-	-	0.000	0.119	0.000
565	267668.29	-	-	-	0.000	0.126	0.000
566	267654.61	-	-	-	0.000	0.137	0.000
567	267640.97	-	-	-	0.000	0.143	0.000
568	267627.38	-	-	-	0.000	0.126	0.000
569	267613.86	-	-	-	0.000	0.119	0.000
570	267600.59	-	-	-	0.000	0.110	0.000

Continued on next page

Table 5 – continued from previous page - R7

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**MILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
571	267587.37	-	-	-	0.000	0.120	0.000
572	267574.16	-	-	-	0.000	0.121	0.000
573	267561.17	-	-	-	0.000	0.114	0.000
574	267548.26	-	-	-	0.000	0.166	0.000
575	267535.39	-	-	-	0.000	0.112	0.000
576	267522.68	-	-	-	0.000	0.125	0.000
577	267510.34	-	-	-	0.000	0.116	0.000
578	267498.02	-	-	-	0.000	0.128	0.000
579	267485.75	-	-	-	0.000	0.111	0.000
580	267473.53	-	-	-	0.000	0.114	0.000
581	267461.42	-	-	-	0.000	0.126	0.000
582	267449.42	-	-	-	0.000	0.115	0.000
583	267437.49	-	-	-	0.000	0.110	0.000
584	267425.57	-	-	-	0.000	0.129	0.000
585	267413.72	-	-	-	0.000	0.130	0.000
586	267402.17	-	-	-	0.000	0.133	0.000
587	267390.64	-	-	-	0.000	0.105	0.000
588	267379.76	-	-	-	0.000	0.114	0.000
589	267368.96	-	-	-	0.000	0.106	0.000
590	267358.17	-	-	-	0.000	0.115	0.000
591	267347.46	-	-	-	0.000	0.120	0.000
592	267336.75	-	-	-	0.000	0.105	0.000
593	267326.15	-	-	-	0.000	0.111	0.000
594	267315.56	-	-	-	0.000	0.129	0.000
595	267305.15	-	-	-	0.000	0.104	0.000
596	267294.85	-	-	-	0.000	0.111	0.000
597	267284.70	-	-	-	0.000	0.116	0.000
598	267274.67	-	-	-	0.000	0.103	0.000
599	267264.64	-	-	-	0.000	0.108	0.000
600	267254.70	-	-	-	0.000	0.126	0.000
601	267244.77	-	-	-	0.000	0.116	0.000
602	267234.84	-	-	-	0.000	0.112	0.000
603	267225.01	-	-	-	0.000	0.113	0.000
604	267215.18	-	-	-	0.000	0.105	0.000
605	267205.44	-	-	-	0.000	0.116	0.000
606	267195.81	-	-	-	0.000	0.113	0.000
607	267186.20	-	-	-	0.000	0.124	0.000
608	267176.60	-	-	-	0.000	0.114	0.000
609	267167.11	-	-	-	0.000	0.120	0.000
610	267157.63	-	-	-	0.000	0.119	0.000
611	267148.20	-	-	-	0.000	0.122	0.000
612	267139.05	-	-	-	0.000	0.115	0.000
613	267129.92	-	-	-	0.000	0.101	0.000
614	267121.01	-	-	-	0.000	0.122	0.000
615	267112.11	-	-	-	0.000	0.112	0.000
616	267103.28	-	-	-	0.000	0.126	0.000
617	267094.49	-	-	-	0.000	0.109	0.000
618	267085.72	-	-	-	0.000	0.108	0.000
619	267077.04	-	-	-	0.000	0.108	0.000
620	267068.57	-	-	-	0.000	0.095	0.000
621	267060.13	-	-	-	0.000	0.104	0.000
622	267051.80	-	-	-	0.000	0.141	0.000

Continued on next page

Table 5 – continued from previous page - R7

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**MILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
623	267043.49	-	-	-	0.000	0.111	0.000
624	267035.20	-	-	-	0.000	0.111	0.000
625	267026.98	-	-	-	0.000	0.100	0.000
626	267018.97	-	-	-	0.000	0.094	0.000
627	267010.98	-	-	-	0.000	0.117	0.000
628	267003.09	-	-	-	0.000	0.109	0.000
629	266995.34	-	-	-	0.000	0.092	0.000
630	266987.59	-	-	-	0.000	0.122	0.000
631	266979.90	-	-	-	0.000	0.093	0.000
632	266972.30	-	-	-	0.000	0.107	0.000
633	266964.95	-	-	-	0.000	0.114	0.000
634	266957.71	-	-	-	0.000	0.112	0.000
635	266950.71	-	-	-	0.000	0.103	0.000
636	266943.83	-	-	-	0.000	0.115	0.000
637	266937.02	-	-	-	0.000	0.111	0.000
638	266930.22	-	-	-	0.000	0.108	0.000
639	266923.41	-	-	-	0.000	0.104	0.000
640	266916.61	-	-	-	0.000	0.106	0.000
641	266909.86	-	-	-	0.000	0.104	0.000
642	266903.17	-	-	-	0.000	0.101	0.000
643	266896.50	-	-	-	0.000	0.098	0.000
644	266890.06	-	-	-	0.000	0.106	0.000
645	266883.72	-	-	-	0.000	0.104	0.000
646	266877.45	-	-	-	0.000	0.130	0.000
647	266871.18	-	-	-	0.000	0.133	0.000
648	266864.98	-	-	-	0.000	0.098	0.000
649	266858.80	-	-	-	0.000	0.085	0.000
650	266852.64	-	-	-	0.000	0.097	0.000
651	266846.48	-	-	-	0.000	0.121	0.000
652	266840.32	-	-	-	0.000	0.108	0.000
653	266834.16	-	-	-	0.000	0.124	0.000
654	266828.14	-	-	-	0.000	0.084	0.000
655	266822.12	-	-	-	0.000	0.122	0.000
656	266816.17	-	-	-	0.000	0.133	0.000
657	266810.25	-	-	-	0.000	0.141	0.000
658	266804.32	-	-	-	0.000	0.117	0.000
659	266798.40	-	-	-	0.000	0.218	0.000
660	266792.50	-	-	-	0.000	0.158	0.000
661	266786.63	-	-	-	0.000	0.110	0.000
662	266780.85	-	-	-	0.000	0.115	0.000
663	266775.12	-	-	-	0.000	0.150	0.000
664	266769.43	-	-	-	0.000	0.160	0.000
665	266763.74	-	-	-	0.000	0.111	0.000
666	266758.06	-	-	-	0.000	0.143	0.000
667	266752.53	-	-	-	0.000	0.114	0.000
668	266747.04	-	-	-	0.000	0.104	0.000
669	266741.54	-	-	-	0.000	0.130	0.000
670	266736.13	-	-	-	0.000	0.107	0.000
671	266730.72	-	-	-	0.000	0.123	0.000
672	266725.32	-	-	-	0.000	0.110	0.000
673	266719.91	-	-	-	0.000	0.104	0.000
674	266714.57	-	-	-	0.000	0.112	0.000

Continued on next page

Table 5 – continued from previous page - R7

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**MILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
675	266709.24	-	-	-	0.000	0.129	0.000
676	266703.92	-	-	-	0.000	0.120	0.000
677	266698.61	-	-	-	0.000	0.106	0.000
678	266693.31	-	-	-	0.000	0.134	0.000
679	266688.06	-	-	-	0.000	0.133	0.000
680	266682.88	-	-	-	0.000	0.121	0.000
681	266677.73	-	-	-	0.000	0.117	0.000
682	266672.67	-	-	-	0.000	0.128	0.000
683	266667.68	-	-	-	0.000	0.116	0.000
684	266662.82	-	-	-	0.000	0.163	0.000
685	266658.08	-	-	-	0.000	0.118	0.000
686	266653.35	-	-	-	0.000	0.109	0.000
687	266648.64	-	-	-	0.000	0.121	0.000
688	266643.94	-	-	-	0.000	0.133	0.000
689	266639.27	-	-	-	0.000	0.114	0.000
690	266634.61	-	-	-	0.000	0.130	0.000
691	266629.95	-	-	-	0.000	0.127	0.000
692	266625.31	-	-	-	0.000	0.115	0.000
693	266620.73	-	-	-	0.000	0.129	0.000
694	266616.22	-	-	-	0.000	0.121	0.000
695	266611.82	-	-	-	0.000	0.142	0.000
696	266607.42	-	-	-	0.000	0.126	0.000
697	266603.05	-	-	-	0.000	0.104	0.000
698	266598.69	-	-	-	0.000	0.107	0.000
699	266594.36	-	-	-	0.000	0.128	0.000
700	266590.14	-	-	-	0.000	0.119	0.000
701	266585.92	-	-	-	0.000	0.115	0.000
702	266581.79	-	-	-	0.000	0.123	0.000
703	266577.65	-	-	-	0.000	0.110	0.000
704	266573.64	-	-	-	0.000	0.114	0.000
705	266569.73	-	-	-	0.000	0.127	0.000
706	266565.94	-	-	-	0.000	0.123	0.000
707	266562.17	-	-	-	0.000	0.126	0.000
708	266558.40	-	-	-	0.000	0.113	0.000
709	266554.69	-	-	-	0.000	0.118	0.000
710	266550.99	-	-	-	0.000	0.119	0.000
711	266547.33	-	-	-	0.000	0.117	0.000
712	266543.73	-	-	-	0.000	0.118	0.000
713	266540.13	-	-	-	0.000	0.116	0.000
714	266536.52	-	-	-	0.000	0.113	0.000
715	266533.06	-	-	-	0.000	0.116	0.000
716	266529.70	-	-	-	0.000	0.120	0.000
717	266526.34	-	-	-	0.000	0.106	0.000
718	266523.03	-	-	-	0.000	0.127	0.000
719	266519.86	-	-	-	0.000	0.128	0.000
720	266516.74	-	-	-	0.000	0.112	0.000
721	266513.63	-	-	-	0.000	0.118	0.000
722	266510.56	-	-	-	0.000	0.108	0.000
723	266507.50	-	-	-	0.000	0.109	0.000
724	266504.45	-	-	-	0.000	0.120	0.000
725	266501.39	-	-	-	0.000	0.119	0.000
726	266498.36	-	-	-	0.000	0.136	0.000

Continued on next page

Table 5 – continued from previous page - R7

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**MILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
727	266495.33	-	-	-	0.000	0.122	0.000
728	266492.32	-	-	-	0.000	0.124	0.000
729	266489.41	-	-	-	0.000	0.113	0.000
730	266486.50	-	-	-	0.000	0.111	0.000
731	266483.59	-	-	-	0.000	0.134	0.000
732	266480.71	-	-	-	0.000	0.110	0.000
733	266477.84	-	-	-	0.000	0.124	0.000
734	266474.99	-	-	-	0.000	0.112	0.000
735	266472.16	-	-	-	0.000	0.108	0.000
736	266469.33	-	-	-	0.000	0.119	0.000
737	266466.49	-	-	-	0.000	0.112	0.000
738	266463.66	-	-	-	0.000	0.129	0.000
739	266460.83	-	-	-	0.000	0.103	0.000
740	266458.00	-	-	-	0.000	0.109	0.000
741	266455.17	-	-	-	0.000	0.103	0.000
742	266452.38	-	-	-	0.000	0.108	0.000
743	266449.59	-	-	-	0.000	0.124	0.000
744	266446.83	-	-	-	0.000	0.102	0.000
745	266444.11	-	-	-	0.000	0.126	0.000
746	266441.40	-	-	-	0.000	0.100	0.000
747	266438.88	-	-	-	0.000	0.106	0.000
748	266436.40	-	-	-	0.000	0.105	0.000
749	266433.96	-	-	-	0.000	0.119	0.000
750	266431.54	-	-	-	0.000	0.116	0.000
751	266429.15	-	-	-	0.000	0.116	0.000
752	266426.76	-	-	-	0.000	0.117	0.000
753	266424.38	-	-	-	0.000	0.116	0.000
754	266422.10	-	-	-	0.000	0.103	0.000
755	266419.82	-	-	-	0.000	0.103	0.000
756	266417.54	-	-	-	0.000	0.109	0.000
757	266415.27	-	-	-	0.000	0.094	0.000
758	266413.09	-	-	-	0.000	0.105	0.000
759	266410.94	-	-	-	0.000	0.105	0.000
760	266408.85	-	-	-	0.000	0.105	0.000
761	266406.80	-	-	-	0.000	0.097	0.000
762	266404.74	-	-	-	0.000	0.100	0.000
763	266402.70	-	-	-	0.000	0.094	0.000
764	266400.72	-	-	-	0.000	0.105	0.000
765	266398.74	-	-	-	0.000	0.088	0.000
766	266396.76	-	-	-	0.000	0.098	0.000
767	266394.79	-	-	-	0.000	0.083	0.000
768	266392.82	-	-	-	0.000	0.092	0.000
769	266390.93	-	-	-	0.000	0.096	0.000
770	266389.05	-	-	-	0.000	0.094	0.000
771	266387.19	-	-	-	0.000	0.093	0.000
772	266385.37	-	-	-	0.000	0.097	0.000
773	266383.57	-	-	-	0.000	0.092	0.000
774	266381.76	-	-	-	0.000	0.097	0.000
775	266379.95	-	-	-	0.000	0.085	0.000
776	266378.15	-	-	-	0.000	0.104	0.000
777	266376.35	-	-	-	0.000	0.096	0.000
778	266374.56	-	-	-	0.000	0.088	0.000

Continued on next page

Table 5 – continued from previous page - R7

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**MILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
779	266372.78	-	-	-	0.000	0.087	0.000
780	266371.05	-	-	-	0.000	0.105	0.000
781	266369.33	-	-	-	0.000	0.088	0.000
782	266367.65	-	-	-	0.000	0.089	0.000
783	266365.97	-	-	-	0.000	0.079	0.000
784	266364.30	-	-	-	0.000	0.100	0.000
785	266362.68	-	-	-	0.000	0.088	0.000
786	266361.11	-	-	-	0.000	0.090	0.000
787	266359.54	-	-	-	0.000	0.083	0.000
788	266357.98	-	-	-	0.000	0.095	0.000
789	266356.46	-	-	-	0.000	0.092	0.000
790	266354.96	-	-	-	0.000	0.089	0.000
791	266353.46	-	-	-	0.000	0.084	0.000
792	266351.98	-	-	-	0.000	0.080	0.000
793	266350.52	-	-	-	0.000	0.085	0.000
794	266349.08	-	-	-	0.000	0.078	0.000
795	266347.68	-	-	-	0.000	0.070	0.000
796	266346.27	-	-	-	0.000	0.088	0.000
797	266344.89	-	-	-	0.000	0.075	0.000
798	266343.50	-	-	-	0.000	0.090	0.000
799	266342.22	-	-	-	0.000	0.077	0.000
800	266340.95	-	-	-	0.000	0.075	0.000
801	266339.69	-	-	-	0.000	0.077	0.000
802	266338.42	-	-	-	0.000	0.078	0.000
803	266337.17	-	-	-	0.000	0.073	0.000
804	266335.93	-	-	-	0.000	0.075	0.000
805	266334.74	-	-	-	0.000	0.080	0.000
806	266333.55	-	-	-	0.000	0.079	0.000
807	266332.37	-	-	-	0.000	0.082	0.000
808	266331.19	-	-	-	0.000	0.078	0.000
809	266330.01	-	-	-	0.000	0.071	0.000
810	266328.89	-	-	-	0.000	0.076	0.000
811	266327.82	-	-	-	0.000	0.071	0.000
812	266326.74	-	-	-	0.000	0.078	0.000
813	266325.66	-	-	-	0.000	0.067	0.000
814	266324.59	-	-	-	0.000	0.077	0.000
815	266323.64	-	-	-	0.000	0.081	0.000
816	266322.69	-	-	-	0.000	0.069	0.000
817	266321.73	-	-	-	0.000	0.080	0.000
818	266320.79	-	-	-	0.000	0.068	0.000
819	266319.89	-	-	-	0.000	0.073	0.000
820	266319.00	-	-	-	0.000	0.109	0.000
821	266318.11	-	-	-	0.000	0.075	0.000
822	266317.23	-	-	-	0.000	0.074	0.000
823	266316.34	-	-	-	0.000	0.074	0.000
824	266315.50	-	-	-	0.000	0.029	0.000
825	266314.66	-	-	-	0.000	0.098	0.000
826	266313.83	-	-	-	0.000	0.075	0.000
827	266313.02	-	-	-	0.000	0.092	0.000
828	266312.22	-	-	-	0.000	0.055	0.000
829	266311.46	-	-	-	0.000	0.050	0.000
830	266310.71	-	-	-	0.000	0.099	0.000

Continued on next page

Table 5 – continued from previous page - R7

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**MILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
831	266310.03	-	-	-	0.000	0.067	0.000
832	266309.34	-	-	-	0.000	0.097	0.000
833	266308.66	-	-	-	0.000	0.108	0.000
834	266307.98	-	-	-	0.000	0.092	0.000
835	266307.31	-	-	-	0.000	0.096	0.000
836	266306.69	-	-	-	0.000	0.093	0.000
837	266306.11	-	-	-	0.000	0.034	0.000
838	266305.53	-	-	-	0.000	0.030	0.000
839	266304.95	-	-	-	0.000	0.031	0.000
840	266304.40	-	-	-	0.000	0.030	0.000
841	266303.85	-	-	-	0.000	0.031	0.000
842	266303.30	-	-	-	0.000	0.030	0.000
843	266302.76	-	-	-	0.000	0.030	0.000
844	266302.23	-	-	-	0.000	0.030	0.000
845	266301.70	-	-	-	0.000	0.032	0.000
846	266301.16	-	-	-	0.000	0.031	0.000
847	266300.63	-	-	-	0.000	0.029	0.000
848	266300.11	-	-	-	0.000	0.030	0.000
849	266299.58	-	-	-	0.000	0.029	0.000
850	266299.18	-	-	-	0.000	0.032	0.000
851	266298.79	-	-	-	0.000	0.029	0.000
852	266298.39	-	-	-	0.000	0.028	0.000
853	266298.00	-	-	-	0.000	0.030	0.000
854	266297.60	-	-	-	0.000	0.029	0.000
855	266297.21	-	-	-	0.000	0.027	0.000
856	266296.86	-	-	-	0.000	0.028	0.000
857	266296.53	-	-	-	0.000	0.028	0.000
858	266296.23	-	-	-	0.000	0.030	0.000
859	266295.92	-	-	-	0.000	0.028	0.000
860	266295.61	-	-	-	0.000	0.027	0.000
861	266295.31	-	-	-	0.000	0.026	0.000
862	266295.01	-	-	-	0.000	0.027	0.000
863	266294.71	-	-	-	0.000	0.027	0.000
864	266294.46	-	-	-	0.000	0.026	0.000
865	266294.23	-	-	-	0.000	0.020	0.000
866	266294.08	-	-	-	0.000	0.018	0.000
867	266293.94	-	-	-	0.000	0.032	0.000
868	266293.81	-	-	-	0.000	0.030	0.000
869	266293.74	-	-	-	0.000	0.027	0.000
870	266293.69	-	-	-	0.000	0.024	0.000
871	266293.66	-	-	-	0.000	0.023	0.000
872	266293.64	-	-	-	0.000	0.010	0.000
873	266293.63	-	-	-	0.000	0.009	0.000
874	266293.63	-	-	-	0.000	0.009	0.000
875	266293.63	-	-	-	0.000	0.009	0.000
876	266293.63	-	-	-	0.000	0.009	0.000
877	266293.63	-	-	-	0.000	0.009	0.000
878	266293.63	-	-	-	0.000	0.009	0.000
879	266293.63	-	-	-	0.000	0.018	0.000
Total		**7303.22**	**9143.77**	**10552.00**	**2.00**	**760.11**	**0.25**

Table 6: ENS optimization - pr76zb.

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
0	7202.21	0.005	0.004	0.000	0.000	0.000	0.000
1	4782.33	0.003	0.004	0.000	0.000	0.003	0.000
2	3658.65	0.035	0.004	0.000	0.000	0.002	0.000
3	3038.70	0.082	0.007	0.000	0.000	0.011	0.000
4	2476.75	0.088	0.008	0.000	0.000	0.004	0.000
5	2114.28	0.273	0.016	0.000	0.000	0.004	0.000
6	1887.58	1.485	0.015	0.010	0.000	0.011	0.000
7	1784.09	4.794	0.025	0.000	0.000	0.012	0.000
8	1702.56	14.584	0.024	0.000	0.000	0.014	0.000
9	1632.03	35.446	0.027	0.010	0.000	0.015	0.000
10	1561.84	84.483	0.043	0.000	0.000	0.016	0.000
11	1502.62	190.086	0.045	0.010	0.000	0.013	0.000
12	1447.16	378.816	0.060	0.000	0.000	0.012	0.000
13	1393.84	686.155	0.067	0.010	0.000	0.017	0.000
14	1340.52	1302.415	0.073	0.000	0.000	0.018	0.000
15	1296.60	2457.141	0.079	0.010	0.000	0.015	0.000
16	1253.62	-	0.114	0.010	0.000	0.015	0.000
17	1215.81	-	0.124	0.000	0.000	0.013	0.000
18	1179.49	-	0.155	0.010	0.000	0.022	0.000
19	1144.02	-	0.164	0.000	0.000	0.015	0.000
20	1114.37	-	0.303	0.010	0.000	0.015	0.000
21	1083.41	-	0.293	0.010	0.000	0.018	0.000
22	1054.70	-	0.359	0.010	0.000	0.018	0.000
23	1026.05	-	0.329	0.000	0.000	0.014	0.000
24	1000.48	-	0.317	0.010	0.000	0.015	0.000
25	977.15	-	0.325	0.010	0.000	0.014	0.000
26	954.60	-	0.362	0.000	0.000	0.014	0.000
27	933.06	-	0.343	0.010	0.000	0.016	0.000
28	916.77	-	0.380	0.010	0.000	0.017	0.000
29	901.07	-	0.419	0.000	0.000	0.013	0.000
30	885.78	-	0.541	0.010	0.000	0.013	0.000
31	870.83	-	0.467	0.000	0.000	0.014	0.000
32	856.97	-	0.570	0.010	0.000	0.014	0.000
33	844.24	-	0.592	0.010	0.000	0.015	0.000
34	832.00	-	0.591	0.000	0.000	0.011	0.000
35	820.13	-	0.647	0.010	0.000	0.013	0.000
36	808.76	-	0.709	0.000	0.000	0.013	0.000
37	799.29	-	0.719	0.010	0.000	0.014	0.000
38	791.31	-	1.035	0.000	0.000	0.013	0.000
39	783.55	-	1.667	0.010	0.000	0.014	0.000
40	775.61	-	1.641	0.010	0.000	0.012	0.000
41	767.85	-	1.654	0.000	0.000	0.013	0.000
42	760.53	-	1.924	0.010	0.000	0.012	0.000
43	753.39	-	2.152	0.000	0.000	0.013	0.000
44	746.07	-	1.658	0.010	0.000	0.012	0.000
45	739.80	-	1.897	0.000	0.000	0.013	0.000
46	733.64	-	1.646	0.000	0.000	0.010	0.000
47	728.54	-	1.749	0.010	0.000	0.010	0.000
48	723.99	-	1.947	0.000	0.000	0.011	0.000
49	719.70	-	2.246	0.010	0.000	0.010	0.000
50	715.50	-	1.986	0.000	0.000	0.016	0.000

Continued on next page

Table 6 – continued from previous page - pr76zb

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
51	712.00	-	2.919	0.000	0.000	0.011	0.000
52	708.75	-	2.458	0.010	0.000	0.010	0.000
53	705.75	-	2.749	0.000	0.000	0.014	0.000
54	702.61	-	3.198	0.010	0.000	0.010	0.000
55	699.91	-	2.286	0.000	0.000	0.010	0.000
56	697.24	-	1.892	0.000	0.000	0.010	0.000
57	694.60	-	1.244	0.010	0.000	0.009	0.000
58	692.24	-	1.148	0.000	0.000	0.009	0.000
59	690.15	-	0.880	0.000	0.000	0.008	0.000
60	688.09	-	0.983	0.000	0.000	0.009	0.000
61	686.05	-	0.436	0.010	0.000	0.009	0.000
62	684.64	-	0.361	0.000	0.000	0.008	0.000
63	683.41	-	0.275	0.000	0.000	0.006	0.000
64	682.22	-	0.191	0.000	0.000	0.007	0.000
65	681.05	-	0.111	0.000	0.000	0.006	0.000
66	680.05	-	0.029	0.010	0.000	0.006	0.000
67	679.20	-	0.023	0.000	0.000	0.005	0.000
68	678.52	-	0.015	0.000	0.000	0.004	0.000
69	677.86	-	0.007	0.000	0.000	0.003	0.000
70	677.22	-	0.005	0.000	0.000	0.004	0.000
71	676.75	-	0.004	0.000	0.000	0.003	0.000
72	676.32	-	0.001	0.000	0.000	0.002	0.000
73	675.89	-	0.001	0.000	0.000	0.001	0.000
74	675.89	-	0.000	0.000	0.000	0.000	0.000
75	675.89	-	0.000	0.000	0.000	0.000	0.000
76	675.89	-	0.000	0.000	0.000	0.000	0.000
Total		**8755.89**	**53.74**	**0.30**	**0.01**	**0.816**	**0.000**

Table 7: ENS optimization - pr112zb.

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
0	15958.20	0.003	0.000	0.000	0.000	0.000	0.000
1	11844.50	0.008	0.004	0.000	0.000	0.005	0.000
2	9622.72	0.083	0.010	0.000	0.000	0.005	0.000
3	7463.52	0.140	0.010	0.000	0.000	0.005	0.000
4	6123.49	0.651	0.014	0.010	0.000	0.009	0.000
5	5277.61	1.085	0.015	0.000	0.000	0.011	0.000
6	4915.14	8.541	0.037	0.010	0.000	0.036	0.000
7	4591.26	38.887	0.082	0.010	0.000	0.029	0.000
8	4303.65	158.147	0.125	0.000	0.000	0.018	0.000
9	4076.94	575.926	0.122	0.010	0.000	0.017	0.000
10	3897.37	2176.144	0.152	0.010	0.000	0.019	0.000
11	3737.94	-	0.297	0.010	0.000	0.019	0.000
12	3590.20	-	0.359	0.010	0.000	0.019	0.000
13	3466.08	-	0.388	0.010	0.000	0.017	0.000
14	3350.71	-	0.384	0.010	0.000	0.019	0.000
15	3245.32	-	0.403	0.010	0.000	0.019	0.000
16	3139.93	-	0.391	0.020	0.000	0.019	0.000

Continued on next page

Table 7 – continued from previous page - pr112zb

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
17	3036.17	-	0.512	0.010	0.000	0.018	0.000
18	2932.69	-	0.513	0.020	0.000	0.019	0.000
19	2846.87	-	0.821	0.010	0.000	0.021	0.000
20	2773.64	-	0.992	0.020	0.000	0.019	0.000
21	2700.85	-	1.132	0.020	0.000	0.019	0.000
22	2629.15	-	1.332	0.010	0.000	0.020	0.000
23	2558.75	-	1.109	0.020	0.000	0.018	0.000
24	2488.56	-	1.068	0.020	0.000	0.020	0.000
25	2420.24	-	1.144	0.020	0.000	0.020	0.000
26	2368.88	-	1.395	0.010	0.000	0.024	0.000
27	2322.05	-	1.826	0.020	0.000	0.022	0.000
28	2275.52	-	2.206	0.020	0.000	0.026	0.000
29	2229.03	-	2.697	0.020	0.000	0.024	0.000
30	2182.86	-	3.115	0.020	0.000	0.025	0.000
31	2136.33	-	3.227	0.010	0.000	0.022	0.000
32	2090.55	-	3.315	0.020	0.000	0.022	0.000
33	2052.74	-	4.173	0.020	0.000	0.022	0.000
34	2015.78	-	4.749	0.020	0.000	0.018	0.000
35	1980.31	-	5.397	0.010	0.000	0.020	0.000
36	1948.52	-	6.628	0.020	0.000	0.022	0.000
37	1914.35	-	6.368	0.020	0.000	0.023	0.000
38	1883.03	-	7.301	0.010	0.000	0.023	0.000
39	1853.12	-	8.006	0.020	0.000	0.023	0.000
40	1821.80	-	7.060	0.010	0.000	0.020	0.000
41	1792.15	-	6.417	0.020	0.000	0.026	0.000
42	1762.62	-	5.216	0.020	0.000	0.026	0.000
43	1735.61	-	4.456	0.010	0.000	0.022	0.000
44	1709.41	-	3.675	0.020	0.000	0.017	0.000
45	1686.86	-	3.671	0.010	0.000	0.021	0.000
46	1665.32	-	3.266	0.020	0.000	0.017	0.000
47	1644.62	-	2.969	0.010	0.000	0.022	0.000
48	1625.16	-	3.577	0.020	0.000	0.022	0.000
49	1606.46	-	3.442	0.010	0.000	0.020	0.000
50	1589.53	-	3.682	0.020	0.000	0.019	0.000
51	1574.38	-	4.620	0.010	0.000	0.019	0.000
52	1560.51	-	6.552	0.020	0.000	0.019	0.000
53	1547.23	-	14.629	0.010	0.000	0.019	0.000
54	1534.09	-	16.511	0.020	0.000	0.018	0.000
55	1521.37	-	17.361	0.020	0.000	0.020	0.000
56	1509.13	-	22.404	0.010	0.000	0.019	0.000
57	1497.25	-	35.591	0.010	0.000	0.020	0.000
58	1485.89	-	51.772	0.020	0.000	0.022	0.000
59	1475.29	-	63.084	0.010	0.000	0.019	0.000
60	1466.15	-	78.085	0.010	0.000	0.020	0.000
61	1458.17	-	111.779	0.010	0.000	0.019	0.000
62	1450.41	-	131.318	0.010	0.000	0.019	0.000
63	1442.48	-	134.916	0.020	0.000	0.019	0.000
64	1434.72	-	128.803	0.010	0.000	0.018	0.000
65	1427.39	-	140.172	0.010	0.000	0.019	0.000
66	1420.94	-	153.888	0.010	0.000	0.017	0.000
67	1414.67	-	158.876	0.010	0.000	0.016	0.000
68	1408.52	-	160.544	0.010	0.000	0.015	0.000

Continued on next page

Table 7 – continued from previous page - pr112zb

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
69	1402.86	-	195.256	0.010	0.000	0.015	0.000
70	1398.31	-	270.313	0.010	0.000	0.016	0.000
71	1393.28	-	265.807	0.010	0.000	0.016	0.000
72	1388.73	-	341.337	0.010	0.000	0.015	0.000
73	1384.28	-	453.708	0.010	0.000	0.015	0.000
74	1379.99	-	558.615	0.010	0.000	0.015	0.000
75	1375.79	-	567.210	0.010	0.000	0.014	0.000
76	1372.19	-	632.541	0.010	0.000	0.014	0.000
77	1368.69	-	721.299	0.010	0.000	0.020	0.000
78	1365.69	-	551.486	0.010	0.000	0.016	0.000
79	1362.55	-	368.395	0.010	0.000	0.015	0.000
80	1359.85	-	375.877	0.010	0.000	0.015	0.000
81	1357.17	-	-	0.000	0.000	0.014	0.000
82	1354.50	-	-	0.010	0.000	0.016	0.000
83	1352.14	-	-	0.010	0.000	0.015	0.000
84	1350.06	-	-	0.010	0.000	0.013	0.000
85	1348.00	-	-	0.000	0.000	0.013	0.000
86	1345.96	-	-	0.010	0.000	0.014	0.000
87	1344.07	-	-	0.000	0.000	0.012	0.000
88	1342.65	-	-	0.010	0.000	0.012	0.000
89	1341.41	-	-	0.010	0.000	0.012	0.000
90	1340.18	-	-	0.000	0.000	0.011	0.000
91	1338.97	-	-	0.010	0.000	0.012	0.000
92	1337.78	-	-	0.000	0.000	0.011	0.000
93	1336.60	-	-	0.010	0.000	0.011	0.000
94	1335.60	-	-	0.000	0.000	0.011	0.000
95	1334.62	-	-	0.010	0.000	0.010	0.000
96	1333.77	-	-	0.000	0.000	0.010	0.000
97	1333.02	-	-	0.000	0.000	0.010	0.000
98	1332.31	-	-	0.010	0.000	0.010	0.000
99	1331.63	-	-	0.000	0.000	0.009	0.000
100	1330.97	-	-	0.000	0.000	0.009	0.000
101	1330.34	-	-	0.000	0.000	0.010	0.000
102	1329.79	-	-	0.010	0.000	0.007	0.000
103	1329.31	-	-	0.000	0.000	0.010	0.000
104	1328.87	-	-	0.000	0.000	0.007	0.000
105	1328.42	-	-	0.000	0.000	0.014	0.000
106	1327.97	-	-	0.000	0.000	0.007	0.000
107	1327.54	-	-	0.000	0.000	0.004	0.000
108	1327.12	-	-	0.010	0.000	0.003	0.000
109	1326.86	-	-	0.000	0.000	0.002	0.000
110	1326.86	-	-	0.000	0.000	0.001	0.000
111	1326.86	-	-	0.000	0.000	0.000	0.000
112	1326.86	-	-	0.000	0.000	0.000	0.000
Total		**10159.61**	**7391.90**	**1.16**	**0.01**	**1.811**	**0.000**

Table 8: ENS optimization - pr199zb.

m	best ENS	Time (sec)					
		ILP-GALIAS	ILP-IFLOWS	DP-TS	DP-N2M2	ILP-CUTS	DP-PC
0	58226.30	0.005	0.001	0.000	0.000	0.001	0.000
1	40600.10	0.015	0.011	0.000	0.000	0.011	0.000
2	26659.80	0.169	0.005	0.000	0.000	0.005	0.000
3	21246.90	0.126	0.015	0.010	0.000	0.015	0.000
4	17694.00	3.898	0.020	0.010	0.000	0.020	0.000
5	15691.50	19.000	0.024	0.020	0.000	0.024	0.000
6	14129.70	86.690	0.027	0.030	0.000	0.027	0.000
7	12629.80	440.242	0.033	0.060	0.000	0.033	0.000
8	11682.60	2168.202	0.063	0.110	0.000	0.027	0.000
9	10868.70	-	0.131	0.160	0.000	0.026	0.000
10	10063.70	-	0.176	0.260	0.000	0.038	0.000
11	9279.62	-	0.137	0.370	0.000	0.032	0.000
12	8788.67	-	0.195	0.530	0.000	0.031	0.000
13	8423.90	-	0.287	0.690	0.000	0.031	0.000
14	8100.02	-	0.310	0.920	0.000	0.032	0.000
15	7799.98	-	0.418	1.150	0.000	0.030	0.000
16	7512.38	-	0.576	1.460	0.000	0.031	0.000
17	7285.67	-	0.984	1.800	0.000	0.030	0.000
18	7076.93	-	1.277	2.180	0.000	0.031	0.000
19	6882.73	-	1.457	2.570	0.000	0.032	0.000
20	6693.08	-	1.683	2.920	0.000	0.027	0.000
21	6507.08	-	2.070	3.400	0.000	0.030	0.000
22	6327.51	-	2.158	3.930	0.000	0.028	0.000
23	6151.95	-	2.559	4.430	0.000	0.027	0.000
24	5992.52	-	2.793	5.070	0.000	0.031	0.000
25	5844.77	-	3.376	5.700	0.000	0.026	0.000
26	5720.66	-	3.486	6.280	0.000	0.029	0.000
27	5604.15	-	4.007	6.940	0.000	0.028	0.000
28	5488.78	-	4.419	7.640	0.000	0.027	0.000
29	5383.38	-	5.169	8.460	0.000	0.027	0.000
30	5277.99	-	6.280	9.380	0.000	0.030	0.000
31	5174.24	-	5.516	9.940	0.000	0.031	0.000
32	5070.75	-	5.908	10.840	0.001	0.029	0.000
33	4971.78	-	6.218	11.680	0.000	0.030	0.000
34	4881.06	-	7.647	12.460	0.000	0.032	0.000
35	4794.75	-	11.196	13.380	0.001	0.029	0.000
36	4708.94	-	14.132	14.440	0.000	0.027	0.000
37	4635.70	-	23.398	15.220	0.000	0.030	0.000
38	4562.92	-	32.894	16.320	0.000	0.030	0.000
39	4491.22	-	54.902	17.250	0.000	0.032	0.000
40	4420.82	-	69.520	18.390	0.000	0.032	0.000
41	4350.63	-	105.535	19.370	0.000	0.030	0.000
42	4282.14	-	134.385	20.530	0.000	0.030	0.000
43	4213.82	-	136.850	21.690	0.000	0.034	0.000
44	4149.29	-	143.730	22.770	0.000	0.032	0.000
45	4097.92	-	218.613	23.880	0.000	0.034	0.000
46	4049.22	-	297.438	25.000	0.000	0.035	0.000
47	4002.40	-	444.198	25.970	0.000	0.038	0.000
48	3955.87	-	534.629	27.320	0.000	0.032	0.000
49	3909.38	-	678.595	28.220	0.000	0.035	0.000
50	3863.21	-	1282.212	29.210	0.000	0.037	0.000

Continued on next page

Table 8 – continued from previous page - pr199zb

		Time (sec)					
m	best ENS	ILP-GALIAS	ILP-IFLOWS	DP-TS	DP-N2M2	ILP-CUTS	DP-PC
51	3816.68	-	1094.963	30.280	0.000	0.037	0.000
52	3770.89	-	1231.472	31.560	0.000	0.037	0.000
53	3725.98	-	-	32.540	0.000	0.030	0.000
54	3685.32	-	-	33.500	0.000	0.033	0.000
55	3647.51	-	-	34.470	0.000	0.038	0.000
56	3610.06	-	-	35.700	0.000	0.032	0.000
57	3573.09	-	-	36.720	0.000	0.030	0.000
58	3537.62	-	-	37.650	0.000	0.028	0.000
59	3505.84	-	-	38.460	0.000	0.036	0.000
60	3471.66	-	-	39.700	0.000	0.034	0.000
61	3439.95	-	-	40.370	0.000	0.032	0.000
62	3408.63	-	-	41.650	0.000	0.033	0.000
63	3378.14	-	-	42.760	0.000	0.034	0.000
64	3347.40	-	-	43.680	0.000	0.031	0.000
65	3316.92	-	-	44.800	0.000	0.034	0.000
66	3287.26	-	-	45.440	0.000	0.036	0.000
67	3257.73	-	-	46.350	0.000	0.029	0.000
68	3230.72	-	-	47.440	0.000	0.034	0.000
69	3204.53	-	-	48.260	0.000	0.033	0.000
70	3178.59	-	-	49.350	0.000	0.034	0.000
71	3153.58	-	-	50.280	0.000	0.035	0.000
72	3130.41	-	-	51.810	0.000	0.035	0.000
73	3107.84	-	-	52.700	0.000	0.033	0.000
74	3085.29	-	-	53.230	0.000	0.033	0.000
75	3063.13	-	-	54.240	0.000	0.034	0.000
76	3041.58	-	-	55.120	0.000	0.032	0.000
77	3020.88	-	-	55.840	0.000	0.037	0.000
78	3001.43	-	-	56.670	0.000	0.035	0.000
79	2982.40	-	-	57.680	0.000	0.035	0.000
80	2963.70	-	-	59.040	0.000	0.035	0.000
81	2945.33	-	-	59.640	0.000	0.038	0.000
82	2927.03	-	-	60.320	0.000	0.036	0.000
83	2910.10	-	-	61.360	0.000	0.034	0.000
84	2893.27	-	-	61.970	0.000	0.036	0.000
85	2876.55	-	-	63.030	0.000	0.038	0.000
86	2860.74	-	-	63.310	0.000	0.035	0.000
87	2845.59	-	-	63.670	0.000	0.036	0.000
88	2831.52	-	-	64.540	0.000	0.035	0.000
89	2817.65	-	-	65.020	0.000	0.033	0.000
90	2803.91	-	-	65.350	0.000	0.037	0.000
91	2790.30	-	-	65.340	0.000	0.033	0.000
92	2777.02	-	-	65.910	0.000	0.031	0.000
93	2763.74	-	-	65.960	0.000	0.034	0.000
94	2750.60	-	-	66.050	0.000	0.035	0.000
95	2737.87	-	-	65.720	0.000	0.036	0.000
96	2725.64	-	-	66.190	0.000	0.036	0.000
97	2713.43	-	-	66.360	0.000	0.037	0.000
98	2701.28	-	-	66.030	0.000	0.035	0.000
99	2689.40	-	-	65.130	0.000	0.037	0.000
100	2677.70	-	-	65.650	0.000	0.037	0.000
101	2666.28	-	-	64.860	0.000	0.034	0.000
102	2654.90	-	-	64.220	0.000	0.036	0.000

Continued on next page

Table 8 – continued from previous page - pr199zb

		Time (sec)					
m	best ENS	ILP-GALIAS	ILP-IFLOWS	DP-TS	DP-N2M2	ILP-CUTS	DP-PC
103	2643.53	-	-	63.250	0.000	0.034	0.000
104	2632.94	-	-	63.880	0.000	0.036	0.000
105	2623.79	-	-	62.310	0.000	0.034	0.000
106	2615.53	-	-	61.470	0.000	0.038	0.000
107	2607.56	-	-	60.450	0.000	0.032	0.000
108	2599.70	-	-	60.040	0.000	0.033	0.000
109	2591.86	-	-	58.910	0.000	0.036	0.000
110	2584.00	-	-	57.860	0.000	0.031	0.000
111	2576.24	-	-	57.080	0.000	0.035	0.000
112	2568.61	-	-	56.560	0.000	0.034	0.000
113	2561.29	-	-	55.340	0.000	0.031	0.000
114	2554.22	-	-	54.570	0.000	0.030	0.000
115	2547.77	-	-	53.230	0.000	0.029	0.000
116	2541.47	-	-	52.620	0.000	0.031	0.000
117	2535.20	-	-	51.370	0.000	0.029	0.000
118	2529.05	-	-	49.890	0.000	0.029	0.000
119	2523.02	-	-	48.770	0.000	0.031	0.000
120	2517.08	-	-	48.190	0.000	0.032	0.000
121	2511.42	-	-	46.660	0.000	0.031	0.000
122	2505.77	-	-	45.980	0.000	0.030	0.000
123	2500.49	-	-	44.450	0.000	0.030	0.000
124	2495.41	-	-	43.660	0.000	0.027	0.000
125	2490.38	-	-	42.410	0.000	0.028	0.000
126	2485.80	-	-	41.360	0.000	0.027	0.000
127	2480.80	-	-	40.450	0.000	0.028	0.000
128	2476.22	-	-	39.520	0.000	0.028	0.000
129	2471.67	-	-	38.220	0.000	0.027	0.000
130	2467.23	-	-	37.580	0.000	0.026	0.000
131	2462.93	-	-	36.370	0.000	0.026	0.000
132	2458.74	-	-	35.080	0.000	0.026	0.000
133	2455.13	-	-	33.820	0.000	0.025	0.000
134	2451.64	-	-	33.580	0.000	0.035	0.000
135	2448.19	-	-	31.900	0.000	0.037	0.000
136	2444.93	-	-	31.140	0.000	0.038	0.000
137	2441.82	-	-	30.100	0.000	0.039	0.000
138	2438.79	-	-	29.140	0.000	0.038	0.000
139	2435.68	-	-	28.260	0.000	0.027	0.000
140	2432.78	-	-	27.410	0.000	0.032	0.000
141	2430.09	-	-	26.340	0.000	0.031	0.000
142	2427.40	-	-	25.720	0.000	0.027	0.000
143	2424.74	-	-	24.920	0.000	0.030	0.000
144	2422.21	-	-	24.300	0.000	0.028	0.000
145	2419.79	-	-	23.340	0.000	0.029	0.000
146	2417.43	-	-	22.720	0.000	0.026	0.000
147	2415.22	-	-	22.150	0.000	0.027	0.000
148	2413.12	-	-	21.150	0.000	0.024	0.000
149	2411.04	-	-	20.300	0.000	0.025	0.000
150	2408.98	-	-	19.620	0.000	0.025	0.000
151	2406.94	-	-	18.720	0.000	0.026	0.000
152	2404.98	-	-	18.220	0.000	0.026	0.000
153	2403.06	-	-	17.480	0.000	0.025	0.000
154	2401.17	-	-	16.680	0.000	0.026	0.000

Continued on next page

Table 8 – continued from previous page - pr199zb

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
155	2399.33	-	-	16.220	0.000	0.024	0.000
156	2397.55	-	-	15.350	0.000	0.024	0.000
157	2396.03	-	-	14.550	0.000	0.024	0.000
158	2394.62	-	-	13.910	0.000	0.022	0.000
159	2393.33	-	-	13.180	0.000	0.024	0.000
160	2392.07	-	-	12.600	0.000	0.019	0.000
161	2390.83	-	-	11.880	0.000	0.021	0.000
162	2389.60	-	-	11.250	0.000	0.025	0.000
163	2388.39	-	-	10.530	0.000	0.020	0.000
164	2387.19	-	-	9.860	0.000	0.020	0.000
165	2386.02	-	-	9.170	0.000	0.019	0.000
166	2384.94	-	-	8.560	0.000	0.021	0.000
167	2383.88	-	-	7.850	0.000	0.024	0.000
168	2382.88	-	-	7.350	0.000	0.019	0.000
169	2381.90	-	-	6.670	0.000	0.023	0.000
170	2380.97	-	-	6.100	0.000	0.018	0.000
171	2380.06	-	-	5.540	0.000	0.019	0.000
172	2379.16	-	-	4.980	0.000	0.017	0.000
173	2378.26	-	-	4.510	0.000	0.018	0.000
174	2377.41	-	-	4.020	0.000	0.017	0.000
175	2376.67	-	-	3.530	0.000	0.016	0.000
176	2375.96	-	-	3.120	0.000	0.015	0.000
177	2375.28	-	-	2.690	0.000	0.016	0.000
178	2374.61	-	-	2.330	0.000	0.015	0.000
179	2373.98	-	-	2.020	0.000	0.015	0.000
180	2373.42	-	-	1.770	0.000	0.016	0.000
181	2372.87	-	-	1.450	0.000	0.015	0.000
182	2372.40	-	-	1.220	0.000	0.014	0.000
183	2371.95	-	-	1.030	0.000	0.013	0.000
184	2371.50	-	-	0.870	0.000	0.012	0.000
185	2371.05	-	-	0.710	0.000	0.012	0.000
186	2370.61	-	-	0.570	0.000	0.016	0.000
187	2370.18	-	-	0.470	0.000	0.015	0.000
188	2369.74	-	-	0.380	0.000	0.013	0.000
189	2369.32	-	-	0.290	0.000	0.013	0.000
190	2368.95	-	-	0.220	0.000	0.012	0.000
191	2368.61	-	-	0.180	0.000	0.011	0.000
192	2368.35	-	-	0.150	0.000	0.006	0.000
193	2368.11	-	-	0.130	0.000	0.004	0.000
194	2367.91	-	-	0.110	0.000	0.004	0.000
195	2367.81	-	-	0.100	0.000	0.003	0.000
196	2367.81	-	-	0.090	0.000	0.001	0.000
197	2367.81	-	-	0.090	0.000	0.001	0.000
198	2367.81	-	-	0.090	0.000	0.001	0.000
199	2367.81	-	-	0.090	0.000	0.001	0.000
Total		**9918.35**	**8248.63**	**5495.66**	**0.04**	**5.447**	**0.000**

Table 9: ENS optimization - pr262zb.

m	best ENS	Time (sec)					
		ILP-GALIAS	ILP-IFLOWS	DP-TS	DP-N2M2	ILP-CUTS	DP-PC
0	105636.00	0.007	0.001	0.000	0.000	0.001	0.000
1	78817.40	0.019	0.014	0.000	0.000	0.016	0.000
2	57773.40	0.189	0.006	0.010	0.002	0.007	0.000
3	37227.00	0.123	0.006	0.010	0.001	0.007	0.001
4	29686.60	0.205	0.017	0.020	0.001	0.009	0.000
5	25315.20	8.540	0.019	0.080	0.000	0.015	0.000
6	23255.50	76.210	0.027	0.210	0.000	0.023	0.000
7	21252.90	489.241	0.026	0.520	0.000	0.020	0.000
8	19691.10	2783.666	0.034	1.130	0.000	0.023	0.001
9	18270.30	-	0.041	2.200	0.000	0.027	0.001
10	17286.40	-	0.062	3.990	0.000	0.025	0.000
11	16339.10	-	0.094	6.570	0.000	0.029	0.000
12	15525.20	-	0.129	10.390	0.001	0.031	0.000
13	14720.30	-	0.327	15.600	0.001	0.033	0.000
14	13936.20	-	0.336	22.490	0.001	0.038	0.000
15	13299.60	-	0.345	31.790	0.001	0.030	0.000
16	12718.80	-	0.533	44.670	0.001	0.033	0.000
17	12227.90	-	0.712	57.830	0.001	0.040	0.000
18	11749.80	-	0.616	75.080	0.001	0.035	0.000
19	11375.60	-	1.055	95.880	0.001	0.040	0.000
20	11010.80	-	1.291	120.660	0.000	0.036	0.000
21	10687.00	-	1.456	147.660	0.000	0.033	0.000
22	10386.90	-	1.856	181.620	0.000	0.036	0.000
23	10099.30	-	2.925	213.810	0.001	0.032	0.001
24	9872.61	-	5.908	257.980	0.000	0.036	0.000
25	9663.87	-	8.030	305.340	0.001	0.033	0.001
26	9469.67	-	12.572	354.210	0.000	0.042	0.000
27	9280.02	-	19.070	420.580	0.000	0.035	0.000
28	9094.02	-	22.593	492.220	0.000	0.034	0.000
29	8914.45	-	26.046	545.120	0.000	0.034	0.000
30	8737.34	-	29.360	622.880	0.000	0.033	0.000
31	8561.78	-	37.572	703.710	0.000	0.031	0.000
32	8394.09	-	56.788	796.840	0.000	0.032	0.000
33	8234.66	-	75.784	891.760	0.000	0.032	0.000
34	8086.91	-	103.930	-	0.000	0.033	0.000
35	7962.80	-	161.121	-	0.000	0.035	0.000
36	7846.28	-	186.751	-	0.000	0.034	0.000
37	7729.77	-	208.349	-	0.000	0.031	0.000
38	7614.39	-	265.843	-	0.000	0.036	0.000
39	7499.50	-	304.892	-	0.000	0.033	0.000
40	7394.01	-	342.537	-	0.000	0.035	0.000
41	7288.62	-	421.873	-	0.000	0.034	0.000
42	7183.23	-	441.878	-	0.000	0.032	0.000
43	7079.47	-	477.708	-	0.000	0.032	0.000
44	6975.99	-	485.787	-	0.000	0.032	0.000
45	6877.02	-	571.075	-	0.000	0.032	0.000
46	6778.74	-	606.382	-	0.000	0.037	0.000
47	6688.03	-	692.006	-	0.000	0.036	0.000
48	6601.72	-	1033.717	-	0.000	0.033	0.000
49	6515.90	-	1386.689	-	0.000	0.034	0.000
50	6432.62	-	-	-	0.000	0.036	0.000

Continued on next page

Table 9 – continued from previous page - pr262zb

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
51	6351.70	-	-	-	0.000	0.032	0.000
52	6274.74	-	-	-	0.000	0.032	0.000
53	6198.56	-	-	-	0.000	0.038	0.000
54	6125.33	-	-	-	0.000	0.033	0.000
55	6052.54	-	-	-	0.000	0.038	0.000
56	5980.84	-	-	-	0.000	0.034	0.000
57	5910.44	-	-	-	0.000	0.038	0.000
58	5840.25	-	-	-	0.000	0.033	0.000
59	5771.76	-	-	-	0.000	0.037	0.000
60	5703.44	-	-	-	0.000	0.033	0.000
61	5638.62	-	-	-	0.000	0.037	0.000
62	5574.08	-	-	-	0.000	0.035	0.000
63	5518.13	-	-	-	0.000	0.035	0.000
64	5466.77	-	-	-	0.000	0.039	0.000
65	5418.07	-	-	-	0.000	0.039	0.000
66	5371.25	-	-	-	0.000	0.039	0.000
67	5324.71	-	-	-	0.000	0.038	0.000
68	5278.22	-	-	-	0.000	0.036	0.000
69	5232.06	-	-	-	0.000	0.037	0.000
70	5185.52	-	-	-	0.000	0.036	0.000
71	5139.74	-	-	-	0.000	0.038	0.000
72	5094.83	-	-	-	0.000	0.040	0.000
73	5054.17	-	-	-	0.000	0.037	0.000
74	5016.36	-	-	-	0.000	0.037	0.000
75	4978.91	-	-	-	0.000	0.034	0.000
76	4941.94	-	-	-	0.000	0.030	0.000
77	4906.47	-	-	-	0.000	0.034	0.000
78	4874.69	-	-	-	0.000	0.043	0.000
79	4840.51	-	-	-	0.000	0.035	0.000
80	4808.79	-	-	-	0.000	0.038	0.000
81	4777.47	-	-	-	0.000	0.037	0.000
82	4746.99	-	-	-	0.000	0.036	0.000
83	4716.25	-	-	-	0.000	0.038	0.000
84	4685.76	-	-	-	0.000	0.038	0.000
85	4655.37	-	-	-	0.000	0.038	0.000
86	4624.98	-	-	-	0.000	0.042	0.000
87	4595.33	-	-	-	0.000	0.042	0.000
88	4565.80	-	-	-	0.000	0.040	0.000
89	4538.79	-	-	-	0.000	0.041	0.000
90	4512.59	-	-	-	0.000	0.038	0.000
91	4486.66	-	-	-	0.000	0.037	0.000
92	4460.89	-	-	-	0.000	0.036	0.000
93	4435.87	-	-	-	0.000	0.040	0.000
94	4411.78	-	-	-	0.000	0.036	0.000
95	4388.05	-	-	-	0.000	0.036	0.000
96	4364.88	-	-	-	0.000	0.038	0.000
97	4342.31	-	-	-	0.000	0.036	0.000
98	4319.76	-	-	-	0.000	0.038	0.000
99	4297.60	-	-	-	0.000	0.039	0.000
100	4276.05	-	-	-	0.000	0.039	0.000
101	4255.35	-	-	-	0.000	0.037	0.000
102	4234.72	-	-	-	0.000	0.036	0.000

Continued on next page

Table 9 – continued from previous page - pr262zb

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
103	4215.26	-	-	-	0.000	0.040	0.000
104	4196.23	-	-	-	0.000	0.036	0.000
105	4177.27	-	-	-	0.000	0.038	0.000
106	4158.57	-	-	-	0.000	0.039	0.000
107	4140.05	-	-	-	0.000	0.038	0.000
108	4121.68	-	-	-	0.000	0.038	0.000
109	4103.38	-	-	-	0.000	0.042	0.000
110	4086.45	-	-	-	0.000	0.036	0.000
111	4069.62	-	-	-	0.000	0.039	0.000
112	4052.90	-	-	-	0.000	0.041	0.000
113	4037.09	-	-	-	0.000	0.041	0.000
114	4021.94	-	-	-	0.000	0.039	0.000
115	4007.87	-	-	-	0.000	0.041	0.000
116	3992.97	-	-	-	0.000	0.041	0.000
117	3978.89	-	-	-	0.000	0.038	0.000
118	3965.03	-	-	-	0.000	0.039	0.000
119	3951.29	-	-	-	0.000	0.041	0.000
120	3937.66	-	-	-	0.000	0.040	0.000
121	3924.05	-	-	-	0.000	0.039	0.000
122	3910.77	-	-	-	0.000	0.038	0.000
123	3897.49	-	-	-	0.000	0.043	0.000
124	3884.34	-	-	-	0.000	0.038	0.000
125	3871.62	-	-	-	0.000	0.045	0.000
126	3859.38	-	-	-	0.000	0.042	0.000
127	3847.18	-	-	-	0.000	0.038	0.000
128	3835.03	-	-	-	0.000	0.043	0.000
129	3823.15	-	-	-	0.000	0.043	0.000
130	3811.38	-	-	-	0.000	0.041	0.000
131	3799.68	-	-	-	0.000	0.039	0.000
132	3788.26	-	-	-	0.000	0.039	0.000
133	3776.87	-	-	-	0.000	0.041	0.000
134	3765.48	-	-	-	0.000	0.041	0.000
135	3754.12	-	-	-	0.000	0.048	0.000
136	3743.52	-	-	-	0.000	0.040	0.000
137	3733.43	-	-	-	0.000	0.038	0.000
138	3724.18	-	-	-	0.000	0.040	0.000
139	3715.03	-	-	-	0.000	0.038	0.000
140	3706.62	-	-	-	0.000	0.041	0.000
141	3698.36	-	-	-	0.000	0.044	0.000
142	3690.38	-	-	-	0.000	0.042	0.000
143	3682.53	-	-	-	0.000	0.042	0.000
144	3674.69	-	-	-	0.000	0.038	0.000
145	3666.83	-	-	-	0.000	0.039	0.000
146	3659.07	-	-	-	0.000	0.042	0.000
147	3651.44	-	-	-	0.000	0.039	0.000
148	3644.11	-	-	-	0.000	0.038	0.000
149	3637.03	-	-	-	0.000	0.038	0.000
150	3629.96	-	-	-	0.000	0.034	0.000
151	3623.30	-	-	-	0.000	0.034	0.000
152	3616.85	-	-	-	0.000	0.033	0.000
153	3610.55	-	-	-	0.000	0.034	0.000
154	3604.28	-	-	-	0.000	0.042	0.000

Continued on next page

Table 9 – continued from previous page - pr262zb

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
155	3598.12	-	-	-	0.000	0.035	0.000
156	3592.00	-	-	-	0.000	0.036	0.000
157	3585.98	-	-	-	0.000	0.035	0.000
158	3579.96	-	-	-	0.000	0.032	0.000
159	3574.02	-	-	-	0.000	0.038	0.000
160	3568.25	-	-	-	0.000	0.038	0.000
161	3562.59	-	-	-	0.000	0.042	0.000
162	3556.94	-	-	-	0.000	0.039	0.000
163	3551.42	-	-	-	0.000	0.037	0.000
164	3546.14	-	-	-	0.000	0.036	0.000
165	3540.95	-	-	-	0.000	0.036	0.000
166	3535.88	-	-	-	0.000	0.036	0.000
167	3530.85	-	-	-	0.000	0.034	0.000
168	3526.27	-	-	-	0.000	0.036	0.000
169	3521.27	-	-	-	0.000	0.030	0.000
170	3516.69	-	-	-	0.000	0.030	0.000
171	3512.14	-	-	-	0.000	0.035	0.000
172	3507.69	-	-	-	0.000	0.035	0.000
173	3503.26	-	-	-	0.000	0.034	0.000
174	3498.87	-	-	-	0.000	0.035	0.000
175	3494.58	-	-	-	0.000	0.034	0.000
176	3490.38	-	-	-	0.000	0.042	0.000
177	3486.41	-	-	-	0.000	0.031	0.000
178	3482.81	-	-	-	0.000	0.029	0.000
179	3479.31	-	-	-	0.000	0.030	0.000
180	3475.86	-	-	-	0.000	0.028	0.000
181	3472.52	-	-	-	0.000	0.032	0.000
182	3469.26	-	-	-	0.000	0.029	0.000
183	3466.05	-	-	-	0.000	0.032	0.000
184	3462.94	-	-	-	0.000	0.032	0.000
185	3459.90	-	-	-	0.000	0.031	0.000
186	3456.80	-	-	-	0.000	0.048	0.000
187	3453.90	-	-	-	0.000	0.035	0.000
188	3451.09	-	-	-	0.000	0.034	0.000
189	3448.39	-	-	-	0.000	0.031	0.000
190	3445.71	-	-	-	0.000	0.036	0.000
191	3443.04	-	-	-	0.000	0.031	0.000
192	3440.51	-	-	-	0.000	0.043	0.000
193	3438.04	-	-	-	0.000	0.044	0.000
194	3435.62	-	-	-	0.000	0.033	0.000
195	3433.26	-	-	-	0.000	0.040	0.000
196	3431.06	-	-	-	0.000	0.039	0.000
197	3428.96	-	-	-	0.000	0.031	0.000
198	3426.87	-	-	-	0.000	0.032	0.000
199	3424.81	-	-	-	0.000	0.036	0.000
200	3422.75	-	-	-	0.000	0.036	0.000
201	3420.70	-	-	-	0.000	0.032	0.000
202	3418.66	-	-	-	0.000	0.033	0.000
203	3416.69	-	-	-	0.000	0.031	0.000
204	3414.78	-	-	-	0.000	0.034	0.000
205	3412.89	-	-	-	0.000	0.034	0.000
206	3411.05	-	-	-	0.000	0.030	0.000

Continued on next page

Table 9 – continued from previous page - pr262zb

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
207	3409.27	-	-	-	0.000	0.028	0.000
208	3407.66	-	-	-	0.000	0.037	0.000
209	3406.14	-	-	-	0.000	0.034	0.000
210	3404.73	-	-	-	0.000	0.029	0.000
211	3403.37	-	-	-	0.000	0.028	0.000
212	3402.08	-	-	-	0.000	0.027	0.000
213	3400.80	-	-	-	0.000	0.028	0.000
214	3399.54	-	-	-	0.000	0.030	0.000
215	3398.30	-	-	-	0.000	0.032	0.000
216	3397.06	-	-	-	0.000	0.030	0.000
217	3395.83	-	-	-	0.000	0.026	0.000
218	3394.62	-	-	-	0.000	0.028	0.000
219	3393.43	-	-	-	0.000	0.025	0.000
220	3392.25	-	-	-	0.000	0.034	0.000
221	3391.12	-	-	-	0.000	0.023	0.000
222	3390.03	-	-	-	0.000	0.026	0.000
223	3388.97	-	-	-	0.000	0.027	0.000
224	3387.91	-	-	-	0.000	0.028	0.000
225	3386.91	-	-	-	0.000	0.025	0.000
226	3385.93	-	-	-	0.000	0.025	0.000
227	3385.00	-	-	-	0.000	0.024	0.000
228	3384.09	-	-	-	0.000	0.030	0.000
229	3383.18	-	-	-	0.000	0.024	0.000
230	3382.29	-	-	-	0.000	0.023	0.000
231	3381.44	-	-	-	0.000	0.026	0.000
232	3380.66	-	-	-	0.000	0.022	0.000
233	3379.91	-	-	-	0.000	0.025	0.000
234	3379.20	-	-	-	0.000	0.021	0.000
235	3378.53	-	-	-	0.000	0.020	0.000
236	3377.86	-	-	-	0.000	0.027	0.000
237	3377.23	-	-	-	0.000	0.019	0.000
238	3376.64	-	-	-	0.000	0.026	0.000
239	3376.08	-	-	-	0.000	0.019	0.000
240	3375.53	-	-	-	0.000	0.019	0.000
241	3375.06	-	-	-	0.000	0.019	0.000
242	3374.59	-	-	-	0.000	0.024	0.000
243	3374.14	-	-	-	0.000	0.015	0.000
244	3373.70	-	-	-	0.000	0.015	0.000
245	3373.25	-	-	-	0.000	0.015	0.000
246	3372.80	-	-	-	0.000	0.013	0.000
247	3372.37	-	-	-	0.000	0.017	0.000
248	3371.94	-	-	-	0.000	0.010	0.000
249	3371.52	-	-	-	0.000	0.012	0.000
250	3371.15	-	-	-	0.000	0.013	0.000
251	3370.81	-	-	-	0.000	0.010	0.000
252	3370.55	-	-	-	0.000	0.011	0.000
253	3370.29	-	-	-	0.000	0.009	0.000
254	3370.05	-	-	-	0.000	0.006	0.000
255	3369.85	-	-	-	0.000	0.005	0.000
256	3369.75	-	-	-	0.000	0.004	0.000
257	3369.75	-	-	-	0.000	0.001	0.000
258	3369.75	-	-	-	0.000	0.001	0.000

Continued on next page

Table 9 – continued from previous page - pr262zb

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
259	3369.75	-	-	-	0.000	0.001	0.000
260	3369.75	-	-	-	0.000	0.001	0.000
261	3369.75	-	-	-	0.000	0.001	0.000
262	3369.75	-	-	-	0.000	0.001	0.000
Total		**10558.20**	**7996.19**	**7414.00**	**0.07**	**8.421**	**0.005**

Table 10: ENS optimization - IEEE8500 - n384.

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
0	3388.78	0.090	0.004	0.000	0.000	0.001	0.000
1	2565.67	0.228	0.029	0.010	0.000	0.028	0.000
2	2128.39	1.922	0.031	0.010	0.003	0.013	0.003
3	1768.60	5.723	0.031	0.030	0.002	0.012	0.003
4	1562.15	56.356	0.063	0.050	0.003	0.027	0.003
5	1389.79	483.837	0.097	0.060	0.002	0.039	0.003
6	1287.20	-	0.441	0.070	0.002	0.059	0.003
7	1229.08	-	5.130	0.090	0.003	0.099	0.003
8	1176.14	-	5.211	0.100	0.003	0.260	0.003
9	1126.45	-	7.624	0.110	0.004	0.119	0.004
10	1076.81	-	7.431	0.130	0.003	0.086	0.004
11	1032.10	-	6.167	0.140	0.002	0.082	0.002
12	991.69	-	5.842	0.160	0.002	0.076	0.002
13	954.96	-	8.114	0.160	0.002	0.113	0.002
14	920.76	-	9.739	0.180	0.002	0.071	0.002
15	888.58	-	10.452	0.200	0.002	0.088	0.002
16	858.97	-	14.171	0.210	0.002	0.110	0.002
17	831.86	-	17.210	0.230	0.002	0.107	0.002
18	806.72	-	26.896	0.240	0.002	0.072	0.002
19	781.91	-	56.872	0.260	0.003	0.068	0.002
20	758.12	-	81.789	0.280	0.003	0.068	0.002
21	738.65	-	156.244	0.300	0.003	0.073	0.002
22	723.38	-	438.331	0.300	0.003	0.100	0.002
23	708.43	-	1471.175	0.310	0.003	0.125	0.002
24	693.59	-	2976.774	0.340	0.003	0.995	0.002
25	678.97	-	-	0.360	0.003	0.490	0.002
26	665.98	-	-	0.380	0.005	0.573	0.005
27	654.17	-	-	0.380	0.005	0.488	0.005
28	642.46	-	-	0.400	0.003	0.902	0.002
29	633.34	-	-	0.420	0.003	0.492	0.002
30	624.22	-	-	0.420	0.003	0.465	0.002
31	615.31	-	-	0.430	0.006	0.477	0.002
32	608.33	-	-	0.440	0.006	0.519	0.002
33	602.20	-	-	0.450	0.005	0.501	0.002
34	596.43	-	-	0.460	0.004	0.538	0.002
35	591.42	-	-	0.460	0.004	0.539	0.002
36	586.78	-	-	0.480	0.004	0.488	0.002
37	582.50	-	-	0.470	0.004	0.483	0.002
38	578.28	-	-	0.490	0.004	0.471	0.002

Continued on next page

Table 10 – continued from previous page - IEEE8500 - n384

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
39	574.10	-	-	0.480	0.004	0.436	0.002
40	570.05	-	-	0.490	0.004	0.438	0.002
41	566.04	-	-	0.500	0.004	0.453	0.002
42	562.04	-	-	0.500	0.004	0.542	0.002
43	558.08	-	-	0.510	0.004	0.519	0.002
44	554.17	-	-	0.510	0.004	0.458	0.002
45	550.39	-	-	0.520	0.004	0.536	0.002
46	546.76	-	-	0.530	0.005	0.501	0.002
47	543.51	-	-	0.540	0.005	0.509	0.002
48	540.35	-	-	0.560	0.005	0.552	0.002
49	537.21	-	-	0.540	0.005	0.516	0.002
50	534.32	-	-	0.580	0.005	0.543	0.002
51	531.63	-	-	0.570	0.005	0.554	0.002
52	528.96	-	-	0.580	0.005	0.508	0.002
53	526.49	-	-	0.580	0.005	0.578	0.002
54	524.12	-	-	0.590	0.005	0.564	0.002
55	521.84	-	-	0.600	0.005	0.618	0.002
56	519.79	-	-	0.610	0.005	0.511	0.002
57	517.77	-	-	0.620	0.005	0.556	0.002
58	515.79	-	-	0.630	0.005	0.576	0.002
59	513.90	-	-	0.650	0.005	0.514	0.002
60	512.03	-	-	0.630	0.005	0.523	0.002
61	510.18	-	-	0.650	0.005	0.514	0.002
62	508.59	-	-	0.640	0.005	0.572	0.002
63	507.02	-	-	0.640	0.005	0.596	0.002
64	505.46	-	-	0.660	0.005	0.587	0.002
65	503.98	-	-	0.660	0.005	0.628	0.002
66	502.56	-	-	0.660	0.005	0.519	0.002
67	501.23	-	-	0.660	0.005	0.511	0.002
68	499.94	-	-	0.670	0.005	0.552	0.002
69	498.69	-	-	0.680	0.005	0.555	0.002
70	497.53	-	-	0.670	0.005	0.502	0.002
71	496.42	-	-	0.660	0.005	0.521	0.002
72	495.36	-	-	0.670	0.005	0.524	0.001
73	494.38	-	-	0.670	0.005	0.510	0.002
74	493.46	-	-	0.670	0.005	0.531	0.002
75	492.55	-	-	0.700	0.005	0.558	0.002
76	491.66	-	-	0.660	0.005	0.516	0.001
77	490.87	-	-	0.680	0.005	0.519	0.002
78	490.09	-	-	0.680	0.006	0.532	0.002
79	489.34	-	-	0.670	0.006	0.491	0.002
80	488.60	-	-	0.670	0.006	0.540	0.002
81	487.88	-	-	0.660	0.006	0.515	0.002
82	487.15	-	-	0.660	0.006	0.554	0.002
83	486.43	-	-	0.680	0.006	0.481	0.002
84	485.73	-	-	0.670	0.006	0.525	0.002
85	485.02	-	-	0.650	0.016	0.552	0.011
86	484.32	-	-	0.640	0.008	0.564	0.002
87	483.65	-	-	0.650	0.007	0.546	0.002
88	482.99	-	-	0.650	0.017	0.513	0.012
89	482.32	-	-	0.650	0.008	0.533	0.002
90	481.66	-	-	0.650	0.007	0.507	0.002

Continued on next page

Table 10 – continued from previous page - IEEE8500 - n384

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
91	481.02	-	-	0.650	0.007	0.544	0.002
92	480.43	-	-	0.640	0.007	0.534	0.002
93	479.84	-	-	0.650	0.007	0.514	0.002
94	479.26	-	-	0.660	0.007	0.604	0.002
95	478.68	-	-	0.690	0.007	0.535	0.002
96	478.11	-	-	0.650	0.007	0.535	0.002
97	477.54	-	-	0.630	0.007	0.559	0.001
98	476.98	-	-	0.640	0.007	0.550	0.001
99	476.43	-	-	0.630	0.007	0.513	0.001
100	475.89	-	-	0.650	0.007	0.516	0.001
101	475.37	-	-	0.640	0.006	0.543	0.001
102	474.85	-	-	0.640	0.006	0.547	0.001
103	474.33	-	-	0.630	0.007	0.532	0.001
104	473.81	-	-	0.630	0.007	0.597	0.001
105	473.31	-	-	0.620	0.007	0.540	0.001
106	472.81	-	-	0.600	0.007	0.477	0.001
107	472.32	-	-	0.590	0.007	0.511	0.001
108	471.85	-	-	0.580	0.007	0.587	0.001
109	471.38	-	-	0.590	0.007	0.501	0.001
110	470.91	-	-	0.580	0.008	0.489	0.001
111	470.44	-	-	0.550	0.010	0.515	0.001
112	469.97	-	-	0.540	0.009	0.501	0.001
113	469.51	-	-	0.530	0.008	0.556	0.001
114	469.05	-	-	0.540	0.008	0.542	0.001
115	468.59	-	-	0.490	0.008	0.510	0.001
116	468.15	-	-	0.470	0.008	0.569	0.001
117	467.76	-	-	0.480	0.008	0.521	0.001
118	467.39	-	-	0.440	0.008	0.500	0.001
119	467.02	-	-	0.430	0.008	0.514	0.001
120	466.67	-	-	0.400	0.009	0.565	0.002
121	466.33	-	-	0.380	0.009	0.499	0.002
122	465.99	-	-	0.360	0.009	0.519	0.002
123	465.65	-	-	0.340	0.009	0.486	0.002
124	465.32	-	-	0.340	0.009	0.452	0.002
125	465.00	-	-	0.330	0.009	0.541	0.002
126	464.68	-	-	0.320	0.010	0.525	0.002
127	464.37	-	-	0.300	0.009	0.478	0.002
128	464.05	-	-	0.310	0.010	0.540	0.001
129	463.74	-	-	0.280	0.010	0.502	0.002
130	463.44	-	-	0.300	0.010	0.547	0.002
131	463.15	-	-	0.280	0.010	0.536	0.002
132	462.86	-	-	0.300	0.010	0.526	0.001
133	462.58	-	-	0.270	0.010	0.579	0.001
134	462.29	-	-	0.270	0.011	0.502	0.002
135	462.02	-	-	0.270	0.011	0.562	0.002
136	461.75	-	-	0.260	0.011	0.516	0.002
137	461.50	-	-	0.270	0.011	0.489	0.002
138	461.26	-	-	0.260	0.011	0.474	0.002
139	461.02	-	-	0.260	0.011	0.560	0.002
140	460.78	-	-	0.270	0.011	0.519	0.002
141	460.54	-	-	0.270	0.011	0.519	0.001
142	460.31	-	-	0.260	0.010	0.560	0.001

Continued on next page

Table 10 – continued from previous page - IEEE8500 - n384

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
143	460.08	-	-	0.290	0.010	0.466	0.001
144	459.85	-	-	0.280	0.010	0.502	0.001
145	459.63	-	-	0.260	0.009	0.503	0.001
146	459.42	-	-	0.270	0.010	0.626	0.001
147	459.20	-	-	0.280	0.010	0.554	0.001
148	458.99	-	-	0.270	0.010	0.514	0.001
149	458.79	-	-	0.260	0.010	0.497	0.001
150	458.58	-	-	0.270	0.010	0.697	0.001
151	458.38	-	-	0.270	0.009	0.570	0.001
152	458.18	-	-	0.260	0.009	0.542	0.001
153	457.98	-	-	0.260	0.009	0.554	0.001
154	457.79	-	-	0.280	0.009	0.551	0.001
155	457.61	-	-	0.250	0.009	0.546	0.001
156	457.42	-	-	0.270	0.009	0.590	0.001
157	457.24	-	-	0.260	0.008	0.517	0.001
158	457.06	-	-	0.250	0.008	0.523	0.001
159	456.90	-	-	0.260	0.008	0.494	0.001
160	456.73	-	-	0.250	0.008	0.597	0.001
161	456.57	-	-	0.260	0.008	0.577	0.001
162	456.40	-	-	0.240	0.009	0.622	0.001
163	456.24	-	-	0.260	0.009	0.568	0.001
164	456.08	-	-	0.260	0.009	0.547	0.001
165	455.93	-	-	0.240	0.009	0.566	0.001
166	455.78	-	-	0.240	0.009	0.545	0.001
167	455.63	-	-	0.240	0.009	0.546	0.001
168	455.50	-	-	0.250	0.009	0.586	0.001
169	455.36	-	-	0.250	0.009	0.532	0.001
170	455.23	-	-	0.250	0.011	0.504	0.001
171	455.09	-	-	0.250	0.010	0.522	0.001
172	454.96	-	-	0.260	0.008	0.665	0.001
173	454.83	-	-	0.240	0.008	0.483	0.001
174	454.70	-	-	0.240	0.007	0.487	0.001
175	454.58	-	-	0.240	0.007	0.490	0.001
176	454.45	-	-	0.240	0.007	0.504	0.001
177	454.33	-	-	0.240	0.007	0.474	0.001
178	454.22	-	-	0.250	0.006	0.535	0.001
179	454.12	-	-	0.250	0.006	0.531	0.001
180	454.02	-	-	0.240	0.006	0.595	0.001
181	453.92	-	-	0.240	0.006	0.576	0.001
182	453.82	-	-	0.240	0.006	0.483	0.001
183	453.72	-	-	0.230	0.006	0.546	0.001
184	453.62	-	-	0.240	0.006	0.533	0.001
185	453.53	-	-	0.230	0.006	0.481	0.001
186	453.44	-	-	0.230	0.006	0.489	0.001
187	453.36	-	-	0.240	0.006	0.455	0.001
188	453.27	-	-	0.240	0.006	0.512	0.001
189	453.19	-	-	0.240	0.005	0.528	0.000
190	453.11	-	-	0.230	0.005	0.469	0.000
191	453.03	-	-	0.250	0.005	0.464	0.000
192	452.95	-	-	0.230	0.005	0.466	0.000
193	452.88	-	-	0.230	0.005	0.513	0.000
194	452.80	-	-	0.240	0.005	0.446	0.000

Continued on next page

Table 10 – continued from previous page - IEEE8500 - n384

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
195	452.73	-	-	0.230	0.005	0.517	0.000
196	452.65	-	-	0.230	0.005	0.444	0.000
197	452.58	-	-	0.230	0.004	0.468	0.000
198	452.50	-	-	0.240	0.004	0.454	0.000
199	452.43	-	-	0.230	0.004	0.446	0.000
200	452.36	-	-	0.230	0.004	0.444	0.000
201	452.29	-	-	0.230	0.004	0.539	0.000
202	452.22	-	-	0.230	0.003	0.415	0.000
203	452.15	-	-	0.240	0.004	0.461	0.000
204	452.08	-	-	0.220	0.004	0.463	0.000
205	452.01	-	-	0.230	0.004	0.451	0.000
206	451.94	-	-	0.230	0.004	0.468	0.000
207	451.87	-	-	0.230	0.004	0.448	0.000
208	451.80	-	-	0.230	0.004	0.472	0.000
209	451.74	-	-	0.230	0.004	0.458	0.000
210	451.67	-	-	0.240	0.004	0.465	0.000
211	451.61	-	-	0.240	0.004	0.456	0.000
212	451.54	-	-	0.240	0.004	0.465	0.000
213	451.48	-	-	0.220	0.004	0.466	0.000
214	451.41	-	-	0.240	0.003	0.457	0.000
215	451.35	-	-	0.240	0.003	0.418	0.000
216	451.29	-	-	0.240	0.003	0.445	0.000
217	451.23	-	-	0.240	0.003	0.433	0.000
218	451.16	-	-	0.230	0.003	0.439	0.000
219	451.11	-	-	0.250	0.003	0.456	0.000
220	451.05	-	-	0.230	0.003	0.426	0.000
221	450.99	-	-	0.240	0.002	0.487	0.000
222	450.93	-	-	0.230	0.002	0.435	0.000
223	450.88	-	-	0.240	0.002	0.429	0.000
224	450.82	-	-	0.240	0.002	0.496	0.000
225	450.77	-	-	0.240	0.002	0.436	0.000
226	450.71	-	-	0.250	0.002	0.466	0.000
227	450.66	-	-	0.240	0.002	0.436	0.000
228	450.61	-	-	0.250	0.002	0.405	0.000
229	450.56	-	-	0.240	0.001	0.124	0.000
230	450.51	-	-	0.240	0.001	0.128	0.000
231	450.46	-	-	0.240	0.002	0.121	0.000
232	450.41	-	-	0.270	0.001	0.107	0.000
233	450.37	-	-	0.240	0.002	0.172	0.000
234	450.32	-	-	0.250	0.002	0.195	0.000
235	450.27	-	-	0.270	0.001	0.213	0.000
236	450.22	-	-	0.250	0.001	0.224	0.000
237	450.17	-	-	0.250	0.001	0.145	0.000
238	450.13	-	-	0.240	0.001	0.317	0.000
239	450.08	-	-	0.250	0.001	0.296	0.000
240	450.03	-	-	0.260	0.001	0.281	0.000
241	449.99	-	-	0.250	0.001	0.249	0.000
242	449.94	-	-	0.260	0.001	0.169	0.000
243	449.90	-	-	0.250	0.001	0.307	0.000
244	449.85	-	-	0.270	0.001	0.226	0.000
245	449.81	-	-	0.260	0.001	0.227	0.000
246	449.76	-	-	0.250	0.001	0.298	0.000

Continued on next page

Table 10 – continued from previous page - IEEE8500 - n384

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
247	449.72	-	-	0.260	0.001	0.126	0.000
248	449.68	-	-	0.260	0.000	0.243	0.000
249	449.63	-	-	0.250	0.001	0.188	0.000
250	449.59	-	-	0.260	0.001	0.156	0.000
251	449.55	-	-	0.250	0.001	0.288	0.000
252	449.51	-	-	0.270	0.001	0.408	0.000
253	449.47	-	-	0.250	0.001	0.154	0.000
254	449.43	-	-	0.270	0.001	0.169	0.000
255	449.39	-	-	0.260	0.000	0.165	0.000
256	449.35	-	-	0.250	0.000	0.269	0.000
257	449.31	-	-	0.260	0.000	0.228	0.000
258	449.26	-	-	0.250	0.000	0.156	0.000
259	449.22	-	-	0.240	0.000	0.253	0.000
260	449.19	-	-	0.230	0.000	0.246	0.000
261	449.15	-	-	0.230	0.000	0.186	0.000
262	449.11	-	-	0.230	0.000	0.216	0.000
263	449.07	-	-	0.220	0.000	0.151	0.000
264	449.03	-	-	0.220	0.000	0.064	0.000
265	449.00	-	-	0.210	0.000	0.170	0.000
266	448.96	-	-	0.210	0.000	0.217	0.000
267	448.93	-	-	0.210	0.000	0.143	0.000
268	448.89	-	-	0.200	0.000	0.100	0.000
269	448.86	-	-	0.200	0.000	0.080	0.000
270	448.82	-	-	0.200	0.000	0.133	0.000
271	448.79	-	-	0.180	0.000	0.123	0.000
272	448.75	-	-	0.200	0.000	0.118	0.000
273	448.72	-	-	0.170	0.000	0.131	0.000
274	448.69	-	-	0.170	0.000	0.101	0.000
275	448.65	-	-	0.170	0.000	0.124	0.000
276	448.62	-	-	0.160	0.000	0.058	0.000
277	448.59	-	-	0.150	0.000	0.075	0.000
278	448.56	-	-	0.150	0.000	0.063	0.000
279	448.53	-	-	0.150	0.000	0.086	0.000
280	448.50	-	-	0.150	0.000	0.082	0.000
281	448.47	-	-	0.140	0.000	0.068	0.000
282	448.45	-	-	0.160	0.000	0.100	0.000
283	448.42	-	-	0.140	0.000	0.081	0.000
284	448.39	-	-	0.130	0.000	0.097	0.000
285	448.36	-	-	0.130	0.000	0.068	0.000
286	448.34	-	-	0.130	0.000	0.093	0.000
287	448.31	-	-	0.120	0.000	0.093	0.000
288	448.28	-	-	0.120	0.000	0.094	0.000
289	448.26	-	-	0.130	0.000	0.078	0.000
290	448.23	-	-	0.110	0.000	0.085	0.000
291	448.21	-	-	0.120	0.000	0.087	0.000
292	448.18	-	-	0.110	0.000	0.072	0.000
293	448.15	-	-	0.120	0.000	0.098	0.000
294	448.13	-	-	0.110	0.000	0.096	0.000
295	448.11	-	-	0.110	0.000	0.076	0.000
296	448.08	-	-	0.110	0.000	0.079	0.000
297	448.06	-	-	0.110	0.000	0.072	0.000
298	448.03	-	-	0.110	0.000	0.077	0.000

Continued on next page

Table 10 – continued from previous page - IEEE8500 - n384

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
299	448.01	-	-	0.110	0.000	0.093	0.000
300	447.99	-	-	0.100	0.000	0.075	0.000
301	447.96	-	-	0.100	0.000	0.062	0.000
302	447.94	-	-	0.100	0.000	0.075	0.000
303	447.92	-	-	0.100	0.000	0.074	0.000
304	447.90	-	-	0.100	0.000	0.085	0.000
305	447.88	-	-	0.100	0.000	0.078	0.000
306	447.86	-	-	0.090	0.000	0.086	0.000
307	447.83	-	-	0.090	0.000	0.088	0.000
308	447.81	-	-	0.090	0.000	0.065	0.000
309	447.79	-	-	0.090	0.000	0.068	0.000
310	447.77	-	-	0.090	0.000	0.069	0.000
311	447.75	-	-	0.090	0.000	0.066	0.000
312	447.74	-	-	0.080	0.000	0.064	0.000
313	447.72	-	-	0.080	0.000	0.081	0.000
314	447.70	-	-	0.080	0.000	0.052	0.000
315	447.68	-	-	0.080	0.000	0.083	0.000
316	447.66	-	-	0.080	0.000	0.064	0.000
317	447.64	-	-	0.070	0.000	0.061	0.000
318	447.62	-	-	0.070	0.000	0.051	0.000
319	447.61	-	-	0.080	0.000	0.065	0.000
320	447.59	-	-	0.070	0.000	0.057	0.000
321	447.57	-	-	0.060	0.000	0.062	0.000
322	447.56	-	-	0.070	0.000	0.058	0.000
323	447.54	-	-	0.070	0.000	0.059	0.000
324	447.52	-	-	0.060	0.000	0.061	0.000
325	447.51	-	-	0.070	0.000	0.054	0.000
326	447.49	-	-	0.060	0.000	0.064	0.000
327	447.48	-	-	0.070	0.000	0.052	0.000
328	447.46	-	-	0.060	0.000	0.058	0.000
329	447.44	-	-	0.070	0.000	0.059	0.000
330	447.43	-	-	0.060	0.000	0.067	0.000
331	447.41	-	-	0.070	0.000	0.058	0.000
332	447.40	-	-	0.060	0.000	0.059	0.000
333	447.38	-	-	0.070	0.000	0.050	0.000
334	447.37	-	-	0.070	0.000	0.053	0.000
335	447.35	-	-	0.060	0.000	0.040	0.000
336	447.34	-	-	0.050	0.000	0.047	0.000
337	447.32	-	-	0.060	0.000	0.050	0.000
338	447.31	-	-	0.050	0.000	0.043	0.000
339	447.30	-	-	0.050	0.000	0.037	0.000
340	447.28	-	-	0.050	0.000	0.044	0.000
341	447.27	-	-	0.060	0.000	0.046	0.000
342	447.25	-	-	0.050	0.000	0.043	0.000
343	447.24	-	-	0.050	0.000	0.055	0.000
344	447.23	-	-	0.050	0.000	0.055	0.000
345	447.22	-	-	0.060	0.000	0.050	0.000
346	447.20	-	-	0.040	0.000	0.046	0.000
347	447.19	-	-	0.050	0.000	0.047	0.000
348	447.18	-	-	0.050	0.000	0.036	0.000
349	447.17	-	-	0.050	0.000	0.032	0.000
350	447.16	-	-	0.060	0.000	0.036	0.000

Continued on next page

Table 10 – continued from previous page - IEEE8500 - n384

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
351	447.15	-	-	0.060	0.000	0.033	0.000
352	447.14	-	-	0.040	0.000	0.042	0.000
353	447.13	-	-	0.050	0.000	0.029	0.000
354	447.12	-	-	0.040	0.000	0.035	0.000
355	447.11	-	-	0.040	0.000	0.034	0.000
356	447.10	-	-	0.050	0.000	0.025	0.000
357	447.09	-	-	0.040	0.000	0.032	0.000
358	447.09	-	-	0.040	0.000	0.034	0.000
359	447.08	-	-	0.040	0.000	0.023	0.000
360	447.07	-	-	0.030	0.000	0.032	0.000
361	447.06	-	-	0.040	0.000	0.032	0.000
362	447.06	-	-	0.030	0.000	0.023	0.000
363	447.05	-	-	0.030	0.000	0.029	0.000
364	447.04	-	-	0.030	0.000	0.030	0.000
365	447.03	-	-	0.030	0.000	0.021	0.000
366	447.03	-	-	0.020	0.000	0.019	0.000
367	447.02	-	-	0.030	0.000	0.021	0.000
368	447.02	-	-	0.020	0.000	0.018	0.000
369	447.01	-	-	0.020	0.000	0.011	0.000
370	447.01	-	-	0.020	0.000	0.012	0.000
371	447.00	-	-	0.020	0.000	0.011	0.000
372	447.00	-	-	0.010	0.000	0.010	0.000
373	446.99	-	-	0.020	0.000	0.010	0.000
374	446.99	-	-	0.020	0.000	0.009	0.000
375	446.98	-	-	0.010	0.000	0.009	0.000
376	446.98	-	-	0.010	0.000	0.009	0.000
377	446.98	-	-	0.020	0.000	0.009	0.000
378	446.97	-	-	0.010	0.000	0.008	0.000
379	446.97	-	-	0.010	0.000	0.008	0.000
380	446.97	-	-	0.010	0.000	0.007	0.000
381	446.96	-	-	0.000	0.000	0.005	0.000
382	446.96	-	-	0.010	0.000	0.001	0.000
383	446.96	-	-	0.010	0.000	0.001	0.000
Total		**7748.20**	**8905.87**	**106.18**	**1.69**	**122.987**	**0.334**

Table 11: ENS optimization - IEEE8500 - n568.

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
0	8812.34	0.249	0.001	0.000	0.000	0.001	0.000
1	6533.08	0.798	0.050	0.010	0.000	0.056	0.000
2	4603.88	5.275	0.012	0.020	0.007	0.013	0.007
3	4022.27	3.433	0.339	0.060	0.005	0.028	0.007
4	3610.72	1508.626	0.518	0.090	0.005	0.048	0.007
5	3255.64	-	0.858	0.120	0.005	0.088	0.007
6	2942.39	-	1.231	0.130	0.004	0.082	0.005
7	2678.13	-	1.859	0.170	0.005	0.304	0.005
8	2484.79	-	2.766	0.180	0.005	1.011	0.006
9	2371.59	-	6.162	0.230	0.005	0.778	0.006

Continued on next page

Table 11 – continued from previous page - IEEE8500 - n568

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
10	2279.47	-	18.236	0.260	0.009	1.320	0.011
11	2188.66	-	31.264	0.260	0.009	1.041	0.011
12	2107.87	-	43.854	0.290	0.006	0.958	0.007
13	2029.68	-	63.339	0.310	0.006	1.093	0.007
14	1951.27	-	83.285	0.350	0.006	1.004	0.007
15	1876.39	-	90.429	0.430	0.007	1.048	0.007
16	1809.89	-	176.975	0.480	0.007	0.902	0.007
17	1743.52	-	256.767	0.510	0.007	0.829	0.007
18	1693.98	-	366.280	0.530	0.007	0.944	0.007
19	1644.78	-	398.505	0.580	0.007	0.795	0.007
20	1599.11	-	716.094	0.560	0.008	0.971	0.007
21	1553.88	-	654.559	0.590	0.008	1.089	0.006
22	1516.48	-	1158.400	0.630	0.008	0.837	0.006
23	1479.98	-	2247.905	0.660	0.016	1.158	0.007
24	1453.78	-	-	0.700	0.014	1.452	0.007
25	1428.06	-	-	0.710	0.010	1.094	0.007
26	1405.17	-	-	0.750	0.010	1.121	0.007
27	1385.60	-	-	0.770	0.022	1.142	0.017
28	1366.14	-	-	0.780	0.022	1.333	0.018
29	1347.05	-	-	0.810	0.012	1.459	0.007
30	1328.04	-	-	0.830	0.012	1.370	0.007
31	1309.33	-	-	0.840	0.012	1.292	0.006
32	1294.23	-	-	0.940	0.012	1.317	0.011
33	1279.45	-	-	0.940	0.013	1.105	0.009
34	1264.84	-	-	0.950	0.013	1.259	0.007
35	1251.90	-	-	0.890	0.014	1.205	0.007
36	1239.30	-	-	0.910	0.014	1.185	0.007
37	1226.88	-	-	0.940	0.015	1.323	0.007
38	1214.97	-	-	0.930	0.015	1.385	0.007
39	1203.12	-	-	0.920	0.016	1.145	0.007
40	1191.32	-	-	0.950	0.016	1.111	0.007
41	1180.18	-	-	0.960	0.016	1.070	0.007
42	1169.20	-	-	0.990	0.016	1.314	0.007
43	1158.44	-	-	1.030	0.017	1.100	0.006
44	1148.00	-	-	1.030	0.018	1.153	0.007
45	1137.98	-	-	1.020	0.018	1.252	0.008
46	1128.18	-	-	1.050	0.018	1.273	0.007
47	1118.96	-	-	1.050	0.018	1.245	0.007
48	1109.82	-	-	1.080	0.019	1.171	0.006
49	1102.01	-	-	1.080	0.019	1.247	0.006
50	1094.36	-	-	1.110	0.019	1.098	0.007
51	1087.14	-	-	1.110	0.020	1.391	0.007
52	1080.83	-	-	1.140	0.021	1.227	0.007
53	1074.59	-	-	1.180	0.023	1.334	0.008
54	1068.51	-	-	1.180	0.022	1.298	0.010
55	1062.45	-	-	1.170	0.022	1.299	0.008
56	1056.95	-	-	1.200	0.023	1.409	0.007
57	1051.48	-	-	1.210	0.024	1.502	0.007
58	1045.98	-	-	1.240	0.024	1.621	0.007
59	1040.78	-	-	1.240	0.024	1.253	0.007
60	1035.75	-	-	1.230	0.024	1.504	0.007
61	1030.91	-	-	1.240	0.025	1.453	0.007

Continued on next page

Table 11 – continued from previous page - IEEE8500 - n568

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
62	1026.16	-	-	1.280	0.025	1.398	0.007
63	1021.55	-	-	1.270	0.025	1.471	0.007
64	1017.16	-	-	1.310	0.026	1.583	0.007
65	1013.20	-	-	1.290	0.026	1.122	0.007
66	1009.26	-	-	1.340	0.027	1.172	0.008
67	1005.39	-	-	1.340	0.027	1.572	0.008
68	1001.62	-	-	1.350	0.028	1.217	0.008
69	998.00	-	-	1.380	0.028	1.440	0.008
70	994.58	-	-	1.370	0.029	1.196	0.007
71	991.29	-	-	1.380	0.029	1.999	0.008
72	988.15	-	-	1.380	0.030	2.070	0.007
73	985.12	-	-	1.480	0.030	1.321	0.007
74	982.12	-	-	1.490	0.030	1.828	0.007
75	979.19	-	-	1.490	0.032	1.416	0.007
76	976.28	-	-	1.490	0.031	1.594	0.007
77	973.45	-	-	1.490	0.031	1.700	0.008
78	970.62	-	-	1.520	0.031	1.321	0.007
79	967.94	-	-	1.510	0.032	1.406	0.007
80	965.27	-	-	1.540	0.032	1.450	0.008
81	962.61	-	-	1.540	0.032	1.389	0.008
82	959.98	-	-	1.540	0.033	1.788	0.008
83	957.41	-	-	1.570	0.064	1.340	0.042
84	954.94	-	-	1.580	0.035	1.271	0.011
85	952.47	-	-	1.600	0.035	1.380	0.009
86	950.11	-	-	1.580	0.067	1.222	0.043
87	947.85	-	-	1.600	0.035	1.233	0.010
88	945.72	-	-	1.590	0.035	1.306	0.009
89	943.60	-	-	1.610	0.035	1.215	0.008
90	941.50	-	-	1.620	0.036	1.771	0.008
91	939.57	-	-	1.610	0.038	1.079	0.008
92	937.67	-	-	1.600	0.037	1.541	0.008
93	935.77	-	-	1.630	0.037	1.162	0.008
94	933.96	-	-	1.600	0.038	1.493	0.008
95	932.17	-	-	1.610	0.038	1.173	0.008
96	930.43	-	-	1.620	0.038	1.503	0.008
97	928.71	-	-	1.630	0.039	1.219	0.007
98	927.00	-	-	1.640	0.039	1.380	0.007
99	925.31	-	-	1.660	0.037	1.341	0.007
100	923.62	-	-	1.640	0.038	1.716	0.007
101	921.94	-	-	1.690	0.037	1.158	0.007
102	920.27	-	-	1.690	0.038	1.221	0.007
103	918.59	-	-	1.680	0.038	1.290	0.007
104	916.92	-	-	1.710	0.037	1.252	0.007
105	915.25	-	-	1.740	0.036	1.204	0.007
106	913.67	-	-	1.740	0.037	1.279	0.007
107	912.11	-	-	1.730	0.037	1.571	0.007
108	910.62	-	-	1.760	0.035	1.291	0.006
109	909.21	-	-	1.780	0.035	1.407	0.006
110	907.82	-	-	1.820	0.034	1.230	0.005
111	906.44	-	-	1.800	0.034	1.389	0.005
112	905.11	-	-	1.810	0.035	1.186	0.005
113	903.81	-	-	1.840	0.035	1.202	0.006

Continued on next page

Table 11 – continued from previous page - IEEE8500 - n568

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
114	902.54	-	-	1.830	0.035	1.997	0.005
115	901.32	-	-	1.860	0.035	1.621	0.005
116	900.23	-	-	1.940	0.034	1.208	0.005
117	899.22	-	-	1.890	0.034	1.233	0.005
118	898.23	-	-	1.890	0.033	1.454	0.005
119	897.25	-	-	1.920	0.033	1.477	0.005
120	896.28	-	-	1.910	0.032	1.477	0.005
121	895.31	-	-	1.890	0.032	1.636	0.005
122	894.38	-	-	1.920	0.032	1.092	0.005
123	893.46	-	-	1.910	0.033	1.465	0.005
124	892.53	-	-	1.950	0.033	1.161	0.004
125	891.61	-	-	1.970	0.033	1.536	0.004
126	890.70	-	-	1.950	0.033	1.269	0.004
127	889.83	-	-	1.980	0.033	1.754	0.004
128	888.98	-	-	1.980	0.033	2.418	0.004
129	888.13	-	-	1.940	0.033	1.963	0.005
130	887.31	-	-	1.990	0.033	1.504	0.004
131	886.49	-	-	1.930	0.033	1.215	0.004
132	885.69	-	-	1.960	0.033	2.036	0.004
133	884.89	-	-	1.940	0.033	1.105	0.004
134	884.12	-	-	1.960	0.034	1.193	0.005
135	883.36	-	-	2.040	0.033	1.220	0.004
136	882.61	-	-	1.960	0.034	1.292	0.004
137	881.87	-	-	1.960	0.034	1.403	0.004
138	881.15	-	-	1.960	0.034	1.225	0.004
139	880.43	-	-	1.960	0.035	1.494	0.004
140	879.72	-	-	1.940	0.035	1.111	0.005
141	879.01	-	-	1.930	0.037	1.719	0.004
142	878.32	-	-	1.960	0.036	1.367	0.004
143	877.62	-	-	1.910	0.036	1.403	0.004
144	876.93	-	-	1.980	0.036	1.147	0.004
145	876.24	-	-	1.930	0.036	1.760	0.004
146	875.56	-	-	1.950	0.035	1.683	0.004
147	874.90	-	-	1.930	0.035	1.178	0.004
148	874.26	-	-	2.000	0.034	1.480	0.004
149	873.62	-	-	1.950	0.034	1.509	0.004
150	872.98	-	-	1.980	0.033	1.318	0.004
151	872.35	-	-	1.970	0.034	1.057	0.004
152	871.73	-	-	1.960	0.034	1.236	0.004
153	871.12	-	-	1.950	0.034	1.047	0.004
154	870.52	-	-	1.930	0.034	1.812	0.004
155	869.94	-	-	1.890	0.034	1.051	0.004
156	869.38	-	-	1.920	0.035	1.092	0.004
157	868.82	-	-	1.890	0.036	1.157	0.004
158	868.27	-	-	1.850	0.036	0.951	0.004
159	867.71	-	-	1.840	0.036	1.024	0.004
160	867.17	-	-	1.790	0.036	1.314	0.004
161	866.63	-	-	1.780	0.036	1.718	0.004
162	866.11	-	-	1.750	0.036	1.132	0.004
163	865.61	-	-	1.740	0.037	0.945	0.004
164	865.11	-	-	1.730	0.037	1.062	0.004
165	864.62	-	-	1.670	0.037	1.245	0.004

Continued on next page

Table 11 – continued from previous page - IEEE8500 - n568

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
166	864.15	-	-	1.660	0.037	1.200	0.004
167	863.67	-	-	1.620	0.038	0.920	0.004
168	863.20	-	-	1.590	0.038	1.021	0.004
169	862.74	-	-	1.560	0.038	1.014	0.004
170	862.28	-	-	1.540	0.039	1.108	0.004
171	861.82	-	-	1.530	0.039	1.053	0.004
172	861.37	-	-	1.490	0.039	1.220	0.004
173	860.91	-	-	1.480	0.040	1.013	0.004
174	860.46	-	-	1.480	0.040	1.057	0.004
175	860.08	-	-	1.440	0.040	0.911	0.004
176	859.71	-	-	1.440	0.040	0.838	0.004
177	859.34	-	-	1.450	0.040	0.851	0.004
178	858.97	-	-	1.410	0.040	0.963	0.006
179	858.60	-	-	1.400	0.041	1.245	0.006
180	858.24	-	-	1.430	0.041	1.110	0.006
181	857.88	-	-	1.420	0.041	1.036	0.005
182	857.52	-	-	1.390	0.042	0.860	0.004
183	857.18	-	-	1.390	0.042	1.375	0.005
184	856.84	-	-	1.370	0.042	0.952	0.004
185	856.50	-	-	1.370	0.042	0.920	0.004
186	856.16	-	-	1.400	0.042	1.157	0.004
187	855.83	-	-	1.410	0.044	1.028	0.004
188	855.50	-	-	1.430	0.043	1.340	0.004
189	855.17	-	-	1.400	0.041	0.978	0.004
190	854.85	-	-	1.410	0.041	1.221	0.004
191	854.53	-	-	1.420	0.040	0.967	0.004
192	854.21	-	-	1.420	0.040	0.925	0.004
193	853.89	-	-	1.420	0.040	1.039	0.004
194	853.58	-	-	1.430	0.038	0.863	0.004
195	853.27	-	-	1.430	0.038	1.621	0.003
196	852.96	-	-	1.440	0.038	0.921	0.003
197	852.65	-	-	1.450	0.038	0.977	0.003
198	852.34	-	-	1.460	0.038	0.912	0.003
199	852.04	-	-	1.450	0.039	1.113	0.003
200	851.73	-	-	1.430	0.039	0.979	0.003
201	851.43	-	-	1.450	0.039	1.156	0.004
202	851.12	-	-	1.430	0.040	1.060	0.003
203	850.83	-	-	1.520	0.040	1.126	0.003
204	850.53	-	-	1.440	0.038	1.013	0.003
205	850.23	-	-	1.450	0.038	1.048	0.003
206	849.94	-	-	1.420	0.037	1.379	0.003
207	849.65	-	-	1.430	0.037	1.211	0.003
208	849.36	-	-	1.450	0.036	1.098	0.003
209	849.08	-	-	1.440	0.036	1.159	0.003
210	848.79	-	-	1.460	0.035	1.197	0.003
211	848.52	-	-	1.430	0.035	1.284	0.003
212	848.25	-	-	1.420	0.035	1.171	0.003
213	848.00	-	-	1.490	0.035	1.129	0.003
214	847.75	-	-	1.440	0.035	1.068	0.003
215	847.50	-	-	1.440	0.036	1.116	0.003
216	847.26	-	-	1.460	0.036	1.175	0.003
217	847.02	-	-	1.460	0.036	1.319	0.003

Continued on next page

Table 11 – continued from previous page - IEEE8500 - n568

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
218	846.78	-	-	1.440	0.037	1.260	0.003
219	846.54	-	-	1.440	0.037	1.189	0.003
220	846.31	-	-	1.410	0.037	1.548	0.003
221	846.08	-	-	1.420	0.037	1.079	0.003
222	845.85	-	-	1.480	0.037	1.351	0.003
223	845.63	-	-	1.430	0.034	1.551	0.002
224	845.41	-	-	1.440	0.034	1.320	0.003
225	845.19	-	-	1.430	0.033	1.667	0.002
226	844.97	-	-	1.460	0.033	1.487	0.002
227	844.76	-	-	1.450	0.032	1.232	0.002
228	844.55	-	-	1.470	0.031	1.197	0.002
229	844.35	-	-	1.440	0.030	1.216	0.002
230	844.15	-	-	1.440	0.030	1.280	0.003
231	843.95	-	-	1.450	0.029	1.059	0.002
232	843.75	-	-	1.430	0.029	1.671	0.002
233	843.55	-	-	1.480	0.029	1.263	0.002
234	843.36	-	-	1.440	0.029	1.322	0.002
235	843.17	-	-	1.460	0.030	1.203	0.002
236	842.98	-	-	1.400	0.030	1.296	0.002
237	842.79	-	-	1.460	0.030	1.241	0.002
238	842.61	-	-	1.420	0.030	1.248	0.002
239	842.44	-	-	1.410	0.030	1.400	0.002
240	842.26	-	-	1.450	0.027	1.376	0.002
241	842.10	-	-	1.420	0.027	1.189	0.002
242	841.93	-	-	1.440	0.026	1.274	0.002
243	841.77	-	-	1.410	0.026	1.164	0.002
244	841.61	-	-	1.430	0.026	1.261	0.002
245	841.45	-	-	1.380	0.026	1.180	0.002
246	841.28	-	-	1.400	0.026	1.261	0.002
247	841.13	-	-	1.370	0.026	1.132	0.002
248	840.97	-	-	1.420	0.026	1.281	0.002
249	840.81	-	-	1.370	0.026	1.128	0.002
250	840.65	-	-	1.340	0.026	1.260	0.002
251	840.49	-	-	1.340	0.026	1.323	0.002
252	840.34	-	-	1.340	0.027	1.327	0.002
253	840.18	-	-	1.340	0.027	1.270	0.002
254	840.03	-	-	1.320	0.027	1.328	0.002
255	839.89	-	-	1.330	0.027	1.089	0.002
256	839.74	-	-	1.290	0.028	1.357	0.002
257	839.60	-	-	1.290	0.028	1.340	0.002
258	839.46	-	-	1.300	0.027	1.244	0.002
259	839.32	-	-	1.300	0.027	1.568	0.002
260	839.18	-	-	1.290	0.028	1.119	0.002
261	839.05	-	-	1.290	0.028	1.217	0.002
262	838.92	-	-	1.320	0.028	1.263	0.002
263	838.79	-	-	1.280	0.028	1.093	0.002
264	838.66	-	-	1.280	0.028	0.999	0.002
265	838.53	-	-	1.270	0.028	0.973	0.002
266	838.40	-	-	1.280	0.028	1.125	0.002
267	838.27	-	-	1.410	0.029	1.103	0.002
268	838.15	-	-	1.280	0.029	1.024	0.002
269	838.02	-	-	1.290	0.029	0.878	0.002

Continued on next page

Table 11 – continued from previous page - IEEE8500 - n568

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
270	837.90	-	-	1.270	0.029	1.012	0.002
271	837.78	-	-	1.280	0.029	0.941	0.002
272	837.66	-	-	1.300	0.029	0.944	0.002
273	837.55	-	-	1.350	0.029	0.921	0.002
274	837.44	-	-	1.280	0.029	0.915	0.002
275	837.33	-	-	1.280	0.029	1.147	0.002
276	837.22	-	-	1.280	0.027	1.024	0.002
277	837.11	-	-	1.270	0.027	0.990	0.001
278	837.00	-	-	1.310	0.025	0.989	0.001
279	836.89	-	-	1.310	0.024	1.003	0.001
280	836.79	-	-	1.270	0.023	1.022	0.001
281	836.69	-	-	1.290	0.023	0.996	0.001
282	836.59	-	-	1.280	0.023	0.975	0.001
283	836.49	-	-	1.280	0.023	1.026	0.001
284	836.39	-	-	1.330	0.023	1.008	0.001
285	836.29	-	-	1.310	0.023	0.989	0.001
286	836.19	-	-	1.310	0.024	1.051	0.001
287	836.09	-	-	1.310	0.024	0.984	0.001
288	836.00	-	-	1.350	0.024	0.942	0.001
289	835.90	-	-	1.310	0.024	1.076	0.001
290	835.81	-	-	1.330	0.024	1.133	0.001
291	835.72	-	-	1.300	0.024	1.016	0.001
292	835.63	-	-	1.290	0.024	1.065	0.001
293	835.54	-	-	1.330	0.022	0.933	0.001
294	835.45	-	-	1.330	0.022	1.142	0.001
295	835.36	-	-	1.300	0.021	1.050	0.001
296	835.28	-	-	1.340	0.021	0.990	0.001
297	835.19	-	-	1.350	0.021	0.972	0.001
298	835.11	-	-	1.340	0.021	0.975	0.001
299	835.03	-	-	1.330	0.020	0.891	0.001
300	834.95	-	-	1.330	0.020	0.805	0.001
301	834.87	-	-	1.360	0.019	0.935	0.001
302	834.79	-	-	1.340	0.018	0.947	0.001
303	834.72	-	-	1.330	0.017	0.935	0.001
304	834.64	-	-	1.330	0.017	1.062	0.001
305	834.56	-	-	1.350	0.016	1.065	0.001
306	834.49	-	-	1.340	0.015	0.951	0.001
307	834.41	-	-	1.340	0.014	1.030	0.001
308	834.34	-	-	1.330	0.014	1.129	0.001
309	834.26	-	-	1.370	0.014	0.908	0.001
310	834.19	-	-	1.340	0.014	0.897	0.001
311	834.11	-	-	1.350	0.014	0.918	0.001
312	834.04	-	-	1.340	0.014	0.963	0.001
313	833.97	-	-	1.340	0.014	1.003	0.001
314	833.90	-	-	1.350	0.014	1.127	0.001
315	833.83	-	-	1.380	0.013	0.970	0.001
316	833.76	-	-	1.340	0.013	1.013	0.001
317	833.69	-	-	1.360	0.013	1.040	0.000
318	833.62	-	-	1.350	0.013	0.803	0.001
319	833.55	-	-	1.370	0.012	1.021	0.000
320	833.48	-	-	1.350	0.012	1.009	0.000
321	833.42	-	-	1.350	0.011	0.924	0.000

Continued on next page

Table 11 – continued from previous page - IEEE8500 - n568

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
322	833.35	-	-	1.420	0.010	1.127	0.000
323	833.29	-	-	1.360	0.009	0.962	0.000
324	833.22	-	-	1.370	0.009	0.861	0.000
325	833.16	-	-	1.390	0.008	1.037	0.000
326	833.09	-	-	1.380	0.008	0.909	0.000
327	833.03	-	-	1.460	0.007	0.980	0.000
328	832.96	-	-	1.390	0.007	1.045	0.000
329	832.90	-	-	1.370	0.008	0.987	0.000
330	832.83	-	-	1.360	0.008	1.031	0.000
331	832.77	-	-	1.400	0.008	0.933	0.000
332	832.71	-	-	1.380	0.008	0.946	0.000
333	832.65	-	-	1.390	0.008	0.983	0.000
334	832.59	-	-	1.360	0.008	0.919	0.000
335	832.53	-	-	1.420	0.007	1.037	0.000
336	832.48	-	-	1.360	0.006	0.818	0.000
337	832.42	-	-	1.400	0.006	0.979	0.000
338	832.36	-	-	1.400	0.005	0.898	0.000
339	832.31	-	-	1.370	0.006	0.818	0.000
340	832.25	-	-	1.370	0.006	0.944	0.000
341	832.19	-	-	1.350	0.005	0.939	0.000
342	832.14	-	-	1.310	0.005	0.970	0.000
343	832.09	-	-	1.300	0.005	0.782	0.000
344	832.03	-	-	1.330	0.006	0.782	0.000
345	831.98	-	-	1.290	0.006	0.841	0.000
346	831.93	-	-	1.240	0.006	0.815	0.000
347	831.87	-	-	1.260	0.005	0.616	0.000
348	831.82	-	-	1.260	0.006	0.529	0.000
349	831.77	-	-	1.220	0.006	0.131	0.000
350	831.72	-	-	1.240	0.006	0.127	0.000
351	831.67	-	-	1.200	0.006	0.141	0.000
352	831.62	-	-	1.180	0.007	0.163	0.000
353	831.57	-	-	1.180	0.007	0.137	0.000
354	831.52	-	-	1.140	0.007	0.137	0.000
355	831.48	-	-	1.110	0.006	0.138	0.000
356	831.43	-	-	1.100	0.006	0.151	0.000
357	831.38	-	-	1.080	0.006	0.183	0.000
358	831.33	-	-	1.060	0.006	0.166	0.000
359	831.28	-	-	1.060	0.006	0.165	0.000
360	831.24	-	-	1.100	0.006	0.178	0.000
361	831.19	-	-	1.070	0.006	0.158	0.000
362	831.14	-	-	1.050	0.006	0.154	0.000
363	831.10	-	-	1.020	0.006	0.188	0.000
364	831.05	-	-	1.020	0.006	0.122	0.000
365	831.00	-	-	0.970	0.006	0.149	0.000
366	830.96	-	-	0.940	0.006	0.123	0.000
367	830.91	-	-	0.940	0.006	0.147	0.000
368	830.87	-	-	0.940	0.006	0.159	0.000
369	830.82	-	-	0.940	0.007	0.156	0.000
370	830.78	-	-	0.920	0.007	0.158	0.000
371	830.74	-	-	0.910	0.007	0.189	0.000
372	830.69	-	-	0.890	0.007	0.114	0.000
373	830.65	-	-	0.890	0.006	0.134	0.000

Continued on next page

Table 11 – continued from previous page - IEEE8500 - n568

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
374	830.61	-	-	0.850	0.006	0.139	0.000
375	830.56	-	-	0.820	0.007	0.128	0.000
376	830.52	-	-	0.810	0.007	0.229	0.000
377	830.48	-	-	0.790	0.007	0.170	0.000
378	830.44	-	-	0.770	0.007	0.156	0.000
379	830.40	-	-	0.750	0.007	0.173	0.000
380	830.36	-	-	0.760	0.007	0.127	0.000
381	830.32	-	-	0.770	0.007	0.149	0.000
382	830.28	-	-	0.730	0.007	0.136	0.000
383	830.24	-	-	0.730	0.007	0.146	0.000
384	830.20	-	-	0.700	0.007	0.159	0.000
385	830.15	-	-	0.690	0.007	0.120	0.000
386	830.12	-	-	0.670	0.007	0.158	0.000
387	830.08	-	-	0.680	0.007	0.100	0.000
388	830.04	-	-	0.690	0.007	0.086	0.000
389	830.00	-	-	0.680	0.007	0.067	0.000
390	829.96	-	-	0.650	0.008	0.226	0.000
391	829.92	-	-	0.630	0.008	0.114	0.000
392	829.88	-	-	0.650	0.007	0.111	0.000
393	829.85	-	-	0.620	0.007	0.137	0.000
394	829.81	-	-	0.610	0.007	0.150	0.000
395	829.77	-	-	0.610	0.007	0.187	0.000
396	829.74	-	-	0.600	0.007	0.208	0.000
397	829.70	-	-	0.580	0.008	0.142	0.000
398	829.66	-	-	0.580	0.008	0.139	0.000
399	829.62	-	-	0.580	0.008	0.178	0.000
400	829.59	-	-	0.560	0.008	0.289	0.000
401	829.55	-	-	0.560	0.008	0.124	0.000
402	829.52	-	-	0.530	0.008	0.154	0.000
403	829.49	-	-	0.540	0.008	0.130	0.000
404	829.45	-	-	0.530	0.008	0.089	0.000
405	829.42	-	-	0.510	0.008	0.128	0.000
406	829.38	-	-	0.510	0.008	0.103	0.000
407	829.35	-	-	0.500	0.008	0.088	0.000
408	829.32	-	-	0.480	0.008	0.087	0.000
409	829.28	-	-	0.480	0.008	0.120	0.000
410	829.25	-	-	0.490	0.008	0.082	0.000
411	829.22	-	-	0.480	0.008	0.078	0.000
412	829.19	-	-	0.480	0.008	0.125	0.000
413	829.15	-	-	0.460	0.008	0.075	0.000
414	829.12	-	-	0.450	0.008	0.075	0.000
415	829.09	-	-	0.440	0.008	0.117	0.000
416	829.06	-	-	0.440	0.009	0.078	0.000
417	829.03	-	-	0.430	0.009	0.156	0.000
418	829.00	-	-	0.420	0.008	0.077	0.000
419	828.98	-	-	0.420	0.009	0.095	0.000
420	828.95	-	-	0.430	0.010	0.070	0.000
421	828.92	-	-	0.410	0.009	0.071	0.000
422	828.89	-	-	0.410	0.009	0.129	0.000
423	828.86	-	-	0.400	0.009	0.068	0.000
424	828.84	-	-	0.400	0.009	0.139	0.000
425	828.81	-	-	0.400	0.009	0.091	0.000

Continued on next page

Table 11 – continued from previous page - IEEE8500 - n568

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
426	828.78	-	-	0.390	0.009	0.116	0.000
427	828.76	-	-	0.390	0.009	0.119	0.000
428	828.73	-	-	0.390	0.009	0.120	0.000
429	828.70	-	-	0.370	0.009	0.118	0.000
430	828.68	-	-	0.380	0.009	0.120	0.000
431	828.65	-	-	0.370	0.009	0.114	0.000
432	828.63	-	-	0.360	0.009	0.120	0.000
433	828.60	-	-	0.360	0.009	0.114	0.000
434	828.58	-	-	0.350	0.009	0.096	0.000
435	828.55	-	-	0.350	0.009	0.110	0.000
436	828.53	-	-	0.350	0.009	0.091	0.000
437	828.50	-	-	0.340	0.009	0.110	0.000
438	828.48	-	-	0.340	0.009	0.085	0.000
439	828.46	-	-	0.330	0.009	0.091	0.000
440	828.43	-	-	0.340	0.009	0.087	0.000
441	828.41	-	-	0.340	0.009	0.106	0.000
442	828.39	-	-	0.330	0.009	0.112	0.000
443	828.36	-	-	0.310	0.009	0.107	0.000
444	828.34	-	-	0.310	0.009	0.136	0.000
445	828.32	-	-	0.320	0.009	0.108	0.000
446	828.30	-	-	0.300	0.009	0.114	0.000
447	828.27	-	-	0.300	0.010	0.111	0.000
448	828.25	-	-	0.290	0.010	0.084	0.000
449	828.23	-	-	0.280	0.010	0.086	0.000
450	828.21	-	-	0.290	0.010	0.126	0.000
451	828.19	-	-	0.280	0.010	0.139	0.000
452	828.17	-	-	0.280	0.010	0.102	0.000
453	828.15	-	-	0.260	0.010	0.109	0.000
454	828.13	-	-	0.260	0.010	0.136	0.000
455	828.11	-	-	0.250	0.010	0.146	0.000
456	828.09	-	-	0.240	0.010	0.091	0.000
457	828.07	-	-	0.230	0.010	0.082	0.000
458	828.05	-	-	0.230	0.010	0.101	0.000
459	828.03	-	-	0.220	0.010	0.104	0.000
460	828.01	-	-	0.220	0.010	0.091	0.000
461	827.99	-	-	0.200	0.010	0.103	0.000
462	827.97	-	-	0.200	0.010	0.103	0.000
463	827.95	-	-	0.200	0.010	0.088	0.000
464	827.93	-	-	0.200	0.010	0.096	0.000
465	827.91	-	-	0.190	0.010	0.096	0.000
466	827.90	-	-	0.180	0.010	0.103	0.000
467	827.88	-	-	0.170	0.010	0.096	0.000
468	827.86	-	-	0.160	0.010	0.093	0.000
469	827.84	-	-	0.160	0.010	0.091	0.000
470	827.83	-	-	0.160	0.010	0.084	0.000
471	827.81	-	-	0.150	0.011	0.082	0.000
472	827.79	-	-	0.150	0.011	0.081	0.000
473	827.77	-	-	0.150	0.010	0.064	0.000
474	827.76	-	-	0.150	0.007	0.071	0.000
475	827.74	-	-	0.150	0.007	0.092	0.000
476	827.73	-	-	0.160	0.006	0.085	0.000
477	827.71	-	-	0.140	0.006	0.064	0.000

Continued on next page

Table 11 – continued from previous page - IEEE8500 - n568

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
478	827.69	-	-	0.140	0.005	0.087	0.000
479	827.68	-	-	0.150	0.005	0.079	0.000
480	827.66	-	-	0.140	0.005	0.076	0.000
481	827.65	-	-	0.150	0.005	0.073	0.000
482	827.63	-	-	0.140	0.005	0.063	0.000
483	827.62	-	-	0.140	0.005	0.086	0.000
484	827.60	-	-	0.140	0.004	0.067	0.000
485	827.59	-	-	0.140	0.004	0.107	0.000
486	827.57	-	-	0.140	0.003	0.068	0.000
487	827.56	-	-	0.140	0.003	0.073	0.000
488	827.54	-	-	0.150	0.002	0.076	0.000
489	827.53	-	-	0.140	0.002	0.077	0.000
490	827.51	-	-	0.140	0.002	0.075	0.000
491	827.50	-	-	0.140	0.002	0.080	0.000
492	827.48	-	-	0.140	0.001	0.073	0.000
493	827.47	-	-	0.140	0.001	0.059	0.000
494	827.45	-	-	0.140	0.001	0.058	0.000
495	827.44	-	-	0.140	0.001	0.050	0.000
496	827.43	-	-	0.130	0.001	0.062	0.000
497	827.41	-	-	0.140	0.001	0.063	0.000
498	827.40	-	-	0.140	0.001	0.070	0.000
499	827.39	-	-	0.130	0.001	0.087	0.000
500	827.37	-	-	0.130	0.001	0.049	0.000
501	827.36	-	-	0.130	0.001	0.049	0.000
502	827.35	-	-	0.130	0.001	0.073	0.000
503	827.33	-	-	0.140	0.001	0.072	0.000
504	827.32	-	-	0.130	0.000	0.052	0.000
505	827.31	-	-	0.140	0.000	0.066	0.000
506	827.30	-	-	0.120	0.000	0.051	0.000
507	827.28	-	-	0.130	0.000	0.048	0.000
508	827.27	-	-	0.130	0.000	0.044	0.000
509	827.26	-	-	0.120	0.000	0.046	0.000
510	827.25	-	-	0.120	0.000	0.050	0.000
511	827.24	-	-	0.130	0.000	0.049	0.000
512	827.23	-	-	0.110	0.000	0.050	0.000
513	827.22	-	-	0.120	0.000	0.049	0.000
514	827.21	-	-	0.120	0.000	0.049	0.000
515	827.19	-	-	0.110	0.000	0.041	0.000
516	827.18	-	-	0.110	0.000	0.047	0.000
517	827.17	-	-	0.120	0.000	0.046	0.000
518	827.16	-	-	0.110	0.000	0.045	0.000
519	827.15	-	-	0.110	0.000	0.042	0.000
520	827.14	-	-	0.110	0.000	0.044	0.000
521	827.13	-	-	0.100	0.000	0.041	0.000
522	827.13	-	-	0.100	0.000	0.043	0.000
523	827.12	-	-	0.100	0.000	0.044	0.000
524	827.11	-	-	0.110	0.000	0.044	0.000
525	827.10	-	-	0.100	0.000	0.040	0.000
526	827.09	-	-	0.100	0.000	0.038	0.000
527	827.08	-	-	0.100	0.000	0.041	0.000
528	827.07	-	-	0.090	0.000	0.038	0.000
529	827.07	-	-	0.090	0.000	0.039	0.000

Continued on next page

Table 11 – continued from previous page - IEEE8500 - n568

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
530	827.06	-	-	0.090	0.000	0.039	0.000
531	827.05	-	-	0.100	0.000	0.039	0.000
532	827.04	-	-	0.090	0.000	0.038	0.000
533	827.03	-	-	0.090	0.000	0.040	0.000
534	827.03	-	-	0.090	0.000	0.043	0.000
535	827.02	-	-	0.080	0.000	0.036	0.000
536	827.01	-	-	0.090	0.000	0.035	0.000
537	827.01	-	-	0.080	0.000	0.041	0.000
538	827.00	-	-	0.080	0.000	0.038	0.000
539	826.99	-	-	0.080	0.000	0.040	0.000
540	826.99	-	-	0.090	0.000	0.032	0.000
541	826.98	-	-	0.070	0.000	0.038	0.000
542	826.97	-	-	0.070	0.000	0.038	0.000
543	826.97	-	-	0.060	0.000	0.038	0.000
544	826.96	-	-	0.070	0.000	0.038	0.000
545	826.96	-	-	0.060	0.000	0.019	0.000
546	826.95	-	-	0.060	0.000	0.017	0.000
547	826.95	-	-	0.060	0.000	0.018	0.000
548	826.95	-	-	0.050	0.000	0.017	0.000
549	826.94	-	-	0.050	0.000	0.017	0.000
550	826.94	-	-	0.050	0.000	0.017	0.000
551	826.93	-	-	0.040	0.000	0.018	0.000
552	826.93	-	-	0.050	0.000	0.015	0.000
553	826.92	-	-	0.040	0.000	0.015	0.000
554	826.92	-	-	0.040	0.000	0.015	0.000
555	826.91	-	-	0.040	0.000	0.015	0.000
556	826.91	-	-	0.040	0.000	0.014	0.000
557	826.90	-	-	0.030	0.000	0.014	0.000
558	826.90	-	-	0.040	0.000	0.014	0.000
559	826.90	-	-	0.030	0.000	0.012	0.000
560	826.89	-	-	0.030	0.000	0.013	0.000
561	826.89	-	-	0.030	0.000	0.012	0.000
562	826.89	-	-	0.030	0.000	0.011	0.000
563	826.88	-	-	0.020	0.000	0.012	0.000
564	826.88	-	-	0.030	0.000	0.006	0.000
565	826.88	-	-	0.020	0.000	0.009	0.000
566	826.88	-	-	0.030	0.000	0.002	0.000
567	826.88	-	-	0.020	0.000	0.002	0.000
Total		**8718.49**	**9527.96**	**559.50**	**11.12**	**10.308**	**1.484**

Table 12: ENS optimization - IEEE8500 - n1149.

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
0	30093.20	1.512	0.002	0.000	0.000	0.006	0.000
1	22012.00	4.393	0.075	0.020	0.000	0.086	0.000
2	15397.00	24.582	0.030	0.050	0.021	0.034	0.024
3	13459.60	15.930	0.350	0.110	0.019	0.087	0.024
4	11758.10	-	1.317	0.160	0.017	0.055	0.023

Continued on next page

Table 12 – continued from previous page - IEEE8500 - n1149

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
5	10591.20	-	1.424	0.240	0.017	0.087	0.025
6	9642.90	-	1.492	0.280	0.019	2.594	0.025
7	8960.76	-	8.431	0.320	0.051	0.105	0.049
8	8323.38	-	6.005	0.400	0.026	0.294	0.028
9	7799.09	-	9.464	0.510	0.029	0.493	0.030
10	7358.07	-	13.708	0.570	0.031	0.268	0.033
11	6971.94	-	29.598	0.670	0.034	1.621	0.034
12	6612.91	-	55.988	0.770	0.036	1.799	0.035
13	6325.78	-	55.148	0.830	0.039	2.425	0.037
14	6102.10	-	77.012	0.930	0.041	1.555	0.033
15	5895.56	-	283.947	0.920	0.044	4.304	0.036
16	5712.89	-	413.644	1.020	0.078	2.607	0.075
17	5538.82	-	-	1.110	0.080	3.148	0.074
18	5381.95	-	-	1.200	0.050	1.941	0.037
19	5257.70	-	-	1.310	0.051	1.966	0.038
20	5146.77	-	-	1.410	0.052	2.156	0.040
21	5036.49	-	-	1.520	0.054	1.465	0.035
22	4936.81	-	-	1.630	0.056	1.597	0.036
23	4838.71	-	-	1.750	0.058	1.717	0.039
24	4741.36	-	-	1.790	0.059	1.733	0.041
25	4650.34	-	-	1.870	0.062	1.972	0.041
26	4573.08	-	-	1.960	0.063	2.319	0.040
27	4503.39	-	-	2.040	0.066	1.922	0.037
28	4434.62	-	-	2.170	0.069	1.959	0.038
29	4366.88	-	-	2.200	0.070	2.086	0.042
30	4303.98	-	-	2.280	0.071	2.619	0.043
31	4249.50	-	-	2.380	0.073	2.149	0.042
32	4195.18	-	-	2.420	0.075	2.612	0.037
33	4142.80	-	-	2.470	0.077	2.753	0.040
34	4092.05	-	-	2.570	0.079	2.485	0.040
35	4041.43	-	-	2.610	0.082	2.826	0.043
36	3991.23	-	-	2.710	0.084	2.514	0.046
37	3946.91	-	-	2.760	0.085	2.452	0.046
38	3904.30	-	-	2.770	0.085	2.818	0.046
39	3863.68	-	-	2.810	0.087	2.626	0.047
40	3825.89	-	-	2.910	0.088	2.842	0.045
41	3788.39	-	-	2.930	0.090	3.119	0.041
42	3752.09	-	-	3.030	0.091	2.551	0.043
43	3715.97	-	-	3.090	0.094	2.213	0.045
44	3680.39	-	-	3.110	0.173	2.834	0.121
45	3645.44	-	-	3.170	0.174	3.267	0.124
46	3611.20	-	-	3.250	0.089	2.708	0.044
47	3577.99	-	-	3.300	0.089	3.715	0.042
48	3550.26	-	-	3.360	0.090	2.747	0.037
49	3522.81	-	-	3.630	0.092	2.813	0.037
50	3495.80	-	-	3.670	0.092	2.796	0.038
51	3469.17	-	-	3.720	0.093	2.544	0.038
52	3442.92	-	-	3.810	0.093	2.737	0.037
53	3416.79	-	-	3.670	0.094	2.817	0.039
54	3391.74	-	-	3.730	0.095	2.845	0.043
55	3367.21	-	-	3.750	0.095	2.275	0.041
56	3342.88	-	-	3.780	0.096	2.351	0.041

Continued on next page

Table 12 – continued from previous page - IEEE8500 - n1149

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
57	3319.77	-	-	3.810	0.098	2.204	0.041
58	3296.92	-	-	3.830	0.099	2.247	0.040
59	3275.29	-	-	3.900	0.100	2.329	0.041
60	3253.39	-	-	3.930	0.103	2.570	0.040
61	3231.84	-	-	3.960	0.104	2.370	0.040
62	3210.84	-	-	3.950	0.105	2.262	0.038
63	3191.28	-	-	3.970	0.107	2.163	0.040
64	3172.21	-	-	4.060	0.107	2.227	0.039
65	3153.88	-	-	4.050	0.109	1.983	0.038
66	3135.78	-	-	4.080	0.109	2.065	0.039
67	3118.17	-	-	4.080	0.110	2.352	0.039
68	3102.45	-	-	4.110	0.109	2.726	0.040
69	3087.20	-	-	4.120	0.111	3.195	0.042
70	3072.06	-	-	4.160	0.110	2.465	0.040
71	3058.15	-	-	4.200	0.112	2.649	0.039
72	3044.29	-	-	4.220	0.112	3.266	0.036
73	3030.98	-	-	4.260	0.115	3.763	0.036
74	3018.26	-	-	4.290	0.116	2.522	0.036
75	3005.86	-	-	4.300	0.115	2.208	0.036
76	2993.54	-	-	4.370	0.117	2.975	0.036
77	2981.38	-	-	4.410	0.117	2.526	0.036
78	2969.38	-	-	4.470	0.118	2.993	0.036
79	2958.50	-	-	4.520	0.118	3.026	0.035
80	2947.67	-	-	4.550	0.120	2.971	0.037
81	2937.24	-	-	4.590	0.120	2.865	0.039
82	2927.30	-	-	4.680	0.122	2.852	0.039
83	2917.51	-	-	4.740	0.123	3.039	0.039
84	2907.92	-	-	4.760	0.125	2.360	0.040
85	2898.48	-	-	4.750	0.124	2.641	0.040
86	2889.53	-	-	4.870	0.126	2.685	0.039
87	2880.58	-	-	4.800	0.127	2.746	0.038
88	2871.63	-	-	4.900	0.129	2.870	0.038
89	2862.77	-	-	4.890	0.126	2.827	0.037
90	2854.42	-	-	4.980	0.127	2.851	0.037
91	2846.28	-	-	5.020	0.128	2.875	0.037
92	2838.54	-	-	5.130	0.127	2.787	0.036
93	2830.84	-	-	5.140	0.126	2.618	0.034
94	2823.18	-	-	5.240	0.126	3.157	0.033
95	2815.53	-	-	5.300	0.125	3.076	0.035
96	2808.32	-	-	5.290	0.126	2.612	0.034
97	2801.14	-	-	5.300	0.125	2.867	0.034
98	2794.06	-	-	5.360	0.125	2.451	0.033
99	2787.11	-	-	5.350	0.124	2.823	0.034
100	2780.18	-	-	5.450	0.126	2.521	0.034
101	2773.26	-	-	5.420	0.127	3.014	0.036
102	2766.34	-	-	5.450	0.124	2.503	0.035
103	2759.65	-	-	5.580	0.123	2.638	0.034
104	2752.98	-	-	5.590	0.125	2.636	0.034
105	2746.48	-	-	5.670	0.125	3.656	0.033
106	2739.98	-	-	5.790	0.126	2.780	0.033
107	2733.68	-	-	5.790	0.127	2.733	0.033
108	2727.45	-	-	5.800	0.126	3.834	0.030

Continued on next page

Table 12 – continued from previous page - IEEE8500 - n1149

		Time (sec)					
m	best ENS	ILP-GALIAS	ILP-IFLOWS	DP-TS	DP-N2M2	ILP-CUTS	DP-PC
109	2721.60	-	-	5.830	0.126	2.974	0.030
110	2715.95	-	-	5.930	0.127	2.894	0.030
111	2710.32	-	-	5.960	0.126	2.815	0.029
112	2704.75	-	-	6.020	0.125	2.939	0.029
113	2699.19	-	-	6.020	0.125	2.507	0.030
114	2693.68	-	-	6.100	0.124	3.045	0.029
115	2688.17	-	-	6.160	0.125	3.036	0.029
116	2682.82	-	-	6.180	0.124	3.289	0.029
117	2677.48	-	-	6.230	0.122	3.143	0.028
118	2672.22	-	-	6.250	0.123	2.852	0.028
119	2667.02	-	-	6.220	0.123	2.812	0.028
120	2662.03	-	-	6.270	0.124	2.796	0.031
121	2657.11	-	-	6.290	0.123	2.642	0.030
122	2652.27	-	-	6.330	0.124	2.425	0.031
123	2647.49	-	-	6.470	0.122	3.375	0.030
124	2642.73	-	-	6.740	0.122	2.896	0.029
125	2637.98	-	-	6.730	0.121	3.078	0.029
126	2633.42	-	-	6.870	0.121	2.733	0.028
127	2628.87	-	-	6.750	0.122	2.649	0.028
128	2624.37	-	-	6.830	0.121	2.567	0.028
129	2619.93	-	-	6.800	0.121	3.003	0.028
130	2615.50	-	-	6.720	0.120	3.151	0.027
131	2611.15	-	-	6.740	0.119	3.078	0.027
132	2606.81	-	-	6.760	0.119	3.072	0.027
133	2602.61	-	-	6.830	0.118	2.969	0.026
134	2598.41	-	-	6.800	0.118	2.976	0.027
135	2594.24	-	-	6.890	0.116	2.757	0.026
136	2590.09	-	-	6.920	0.115	3.214	0.025
137	2585.96	-	-	6.880	0.115	2.874	0.025
138	2581.93	-	-	6.970	0.114	3.193	0.025
139	2577.94	-	-	6.970	0.115	2.910	0.024
140	2573.99	-	-	7.040	0.115	2.973	0.023
141	2570.08	-	-	7.000	0.116	3.519	0.023
142	2566.18	-	-	7.020	0.117	2.785	0.025
143	2562.43	-	-	7.090	0.118	2.638	0.025
144	2558.70	-	-	7.490	0.119	3.713	0.024
145	2554.97	-	-	7.030	0.120	3.631	0.024
146	2551.28	-	-	7.080	0.120	3.282	0.024
147	2547.66	-	-	7.160	0.121	3.558	0.024
148	2544.14	-	-	7.190	0.122	2.954	0.024
149	2540.63	-	-	7.320	0.123	3.153	0.025
150	2537.12	-	-	7.310	0.124	3.083	0.025
151	2533.61	-	-	7.270	0.125	3.325	0.025
152	2530.10	-	-	7.340	0.125	2.758	0.025
153	2526.60	-	-	7.590	0.126	3.031	0.026
154	2523.18	-	-	7.440	0.128	2.817	0.026
155	2519.79	-	-	7.860	0.128	3.165	0.027
156	2516.41	-	-	8.040	0.129	4.156	0.026
157	2513.04	-	-	8.170	0.130	3.131	0.026
158	2509.73	-	-	8.010	0.127	3.182	0.026
159	2506.49	-	-	8.120	0.128	3.894	0.026
160	2503.31	-	-	8.150	0.127	3.238	0.025

Continued on next page

Table 12 – continued from previous page - IEEE8500 - n1149

		Time (sec)					
m	best ENS	ILP-GALIAS	ILP-IFLOWS	DP-TS	DP-N2M2	ILP-CUTS	DP-PC
161	2500.17	-	-	8.380	0.127	3.597	0.025
162	2497.09	-	-	8.180	0.126	3.659	0.024
163	2494.06	-	-	8.360	0.128	4.080	0.023
164	2491.12	-	-	8.240	0.126	3.974	0.023
165	2488.25	-	-	8.340	0.127	2.971	0.024
166	2485.42	-	-	8.320	0.313	4.187	0.204
167	2482.62	-	-	8.570	0.125	2.973	0.023
168	2479.88	-	-	8.450	0.125	3.404	0.022
169	2477.41	-	-	8.350	0.124	2.880	0.022
170	2474.94	-	-	8.470	0.314	3.791	0.207
171	2472.48	-	-	8.590	0.122	2.558	0.024
172	2470.04	-	-	8.530	0.122	2.826	0.023
173	2467.65	-	-	8.560	0.121	3.021	0.023
174	2465.28	-	-	8.600	0.122	3.034	0.022
175	2462.91	-	-	8.560	0.121	2.647	0.023
176	2460.55	-	-	8.580	0.121	2.800	0.024
177	2458.25	-	-	8.620	0.120	2.627	0.022
178	2456.05	-	-	8.760	0.120	2.550	0.022
179	2453.94	-	-	8.630	0.119	2.777	0.021
180	2451.85	-	-	8.580	0.120	2.850	0.022
181	2449.84	-	-	8.750	0.120	2.790	0.022
182	2447.85	-	-	8.800	0.121	2.715	0.022
183	2445.87	-	-	8.570	0.121	2.488	0.023
184	2443.91	-	-	8.730	0.122	3.189	0.022
185	2441.95	-	-	8.650	0.123	3.295	0.022
186	2440.00	-	-	8.700	0.123	2.818	0.022
187	2438.06	-	-	8.640	0.124	3.110	0.022
188	2436.13	-	-	8.750	0.124	3.045	0.022
189	2434.24	-	-	9.030	0.126	3.091	0.022
190	2432.42	-	-	9.250	0.126	2.676	0.022
191	2430.62	-	-	8.830	0.127	2.691	0.022
192	2428.81	-	-	8.800	0.127	2.994	0.022
193	2427.03	-	-	8.820	0.128	3.359	0.022
194	2425.27	-	-	8.810	0.129	3.338	0.022
195	2423.51	-	-	8.940	0.129	3.114	0.022
196	2421.82	-	-	8.930	0.130	2.887	0.022
197	2420.12	-	-	9.000	0.131	3.209	0.022
198	2418.43	-	-	9.140	0.132	3.378	0.022
199	2416.74	-	-	9.070	0.132	2.873	0.022
200	2415.05	-	-	9.070	0.132	2.807	0.022
201	2413.36	-	-	9.140	0.133	2.887	0.022
202	2411.68	-	-	9.140	0.134	2.854	0.024
203	2410.00	-	-	9.210	0.135	2.996	0.023
204	2408.36	-	-	9.200	0.135	3.451	0.022
205	2406.72	-	-	9.310	0.132	3.263	0.021
206	2405.08	-	-	9.180	0.133	3.335	0.021
207	2403.48	-	-	9.290	0.132	3.225	0.021
208	2401.89	-	-	9.440	0.132	2.925	0.021
209	2400.31	-	-	9.320	0.131	3.248	0.020
210	2398.74	-	-	9.290	0.132	3.117	0.020
211	2397.17	-	-	9.280	0.132	3.533	0.019
212	2395.62	-	-	9.440	0.133	3.550	0.020

Continued on next page

Table 12 – continued from previous page - IEEE8500 - n1149

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
213	2394.08	-	-	9.290	0.134	3.641	0.019
214	2392.54	-	-	9.340	0.134	3.149	0.019
215	2391.03	-	-	9.320	0.135	3.023	0.020
216	2389.54	-	-	9.260	0.136	3.216	0.020
217	2388.07	-	-	9.340	0.136	3.378	0.020
218	2386.62	-	-	9.460	0.134	4.307	0.020
219	2385.19	-	-	9.340	0.134	3.032	0.020
220	2383.77	-	-	9.250	0.133	3.268	0.019
221	2382.35	-	-	9.210	0.134	2.830	0.020
222	2380.94	-	-	9.170	0.132	3.239	0.019
223	2379.54	-	-	9.020	0.132	2.800	0.019
224	2378.14	-	-	8.930	0.133	2.968	0.020
225	2376.75	-	-	8.980	0.134	3.112	0.020
226	2375.37	-	-	8.980	0.134	2.969	0.020
227	2374.03	-	-	8.850	0.135	3.293	0.020
228	2372.71	-	-	8.780	0.135	2.997	0.020
229	2371.38	-	-	8.780	0.136	2.894	0.020
230	2370.05	-	-	8.750	0.137	3.446	0.021
231	2368.73	-	-	8.830	0.137	3.554	0.023
232	2367.46	-	-	8.500	0.138	3.178	0.022
233	2366.18	-	-	8.510	0.138	3.381	0.021
234	2364.92	-	-	8.400	0.140	3.548	0.021
235	2363.67	-	-	8.340	0.140	3.579	0.021
236	2362.42	-	-	8.270	0.140	3.607	0.020
237	2361.18	-	-	8.420	0.141	3.740	0.020
238	2359.94	-	-	8.220	0.142	3.759	0.020
239	2358.72	-	-	8.310	0.142	3.947	0.020
240	2357.50	-	-	8.150	0.139	3.608	0.020
241	2356.29	-	-	8.060	0.140	4.124	0.020
242	2355.07	-	-	8.050	0.138	3.367	0.020
243	2353.87	-	-	8.150	0.138	3.235	0.019
244	2352.74	-	-	8.130	0.139	3.167	0.019
245	2351.63	-	-	8.290	0.139	3.374	0.019
246	2350.53	-	-	8.230	0.140	3.135	0.019
247	2349.43	-	-	8.260	0.141	3.201	0.019
248	2348.33	-	-	8.220	0.141	3.663	0.019
249	2347.24	-	-	8.210	0.142	3.748	0.018
250	2346.16	-	-	8.220	0.142	3.170	0.018
251	2345.08	-	-	8.260	0.143	3.786	0.019
252	2344.01	-	-	8.240	0.143	3.125	0.019
253	2342.97	-	-	8.130	0.144	3.854	0.018
254	2341.95	-	-	8.050	0.145	4.007	0.018
255	2340.94	-	-	8.030	0.146	4.208	0.019
256	2339.93	-	-	7.990	0.146	4.329	0.019
257	2338.93	-	-	8.090	0.146	4.447	0.019
258	2337.95	-	-	7.940	0.147	4.140	0.019
259	2336.97	-	-	7.990	0.148	4.329	0.019
260	2336.00	-	-	7.980	0.148	3.813	0.019
261	2335.02	-	-	7.920	0.149	3.680	0.021
262	2334.05	-	-	8.070	0.149	4.115	0.021
263	2333.07	-	-	8.060	0.151	4.240	0.020
264	2332.12	-	-	7.970	0.150	3.423	0.019

Continued on next page

Table 12 – continued from previous page - IEEE8500 - n1149

		Time (sec)					
m	best ENS	ILP-GALIAS	ILP-IFLOWS	DP-TS	DP-N2M2	ILP-CUTS	DP-PC
265	2331.17	-	-	8.270	0.151	4.124	0.019
266	2330.23	-	-	8.060	0.152	4.265	0.019
267	2329.30	-	-	8.090	0.153	3.674	0.019
268	2328.38	-	-	7.990	0.153	3.928	0.019
269	2327.45	-	-	8.030	0.153	3.356	0.019
270	2326.53	-	-	8.170	0.154	4.141	0.020
271	2325.61	-	-	8.020	0.155	3.942	0.020
272	2324.71	-	-	8.130	0.155	4.850	0.020
273	2323.81	-	-	8.140	0.155	3.930	0.020
274	2322.95	-	-	8.130	0.157	3.966	0.020
275	2322.10	-	-	8.250	0.157	5.303	0.021
276	2321.26	-	-	8.230	0.157	3.947	0.020
277	2320.43	-	-	8.210	0.158	4.024	0.020
278	2319.62	-	-	8.180	0.159	4.786	0.020
279	2318.82	-	-	8.310	0.155	5.057	0.020
280	2318.03	-	-	8.220	0.155	5.305	0.020
281	2317.25	-	-	8.340	0.153	4.221	0.019
282	2316.48	-	-	8.350	0.154	4.131	0.019
283	2315.72	-	-	8.320	0.154	4.152	0.019
284	2314.96	-	-	8.470	0.150	4.625	0.019
285	2314.21	-	-	8.280	0.151	4.443	0.019
286	2313.47	-	-	8.380	0.152	4.414	0.019
287	2312.73	-	-	8.500	0.152	4.368	0.019
288	2312.00	-	-	8.440	0.153	5.007	0.019
289	2311.27	-	-	8.490	0.154	4.244	0.019
290	2310.54	-	-	8.540	0.154	4.416	0.018
291	2309.82	-	-	8.590	0.154	4.652	0.020
292	2309.10	-	-	8.590	0.155	4.722	0.021
293	2308.39	-	-	8.640	0.156	3.769	0.020
294	2307.69	-	-	8.730	0.156	4.877	0.019
295	2307.00	-	-	8.610	0.156	4.449	0.019
296	2306.31	-	-	8.500	0.157	4.484	0.019
297	2305.63	-	-	8.680	0.158	4.686	0.019
298	2304.94	-	-	8.560	0.155	4.210	0.018
299	2304.27	-	-	8.590	0.155	4.890	0.018
300	2303.60	-	-	8.710	0.153	3.049	0.018
301	2302.94	-	-	8.690	0.154	4.190	0.018
302	2302.28	-	-	8.680	0.151	3.994	0.018
303	2301.63	-	-	8.740	0.152	4.910	0.018
304	2300.99	-	-	8.780	0.150	4.430	0.017
305	2300.36	-	-	8.660	0.151	6.540	0.017
306	2299.74	-	-	8.780	0.151	5.041	0.017
307	2299.13	-	-	9.040	0.151	5.510	0.017
308	2298.52	-	-	8.940	0.152	4.974	0.017
309	2297.93	-	-	9.430	0.153	4.474	0.017
310	2297.35	-	-	9.250	0.153	5.238	0.017
311	2296.77	-	-	8.880	0.153	5.405	0.017
312	2296.19	-	-	8.850	0.153	5.519	0.017
313	2295.63	-	-	8.790	0.155	5.041	0.017
314	2295.06	-	-	8.850	0.155	4.370	0.017
315	2294.50	-	-	8.760	0.155	5.581	0.017
316	2293.94	-	-	8.830	0.155	4.404	0.017

Continued on next page

Table 12 – continued from previous page - IEEE8500 - n1149

		Time (sec)					
m	best ENS	ILP-GALIAS	ILP-IFLOWS	DP-TS	DP-N2M2	ILP-CUTS	DP-PC
317	2293.38	-	-	8.770	0.151	4.675	0.016
318	2292.83	-	-	8.880	0.151	3.240	0.016
319	2292.29	-	-	8.840	0.149	4.710	0.015
320	2291.74	-	-	8.800	0.149	5.011	0.015
321	2291.20	-	-	8.860	0.148	4.895	0.015
322	2290.66	-	-	8.850	0.148	4.411	0.015
323	2290.12	-	-	8.880	0.146	4.780	0.016
324	2289.59	-	-	9.100	0.146	5.236	0.015
325	2289.06	-	-	8.970	0.145	6.565	0.018
326	2288.54	-	-	9.090	0.145	4.580	0.017
327	2288.02	-	-	9.140	0.145	4.820	0.016
328	2287.51	-	-	8.970	0.145	4.892	0.015
329	2287.01	-	-	9.010	0.147	4.174	0.015
330	2286.52	-	-	9.090	0.146	4.390	0.015
331	2286.03	-	-	9.040	0.147	3.227	0.015
332	2285.55	-	-	8.980	0.147	3.652	0.015
333	2285.07	-	-	8.920	0.148	4.398	0.015
334	2284.59	-	-	8.970	0.144	5.062	0.014
335	2284.12	-	-	9.050	0.144	4.585	0.014
336	2283.66	-	-	9.070	0.142	4.263	0.015
337	2283.20	-	-	9.110	0.143	4.075	0.015
338	2282.74	-	-	9.040	0.142	4.113	0.015
339	2282.28	-	-	9.040	0.143	5.390	0.014
340	2281.83	-	-	9.100	0.143	4.081	0.014
341	2281.38	-	-	9.020	0.144	4.820	0.014
342	2280.93	-	-	8.920	0.144	3.250	0.014
343	2280.49	-	-	8.860	0.144	3.361	0.014
344	2280.04	-	-	8.900	0.145	5.681	0.014
345	2279.60	-	-	8.920	0.145	3.614	0.015
346	2279.16	-	-	8.950	0.146	4.301	0.015
347	2278.71	-	-	8.800	0.146	3.675	0.015
348	2278.28	-	-	8.930	0.146	3.151	0.015
349	2277.84	-	-	8.870	0.147	3.786	0.015
350	2277.42	-	-	8.900	0.147	2.933	0.015
351	2276.99	-	-	8.860	0.147	5.489	0.015
352	2276.57	-	-	8.860	0.148	3.683	0.015
353	2276.15	-	-	8.760	0.149	3.202	0.015
354	2275.73	-	-	8.820	0.149	3.262	0.015
355	2275.33	-	-	8.860	0.148	3.648	0.015
356	2274.92	-	-	8.830	0.149	3.756	0.015
357	2274.52	-	-	8.830	0.150	3.638	0.015
358	2274.12	-	-	8.860	0.150	3.383	0.015
359	2273.73	-	-	8.810	0.150	6.073	0.015
360	2273.33	-	-	8.890	0.150	3.586	0.015
361	2272.95	-	-	8.960	0.151	3.749	0.015
362	2272.57	-	-	8.990	0.151	3.622	0.015
363	2272.19	-	-	8.860	0.152	4.581	0.015
364	2271.81	-	-	8.810	0.152	3.278	0.015
365	2271.44	-	-	9.090	0.153	3.463	0.017
366	2271.07	-	-	8.910	0.153	4.374	0.016
367	2270.71	-	-	8.900	0.153	3.361	0.015
368	2270.34	-	-	8.870	0.154	3.221	0.014

Continued on next page

Table 12 – continued from previous page - IEEE8500 - n1149

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
369	2269.98	-	-	9.020	0.154	4.270	0.014
370	2269.62	-	-	8.890	0.154	4.315	0.014
371	2269.27	-	-	8.910	0.155	4.337	0.014
372	2268.91	-	-	8.890	0.155	3.508	0.014
373	2268.55	-	-	8.950	0.155	3.933	0.014
374	2268.21	-	-	8.890	0.156	4.122	0.014
375	2267.86	-	-	9.100	0.156	4.006	0.014
376	2267.52	-	-	8.950	0.157	4.594	0.014
377	2267.18	-	-	9.080	0.157	4.043	0.014
378	2266.83	-	-	8.970	0.158	4.646	0.014
379	2266.49	-	-	8.940	0.158	4.240	0.014
380	2266.16	-	-	8.990	0.159	3.497	0.014
381	2265.83	-	-	8.930	0.159	4.245	0.014
382	2265.50	-	-	8.990	0.159	4.618	0.014
383	2265.18	-	-	9.140	0.160	4.058	0.015
384	2264.86	-	-	9.040	0.160	3.858	0.015
385	2264.54	-	-	9.030	0.160	3.979	0.014
386	2264.22	-	-	8.970	0.161	3.705	0.015
387	2263.90	-	-	8.960	0.162	3.528	0.015
388	2263.58	-	-	9.000	0.162	4.194	0.014
389	2263.27	-	-	8.920	0.162	4.376	0.014
390	2262.96	-	-	9.000	0.162	3.460	0.014
391	2262.65	-	-	9.060	0.163	3.838	0.015
392	2262.34	-	-	9.020	0.163	4.609	0.015
393	2262.03	-	-	9.000	0.164	4.187	0.015
394	2261.72	-	-	9.030	0.164	2.810	0.014
395	2261.41	-	-	9.030	0.164	4.217	0.014
396	2261.10	-	-	9.100	0.165	3.692	0.014
397	2260.80	-	-	9.090	0.165	3.745	0.014
398	2260.49	-	-	9.100	0.166	4.308	0.015
399	2260.18	-	-	9.200	0.166	3.336	0.014
400	2259.88	-	-	9.190	0.162	5.252	0.014
401	2259.57	-	-	9.040	0.162	3.722	0.014
402	2259.27	-	-	9.060	0.160	3.777	0.014
403	2258.97	-	-	9.100	0.160	3.413	0.014
404	2258.67	-	-	9.330	0.158	4.362	0.014
405	2258.37	-	-	9.120	0.159	3.877	0.016
406	2258.07	-	-	9.200	0.159	3.690	0.016
407	2257.77	-	-	9.110	0.160	3.482	0.015
408	2257.47	-	-	9.250	0.160	3.506	0.014
409	2257.18	-	-	9.100	0.160	4.091	0.014
410	2256.88	-	-	9.150	0.161	4.681	0.014
411	2256.59	-	-	9.290	0.161	4.033	0.014
412	2256.30	-	-	9.280	0.161	4.337	0.013
413	2256.00	-	-	9.280	0.162	3.725	0.014
414	2255.72	-	-	9.320	0.162	4.491	0.014
415	2255.43	-	-	9.620	0.163	3.268	0.014
416	2255.14	-	-	9.260	0.163	3.695	0.014
417	2254.86	-	-	9.690	0.161	4.305	0.014
418	2254.58	-	-	9.430	0.161	4.246	0.014
419	2254.29	-	-	9.420	0.159	3.970	0.014
420	2254.01	-	-	9.380	0.160	3.307	0.013

Continued on next page

Table 12 – continued from previous page - IEEE8500 - n1149

		Time (sec)					
m	best ENS	ILP-GALIAS	ILP-IFLOWS	DP-TS	DP-N2M2	ILP-CUTS	DP-PC
421	2253.73	-	-	9.500	0.160	4.171	0.013
422	2253.45	-	-	9.330	0.160	5.781	0.013
423	2253.17	-	-	9.450	0.158	4.519	0.014
424	2252.89	-	-	9.420	0.158	4.357	0.013
425	2252.62	-	-	9.410	0.156	4.627	0.013
426	2252.34	-	-	9.470	0.156	3.790	0.013
427	2252.08	-	-	9.520	0.155	5.037	0.013
428	2251.81	-	-	9.540	0.155	4.433	0.013
429	2251.54	-	-	9.540	0.153	3.903	0.012
430	2251.28	-	-	9.510	0.154	5.274	0.012
431	2251.01	-	-	9.500	0.152	3.460	0.012
432	2250.76	-	-	9.570	0.152	4.785	0.012
433	2250.50	-	-	9.550	0.153	3.844	0.012
434	2250.25	-	-	9.720	0.153	3.961	0.012
435	2249.99	-	-	9.660	0.153	3.274	0.012
436	2249.74	-	-	9.650	0.154	3.515	0.012
437	2249.49	-	-	9.770	0.154	3.776	0.013
438	2249.24	-	-	9.760	0.154	2.961	0.012
439	2248.99	-	-	9.710	0.152	3.500	0.012
440	2248.75	-	-	9.740	0.153	4.057	0.012
441	2248.51	-	-	9.640	0.153	3.740	0.012
442	2248.27	-	-	9.710	0.153	4.185	0.012
443	2248.03	-	-	9.770	0.152	5.529	0.012
444	2247.80	-	-	9.660	0.152	3.548	0.012
445	2247.56	-	-	9.800	0.150	3.147	0.012
446	2247.33	-	-	9.850	0.151	3.358	0.012
447	2247.10	-	-	9.740	0.149	4.062	0.011
448	2246.87	-	-	9.900	0.149	3.452	0.011
449	2246.64	-	-	9.850	0.148	4.645	0.012
450	2246.41	-	-	9.820	0.148	4.114	0.014
451	2246.19	-	-	9.890	0.148	3.754	0.013
452	2245.97	-	-	9.880	0.148	4.312	0.012
453	2245.76	-	-	9.990	0.149	3.493	0.012
454	2245.54	-	-	10.090	0.149	4.497	0.012
455	2245.32	-	-	9.950	0.150	3.485	0.011
456	2245.10	-	-	10.020	0.150	3.707	0.011
457	2244.88	-	-	9.950	0.150	4.585	0.011
458	2244.67	-	-	9.930	0.151	3.934	0.011
459	2244.45	-	-	9.970	0.149	3.602	0.011
460	2244.23	-	-	9.940	0.149	4.591	0.011
461	2244.02	-	-	10.050	0.148	5.357	0.011
462	2243.80	-	-	10.010	0.148	4.958	0.011
463	2243.59	-	-	10.090	0.148	4.664	0.010
464	2243.38	-	-	10.000	0.148	4.715	0.011
465	2243.17	-	-	10.020	0.140	4.631	0.010
466	2242.97	-	-	9.950	0.140	3.744	0.010
467	2242.76	-	-	10.020	0.141	5.102	0.010
468	2242.56	-	-	9.900	0.141	3.618	0.010
469	2242.36	-	-	9.900	0.141	4.382	0.009
470	2242.16	-	-	9.740	0.134	3.749	0.009
471	2241.96	-	-	9.780	0.134	4.495	0.009
472	2241.77	-	-	9.790	0.134	4.305	0.008

Continued on next page

Table 12 – continued from previous page - IEEE8500 - n1149

		Time (sec)					
m	best ENS	ILP-GALIAS	ILP-IFLOWS	DP-TS	DP-N2M2	ILP-CUTS	DP-PC
473	2241.57	-	-	10.110	0.127	4.088	0.008
474	2241.38	-	-	9.690	0.127	4.070	0.008
475	2241.19	-	-	9.850	0.123	4.341	0.007
476	2241.00	-	-	9.670	0.123	3.986	0.007
477	2240.81	-	-	9.720	0.118	4.274	0.007
478	2240.62	-	-	9.790	0.118	3.558	0.007
479	2240.43	-	-	9.600	0.119	4.355	0.006
480	2240.25	-	-	9.550	0.119	6.619	0.006
481	2240.06	-	-	9.510	0.114	4.015	0.006
482	2239.88	-	-	9.560	0.114	4.367	0.006
483	2239.70	-	-	9.370	0.109	4.465	0.006
484	2239.52	-	-	9.350	0.110	3.994	0.006
485	2239.35	-	-	9.450	0.110	6.832	0.006
486	2239.18	-	-	9.390	0.110	5.446	0.006
487	2239.01	-	-	9.340	0.110	5.087	0.006
488	2238.84	-	-	9.350	0.106	4.765	0.006
489	2238.67	-	-	9.260	0.106	4.841	0.006
490	2238.50	-	-	9.300	0.102	4.213	0.005
491	2238.34	-	-	9.110	0.102	4.504	0.005
492	2238.17	-	-	9.190	0.102	5.468	0.005
493	2238.01	-	-	9.140	0.102	4.748	0.005
494	2237.84	-	-	9.160	0.103	4.456	0.005
495	2237.68	-	-	9.020	0.103	5.075	0.005
496	2237.52	-	-	9.130	0.103	4.724	0.005
497	2237.36	-	-	9.090	0.103	5.080	0.005
498	2237.20	-	-	9.050	0.103	4.247	0.005
499	2237.04	-	-	9.130	0.104	4.568	0.005
500	2236.88	-	-	9.120	0.104	3.687	0.005
501	2236.72	-	-	9.010	0.104	6.407	0.005
502	2236.56	-	-	9.020	0.104	6.528	0.005
503	2236.41	-	-	9.010	0.104	3.833	0.005
504	2236.25	-	-	8.980	0.100	6.089	0.006
505	2236.09	-	-	8.920	0.100	4.325	0.006
506	2235.94	-	-	8.980	0.096	4.264	0.005
507	2235.78	-	-	9.000	0.096	4.640	0.005
508	2235.63	-	-	8.830	0.093	5.972	0.005
509	2235.47	-	-	8.860	0.093	3.841	0.004
510	2235.32	-	-	8.840	0.089	3.743	0.004
511	2235.17	-	-	8.890	0.089	4.056	0.004
512	2235.02	-	-	8.930	0.085	3.995	0.004
513	2234.87	-	-	8.860	0.085	4.408	0.004
514	2234.72	-	-	8.860	0.082	4.753	0.004
515	2234.57	-	-	8.750	0.082	5.818	0.004
516	2234.42	-	-	8.770	0.079	3.666	0.003
517	2234.28	-	-	8.790	0.079	3.974	0.003
518	2234.13	-	-	8.720	0.075	5.316	0.004
519	2233.99	-	-	8.660	0.075	5.013	0.003
520	2233.84	-	-	8.710	0.072	6.447	0.003
521	2233.70	-	-	8.800	0.072	5.007	0.003
522	2233.55	-	-	8.640	0.072	4.602	0.003
523	2233.41	-	-	8.640	0.072	5.161	0.003
524	2233.27	-	-	8.720	0.072	4.150	0.003

Continued on next page

Table 12 – continued from previous page - IEEE8500 - n1149

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
525	2233.14	-	-	8.590	0.073	5.699	0.003
526	2233.00	-	-	8.700	0.073	5.744	0.003
527	2232.86	-	-	8.580	0.073	6.064	0.003
528	2232.73	-	-	8.650	0.073	4.978	0.003
529	2232.59	-	-	8.550	0.073	3.642	0.003
530	2232.46	-	-	8.510	0.073	5.007	0.003
531	2232.32	-	-	8.640	0.073	4.655	0.003
532	2232.19	-	-	8.540	0.073	4.916	0.003
533	2232.05	-	-	8.590	0.074	4.327	0.003
534	2231.92	-	-	8.560	0.073	3.611	0.003
535	2231.79	-	-	8.680	0.068	3.214	0.003
536	2231.66	-	-	8.680	0.067	3.885	0.003
537	2231.53	-	-	8.680	0.064	5.995	0.002
538	2231.40	-	-	8.570	0.064	6.037	0.002
539	2231.27	-	-	8.720	0.064	3.946	0.003
540	2231.14	-	-	8.810	0.064	4.017	0.003
541	2231.01	-	-	8.580	0.064	4.695	0.004
542	2230.89	-	-	8.570	0.064	4.268	0.003
543	2230.76	-	-	8.600	0.064	3.151	0.003
544	2230.63	-	-	8.560	0.061	5.063	0.002
545	2230.51	-	-	8.570	0.061	5.880	0.003
546	2230.38	-	-	8.520	0.061	4.492	0.002
547	2230.26	-	-	8.520	0.061	4.342	0.002
548	2230.14	-	-	8.480	0.061	6.307	0.003
549	2230.01	-	-	8.510	0.061	5.157	0.002
550	2229.89	-	-	8.480	0.061	4.910	0.002
551	2229.77	-	-	8.460	0.061	4.892	0.002
552	2229.65	-	-	8.420	0.058	4.090	0.002
553	2229.53	-	-	8.440	0.058	3.232	0.002
554	2229.41	-	-	8.360	0.058	4.490	0.002
555	2229.29	-	-	8.430	0.058	4.270	0.002
556	2229.17	-	-	8.370	0.055	4.863	0.002
557	2229.06	-	-	8.420	0.055	4.058	0.002
558	2228.94	-	-	8.430	0.051	4.311	0.002
559	2228.82	-	-	8.500	0.051	5.974	0.002
560	2228.71	-	-	8.380	0.052	4.596	0.002
561	2228.59	-	-	8.370	0.051	4.055	0.002
562	2228.48	-	-	8.380	0.048	4.482	0.002
563	2228.36	-	-	8.340	0.048	4.339	0.002
564	2228.25	-	-	8.380	0.045	7.043	0.001
565	2228.14	-	-	8.460	0.045	3.707	0.001
566	2228.02	-	-	8.270	0.045	5.688	0.002
567	2227.91	-	-	8.280	0.045	4.692	0.001
568	2227.80	-	-	8.360	0.042	3.318	0.001
569	2227.69	-	-	8.340	0.042	4.370	0.001
570	2227.58	-	-	8.290	0.042	4.328	0.001
571	2227.47	-	-	8.350	0.042	4.472	0.001
572	2227.36	-	-	8.320	0.042	4.661	0.001
573	2227.25	-	-	8.310	0.042	4.417	0.001
574	2227.14	-	-	8.250	0.039	4.298	0.001
575	2227.03	-	-	8.240	0.039	3.883	0.001
576	2226.93	-	-	8.330	0.037	4.189	0.001

Continued on next page

Table 12 – continued from previous page - IEEE8500 - n1149

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
577	2226.82	-	-	8.230	0.036	5.164	0.001
578	2226.71	-	-	8.460	0.034	4.460	0.001
579	2226.60	-	-	8.170	0.034	3.817	0.001
580	2226.50	-	-	8.320	0.031	4.464	0.001
581	2226.39	-	-	8.180	0.031	4.218	0.001
582	2226.29	-	-	8.210	0.029	4.794	0.001
583	2226.18	-	-	8.230	0.029	5.587	0.001
584	2226.08	-	-	8.230	0.029	4.797	0.001
585	2225.98	-	-	8.290	0.029	7.276	0.001
586	2225.88	-	-	8.250	0.026	5.413	0.001
587	2225.78	-	-	8.350	0.026	4.746	0.001
588	2225.68	-	-	8.220	0.024	4.543	0.001
589	2225.58	-	-	8.290	0.024	4.344	0.001
590	2225.48	-	-	8.390	0.022	4.010	0.001
591	2225.38	-	-	8.460	0.022	4.963	0.001
592	2225.28	-	-	8.120	0.020	4.926	0.000
593	2225.19	-	-	8.220	0.020	5.416	0.000
594	2225.09	-	-	8.100	0.020	3.445	0.001
595	2224.99	-	-	7.990	0.020	4.649	0.000
596	2224.90	-	-	7.990	0.020	4.315	0.000
597	2224.80	-	-	7.890	0.020	4.564	0.000
598	2224.71	-	-	7.910	0.020	5.623	0.000
599	2224.61	-	-	7.920	0.020	4.568	0.000
600	2224.52	-	-	7.750	0.020	3.562	0.000
601	2224.43	-	-	7.640	0.020	4.659	0.000
602	2224.34	-	-	7.630	0.020	4.184	0.000
603	2224.25	-	-	7.570	0.020	4.559	0.000
604	2224.16	-	-	7.570	0.020	3.230	0.000
605	2224.07	-	-	7.540	0.020	4.037	0.000
606	2223.98	-	-	7.490	0.020	3.967	0.000
607	2223.89	-	-	7.380	0.020	3.516	0.000
608	2223.81	-	-	7.410	0.020	4.274	0.001
609	2223.72	-	-	7.400	0.020	4.624	0.001
610	2223.63	-	-	7.340	0.020	3.321	0.000
611	2223.54	-	-	7.370	0.020	3.428	0.000
612	2223.46	-	-	7.170	0.020	4.375	0.000
613	2223.37	-	-	7.200	0.020	3.368	0.000
614	2223.29	-	-	7.170	0.020	4.038	0.000
615	2223.20	-	-	7.280	0.020	5.192	0.000
616	2223.12	-	-	7.240	0.020	4.724	0.000
617	2223.03	-	-	7.100	0.020	4.365	0.000
618	2222.95	-	-	7.030	0.020	4.524	0.000
619	2222.87	-	-	7.000	0.020	3.923	0.000
620	2222.78	-	-	6.910	0.021	3.503	0.001
621	2222.70	-	-	6.910	0.021	3.799	0.001
622	2222.62	-	-	6.830	0.021	3.782	0.000
623	2222.54	-	-	6.730	0.021	4.580	0.000
624	2222.46	-	-	6.720	0.021	4.700	0.000
625	2222.37	-	-	6.580	0.021	4.198	0.000
626	2222.29	-	-	6.570	0.021	5.460	0.000
627	2222.21	-	-	6.520	0.021	4.648	0.000
628	2222.13	-	-	6.480	0.021	3.644	0.000

Continued on next page

Table 12 – continued from previous page - IEEE8500 - n1149

		Time (sec)					
m	best ENS	ILP-GALIAS	ILP-IFLOWS	DP-TS	DP-N2M2	ILP-CUTS	DP-PC
629	2222.05	-	-	6.490	0.021	6.017	0.000
630	2221.97	-	-	6.530	0.021	4.331	0.000
631	2221.89	-	-	6.390	0.021	4.619	0.000
632	2221.81	-	-	6.380	0.021	4.159	0.000
633	2221.73	-	-	6.330	0.021	3.798	0.000
634	2221.65	-	-	6.380	0.021	4.386	0.000
635	2221.57	-	-	6.230	0.021	5.511	0.001
636	2221.49	-	-	6.270	0.021	4.883	0.000
637	2221.42	-	-	6.190	0.021	4.138	0.000
638	2221.34	-	-	6.150	0.021	5.095	0.000
639	2221.26	-	-	6.160	0.021	4.452	0.001
640	2221.19	-	-	6.140	0.021	3.760	0.000
641	2221.11	-	-	6.100	0.021	3.841	0.000
642	2221.03	-	-	6.080	0.021	3.754	0.000
643	2220.96	-	-	6.100	0.021	3.774	0.000
644	2220.88	-	-	6.060	0.021	3.762	0.000
645	2220.81	-	-	5.990	0.021	4.573	0.000
646	2220.74	-	-	6.040	0.021	4.450	0.000
647	2220.66	-	-	6.040	0.021	4.555	0.000
648	2220.59	-	-	5.930	0.021	3.812	0.000
649	2220.51	-	-	5.940	0.022	3.788	0.000
650	2220.44	-	-	5.910	0.022	3.869	0.000
651	2220.37	-	-	5.890	0.022	3.921	0.000
652	2220.30	-	-	5.870	0.022	4.475	0.000
653	2220.22	-	-	5.890	0.022	5.169	0.000
654	2220.15	-	-	5.790	0.022	4.280	0.000
655	2220.08	-	-	5.810	0.022	3.554	0.000
656	2220.01	-	-	5.750	0.022	3.981	0.001
657	2219.94	-	-	5.780	0.022	4.823	0.000
658	2219.87	-	-	5.770	0.022	3.447	0.000
659	2219.80	-	-	5.700	0.022	3.812	0.000
660	2219.73	-	-	5.660	0.022	3.791	0.000
661	2219.66	-	-	5.730	0.022	4.189	0.000
662	2219.59	-	-	5.640	0.022	3.994	0.000
663	2219.52	-	-	5.640	0.022	6.643	0.000
664	2219.45	-	-	5.640	0.022	5.941	0.000
665	2219.38	-	-	5.610	0.022	4.281	0.000
666	2219.31	-	-	5.600	0.022	3.406	0.001
667	2219.24	-	-	5.550	0.022	5.123	0.000
668	2219.17	-	-	5.510	0.022	5.946	0.000
669	2219.11	-	-	5.460	0.022	4.053	0.001
670	2219.04	-	-	5.520	0.022	4.430	0.000
671	2218.97	-	-	5.430	0.022	6.351	0.000
672	2218.91	-	-	5.440	0.022	3.599	0.000
673	2218.84	-	-	5.500	0.022	3.904	0.000
674	2218.77	-	-	5.390	0.022	3.489	0.000
675	2218.71	-	-	5.350	0.023	4.229	0.000
676	2218.64	-	-	5.360	0.023	4.358	0.000
677	2218.58	-	-	5.280	0.023	4.043	0.000
678	2218.51	-	-	5.260	0.023	4.935	0.000
679	2218.45	-	-	5.370	0.023	3.766	0.000
680	2218.38	-	-	5.250	0.023	3.684	0.001

Continued on next page

Table 12 – continued from previous page - IEEE8500 - n1149

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
681	2218.32	-	-	5.200	0.023	3.210	0.000
682	2218.25	-	-	5.140	0.023	4.125	0.000
683	2218.19	-	-	5.170	0.023	6.195	0.000
684	2218.12	-	-	5.170	0.023	2.469	0.000
685	2218.06	-	-	5.170	0.023	2.727	0.000
686	2218.00	-	-	5.090	0.023	4.282	0.000
687	2217.93	-	-	5.110	0.023	3.695	0.001
688	2217.87	-	-	5.030	0.023	5.010	0.000
689	2217.81	-	-	5.080	0.023	3.392	0.000
690	2217.75	-	-	5.060	0.023	4.650	0.000
691	2217.68	-	-	5.000	0.023	2.632	0.000
692	2217.62	-	-	5.010	0.023	4.730	0.000
693	2217.56	-	-	4.950	0.023	3.898	0.000
694	2217.50	-	-	4.980	0.023	4.493	0.000
695	2217.44	-	-	4.940	0.023	3.061	0.000
696	2217.38	-	-	4.890	0.023	2.794	0.000
697	2217.32	-	-	4.910	0.023	2.662	0.000
698	2217.27	-	-	4.920	0.023	2.407	0.000
699	2217.21	-	-	4.920	0.023	3.164	0.000
700	2217.15	-	-	4.810	0.023	3.494	0.000
701	2217.09	-	-	4.840	0.023	1.739	0.000
702	2217.04	-	-	4.850	0.023	3.936	0.000
703	2216.98	-	-	4.800	0.024	2.896	0.000
704	2216.92	-	-	4.830	0.024	2.823	0.000
705	2216.87	-	-	4.730	0.023	3.168	0.000
706	2216.81	-	-	4.790	0.024	0.730	0.000
707	2216.75	-	-	4.770	0.024	1.320	0.000
708	2216.70	-	-	4.830	0.024	0.526	0.000
709	2216.64	-	-	5.000	0.024	1.405	0.000
710	2216.59	-	-	4.940	0.024	1.449	0.001
711	2216.53	-	-	4.690	0.024	1.134	0.000
712	2216.47	-	-	4.690	0.024	0.828	0.000
713	2216.42	-	-	4.750	0.024	1.050	0.000
714	2216.36	-	-	4.680	0.024	2.082	0.000
715	2216.31	-	-	4.890	0.024	1.023	0.000
716	2216.26	-	-	4.610	0.024	0.452	0.000
717	2216.20	-	-	4.660	0.024	1.377	0.000
718	2216.15	-	-	4.580	0.024	1.047	0.000
719	2216.10	-	-	4.520	0.024	1.128	0.000
720	2216.04	-	-	4.550	0.024	1.016	0.000
721	2215.99	-	-	4.520	0.024	1.125	0.000
722	2215.94	-	-	4.470	0.024	0.878	0.000
723	2215.88	-	-	4.470	0.024	1.018	0.000
724	2215.83	-	-	4.430	0.024	1.034	0.000
725	2215.78	-	-	4.420	0.024	1.055	0.000
726	2215.73	-	-	4.400	0.024	0.386	0.000
727	2215.68	-	-	4.410	0.024	1.203	0.000
728	2215.63	-	-	4.450	0.024	0.725	0.001
729	2215.57	-	-	4.310	0.024	1.176	0.001
730	2215.52	-	-	4.270	0.024	1.340	0.000
731	2215.47	-	-	4.370	0.024	0.657	0.000
732	2215.42	-	-	4.270	0.024	1.242	0.000

Continued on next page

Table 12 – continued from previous page - IEEE8500 - n1149

		Time (sec)					
m	best ENS	ILP-GALIAS	ILP-IFLOWS	DP-TS	DP-N2M2	ILP-CUTS	DP-PC
733	2215.37	-	-	4.290	0.024	0.640	0.000
734	2215.32	-	-	4.320	0.025	1.015	0.000
735	2215.27	-	-	4.180	0.025	0.617	0.000
736	2215.22	-	-	4.210	0.025	1.180	0.000
737	2215.17	-	-	4.120	0.025	1.212	0.000
738	2215.12	-	-	4.130	0.025	1.281	0.000
739	2215.07	-	-	4.120	0.025	0.826	0.000
740	2215.02	-	-	4.100	0.025	0.686	0.000
741	2214.98	-	-	4.110	0.025	1.066	0.000
742	2214.93	-	-	4.080	0.025	0.323	0.000
743	2214.88	-	-	4.020	0.025	0.961	0.000
744	2214.83	-	-	4.020	0.025	0.921	0.000
745	2214.79	-	-	4.000	0.025	0.794	0.000
746	2214.74	-	-	4.000	0.025	1.127	0.000
747	2214.69	-	-	3.950	0.025	1.092	0.001
748	2214.64	-	-	3.990	0.025	0.564	0.000
749	2214.60	-	-	3.930	0.025	0.955	0.000
750	2214.55	-	-	3.900	0.025	1.020	0.000
751	2214.50	-	-	3.910	0.025	0.914	0.000
752	2214.46	-	-	3.870	0.025	0.319	0.000
753	2214.41	-	-	3.920	0.025	0.793	0.000
754	2214.37	-	-	3.770	0.025	0.990	0.000
755	2214.32	-	-	3.800	0.025	0.999	0.000
756	2214.28	-	-	3.800	0.025	1.060	0.001
757	2214.23	-	-	3.740	0.025	0.935	0.000
758	2214.19	-	-	3.720	0.025	0.969	0.000
759	2214.14	-	-	3.690	0.025	0.955	0.000
760	2214.10	-	-	3.750	0.025	0.435	0.000
761	2214.05	-	-	3.660	0.025	0.977	0.000
762	2214.01	-	-	3.700	0.025	1.079	0.000
763	2213.96	-	-	3.750	0.025	1.019	0.000
764	2213.92	-	-	3.590	0.025	1.124	0.000
765	2213.87	-	-	3.700	0.026	1.020	0.000
766	2213.83	-	-	3.590	0.026	1.171	0.000
767	2213.79	-	-	3.560	0.026	0.819	0.000
768	2213.74	-	-	3.500	0.026	1.282	0.000
769	2213.70	-	-	3.540	0.026	0.803	0.000
770	2213.66	-	-	3.490	0.026	1.088	0.000
771	2213.61	-	-	3.460	0.026	0.962	0.000
772	2213.57	-	-	3.500	0.026	1.031	0.000
773	2213.53	-	-	3.520	0.026	1.019	0.000
774	2213.48	-	-	3.440	0.026	0.950	0.000
775	2213.44	-	-	3.420	0.026	0.915	0.000
776	2213.40	-	-	3.390	0.026	1.024	0.000
777	2213.36	-	-	3.410	0.026	0.851	0.001
778	2213.31	-	-	3.380	0.026	1.062	0.000
779	2213.27	-	-	3.360	0.026	1.247	0.000
780	2213.23	-	-	3.340	0.026	1.081	0.000
781	2213.19	-	-	3.390	0.026	1.004	0.000
782	2213.15	-	-	3.280	0.026	0.962	0.000
783	2213.10	-	-	3.320	0.026	0.862	0.000
784	2213.06	-	-	3.280	0.026	0.869	0.000

Continued on next page

Table 12 – continued from previous page - IEEE8500 - n1149

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
785	2213.02	-	-	3.300	0.026	0.859	0.000
786	2212.98	-	-	3.330	0.026	0.895	0.000
787	2212.94	-	-	3.230	0.026	0.315	0.000
788	2212.90	-	-	3.200	0.026	0.834	0.000
789	2212.86	-	-	3.320	0.026	0.737	0.000
790	2212.82	-	-	3.190	0.026	1.068	0.000
791	2212.78	-	-	3.180	0.026	0.804	0.000
792	2212.74	-	-	3.170	0.026	1.255	0.000
793	2212.70	-	-	3.140	0.027	0.919	0.000
794	2212.66	-	-	3.140	0.027	0.950	0.000
795	2212.62	-	-	3.120	0.027	0.691	0.000
796	2212.59	-	-	3.130	0.027	0.853	0.000
797	2212.55	-	-	3.150	0.027	0.247	0.000
798	2212.51	-	-	3.080	0.027	0.767	0.000
799	2212.47	-	-	3.080	0.027	0.316	0.000
800	2212.44	-	-	3.080	0.027	0.934	0.000
801	2212.40	-	-	3.040	0.027	0.315	0.000
802	2212.36	-	-	3.040	0.027	0.315	0.000
803	2212.32	-	-	3.070	0.027	0.301	0.000
804	2212.28	-	-	3.030	0.027	0.840	0.000
805	2212.25	-	-	3.010	0.027	0.860	0.000
806	2212.21	-	-	3.010	0.027	0.900	0.000
807	2212.17	-	-	3.010	0.027	0.273	0.000
808	2212.14	-	-	2.960	0.027	0.645	0.000
809	2212.10	-	-	3.000	0.027	0.842	0.000
810	2212.06	-	-	2.990	0.027	0.478	0.000
811	2212.03	-	-	2.950	0.027	1.108	0.000
812	2211.99	-	-	2.950	0.027	0.711	0.000
813	2211.95	-	-	2.940	0.027	0.879	0.000
814	2211.92	-	-	2.940	0.027	0.775	0.000
815	2211.88	-	-	2.960	0.027	0.947	0.000
816	2211.85	-	-	2.920	0.027	1.169	0.000
817	2211.81	-	-	2.910	0.027	0.571	0.000
818	2211.78	-	-	3.020	0.027	0.846	0.001
819	2211.74	-	-	2.870	0.027	0.851	0.000
820	2211.71	-	-	2.840	0.028	0.707	0.000
821	2211.67	-	-	2.970	0.027	0.654	0.000
822	2211.64	-	-	2.910	0.028	0.813	0.001
823	2211.60	-	-	2.820	0.028	0.856	0.000
824	2211.57	-	-	2.780	0.028	0.916	0.000
825	2211.53	-	-	2.780	0.028	1.005	0.000
826	2211.50	-	-	2.820	0.028	0.496	0.000
827	2211.47	-	-	2.730	0.028	0.772	0.000
828	2211.43	-	-	2.770	0.028	0.738	0.000
829	2211.40	-	-	2.800	0.028	0.287	0.000
830	2211.36	-	-	2.800	0.028	0.824	0.000
831	2211.33	-	-	2.750	0.028	0.633	0.000
832	2211.30	-	-	2.720	0.028	0.509	0.000
833	2211.26	-	-	2.720	0.028	0.672	0.000
834	2211.23	-	-	2.750	0.028	0.642	0.000
835	2211.20	-	-	2.720	0.028	0.584	0.000
836	2211.17	-	-	2.720	0.028	0.506	0.000

Continued on next page

Table 12 – continued from previous page - IEEE8500 - n1149

		Time (sec)					
m	best ENS	ILP-GALIAS	ILP-IFLOWS	DP-TS	DP-N2M2	ILP-CUTS	DP-PC
837	2211.13	-	-	2.710	0.028	0.524	0.000
838	2211.10	-	-	2.630	0.028	0.489	0.000
839	2211.07	-	-	2.670	0.028	0.739	0.000
840	2211.04	-	-	2.700	0.028	0.630	0.000
841	2211.01	-	-	2.630	0.028	0.701	0.000
842	2210.98	-	-	2.610	0.028	0.397	0.000
843	2210.94	-	-	2.600	0.028	0.625	0.000
844	2210.91	-	-	2.590	0.028	0.295	0.000
845	2210.88	-	-	2.580	0.028	0.548	0.000
846	2210.85	-	-	2.570	0.028	0.352	0.000
847	2210.82	-	-	2.560	0.028	0.359	0.000
848	2210.79	-	-	2.530	0.028	0.656	0.000
849	2210.76	-	-	2.520	0.029	0.461	0.000
850	2210.73	-	-	2.500	0.029	0.513	0.000
851	2210.70	-	-	2.530	0.029	0.598	0.000
852	2210.67	-	-	2.470	0.029	0.534	0.000
853	2210.64	-	-	2.470	0.029	0.484	0.000
854	2210.61	-	-	2.460	0.029	0.521	0.000
855	2210.58	-	-	2.500	0.029	0.584	0.000
856	2210.55	-	-	2.470	0.029	0.380	0.000
857	2210.52	-	-	2.420	0.029	0.446	0.000
858	2210.50	-	-	2.430	0.029	0.375	0.000
859	2210.47	-	-	2.420	0.029	0.538	0.000
860	2210.44	-	-	2.410	0.029	0.718	0.000
861	2210.41	-	-	2.390	0.029	0.388	0.000
862	2210.38	-	-	2.360	0.029	0.304	0.000
863	2210.35	-	-	2.350	0.029	0.589	0.001
864	2210.33	-	-	2.350	0.029	0.608	0.000
865	2210.30	-	-	2.340	0.029	0.515	0.000
866	2210.27	-	-	2.330	0.029	0.388	0.000
867	2210.24	-	-	2.300	0.029	0.626	0.000
868	2210.22	-	-	2.270	0.029	0.672	0.000
869	2210.19	-	-	2.260	0.029	0.278	0.000
870	2210.16	-	-	2.260	0.029	0.523	0.000
871	2210.13	-	-	2.280	0.029	0.362	0.000
872	2210.11	-	-	2.250	0.029	0.468	0.000
873	2210.08	-	-	2.240	0.029	0.258	0.000
874	2210.05	-	-	2.240	0.029	0.518	0.000
875	2210.03	-	-	2.250	0.029	0.282	0.000
876	2210.00	-	-	2.220	0.029	0.620	0.000
877	2209.98	-	-	2.200	0.029	0.282	0.000
878	2209.95	-	-	2.200	0.029	0.588	0.000
879	2209.92	-	-	2.200	0.030	0.428	0.000
880	2209.90	-	-	2.200	0.030	0.207	0.000
881	2209.87	-	-	2.170	0.030	0.620	0.000
882	2209.85	-	-	2.200	0.030	0.468	0.000
883	2209.82	-	-	2.180	0.030	0.342	0.000
884	2209.80	-	-	2.190	0.030	0.569	0.000
885	2209.77	-	-	2.170	0.030	0.668	0.000
886	2209.74	-	-	2.130	0.030	0.230	0.000
887	2209.72	-	-	2.140	0.030	0.651	0.000
888	2209.70	-	-	2.140	0.030	0.452	0.000

Continued on next page

Table 12 – continued from previous page - IEEE8500 - n1149

		Time (sec)					
m	best ENS	ILP-GALIAS	ILP-IFLOWS	DP-TS	DP-N2M2	ILP-CUTS	DP-PC
889	2209.67	-	-	2.140	0.030	0.568	0.000
890	2209.65	-	-	2.100	0.030	0.378	0.000
891	2209.62	-	-	2.080	0.030	0.529	0.000
892	2209.60	-	-	2.080	0.030	0.535	0.000
893	2209.58	-	-	2.070	0.030	0.323	0.000
894	2209.55	-	-	2.070	0.030	0.279	0.000
895	2209.53	-	-	2.070	0.030	0.291	0.000
896	2209.50	-	-	2.070	0.030	0.652	0.000
897	2209.48	-	-	2.080	0.030	0.563	0.000
898	2209.46	-	-	2.040	0.030	0.210	0.000
899	2209.43	-	-	2.030	0.030	0.277	0.000
900	2209.41	-	-	2.010	0.030	0.537	0.000
901	2209.39	-	-	2.010	0.032	0.612	0.000
902	2209.36	-	-	2.040	0.031	0.445	0.000
903	2209.34	-	-	1.970	0.031	0.149	0.000
904	2209.32	-	-	1.970	0.031	0.208	0.000
905	2209.30	-	-	1.970	0.031	0.551	0.000
906	2209.27	-	-	1.980	0.031	0.624	0.000
907	2209.25	-	-	1.950	0.031	0.128	0.000
908	2209.23	-	-	1.940	0.031	0.179	0.000
909	2209.21	-	-	1.930	0.031	0.195	0.000
910	2209.18	-	-	1.940	0.031	0.483	0.000
911	2209.16	-	-	1.900	0.031	0.129	0.000
912	2209.14	-	-	1.920	0.031	0.577	0.001
913	2209.12	-	-	1.920	0.031	0.622	0.000
914	2209.10	-	-	1.890	0.031	0.582	0.000
915	2209.07	-	-	1.890	0.031	0.527	0.000
916	2209.05	-	-	1.910	0.031	0.570	0.000
917	2209.03	-	-	1.870	0.031	0.607	0.000
918	2209.01	-	-	1.890	0.031	0.694	0.000
919	2208.99	-	-	1.850	0.031	0.120	0.000
920	2208.97	-	-	1.810	0.031	0.566	0.000
921	2208.95	-	-	1.830	0.032	0.530	0.000
922	2208.93	-	-	1.820	0.032	0.245	0.000
923	2208.91	-	-	1.800	0.032	0.442	0.000
924	2208.89	-	-	1.790	0.032	0.201	0.000
925	2208.87	-	-	1.810	0.032	0.627	0.000
926	2208.84	-	-	1.790	0.032	0.600	0.000
927	2208.82	-	-	1.770	0.032	0.526	0.000
928	2208.80	-	-	1.780	0.032	0.578	0.000
929	2208.78	-	-	1.760	0.032	0.573	0.000
930	2208.77	-	-	1.720	0.032	0.378	0.001
931	2208.75	-	-	1.730	0.032	0.193	0.000
932	2208.73	-	-	1.730	0.032	0.151	0.000
933	2208.71	-	-	1.750	0.032	0.337	0.000
934	2208.69	-	-	1.710	0.032	0.130	0.000
935	2208.67	-	-	1.720	0.032	0.281	0.000
936	2208.65	-	-	1.700	0.032	0.479	0.000
937	2208.63	-	-	1.680	0.032	0.160	0.000
938	2208.61	-	-	1.700	0.032	0.152	0.000
939	2208.59	-	-	1.660	0.032	0.425	0.000
940	2208.58	-	-	1.650	0.032	0.386	0.000

Continued on next page

Table 12 – continued from previous page - IEEE8500 - n1149

		Time (sec)					
m	best ENS	ILP-GALIAS	ILP-IFLOWS	DP-TS	DP-N2M2	ILP-CUTS	DP-PC
941	2208.56	-	-	1.640	0.032	0.388	0.000
942	2208.54	-	-	1.630	0.032	0.329	0.000
943	2208.52	-	-	1.640	0.032	0.395	0.000
944	2208.50	-	-	1.620	0.032	0.462	0.000
945	2208.49	-	-	1.580	0.032	0.123	0.000
946	2208.47	-	-	1.600	0.032	0.204	0.000
947	2208.45	-	-	1.600	0.032	0.421	0.000
948	2208.43	-	-	1.590	0.032	0.169	0.000
949	2208.42	-	-	1.550	0.033	0.296	0.000
950	2208.40	-	-	1.580	0.033	0.151	0.000
951	2208.38	-	-	1.540	0.032	0.361	0.000
952	2208.36	-	-	1.570	0.033	0.100	0.000
953	2208.35	-	-	1.530	0.033	0.117	0.000
954	2208.33	-	-	1.540	0.033	0.114	0.000
955	2208.31	-	-	1.510	0.033	0.252	0.000
956	2208.30	-	-	1.500	0.033	0.364	0.000
957	2208.28	-	-	1.460	0.033	0.375	0.000
958	2208.26	-	-	1.500	0.033	0.241	0.000
959	2208.25	-	-	1.470	0.033	0.284	0.000
960	2208.23	-	-	1.460	0.033	0.112	0.000
961	2208.21	-	-	1.470	0.033	0.099	0.000
962	2208.20	-	-	1.450	0.033	0.105	0.000
963	2208.18	-	-	1.420	0.033	0.130	0.000
964	2208.17	-	-	1.430	0.033	0.107	0.000
965	2208.15	-	-	1.410	0.033	0.177	0.000
966	2208.13	-	-	1.380	0.033	0.104	0.000
967	2208.12	-	-	1.390	0.033	0.151	0.000
968	2208.10	-	-	1.350	0.033	0.144	0.000
969	2208.09	-	-	1.330	0.033	0.103	0.000
970	2208.07	-	-	1.340	0.033	0.174	0.000
971	2208.06	-	-	1.330	0.033	0.099	0.000
972	2208.04	-	-	1.310	0.033	0.276	0.000
973	2208.03	-	-	1.300	0.033	0.103	0.000
974	2208.01	-	-	1.290	0.034	0.106	0.000
975	2207.99	-	-	1.300	0.034	0.143	0.000
976	2207.98	-	-	1.290	0.033	0.101	0.000
977	2207.96	-	-	1.280	0.033	0.159	0.000
978	2207.95	-	-	1.240	0.033	0.110	0.000
979	2207.93	-	-	1.260	0.034	0.097	0.000
980	2207.92	-	-	1.220	0.034	0.193	0.000
981	2207.90	-	-	1.230	0.033	0.129	0.000
982	2207.89	-	-	1.200	0.034	0.144	0.000
983	2207.87	-	-	1.190	0.034	0.141	0.000
984	2207.86	-	-	1.170	0.034	0.110	0.000
985	2207.84	-	-	1.180	0.034	0.107	0.000
986	2207.83	-	-	1.190	0.034	0.160	0.000
987	2207.82	-	-	1.150	0.034	0.187	0.000
988	2207.80	-	-	1.140	0.034	0.099	0.000
989	2207.79	-	-	1.150	0.034	0.092	0.000
990	2207.77	-	-	1.110	0.034	0.100	0.000
991	2207.76	-	-	1.110	0.034	0.096	0.000
992	2207.74	-	-	1.090	0.034	0.090	0.000

Continued on next page

Table 12 – continued from previous page - IEEE8500 - n1149

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
993	2207.73	-	-	1.110	0.034	0.125	0.000
994	2207.72	-	-	1.070	0.034	0.122	0.000
995	2207.70	-	-	1.060	0.034	0.128	0.000
996	2207.69	-	-	1.070	0.034	0.128	0.000
997	2207.67	-	-	1.040	0.034	0.116	0.000
998	2207.66	-	-	1.030	0.034	0.124	0.000
999	2207.65	-	-	1.030	0.034	0.112	0.000
1000	2207.63	-	-	1.000	0.034	0.118	0.000
1001	2207.62	-	-	1.000	0.034	0.128	0.000
1002	2207.61	-	-	0.980	0.034	0.115	0.000
1003	2207.59	-	-	0.970	0.034	0.115	0.000
1004	2207.58	-	-	0.970	0.034	0.120	0.000
1005	2207.57	-	-	0.950	0.034	0.110	0.000
1006	2207.55	-	-	0.940	0.034	0.119	0.000
1007	2207.54	-	-	0.930	0.034	0.125	0.000
1008	2207.53	-	-	0.930	0.034	0.124	0.000
1009	2207.51	-	-	0.920	0.034	0.120	0.000
1010	2207.50	-	-	0.900	0.035	0.122	0.000
1011	2207.49	-	-	0.890	0.034	0.114	0.000
1012	2207.48	-	-	0.890	0.035	0.129	0.000
1013	2207.46	-	-	0.870	0.035	0.112	0.000
1014	2207.45	-	-	0.860	0.035	0.116	0.000
1015	2207.44	-	-	0.840	0.035	0.119	0.000
1016	2207.43	-	-	0.850	0.035	0.116	0.000
1017	2207.42	-	-	0.810	0.035	0.123	0.000
1018	2207.40	-	-	0.810	0.035	0.114	0.000
1019	2207.39	-	-	0.800	0.035	0.112	0.000
1020	2207.38	-	-	0.800	0.035	0.116	0.000
1021	2207.37	-	-	0.780	0.035	0.114	0.000
1022	2207.36	-	-	0.780	0.035	0.113	0.000
1023	2207.34	-	-	0.760	0.035	0.110	0.000
1024	2207.33	-	-	0.750	0.035	0.112	0.000
1025	2207.32	-	-	0.790	0.035	0.115	0.000
1026	2207.31	-	-	0.740	0.035	0.114	0.000
1027	2207.30	-	-	0.720	0.035	0.113	0.000
1028	2207.29	-	-	0.710	0.035	0.106	0.000
1029	2207.28	-	-	0.700	0.035	0.109	0.000
1030	2207.27	-	-	0.690	0.035	0.112	0.000
1031	2207.26	-	-	0.670	0.035	0.116	0.000
1032	2207.25	-	-	0.660	0.035	0.117	0.000
1033	2207.24	-	-	0.650	0.035	0.113	0.000
1034	2207.23	-	-	0.670	0.035	0.126	0.000
1035	2207.22	-	-	0.630	0.035	0.109	0.000
1036	2207.20	-	-	0.600	0.035	0.112	0.000
1037	2207.19	-	-	0.610	0.035	0.123	0.000
1038	2207.18	-	-	0.590	0.035	0.106	0.000
1039	2207.17	-	-	0.570	0.035	0.169	0.000
1040	2207.16	-	-	0.560	0.035	0.100	0.000
1041	2207.15	-	-	0.550	0.036	0.094	0.000
1042	2207.15	-	-	0.540	0.036	0.105	0.000
1043	2207.14	-	-	0.520	0.036	0.164	0.000
1044	2207.13	-	-	0.510	0.036	0.174	0.000

Continued on next page

Table 12 – continued from previous page - IEEE8500 - n1149

		Time (sec)					
m	best ENS	ILP-GALIAS	ILP-IFLOWS	DP-TS	DP-N2M2	ILP-CUTS	DP-PC
1045	2207.12	-	-	0.500	0.036	0.158	0.000
1046	2207.11	-	-	0.480	0.036	0.153	0.000
1047	2207.10	-	-	0.480	0.036	0.173	0.000
1048	2207.09	-	-	0.460	0.036	0.167	0.000
1049	2207.08	-	-	0.450	0.036	0.160	0.000
1050	2207.07	-	-	0.450	0.036	0.159	0.000
1051	2207.06	-	-	0.430	0.036	0.124	0.000
1052	2207.05	-	-	0.410	0.036	0.167	0.000
1053	2207.05	-	-	0.420	0.036	0.133	0.000
1054	2207.04	-	-	0.410	0.035	0.130	0.000
1055	2207.03	-	-	0.410	0.027	0.124	0.000
1056	2207.02	-	-	0.420	0.026	0.126	0.000
1057	2207.01	-	-	0.410	0.024	0.110	0.000
1058	2207.00	-	-	0.400	0.024	0.111	0.000
1059	2206.99	-	-	0.400	0.024	0.125	0.000
1060	2206.99	-	-	0.400	0.024	0.115	0.000
1061	2206.98	-	-	0.400	0.024	0.114	0.000
1062	2206.97	-	-	0.390	0.023	0.108	0.000
1063	2206.96	-	-	0.400	0.021	0.116	0.000
1064	2206.96	-	-	0.400	0.020	0.121	0.000
1065	2206.95	-	-	0.400	0.018	0.111	0.000
1066	2206.94	-	-	0.390	0.018	0.116	0.000
1067	2206.93	-	-	0.390	0.016	0.121	0.000
1068	2206.93	-	-	0.400	0.015	0.122	0.000
1069	2206.92	-	-	0.390	0.013	0.103	0.000
1070	2206.91	-	-	0.390	0.013	0.120	0.000
1071	2206.90	-	-	0.390	0.011	0.122	0.000
1072	2206.89	-	-	0.380	0.010	0.125	0.000
1073	2206.89	-	-	0.370	0.008	0.120	0.000
1074	2206.88	-	-	0.390	0.008	0.094	0.000
1075	2206.87	-	-	0.380	0.008	0.111	0.000
1076	2206.86	-	-	0.370	0.008	0.108	0.000
1077	2206.86	-	-	0.380	0.008	0.106	0.000
1078	2206.85	-	-	0.370	0.008	0.108	0.000
1079	2206.84	-	-	0.370	0.008	0.102	0.000
1080	2206.83	-	-	0.370	0.008	0.099	0.000
1081	2206.83	-	-	0.370	0.009	0.102	0.000
1082	2206.82	-	-	0.360	0.008	0.105	0.000
1083	2206.81	-	-	0.360	0.007	0.099	0.000
1084	2206.80	-	-	0.360	0.006	0.097	0.000
1085	2206.80	-	-	0.360	0.005	0.104	0.000
1086	2206.79	-	-	0.350	0.005	0.105	0.000
1087	2206.78	-	-	0.350	0.005	0.106	0.000
1088	2206.78	-	-	0.340	0.005	0.115	0.000
1089	2206.77	-	-	0.350	0.005	0.103	0.000
1090	2206.76	-	-	0.320	0.005	0.100	0.000
1091	2206.76	-	-	0.330	0.005	0.110	0.000
1092	2206.75	-	-	0.330	0.005	0.098	0.000
1093	2206.75	-	-	0.310	0.005	0.104	0.000
1094	2206.74	-	-	0.320	0.005	0.098	0.000
1095	2206.73	-	-	0.310	0.003	0.101	0.000
1096	2206.73	-	-	0.310	0.003	0.097	0.000

Continued on next page

Table 12 – continued from previous page - IEEE8500 - n1149

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
1097	2206.72	-	-	0.310	0.003	0.030	0.000
1098	2206.72	-	-	0.300	0.003	0.034	0.000
1099	2206.71	-	-	0.300	0.003	0.032	0.000
1100	2206.71	-	-	0.290	0.003	0.027	0.000
1101	2206.70	-	-	0.290	0.003	0.034	0.000
1102	2206.70	-	-	0.290	0.003	0.029	0.000
1103	2206.69	-	-	0.280	0.004	0.039	0.000
1104	2206.69	-	-	0.280	0.003	0.039	0.000
1105	2206.68	-	-	0.270	0.004	0.032	0.000
1106	2206.68	-	-	0.280	0.004	0.028	0.000
1107	2206.68	-	-	0.270	0.004	0.038	0.000
1108	2206.67	-	-	0.260	0.004	0.033	0.000
1109	2206.67	-	-	0.270	0.004	0.031	0.000
1110	2206.66	-	-	0.270	0.003	0.034	0.000
1111	2206.66	-	-	0.260	0.002	0.026	0.000
1112	2206.65	-	-	0.260	0.002	0.032	0.000
1113	2206.65	-	-	0.270	0.001	0.033	0.000
1114	2206.64	-	-	0.250	0.001	0.032	0.000
1115	2206.64	-	-	0.260	0.001	0.031	0.000
1116	2206.63	-	-	0.250	0.001	0.026	0.000
1117	2206.63	-	-	0.240	0.001	0.032	0.000
1118	2206.62	-	-	0.250	0.001	0.027	0.000
1119	2206.62	-	-	0.240	0.001	0.031	0.000
1120	2206.62	-	-	0.230	0.001	0.024	0.000
1121	2206.61	-	-	0.230	0.000	0.029	0.000
1122	2206.61	-	-	0.230	0.000	0.029	0.000
1123	2206.60	-	-	0.210	0.000	0.030	0.000
1124	2206.60	-	-	0.210	0.000	0.028	0.000
1125	2206.59	-	-	0.200	0.000	0.030	0.000
1126	2206.59	-	-	0.190	0.000	0.028	0.000
1127	2206.58	-	-	0.180	0.000	0.029	0.000
1128	2206.58	-	-	0.180	0.000	0.028	0.000
1129	2206.58	-	-	0.170	0.000	0.026	0.000
1130	2206.57	-	-	0.170	0.000	0.030	0.000
1131	2206.57	-	-	0.170	0.000	0.025	0.000
1132	2206.56	-	-	0.160	0.000	0.027	0.000
1133	2206.56	-	-	0.160	0.000	0.024	0.000
1134	2206.56	-	-	0.150	0.000	0.025	0.000
1135	2206.55	-	-	0.150	0.000	0.026	0.000
1136	2206.55	-	-	0.150	0.000	0.025	0.000
1137	2206.55	-	-	0.140	0.000	0.026	0.000
1138	2206.54	-	-	0.140	0.000	0.023	0.000
1139	2206.54	-	-	0.130	0.000	0.024	0.000
1140	2206.54	-	-	0.140	0.000	0.016	0.000
1141	2206.53	-	-	0.120	0.000	0.014	0.000
1142	2206.53	-	-	0.120	0.000	0.010	0.000
1143	2206.53	-	-	0.120	0.000	0.008	0.000
1144	2206.53	-	-	0.120	0.000	0.010	0.000
1145	2206.52	-	-	0.110	0.000	0.008	0.000
1146	2206.52	-	-	0.120	0.000	0.022	0.000
1147	2206.52	-	-	0.110	0.000	0.003	0.000
1148	2206.52	-	-	0.110	0.000	0.003	0.000

Continued on next page

Table 12 – continued from previous page - IEEE8500 - n1149

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
Total		**7246.69**	**8157.64**	**6091.76**	**89.51**		

Table 13: ENS optimization - IEEE8500 - n2250.

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
0	98575.40	8.929	0.004	0.020	0.000	0.004	0.000
1	73457.20	42.642	0.135	0.050	0.000	0.129	0.000
2	51488.40	3553.158	0.056	0.140	0.078	0.043	0.085
3	42512.30	-	0.171	0.240	0.092	0.254	0.103
4	36869.00	-	1.264	0.410	0.114	0.199	0.130
5	33277.40	-	2.820	0.530	0.133	0.351	0.150
6	30418.70	-	8.111	0.670	0.095	0.298	0.107
7	27921.10	-	11.404	0.790	0.109	0.229	0.104
8	26030.00	-	24.382	0.920	0.115	0.362	0.114
9	24436.50	-	100.647	1.160	0.127	5.749	0.118
10	22985.70	-	165.421	1.270	0.217	1.820	0.205
11	21774.50	-	279.056	1.510	0.229	5.124	0.206
12	20593.70	-	598.683	1.680	0.140	4.858	0.123
13	19888.90	-	3238.707	1.920	0.148	8.953	0.131
14	19205.30	-	-	2.120	0.153	8.002	0.119
15	18541.20	-	-	2.450	0.164	6.969	0.129
16	17941.80	-	-	2.680	0.170	4.471	0.138
17	17366.60	-	-	2.820	0.178	5.559	0.139
18	16835.80	-	-	2.940	0.185	4.796	0.133
19	16353.20	-	-	3.180	0.193	6.560	0.141
20	15941.70	-	-	3.400	0.199	8.272	0.149
21	15590.90	-	-	3.620	0.209	7.290	0.130
22	15251.70	-	-	3.830	0.214	6.511	0.137
23	14928.10	-	-	4.010	0.220	4.937	0.144
24	14648.70	-	-	4.100	0.227	6.586	0.155
25	14370.90	-	-	4.270	0.235	5.937	0.157
26	14106.10	-	-	4.490	0.433	6.437	0.339
27	13861.70	-	-	4.630	0.448	6.913	0.330
28	13647.00	-	-	4.800	0.238	6.691	0.139
29	13440.20	-	-	4.990	0.242	7.541	0.144
30	13240.00	-	-	5.080	0.244	8.084	0.149
31	13041.30	-	-	5.280	0.249	5.294	0.148
32	12847.20	-	-	5.580	0.250	5.261	0.128
33	12654.10	-	-	5.710	0.256	7.973	0.136
34	12470.80	-	-	5.870	0.256	9.173	0.132
35	12310.60	-	-	6.550	0.265	6.721	0.141
36	12154.60	-	-	6.830	0.265	4.473	0.147
37	12005.00	-	-	6.990	0.271	6.845	0.145
38	11858.70	-	-	7.190	0.274	6.452	0.142
39	11715.30	-	-	7.470	0.277	6.317	0.140
40	11576.30	-	-	7.090	0.279	6.265	0.140
41	11437.90	-	-	7.220	0.282	6.082	0.126
42	11302.70	-	-	7.320	0.285	5.382	0.131

Continued on next page

Table 13 – continued from previous page - IEEE8500 - n2250

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
43	11169.20	-	-	7.620	0.290	7.412	0.130
44	11035.90	-	-	7.760	0.289	6.861	0.136
45	10905.70	-	-	7.930	0.295	7.238	0.141
46	10785.00	-	-	8.160	0.295	7.256	0.138
47	10672.30	-	-	8.250	0.301	7.873	0.138
48	10559.90	-	-	8.480	0.303	8.707	0.124
49	10447.20	-	-	8.680	0.308	8.629	0.124
50	10335.40	-	-	8.790	0.310	6.612	0.128
51	10223.90	-	-	9.030	0.314	7.646	0.128
52	10119.70	-	-	9.210	0.316	9.476	0.127
53	10018.50	-	-	9.490	0.318	8.355	0.133
54	9921.14	-	-	9.700	0.321	7.676	0.138
55	9825.00	-	-	9.730	0.325	10.955	0.137
56	9728.95	-	-	10.070	0.328	7.463	0.136
57	9637.56	-	-	10.150	0.328	6.637	0.134
58	9548.48	-	-	10.440	0.333	10.113	0.135
59	9463.24	-	-	10.690	0.332	9.913	0.132
60	9380.82	-	-	10.720	0.335	7.760	0.131
61	9298.53	-	-	11.090	0.338	9.817	0.130
62	9225.12	-	-	11.170	0.342	11.358	0.122
63	9142.83	-	-	11.270	0.344	9.523	0.127
64	9070.31	-	-	11.540	0.347	11.704	0.127
65	9001.72	-	-	11.720	0.353	14.106	0.127
66	8934.74	-	-	11.860	0.356	12.657	0.132
67	8868.55	-	-	12.130	0.362	9.555	0.135
68	8805.65	-	-	12.280	0.365	13.011	0.139
69	8746.18	-	-	12.480	0.369	13.661	0.138
70	8690.23	-	-	12.500	0.377	13.746	0.138
71	8635.65	-	-	13.020	0.380	15.640	0.138
72	8581.82	-	-	13.170	0.379	17.153	0.125
73	8528.30	-	-	13.310	0.381	14.688	0.125
74	8476.05	-	-	13.540	0.386	18.713	0.125
75	8424.05	-	-	13.610	0.389	14.991	0.131
76	8374.07	-	-	13.850	0.394	12.030	0.133
77	8325.62	-	-	14.090	0.396	11.007	0.131
78	8278.56	-	-	13.700	0.401	14.631	0.130
79	8234.08	-	-	13.750	0.404	18.608	0.129
80	8191.06	-	-	14.080	0.410	19.683	0.136
81	8148.47	-	-	13.930	0.414	17.776	0.142
82	8106.01	-	-	14.190	0.418	15.168	0.141
83	8064.52	-	-	14.210	0.834	20.425	0.553
84	8023.38	-	-	14.300	0.417	12.242	0.134
85	7982.51	-	-	14.500	0.834	11.375	0.555
86	7942.03	-	-	14.570	0.405	13.449	0.130
87	7901.88	-	-	14.650	0.409	18.903	0.129
88	7861.78	-	-	14.760	0.414	10.985	0.131
89	7822.71	-	-	15.130	0.415	15.454	0.127
90	7784.24	-	-	15.280	0.419	16.478	0.127
91	7746.45	-	-	15.300	0.422	29.215	0.126
92	7710.14	-	-	15.560	0.426	11.564	0.127
93	7674.50	-	-	15.720	0.429	12.236	0.119
94	7639.61	-	-	16.080	0.434	13.544	0.119

Continued on next page

Table 13 – continued from previous page - IEEE8500 - n2250

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
95	7605.07	-	-	16.190	0.438	10.917	0.124
96	7570.57	-	-	16.150	0.442	13.514	0.124
97	7538.16	-	-	16.350	0.444	14.089	0.125
98	7507.13	-	-	16.320	0.447	17.533	0.124
99	7478.45	-	-	16.360	0.449	15.772	0.128
100	7450.50	-	-	16.470	0.453	13.389	0.128
101	7422.90	-	-	16.640	0.454	16.028	0.127
102	7395.73	-	-	16.620	0.457	13.251	0.132
103	7368.64	-	-	16.830	0.460	10.674	0.131
104	7341.72	-	-	16.880	0.464	14.720	0.131
105	7315.15	-	-	17.250	0.467	13.308	0.131
106	7288.78	-	-	17.230	0.472	14.573	0.131
107	7263.45	-	-	17.280	0.480	13.950	0.132
108	7238.89	-	-	17.430	0.477	13.882	0.120
109	7215.91	-	-	17.650	0.479	7.891	0.120
110	7193.09	-	-	17.870	0.480	10.694	0.119
111	7170.42	-	-	17.840	0.482	13.024	0.120
112	7148.14	-	-	18.030	0.487	13.952	0.121
113	7126.59	-	-	18.020	0.489	12.513	0.124
114	7105.07	-	-	18.190	0.493	11.523	0.124
115	7083.57	-	-	18.550	0.492	11.515	0.124
116	7062.10	-	-	18.660	0.497	10.812	0.125
117	7040.69	-	-	18.530	0.496	14.320	0.123
118	7019.59	-	-	18.740	0.500	17.059	0.123
119	6998.82	-	-	18.710	0.499	15.684	0.122
120	6978.15	-	-	18.910	0.501	13.512	0.125
121	6957.62	-	-	19.270	0.500	15.919	0.126
122	6937.53	-	-	19.490	0.501	11.133	0.129
123	6917.82	-	-	19.470	0.498	15.493	0.126
124	6898.43	-	-	19.640	0.500	14.878	0.126
125	6880.94	-	-	19.860	0.499	23.218	0.124
126	6863.58	-	-	19.950	0.500	14.533	0.125
127	6846.24	-	-	20.090	0.503	17.823	0.124
128	6828.92	-	-	20.330	0.499	18.949	0.122
129	6811.73	-	-	20.650	0.501	18.372	0.122
130	6795.54	-	-	20.840	0.498	18.899	0.121
131	6779.36	-	-	21.410	0.499	18.481	0.121
132	6763.63	-	-	21.200	0.500	18.637	0.119
133	6747.97	-	-	21.660	0.501	19.928	0.119
134	6732.84	-	-	21.980	0.496	9.552	0.118
135	6718.08	-	-	22.270	0.499	15.112	0.117
136	6703.94	-	-	22.550	0.496	10.844	0.117
137	6689.86	-	-	22.830	0.500	15.579	0.116
138	6675.85	-	-	23.150	0.496	16.025	0.114
139	6662.01	-	-	23.090	0.493	16.202	0.113
140	6648.44	-	-	23.550	0.492	21.019	0.107
141	6634.89	-	-	23.880	0.493	19.824	0.109
142	6621.59	-	-	23.530	0.494	17.095	0.106
143	6608.36	-	-	23.580	0.494	19.464	0.110
144	6595.14	-	-	23.780	0.493	20.139	0.109
145	6582.09	-	-	23.830	0.492	20.204	0.108
146	6569.10	-	-	24.240	0.495	17.979	0.108

Continued on next page

Table 13 – continued from previous page - IEEE8500 - n2250

		Time (sec)					
m	best ENS	ILP-GALIAS	ILP-IFLOWS	DP-TS	DP-N2M2	ILP-CUTS	DP-PC
147	6556.20	-	-	24.190	0.489	19.908	0.107
148	6543.33	-	-	24.630	0.490	18.963	0.105
149	6530.56	-	-	24.660	0.487	21.286	0.108
150	6518.17	-	-	24.790	0.487	20.691	0.107
151	6506.34	-	-	24.920	0.486	20.287	0.106
152	6494.60	-	-	24.930	0.486	20.088	0.107
153	6482.91	-	-	25.390	0.486	19.382	0.110
154	6471.46	-	-	25.510	0.488	17.296	0.109
155	6460.01	-	-	25.190	0.487	20.364	0.108
156	6448.61	-	-	25.550	0.487	17.265	0.107
157	6437.69	-	-	25.900	0.487	15.112	0.107
158	6426.80	-	-	25.970	0.487	13.340	0.108
159	6416.00	-	-	25.950	0.487	18.983	0.106
160	6405.24	-	-	26.360	0.486	19.681	0.105
161	6394.68	-	-	26.180	0.486	21.506	0.104
162	6384.31	-	-	26.450	0.488	18.153	0.098
163	6374.02	-	-	26.950	0.488	16.199	0.098
164	6363.78	-	-	27.090	0.484	20.355	0.097
165	6353.72	-	-	27.120	0.484	17.696	0.096
166	6343.94	-	-	26.980	0.487	20.580	0.095
167	6334.17	-	-	26.970	0.483	18.090	0.094
168	6324.60	-	-	27.530	0.482	21.259	0.094
169	6315.10	-	-	27.790	0.484	17.937	0.095
170	6305.66	-	-	27.850	0.484	19.989	0.099
171	6296.25	-	-	27.690	0.483	18.308	0.097
172	6286.83	-	-	28.390	0.483	16.316	0.096
173	6277.57	-	-	28.660	0.482	20.349	0.095
174	6268.33	-	-	28.530	0.484	20.495	0.095
175	6259.45	-	-	28.780	0.480	19.389	0.094
176	6250.71	-	-	29.050	0.478	19.848	0.095
177	6242.01	-	-	29.130	0.472	20.055	0.092
178	6233.78	-	-	29.920	0.475	20.246	0.092
179	6225.57	-	-	29.700	0.468	21.258	0.091
180	6217.36	-	-	29.780	0.471	19.939	0.093
181	6209.17	-	-	29.370	0.466	17.233	0.092
182	6200.98	-	-	29.550	0.468	19.236	0.092
183	6192.90	-	-	29.560	0.468	27.933	0.096
184	6184.89	-	-	29.610	0.469	22.180	0.095
185	6176.88	-	-	29.740	0.464	21.139	0.093
186	6168.94	-	-	30.190	0.463	18.324	0.092
187	6161.02	-	-	32.970	0.462	17.704	0.092
188	6153.36	-	-	33.280	0.461	23.143	0.091
189	6145.71	-	-	33.320	0.463	22.265	0.093
190	6138.06	-	-	33.640	0.465	20.191	0.091
191	6130.41	-	-	33.530	0.467	18.435	0.091
192	6122.76	-	-	33.600	0.466	18.369	0.090
193	6115.12	-	-	34.180	0.469	21.466	0.090
194	6107.62	-	-	34.060	0.471	17.391	0.091
195	6100.19	-	-	34.400	0.473	19.715	0.091
196	6092.89	-	-	34.780	0.472	21.212	0.091
197	6085.70	-	-	34.570	0.470	16.932	0.090
198	6078.57	-	-	34.850	0.469	21.633	0.089

Continued on next page

Table 13 – continued from previous page - IEEE8500 - n2250

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
199	6071.45	-	-	34.970	0.469	20.176	0.089
200	6064.34	-	-	35.590	0.469	21.098	0.088
201	6057.52	-	-	35.600	0.465	18.106	0.089
202	6050.72	-	-	35.510	0.464	21.358	0.089
203	6043.95	-	-	35.830	0.466	29.257	0.089
204	6037.26	-	-	35.910	0.468	28.447	0.087
205	6030.62	-	-	35.770	0.465	17.658	0.086
206	6024.01	-	-	36.020	0.467	19.234	0.087
207	6017.44	-	-	36.130	0.466	19.204	0.086
208	6010.91	-	-	36.100	0.468	20.049	0.086
209	6004.45	-	-	36.160	0.470	19.620	0.088
210	5998.33	-	-	36.600	0.473	19.926	0.083
211	5992.28	-	-	36.830	0.474	30.811	0.083
212	5986.41	-	-	37.110	0.476	33.856	0.083
213	5980.63	-	-	37.080	0.475	30.012	0.082
214	5974.86	-	-	37.390	0.477	29.901	0.082
215	5969.13	-	-	37.170	0.475	29.201	0.084
216	5963.49	-	-	37.440	0.477	22.271	0.085
217	5957.85	-	-	37.710	0.480	21.328	0.084
218	5952.21	-	-	37.880	0.482	21.710	0.084
219	5946.58	-	-	38.220	0.484	22.190	0.084
220	5941.00	-	-	38.430	0.478	21.526	0.083
221	5935.43	-	-	38.880	0.480	20.162	0.083
222	5929.87	-	-	39.280	0.478	19.812	0.082
223	5924.35	-	-	39.500	0.480	14.774	0.083
224	5918.82	-	-	39.460	0.478	22.406	0.085
225	5913.36	-	-	39.660	0.480	20.172	0.084
226	5908.03	-	-	39.680	0.482	19.435	0.085
227	5902.75	-	-	39.540	0.484	20.354	0.084
228	5897.46	-	-	39.440	0.486	19.462	0.084
229	5892.18	-	-	39.770	0.489	18.973	0.085
230	5886.97	-	-	39.630	0.491	14.173	0.088
231	5881.74	-	-	39.740	0.493	21.030	0.088
232	5876.55	-	-	39.970	0.494	24.145	0.088
233	5871.34	-	-	39.990	0.497	26.912	0.088
234	5866.13	-	-	40.400	0.499	29.929	0.088
235	5860.98	-	-	40.770	0.501	23.743	0.088
236	5855.89	-	-	40.800	0.504	24.548	0.089
237	5850.81	-	-	40.900	0.506	18.301	0.090
238	5845.92	-	-	41.120	0.508	25.747	0.089
239	5841.03	-	-	41.050	0.510	22.861	0.088
240	5836.18	-	-	41.110	0.512	21.380	0.088
241	5831.35	-	-	41.730	0.514	28.048	0.088
242	5826.55	-	-	41.850	0.516	21.412	0.088
243	5821.76	-	-	42.090	0.519	22.057	0.083
244	5817.04	-	-	41.950	0.520	22.102	0.085
245	5812.37	-	-	42.330	0.522	18.950	0.083
246	5807.73	-	-	42.470	0.524	22.605	0.083
247	5803.12	-	-	42.510	0.526	21.289	0.083
248	5798.55	-	-	42.690	0.529	24.188	0.083
249	5793.95	-	-	43.100	0.531	22.211	0.083
250	5789.38	-	-	43.160	0.533	23.045	0.083

Continued on next page

Table 13 – continued from previous page - IEEE8500 - n2250

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
251	5784.82	-	-	43.250	0.535	24.453	0.084
252	5780.28	-	-	43.760	0.530	25.651	0.082
253	5775.74	-	-	44.220	0.527	25.476	0.081
254	5771.20	-	-	44.730	0.529	24.180	0.081
255	5766.66	-	-	44.380	0.526	28.719	0.083
256	5762.12	-	-	44.490	0.524	25.679	0.082
257	5757.58	-	-	44.770	0.522	26.797	0.081
258	5753.05	-	-	44.720	0.521	24.234	0.082
259	5748.51	-	-	45.070	0.518	24.487	0.082
260	5744.00	-	-	45.030	0.516	25.608	0.080
261	5739.47	-	-	45.100	0.506	33.953	0.078
262	5734.94	-	-	45.520	0.508	21.797	0.078
263	5730.43	-	-	45.390	0.498	23.635	0.076
264	5726.01	-	-	45.680	0.500	24.809	0.077
265	5721.68	-	-	46.280	0.496	26.168	0.076
266	5717.40	-	-	45.880	0.491	25.685	0.076
267	5713.13	-	-	45.950	0.493	27.569	0.075
268	5708.86	-	-	46.290	0.496	25.982	0.075
269	5704.60	-	-	46.270	0.497	26.427	0.075
270	5700.37	-	-	46.500	0.495	22.460	0.077
271	5696.19	-	-	46.560	0.497	22.339	0.076
272	5692.05	-	-	47.200	0.494	18.845	0.076
273	5687.93	-	-	47.220	0.490	25.632	0.075
274	5683.86	-	-	47.220	0.488	21.180	0.076
275	5679.93	-	-	47.500	0.484	22.438	0.076
276	5676.00	-	-	47.930	0.482	36.096	0.076
277	5672.10	-	-	48.320	0.483	27.347	0.076
278	5668.19	-	-	48.700	0.485	21.877	0.075
279	5664.38	-	-	49.330	0.480	20.963	0.074
280	5660.57	-	-	49.000	0.482	30.552	0.074
281	5656.77	-	-	49.490	0.477	23.645	0.073
282	5653.05	-	-	49.690	0.478	26.555	0.075
283	5649.54	-	-	50.040	0.480	27.388	0.074
284	5645.90	-	-	50.080	0.482	27.130	0.073
285	5642.39	-	-	50.560	0.484	30.851	0.073
286	5638.91	-	-	49.860	0.485	35.075	0.074
287	5635.44	-	-	50.160	0.487	22.422	0.073
288	5632.00	-	-	50.470	0.489	29.101	0.073
289	5628.63	-	-	50.490	0.490	25.516	0.073
290	5625.31	-	-	-	0.492	28.628	0.075
291	5621.98	-	-	-	0.493	25.471	0.074
292	5618.66	-	-	-	0.495	32.445	0.074
293	5615.34	-	-	-	0.496	27.090	0.074
294	5612.02	-	-	-	0.498	27.158	0.074
295	5608.77	-	-	-	0.500	28.934	0.074
296	5605.58	-	-	-	0.502	28.640	0.074
297	5602.40	-	-	-	0.503	21.006	0.074
298	5599.22	-	-	-	0.505	26.661	0.075
299	5596.08	-	-	-	0.507	26.709	0.075
300	5592.95	-	-	-	0.509	29.855	0.074
301	5589.83	-	-	-	0.510	24.480	0.074
302	5586.78	-	-	-	0.512	32.599	0.074

Continued on next page

Table 13 – continued from previous page - IEEE8500 - n2250

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
303	5583.75	-	-	-	0.514	21.891	0.074
304	5580.75	-	-	-	0.516	27.978	0.074
305	5577.80	-	-	-	0.510	27.437	0.073
306	5574.85	-	-	-	0.511	31.705	0.075
307	5571.92	-	-	-	0.509	26.885	0.073
308	5569.09	-	-	-	0.511	28.377	0.073
309	5566.29	-	-	-	0.508	32.765	0.073
310	5563.53	-	-	-	0.510	28.411	0.072
311	5560.77	-	-	-	0.512	35.719	0.073
312	5558.00	-	-	-	0.513	25.652	0.073
313	5555.28	-	-	-	0.515	26.418	0.073
314	5552.56	-	-	-	0.517	31.259	0.074
315	5549.86	-	-	-	0.519	27.578	0.071
316	5547.18	-	-	-	0.520	21.679	0.070
317	5544.62	-	-	-	0.514	24.870	0.069
318	5542.09	-	-	-	0.516	25.794	0.069
319	5539.63	-	-	-	0.511	26.905	0.068
320	5537.20	-	-	-	0.512	29.988	0.068
321	5534.78	-	-	-	0.507	27.393	0.067
322	5532.43	-	-	-	0.509	27.837	0.067
323	5530.10	-	-	-	0.510	24.378	0.071
324	5527.77	-	-	-	0.512	31.094	0.070
325	5525.44	-	-	-	0.514	28.174	0.069
326	5523.14	-	-	-	0.515	27.403	0.069
327	5520.83	-	-	-	0.517	24.447	0.069
328	5518.57	-	-	-	0.519	25.445	0.069
329	5516.30	-	-	-	0.520	22.377	0.069
330	5514.04	-	-	-	0.522	30.180	0.069
331	5511.79	-	-	-	0.523	27.210	0.070
332	5509.54	-	-	-	0.525	28.040	0.071
333	5507.34	-	-	-	0.527	31.737	0.070
334	5505.13	-	-	-	0.529	33.622	0.070
335	5502.95	-	-	-	0.531	31.121	0.070
336	5500.76	-	-	-	0.532	26.225	0.072
337	5498.58	-	-	-	0.534	38.388	0.071
338	5496.39	-	-	-	0.535	21.992	0.071
339	5494.21	-	-	-	0.537	27.832	0.071
340	5492.04	-	-	-	0.538	28.359	0.073
341	5489.88	-	-	-	0.540	26.535	0.072
342	5487.72	-	-	-	0.542	21.580	0.072
343	5485.59	-	-	-	0.543	15.483	0.071
344	5483.50	-	-	-	0.545	26.710	0.072
345	5481.45	-	-	-	0.547	28.422	0.073
346	5479.40	-	-	-	0.549	28.775	0.073
347	5477.36	-	-	-	0.550	27.343	0.073
348	5475.33	-	-	-	0.552	29.236	0.075
349	5473.30	-	-	-	0.553	28.350	0.074
350	5471.27	-	-	-	0.555	27.118	0.074
351	5469.25	-	-	-	0.556	28.574	0.073
352	5467.22	-	-	-	0.558	27.454	0.074
353	5465.20	-	-	-	0.560	29.148	0.073
354	5463.20	-	-	-	0.561	24.273	0.073

Continued on next page

Table 13 – continued from previous page - IEEE8500 - n2250

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
355	5461.20	-	-	-	0.563	23.470	0.073
356	5459.22	-	-	-	1.476	26.802	0.994
357	5457.23	-	-	-	0.561	27.515	0.070
358	5455.26	-	-	-	0.563	16.485	0.070
359	5453.29	-	-	-	0.557	33.371	0.068
360	5451.35	-	-	-	0.558	18.086	0.069
361	5449.42	-	-	-	0.552	17.712	0.068
362	5447.49	-	-	-	1.477	28.057	0.994
363	5445.57	-	-	-	0.538	29.145	0.066
364	5443.66	-	-	-	0.540	27.446	0.066
365	5441.74	-	-	-	0.541	25.589	0.063
366	5439.82	-	-	-	0.542	16.753	0.062
367	5437.91	-	-	-	0.544	40.636	0.061
368	5436.00	-	-	-	0.545	28.803	0.061
369	5434.13	-	-	-	0.547	29.163	0.061
370	5432.26	-	-	-	0.548	29.524	0.061
371	5430.39	-	-	-	0.549	26.277	0.061
372	5428.53	-	-	-	0.551	24.517	0.061
373	5426.67	-	-	-	0.553	20.962	0.061
374	5424.81	-	-	-	0.553	32.257	0.063
375	5422.97	-	-	-	0.555	28.750	0.061
376	5421.12	-	-	-	0.556	32.883	0.061
377	5419.28	-	-	-	0.558	-	0.060
378	5417.44	-	-	-	0.560	-	0.060
379	5415.61	-	-	-	0.553	-	0.059
380	5413.80	-	-	-	0.554	-	0.060
381	5411.99	-	-	-	0.549	-	0.059
382	5410.22	-	-	-	0.550	-	0.059
383	5408.46	-	-	-	0.544	-	0.060
384	5406.70	-	-	-	0.545	-	0.062
385	5404.97	-	-	-	0.546	-	0.060
386	5403.24	-	-	-	0.548	-	0.060
387	5401.55	-	-	-	0.549	-	0.060
388	5399.86	-	-	-	0.550	-	0.060
389	5398.17	-	-	-	0.543	-	0.059
390	5396.51	-	-	-	0.544	-	0.058
391	5394.85	-	-	-	0.546	-	0.058
392	5393.20	-	-	-	0.547	-	0.058
393	5391.56	-	-	-	0.549	-	0.058
394	5389.95	-	-	-	0.550	-	0.061
395	5388.35	-	-	-	0.552	-	0.059
396	5386.77	-	-	-	0.553	-	0.059
397	5385.19	-	-	-	0.547	-	0.058
398	5383.62	-	-	-	0.548	-	0.058
399	5382.06	-	-	-	0.532	-	0.056
400	5380.51	-	-	-	0.533	-	0.056
401	5378.96	-	-	-	0.524	-	0.055
402	5377.43	-	-	-	0.525	-	0.055
403	5375.90	-	-	-	0.526	-	0.055
404	5374.36	-	-	-	0.518	-	0.054
405	5372.83	-	-	-	0.512	-	0.056
406	5371.30	-	-	-	0.513	-	0.055

Continued on next page

Table 13 – continued from previous page - IEEE8500 - n2250

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
407	5369.77	-	-	-	0.514	-	0.054
408	5368.24	-	-	-	0.516	-	0.054
409	5366.71	-	-	-	0.517	-	0.054
410	5365.19	-	-	-	0.518	-	0.054
411	5363.68	-	-	-	0.520	-	0.054
412	5362.19	-	-	-	0.521	-	0.054
413	5360.70	-	-	-	0.523	-	0.056
414	5359.22	-	-	-	0.523	-	0.056
415	5357.74	-	-	-	0.525	-	0.056
416	5356.28	-	-	-	0.526	-	0.058
417	5354.84	-	-	-	0.527	-	0.056
418	5353.41	-	-	-	0.528	-	0.056
419	5351.98	-	-	-	0.522	-	0.055
420	5350.55	-	-	-	0.523	-	0.055
421	5349.14	-	-	-	0.524	-	0.055
422	5347.73	-	-	-	0.525	-	0.055
423	5346.32	-	-	-	0.520	-	0.054
424	5344.93	-	-	-	0.521	-	0.054
425	5343.55	-	-	-	0.513	-	0.054
426	5342.17	-	-	-	0.509	-	0.055
427	5340.81	-	-	-	0.510	-	0.054
428	5339.48	-	-	-	0.507	-	0.053
429	5338.15	-	-	-	0.507	-	0.053
430	5336.83	-	-	-	0.504	-	0.052
431	5335.53	-	-	-	0.505	-	0.052
432	5334.25	-	-	-	0.501	-	0.051
433	5332.97	-	-	-	0.501	-	0.052
434	5331.69	-	-	-	0.503	-	0.052
435	5330.42	-	-	-	0.504	-	0.052
436	5329.16	-	-	-	0.500	-	0.051
437	5327.91	-	-	-	0.501	-	0.052
438	5326.66	-	-	-	0.502	-	0.053
439	5325.42	-	-	-	0.503	-	0.052
440	5324.18	-	-	-	0.505	-	0.052
441	5322.95	-	-	-	0.506	-	0.051
442	5321.72	-	-	-	0.506	-	0.052
443	5320.49	-	-	-	0.507	-	0.052
444	5319.26	-	-	-	0.509	-	0.051
445	5318.04	-	-	-	0.509	-	0.051
446	5316.81	-	-	-	0.511	-	0.051
447	5315.59	-	-	-	0.512	-	0.051
448	5314.38	-	-	-	0.512	-	0.051
449	5313.17	-	-	-	0.513	-	0.053
450	5311.98	-	-	-	0.515	-	0.052
451	5310.80	-	-	-	0.516	-	0.052
452	5309.64	-	-	-	0.517	-	0.052
453	5308.48	-	-	-	0.517	-	0.052
454	5307.33	-	-	-	0.519	-	0.052
455	5306.17	-	-	-	0.520	-	0.052
456	5305.02	-	-	-	0.521	-	0.052
457	5303.88	-	-	-	0.522	-	0.051
458	5302.76	-	-	-	0.509	-	0.050

Continued on next page

Table 13 – continued from previous page - IEEE8500 - n2250

		Time (sec)					
m	best ENS	ILP-GALIAS	ILP-IFLOWS	DP-TS	DP-N2M2	ILP-CUTS	DP-PC
459	5301.66	-	-	-	0.510	-	0.050
460	5300.56	-	-	-	0.506	-	0.050
461	5299.47	-	-	-	0.508	-	0.052
462	5298.39	-	-	-	0.504	-	0.050
463	5297.31	-	-	-	0.504	-	0.050
464	5296.23	-	-	-	0.501	-	0.049
465	5295.15	-	-	-	0.501	-	0.049
466	5294.07	-	-	-	0.497	-	0.048
467	5293.02	-	-	-	0.498	-	0.049
468	5291.96	-	-	-	0.495	-	0.048
469	5290.90	-	-	-	0.495	-	0.048
470	5289.84	-	-	-	0.492	-	0.048
471	5288.79	-	-	-	0.493	-	0.048
472	5287.74	-	-	-	0.489	-	0.047
473	5286.69	-	-	-	0.489	-	0.048
474	5285.64	-	-	-	0.490	-	0.047
475	5284.60	-	-	-	0.491	-	0.046
476	5283.56	-	-	-	0.492	-	0.046
477	5282.53	-	-	-	0.493	-	0.046
478	5281.51	-	-	-	0.494	-	0.046
479	5280.49	-	-	-	0.495	-	0.046
480	5279.48	-	-	-	0.496	-	0.046
481	5278.46	-	-	-	0.497	-	0.046
482	5277.46	-	-	-	0.498	-	0.046
483	5276.46	-	-	-	0.490	-	0.046
484	5275.46	-	-	-	0.491	-	0.045
485	5274.47	-	-	-	0.487	-	0.046
486	5273.49	-	-	-	0.488	-	0.048
487	5272.50	-	-	-	0.484	-	0.046
488	5271.52	-	-	-	0.485	-	0.046
489	5270.55	-	-	-	0.487	-	0.046
490	5269.57	-	-	-	0.487	-	0.046
491	5268.59	-	-	-	0.488	-	0.046
492	5267.62	-	-	-	0.489	-	0.046
493	5266.64	-	-	-	0.490	-	0.046
494	5265.68	-	-	-	0.491	-	0.046
495	5264.74	-	-	-	0.492	-	0.046
496	5263.79	-	-	-	0.493	-	0.046
497	5262.84	-	-	-	0.494	-	0.046
498	5261.91	-	-	-	0.495	-	0.047
499	5260.99	-	-	-	0.495	-	0.048
500	5260.07	-	-	-	0.496	-	0.046
501	5259.16	-	-	-	0.497	-	0.046
502	5258.25	-	-	-	0.498	-	0.046
503	5257.34	-	-	-	0.499	-	0.046
504	5256.44	-	-	-	0.500	-	0.047
505	5255.53	-	-	-	0.501	-	0.047
506	5254.63	-	-	-	0.502	-	0.047
507	5253.73	-	-	-	0.503	-	0.047
508	5252.83	-	-	-	0.503	-	0.047
509	5251.93	-	-	-	0.505	-	0.047
510	5251.04	-	-	-	0.506	-	0.047

Continued on next page

Table 13 – continued from previous page - IEEE8500 - n2250

		Time (sec)					
m	best ENS	ILP-GALIAS	ILP-IFLOWS	DP-TS	DP-N2M2	ILP-CUTS	DP-PC
511	5250.15	-	-	-	0.507	-	0.048
512	5249.26	-	-	-	0.508	-	0.048
513	5248.38	-	-	-	0.509	-	0.047
514	5247.50	-	-	-	0.510	-	0.047
515	5246.62	-	-	-	0.511	-	0.047
516	5245.75	-	-	-	0.512	-	0.047
517	5244.87	-	-	-	0.513	-	0.047
518	5244.00	-	-	-	0.514	-	0.048
519	5243.13	-	-	-	0.515	-	0.048
520	5242.27	-	-	-	0.516	-	0.048
521	5241.40	-	-	-	0.517	-	0.049
522	5240.54	-	-	-	0.517	-	0.048
523	5239.68	-	-	-	0.518	-	0.048
524	5238.83	-	-	-	0.520	-	0.051
525	5237.99	-	-	-	0.521	-	0.050
526	5237.16	-	-	-	0.522	-	0.049
527	5236.33	-	-	-	0.523	-	0.049
528	5235.50	-	-	-	0.524	-	0.049
529	5234.69	-	-	-	0.525	-	0.049
530	5233.88	-	-	-	0.525	-	0.048
531	5233.08	-	-	-	0.526	-	0.048
532	5232.29	-	-	-	0.527	-	0.048
533	5231.51	-	-	-	0.528	-	0.048
534	5230.73	-	-	-	0.529	-	0.048
535	5229.95	-	-	-	0.530	-	0.048
536	5229.18	-	-	-	0.531	-	0.050
537	5228.41	-	-	-	0.532	-	0.048
538	5227.64	-	-	-	0.533	-	0.048
539	5226.87	-	-	-	0.534	-	0.048
540	5226.11	-	-	-	0.535	-	0.048
541	5225.35	-	-	-	0.535	-	0.047
542	5224.59	-	-	-	0.536	-	0.047
543	5223.83	-	-	-	0.538	-	0.047
544	5223.07	-	-	-	0.539	-	0.047
545	5222.31	-	-	-	0.540	-	0.047
546	5221.56	-	-	-	0.541	-	0.047
547	5220.81	-	-	-	0.543	-	0.047
548	5220.06	-	-	-	0.543	-	0.047
549	5219.32	-	-	-	0.544	-	0.047
550	5218.59	-	-	-	0.544	-	0.046
551	5217.85	-	-	-	0.545	-	0.046
552	5217.12	-	-	-	0.547	-	0.046
553	5216.39	-	-	-	0.547	-	0.045
554	5215.67	-	-	-	0.548	-	0.045
555	5214.97	-	-	-	0.549	-	0.045
556	5214.27	-	-	-	0.550	-	0.045
557	5213.56	-	-	-	0.551	-	0.045
558	5212.87	-	-	-	0.552	-	0.045
559	5212.17	-	-	-	0.553	-	0.045
560	5211.48	-	-	-	0.555	-	0.045
561	5210.79	-	-	-	0.555	-	0.046
562	5210.11	-	-	-	0.556	-	0.047

Continued on next page

Table 13 – continued from previous page - IEEE8500 - n2250

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
563	5209.42	-	-	-	0.558	-	0.046
564	5208.74	-	-	-	0.559	-	0.046
565	5208.06	-	-	-	0.559	-	0.046
566	5207.38	-	-	-	0.560	-	0.046
567	5206.71	-	-	-	0.561	-	0.046
568	5206.05	-	-	-	0.562	-	0.046
569	5205.41	-	-	-	0.563	-	0.045
570	5204.77	-	-	-	0.564	-	0.045
571	5204.12	-	-	-	0.565	-	0.045
572	5203.48	-	-	-	0.566	-	0.045
573	5202.84	-	-	-	0.567	-	0.045
574	5202.20	-	-	-	0.568	-	0.046
575	5201.57	-	-	-	0.569	-	0.048
576	5200.93	-	-	-	0.570	-	0.047
577	5200.30	-	-	-	0.571	-	0.047
578	5199.67	-	-	-	0.572	-	0.047
579	5199.04	-	-	-	0.563	-	0.046
580	5198.41	-	-	-	0.564	-	0.046
581	5197.79	-	-	-	0.559	-	0.045
582	5197.16	-	-	-	0.559	-	0.045
583	5196.54	-	-	-	0.561	-	0.045
584	5195.92	-	-	-	0.561	-	0.045
585	5195.30	-	-	-	0.557	-	0.045
586	5194.68	-	-	-	0.558	-	0.045
587	5194.06	-	-	-	0.555	-	0.046
588	5193.45	-	-	-	0.555	-	0.046
589	5192.84	-	-	-	0.551	-	0.045
590	5192.23	-	-	-	0.552	-	0.045
591	5191.62	-	-	-	0.553	-	0.044
592	5191.02	-	-	-	0.554	-	0.044
593	5190.42	-	-	-	0.555	-	0.045
594	5189.83	-	-	-	0.556	-	0.045
595	5189.24	-	-	-	0.557	-	0.045
596	5188.65	-	-	-	0.558	-	0.044
597	5188.06	-	-	-	0.559	-	0.044
598	5187.47	-	-	-	0.559	-	0.044
599	5186.89	-	-	-	0.560	-	0.044
600	5186.31	-	-	-	0.561	-	0.045
601	5185.73	-	-	-	0.562	-	0.047
602	5185.15	-	-	-	0.563	-	0.045
603	5184.58	-	-	-	0.564	-	0.045
604	5184.00	-	-	-	0.566	-	0.044
605	5183.43	-	-	-	0.567	-	0.044
606	5182.85	-	-	-	0.555	-	0.044
607	5182.28	-	-	-	0.551	-	0.043
608	5181.71	-	-	-	0.542	-	0.044
609	5181.13	-	-	-	0.539	-	0.043
610	5180.57	-	-	-	0.531	-	0.042
611	5180.00	-	-	-	0.531	-	0.042
612	5179.44	-	-	-	0.532	-	0.042
613	5178.89	-	-	-	0.528	-	0.042
614	5178.33	-	-	-	0.528	-	0.043

Continued on next page

Table 13 – continued from previous page - IEEE8500 - n2250

		Time (sec)					
m	best ENS	ILP-GALIAS	ILP-IFLOWS	DP-TS	DP-N2M2	ILP-CUTS	DP-PC
615	5177.78	-	-	-	0.525	-	0.043
616	5177.23	-	-	-	0.525	-	0.042
617	5176.68	-	-	-	0.521	-	0.041
618	5176.13	-	-	-	0.522	-	0.041
619	5175.58	-	-	-	0.519	-	0.041
620	5175.04	-	-	-	0.519	-	0.042
621	5174.49	-	-	-	0.516	-	0.042
622	5173.95	-	-	-	0.517	-	0.042
623	5173.41	-	-	-	0.518	-	0.041
624	5172.87	-	-	-	0.520	-	0.041
625	5172.33	-	-	-	0.520	-	0.041
626	5171.80	-	-	-	0.521	-	0.041
627	5171.27	-	-	-	0.522	-	0.041
628	5170.74	-	-	-	0.523	-	0.042
629	5170.22	-	-	-	0.523	-	0.043
630	5169.70	-	-	-	0.524	-	0.042
631	5169.18	-	-	-	0.524	-	0.042
632	5168.67	-	-	-	0.525	-	0.041
633	5168.15	-	-	-	0.526	-	0.042
634	5167.64	-	-	-	0.526	-	0.042
635	5167.13	-	-	-	0.527	-	0.042
636	5166.62	-	-	-	0.528	-	0.042
637	5166.13	-	-	-	0.529	-	0.042
638	5165.63	-	-	-	0.529	-	0.042
639	5165.14	-	-	-	0.530	-	0.042
640	5164.66	-	-	-	0.526	-	0.041
641	5164.18	-	-	-	0.527	-	0.041
642	5163.70	-	-	-	0.528	-	0.041
643	5163.23	-	-	-	0.528	-	0.044
644	5162.75	-	-	-	0.530	-	0.042
645	5162.28	-	-	-	0.530	-	0.041
646	5161.81	-	-	-	0.531	-	0.041
647	5161.34	-	-	-	0.524	-	0.041
648	5160.87	-	-	-	0.525	-	0.041
649	5160.40	-	-	-	0.522	-	0.040
650	5159.94	-	-	-	0.522	-	0.040
651	5159.47	-	-	-	0.519	-	0.040
652	5159.01	-	-	-	0.520	-	0.040
653	5158.55	-	-	-	0.518	-	0.040
654	5158.10	-	-	-	0.519	-	0.040
655	5157.64	-	-	-	0.515	-	0.040
656	5157.19	-	-	-	0.516	-	0.040
657	5156.74	-	-	-	0.517	-	0.042
658	5156.29	-	-	-	0.518	-	0.041
659	5155.84	-	-	-	0.519	-	0.040
660	5155.39	-	-	-	0.519	-	0.040
661	5154.95	-	-	-	0.520	-	0.040
662	5154.51	-	-	-	0.520	-	0.040
663	5154.07	-	-	-	0.521	-	0.040
664	5153.62	-	-	-	0.522	-	0.040
665	5153.18	-	-	-	0.519	-	0.040
666	5152.74	-	-	-	0.520	-	0.040

Continued on next page

Table 13 – continued from previous page - IEEE8500 - n2250

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
667	5152.30	-	-	-	0.518	-	0.039
668	5151.87	-	-	-	0.518	-	0.039
669	5151.44	-	-	-	0.516	-	0.039
670	5151.00	-	-	-	0.517	-	0.039
671	5150.57	-	-	-	0.518	-	0.039
672	5150.14	-	-	-	0.519	-	0.041
673	5149.71	-	-	-	0.520	-	0.040
674	5149.29	-	-	-	0.520	-	0.039
675	5148.87	-	-	-	0.521	-	0.039
676	5148.45	-	-	-	0.522	-	0.039
677	5148.03	-	-	-	0.523	-	0.039
678	5147.61	-	-	-	0.523	-	0.039
679	5147.20	-	-	-	0.524	-	0.039
680	5146.79	-	-	-	0.525	-	0.039
681	5146.38	-	-	-	0.525	-	0.039
682	5145.97	-	-	-	0.526	-	0.039
683	5145.56	-	-	-	0.527	-	0.039
684	5145.15	-	-	-	0.528	-	0.039
685	5144.74	-	-	-	0.528	-	0.039
686	5144.33	-	-	-	0.529	-	0.039
687	5143.92	-	-	-	0.530	-	0.040
688	5143.52	-	-	-	0.531	-	0.041
689	5143.11	-	-	-	0.532	-	0.039
690	5142.70	-	-	-	0.532	-	0.039
691	5142.30	-	-	-	0.532	-	0.039
692	5141.89	-	-	-	0.533	-	0.039
693	5141.49	-	-	-	0.534	-	0.039
694	5141.09	-	-	-	0.535	-	0.039
695	5140.68	-	-	-	0.536	-	0.039
696	5140.28	-	-	-	0.536	-	0.039
697	5139.89	-	-	-	0.537	-	0.039
698	5139.49	-	-	-	0.538	-	0.039
699	5139.09	-	-	-	0.538	-	0.039
700	5138.70	-	-	-	0.539	-	0.039
701	5138.31	-	-	-	0.540	-	0.039
702	5137.91	-	-	-	0.541	-	0.039
703	5137.53	-	-	-	0.542	-	0.041
704	5137.14	-	-	-	0.542	-	0.040
705	5136.75	-	-	-	0.544	-	0.039
706	5136.37	-	-	-	0.544	-	0.039
707	5135.99	-	-	-	0.546	-	0.039
708	5135.61	-	-	-	0.546	-	0.039
709	5135.24	-	-	-	0.547	-	0.039
710	5134.86	-	-	-	0.548	-	0.038
711	5134.49	-	-	-	0.548	-	0.038
712	5134.12	-	-	-	0.549	-	0.038
713	5133.75	-	-	-	0.549	-	0.038
714	5133.38	-	-	-	0.550	-	0.038
715	5133.01	-	-	-	0.551	-	0.038
716	5132.64	-	-	-	0.552	-	0.038
717	5132.28	-	-	-	0.553	-	0.038
718	5131.91	-	-	-	0.553	-	0.040

Continued on next page

Table 13 – continued from previous page - IEEE8500 - n2250

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
719	5131.55	-	-	-	0.554	-	0.039
720	5131.18	-	-	-	0.555	-	0.038
721	5130.82	-	-	-	0.556	-	0.038
722	5130.46	-	-	-	0.556	-	0.038
723	5130.10	-	-	-	0.558	-	0.038
724	5129.74	-	-	-	0.558	-	0.038
725	5129.39	-	-	-	0.559	-	0.038
726	5129.03	-	-	-	0.559	-	0.038
727	5128.67	-	-	-	0.561	-	0.038
728	5128.32	-	-	-	0.560	-	0.039
729	5127.98	-	-	-	0.561	-	0.039
730	5127.63	-	-	-	0.562	-	0.039
731	5127.29	-	-	-	0.562	-	0.038
732	5126.94	-	-	-	0.564	-	0.039
733	5126.60	-	-	-	0.564	-	0.040
734	5126.26	-	-	-	0.565	-	0.041
735	5125.92	-	-	-	0.565	-	0.039
736	5125.59	-	-	-	0.566	-	0.039
737	5125.25	-	-	-	0.567	-	0.039
738	5124.92	-	-	-	0.567	-	0.039
739	5124.59	-	-	-	0.568	-	0.039
740	5124.26	-	-	-	0.569	-	0.038
741	5123.93	-	-	-	0.570	-	0.039
742	5123.60	-	-	-	0.572	-	0.038
743	5123.28	-	-	-	0.572	-	0.038
744	5122.95	-	-	-	0.573	-	0.038
745	5122.63	-	-	-	0.573	-	0.038
746	5122.30	-	-	-	0.574	-	0.038
747	5121.98	-	-	-	0.575	-	0.039
748	5121.65	-	-	-	0.575	-	0.039
749	5121.33	-	-	-	0.576	-	0.042
750	5121.01	-	-	-	0.577	-	0.039
751	5120.69	-	-	-	0.578	-	0.039
752	5120.37	-	-	-	0.578	-	0.039
753	5120.04	-	-	-	0.580	-	0.039
754	5119.72	-	-	-	0.580	-	0.039
755	5119.40	-	-	-	0.580	-	0.039
756	5119.09	-	-	-	0.581	-	0.040
757	5118.77	-	-	-	0.581	-	0.039
758	5118.46	-	-	-	0.582	-	0.039
759	5118.14	-	-	-	0.583	-	0.040
760	5117.83	-	-	-	0.583	-	0.040
761	5117.52	-	-	-	0.586	-	0.040
762	5117.21	-	-	-	0.586	-	0.040
763	5116.90	-	-	-	0.587	-	0.040
764	5116.60	-	-	-	0.587	-	0.042
765	5116.30	-	-	-	0.587	-	0.040
766	5116.00	-	-	-	0.588	-	0.040
767	5115.69	-	-	-	0.589	-	0.040
768	5115.39	-	-	-	0.590	-	0.040
769	5115.10	-	-	-	0.590	-	0.039
770	5114.80	-	-	-	0.591	-	0.040

Continued on next page

Table 13 – continued from previous page - IEEE8500 - n2250

		Time (sec)					
m	best ENS	ILP-GALIAS	ILP-IFLOWS	DP-TS	DP-N2M2	ILP-CUTS	DP-PC
771	5114.50	-	-	-	0.593	-	0.039
772	5114.21	-	-	-	0.593	-	0.039
773	5113.92	-	-	-	0.594	-	0.039
774	5113.62	-	-	-	0.594	-	0.039
775	5113.33	-	-	-	0.595	-	0.039
776	5113.04	-	-	-	0.596	-	0.039
777	5112.76	-	-	-	0.596	-	0.040
778	5112.47	-	-	-	0.597	-	0.040
779	5112.18	-	-	-	0.598	-	0.042
780	5111.89	-	-	-	0.599	-	0.041
781	5111.61	-	-	-	0.600	-	0.040
782	5111.32	-	-	-	0.600	-	0.040
783	5111.04	-	-	-	0.601	-	0.040
784	5110.76	-	-	-	0.601	-	0.041
785	5110.48	-	-	-	0.603	-	0.041
786	5110.20	-	-	-	0.604	-	0.041
787	5109.93	-	-	-	0.604	-	0.041
788	5109.65	-	-	-	0.606	-	0.041
789	5109.38	-	-	-	0.606	-	0.041
790	5109.12	-	-	-	0.607	-	0.040
791	5108.85	-	-	-	0.608	-	0.040
792	5108.58	-	-	-	0.610	-	0.040
793	5108.31	-	-	-	0.609	-	0.042
794	5108.05	-	-	-	0.610	-	0.041
795	5107.78	-	-	-	0.610	-	0.040
796	5107.52	-	-	-	0.611	-	0.040
797	5107.25	-	-	-	0.612	-	0.040
798	5106.99	-	-	-	0.613	-	0.040
799	5106.73	-	-	-	0.614	-	0.040
800	5106.47	-	-	-	0.615	-	0.040
801	5106.21	-	-	-	0.615	-	0.040
802	5105.96	-	-	-	0.616	-	0.040
803	5105.70	-	-	-	0.617	-	0.040
804	5105.44	-	-	-	0.618	-	0.040
805	5105.19	-	-	-	0.619	-	0.040
806	5104.93	-	-	-	0.619	-	0.040
807	5104.68	-	-	-	0.620	-	0.041
808	5104.42	-	-	-	0.621	-	0.043
809	5104.17	-	-	-	0.622	-	0.041
810	5103.92	-	-	-	0.623	-	0.040
811	5103.66	-	-	-	0.623	-	0.040
812	5103.41	-	-	-	0.624	-	0.040
813	5103.17	-	-	-	0.625	-	0.040
814	5102.92	-	-	-	0.626	-	0.040
815	5102.67	-	-	-	0.626	-	0.040
816	5102.43	-	-	-	0.627	-	0.040
817	5102.18	-	-	-	0.627	-	0.040
818	5101.94	-	-	-	0.629	-	0.040
819	5101.69	-	-	-	0.629	-	0.040
820	5101.45	-	-	-	0.630	-	0.040
821	5101.21	-	-	-	0.630	-	0.040
822	5100.98	-	-	-	0.643	-	0.039

Continued on next page

Table 13 – continued from previous page - IEEE8500 - n2250

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
823	5100.74	-	-	-	0.642	-	0.040
824	5100.50	-	-	-	0.643	-	0.039
825	5100.27	-	-	-	0.644	-	0.038
826	5100.03	-	-	-	0.645	-	0.038
827	5099.79	-	-	-	0.645	-	0.038
828	5099.56	-	-	-	0.647	-	0.038
829	5099.33	-	-	-	0.647	-	0.038
830	5099.10	-	-	-	0.650	-	0.038
831	5098.86	-	-	-	0.649	-	0.038
832	5098.63	-	-	-	0.649	-	0.038
833	5098.40	-	-	-	0.650	-	0.038
834	5098.17	-	-	-	0.651	-	0.038
835	5097.94	-	-	-	0.652	-	0.038
836	5097.71	-	-	-	0.652	-	0.038
837	5097.49	-	-	-	0.653	-	0.038
838	5097.26	-	-	-	0.654	-	0.040
839	5097.04	-	-	-	0.655	-	0.039
840	5096.81	-	-	-	0.656	-	0.038
841	5096.59	-	-	-	0.657	-	0.038
842	5096.37	-	-	-	0.657	-	0.038
843	5096.15	-	-	-	0.657	-	0.038
844	5095.93	-	-	-	0.659	-	0.038
845	5095.71	-	-	-	0.660	-	0.038
846	5095.49	-	-	-	0.660	-	0.038
847	5095.27	-	-	-	0.661	-	0.038
848	5095.05	-	-	-	0.662	-	0.038
849	5094.83	-	-	-	0.663	-	0.038
850	5094.62	-	-	-	0.664	-	0.038
851	5094.41	-	-	-	0.664	-	0.038
852	5094.20	-	-	-	0.666	-	0.038
853	5093.99	-	-	-	0.666	-	0.039
854	5093.78	-	-	-	0.666	-	0.040
855	5093.57	-	-	-	0.667	-	0.039
856	5093.36	-	-	-	0.668	-	0.038
857	5093.16	-	-	-	0.668	-	0.038
858	5092.95	-	-	-	0.669	-	0.038
859	5092.75	-	-	-	0.670	-	0.038
860	5092.54	-	-	-	0.671	-	0.038
861	5092.33	-	-	-	0.671	-	0.038
862	5092.13	-	-	-	0.672	-	0.038
863	5091.93	-	-	-	0.673	-	0.039
864	5091.73	-	-	-	0.674	-	0.039
865	5091.52	-	-	-	0.674	-	0.039
866	5091.32	-	-	-	0.675	-	0.039
867	5091.12	-	-	-	0.676	-	0.039
868	5090.92	-	-	-	0.677	-	0.039
869	5090.73	-	-	-	0.678	-	0.041
870	5090.53	-	-	-	0.679	-	0.040
871	5090.33	-	-	-	0.679	-	0.039
872	5090.14	-	-	-	0.680	-	0.039
873	5089.94	-	-	-	0.681	-	0.039
874	5089.75	-	-	-	0.682	-	0.039

Continued on next page

Table 13 – continued from previous page - IEEE8500 - n2250

		Time (sec)					
m	best ENS	ILP-GALIAS	ILP-IFLOWS	DP-TS	DP-N2M2	ILP-CUTS	DP-PC
875	5089.56	-	-	-	0.683	-	0.039
876	5089.36	-	-	-	0.684	-	0.039
877	5089.17	-	-	-	0.684	-	0.039
878	5088.98	-	-	-	0.685	-	0.039
879	5088.79	-	-	-	0.686	-	0.039
880	5088.60	-	-	-	0.687	-	0.039
881	5088.41	-	-	-	0.688	-	0.039
882	5088.23	-	-	-	0.688	-	0.039
883	5088.04	-	-	-	0.690	-	0.039
884	5087.85	-	-	-	0.689	-	0.041
885	5087.66	-	-	-	0.691	-	0.040
886	5087.48	-	-	-	0.692	-	0.039
887	5087.29	-	-	-	0.692	-	0.039
888	5087.10	-	-	-	0.693	-	0.039
889	5086.92	-	-	-	0.693	-	0.039
890	5086.73	-	-	-	0.695	-	0.039
891	5086.55	-	-	-	0.696	-	0.039
892	5086.36	-	-	-	0.696	-	0.039
893	5086.18	-	-	-	0.697	-	0.039
894	5085.99	-	-	-	0.697	-	0.039
895	5085.81	-	-	-	0.698	-	0.039
896	5085.63	-	-	-	0.699	-	0.039
897	5085.44	-	-	-	0.700	-	0.039
898	5085.26	-	-	-	0.701	-	0.039
899	5085.08	-	-	-	0.701	-	0.040
900	5084.90	-	-	-	0.701	-	0.041
901	5084.72	-	-	-	0.702	-	0.039
902	5084.54	-	-	-	0.703	-	0.039
903	5084.36	-	-	-	0.704	-	0.039
904	5084.18	-	-	-	0.705	-	0.039
905	5084.00	-	-	-	0.706	-	0.039
906	5083.82	-	-	-	0.707	-	0.039
907	5083.64	-	-	-	0.707	-	0.039
908	5083.47	-	-	-	0.707	-	0.039
909	5083.29	-	-	-	0.709	-	0.039
910	5083.12	-	-	-	0.710	-	0.039
911	5082.94	-	-	-	0.710	-	0.039
912	5082.77	-	-	-	0.711	-	0.040
913	5082.59	-	-	-	0.712	-	0.040
914	5082.42	-	-	-	0.713	-	0.041
915	5082.25	-	-	-	0.713	-	0.041
916	5082.08	-	-	-	0.705	-	0.040
917	5081.91	-	-	-	0.704	-	0.040
918	5081.74	-	-	-	0.705	-	0.040
919	5081.57	-	-	-	0.705	-	0.039
920	5081.41	-	-	-	0.706	-	0.039
921	5081.24	-	-	-	0.707	-	0.039
922	5081.07	-	-	-	0.708	-	0.039
923	5080.91	-	-	-	0.709	-	0.039
924	5080.74	-	-	-	0.710	-	0.039
925	5080.57	-	-	-	0.711	-	0.039
926	5080.41	-	-	-	0.711	-	0.039

Continued on next page

Table 13 – continued from previous page - IEEE8500 - n2250

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
927	5080.24	-	-	-	0.712	-	0.039
928	5080.08	-	-	-	0.714	-	0.039
929	5079.91	-	-	-	0.714	-	0.040
930	5079.75	-	-	-	0.716	-	0.042
931	5079.59	-	-	-	0.715	-	0.041
932	5079.42	-	-	-	0.716	-	0.041
933	5079.26	-	-	-	0.717	-	0.040
934	5079.10	-	-	-	0.716	-	0.040
935	5078.94	-	-	-	0.718	-	0.040
936	5078.78	-	-	-	0.719	-	0.040
937	5078.61	-	-	-	0.720	-	0.040
938	5078.45	-	-	-	0.720	-	0.040
939	5078.29	-	-	-	0.721	-	0.040
940	5078.13	-	-	-	0.722	-	0.040
941	5077.97	-	-	-	0.723	-	0.040
942	5077.81	-	-	-	0.723	-	0.040
943	5077.65	-	-	-	0.725	-	0.040
944	5077.50	-	-	-	0.725	-	0.042
945	5077.34	-	-	-	0.725	-	0.041
946	5077.18	-	-	-	0.726	-	0.040
947	5077.02	-	-	-	0.728	-	0.040
948	5076.86	-	-	-	0.728	-	0.040
949	5076.71	-	-	-	0.729	-	0.040
950	5076.55	-	-	-	0.730	-	0.040
951	5076.39	-	-	-	0.744	-	0.040
952	5076.24	-	-	-	0.744	-	0.040
953	5076.08	-	-	-	0.745	-	0.040
954	5075.93	-	-	-	0.746	-	0.040
955	5075.77	-	-	-	0.747	-	0.040
956	5075.62	-	-	-	0.748	-	0.040
957	5075.46	-	-	-	0.749	-	0.040
958	5075.31	-	-	-	0.739	-	0.040
959	5075.15	-	-	-	0.738	-	0.043
960	5075.00	-	-	-	0.738	-	0.041
961	5074.85	-	-	-	0.739	-	0.041
962	5074.69	-	-	-	0.740	-	0.040
963	5074.54	-	-	-	0.741	-	0.040
964	5074.39	-	-	-	0.742	-	0.040
965	5074.24	-	-	-	0.743	-	0.040
966	5074.09	-	-	-	0.744	-	0.040
967	5073.94	-	-	-	0.744	-	0.040
968	5073.79	-	-	-	0.745	-	0.040
969	5073.64	-	-	-	0.746	-	0.040
970	5073.49	-	-	-	0.750	-	0.040
971	5073.34	-	-	-	0.747	-	0.040
972	5073.20	-	-	-	0.749	-	0.040
973	5073.05	-	-	-	0.749	-	0.042
974	5072.90	-	-	-	0.750	-	0.042
975	5072.75	-	-	-	0.751	-	0.041
976	5072.61	-	-	-	0.751	-	0.040
977	5072.46	-	-	-	0.752	-	0.040
978	5072.31	-	-	-	0.753	-	0.040

Continued on next page

Table 13 – continued from previous page - IEEE8500 - n2250

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
979	5072.16	-	-	-	0.768	-	0.040
980	5072.02	-	-	-	0.767	-	0.040
981	5071.87	-	-	-	0.768	-	0.040
982	5071.73	-	-	-	0.768	-	0.040
983	5071.58	-	-	-	0.769	-	0.040
984	5071.44	-	-	-	0.770	-	0.040
985	5071.29	-	-	-	0.771	-	0.040
986	5071.15	-	-	-	0.772	-	0.040
987	5071.01	-	-	-	0.773	-	0.040
988	5070.87	-	-	-	0.774	-	0.041
989	5070.73	-	-	-	0.775	-	0.042
990	5070.58	-	-	-	0.775	-	0.041
991	5070.44	-	-	-	0.776	-	0.040
992	5070.30	-	-	-	0.776	-	0.040
993	5070.16	-	-	-	0.779	-	0.040
994	5070.02	-	-	-	0.779	-	0.040
995	5069.88	-	-	-	0.779	-	0.040
996	5069.74	-	-	-	0.779	-	0.040
997	5069.60	-	-	-	0.780	-	0.040
998	5069.47	-	-	-	0.782	-	0.040
999	5069.33	-	-	-	0.783	-	0.040
1000	5069.20	-	-	-	0.784	-	0.040
1001	5069.06	-	-	-	0.784	-	0.040
1002	5068.93	-	-	-	0.785	-	0.040
1003	5068.79	-	-	-	0.786	-	0.042
1004	5068.66	-	-	-	0.786	-	0.041
1005	5068.52	-	-	-	0.787	-	0.040
1006	5068.39	-	-	-	0.789	-	0.040
1007	5068.25	-	-	-	0.791	-	0.040
1008	5068.12	-	-	-	0.790	-	0.040
1009	5067.99	-	-	-	0.791	-	0.040
1010	5067.85	-	-	-	0.792	-	0.040
1011	5067.72	-	-	-	0.792	-	0.040
1012	5067.59	-	-	-	0.793	-	0.040
1013	5067.46	-	-	-	0.794	-	0.040
1014	5067.33	-	-	-	0.794	-	0.040
1015	5067.20	-	-	-	0.796	-	0.040
1016	5067.07	-	-	-	0.796	-	0.040
1017	5066.93	-	-	-	0.797	-	0.040
1018	5066.80	-	-	-	0.798	-	0.042
1019	5066.67	-	-	-	0.798	-	0.044
1020	5066.54	-	-	-	0.800	-	0.042
1021	5066.41	-	-	-	0.801	-	0.041
1022	5066.28	-	-	-	0.802	-	0.040
1023	5066.15	-	-	-	0.803	-	0.040
1024	5066.02	-	-	-	0.803	-	0.041
1025	5065.89	-	-	-	0.804	-	0.040
1026	5065.77	-	-	-	0.805	-	0.042
1027	5065.64	-	-	-	0.806	-	0.041
1028	5065.51	-	-	-	0.808	-	0.041
1029	5065.39	-	-	-	0.809	-	0.040
1030	5065.26	-	-	-	0.810	-	0.040

Continued on next page

Table 13 – continued from previous page - IEEE8500 - n2250

		Time (sec)					
m	best ENS	ILP-GALIAS	ILP-IFLOWS	DP-TS	DP-N2M2	ILP-CUTS	DP-PC
1031	5065.14	-	-	-	0.810	-	0.040
1032	5065.01	-	-	-	0.811	-	0.042
1033	5064.88	-	-	-	0.811	-	0.041
1034	5064.76	-	-	-	0.813	-	0.040
1035	5064.63	-	-	-	0.815	-	0.040
1036	5064.51	-	-	-	0.813	-	0.040
1037	5064.39	-	-	-	0.773	-	0.037
1038	5064.26	-	-	-	0.773	-	0.037
1039	5064.14	-	-	-	0.762	-	0.037
1040	5064.02	-	-	-	0.760	-	0.038
1041	5063.89	-	-	-	0.761	-	0.037
1042	5063.77	-	-	-	0.762	-	0.037
1043	5063.65	-	-	-	0.762	-	0.036
1044	5063.53	-	-	-	0.733	-	0.035
1045	5063.41	-	-	-	0.734	-	0.035
1046	5063.28	-	-	-	0.734	-	0.035
1047	5063.16	-	-	-	0.706	-	0.034
1048	5063.04	-	-	-	0.706	-	0.035
1049	5062.92	-	-	-	0.682	-	0.033
1050	5062.80	-	-	-	0.681	-	0.033
1051	5062.68	-	-	-	0.661	-	0.031
1052	5062.56	-	-	-	0.662	-	0.032
1053	5062.44	-	-	-	0.663	-	0.032
1054	5062.32	-	-	-	0.663	-	0.032
1055	5062.20	-	-	-	0.664	-	0.031
1056	5062.08	-	-	-	0.663	-	0.031
1057	5061.96	-	-	-	0.648	-	0.030
1058	5061.84	-	-	-	0.648	-	0.030
1059	5061.72	-	-	-	0.634	-	0.030
1060	5061.60	-	-	-	0.634	-	0.029
1061	5061.49	-	-	-	0.618	-	0.029
1062	5061.37	-	-	-	0.618	-	0.029
1063	5061.25	-	-	-	0.619	-	0.029
1064	5061.13	-	-	-	0.619	-	0.029
1065	5061.01	-	-	-	0.622	-	0.028
1066	5060.90	-	-	-	0.621	-	0.028
1067	5060.78	-	-	-	0.622	-	0.029
1068	5060.66	-	-	-	0.622	-	0.030
1069	5060.55	-	-	-	0.623	-	0.029
1070	5060.43	-	-	-	0.623	-	0.028
1071	5060.32	-	-	-	0.624	-	0.028
1072	5060.20	-	-	-	0.624	-	0.028
1073	5060.09	-	-	-	0.626	-	0.028
1074	5059.97	-	-	-	0.625	-	0.028
1075	5059.86	-	-	-	0.626	-	0.028
1076	5059.74	-	-	-	0.626	-	0.028
1077	5059.63	-	-	-	0.610	-	0.027
1078	5059.51	-	-	-	0.610	-	0.027
1079	5059.40	-	-	-	0.611	-	0.027
1080	5059.28	-	-	-	0.611	-	0.027
1081	5059.17	-	-	-	0.612	-	0.027
1082	5059.06	-	-	-	0.598	-	0.026

Continued on next page

Table 13 – continued from previous page - IEEE8500 - n2250

		Time (sec)					
m	best ENS	ILP-GALIAS	ILP-IFLOWS	DP-TS	DP-N2M2	ILP-CUTS	DP-PC
1083	5058.95	-	-	-	0.598	-	0.026
1084	5058.83	-	-	-	0.580	-	0.025
1085	5058.72	-	-	-	0.580	-	0.026
1086	5058.61	-	-	-	0.581	-	0.026
1087	5058.50	-	-	-	0.581	-	0.025
1088	5058.38	-	-	-	0.582	-	0.025
1089	5058.27	-	-	-	0.582	-	0.028
1090	5058.16	-	-	-	0.583	-	0.027
1091	5058.05	-	-	-	0.583	-	0.026
1092	5057.94	-	-	-	0.584	-	0.026
1093	5057.83	-	-	-	0.584	-	0.026
1094	5057.72	-	-	-	0.584	-	0.026
1095	5057.61	-	-	-	0.586	-	0.026
1096	5057.50	-	-	-	0.586	-	0.026
1097	5057.39	-	-	-	0.586	-	0.026
1098	5057.28	-	-	-	0.587	-	0.026
1099	5057.18	-	-	-	0.588	-	0.026
1100	5057.07	-	-	-	0.588	-	0.026
1101	5056.96	-	-	-	0.588	-	0.026
1102	5056.85	-	-	-	0.589	-	0.026
1103	5056.75	-	-	-	0.590	-	0.026
1104	5056.64	-	-	-	0.590	-	0.026
1105	5056.54	-	-	-	0.590	-	0.026
1106	5056.43	-	-	-	0.591	-	0.026
1107	5056.33	-	-	-	0.591	-	0.026
1108	5056.22	-	-	-	0.603	-	0.026
1109	5056.12	-	-	-	0.603	-	0.026
1110	5056.01	-	-	-	0.604	-	0.026
1111	5055.91	-	-	-	0.604	-	0.026
1112	5055.81	-	-	-	0.604	-	0.028
1113	5055.71	-	-	-	0.605	-	0.027
1114	5055.60	-	-	-	0.606	-	0.026
1115	5055.50	-	-	-	0.607	-	0.026
1116	5055.40	-	-	-	0.607	-	0.026
1117	5055.30	-	-	-	0.607	-	0.026
1118	5055.19	-	-	-	0.608	-	0.026
1119	5055.09	-	-	-	0.608	-	0.026
1120	5054.99	-	-	-	0.609	-	0.026
1121	5054.89	-	-	-	0.609	-	0.026
1122	5054.79	-	-	-	0.610	-	0.026
1123	5054.69	-	-	-	0.611	-	0.026
1124	5054.59	-	-	-	0.611	-	0.026
1125	5054.49	-	-	-	0.612	-	0.026
1126	5054.39	-	-	-	0.604	-	0.026
1127	5054.29	-	-	-	0.603	-	0.026
1128	5054.19	-	-	-	0.604	-	0.026
1129	5054.09	-	-	-	0.605	-	0.026
1130	5053.99	-	-	-	0.605	-	0.026
1131	5053.89	-	-	-	0.606	-	0.026
1132	5053.79	-	-	-	0.606	-	0.026
1133	5053.70	-	-	-	0.606	-	0.026
1134	5053.60	-	-	-	0.608	-	0.028

Continued on next page

Table 13 – continued from previous page - IEEE8500 - n2250

		Time (sec)					
m	best ENS	ILP-GALIAS	ILP-IFLOWS	DP-TS	DP-N2M2	ILP-CUTS	DP-PC
1135	5053.50	-	-	-	0.608	-	0.028
1136	5053.40	-	-	-	0.612	-	0.027
1137	5053.31	-	-	-	0.609	-	0.026
1138	5053.21	-	-	-	0.610	-	0.026
1139	5053.11	-	-	-	0.610	-	0.026
1140	5053.02	-	-	-	0.611	-	0.026
1141	5052.92	-	-	-	0.611	-	0.026
1142	5052.82	-	-	-	0.612	-	0.026
1143	5052.73	-	-	-	0.613	-	0.026
1144	5052.63	-	-	-	0.613	-	0.026
1145	5052.54	-	-	-	0.614	-	0.026
1146	5052.44	-	-	-	0.614	-	0.026
1147	5052.35	-	-	-	0.614	-	0.026
1148	5052.25	-	-	-	0.615	-	0.026
1149	5052.16	-	-	-	0.615	-	0.026
1150	5052.06	-	-	-	0.615	-	0.026
1151	5051.97	-	-	-	0.617	-	0.026
1152	5051.88	-	-	-	0.629	-	0.026
1153	5051.78	-	-	-	0.626	-	0.026
1154	5051.69	-	-	-	0.627	-	0.026
1155	5051.60	-	-	-	0.627	-	0.026
1156	5051.50	-	-	-	0.628	-	0.026
1157	5051.41	-	-	-	0.630	-	0.029
1158	5051.32	-	-	-	0.631	-	0.027
1159	5051.22	-	-	-	0.631	-	0.026
1160	5051.13	-	-	-	0.631	-	0.026
1161	5051.04	-	-	-	0.632	-	0.026
1162	5050.95	-	-	-	0.633	-	0.026
1163	5050.86	-	-	-	0.634	-	0.026
1164	5050.77	-	-	-	0.634	-	0.026
1165	5050.68	-	-	-	0.634	-	0.026
1166	5050.59	-	-	-	0.635	-	0.027
1167	5050.50	-	-	-	0.636	-	0.027
1168	5050.41	-	-	-	0.636	-	0.026
1169	5050.32	-	-	-	0.637	-	0.026
1170	5050.23	-	-	-	0.637	-	0.027
1171	5050.14	-	-	-	0.638	-	0.027
1172	5050.05	-	-	-	0.639	-	0.026
1173	5049.97	-	-	-	0.638	-	0.027
1174	5049.88	-	-	-	0.639	-	0.027
1175	5049.79	-	-	-	0.640	-	0.027
1176	5049.70	-	-	-	0.641	-	0.026
1177	5049.61	-	-	-	0.641	-	0.026
1178	5049.52	-	-	-	0.641	-	0.026
1179	5049.44	-	-	-	0.642	-	0.029
1180	5049.35	-	-	-	0.643	-	0.028
1181	5049.26	-	-	-	0.644	-	0.027
1182	5049.17	-	-	-	0.644	-	0.027
1183	5049.09	-	-	-	0.644	-	0.027
1184	5049.00	-	-	-	0.645	-	0.027
1185	5048.91	-	-	-	0.645	-	0.027
1186	5048.83	-	-	-	0.627	-	0.026

Continued on next page

Table 13 – continued from previous page - IEEE8500 - n2250

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
1187	5048.74	-	-	-	0.627	-	0.026
1188	5048.66	-	-	-	0.613	-	0.025
1189	5048.57	-	-	-	0.612	-	0.025
1190	5048.48	-	-	-	0.595	-	0.024
1191	5048.40	-	-	-	0.595	-	0.024
1192	5048.31	-	-	-	0.579	-	0.023
1193	5048.23	-	-	-	0.579	-	0.023
1194	5048.14	-	-	-	0.579	-	0.023
1195	5048.06	-	-	-	0.578	-	0.023
1196	5047.97	-	-	-	0.563	-	0.023
1197	5047.89	-	-	-	0.563	-	0.022
1198	5047.81	-	-	-	0.545	-	0.022
1199	5047.72	-	-	-	0.546	-	0.022
1200	5047.64	-	-	-	0.545	-	0.022
1201	5047.55	-	-	-	0.546	-	0.022
1202	5047.47	-	-	-	0.531	-	0.021
1203	5047.39	-	-	-	0.531	-	0.023
1204	5047.30	-	-	-	0.531	-	0.023
1205	5047.22	-	-	-	0.532	-	0.022
1206	5047.14	-	-	-	0.532	-	0.021
1207	5047.06	-	-	-	0.532	-	0.021
1208	5046.98	-	-	-	0.517	-	0.020
1209	5046.90	-	-	-	0.518	-	0.020
1210	5046.82	-	-	-	0.518	-	0.020
1211	5046.74	-	-	-	0.517	-	0.020
1212	5046.66	-	-	-	0.518	-	0.020
1213	5046.58	-	-	-	0.518	-	0.020
1214	5046.49	-	-	-	0.504	-	0.020
1215	5046.42	-	-	-	0.504	-	0.020
1216	5046.34	-	-	-	0.491	-	0.019
1217	5046.26	-	-	-	0.491	-	0.018
1218	5046.18	-	-	-	0.492	-	0.018
1219	5046.10	-	-	-	0.491	-	0.018
1220	5046.02	-	-	-	0.478	-	0.018
1221	5045.94	-	-	-	0.472	-	0.018
1222	5045.87	-	-	-	0.471	-	0.018
1223	5045.79	-	-	-	0.472	-	0.018
1224	5045.71	-	-	-	0.472	-	0.018
1225	5045.63	-	-	-	0.472	-	0.018
1226	5045.56	-	-	-	0.473	-	0.018
1227	5045.48	-	-	-	0.473	-	0.018
1228	5045.40	-	-	-	0.472	-	0.018
1229	5045.32	-	-	-	0.473	-	0.018
1230	5045.25	-	-	-	0.473	-	0.018
1231	5045.17	-	-	-	0.474	-	0.018
1232	5045.09	-	-	-	0.476	-	0.018
1233	5045.02	-	-	-	0.474	-	0.018
1234	5044.94	-	-	-	0.461	-	0.019
1235	5044.87	-	-	-	0.461	-	0.019
1236	5044.79	-	-	-	0.448	-	0.017
1237	5044.71	-	-	-	0.449	-	0.016
1238	5044.64	-	-	-	0.435	-	0.016

Continued on next page

Table 13 – continued from previous page - IEEE8500 - n2250

		Time (sec)					
m	best ENS	ILP-GALIAS	ILP-IFLOWS	DP-TS	DP-N2M2	ILP-CUTS	DP-PC
1239	5044.56	-	-	-	0.434	-	0.015
1240	5044.49	-	-	-	0.422	-	0.015
1241	5044.41	-	-	-	0.422	-	0.015
1242	5044.34	-	-	-	0.405	-	0.014
1243	5044.26	-	-	-	0.406	-	0.014
1244	5044.19	-	-	-	0.406	-	0.014
1245	5044.11	-	-	-	0.407	-	0.014
1246	5044.04	-	-	-	0.406	-	0.014
1247	5043.96	-	-	-	0.407	-	0.014
1248	5043.89	-	-	-	0.407	-	0.014
1249	5043.81	-	-	-	0.408	-	0.014
1250	5043.74	-	-	-	0.408	-	0.014
1251	5043.66	-	-	-	0.408	-	0.014
1252	5043.59	-	-	-	0.408	-	0.014
1253	5043.52	-	-	-	0.408	-	0.014
1254	5043.44	-	-	-	0.409	-	0.014
1255	5043.37	-	-	-	0.409	-	0.014
1256	5043.30	-	-	-	0.409	-	0.014
1257	5043.22	-	-	-	0.410	-	0.014
1258	5043.15	-	-	-	0.410	-	0.014
1259	5043.08	-	-	-	0.410	-	0.014
1260	5043.00	-	-	-	0.411	-	0.014
1261	5042.93	-	-	-	0.411	-	0.014
1262	5042.86	-	-	-	0.411	-	0.014
1263	5042.79	-	-	-	0.411	-	0.014
1264	5042.72	-	-	-	0.411	-	0.014
1265	5042.64	-	-	-	0.398	-	0.013
1266	5042.57	-	-	-	0.397	-	0.013
1267	5042.50	-	-	-	0.387	-	0.013
1268	5042.43	-	-	-	0.385	-	0.013
1269	5042.36	-	-	-	0.371	-	0.012
1270	5042.29	-	-	-	0.371	-	0.012
1271	5042.22	-	-	-	0.371	-	0.012
1272	5042.15	-	-	-	0.371	-	0.012
1273	5042.08	-	-	-	0.357	-	0.011
1274	5042.01	-	-	-	0.357	-	0.012
1275	5041.94	-	-	-	0.342	-	0.013
1276	5041.87	-	-	-	0.343	-	0.014
1277	5041.80	-	-	-	0.343	-	0.016
1278	5041.73	-	-	-	0.342	-	0.014
1279	5041.66	-	-	-	0.330	-	0.012
1280	5041.59	-	-	-	0.330	-	0.011
1281	5041.52	-	-	-	0.318	-	0.011
1282	5041.45	-	-	-	0.318	-	0.010
1283	5041.38	-	-	-	0.307	-	0.010
1284	5041.31	-	-	-	0.306	-	0.010
1285	5041.24	-	-	-	0.296	-	0.009
1286	5041.18	-	-	-	0.295	-	0.009
1287	5041.11	-	-	-	0.285	-	0.009
1288	5041.04	-	-	-	0.285	-	0.010
1289	5040.98	-	-	-	0.274	-	0.009
1290	5040.91	-	-	-	0.275	-	0.008

Continued on next page

Table 13 – continued from previous page - IEEE8500 - n2250

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
1291	5040.84	-	-	-	0.274	-	0.008
1292	5040.78	-	-	-	0.275	-	0.008
1293	5040.71	-	-	-	0.275	-	0.008
1294	5040.64	-	-	-	0.275	-	0.007
1295	5040.58	-	-	-	0.275	-	0.008
1296	5040.51	-	-	-	0.275	-	0.008
1297	5040.45	-	-	-	0.275	-	0.008
1298	5040.38	-	-	-	0.275	-	0.008
1299	5040.31	-	-	-	0.276	-	0.008
1300	5040.25	-	-	-	0.276	-	0.008
1301	5040.18	-	-	-	0.277	-	0.008
1302	5040.12	-	-	-	0.277	-	0.007
1303	5040.05	-	-	-	0.277	-	0.007
1304	5039.99	-	-	-	0.277	-	0.007
1305	5039.92	-	-	-	0.277	-	0.008
1306	5039.86	-	-	-	0.277	-	0.008
1307	5039.79	-	-	-	0.278	-	0.007
1308	5039.73	-	-	-	0.278	-	0.007
1309	5039.66	-	-	-	0.278	-	0.007
1310	5039.60	-	-	-	0.278	-	0.007
1311	5039.54	-	-	-	0.278	-	0.007
1312	5039.47	-	-	-	0.278	-	0.007
1313	5039.41	-	-	-	0.279	-	0.007
1314	5039.34	-	-	-	0.279	-	0.007
1315	5039.28	-	-	-	0.279	-	0.007
1316	5039.21	-	-	-	0.285	-	0.007
1317	5039.15	-	-	-	0.284	-	0.007
1318	5039.09	-	-	-	0.284	-	0.007
1319	5039.02	-	-	-	0.284	-	0.007
1320	5038.96	-	-	-	0.285	-	0.007
1321	5038.90	-	-	-	0.285	-	0.007
1322	5038.83	-	-	-	0.285	-	0.007
1323	5038.77	-	-	-	0.285	-	0.007
1324	5038.71	-	-	-	0.285	-	0.007
1325	5038.65	-	-	-	0.285	-	0.007
1326	5038.58	-	-	-	0.286	-	0.007
1327	5038.52	-	-	-	0.286	-	0.007
1328	5038.46	-	-	-	0.286	-	0.007
1329	5038.40	-	-	-	0.286	-	0.007
1330	5038.34	-	-	-	0.286	-	0.007
1331	5038.28	-	-	-	0.287	-	0.007
1332	5038.22	-	-	-	0.287	-	0.007
1333	5038.16	-	-	-	0.286	-	0.007
1334	5038.10	-	-	-	0.287	-	0.007
1335	5038.04	-	-	-	0.287	-	0.007
1336	5037.98	-	-	-	0.287	-	0.007
1337	5037.92	-	-	-	0.288	-	0.007
1338	5037.86	-	-	-	0.288	-	0.007
1339	5037.80	-	-	-	0.288	-	0.007
1340	5037.74	-	-	-	0.288	-	0.007
1341	5037.68	-	-	-	0.288	-	0.007
1342	5037.62	-	-	-	0.288	-	0.007

Continued on next page

Table 13 – continued from previous page - IEEE8500 - n2250

		Time (sec)					
m	best ENS	ILP-GALIAS	ILP-IFLOWS	DP-TS	DP-N2M2	ILP-CUTS	DP-PC
1343	5037.56	-	-	-	0.288	-	0.007
1344	5037.50	-	-	-	0.289	-	0.007
1345	5037.45	-	-	-	0.289	-	0.007
1346	5037.39	-	-	-	0.289	-	0.007
1347	5037.33	-	-	-	0.289	-	0.007
1348	5037.27	-	-	-	0.290	-	0.007
1349	5037.21	-	-	-	0.290	-	0.010
1350	5037.16	-	-	-	0.289	-	0.010
1351	5037.10	-	-	-	0.270	-	0.008
1352	5037.04	-	-	-	0.270	-	0.007
1353	5036.98	-	-	-	0.256	-	0.007
1354	5036.93	-	-	-	0.256	-	0.006
1355	5036.87	-	-	-	0.256	-	0.006
1356	5036.81	-	-	-	0.256	-	0.006
1357	5036.75	-	-	-	0.256	-	0.006
1358	5036.70	-	-	-	0.257	-	0.006
1359	5036.64	-	-	-	0.257	-	0.006
1360	5036.58	-	-	-	0.257	-	0.006
1361	5036.53	-	-	-	0.245	-	0.005
1362	5036.47	-	-	-	0.245	-	0.005
1363	5036.41	-	-	-	0.245	-	0.005
1364	5036.36	-	-	-	0.246	-	0.005
1365	5036.30	-	-	-	0.246	-	0.005
1366	5036.25	-	-	-	0.246	-	0.005
1367	5036.19	-	-	-	0.246	-	0.005
1368	5036.14	-	-	-	0.245	-	0.006
1369	5036.08	-	-	-	0.235	-	0.005
1370	5036.03	-	-	-	0.235	-	0.005
1371	5035.97	-	-	-	0.235	-	0.005
1372	5035.92	-	-	-	0.235	-	0.005
1373	5035.86	-	-	-	0.235	-	0.005
1374	5035.81	-	-	-	0.235	-	0.005
1375	5035.76	-	-	-	0.226	-	0.005
1376	5035.70	-	-	-	0.226	-	0.005
1377	5035.65	-	-	-	0.213	-	0.004
1378	5035.59	-	-	-	0.214	-	0.004
1379	5035.54	-	-	-	0.214	-	0.004
1380	5035.49	-	-	-	0.214	-	0.004
1381	5035.43	-	-	-	0.214	-	0.004
1382	5035.38	-	-	-	0.214	-	0.004
1383	5035.33	-	-	-	0.202	-	0.004
1384	5035.27	-	-	-	0.202	-	0.004
1385	5035.22	-	-	-	0.191	-	0.004
1386	5035.17	-	-	-	0.191	-	0.004
1387	5035.12	-	-	-	0.191	-	0.004
1388	5035.06	-	-	-	0.191	-	0.004
1389	5035.01	-	-	-	0.191	-	0.004
1390	5034.96	-	-	-	0.191	-	0.004
1391	5034.91	-	-	-	0.191	-	0.004
1392	5034.85	-	-	-	0.191	-	0.004
1393	5034.80	-	-	-	0.181	-	0.004
1394	5034.75	-	-	-	0.180	-	0.004

Continued on next page

Table 13 – continued from previous page - IEEE8500 - n2250

		Time (sec)					
m	best ENS	ILP-GALIAS	ILP-IFLOWS	DP-TS	DP-N2M2	ILP-CUTS	DP-PC
1395	5034.70	-	-	-	0.171	-	0.004
1396	5034.65	-	-	-	0.171	-	0.003
1397	5034.60	-	-	-	0.171	-	0.003
1398	5034.54	-	-	-	0.171	-	0.003
1399	5034.49	-	-	-	0.171	-	0.003
1400	5034.44	-	-	-	0.171	-	0.003
1401	5034.39	-	-	-	0.161	-	0.003
1402	5034.34	-	-	-	0.160	-	0.003
1403	5034.29	-	-	-	0.153	-	0.003
1404	5034.24	-	-	-	0.153	-	0.003
1405	5034.19	-	-	-	0.144	-	0.003
1406	5034.14	-	-	-	0.144	-	0.003
1407	5034.09	-	-	-	0.144	-	0.003
1408	5034.04	-	-	-	0.144	-	0.003
1409	5033.99	-	-	-	0.145	-	0.003
1410	5033.94	-	-	-	0.144	-	0.003
1411	5033.89	-	-	-	0.137	-	0.002
1412	5033.84	-	-	-	0.136	-	0.002
1413	5033.79	-	-	-	0.129	-	0.002
1414	5033.74	-	-	-	0.129	-	0.002
1415	5033.69	-	-	-	0.121	-	0.002
1416	5033.64	-	-	-	0.122	-	0.002
1417	5033.59	-	-	-	0.122	-	0.002
1418	5033.55	-	-	-	0.121	-	0.002
1419	5033.50	-	-	-	0.114	-	0.002
1420	5033.45	-	-	-	0.114	-	0.002
1421	5033.40	-	-	-	0.108	-	0.002
1422	5033.35	-	-	-	0.107	-	0.002
1423	5033.30	-	-	-	0.100	-	0.002
1424	5033.26	-	-	-	0.100	-	0.002
1425	5033.21	-	-	-	0.093	-	0.002
1426	5033.16	-	-	-	0.093	-	0.002
1427	5033.11	-	-	-	0.093	-	0.001
1428	5033.06	-	-	-	0.093	-	0.001
1429	5033.02	-	-	-	0.093	-	0.001
1430	5032.97	-	-	-	0.093	-	0.002
1431	5032.92	-	-	-	0.093	-	0.002
1432	5032.87	-	-	-	0.093	-	0.001
1433	5032.83	-	-	-	0.093	-	0.001
1434	5032.78	-	-	-	0.094	-	0.001
1435	5032.73	-	-	-	0.094	-	0.001
1436	5032.68	-	-	-	0.094	-	0.002
1437	5032.64	-	-	-	0.094	-	0.002
1438	5032.59	-	-	-	0.094	-	0.001
1439	5032.54	-	-	-	0.094	-	0.002
1440	5032.50	-	-	-	0.094	-	0.002
1441	5032.45	-	-	-	0.094	-	0.001
1442	5032.40	-	-	-	0.094	-	0.001
1443	5032.36	-	-	-	0.094	-	0.001
1444	5032.31	-	-	-	0.094	-	0.001
1445	5032.26	-	-	-	0.094	-	0.001
1446	5032.22	-	-	-	0.094	-	0.001

Continued on next page

Table 13 – continued from previous page - IEEE8500 - n2250

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
1447	5032.17	-	-	-	0.094	-	0.001
1448	5032.12	-	-	-	0.094	-	0.001
1449	5032.08	-	-	-	0.094	-	0.001
1450	5032.03	-	-	-	0.094	-	0.001
1451	5031.99	-	-	-	0.094	-	0.001
1452	5031.94	-	-	-	0.094	-	0.001
1453	5031.89	-	-	-	0.095	-	0.001
1454	5031.85	-	-	-	0.094	-	0.001
1455	5031.80	-	-	-	0.094	-	0.001
1456	5031.76	-	-	-	0.095	-	0.001
1457	5031.71	-	-	-	0.095	-	0.002
1458	5031.67	-	-	-	0.095	-	0.002
1459	5031.62	-	-	-	0.095	-	0.002
1460	5031.58	-	-	-	0.095	-	0.001
1461	5031.53	-	-	-	0.095	-	0.001
1462	5031.49	-	-	-	0.095	-	0.001
1463	5031.44	-	-	-	0.095	-	0.001
1464	5031.40	-	-	-	0.095	-	0.001
1465	5031.36	-	-	-	0.095	-	0.001
1466	5031.31	-	-	-	0.096	-	0.001
1467	5031.27	-	-	-	0.095	-	0.001
1468	5031.22	-	-	-	0.095	-	0.001
1469	5031.18	-	-	-	0.096	-	0.001
1470	5031.13	-	-	-	0.095	-	0.001
1471	5031.09	-	-	-	0.095	-	0.001
1472	5031.05	-	-	-	0.096	-	0.001
1473	5031.00	-	-	-	0.096	-	0.001
1474	5030.96	-	-	-	0.096	-	0.001
1475	5030.91	-	-	-	0.096	-	0.001
1476	5030.87	-	-	-	0.096	-	0.002
1477	5030.83	-	-	-	0.096	-	0.002
1478	5030.78	-	-	-	0.096	-	0.001
1479	5030.74	-	-	-	0.096	-	0.001
1480	5030.69	-	-	-	0.096	-	0.001
1481	5030.65	-	-	-	0.096	-	0.001
1482	5030.61	-	-	-	0.096	-	0.001
1483	5030.56	-	-	-	0.096	-	0.001
1484	5030.52	-	-	-	0.096	-	0.001
1485	5030.48	-	-	-	0.096	-	0.001
1486	5030.43	-	-	-	0.096	-	0.001
1487	5030.39	-	-	-	0.096	-	0.001
1488	5030.35	-	-	-	0.097	-	0.001
1489	5030.31	-	-	-	0.097	-	0.001
1490	5030.26	-	-	-	0.097	-	0.001
1491	5030.22	-	-	-	0.097	-	0.001
1492	5030.18	-	-	-	0.097	-	0.001
1493	5030.14	-	-	-	0.097	-	0.001
1494	5030.09	-	-	-	0.097	-	0.001
1495	5030.05	-	-	-	0.097	-	0.001
1496	5030.01	-	-	-	0.097	-	0.001
1497	5029.97	-	-	-	0.097	-	0.001
1498	5029.93	-	-	-	0.097	-	0.001

Continued on next page

Table 13 – continued from previous page - IEEE8500 - n2250

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
1499	5029.88	-	-	-	0.097	-	0.002
1500	5029.84	-	-	-	0.097	-	0.001
1501	5029.80	-	-	-	0.097	-	0.001
1502	5029.76	-	-	-	0.097	-	0.001
1503	5029.72	-	-	-	0.097	-	0.001
1504	5029.68	-	-	-	0.097	-	0.001
1505	5029.63	-	-	-	0.097	-	0.001
1506	5029.59	-	-	-	0.097	-	0.001
1507	5029.55	-	-	-	0.097	-	0.001
1508	5029.51	-	-	-	0.097	-	0.001
1509	5029.47	-	-	-	0.098	-	0.001
1510	5029.43	-	-	-	0.098	-	0.001
1511	5029.39	-	-	-	0.098	-	0.001
1512	5029.35	-	-	-	0.098	-	0.001
1513	5029.31	-	-	-	0.098	-	0.001
1514	5029.26	-	-	-	0.098	-	0.001
1515	5029.22	-	-	-	0.098	-	0.001
1516	5029.18	-	-	-	0.098	-	0.001
1517	5029.14	-	-	-	0.098	-	0.001
1518	5029.10	-	-	-	0.098	-	0.001
1519	5029.06	-	-	-	0.098	-	0.001
1520	5029.02	-	-	-	0.098	-	0.001
1521	5028.98	-	-	-	0.098	-	0.001
1522	5028.94	-	-	-	0.098	-	0.001
1523	5028.90	-	-	-	0.098	-	0.001
1524	5028.86	-	-	-	0.098	-	0.001
1525	5028.82	-	-	-	0.098	-	0.001
1526	5028.78	-	-	-	0.099	-	0.001
1527	5028.74	-	-	-	0.099	-	0.001
1528	5028.71	-	-	-	0.099	-	0.001
1529	5028.67	-	-	-	0.099	-	0.001
1530	5028.63	-	-	-	0.099	-	0.002
1531	5028.59	-	-	-	0.099	-	0.002
1532	5028.55	-	-	-	0.099	-	0.001
1533	5028.51	-	-	-	0.099	-	0.001
1534	5028.47	-	-	-	0.099	-	0.001
1535	5028.43	-	-	-	0.099	-	0.001
1536	5028.39	-	-	-	0.099	-	0.001
1537	5028.36	-	-	-	0.099	-	0.001
1538	5028.32	-	-	-	0.099	-	0.001
1539	5028.28	-	-	-	0.099	-	0.001
1540	5028.24	-	-	-	0.099	-	0.001
1541	5028.20	-	-	-	0.099	-	0.001
1542	5028.17	-	-	-	0.100	-	0.001
1543	5028.13	-	-	-	0.099	-	0.001
1544	5028.09	-	-	-	0.100	-	0.002
1545	5028.05	-	-	-	0.100	-	0.002
1546	5028.02	-	-	-	0.100	-	0.002
1547	5027.98	-	-	-	0.100	-	0.002
1548	5027.94	-	-	-	0.100	-	0.002
1549	5027.90	-	-	-	0.100	-	0.002
1550	5027.87	-	-	-	0.100	-	0.002

Continued on next page

Table 13 – continued from previous page - IEEE8500 - n2250

		Time (sec)					
m	best ENS	ILP-GALIAS	ILP-IFLOWS	DP-TS	DP-N2M2	ILP-CUTS	DP-PC
1551	5027.83	-	-	-	0.100	-	0.002
1552	5027.79	-	-	-	0.100	-	0.002
1553	5027.76	-	-	-	0.099	-	0.002
1554	5027.72	-	-	-	0.099	-	0.002
1555	5027.68	-	-	-	0.099	-	0.002
1556	5027.65	-	-	-	0.099	-	0.001
1557	5027.61	-	-	-	0.099	-	0.001
1558	5027.57	-	-	-	0.099	-	0.002
1559	5027.54	-	-	-	0.099	-	0.001
1560	5027.50	-	-	-	0.099	-	0.001
1561	5027.47	-	-	-	0.099	-	0.001
1562	5027.43	-	-	-	0.099	-	0.001
1563	5027.39	-	-	-	0.099	-	0.002
1564	5027.36	-	-	-	0.099	-	0.002
1565	5027.32	-	-	-	0.099	-	0.001
1566	5027.29	-	-	-	0.099	-	0.002
1567	5027.25	-	-	-	0.099	-	0.002
1568	5027.22	-	-	-	0.099	-	0.001
1569	5027.18	-	-	-	0.099	-	0.001
1570	5027.15	-	-	-	0.099	-	0.001
1571	5027.11	-	-	-	0.099	-	0.001
1572	5027.08	-	-	-	0.099	-	0.001
1573	5027.04	-	-	-	0.100	-	0.001
1574	5027.01	-	-	-	0.100	-	0.001
1575	5026.97	-	-	-	0.099	-	0.001
1576	5026.94	-	-	-	0.100	-	0.001
1577	5026.90	-	-	-	0.100	-	0.001
1578	5026.87	-	-	-	0.100	-	0.002
1579	5026.83	-	-	-	0.100	-	0.001
1580	5026.80	-	-	-	0.100	-	0.001
1581	5026.76	-	-	-	0.100	-	0.001
1582	5026.73	-	-	-	0.100	-	0.001
1583	5026.69	-	-	-	0.100	-	0.001
1584	5026.66	-	-	-	0.100	-	0.001
1585	5026.62	-	-	-	0.100	-	0.001
1586	5026.59	-	-	-	0.100	-	0.001
1587	5026.55	-	-	-	0.101	-	0.001
1588	5026.52	-	-	-	0.101	-	0.001
1589	5026.49	-	-	-	0.101	-	0.001
1590	5026.45	-	-	-	0.101	-	0.001
1591	5026.42	-	-	-	0.101	-	0.001
1592	5026.38	-	-	-	0.101	-	0.001
1593	5026.35	-	-	-	0.101	-	0.001
1594	5026.32	-	-	-	0.101	-	0.001
1595	5026.28	-	-	-	0.101	-	0.001
1596	5026.25	-	-	-	0.103	-	0.001
1597	5026.21	-	-	-	0.103	-	0.001
1598	5026.18	-	-	-	0.103	-	0.002
1599	5026.15	-	-	-	0.103	-	0.002
1600	5026.11	-	-	-	0.103	-	0.001
1601	5026.08	-	-	-	0.103	-	0.001
1602	5026.04	-	-	-	0.103	-	0.001

Continued on next page

Table 13 – continued from previous page - IEEE8500 - n2250

		Time (sec)					
m	best ENS	ILP-GALIAS	ILP-IFLOWS	DP-TS	DP-N2M2	ILP-CUTS	DP-PC
1603	5026.01	-	-	-	0.103	-	0.001
1604	5025.98	-	-	-	0.103	-	0.001
1605	5025.94	-	-	-	0.103	-	0.001
1606	5025.91	-	-	-	0.103	-	0.001
1607	5025.88	-	-	-	0.103	-	0.001
1608	5025.85	-	-	-	0.103	-	0.001
1609	5025.81	-	-	-	0.103	-	0.001
1610	5025.78	-	-	-	0.103	-	0.001
1611	5025.75	-	-	-	0.104	-	0.001
1612	5025.71	-	-	-	0.104	-	0.001
1613	5025.68	-	-	-	0.104	-	0.001
1614	5025.65	-	-	-	0.103	-	0.001
1615	5025.62	-	-	-	0.104	-	0.001
1616	5025.59	-	-	-	0.104	-	0.001
1617	5025.55	-	-	-	0.104	-	0.001
1618	5025.52	-	-	-	0.104	-	0.001
1619	5025.49	-	-	-	0.104	-	0.001
1620	5025.46	-	-	-	0.104	-	0.001
1621	5025.43	-	-	-	0.104	-	0.001
1622	5025.40	-	-	-	0.104	-	0.001
1623	5025.36	-	-	-	0.104	-	0.001
1624	5025.33	-	-	-	0.104	-	0.001
1625	5025.30	-	-	-	0.104	-	0.001
1626	5025.27	-	-	-	0.104	-	0.001
1627	5025.24	-	-	-	0.104	-	0.001
1628	5025.21	-	-	-	0.104	-	0.001
1629	5025.18	-	-	-	0.105	-	0.001
1630	5025.15	-	-	-	0.104	-	0.001
1631	5025.12	-	-	-	0.104	-	0.001
1632	5025.08	-	-	-	0.104	-	0.001
1633	5025.05	-	-	-	0.105	-	0.001
1634	5025.02	-	-	-	0.104	-	0.001
1635	5024.99	-	-	-	0.104	-	0.001
1636	5024.96	-	-	-	0.105	-	0.001
1637	5024.93	-	-	-	0.104	-	0.001
1638	5024.90	-	-	-	0.103	-	0.002
1639	5024.87	-	-	-	0.103	-	0.001
1640	5024.84	-	-	-	0.103	-	0.001
1641	5024.81	-	-	-	0.103	-	0.001
1642	5024.78	-	-	-	0.103	-	0.001
1643	5024.75	-	-	-	0.103	-	0.001
1644	5024.72	-	-	-	0.103	-	0.001
1645	5024.69	-	-	-	0.104	-	0.001
1646	5024.66	-	-	-	0.104	-	0.001
1647	5024.63	-	-	-	0.104	-	0.001
1648	5024.60	-	-	-	0.104	-	0.001
1649	5024.57	-	-	-	0.104	-	0.001
1650	5024.54	-	-	-	0.104	-	0.001
1651	5024.51	-	-	-	0.104	-	0.001
1652	5024.48	-	-	-	0.104	-	0.001
1653	5024.45	-	-	-	0.104	-	0.001
1654	5024.42	-	-	-	0.104	-	0.001

Continued on next page

Table 13 – continued from previous page - IEEE8500 - n2250

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
1655	5024.39	-	-	-	0.104	-	0.001
1656	5024.36	-	-	-	0.104	-	0.001
1657	5024.33	-	-	-	0.104	-	0.001
1658	5024.30	-	-	-	0.104	-	0.001
1659	5024.27	-	-	-	0.104	-	0.001
1660	5024.24	-	-	-	0.104	-	0.001
1661	5024.21	-	-	-	0.104	-	0.001
1662	5024.18	-	-	-	0.104	-	0.001
1663	5024.15	-	-	-	0.105	-	0.001
1664	5024.12	-	-	-	0.104	-	0.001
1665	5024.09	-	-	-	0.105	-	0.001
1666	5024.06	-	-	-	0.105	-	0.001
1667	5024.04	-	-	-	0.105	-	0.001
1668	5024.01	-	-	-	0.105	-	0.001
1669	5023.98	-	-	-	0.105	-	0.001
1670	5023.95	-	-	-	0.105	-	0.001
1671	5023.92	-	-	-	0.105	-	0.001
1672	5023.89	-	-	-	0.105	-	0.001
1673	5023.86	-	-	-	0.105	-	0.001
1674	5023.83	-	-	-	0.105	-	0.001
1675	5023.80	-	-	-	0.105	-	0.001
1676	5023.78	-	-	-	0.105	-	0.001
1677	5023.75	-	-	-	0.105	-	0.001
1678	5023.72	-	-	-	0.106	-	0.001
1679	5023.69	-	-	-	0.106	-	0.001
1680	5023.66	-	-	-	0.105	-	0.001
1681	5023.63	-	-	-	0.106	-	0.001
1682	5023.61	-	-	-	0.105	-	0.001
1683	5023.58	-	-	-	0.106	-	0.001
1684	5023.55	-	-	-	0.106	-	0.001
1685	5023.52	-	-	-	0.106	-	0.001
1686	5023.49	-	-	-	0.106	-	0.001
1687	5023.46	-	-	-	0.106	-	0.001
1688	5023.44	-	-	-	0.106	-	0.001
1689	5023.41	-	-	-	0.106	-	0.001
1690	5023.38	-	-	-	0.106	-	0.001
1691	5023.35	-	-	-	0.106	-	0.001
1692	5023.33	-	-	-	0.106	-	0.001
1693	5023.30	-	-	-	0.106	-	0.001
1694	5023.27	-	-	-	0.106	-	0.001
1695	5023.24	-	-	-	0.106	-	0.001
1696	5023.22	-	-	-	0.106	-	0.001
1697	5023.19	-	-	-	0.106	-	0.001
1698	5023.16	-	-	-	0.106	-	0.001
1699	5023.13	-	-	-	0.106	-	0.001
1700	5023.11	-	-	-	0.106	-	0.001
1701	5023.08	-	-	-	0.107	-	0.002
1702	5023.05	-	-	-	0.107	-	0.002
1703	5023.03	-	-	-	0.107	-	0.001
1704	5023.00	-	-	-	0.106	-	0.001
1705	5022.97	-	-	-	0.107	-	0.001
1706	5022.94	-	-	-	0.107	-	0.001

Continued on next page

Table 13 – continued from previous page - IEEE8500 - n2250

		Time (sec)					
m	best ENS	ILP-GALIAS	ILP-IFLOWS	DP-TS	DP-N2M2	ILP-CUTS	DP-PC
1707	5022.92	-	-	-	0.107	-	0.001
1708	5022.89	-	-	-	0.107	-	0.001
1709	5022.86	-	-	-	0.107	-	0.001
1710	5022.84	-	-	-	0.107	-	0.001
1711	5022.81	-	-	-	0.107	-	0.001
1712	5022.78	-	-	-	0.107	-	0.001
1713	5022.76	-	-	-	0.107	-	0.001
1714	5022.73	-	-	-	0.107	-	0.001
1715	5022.70	-	-	-	0.107	-	0.001
1716	5022.68	-	-	-	0.107	-	0.001
1717	5022.65	-	-	-	0.107	-	0.001
1718	5022.62	-	-	-	0.108	-	0.001
1719	5022.60	-	-	-	0.108	-	0.001
1720	5022.57	-	-	-	0.108	-	0.001
1721	5022.55	-	-	-	0.108	-	0.001
1722	5022.52	-	-	-	0.108	-	0.001
1723	5022.49	-	-	-	0.108	-	0.001
1724	5022.47	-	-	-	0.108	-	0.001
1725	5022.44	-	-	-	0.107	-	0.001
1726	5022.42	-	-	-	0.108	-	0.001
1727	5022.39	-	-	-	0.108	-	0.001
1728	5022.36	-	-	-	0.108	-	0.001
1729	5022.34	-	-	-	0.108	-	0.001
1730	5022.31	-	-	-	0.108	-	0.001
1731	5022.29	-	-	-	0.108	-	0.001
1732	5022.26	-	-	-	0.108	-	0.001
1733	5022.24	-	-	-	0.108	-	0.001
1734	5022.21	-	-	-	0.108	-	0.001
1735	5022.18	-	-	-	0.108	-	0.001
1736	5022.16	-	-	-	0.108	-	0.001
1737	5022.13	-	-	-	0.108	-	0.001
1738	5022.11	-	-	-	0.108	-	0.001
1739	5022.08	-	-	-	0.109	-	0.001
1740	5022.06	-	-	-	0.108	-	0.001
1741	5022.03	-	-	-	0.108	-	0.001
1742	5022.01	-	-	-	0.109	-	0.001
1743	5021.98	-	-	-	0.109	-	0.001
1744	5021.96	-	-	-	0.109	-	0.001
1745	5021.93	-	-	-	0.109	-	0.001
1746	5021.91	-	-	-	0.109	-	0.001
1747	5021.88	-	-	-	0.109	-	0.001
1748	5021.86	-	-	-	0.109	-	0.001
1749	5021.83	-	-	-	0.109	-	0.002
1750	5021.81	-	-	-	0.109	-	0.001
1751	5021.78	-	-	-	0.109	-	0.001
1752	5021.76	-	-	-	0.109	-	0.001
1753	5021.74	-	-	-	0.109	-	0.001
1754	5021.71	-	-	-	0.109	-	0.001
1755	5021.69	-	-	-	0.109	-	0.001
1756	5021.66	-	-	-	0.109	-	0.001
1757	5021.64	-	-	-	0.109	-	0.001
1758	5021.62	-	-	-	0.109	-	0.001

Continued on next page

Table 13 – continued from previous page - IEEE8500 - n2250

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
1759	5021.59	-	-	-	0.110	-	0.001
1760	5021.57	-	-	-	0.109	-	0.001
1761	5021.54	-	-	-	0.110	-	0.001
1762	5021.52	-	-	-	0.110	-	0.001
1763	5021.50	-	-	-	0.110	-	0.001
1764	5021.47	-	-	-	0.110	-	0.001
1765	5021.45	-	-	-	0.110	-	0.001
1766	5021.42	-	-	-	0.110	-	0.001
1767	5021.40	-	-	-	0.110	-	0.001
1768	5021.38	-	-	-	0.110	-	0.001
1769	5021.35	-	-	-	0.110	-	0.001
1770	5021.33	-	-	-	0.110	-	0.001
1771	5021.31	-	-	-	0.110	-	0.001
1772	5021.28	-	-	-	0.110	-	0.001
1773	5021.26	-	-	-	0.110	-	0.001
1774	5021.24	-	-	-	0.110	-	0.001
1775	5021.21	-	-	-	0.110	-	0.001
1776	5021.19	-	-	-	0.110	-	0.001
1777	5021.17	-	-	-	0.110	-	0.001
1778	5021.14	-	-	-	0.110	-	0.001
1779	5021.12	-	-	-	0.110	-	0.001
1780	5021.10	-	-	-	0.111	-	0.001
1781	5021.07	-	-	-	0.111	-	0.001
1782	5021.05	-	-	-	0.111	-	0.001
1783	5021.03	-	-	-	0.111	-	0.001
1784	5021.00	-	-	-	0.111	-	0.001
1785	5020.98	-	-	-	0.111	-	0.001
1786	5020.96	-	-	-	0.111	-	0.001
1787	5020.94	-	-	-	0.111	-	0.001
1788	5020.91	-	-	-	0.111	-	0.001
1789	5020.89	-	-	-	0.111	-	0.001
1790	5020.87	-	-	-	0.111	-	0.001
1791	5020.85	-	-	-	0.111	-	0.001
1792	5020.82	-	-	-	0.111	-	0.001
1793	5020.80	-	-	-	0.111	-	0.001
1794	5020.78	-	-	-	0.111	-	0.001
1795	5020.76	-	-	-	0.111	-	0.001
1796	5020.73	-	-	-	0.111	-	0.001
1797	5020.71	-	-	-	0.112	-	0.001
1798	5020.69	-	-	-	0.111	-	0.001
1799	5020.67	-	-	-	0.111	-	0.001
1800	5020.64	-	-	-	0.112	-	0.001
1801	5020.62	-	-	-	0.112	-	0.001
1802	5020.60	-	-	-	0.112	-	0.001
1803	5020.58	-	-	-	0.112	-	0.001
1804	5020.56	-	-	-	0.112	-	0.001
1805	5020.53	-	-	-	0.112	-	0.001
1806	5020.51	-	-	-	0.112	-	0.001
1807	5020.49	-	-	-	0.112	-	0.001
1808	5020.47	-	-	-	0.112	-	0.001
1809	5020.45	-	-	-	0.112	-	0.001
1810	5020.42	-	-	-	0.112	-	0.001

Continued on next page

Table 13 – continued from previous page - IEEE8500 - n2250

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
1811	5020.40	-	-	-	0.112	-	0.001
1812	5020.38	-	-	-	0.112	-	0.001
1813	5020.36	-	-	-	0.112	-	0.001
1814	5020.34	-	-	-	0.113	-	0.001
1815	5020.32	-	-	-	0.112	-	0.001
1816	5020.30	-	-	-	0.113	-	0.001
1817	5020.27	-	-	-	0.113	-	0.001
1818	5020.25	-	-	-	0.113	-	0.001
1819	5020.23	-	-	-	0.113	-	0.001
1820	5020.21	-	-	-	0.113	-	0.001
1821	5020.19	-	-	-	0.113	-	0.001
1822	5020.17	-	-	-	0.113	-	0.001
1823	5020.15	-	-	-	0.113	-	0.001
1824	5020.13	-	-	-	0.113	-	0.001
1825	5020.11	-	-	-	0.113	-	0.001
1826	5020.09	-	-	-	0.113	-	0.001
1827	5020.07	-	-	-	0.113	-	0.001
1828	5020.05	-	-	-	0.113	-	0.001
1829	5020.03	-	-	-	0.113	-	0.001
1830	5020.01	-	-	-	0.113	-	0.001
1831	5019.99	-	-	-	0.114	-	0.001
1832	5019.97	-	-	-	0.113	-	0.001
1833	5019.95	-	-	-	0.113	-	0.001
1834	5019.93	-	-	-	0.114	-	0.001
1835	5019.91	-	-	-	0.113	-	0.001
1836	5019.89	-	-	-	0.114	-	0.001
1837	5019.87	-	-	-	0.114	-	0.001
1838	5019.85	-	-	-	0.114	-	0.001
1839	5019.83	-	-	-	0.114	-	0.001
1840	5019.81	-	-	-	0.114	-	0.001
1841	5019.79	-	-	-	0.114	-	0.001
1842	5019.77	-	-	-	0.114	-	0.001
1843	5019.75	-	-	-	0.114	-	0.001
1844	5019.73	-	-	-	0.114	-	0.001
1845	5019.71	-	-	-	0.114	-	0.001
1846	5019.69	-	-	-	0.114	-	0.001
1847	5019.67	-	-	-	0.114	-	0.001
1848	5019.65	-	-	-	0.114	-	0.001
1849	5019.63	-	-	-	0.114	-	0.001
1850	5019.61	-	-	-	0.114	-	0.002
1851	5019.59	-	-	-	0.115	-	0.001
1852	5019.58	-	-	-	0.114	-	0.001
1853	5019.56	-	-	-	0.115	-	0.001
1854	5019.54	-	-	-	0.114	-	0.001
1855	5019.52	-	-	-	0.114	-	0.001
1856	5019.50	-	-	-	0.115	-	0.001
1857	5019.48	-	-	-	0.115	-	0.001
1858	5019.46	-	-	-	0.114	-	0.001
1859	5019.44	-	-	-	0.115	-	0.001
1860	5019.42	-	-	-	0.115	-	0.001
1861	5019.41	-	-	-	0.115	-	0.001
1862	5019.39	-	-	-	0.115	-	0.001

Continued on next page

Table 13 – continued from previous page - IEEE8500 - n2250

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
1863	5019.37	-	-	-	0.115	-	0.001
1864	5019.35	-	-	-	0.115	-	0.001
1865	5019.33	-	-	-	0.115	-	0.001
1866	5019.31	-	-	-	0.116	-	0.001
1867	5019.29	-	-	-	0.115	-	0.001
1868	5019.28	-	-	-	0.115	-	0.001
1869	5019.26	-	-	-	0.115	-	0.001
1870	5019.24	-	-	-	0.115	-	0.001
1871	5019.22	-	-	-	0.116	-	0.001
1872	5019.21	-	-	-	0.116	-	0.001
1873	5019.19	-	-	-	0.116	-	0.001
1874	5019.17	-	-	-	0.116	-	0.001
1875	5019.15	-	-	-	0.116	-	0.001
1876	5019.14	-	-	-	0.116	-	0.001
1877	5019.12	-	-	-	0.116	-	0.001
1878	5019.10	-	-	-	0.116	-	0.001
1879	5019.08	-	-	-	0.116	-	0.001
1880	5019.07	-	-	-	0.116	-	0.002
1881	5019.05	-	-	-	0.116	-	0.002
1882	5019.03	-	-	-	0.116	-	0.001
1883	5019.01	-	-	-	0.116	-	0.001
1884	5019.00	-	-	-	0.116	-	0.002
1885	5018.98	-	-	-	0.116	-	0.001
1886	5018.96	-	-	-	0.116	-	0.001
1887	5018.95	-	-	-	0.116	-	0.001
1888	5018.93	-	-	-	0.116	-	0.001
1889	5018.91	-	-	-	0.116	-	0.001
1890	5018.90	-	-	-	0.116	-	0.001
1891	5018.88	-	-	-	0.116	-	0.001
1892	5018.86	-	-	-	0.116	-	0.001
1893	5018.85	-	-	-	0.117	-	0.001
1894	5018.83	-	-	-	0.117	-	0.001
1895	5018.81	-	-	-	0.117	-	0.001
1896	5018.80	-	-	-	0.117	-	0.001
1897	5018.78	-	-	-	0.117	-	0.001
1898	5018.76	-	-	-	0.117	-	0.001
1899	5018.75	-	-	-	0.117	-	0.001
1900	5018.73	-	-	-	0.117	-	0.001
1901	5018.71	-	-	-	0.117	-	0.001
1902	5018.70	-	-	-	0.117	-	0.001
1903	5018.68	-	-	-	0.117	-	0.001
1904	5018.67	-	-	-	0.117	-	0.001
1905	5018.65	-	-	-	0.117	-	0.001
1906	5018.63	-	-	-	0.117	-	0.001
1907	5018.62	-	-	-	0.117	-	0.001
1908	5018.60	-	-	-	0.118	-	0.001
1909	5018.59	-	-	-	0.118	-	0.001
1910	5018.57	-	-	-	0.118	-	0.001
1911	5018.56	-	-	-	0.118	-	0.001
1912	5018.54	-	-	-	0.118	-	0.001
1913	5018.52	-	-	-	0.118	-	0.001
1914	5018.51	-	-	-	0.118	-	0.001

Continued on next page

Table 13 – continued from previous page - IEEE8500 - n2250

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
1915	5018.49	-	-	-	0.118	-	0.001
1916	5018.48	-	-	-	0.118	-	0.001
1917	5018.46	-	-	-	0.118	-	0.001
1918	5018.45	-	-	-	0.118	-	0.001
1919	5018.43	-	-	-	0.118	-	0.001
1920	5018.42	-	-	-	0.118	-	0.001
1921	5018.40	-	-	-	0.118	-	0.001
1922	5018.39	-	-	-	0.118	-	0.001
1923	5018.37	-	-	-	0.118	-	0.001
1924	5018.35	-	-	-	0.118	-	0.001
1925	5018.34	-	-	-	0.118	-	0.001
1926	5018.32	-	-	-	0.119	-	0.001
1927	5018.31	-	-	-	0.119	-	0.001
1928	5018.29	-	-	-	0.118	-	0.001
1929	5018.28	-	-	-	0.119	-	0.001
1930	5018.26	-	-	-	0.118	-	0.001
1931	5018.25	-	-	-	0.119	-	0.001
1932	5018.23	-	-	-	0.119	-	0.001
1933	5018.22	-	-	-	0.119	-	0.001
1934	5018.20	-	-	-	0.119	-	0.001
1935	5018.19	-	-	-	0.119	-	0.001
1936	5018.17	-	-	-	0.119	-	0.001
1937	5018.16	-	-	-	0.119	-	0.001
1938	5018.14	-	-	-	0.119	-	0.001
1939	5018.13	-	-	-	0.119	-	0.001
1940	5018.11	-	-	-	0.119	-	0.001
1941	5018.10	-	-	-	0.120	-	0.001
1942	5018.08	-	-	-	0.119	-	0.001
1943	5018.07	-	-	-	0.119	-	0.001
1944	5018.05	-	-	-	0.120	-	0.001
1945	5018.04	-	-	-	0.120	-	0.001
1946	5018.02	-	-	-	0.122	-	0.001
1947	5018.01	-	-	-	0.122	-	0.001
1948	5018.00	-	-	-	0.122	-	0.001
1949	5017.98	-	-	-	0.119	-	0.001
1950	5017.97	-	-	-	0.120	-	0.001
1951	5017.95	-	-	-	0.120	-	0.001
1952	5017.94	-	-	-	0.120	-	0.001
1953	5017.92	-	-	-	0.120	-	0.001
1954	5017.91	-	-	-	0.120	-	0.001
1955	5017.90	-	-	-	0.120	-	0.001
1956	5017.88	-	-	-	0.120	-	0.001
1957	5017.87	-	-	-	0.120	-	0.001
1958	5017.85	-	-	-	0.120	-	0.001
1959	5017.84	-	-	-	0.120	-	0.001
1960	5017.83	-	-	-	0.120	-	0.001
1961	5017.81	-	-	-	0.120	-	0.001
1962	5017.80	-	-	-	0.121	-	0.001
1963	5017.78	-	-	-	0.121	-	0.001
1964	5017.77	-	-	-	0.120	-	0.001
1965	5017.76	-	-	-	0.121	-	0.001
1966	5017.74	-	-	-	0.121	-	0.001

Continued on next page

Table 13 – continued from previous page - IEEE8500 - n2250

		Time (sec)					
m	best ENS	ILP-GALIAS	ILP-IFLOWS	DP-TS	DP-N2M2	ILP-CUTS	DP-PC
1967	5017.73	-	-	-	0.121	-	0.001
1968	5017.72	-	-	-	0.121	-	0.001
1969	5017.70	-	-	-	0.121	-	0.001
1970	5017.69	-	-	-	0.121	-	0.001
1971	5017.68	-	-	-	0.121	-	0.001
1972	5017.66	-	-	-	0.121	-	0.001
1973	5017.65	-	-	-	0.121	-	0.001
1974	5017.63	-	-	-	0.121	-	0.001
1975	5017.62	-	-	-	0.121	-	0.001
1976	5017.61	-	-	-	0.121	-	0.001
1977	5017.59	-	-	-	0.121	-	0.001
1978	5017.58	-	-	-	0.122	-	0.001
1979	5017.57	-	-	-	0.121	-	0.001
1980	5017.55	-	-	-	0.121	-	0.001
1981	5017.54	-	-	-	0.121	-	0.001
1982	5017.53	-	-	-	0.121	-	0.001
1983	5017.51	-	-	-	0.121	-	0.001
1984	5017.50	-	-	-	0.122	-	0.001
1985	5017.49	-	-	-	0.122	-	0.001
1986	5017.48	-	-	-	0.122	-	0.001
1987	5017.46	-	-	-	0.122	-	0.001
1988	5017.45	-	-	-	0.122	-	0.001
1989	5017.44	-	-	-	0.122	-	0.001
1990	5017.42	-	-	-	0.122	-	0.001
1991	5017.41	-	-	-	0.122	-	0.001
1992	5017.40	-	-	-	0.122	-	0.001
1993	5017.39	-	-	-	0.122	-	0.001
1994	5017.37	-	-	-	0.122	-	0.001
1995	5017.36	-	-	-	0.122	-	0.001
1996	5017.35	-	-	-	0.122	-	0.001
1997	5017.34	-	-	-	0.122	-	0.001
1998	5017.32	-	-	-	0.123	-	0.001
1999	5017.31	-	-	-	0.122	-	0.001
2000	5017.30	-	-	-	0.123	-	0.001
2001	5017.29	-	-	-	0.123	-	0.001
2002	5017.28	-	-	-	0.123	-	0.001
2003	5017.26	-	-	-	0.123	-	0.001
2004	5017.25	-	-	-	0.123	-	0.001
2005	5017.24	-	-	-	0.123	-	0.001
2006	5017.23	-	-	-	0.123	-	0.001
2007	5017.22	-	-	-	0.123	-	0.001
2008	5017.20	-	-	-	0.123	-	0.001
2009	5017.19	-	-	-	0.123	-	0.001
2010	5017.18	-	-	-	0.123	-	0.001
2011	5017.17	-	-	-	0.123	-	0.001
2012	5017.16	-	-	-	0.123	-	0.001
2013	5017.15	-	-	-	0.126	-	0.001
2014	5017.13	-	-	-	0.125	-	0.001
2015	5017.12	-	-	-	0.125	-	0.001
2016	5017.11	-	-	-	0.126	-	0.001
2017	5017.10	-	-	-	0.125	-	0.001
2018	5017.09	-	-	-	0.125	-	0.001

Continued on next page

Table 13 – continued from previous page - IEEE8500 - n2250

		Time (sec)					
m	best ENS	ILP-GALIAS	ILP-IFLOWS	DP-TS	DP-N2M2	ILP-CUTS	DP-PC
2019	5017.08	-	-	-	0.125	-	0.001
2020	5017.07	-	-	-	0.125	-	0.001
2021	5017.06	-	-	-	0.125	-	0.001
2022	5017.05	-	-	-	0.125	-	0.001
2023	5017.03	-	-	-	0.126	-	0.001
2024	5017.02	-	-	-	0.126	-	0.001
2025	5017.01	-	-	-	0.126	-	0.001
2026	5017.00	-	-	-	0.126	-	0.001
2027	5016.99	-	-	-	0.126	-	0.001
2028	5016.98	-	-	-	0.126	-	0.001
2029	5016.97	-	-	-	0.126	-	0.001
2030	5016.96	-	-	-	0.126	-	0.001
2031	5016.95	-	-	-	0.126	-	0.001
2032	5016.94	-	-	-	0.126	-	0.001
2033	5016.93	-	-	-	0.126	-	0.001
2034	5016.92	-	-	-	0.126	-	0.001
2035	5016.91	-	-	-	0.126	-	0.001
2036	5016.90	-	-	-	0.126	-	0.001
2037	5016.89	-	-	-	0.126	-	0.001
2038	5016.88	-	-	-	0.126	-	0.001
2039	5016.87	-	-	-	0.126	-	0.001
2040	5016.86	-	-	-	0.127	-	0.001
2041	5016.85	-	-	-	0.127	-	0.001
2042	5016.84	-	-	-	0.126	-	0.001
2043	5016.83	-	-	-	0.126	-	0.001
2044	5016.82	-	-	-	0.127	-	0.001
2045	5016.81	-	-	-	0.127	-	0.001
2046	5016.80	-	-	-	0.127	-	0.001
2047	5016.79	-	-	-	0.126	-	0.001
2048	5016.78	-	-	-	0.125	-	0.001
2049	5016.77	-	-	-	0.125	-	0.001
2050	5016.76	-	-	-	0.125	-	0.001
2051	5016.75	-	-	-	0.125	-	0.001
2052	5016.74	-	-	-	0.125	-	0.001
2053	5016.73	-	-	-	0.125	-	0.001
2054	5016.72	-	-	-	0.125	-	0.001
2055	5016.71	-	-	-	0.125	-	0.001
2056	5016.70	-	-	-	0.125	-	0.001
2057	5016.69	-	-	-	0.125	-	0.001
2058	5016.68	-	-	-	0.125	-	0.001
2059	5016.67	-	-	-	0.126	-	0.001
2060	5016.66	-	-	-	0.125	-	0.001
2061	5016.65	-	-	-	0.126	-	0.001
2062	5016.64	-	-	-	0.125	-	0.001
2063	5016.64	-	-	-	0.126	-	0.001
2064	5016.63	-	-	-	0.126	-	0.001
2065	5016.62	-	-	-	0.126	-	0.001
2066	5016.61	-	-	-	0.126	-	0.001
2067	5016.60	-	-	-	0.126	-	0.001
2068	5016.59	-	-	-	0.126	-	0.001
2069	5016.58	-	-	-	0.126	-	0.001
2070	5016.57	-	-	-	0.126	-	0.001

Continued on next page

Table 13 – continued from previous page - IEEE8500 - n2250

		Time (sec)					
m	best ENS	ILP-GALIAS	ILP-IFLOWS	DP-TS	DP-N2M2	ILP-CUTS	DP-PC
2071	5016.57	-	-	-	0.126	-	0.001
2072	5016.56	-	-	-	0.126	-	0.001
2073	5016.55	-	-	-	0.126	-	0.001
2074	5016.54	-	-	-	0.126	-	0.001
2075	5016.53	-	-	-	0.126	-	0.001
2076	5016.52	-	-	-	0.126	-	0.001
2077	5016.52	-	-	-	0.126	-	0.001
2078	5016.51	-	-	-	0.126	-	0.001
2079	5016.50	-	-	-	0.126	-	0.001
2080	5016.49	-	-	-	0.126	-	0.001
2081	5016.48	-	-	-	0.127	-	0.001
2082	5016.48	-	-	-	0.127	-	0.001
2083	5016.47	-	-	-	0.126	-	0.001
2084	5016.46	-	-	-	0.126	-	0.001
2085	5016.45	-	-	-	0.126	-	0.001
2086	5016.45	-	-	-	0.127	-	0.001
2087	5016.44	-	-	-	0.127	-	0.001
2088	5016.43	-	-	-	0.127	-	0.001
2089	5016.42	-	-	-	0.127	-	0.001
2090	5016.42	-	-	-	0.127	-	0.001
2091	5016.41	-	-	-	0.127	-	0.001
2092	5016.40	-	-	-	0.127	-	0.001
2093	5016.39	-	-	-	0.127	-	0.001
2094	5016.38	-	-	-	0.127	-	0.001
2095	5016.38	-	-	-	0.127	-	0.001
2096	5016.37	-	-	-	0.127	-	0.001
2097	5016.36	-	-	-	0.124	-	0.001
2098	5016.35	-	-	-	0.101	-	0.001
2099	5016.35	-	-	-	0.101	-	0.001
2100	5016.34	-	-	-	0.094	-	0.001
2101	5016.33	-	-	-	0.094	-	0.001
2102	5016.32	-	-	-	0.094	-	0.001
2103	5016.31	-	-	-	0.093	-	0.001
2104	5016.31	-	-	-	0.094	-	0.001
2105	5016.30	-	-	-	0.093	-	0.001
2106	5016.29	-	-	-	0.085	-	0.000
2107	5016.28	-	-	-	0.084	-	0.000
2108	5016.28	-	-	-	0.077	-	0.000
2109	5016.27	-	-	-	0.076	-	0.000
2110	5016.26	-	-	-	0.068	-	0.000
2111	5016.25	-	-	-	0.067	-	0.000
2112	5016.25	-	-	-	0.060	-	0.000
2113	5016.24	-	-	-	0.059	-	0.000
2114	5016.23	-	-	-	0.053	-	0.000
2115	5016.22	-	-	-	0.052	-	0.000
2116	5016.22	-	-	-	0.045	-	0.000
2117	5016.21	-	-	-	0.045	-	0.000
2118	5016.20	-	-	-	0.045	-	0.000
2119	5016.19	-	-	-	0.045	-	0.000
2120	5016.19	-	-	-	0.045	-	0.000
2121	5016.18	-	-	-	0.045	-	0.000
2122	5016.17	-	-	-	0.045	-	0.000

Continued on next page

Table 13 – continued from previous page - IEEE8500 - n2250

		Time (sec)					
m	best ENS	ILP-GALIAS	ILP-IFLOWS	DP-TS	DP-N2M2	ILP-CUTS	DP-PC
2123	5016.17	-	-	-	0.045	-	0.000
2124	5016.16	-	-	-	0.045	-	0.000
2125	5016.15	-	-	-	0.045	-	0.000
2126	5016.15	-	-	-	0.045	-	0.000
2127	5016.14	-	-	-	0.044	-	0.000
2128	5016.13	-	-	-	0.038	-	0.000
2129	5016.12	-	-	-	0.037	-	0.000
2130	5016.12	-	-	-	0.033	-	0.000
2131	5016.11	-	-	-	0.032	-	0.000
2132	5016.10	-	-	-	0.028	-	0.000
2133	5016.10	-	-	-	0.028	-	0.000
2134	5016.09	-	-	-	0.027	-	0.000
2135	5016.08	-	-	-	0.028	-	0.000
2136	5016.08	-	-	-	0.028	-	0.000
2137	5016.07	-	-	-	0.027	-	0.000
2138	5016.06	-	-	-	0.028	-	0.000
2139	5016.06	-	-	-	0.027	-	0.000
2140	5016.05	-	-	-	0.028	-	0.000
2141	5016.04	-	-	-	0.028	-	0.000
2142	5016.04	-	-	-	0.028	-	0.000
2143	5016.03	-	-	-	0.027	-	0.000
2144	5016.02	-	-	-	0.022	-	0.000
2145	5016.02	-	-	-	0.022	-	0.000
2146	5016.01	-	-	-	0.022	-	0.000
2147	5016.00	-	-	-	0.022	-	0.000
2148	5016.00	-	-	-	0.022	-	0.000
2149	5015.99	-	-	-	0.022	-	0.000
2150	5015.98	-	-	-	0.022	-	0.000
2151	5015.98	-	-	-	0.022	-	0.000
2152	5015.97	-	-	-	0.022	-	0.000
2153	5015.97	-	-	-	0.022	-	0.000
2154	5015.96	-	-	-	0.022	-	0.000
2155	5015.95	-	-	-	0.022	-	0.000
2156	5015.95	-	-	-	0.022	-	0.000
2157	5015.94	-	-	-	0.022	-	0.000
2158	5015.94	-	-	-	0.022	-	0.000
2159	5015.93	-	-	-	0.022	-	0.000
2160	5015.93	-	-	-	0.022	-	0.000
2161	5015.92	-	-	-	0.022	-	0.000
2162	5015.92	-	-	-	0.022	-	0.000
2163	5015.91	-	-	-	0.022	-	0.000
2164	5015.91	-	-	-	0.022	-	0.000
2165	5015.90	-	-	-	0.022	-	0.000
2166	5015.90	-	-	-	0.022	-	0.000
2167	5015.90	-	-	-	0.023	-	0.000
2168	5015.89	-	-	-	0.022	-	0.000
2169	5015.89	-	-	-	0.022	-	0.000
2170	5015.88	-	-	-	0.023	-	0.000
2171	5015.88	-	-	-	0.022	-	0.000
2172	5015.87	-	-	-	0.023	-	0.000
2173	5015.87	-	-	-	0.022	-	0.000
2174	5015.86	-	-	-	0.018	-	0.000

Continued on next page

Table 13 – continued from previous page - IEEE8500 - n2250

		Time (sec)					
m	best ENS	ILP-GALIAS	ILP-IFLOWS	DP-TS	DP-N2M2	ILP-CUTS	DP-PC
2175	5015.86	-	-	-	0.017	-	0.000
2176	5015.85	-	-	-	0.014	-	0.000
2177	5015.85	-	-	-	0.013	-	0.000
2178	5015.84	-	-	-	0.011	-	0.000
2179	5015.84	-	-	-	0.010	-	0.000
2180	5015.83	-	-	-	0.008	-	0.000
2181	5015.83	-	-	-	0.008	-	0.000
2182	5015.83	-	-	-	0.008	-	0.000
2183	5015.82	-	-	-	0.008	-	0.000
2184	5015.82	-	-	-	0.008	-	0.000
2185	5015.81	-	-	-	0.008	-	0.000
2186	5015.81	-	-	-	0.008	-	0.000
2187	5015.80	-	-	-	0.007	-	0.000
2188	5015.80	-	-	-	0.005	-	0.000
2189	5015.79	-	-	-	0.005	-	0.000
2190	5015.79	-	-	-	0.005	-	0.000
2191	5015.78	-	-	-	0.005	-	0.000
2192	5015.78	-	-	-	0.005	-	0.000
2193	5015.78	-	-	-	0.005	-	0.000
2194	5015.77	-	-	-	0.005	-	0.000
2195	5015.77	-	-	-	0.005	-	0.000
2196	5015.76	-	-	-	0.005	-	0.000
2197	5015.76	-	-	-	0.005	-	0.000
2198	5015.75	-	-	-	0.005	-	0.000
2199	5015.75	-	-	-	0.005	-	0.000
2200	5015.74	-	-	-	0.005	-	0.000
2201	5015.74	-	-	-	0.005	-	0.000
2202	5015.74	-	-	-	0.005	-	0.000
2203	5015.73	-	-	-	0.005	-	0.000
2204	5015.73	-	-	-	0.005	-	0.000
2205	5015.72	-	-	-	0.005	-	0.000
2206	5015.72	-	-	-	0.005	-	0.000
2207	5015.72	-	-	-	0.005	-	0.000
2208	5015.71	-	-	-	0.005	-	0.000
2209	5015.71	-	-	-	0.005	-	0.000
2210	5015.70	-	-	-	0.005	-	0.000
2211	5015.70	-	-	-	0.005	-	0.000
2212	5015.70	-	-	-	0.005	-	0.000
2213	5015.69	-	-	-	0.005	-	0.000
2214	5015.69	-	-	-	0.005	-	0.000
2215	5015.68	-	-	-	0.005	-	0.000
2216	5015.68	-	-	-	0.005	-	0.000
2217	5015.68	-	-	-	0.005	-	0.000
2218	5015.68	-	-	-	0.005	-	0.000
2219	5015.67	-	-	-	0.005	-	0.000
2220	5015.67	-	-	-	0.005	-	0.000
2221	5015.67	-	-	-	0.005	-	0.000
2222	5015.66	-	-	-	0.005	-	0.000
2223	5015.66	-	-	-	0.005	-	0.000
2224	5015.66	-	-	-	0.005	-	0.000
2225	5015.65	-	-	-	0.005	-	0.000
2226	5015.65	-	-	-	0.005	-	0.000

Continued on next page

Table 13 – continued from previous page - IEEE8500 - n2250

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
2227	5015.65	-	-	-	0.005	-	0.000
2228	5015.65	-	-	-	0.005	-	0.000
2229	5015.65	-	-	-	0.005	-	0.000
2230	5015.64	-	-	-	0.005	-	0.000
2231	5015.64	-	-	-	0.005	-	0.000
2232	5015.64	-	-	-	0.005	-	0.000
2233	5015.64	-	-	-	0.005	-	0.000
2234	5015.64	-	-	-	0.005	-	0.000
2235	5015.64	-	-	-	0.005	-	0.000
2236	5015.64	-	-	-	0.005	-	0.000
2237	5015.64	-	-	-	0.005	-	0.000
2238	5015.63	-	-	-	0.005	-	0.000
2239	5015.63	-	-	-	0.005	-	0.000
2240	5015.63	-	-	-	0.005	-	0.000
2241	5015.63	-	-	-	0.005	-	0.000
2242	5015.63	-	-	-	0.005	-	0.000
2243	5015.63	-	-	-	0.005	-	0.000
2244	5015.63	-	-	-	0.005	-	0.000
2245	5015.63	-	-	-	0.004	-	0.000
2246	5015.63	-	-	-	0.003	-	0.000
2247	5015.63	-	-	-	0.002	-	0.000
2248	5015.63	-	-	-	0.001	-	0.000
2249	5015.63	-	-	-	0.000	-	0.000
Total		**7204.84**	**8030.86**	**7216.01**	**847.67**	**7221.82**	**76.30**

Table 14: ENS optimization - IEEE8500 - n3637.

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
0	98575.26	66.624	0.008	0.050	0.000	0.008	0.000
1	73457.10	617.247	0.255	0.110	0.000	0.263	0.001
2	51488.30	-	0.154	0.170	0.290	0.130	0.300
3	42512.25	-	1.170	0.300	0.390	0.813	0.434
4	36868.90	-	265.239	0.490	0.300	0.753	0.335
5	33277.31	-	1.463.800	0.680	0.400	2.406	0.448
6	30418.69	-	2965.205	0.920	0.310	9.503	0.344
7	27921.05	-	-	1.140	0.530	0.795	0.512
8	26029.92	-	-	1.420	0.370	1.240	0.348
9	24436.45	-	-	1.770	0.390	12.769	0.342
10	22985.62	-	-	2.150	0.620	11.104	0.582
11	21774.45	-	-	2.540	0.390	14.978	0.342
12	20593.68	-	-	2.950	0.410	13.316	0.349
13	19888.90	-	-	3.380	0.450	16.251	0.370
14	19205.22	-	-	3.670	0.460	21.089	0.339
15	18541.18	-	-	4.380	0.480	27.699	0.362
16	17941.78	-	-	4.750	0.510	17.615	0.390
17	17366.60	-	-	5.090	0.930	14.363	0.782
18	16835.76	-	-	5.580	0.540	15.466	0.363
19	16353.16	-	-	6.130	0.560	27.361	0.378

Continued on next page

Table 14 – continued from previous page - IEEE8500 - n3637

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
20	15941.69	-	-	6.520	0.580	33.623	0.398
21	15590.82	-	-	6.910	0.600	20.859	0.358
22	15251.69	-	-	7.390	0.620	17.643	0.379
23	14928.04	-	-	8.020	0.640	17.538	0.401
24	14648.64	-	-	8.180	1.100	15.525	0.882
25	14370.89	-	-	8.610	0.610	18.806	0.394
26	14106.08	-	-	8.870	0.630	17.879	0.388
27	13861.71	-	-	9.490	0.650	20.999	0.356
28	13646.95	-	-	9.740	0.660	28.647	0.374
29	13440.21	-	-	9.840	0.680	23.567	0.392
30	13240.02	-	-	9.980	0.690	21.735	0.411
31	13041.31	-	-	10.300	0.710	21.821	0.408
32	12847.21	-	-	10.830	0.730	18.680	0.367
33	12654.12	-	-	11.480	0.740	21.881	0.385
34	12470.74	-	-	11.780	0.760	28.885	0.386
35	12310.52	-	-	12.590	0.770	37.649	0.404
36	12154.57	-	-	13.440	0.790	25.912	0.420
37	12004.94	-	-	13.510	0.800	27.592	0.420
38	11858.67	-	-	14.040	0.820	33.966	0.420
39	11715.22	-	-	14.400	0.830	31.511	0.417
40	11576.29	-	-	14.400	0.850	17.714	0.421
41	11437.90	-	-	14.850	0.850	28.845	0.381
42	11302.62	-	-	15.350	0.860	17.748	0.399
43	11169.14	-	-	15.840	1.760	19.159	1.280
44	11035.85	-	-	16.060	0.840	20.637	0.395
45	10905.70	-	-	16.490	0.850	41.057	0.415
46	10784.99	-	-	16.950	0.870	17.592	0.411
47	10672.28	-	-	17.410	0.870	26.458	0.405
48	10559.89	-	-	17.700	0.890	31.100	0.374
49	10447.18	-	-	18.180	0.890	33.407	0.369
50	10335.38	-	-	18.570	0.900	23.000	0.384
51	10223.88	-	-	18.960	0.910	36.158	0.381
52	10119.65	-	-	19.550	0.920	23.292	0.377
53	10018.45	-	-	20.020	0.920	44.417	0.393
54	9921.11	-	-	20.490	0.930	22.994	0.405
55	9824.96	-	-	21.070	0.940	25.594	0.405
56	9728.91	-	-	21.390	0.950	25.226	0.405
57	9637.52	-	-	21.710	0.960	28.406	0.403
58	9548.44	-	-	22.360	0.960	39.209	0.404
59	9463.20	-	-	22.950	0.960	43.105	0.396
60	9380.78	-	-	23.540	0.980	33.763	0.399
61	9298.49	-	-	24.080	0.980	30.046	0.391
62	9225.09	-	-	24.470	0.990	33.143	0.370
63	9142.79	-	-	24.890	0.990	37.775	0.381
64	9070.27	-	-	25.550	1.000	34.464	0.380
65	9001.69	-	-	26.040	1.020	46.249	0.377
66	8934.71	-	-	26.530	1.960	37.043	1.377
67	8868.52	-	-	27.220	0.950	78.881	0.367
68	8805.61	-	-	27.700	0.950	70.692	0.376
69	8746.15	-	-	28.050	0.950	75.441	0.372
70	8690.20	-	-	28.680	0.950	71.112	0.366
71	8635.62	-	-	30.370	0.950	81.911	0.363

Continued on next page

Table 14 – continued from previous page - IEEE8500 - n3637

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
72	8581.79	-	-	30.960	0.960	65.994	0.336
73	8528.27	-	-	31.850	0.950	62.530	0.330
74	8476.02	-	-	32.240	0.960	79.141	0.329
75	8424.01	-	-	32.820	0.970	95.353	0.340
76	8374.03	-	-	33.320	0.970	81.497	0.334
77	8325.57	-	-	33.770	0.980	87.920	0.335
78	8278.52	-	-	32.650	0.980	85.924	0.331
79	8234.04	-	-	33.150	0.990	69.564	0.328
80	8191.02	-	-	33.580	0.990	56.989	0.338
81	8148.43	-	-	34.070	0.990	38.623	0.349
82	8105.97	-	-	34.720	1.000	50.198	0.347
83	8064.48	-	-	35.190	1.010	88.802	0.347
84	8023.34	-	-	34.830	1.020	71.800	0.347
85	7982.48	-	-	35.520	1.030	68.273	0.345
86	7941.99	-	-	35.830	1.030	84.970	0.346
87	7901.85	-	-	36.290	1.040	60.832	0.345
88	7861.74	-	-	36.570	1.050	50.727	0.345
89	7822.67	-	-	37.070	1.070	60.638	0.347
90	7784.21	-	-	37.650	1.080	41.470	0.348
91	7746.42	-	-	38.300	1.080	56.723	0.345
92	7710.10	-	-	38.680	1.100	49.643	0.344
93	7674.47	-	-	39.140	1.110	50.727	0.328
94	7639.58	-	-	39.620	1.110	64.415	0.325
95	7605.03	-	-	40.060	1.130	60.187	0.338
96	7570.54	-	-	40.590	1.130	51.321	0.337
97	7538.13	-	-	40.920	1.150	55.511	0.337
98	7507.10	-	-	41.150	1.160	69.525	0.335
99	7478.41	-	-	41.640	1.160	55.731	0.345
100	7450.47	-	-	41.780	1.180	70.135	0.347
101	7422.87	-	-	41.830	1.190	48.320	0.348
102	7395.70	-	-	42.240	1.180	53.101	0.357
103	7368.61	-	-	42.470	1.200	50.474	0.360
104	7341.69	-	-	43.440	1.210	44.784	0.358
105	7315.12	-	-	44.120	1.230	56.310	0.359
106	7288.75	-	-	44.040	1.240	43.370	0.358
107	7263.41	-	-	44.160	1.240	70.018	0.358
108	7238.86	-	-	44.170	1.260	44.240	0.332
109	7215.88	-	-	44.590	1.270	45.935	0.334
110	7193.06	-	-	44.770	1.280	76.415	0.333
111	7170.39	-	-	44.970	1.290	75.071	0.334
112	7148.10	-	-	45.340	1.310	64.727	0.336
113	7126.56	-	-	45.770	1.320	55.801	0.348
114	7105.03	-	-	45.630	1.330	59.445	0.348
115	7083.54	-	-	45.930	1.340	59.489	0.349
116	7062.07	-	-	46.240	1.350	55.664	0.349
117	7040.66	-	-	46.720	1.360	59.397	0.351
118	7019.55	-	-	47.390	1.370	78.879	0.350
119	6998.79	-	-	47.250	1.380	57.614	0.350
120	6978.11	-	-	47.240	1.390	73.330	0.361
121	6957.59	-	-	47.620	1.400	58.137	0.359
122	6937.50	-	-	47.720	1.410	70.857	0.370
123	6917.78	-	-	48.420	1.420	72.212	0.371

Continued on next page

Table 14 – continued from previous page - IEEE8500 - n3637

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
124	6898.39	-	-	48.860	1.410	93.494	0.367
125	6880.91	-	-	49.390	1.420	72.854	0.366
126	6863.54	-	-	49.630	1.430	50.680	0.367
127	6846.21	-	-	49.840	1.440	50.308	0.367
128	6828.89	-	-	49.950	1.450	48.549	0.367
129	6811.70	-	-	50.390	1.470	66.886	0.371
130	6795.51	-	-	50.900	1.480	47.912	0.370
131	6779.34	-	-	51.460	1.490	45.783	0.370
132	6763.60	-	-	52.120	1.500	49.856	0.371
133	6747.95	-	-	52.270	1.510	84.743	0.371
134	6732.82	-	-	53.130	3.450	49.031	2.327
135	6718.05	-	-	53.670	1.480	45.961	0.346
136	6703.92	-	-	54.580	1.480	60.142	0.343
137	6689.84	-	-	55.010	1.490	47.883	0.347
138	6675.82	-	-	55.660	1.500	67.050	0.344
139	6661.98	-	-	56.350	1.500	70.009	0.343
140	6648.41	-	-	56.980	1.510	64.882	0.330
141	6634.86	-	-	57.100	1.520	47.645	0.331
142	6621.57	-	-	57.340	1.530	61.240	0.330
143	6608.33	-	-	57.370	1.540	45.435	0.340
144	6595.12	-	-	57.470	1.550	67.562	0.341
145	6582.07	-	-	57.280	1.560	80.327	0.342
146	6569.08	-	-	58.030	1.570	77.489	0.343
147	6556.18	-	-	58.020	1.580	72.814	0.342
148	6543.31	-	-	58.380	1.580	72.642	0.340
149	6530.54	-	-	58.900	1.590	50.764	0.351
150	6518.15	-	-	58.990	1.600	56.247	0.349
151	6506.31	-	-	59.030	1.610	75.603	0.351
152	6494.57	-	-	59.230	1.620	58.757	0.350
153	6482.89	-	-	59.110	1.620	65.970	0.386
154	6471.43	-	-	59.950	1.630	55.827	0.433
155	6459.98	-	-	59.860	1.640	60.443	0.439
156	6448.59	-	-	60.200	1.650	58.971	0.377
157	6437.66	-	-	60.890	1.660	49.595	0.372
158	6426.77	-	-	61.050	1.680	-	0.387
159	6415.97	-	-	61.350	1.690	-	0.433
160	6405.22	-	-	61.520	1.700	-	0.436
161	6394.66	-	-	61.850	1.710	-	0.375
162	6384.29	-	-	62.350	1.710	-	0.343
163	6374.00	-	-	62.640	1.710	-	0.341
164	6363.76	-	-	63.030	1.720	-	0.339
165	6353.70	-	-	63.930	1.730	-	0.349
166	6343.91	-	-	64.580	1.740	-	0.346
167	6334.14	-	-	64.470	1.740	-	0.346
168	6324.58	-	-	64.830	1.740	-	0.345
169	6315.07	-	-	65.230	1.730	-	0.336
170	6305.64	-	-	65.730	1.730	-	0.341
171	6296.22	-	-	65.630	1.720	-	0.345
172	6286.81	-	-	66.170	1.730	-	0.350
173	6277.55	-	-	66.450	1.720	-	0.356
174	6268.31	-	-	67.050	1.720	-	0.334
175	6259.43	-	-	67.290	1.730	-	0.333

Continued on next page

Table 14 – continued from previous page - IEEE8500 - n3637

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
176	6250.69	-	-	67.830	1.740	-	0.332
177	6241.98	-	-	68.460	1.740	-	0.330
178	6233.75	-	-	68.950	1.750	-	0.330
179	6225.55	-	-	69.410	1.760	-	0.330
180	6217.34	-	-	69.750	1.760	-	0.340
181	6209.14	-	-	70.580	1.760	-	0.339
182	6200.95	-	-	70.420	1.770	-	0.342
183	6192.87	-	-	70.900	1.780	-	0.349
184	6184.87	-	-	70.480	1.790	-	0.348
185	6176.86	-	-	70.780	1.800	-	0.351
186	6168.92	-	-	71.770	1.810	-	0.350
187	6160.99	-	-	71.660	1.810	-	0.348
188	6153.33	-	-	71.950	1.820	-	0.348
189	6145.68	-	-	72.630	1.820	-	0.346
190	6138.03	-	-	72.300	1.830	-	0.348
191	6130.38	-	-	-	1.840	-	0.347
192	6122.73	-	-	-	1.850	-	0.348
193	6115.09	-	-	-	1.850	-	0.346
194	6107.60	-	-	-	1.860	-	0.346
195	6100.16	-	-	-	1.850	-	0.343
196	6092.87	-	-	-	1.850	-	0.341
197	6085.68	-	-	-	1.860	-	0.342
198	6078.55	-	-	-	1.850	-	0.338
199	6071.42	-	-	-	1.850	-	0.339
200	6064.32	-	-	-	1.860	-	0.338
201	6057.50	-	-	-	1.850	-	0.333
202	6050.70	-	-	-	1.860	-	0.335
203	6043.93	-	-	-	1.850	-	0.332
204	6037.23	-	-	-	1.820	-	0.325
205	6030.60	-	-	-	1.820	-	0.327
206	6023.99	-	-	-	1.830	-	0.327
207	6017.41	-	-	-	1.830	-	0.322
208	6010.89	-	-	-	1.940	-	0.322
209	6004.42	-	-	-	1.840	-	0.321
210	5998.31	-	-	-	1.820	-	0.310
211	5992.26	-	-	-	1.820	-	0.309
212	5986.39	-	-	-	1.830	-	0.309
213	5980.61	-	-	-	1.820	-	0.305
214	5974.83	-	-	-	1.820	-	0.306
215	5969.11	-	-	-	3.920	-	2.514
216	5963.46	-	-	-	1.730	-	0.303
217	5957.82	-	-	-	1.740	-	0.301
218	5952.19	-	-	-	1.730	-	0.299
219	5946.56	-	-	-	1.730	-	0.296
220	5940.97	-	-	-	1.720	-	0.294
221	5935.41	-	-	-	1.720	-	0.296
222	5929.85	-	-	-	1.730	-	0.293
223	5924.32	-	-	-	1.740	-	0.292
224	5918.80	-	-	-	1.730	-	0.298
225	5913.33	-	-	-	1.730	-	0.295
226	5908.01	-	-	-	1.740	-	0.296
227	5902.72	-	-	-	1.730	-	0.293

Continued on next page

Table 14 – continued from previous page - IEEE8500 - n3637

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
228	5897.44	-	-	-	1.740	-	0.295
229	5892.16	-	-	-	1.750	-	0.294
230	5886.94	-	-	-	1.740	-	0.300
231	5881.72	-	-	-	1.750	-	0.300
232	5876.52	-	-	-	1.750	-	0.299
233	5871.31	-	-	-	1.740	-	0.296
234	5866.10	-	-	-	1.750	-	0.296
235	5860.95	-	-	-	1.760	-	0.295
236	5855.87	-	-	-	1.750	-	0.294
237	5850.78	-	-	-	1.740	-	0.291
238	5845.89	-	-	-	1.740	-	0.290
239	5841.00	-	-	-	1.750	-	0.289
240	5836.16	-	-	-	1.760	-	0.291
241	5831.33	-	-	-	1.750	-	0.288
242	5826.52	-	-	-	1.740	-	0.285
243	5821.74	-	-	-	1.740	-	0.273
244	5817.02	-	-	-	1.730	-	0.268
245	5812.34	-	-	-	1.740	-	0.268
246	5807.70	-	-	-	1.730	-	0.267
247	5803.09	-	-	-	1.730	-	0.266
248	5798.53	-	-	-	1.730	-	0.263
249	5793.92	-	-	-	1.730	-	0.263
250	5789.35	-	-	-	1.730	-	0.262
251	5784.80	-	-	-	1.730	-	0.261
252	5780.25	-	-	-	1.730	-	0.260
253	5775.71	-	-	-	1.730	-	0.259
254	5771.17	-	-	-	1.740	-	0.261
255	5766.63	-	-	-	1.750	-	0.266
256	5762.09	-	-	-	1.740	-	0.266
257	5757.56	-	-	-	1.740	-	0.263
258	5753.02	-	-	-	1.730	-	0.262
259	5748.49	-	-	-	1.740	-	0.262
260	5743.98	-	-	-	1.730	-	0.260
261	5739.44	-	-	-	1.730	-	0.266
262	5734.91	-	-	-	1.720	-	0.263
263	5730.41	-	-	-	1.720	-	0.263
264	5725.99	-	-	-	1.710	-	0.260
265	5721.65	-	-	-	1.710	-	0.265
266	5717.38	-	-	-	1.680	-	0.259
267	5713.11	-	-	-	1.680	-	0.258
268	5708.84	-	-	-	1.670	-	0.252
269	5704.57	-	-	-	1.670	-	0.256
270	5700.34	-	-	-	1.670	-	0.262
271	5696.16	-	-	-	1.680	-	0.262
272	5692.03	-	-	-	1.680	-	0.263
273	5687.91	-	-	-	1.680	-	0.261
274	5683.84	-	-	-	1.680	-	0.261
275	5679.90	-	-	-	1.690	-	0.270
276	5675.98	-	-	-	1.680	-	0.260
277	5672.07	-	-	-	1.670	-	0.259
278	5668.17	-	-	-	1.670	-	0.258
279	5664.35	-	-	-	1.680	-	0.264

Continued on next page

Table 14 – continued from previous page - IEEE8500 - n3637

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
280	5660.54	-	-	-	1.670	-	0.262
281	5656.74	-	-	-	1.660	-	0.261
282	5653.02	-	-	-	1.670	-	0.261
283	5649.51	-	-	-	1.680	-	0.265
284	5645.87	-	-	-	1.670	-	0.265
285	5642.36	-	-	-	1.670	-	0.263
286	5638.88	-	-	-	1.680	-	0.264
287	5635.41	-	-	-	1.680	-	0.262
288	5631.97	-	-	-	1.670	-	0.254
289	5628.61	-	-	-	1.670	-	0.255
290	5625.28	-	-	-	1.670	-	0.253
291	5621.96	-	-	-	1.670	-	0.254
292	5618.63	-	-	-	1.650	-	0.249
293	5615.32	-	-	-	1.660	-	0.250
294	5611.99	-	-	-	1.640	-	0.248
295	5608.75	-	-	-	1.650	-	0.249
296	5605.56	-	-	-	1.640	-	0.249
297	5602.37	-	-	-	1.650	-	0.248
298	5599.20	-	-	-	1.640	-	0.248
299	5596.06	-	-	-	1.650	-	0.246
300	5592.92	-	-	-	1.660	-	0.246
301	5589.81	-	-	-	1.650	-	0.244
302	5586.75	-	-	-	1.640	-	0.237
303	5583.72	-	-	-	1.640	-	0.239
304	5580.72	-	-	-	1.650	-	0.238
305	5577.77	-	-	-	1.640	-	0.237
306	5574.82	-	-	-	1.640	-	0.236
307	5571.90	-	-	-	1.650	-	0.237
308	5569.07	-	-	-	1.660	-	0.239
309	5566.27	-	-	-	1.670	-	0.236
310	5563.50	-	-	-	1.670	-	0.237
311	5560.74	-	-	-	1.660	-	0.236
312	5557.98	-	-	-	1.670	-	0.235
313	5555.25	-	-	-	1.680	-	0.236
314	5552.54	-	-	-	1.680	-	0.235
315	5549.84	-	-	-	1.690	-	0.228
316	5547.16	-	-	-	1.690	-	0.230
317	5544.59	-	-	-	1.700	-	0.229
318	5542.06	-	-	-	1.700	-	0.230
319	5539.61	-	-	-	1.710	-	0.229
320	5537.18	-	-	-	1.720	-	0.229
321	5534.75	-	-	-	1.720	-	0.229
322	5532.41	-	-	-	1.730	-	0.228
323	5530.07	-	-	-	1.730	-	0.234
324	5527.74	-	-	-	1.740	-	0.233
325	5525.42	-	-	-	1.750	-	0.232
326	5523.11	-	-	-	1.750	-	0.234
327	5520.81	-	-	-	1.760	-	0.234
328	5518.54	-	-	-	1.760	-	0.234
329	5516.27	-	-	-	1.770	-	0.235
330	5514.01	-	-	-	1.760	-	0.226
331	5511.76	-	-	-	1.760	-	0.227

Continued on next page

Table 14 – continued from previous page - IEEE8500 - n3637

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
332	5509.52	-	-	-	1.770	-	0.226
333	5507.31	-	-	-	1.770	-	0.227
334	5505.10	-	-	-	1.780	-	0.227
335	5502.92	-	-	-	1.770	-	0.224
336	5500.73	-	-	-	1.780	-	0.230
337	5498.55	-	-	-	1.780	-	0.230
338	5496.37	-	-	-	1.790	-	0.230
339	5494.19	-	-	-	1.790	-	0.230
340	5492.01	-	-	-	1.800	-	0.230
341	5489.85	-	-	-	1.800	-	0.231
342	5487.69	-	-	-	1.810	-	0.233
343	5485.56	-	-	-	1.820	-	0.230
344	5483.47	-	-	-	1.820	-	0.231
345	5481.42	-	-	-	1.810	-	0.234
346	5479.37	-	-	-	1.820	-	0.233
347	5477.34	-	-	-	1.800	-	0.233
348	5475.30	-	-	-	1.810	-	0.231
349	5473.28	-	-	-	1.810	-	0.232
350	5471.25	-	-	-	1.820	-	0.232
351	5469.22	-	-	-	1.820	-	0.231
352	5467.20	-	-	-	1.830	-	0.232
353	5465.17	-	-	-	1.840	-	0.232
354	5463.17	-	-	-	1.840	-	0.233
355	5461.18	-	-	-	1.850	-	0.234
356	5459.19	-	-	-	1.850	-	0.233
357	5457.21	-	-	-	1.830	-	0.228
358	5455.23	-	-	-	1.830	-	0.228
359	5453.27	-	-	-	1.820	-	0.226
360	5451.32	-	-	-	1.830	-	0.226
361	5449.39	-	-	-	1.830	-	0.227
362	5447.46	-	-	-	1.830	-	0.225
363	5445.54	-	-	-	1.820	-	0.225
364	5443.63	-	-	-	1.830	-	0.225
365	5441.71	-	-	-	1.840	-	0.215
366	5439.80	-	-	-	1.840	-	0.215
367	5437.89	-	-	-	1.850	-	0.215
368	5435.98	-	-	-	1.850	-	0.216
369	5434.10	-	-	-	1.860	-	0.215
370	5432.23	-	-	-	1.860	-	0.215
371	5430.36	-	-	-	1.870	-	0.215
372	5428.50	-	-	-	1.870	-	0.216
373	5426.64	-	-	-	1.880	-	0.215
374	5424.79	-	-	-	1.890	-	0.216
375	5422.94	-	-	-	1.890	-	0.216
376	5421.10	-	-	-	1.900	-	0.216
377	5419.26	-	-	-	1.900	-	0.216
378	5417.42	-	-	-	1.910	-	0.215
379	5415.58	-	-	-	1.910	-	0.216
380	5413.77	-	-	-	1.920	-	0.216
381	5411.97	-	-	-	1.920	-	0.216
382	5410.19	-	-	-	1.930	-	0.219
383	5408.43	-	-	-	1.940	-	0.221

Continued on next page

Table 14 – continued from previous page - IEEE8500 - n3637

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
384	5406.68	-	-	-	1.940	-	0.221
385	5404.94	-	-	-	1.950	-	0.220
386	5403.21	-	-	-	1.950	-	0.221
387	5401.52	-	-	-	1.960	-	0.221
388	5399.83	-	-	-	1.940	-	0.219
389	5398.15	-	-	-	1.940	-	0.219
390	5396.48	-	-	-	1.950	-	0.220
391	5394.83	-	-	-	1.950	-	0.219
392	5393.17	-	-	-	1.960	-	0.219
393	5391.53	-	-	-	1.950	-	0.218
394	5389.92	-	-	-	1.960	-	0.218
395	5388.32	-	-	-	1.950	-	0.221
396	5386.74	-	-	-	1.940	-	0.216
397	5385.16	-	-	-	1.930	-	0.215
398	5383.59	-	-	-	1.920	-	0.212
399	5382.03	-	-	-	1.920	-	0.211
400	5380.48	-	-	-	1.890	-	0.208
401	5378.94	-	-	-	1.890	-	0.207
402	5377.41	-	-	-	1.870	-	0.204
403	5375.87	-	-	-	1.860	-	0.202
404	5374.34	-	-	-	1.840	-	0.200
405	5372.81	-	-	-	1.850	-	0.206
406	5371.27	-	-	-	1.860	-	0.206
407	5369.74	-	-	-	1.820	-	0.201
408	5368.21	-	-	-	1.800	-	0.200
409	5366.69	-	-	-	1.800	-	0.200
410	5365.17	-	-	-	1.810	-	0.199
411	5363.65	-	-	-	1.810	-	0.199
412	5362.16	-	-	-	1.810	-	0.198
413	5360.68	-	-	-	1.810	-	0.202
414	5359.20	-	-	-	1.800	-	0.201
415	5357.72	-	-	-	1.810	-	0.202
416	5356.26	-	-	-	1.800	-	0.204
417	5354.81	-	-	-	1.800	-	0.202
418	5353.38	-	-	-	1.800	-	0.201
419	5351.95	-	-	-	1.800	-	0.199
420	5350.53	-	-	-	1.800	-	0.199
421	5349.11	-	-	-	1.810	-	0.200
422	5347.70	-	-	-	1.810	-	0.200
423	5346.30	-	-	-	1.820	-	0.201
424	5344.91	-	-	-	1.800	-	0.198
425	5343.52	-	-	-	1.810	-	0.198
426	5342.14	-	-	-	1.780	-	0.195
427	5340.79	-	-	-	1.790	-	0.195
428	5339.45	-	-	-	1.800	-	0.196
429	5338.12	-	-	-	1.800	-	0.195
430	5336.81	-	-	-	1.800	-	0.195
431	5335.51	-	-	-	1.810	-	0.196
432	5334.22	-	-	-	1.810	-	0.195
433	5332.94	-	-	-	1.820	-	0.196
434	5331.67	-	-	-	1.790	-	0.194
435	5330.39	-	-	-	1.800	-	0.194

Continued on next page

Table 14 – continued from previous page - IEEE8500 - n3637

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
436	5329.13	-	-	-	1.800	-	0.194
437	5327.88	-	-	-	1.810	-	0.194
438	5326.64	-	-	-	1.810	-	0.194
439	5325.40	-	-	-	1.790	-	0.191
440	5324.16	-	-	-	1.800	-	0.191
441	5322.93	-	-	-	1.800	-	0.191
442	5321.69	-	-	-	1.800	-	0.191
443	5320.46	-	-	-	1.810	-	0.192
444	5319.23	-	-	-	1.810	-	0.191
445	5318.01	-	-	-	1.820	-	0.195
446	5316.79	-	-	-	1.820	-	0.194
447	5315.57	-	-	-	1.820	-	0.192
448	5314.35	-	-	-	1.830	-	0.191
449	5313.15	-	-	-	1.830	-	0.192
450	5311.96	-	-	-	1.840	-	0.192
451	5310.78	-	-	-	1.840	-	0.191
452	5309.61	-	-	-	1.850	-	0.191
453	5308.46	-	-	-	1.850	-	0.192
454	5307.30	-	-	-	1.850	-	0.193
455	5306.15	-	-	-	1.860	-	0.193
456	5305.00	-	-	-	1.860	-	0.193
457	5303.85	-	-	-	1.840	-	0.191
458	5302.73	-	-	-	1.850	-	0.190
459	5301.63	-	-	-	1.850	-	0.190
460	5300.54	-	-	-	1.850	-	0.189
461	5299.45	-	-	-	1.860	-	0.189
462	5298.36	-	-	-	1.860	-	0.189
463	5297.28	-	-	-	1.850	-	0.192
464	5296.20	-	-	-	1.860	-	0.191
465	5295.12	-	-	-	1.860	-	0.191
466	5294.05	-	-	-	1.870	-	0.191
467	5292.99	-	-	-	1.850	-	0.189
468	5291.93	-	-	-	1.860	-	0.189
469	5290.88	-	-	-	1.860	-	0.189
470	5289.82	-	-	-	1.870	-	0.189
471	5288.76	-	-	-	1.870	-	0.190
472	5287.71	-	-	-	1.880	-	0.191
473	5286.66	-	-	-	1.880	-	0.184
474	5285.62	-	-	-	1.890	-	0.184
475	5284.58	-	-	-	1.890	-	0.184
476	5283.54	-	-	-	1.890	-	0.184
477	5282.51	-	-	-	1.900	-	0.185
478	5281.48	-	-	-	1.900	-	0.185
479	5280.47	-	-	-	1.910	-	0.185
480	5279.45	-	-	-	1.910	-	0.185
481	5278.44	-	-	-	1.920	-	0.184
482	5277.43	-	-	-	1.920	-	0.188
483	5276.43	-	-	-	1.920	-	0.187
484	5275.44	-	-	-	1.930	-	0.185
485	5274.45	-	-	-	1.930	-	0.189
486	5273.46	-	-	-	1.940	-	0.188
487	5272.48	-	-	-	1.940	-	0.189

Continued on next page

Table 14 – continued from previous page - IEEE8500 - n3637

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
488	5271.50	-	-	-	1.940	-	0.189
489	5270.52	-	-	-	1.950	-	0.189
490	5269.54	-	-	-	1.950	-	0.189
491	5268.57	-	-	-	1.930	-	0.187
492	5267.59	-	-	-	1.940	-	0.188
493	5266.62	-	-	-	1.920	-	0.187
494	5265.66	-	-	-	1.920	-	0.185
495	5264.71	-	-	-	1.920	-	0.184
496	5263.77	-	-	-	1.900	-	0.182
497	5262.82	-	-	-	1.910	-	0.182
498	5261.89	-	-	-	1.910	-	0.182
499	5260.97	-	-	-	1.920	-	0.183
500	5260.05	-	-	-	1.920	-	0.183
501	5259.13	-	-	-	1.920	-	0.183
502	5258.23	-	-	-	1.930	-	0.183
503	5257.32	-	-	-	1.930	-	0.184
504	5256.41	-	-	-	1.940	-	0.190
505	5255.51	-	-	-	1.940	-	0.187
506	5254.61	-	-	-	1.940	-	0.187
507	5253.71	-	-	-	1.950	-	0.187
508	5252.81	-	-	-	1.950	-	0.187
509	5251.91	-	-	-	1.960	-	0.189
510	5251.01	-	-	-	1.960	-	0.188
511	5250.12	-	-	-	1.970	-	0.188
512	5249.24	-	-	-	1.970	-	0.188
513	5248.35	-	-	-	1.970	-	0.189
514	5247.47	-	-	-	1.980	-	0.189
515	5246.60	-	-	-	1.980	-	0.188
516	5245.72	-	-	-	1.990	-	0.189
517	5244.85	-	-	-	1.990	-	0.188
518	5243.98	-	-	-	1.990	-	0.193
519	5243.11	-	-	-	2.000	-	0.193
520	5242.24	-	-	-	2.000	-	0.192
521	5241.38	-	-	-	2.010	-	0.194
522	5240.52	-	-	-	2.010	-	0.193
523	5239.66	-	-	-	2.020	-	0.193
524	5238.80	-	-	-	2.020	-	0.193
525	5237.96	-	-	-	2.030	-	0.193
526	5237.13	-	-	-	6.390	-	4.562
527	5236.30	-	-	-	1.990	-	0.183
528	5235.48	-	-	-	1.990	-	0.183
529	5234.66	-	-	-	2.000	-	0.181
530	5233.86	-	-	-	2.000	-	0.181
531	5233.06	-	-	-	2.000	-	0.182
532	5232.27	-	-	-	2.010	-	0.182
533	5231.49	-	-	-	2.010	-	0.182
534	5230.71	-	-	-	2.020	-	0.181
535	5229.93	-	-	-	2.020	-	0.181
536	5229.15	-	-	-	2.020	-	0.181
537	5228.39	-	-	-	2.030	-	0.182
538	5227.62	-	-	-	2.030	-	0.183
539	5226.85	-	-	-	2.040	-	0.183

Continued on next page

Table 14 – continued from previous page - IEEE8500 - n3637

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
540	5226.09	-	-	-	2.040	-	0.182
541	5225.33	-	-	-	2.040	-	0.182
542	5224.57	-	-	-	2.050	-	0.182
543	5223.80	-	-	-	2.050	-	0.182
544	5223.05	-	-	-	2.050	-	0.182
545	5222.29	-	-	-	2.060	-	0.181
546	5221.54	-	-	-	2.080	-	0.181
547	5220.79	-	-	-	2.060	-	0.181
548	5220.04	-	-	-	2.040	-	0.172
549	5219.30	-	-	-	2.040	-	0.173
550	5218.56	-	-	-	2.050	-	0.173
551	5217.83	-	-	-	2.050	-	0.172
552	5217.09	-	-	-	2.060	-	0.172
553	5216.37	-	-	-	2.030	-	0.170
554	5215.65	-	-	-	2.030	-	0.170
555	5214.94	-	-	-	2.040	-	0.170
556	5214.24	-	-	-	2.040	-	0.170
557	5213.54	-	-	-	2.040	-	0.171
558	5212.85	-	-	-	2.050	-	0.171
559	5212.15	-	-	-	2.050	-	0.170
560	5211.46	-	-	-	2.060	-	0.171
561	5210.77	-	-	-	2.060	-	0.171
562	5210.08	-	-	-	2.060	-	0.171
563	5209.40	-	-	-	2.070	-	0.171
564	5208.71	-	-	-	2.070	-	0.170
565	5208.03	-	-	-	2.080	-	0.171
566	5207.36	-	-	-	2.080	-	0.170
567	5206.69	-	-	-	2.080	-	0.171
568	5206.03	-	-	-	2.090	-	0.171
569	5205.39	-	-	-	2.090	-	0.170
570	5204.74	-	-	-	2.100	-	0.171
571	5204.10	-	-	-	2.100	-	0.171
572	5203.46	-	-	-	2.100	-	0.171
573	5202.82	-	-	-	2.110	-	0.171
574	5202.18	-	-	-	2.110	-	0.170
575	5201.54	-	-	-	2.090	-	0.171
576	5200.91	-	-	-	2.090	-	0.171
577	5200.27	-	-	-	2.070	-	0.169
578	5199.64	-	-	-	2.070	-	0.169
579	5199.02	-	-	-	2.040	-	0.167
580	5198.39	-	-	-	2.050	-	0.167
581	5197.76	-	-	-	2.050	-	0.167
582	5197.14	-	-	-	2.050	-	0.166
583	5196.52	-	-	-	2.060	-	0.167
584	5195.89	-	-	-	2.060	-	0.167
585	5195.27	-	-	-	2.060	-	0.167
586	5194.65	-	-	-	2.070	-	0.167
587	5194.04	-	-	-	2.070	-	0.167
588	5193.42	-	-	-	2.080	-	0.167
589	5192.81	-	-	-	2.080	-	0.168
590	5192.21	-	-	-	2.050	-	0.166
591	5191.60	-	-	-	2.050	-	0.165

Continued on next page

Table 14 – continued from previous page - IEEE8500 - n3637

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
592	5191.00	-	-	-	2.060	-	0.166
593	5190.40	-	-	-	2.060	-	0.166
594	5189.80	-	-	-	2.060	-	0.165
595	5189.21	-	-	-	2.070	-	0.166
596	5188.62	-	-	-	2.070	-	0.165
597	5188.03	-	-	-	2.040	-	0.163
598	5187.45	-	-	-	2.050	-	0.163
599	5186.87	-	-	-	2.050	-	0.163
600	5186.28	-	-	-	2.040	-	0.161
601	5185.71	-	-	-	2.040	-	0.162
602	5185.13	-	-	-	2.050	-	0.162
603	5184.55	-	-	-	2.050	-	0.162
604	5183.98	-	-	-	2.050	-	0.162
605	5183.40	-	-	-	2.030	-	0.160
606	5182.83	-	-	-	2.030	-	0.160
607	5182.25	-	-	-	2.040	-	0.159
608	5181.68	-	-	-	2.040	-	0.164
609	5181.11	-	-	-	2.010	-	0.162
610	5180.54	-	-	-	2.020	-	0.164
611	5179.98	-	-	-	2.020	-	0.163
612	5179.42	-	-	-	2.020	-	0.162
613	5178.86	-	-	-	2.030	-	0.162
614	5178.31	-	-	-	2.000	-	0.159
615	5177.76	-	-	-	2.010	-	0.159
616	5177.21	-	-	-	2.010	-	0.159
617	5176.65	-	-	-	1.980	-	0.157
618	5176.10	-	-	-	1.990	-	0.157
619	5175.56	-	-	-	1.990	-	0.158
620	5175.01	-	-	-	1.990	-	0.162
621	5174.47	-	-	-	2.000	-	0.162
622	5173.93	-	-	-	2.000	-	0.163
623	5173.39	-	-	-	2.000	-	0.163
624	5172.85	-	-	-	2.010	-	0.161
625	5172.31	-	-	-	2.010	-	0.161
626	5171.77	-	-	-	1.980	-	0.158
627	5171.24	-	-	-	1.980	-	0.159
628	5170.71	-	-	-	1.990	-	0.158
629	5170.19	-	-	-	1.990	-	0.159
630	5169.67	-	-	-	1.990	-	0.159
631	5169.16	-	-	-	2.000	-	0.159
632	5168.64	-	-	-	2.000	-	0.158
633	5168.13	-	-	-	2.000	-	0.158
634	5167.61	-	-	-	2.010	-	0.159
635	5167.10	-	-	-	2.010	-	0.159
636	5166.60	-	-	-	2.010	-	0.158
637	5166.10	-	-	-	2.020	-	0.158
638	5165.61	-	-	-	2.020	-	0.158
639	5165.12	-	-	-	2.020	-	0.158
640	5164.64	-	-	-	2.020	-	0.158
641	5164.16	-	-	-	2.030	-	0.159
642	5163.68	-	-	-	2.030	-	0.159
643	5163.20	-	-	-	2.040	-	0.158

Continued on next page

Table 14 – continued from previous page - IEEE8500 - n3637

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
644	5162.73	-	-	-	2.040	-	0.158
645	5162.26	-	-	-	2.040	-	0.158
646	5161.79	-	-	-	2.050	-	0.158
647	5161.32	-	-	-	2.050	-	0.160
648	5160.85	-	-	-	2.050	-	0.159
649	5160.38	-	-	-	2.060	-	0.158
650	5159.91	-	-	-	2.060	-	0.158
651	5159.45	-	-	-	2.060	-	0.158
652	5158.99	-	-	-	2.070	-	0.158
653	5158.53	-	-	-	2.050	-	0.157
654	5158.07	-	-	-	2.050	-	0.158
655	5157.62	-	-	-	2.060	-	0.157
656	5157.16	-	-	-	2.060	-	0.157
657	5156.71	-	-	-	2.060	-	0.157
658	5156.26	-	-	-	2.060	-	0.157
659	5155.82	-	-	-	2.070	-	0.157
660	5155.37	-	-	-	2.050	-	0.156
661	5154.93	-	-	-	2.060	-	0.155
662	5154.48	-	-	-	2.060	-	0.156
663	5154.04	-	-	-	2.050	-	0.155
664	5153.60	-	-	-	2.050	-	0.155
665	5153.16	-	-	-	2.040	-	0.153
666	5152.72	-	-	-	2.040	-	0.156
667	5152.28	-	-	-	2.050	-	0.154
668	5151.85	-	-	-	2.050	-	0.155
669	5151.41	-	-	-	2.050	-	0.154
670	5150.98	-	-	-	2.050	-	0.153
671	5150.55	-	-	-	2.060	-	0.153
672	5150.12	-	-	-	2.060	-	0.154
673	5149.69	-	-	-	2.040	-	0.152
674	5149.27	-	-	-	2.050	-	0.152
675	5148.84	-	-	-	2.050	-	0.152
676	5148.42	-	-	-	2.060	-	0.152
677	5148.00	-	-	-	2.060	-	0.152
678	5147.59	-	-	-	2.060	-	0.151
679	5147.18	-	-	-	2.020	-	0.149
680	5146.77	-	-	-	2.020	-	0.150
681	5146.35	-	-	-	2.030	-	0.150
682	5145.94	-	-	-	2.030	-	0.151
683	5145.53	-	-	-	2.030	-	0.151
684	5145.13	-	-	-	2.040	-	0.151
685	5144.72	-	-	-	2.040	-	0.151
686	5144.31	-	-	-	2.040	-	0.151
687	5143.90	-	-	-	2.020	-	0.149
688	5143.49	-	-	-	2.020	-	0.148
689	5143.09	-	-	-	2.020	-	0.148
690	5142.68	-	-	-	2.020	-	0.148
691	5142.27	-	-	-	2.000	-	0.146
692	5141.87	-	-	-	2.000	-	0.147
693	5141.47	-	-	-	2.000	-	0.148
694	5141.06	-	-	-	2.000	-	0.147
695	5140.66	-	-	-	2.010	-	0.146

Continued on next page

Table 14 – continued from previous page - IEEE8500 - n3637

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
696	5140.26	-	-	-	2.010	-	0.146
697	5139.86	-	-	-	2.010	-	0.146
698	5139.47	-	-	-	2.020	-	0.146
699	5139.07	-	-	-	2.020	-	0.146
700	5138.68	-	-	-	2.020	-	0.146
701	5138.28	-	-	-	1.980	-	0.142
702	5137.89	-	-	-	1.980	-	0.142
703	5137.50	-	-	-	1.970	-	0.142
704	5137.11	-	-	-	1.970	-	0.141
705	5136.73	-	-	-	1.980	-	0.141
706	5136.35	-	-	-	1.980	-	0.141
707	5135.97	-	-	-	1.970	-	0.141
708	5135.59	-	-	-	1.970	-	0.141
709	5135.21	-	-	-	1.960	-	0.140
710	5134.84	-	-	-	1.960	-	0.136
711	5134.46	-	-	-	1.960	-	0.136
712	5134.09	-	-	-	1.950	-	0.136
713	5133.72	-	-	-	1.950	-	0.136
714	5133.35	-	-	-	1.940	-	0.135
715	5132.98	-	-	-	1.940	-	0.135
716	5132.62	-	-	-	1.930	-	0.134
717	5132.25	-	-	-	1.940	-	0.134
718	5131.89	-	-	-	1.940	-	0.142
719	5131.52	-	-	-	1.930	-	0.142
720	5131.16	-	-	-	1.930	-	0.141
721	5130.80	-	-	-	1.930	-	0.142
722	5130.44	-	-	-	1.940	-	0.141
723	5130.08	-	-	-	1.940	-	0.141
724	5129.72	-	-	-	1.940	-	0.141
725	5129.36	-	-	-	1.940	-	0.141
726	5129.01	-	-	-	1.950	-	0.141
727	5128.65	-	-	-	1.950	-	0.141
728	5128.30	-	-	-	1.950	-	0.144
729	5127.95	-	-	-	1.990	-	0.143
730	5127.61	-	-	-	1.990	-	0.143
731	5127.26	-	-	-	1.990	-	0.150
732	5126.92	-	-	-	1.990	-	0.150
733	5126.57	-	-	-	2.000	-	0.155
734	5126.23	-	-	-	2.000	-	0.155
735	5125.90	-	-	-	2.000	-	0.155
736	5125.56	-	-	-	2.000	-	0.155
737	5125.23	-	-	-	2.010	-	0.155
738	5124.89	-	-	-	1.980	-	0.146
739	5124.56	-	-	-	1.980	-	0.146
740	5124.24	-	-	-	1.970	-	0.145
741	5123.91	-	-	-	1.970	-	0.145
742	5123.58	-	-	-	1.970	-	0.145
743	5123.25	-	-	-	1.960	-	0.138
744	5122.93	-	-	-	1.960	-	0.138
745	5122.60	-	-	-	1.970	-	0.138
746	5122.28	-	-	-	1.970	-	0.138
747	5121.95	-	-	-	1.970	-	0.137

Continued on next page

Table 14 – continued from previous page - IEEE8500 - n3637

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
748	5121.63	-	-	-	1.970	-	0.141
749	5121.31	-	-	-	1.980	-	0.139
750	5120.98	-	-	-	1.980	-	0.140
751	5120.66	-	-	-	1.980	-	0.138
752	5120.34	-	-	-	1.990	-	0.138
753	5120.02	-	-	-	1.990	-	0.138
754	5119.70	-	-	-	1.990	-	0.138
755	5119.38	-	-	-	1.990	-	0.138
756	5119.06	-	-	-	2.000	-	0.141
757	5118.75	-	-	-	2.000	-	0.140
758	5118.43	-	-	-	2.000	-	0.140
759	5118.12	-	-	-	2.000	-	0.140
760	5117.81	-	-	-	2.010	-	0.140
761	5117.50	-	-	-	2.010	-	0.141
762	5117.19	-	-	-	2.010	-	0.141
763	5116.88	-	-	-	2.020	-	0.140
764	5116.58	-	-	-	2.020	-	0.141
765	5116.27	-	-	-	2.020	-	0.141
766	5115.97	-	-	-	2.020	-	0.140
767	5115.67	-	-	-	2.030	-	0.141
768	5115.37	-	-	-	2.030	-	0.141
769	5115.07	-	-	-	2.030	-	0.141
770	5114.78	-	-	-	2.030	-	0.141
771	5114.48	-	-	-	2.040	-	0.141
772	5114.18	-	-	-	2.040	-	0.141
773	5113.89	-	-	-	2.040	-	0.141
774	5113.60	-	-	-	2.050	-	0.141
775	5113.31	-	-	-	2.050	-	0.142
776	5113.02	-	-	-	2.050	-	0.141
777	5112.73	-	-	-	2.050	-	0.144
778	5112.44	-	-	-	2.060	-	0.143
779	5112.16	-	-	-	2.060	-	0.143
780	5111.87	-	-	-	2.060	-	0.143
781	5111.59	-	-	-	2.060	-	0.144
782	5111.30	-	-	-	2.070	-	0.144
783	5111.02	-	-	-	2.070	-	0.146
784	5110.74	-	-	-	2.070	-	0.147
785	5110.46	-	-	-	2.080	-	0.145
786	5110.18	-	-	-	2.080	-	0.144
787	5109.90	-	-	-	2.080	-	0.144
788	5109.63	-	-	-	2.080	-	0.143
789	5109.36	-	-	-	2.090	-	0.143
790	5109.09	-	-	-	2.090	-	0.143
791	5108.82	-	-	-	2.090	-	0.143
792	5108.55	-	-	-	2.090	-	0.143
793	5108.29	-	-	-	2.100	-	0.144
794	5108.02	-	-	-	2.100	-	0.144
795	5107.76	-	-	-	2.100	-	0.144
796	5107.49	-	-	-	2.100	-	0.144
797	5107.23	-	-	-	2.110	-	0.144
798	5106.97	-	-	-	2.110	-	0.144
799	5106.71	-	-	-	2.110	-	0.144

Continued on next page

Table 14 – continued from previous page - IEEE8500 - n3637

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
800	5106.45	-	-	-	2.120	-	0.144
801	5106.19	-	-	-	2.120	-	0.144
802	5105.93	-	-	-	2.120	-	0.144
803	5105.68	-	-	-	2.120	-	0.144
804	5105.42	-	-	-	2.130	-	0.144
805	5105.16	-	-	-	2.130	-	0.144
806	5104.91	-	-	-	2.130	-	0.144
807	5104.65	-	-	-	2.130	-	0.144
808	5104.40	-	-	-	2.140	-	0.144
809	5104.15	-	-	-	2.140	-	0.144
810	5103.89	-	-	-	2.140	-	0.144
811	5103.64	-	-	-	2.150	-	0.145
812	5103.39	-	-	-	2.150	-	0.144
813	5103.14	-	-	-	2.150	-	0.144
814	5102.90	-	-	-	2.150	-	0.144
815	5102.65	-	-	-	2.160	-	0.144
816	5102.40	-	-	-	2.160	-	0.145
817	5102.16	-	-	-	2.160	-	0.144
818	5101.91	-	-	-	2.170	-	0.146
819	5101.67	-	-	-	2.170	-	0.145
820	5101.43	-	-	-	2.170	-	0.145
821	5101.19	-	-	-	2.170	-	0.145
822	5100.95	-	-	-	2.180	-	0.140
823	5100.71	-	-	-	2.180	-	0.140
824	5100.48	-	-	-	2.180	-	0.140
825	5100.24	-	-	-	2.190	-	0.141
826	5100.01	-	-	-	2.190	-	0.141
827	5099.77	-	-	-	2.190	-	0.149
828	5099.54	-	-	-	2.190	-	0.149
829	5099.30	-	-	-	2.200	-	0.149
830	5099.07	-	-	-	2.200	-	0.149
831	5098.84	-	-	-	2.200	-	0.149
832	5098.61	-	-	-	2.210	-	0.149
833	5098.38	-	-	-	2.210	-	0.149
834	5098.15	-	-	-	2.210	-	0.148
835	5097.92	-	-	-	2.210	-	0.154
836	5097.69	-	-	-	2.220	-	0.154
837	5097.46	-	-	-	2.220	-	0.154
838	5097.24	-	-	-	2.220	-	0.154
839	5097.01	-	-	-	2.230	-	0.154
840	5096.79	-	-	-	2.230	-	0.154
841	5096.56	-	-	-	2.230	-	0.154
842	5096.34	-	-	-	2.230	-	0.154
843	5096.12	-	-	-	2.230	-	0.154
844	5095.90	-	-	-	2.240	-	0.154
845	5095.68	-	-	-	2.240	-	0.154
846	5095.46	-	-	-	2.240	-	0.155
847	5095.25	-	-	-	2.250	-	0.155
848	5095.03	-	-	-	2.250	-	0.154
849	5094.81	-	-	-	2.250	-	0.154
850	5094.59	-	-	-	2.260	-	0.154
851	5094.38	-	-	-	2.260	-	0.154

Continued on next page

Table 14 – continued from previous page - IEEE8500 - n3637

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
852	5094.17	-	-	-	2.260	-	0.154
853	5093.96	-	-	-	2.260	-	0.154
854	5093.75	-	-	-	2.270	-	0.154
855	5093.55	-	-	-	2.270	-	0.154
856	5093.34	-	-	-	2.270	-	0.155
857	5093.13	-	-	-	2.270	-	0.155
858	5092.93	-	-	-	2.280	-	0.160
859	5092.72	-	-	-	2.280	-	0.155
860	5092.52	-	-	-	2.280	-	0.151
861	5092.31	-	-	-	2.290	-	0.151
862	5092.11	-	-	-	2.290	-	0.151
863	5091.90	-	-	-	2.290	-	0.153
864	5091.70	-	-	-	2.290	-	0.155
865	5091.50	-	-	-	2.300	-	0.153
866	5091.30	-	-	-	2.300	-	0.153
867	5091.10	-	-	-	2.300	-	0.159
868	5090.90	-	-	-	2.310	-	0.159
869	5090.70	-	-	-	2.310	-	0.159
870	5090.51	-	-	-	2.310	-	0.159
871	5090.31	-	-	-	2.310	-	0.159
872	5090.11	-	-	-	2.320	-	0.159
873	5089.92	-	-	-	2.320	-	0.159
874	5089.72	-	-	-	2.320	-	0.159
875	5089.53	-	-	-	2.330	-	0.164
876	5089.34	-	-	-	2.330	-	0.163
877	5089.15	-	-	-	2.330	-	0.163
878	5088.96	-	-	-	2.330	-	0.163
879	5088.77	-	-	-	2.340	-	0.164
880	5088.58	-	-	-	2.340	-	0.163
881	5088.39	-	-	-	2.340	-	0.164
882	5088.20	-	-	-	2.350	-	0.164
883	5088.01	-	-	-	2.350	-	0.164
884	5087.83	-	-	-	2.350	-	0.163
885	5087.64	-	-	-	2.350	-	0.163
886	5087.45	-	-	-	2.360	-	0.169
887	5087.27	-	-	-	2.360	-	0.169
888	5087.08	-	-	-	2.360	-	0.169
889	5086.89	-	-	-	2.370	-	0.170
890	5086.71	-	-	-	2.370	-	0.170
891	5086.52	-	-	-	2.370	-	0.170
892	5086.34	-	-	-	2.370	-	0.170
893	5086.15	-	-	-	2.340	-	0.161
894	5085.97	-	-	-	2.340	-	0.161
895	5085.79	-	-	-	2.320	-	0.161
896	5085.60	-	-	-	2.330	-	0.161
897	5085.42	-	-	-	2.330	-	0.160
898	5085.24	-	-	-	2.330	-	0.160
899	5085.05	-	-	-	2.340	-	0.159
900	5084.87	-	-	-	2.340	-	0.160
901	5084.69	-	-	-	2.350	-	0.165
902	5084.51	-	-	-	2.350	-	0.165
903	5084.33	-	-	-	2.350	-	0.165

Continued on next page

Table 14 – continued from previous page - IEEE8500 - n3637

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
904	5084.15	-	-	-	2.350	-	0.165
905	5083.97	-	-	-	2.340	-	0.156
906	5083.80	-	-	-	2.340	-	0.156
907	5083.62	-	-	-	2.340	-	0.156
908	5083.44	-	-	-	2.350	-	0.156
909	5083.27	-	-	-	2.330	-	0.156
910	5083.09	-	-	-	2.330	-	0.155
911	5082.92	-	-	-	2.320	-	0.146
912	5082.74	-	-	-	2.320	-	0.148
913	5082.57	-	-	-	2.330	-	0.148
914	5082.39	-	-	-	2.330	-	0.149
915	5082.22	-	-	-	2.330	-	0.154
916	5082.05	-	-	-	2.330	-	0.154
917	5081.88	-	-	-	2.340	-	0.153
918	5081.72	-	-	-	2.340	-	0.154
919	5081.55	-	-	-	2.340	-	0.154
920	5081.38	-	-	-	2.350	-	0.154
921	5081.21	-	-	-	2.350	-	0.154
922	5081.05	-	-	-	2.350	-	0.154
923	5080.88	-	-	-	2.350	-	0.154
924	5080.71	-	-	-	2.360	-	0.154
925	5080.55	-	-	-	2.360	-	0.153
926	5080.38	-	-	-	2.360	-	0.154
927	5080.22	-	-	-	2.370	-	0.155
928	5080.05	-	-	-	2.370	-	0.154
929	5079.89	-	-	-	2.370	-	0.154
930	5079.73	-	-	-	2.370	-	0.156
931	5079.56	-	-	-	2.380	-	0.156
932	5079.40	-	-	-	2.380	-	0.156
933	5079.24	-	-	-	2.380	-	0.156
934	5079.07	-	-	-	2.380	-	0.155
935	5078.91	-	-	-	2.390	-	0.155
936	5078.75	-	-	-	2.390	-	0.156
937	5078.59	-	-	-	2.390	-	0.156
938	5078.43	-	-	-	2.380	-	0.155
939	5078.27	-	-	-	2.320	-	0.153
940	5078.11	-	-	-	2.320	-	0.153
941	5077.95	-	-	-	2.280	-	0.150
942	5077.79	-	-	-	2.270	-	0.149
943	5077.63	-	-	-	2.270	-	0.149
944	5077.47	-	-	-	2.270	-	0.149
945	5077.31	-	-	-	2.230	-	0.146
946	5077.16	-	-	-	2.230	-	0.146
947	5077.00	-	-	-	2.240	-	0.145
948	5076.84	-	-	-	2.240	-	0.146
949	5076.68	-	-	-	2.240	-	0.146
950	5076.53	-	-	-	2.230	-	0.146
951	5076.37	-	-	-	2.230	-	0.146
952	5076.21	-	-	-	2.220	-	0.149
953	5076.06	-	-	-	2.220	-	0.146
954	5075.90	-	-	-	2.210	-	0.146
955	5075.75	-	-	-	2.210	-	0.146

Continued on next page

Table 14 – continued from previous page - IEEE8500 - n3637

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
956	5075.59	-	-	-	2.210	-	0.144
957	5075.44	-	-	-	2.200	-	0.143
958	5075.28	-	-	-	2.200	-	0.143
959	5075.13	-	-	-	2.190	-	0.137
960	5074.98	-	-	-	2.190	-	0.131
961	5074.82	-	-	-	2.190	-	0.131
962	5074.67	-	-	-	2.190	-	0.131
963	5074.52	-	-	-	2.200	-	0.131
964	5074.37	-	-	-	2.200	-	0.131
965	5074.22	-	-	-	2.200	-	0.130
966	5074.07	-	-	-	2.210	-	0.131
967	5073.92	-	-	-	2.210	-	0.130
968	5073.77	-	-	-	2.210	-	0.131
969	5073.62	-	-	-	2.210	-	0.131
970	5073.47	-	-	-	2.210	-	0.131
971	5073.32	-	-	-	2.220	-	0.130
972	5073.17	-	-	-	2.220	-	0.130
973	5073.02	-	-	-	2.220	-	0.130
974	5072.88	-	-	-	2.230	-	0.130
975	5072.73	-	-	-	2.230	-	0.130
976	5072.58	-	-	-	2.230	-	0.130
977	5072.43	-	-	-	2.230	-	0.130
978	5072.29	-	-	-	2.230	-	0.130
979	5072.14	-	-	-	2.240	-	0.130
980	5071.99	-	-	-	2.240	-	0.130
981	5071.85	-	-	-	2.240	-	0.131
982	5071.70	-	-	-	2.240	-	0.130
983	5071.56	-	-	-	2.250	-	0.131
984	5071.41	-	-	-	2.250	-	0.130
985	5071.27	-	-	-	2.250	-	0.130
986	5071.13	-	-	-	2.250	-	0.130
987	5070.98	-	-	-	2.260	-	0.130
988	5070.84	-	-	-	2.260	-	0.130
989	5070.70	-	-	-	2.260	-	0.130
990	5070.56	-	-	-	2.270	-	0.130
991	5070.42	-	-	-	2.270	-	0.130
992	5070.28	-	-	-	2.250	-	0.129
993	5070.14	-	-	-	2.250	-	0.129
994	5070.00	-	-	-	2.260	-	0.129
995	5069.86	-	-	-	2.260	-	0.129
996	5069.72	-	-	-	2.260	-	0.129
997	5069.58	-	-	-	2.260	-	0.129
998	5069.44	-	-	-	2.270	-	0.129
999	5069.31	-	-	-	2.270	-	0.129
1000	5069.17	-	-	-	2.270	-	0.129
1001	5069.04	-	-	-	2.270	-	0.129
1002	5068.90	-	-	-	2.280	-	0.129
1003	5068.77	-	-	-	2.280	-	0.129
1004	5068.63	-	-	-	2.280	-	0.129
1005	5068.50	-	-	-	2.250	-	0.127
1006	5068.36	-	-	-	2.250	-	0.127
1007	5068.23	-	-	-	2.240	-	0.126

Continued on next page

Table 14 – continued from previous page - IEEE8500 - n3637

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
1008	5068.10	-	-	-	2.240	-	0.126
1009	5067.96	-	-	-	2.250	-	0.126
1010	5067.83	-	-	-	2.230	-	0.125
1011	5067.70	-	-	-	2.230	-	0.125
1012	5067.57	-	-	-	2.220	-	0.125
1013	5067.43	-	-	-	2.230	-	0.124
1014	5067.30	-	-	-	2.230	-	0.125
1015	5067.17	-	-	-	2.220	-	0.124
1016	5067.04	-	-	-	2.220	-	0.123
1017	5066.91	-	-	-	2.220	-	0.124
1018	5066.78	-	-	-	2.220	-	0.124
1019	5066.65	-	-	-	2.230	-	0.124
1020	5066.52	-	-	-	2.230	-	0.124
1021	5066.39	-	-	-	2.230	-	0.124
1022	5066.26	-	-	-	2.230	-	0.124
1023	5066.13	-	-	-	2.230	-	0.123
1024	5066.00	-	-	-	2.240	-	0.123
1025	5065.87	-	-	-	2.240	-	0.123
1026	5065.74	-	-	-	2.240	-	0.123
1027	5065.62	-	-	-	2.250	-	0.123
1028	5065.49	-	-	-	2.250	-	0.123
1029	5065.36	-	-	-	2.250	-	0.123
1030	5065.24	-	-	-	2.240	-	0.118
1031	5065.11	-	-	-	2.240	-	0.118
1032	5064.99	-	-	-	2.240	-	0.118
1033	5064.86	-	-	-	2.230	-	0.117
1034	5064.73	-	-	-	2.230	-	0.117
1035	5064.61	-	-	-	2.240	-	0.117
1036	5064.49	-	-	-	2.240	-	0.120
1037	5064.36	-	-	-	2.230	-	0.119
1038	5064.24	-	-	-	2.230	-	0.119
1039	5064.12	-	-	-	2.230	-	0.119
1040	5063.99	-	-	-	2.230	-	0.119
1041	5063.87	-	-	-	2.230	-	0.119
1042	5063.75	-	-	-	2.240	-	0.119
1043	5063.63	-	-	-	2.240	-	0.119
1044	5063.50	-	-	-	2.240	-	0.119
1045	5063.38	-	-	-	2.240	-	0.119
1046	5063.26	-	-	-	2.250	-	0.119
1047	5063.14	-	-	-	2.250	-	0.119
1048	5063.02	-	-	-	2.250	-	0.119
1049	5062.90	-	-	-	2.250	-	0.119
1050	5062.77	-	-	-	2.250	-	0.119
1051	5062.65	-	-	-	2.260	-	0.119
1052	5062.53	-	-	-	2.260	-	0.119
1053	5062.41	-	-	-	2.260	-	0.119
1054	5062.29	-	-	-	2.270	-	0.119
1055	5062.17	-	-	-	2.270	-	0.119
1056	5062.06	-	-	-	2.270	-	0.119
1057	5061.94	-	-	-	2.270	-	0.119
1058	5061.82	-	-	-	2.270	-	0.120
1059	5061.70	-	-	-	2.280	-	0.119

Continued on next page

Table 14 – continued from previous page - IEEE8500 - n3637

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
1060	5061.58	-	-	-	2.280	-	0.120
1061	5061.46	-	-	-	2.280	-	0.119
1062	5061.34	-	-	-	2.280	-	0.119
1063	5061.23	-	-	-	2.290	-	0.120
1064	5061.11	-	-	-	2.290	-	0.120
1065	5060.99	-	-	-	2.290	-	0.118
1066	5060.87	-	-	-	2.300	-	0.118
1067	5060.76	-	-	-	2.300	-	0.118
1068	5060.64	-	-	-	2.300	-	0.118
1069	5060.52	-	-	-	2.300	-	0.118
1070	5060.41	-	-	-	2.300	-	0.118
1071	5060.29	-	-	-	2.310	-	0.118
1072	5060.18	-	-	-	2.310	-	0.119
1073	5060.06	-	-	-	2.310	-	0.114
1074	5059.95	-	-	-	2.310	-	0.113
1075	5059.83	-	-	-	2.310	-	0.113
1076	5059.72	-	-	-	2.320	-	0.113
1077	5059.60	-	-	-	2.320	-	0.113
1078	5059.49	-	-	-	2.320	-	0.113
1079	5059.37	-	-	-	2.330	-	0.113
1080	5059.26	-	-	-	2.330	-	0.113
1081	5059.15	-	-	-	2.330	-	0.117
1082	5059.03	-	-	-	2.330	-	0.115
1083	5058.92	-	-	-	2.330	-	0.113
1084	5058.81	-	-	-	2.330	-	0.112
1085	5058.70	-	-	-	2.340	-	0.113
1086	5058.58	-	-	-	2.340	-	0.113
1087	5058.47	-	-	-	2.340	-	0.113
1088	5058.36	-	-	-	2.350	-	0.113
1089	5058.25	-	-	-	2.350	-	0.113
1090	5058.14	-	-	-	2.350	-	0.113
1091	5058.03	-	-	-	2.350	-	0.112
1092	5057.92	-	-	-	2.350	-	0.115
1093	5057.81	-	-	-	2.360	-	0.115
1094	5057.70	-	-	-	2.360	-	0.115
1095	5057.59	-	-	-	2.370	-	0.115
1096	5057.48	-	-	-	2.370	-	0.115
1097	5057.37	-	-	-	2.370	-	0.115
1098	5057.26	-	-	-	2.370	-	0.115
1099	5057.15	-	-	-	2.370	-	0.115
1100	5057.04	-	-	-	2.380	-	0.115
1101	5056.94	-	-	-	2.380	-	0.115
1102	5056.83	-	-	-	2.380	-	0.115
1103	5056.72	-	-	-	2.380	-	0.115
1104	5056.62	-	-	-	2.380	-	0.115
1105	5056.51	-	-	-	2.390	-	0.115
1106	5056.41	-	-	-	2.390	-	0.115
1107	5056.30	-	-	-	2.390	-	0.115
1108	5056.20	-	-	-	2.400	-	0.112
1109	5056.09	-	-	-	2.400	-	0.112
1110	5055.99	-	-	-	2.400	-	0.111
1111	5055.89	-	-	-	2.400	-	0.112

Continued on next page

Table 14 – continued from previous page - IEEE8500 - n3637

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
1112	5055.78	-	-	-	2.400	-	0.111
1113	5055.68	-	-	-	2.400	-	0.112
1114	5055.58	-	-	-	2.410	-	0.112
1115	5055.48	-	-	-	2.410	-	0.112
1116	5055.37	-	-	-	2.410	-	0.113
1117	5055.27	-	-	-	2.420	-	0.112
1118	5055.17	-	-	-	2.420	-	0.114
1119	5055.07	-	-	-	2.420	-	0.112
1120	5054.97	-	-	-	2.420	-	0.112
1121	5054.86	-	-	-	2.420	-	0.112
1122	5054.76	-	-	-	2.430	-	0.112
1123	5054.66	-	-	-	2.430	-	0.112
1124	5054.56	-	-	-	2.430	-	0.112
1125	5054.46	-	-	-	2.440	-	0.114
1126	5054.36	-	-	-	2.440	-	0.113
1127	5054.26	-	-	-	2.440	-	0.113
1128	5054.17	-	-	-	2.440	-	0.112
1129	5054.07	-	-	-	2.450	-	0.111
1130	5053.97	-	-	-	2.450	-	0.112
1131	5053.87	-	-	-	2.450	-	0.112
1132	5053.77	-	-	-	2.460	-	0.112
1133	5053.67	-	-	-	2.460	-	0.112
1134	5053.57	-	-	-	2.460	-	0.114
1135	5053.48	-	-	-	2.460	-	0.114
1136	5053.38	-	-	-	2.460	-	0.113
1137	5053.28	-	-	-	2.470	-	0.113
1138	5053.19	-	-	-	2.470	-	0.113
1139	5053.09	-	-	-	2.470	-	0.116
1140	5052.99	-	-	-	2.480	-	0.116
1141	5052.90	-	-	-	2.480	-	0.116
1142	5052.80	-	-	-	2.480	-	0.116
1143	5052.70	-	-	-	2.480	-	0.116
1144	5052.61	-	-	-	2.480	-	0.116
1145	5052.51	-	-	-	2.490	-	0.116
1146	5052.42	-	-	-	2.460	-	0.117
1147	5052.32	-	-	-	2.460	-	0.116
1148	5052.23	-	-	-	2.460	-	0.116
1149	5052.13	-	-	-	2.460	-	0.113
1150	5052.04	-	-	-	2.460	-	0.113
1151	5051.95	-	-	-	2.470	-	0.114
1152	5051.85	-	-	-	2.470	-	0.114
1153	5051.76	-	-	-	2.470	-	0.114
1154	5051.67	-	-	-	2.470	-	0.113
1155	5051.57	-	-	-	2.480	-	0.113
1156	5051.48	-	-	-	2.480	-	0.113
1157	5051.39	-	-	-	2.480	-	0.113
1158	5051.29	-	-	-	2.480	-	0.114
1159	5051.20	-	-	-	2.490	-	0.114
1160	5051.11	-	-	-	2.490	-	0.114
1161	5051.02	-	-	-	2.490	-	0.114
1162	5050.93	-	-	-	2.490	-	0.114
1163	5050.84	-	-	-	2.500	-	0.113

Continued on next page

Table 14 – continued from previous page - IEEE8500 - n3637

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
1164	5050.75	-	-	-	2.500	-	0.114
1165	5050.66	-	-	-	2.500	-	0.113
1166	5050.57	-	-	-	2.500	-	0.115
1167	5050.48	-	-	-	2.510	-	0.115
1168	5050.39	-	-	-	2.510	-	0.115
1169	5050.30	-	-	-	2.510	-	0.115
1170	5050.21	-	-	-	2.510	-	0.115
1171	5050.12	-	-	-	2.510	-	0.114
1172	5050.03	-	-	-	2.520	-	0.114
1173	5049.94	-	-	-	2.520	-	0.115
1174	5049.85	-	-	-	2.520	-	0.115
1175	5049.76	-	-	-	2.520	-	0.115
1176	5049.68	-	-	-	2.530	-	0.115
1177	5049.59	-	-	-	2.570	-	0.115
1178	5049.50	-	-	-	2.570	-	0.115
1179	5049.41	-	-	-	2.540	-	0.115
1180	5049.32	-	-	-	2.540	-	0.115
1181	5049.24	-	-	-	2.540	-	0.115
1182	5049.15	-	-	-	2.540	-	0.115
1183	5049.06	-	-	-	2.580	-	0.115
1184	5048.98	-	-	-	2.580	-	0.115
1185	5048.89	-	-	-	2.590	-	0.115
1186	5048.80	-	-	-	2.590	-	0.116
1187	5048.72	-	-	-	2.590	-	0.115
1188	5048.63	-	-	-	2.590	-	0.115
1189	5048.55	-	-	-	2.600	-	0.115
1190	5048.46	-	-	-	2.600	-	0.115
1191	5048.38	-	-	-	2.600	-	0.115
1192	5048.29	-	-	-	2.600	-	0.115
1193	5048.20	-	-	-	2.610	-	0.114
1194	5048.12	-	-	-	2.610	-	0.115
1195	5048.03	-	-	-	2.610	-	0.115
1196	5047.95	-	-	-	2.610	-	0.116
1197	5047.87	-	-	-	2.620	-	0.114
1198	5047.78	-	-	-	2.620	-	0.114
1199	5047.70	-	-	-	2.620	-	0.114
1200	5047.61	-	-	-	2.620	-	0.114
1201	5047.53	-	-	-	2.630	-	0.114
1202	5047.45	-	-	-	2.630	-	0.114
1203	5047.36	-	-	-	2.600	-	0.115
1204	5047.28	-	-	-	2.600	-	0.115
1205	5047.20	-	-	-	2.600	-	0.115
1206	5047.12	-	-	-	2.600	-	0.115
1207	5047.03	-	-	-	2.640	-	0.115
1208	5046.95	-	-	-	2.650	-	0.115
1209	5046.87	-	-	-	2.610	-	0.115
1210	5046.79	-	-	-	2.610	-	0.115
1211	5046.71	-	-	-	2.610	-	0.115
1212	5046.63	-	-	-	2.620	-	0.114
1213	5046.55	-	-	-	2.620	-	0.115
1214	5046.47	-	-	-	2.620	-	0.115
1215	5046.39	-	-	-	2.620	-	0.115

Continued on next page

Table 14 – continued from previous page - IEEE8500 - n3637

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
1216	5046.31	-	-	-	2.630	-	0.115
1217	5046.23	-	-	-	2.630	-	0.114
1218	5046.16	-	-	-	7.720	-	5.238
1219	5046.08	-	-	-	2.550	-	0.115
1220	5046.00	-	-	-	2.550	-	0.113
1221	5045.92	-	-	-	2.560	-	0.113
1222	5045.84	-	-	-	2.560	-	0.113
1223	5045.77	-	-	-	2.560	-	0.112
1224	5045.69	-	-	-	2.600	-	0.112
1225	5045.61	-	-	-	2.600	-	0.112
1226	5045.53	-	-	-	2.610	-	0.112
1227	5045.46	-	-	-	2.610	-	0.112
1228	5045.38	-	-	-	2.580	-	0.112
1229	5045.30	-	-	-	2.580	-	0.111
1230	5045.22	-	-	-	2.580	-	0.111
1231	5045.15	-	-	-	2.580	-	0.111
1232	5045.07	-	-	-	2.580	-	0.111
1233	5044.99	-	-	-	2.580	-	0.109
1234	5044.92	-	-	-	2.590	-	0.109
1235	5044.84	-	-	-	2.590	-	0.109
1236	5044.77	-	-	-	2.590	-	0.109
1237	5044.69	-	-	-	2.590	-	0.109
1238	5044.61	-	-	-	2.600	-	0.109
1239	5044.54	-	-	-	2.600	-	0.109
1240	5044.46	-	-	-	2.600	-	0.109
1241	5044.39	-	-	-	2.600	-	0.109
1242	5044.31	-	-	-	2.610	-	0.109
1243	5044.24	-	-	-	2.610	-	0.109
1244	5044.16	-	-	-	2.610	-	0.109
1245	5044.09	-	-	-	2.610	-	0.109
1246	5044.01	-	-	-	2.610	-	0.109
1247	5043.94	-	-	-	2.620	-	0.109
1248	5043.86	-	-	-	2.620	-	0.109
1249	5043.79	-	-	-	2.620	-	0.109
1250	5043.71	-	-	-	2.620	-	0.108
1251	5043.64	-	-	-	2.630	-	0.108
1252	5043.57	-	-	-	2.630	-	0.108
1253	5043.49	-	-	-	2.630	-	0.108
1254	5043.42	-	-	-	2.630	-	0.108
1255	5043.35	-	-	-	2.630	-	0.108
1256	5043.27	-	-	-	2.640	-	0.108
1257	5043.20	-	-	-	2.640	-	0.109
1258	5043.13	-	-	-	2.640	-	0.108
1259	5043.05	-	-	-	2.640	-	0.108
1260	5042.98	-	-	-	2.650	-	0.108
1261	5042.91	-	-	-	2.650	-	0.108
1262	5042.84	-	-	-	2.650	-	0.108
1263	5042.76	-	-	-	2.650	-	0.108
1264	5042.69	-	-	-	2.660	-	0.108
1265	5042.62	-	-	-	2.660	-	0.108
1266	5042.55	-	-	-	2.660	-	0.109
1267	5042.48	-	-	-	2.660	-	0.108

Continued on next page

Table 14 – continued from previous page - IEEE8500 - n3637

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
1268	5042.41	-	-	-	2.710	-	0.109
1269	5042.33	-	-	-	2.710	-	0.109
1270	5042.26	-	-	-	2.710	-	0.109
1271	5042.19	-	-	-	2.710	-	0.109
1272	5042.12	-	-	-	2.720	-	0.109
1273	5042.05	-	-	-	2.710	-	0.109
1274	5041.98	-	-	-	2.720	-	0.108
1275	5041.91	-	-	-	2.720	-	0.109
1276	5041.84	-	-	-	2.690	-	0.109
1277	5041.77	-	-	-	2.690	-	0.108
1278	5041.70	-	-	-	2.690	-	0.108
1279	5041.63	-	-	-	2.690	-	0.108
1280	5041.56	-	-	-	2.690	-	0.108
1281	5041.50	-	-	-	2.690	-	0.108
1282	5041.43	-	-	-	2.700	-	0.108
1283	5041.36	-	-	-	2.700	-	0.108
1284	5041.29	-	-	-	2.700	-	0.108
1285	5041.22	-	-	-	2.700	-	0.108
1286	5041.15	-	-	-	2.710	-	0.108
1287	5041.09	-	-	-	2.710	-	0.108
1288	5041.02	-	-	-	2.710	-	0.108
1289	5040.95	-	-	-	2.710	-	0.108
1290	5040.89	-	-	-	2.720	-	0.108
1291	5040.82	-	-	-	2.720	-	0.108
1292	5040.75	-	-	-	2.720	-	0.108
1293	5040.69	-	-	-	2.720	-	0.108
1294	5040.62	-	-	-	2.770	-	0.108
1295	5040.55	-	-	-	2.770	-	0.110
1296	5040.49	-	-	-	2.770	-	0.109
1297	5040.42	-	-	-	2.770	-	0.109
1298	5040.36	-	-	-	2.770	-	0.110
1299	5040.29	-	-	-	2.780	-	0.110
1300	5040.22	-	-	-	2.780	-	0.110
1301	5040.16	-	-	-	2.780	-	0.112
1302	5040.09	-	-	-	2.790	-	0.112
1303	5040.03	-	-	-	2.790	-	0.112
1304	5039.96	-	-	-	2.790	-	0.111
1305	5039.90	-	-	-	2.790	-	0.110
1306	5039.83	-	-	-	2.790	-	0.110
1307	5039.77	-	-	-	2.800	-	0.110
1308	5039.70	-	-	-	2.760	-	0.110
1309	5039.64	-	-	-	2.760	-	0.110
1310	5039.58	-	-	-	2.760	-	0.111
1311	5039.51	-	-	-	2.760	-	0.112
1312	5039.45	-	-	-	2.770	-	0.112
1313	5039.38	-	-	-	2.770	-	0.110
1314	5039.32	-	-	-	2.770	-	0.110
1315	5039.25	-	-	-	2.770	-	0.110
1316	5039.19	-	-	-	2.770	-	0.110
1317	5039.13	-	-	-	2.770	-	0.110
1318	5039.06	-	-	-	2.820	-	0.110
1319	5039.00	-	-	-	2.830	-	0.110

Continued on next page

Table 14 – continued from previous page - IEEE8500 - n3637

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
1320	5038.94	-	-	-	2.830	-	0.110
1321	5038.87	-	-	-	2.830	-	0.110
1322	5038.81	-	-	-	2.830	-	0.110
1323	5038.75	-	-	-	2.830	-	0.110
1324	5038.69	-	-	-	2.800	-	0.110
1325	5038.62	-	-	-	2.800	-	0.110
1326	5038.56	-	-	-	2.800	-	0.109
1327	5038.50	-	-	-	2.800	-	0.110
1328	5038.44	-	-	-	2.810	-	0.110
1329	5038.38	-	-	-	2.810	-	0.111
1330	5038.32	-	-	-	2.810	-	0.110
1331	5038.26	-	-	-	2.810	-	0.111
1332	5038.19	-	-	-	2.810	-	0.111
1333	5038.13	-	-	-	2.820	-	0.111
1334	5038.07	-	-	-	2.820	-	0.110
1335	5038.01	-	-	-	2.820	-	0.110
1336	5037.96	-	-	-	2.830	-	0.110
1337	5037.90	-	-	-	2.830	-	0.110
1338	5037.84	-	-	-	2.830	-	0.110
1339	5037.78	-	-	-	2.830	-	0.110
1340	5037.72	-	-	-	2.830	-	0.110
1341	5037.66	-	-	-	2.840	-	0.110
1342	5037.60	-	-	-	2.840	-	0.109
1343	5037.54	-	-	-	2.840	-	0.110
1344	5037.48	-	-	-	2.840	-	0.110
1345	5037.42	-	-	-	2.850	-	0.110
1346	5037.36	-	-	-	2.850	-	0.109
1347	5037.31	-	-	-	2.850	-	0.110
1348	5037.25	-	-	-	2.850	-	0.109
1349	5037.19	-	-	-	2.850	-	0.109
1350	5037.13	-	-	-	2.860	-	0.109
1351	5037.07	-	-	-	2.860	-	0.110
1352	5037.02	-	-	-	2.860	-	0.109
1353	5036.96	-	-	-	2.860	-	0.109
1354	5036.90	-	-	-	2.870	-	0.109
1355	5036.84	-	-	-	2.870	-	0.109
1356	5036.79	-	-	-	2.870	-	0.110
1357	5036.73	-	-	-	2.880	-	0.110
1358	5036.67	-	-	-	2.880	-	0.109
1359	5036.62	-	-	-	2.880	-	0.109
1360	5036.56	-	-	-	2.880	-	0.109
1361	5036.50	-	-	-	2.880	-	0.109
1362	5036.45	-	-	-	2.880	-	0.109
1363	5036.39	-	-	-	2.890	-	0.110
1364	5036.33	-	-	-	2.890	-	0.110
1365	5036.28	-	-	-	2.890	-	0.110
1366	5036.22	-	-	-	2.900	-	0.110
1367	5036.17	-	-	-	2.900	-	0.110
1368	5036.11	-	-	-	2.940	-	0.113
1369	5036.06	-	-	-	2.940	-	0.112
1370	5036.00	-	-	-	2.950	-	0.112
1371	5035.95	-	-	-	2.950	-	0.112

Continued on next page

Table 14 – continued from previous page - IEEE8500 - n3637

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
1372	5035.89	-	-	-	2.950	-	0.112
1373	5035.84	-	-	-	2.950	-	0.139
1374	5035.79	-	-	-	2.960	-	0.139
1375	5035.73	-	-	-	2.960	-	0.140
1376	5035.68	-	-	-	2.960	-	0.139
1377	5035.62	-	-	-	2.960	-	0.138
1378	5035.57	-	-	-	2.970	-	0.138
1379	5035.52	-	-	-	2.970	-	0.138
1380	5035.46	-	-	-	2.970	-	0.138
1381	5035.41	-	-	-	2.970	-	0.138
1382	5035.36	-	-	-	2.970	-	0.139
1383	5035.30	-	-	-	2.980	-	0.160
1384	5035.25	-	-	-	2.980	-	0.160
1385	5035.20	-	-	-	2.980	-	0.160
1386	5035.14	-	-	-	2.980	-	0.161
1387	5035.09	-	-	-	2.990	-	0.184
1388	5035.04	-	-	-	2.990	-	0.182
1389	5034.99	-	-	-	2.990	-	0.182
1390	5034.93	-	-	-	2.990	-	0.182
1391	5034.88	-	-	-	3.000	-	0.182
1392	5034.83	-	-	-	3.000	-	0.183
1393	5034.78	-	-	-	3.000	-	0.182
1394	5034.73	-	-	-	3.000	-	0.182
1395	5034.67	-	-	-	3.010	-	0.184
1396	5034.62	-	-	-	3.010	-	0.184
1397	5034.57	-	-	-	3.010	-	0.185
1398	5034.52	-	-	-	3.020	-	0.185
1399	5034.47	-	-	-	3.020	-	0.184
1400	5034.42	-	-	-	3.020	-	0.184
1401	5034.37	-	-	-	3.020	-	0.184
1402	5034.32	-	-	-	3.020	-	0.185
1403	5034.27	-	-	-	3.020	-	0.184
1404	5034.21	-	-	-	3.030	-	0.185
1405	5034.16	-	-	-	3.030	-	0.185
1406	5034.11	-	-	-	3.030	-	0.185
1407	5034.06	-	-	-	3.040	-	0.185
1408	5034.01	-	-	-	3.040	-	0.185
1409	5033.96	-	-	-	3.040	-	0.185
1410	5033.91	-	-	-	3.040	-	0.185
1411	5033.86	-	-	-	3.040	-	0.184
1412	5033.81	-	-	-	3.050	-	0.185
1413	5033.77	-	-	-	3.050	-	0.185
1414	5033.72	-	-	-	3.050	-	0.185
1415	5033.67	-	-	-	3.050	-	0.186
1416	5033.62	-	-	-	3.060	-	0.186
1417	5033.57	-	-	-	3.060	-	0.186
1418	5033.52	-	-	-	3.060	-	0.186
1419	5033.47	-	-	-	3.060	-	0.186
1420	5033.43	-	-	-	3.070	-	0.200
1421	5033.38	-	-	-	3.070	-	0.199
1422	5033.33	-	-	-	3.070	-	0.199
1423	5033.28	-	-	-	3.080	-	0.199

Continued on next page

Table 14 – continued from previous page - IEEE8500 - n3637

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
1424	5033.23	-	-	-	3.080	-	0.199
1425	5033.18	-	-	-	3.080	-	0.200
1426	5033.14	-	-	-	3.080	-	0.200
1427	5033.09	-	-	-	3.080	-	0.201
1428	5033.04	-	-	-	3.080	-	0.200
1429	5032.99	-	-	-	3.090	-	0.200
1430	5032.95	-	-	-	3.090	-	0.200
1431	5032.90	-	-	-	3.090	-	0.200
1432	5032.85	-	-	-	3.090	-	0.200
1433	5032.80	-	-	-	3.100	-	0.200
1434	5032.76	-	-	-	3.100	-	0.199
1435	5032.71	-	-	-	3.100	-	0.200
1436	5032.66	-	-	-	3.100	-	0.200
1437	5032.61	-	-	-	3.110	-	0.200
1438	5032.57	-	-	-	3.110	-	0.200
1439	5032.52	-	-	-	3.110	-	0.200
1440	5032.47	-	-	-	3.110	-	0.200
1441	5032.42	-	-	-	3.110	-	0.201
1442	5032.38	-	-	-	3.120	-	0.201
1443	5032.33	-	-	-	3.120	-	0.201
1444	5032.29	-	-	-	3.120	-	0.201
1445	5032.24	-	-	-	3.130	-	0.201
1446	5032.19	-	-	-	3.130	-	0.202
1447	5032.15	-	-	-	3.130	-	0.202
1448	5032.10	-	-	-	3.130	-	0.202
1449	5032.05	-	-	-	3.140	-	0.202
1450	5032.01	-	-	-	3.140	-	0.202
1451	5031.96	-	-	-	3.140	-	0.201
1452	5031.92	-	-	-	3.150	-	0.202
1453	5031.87	-	-	-	3.150	-	0.201
1454	5031.83	-	-	-	3.150	-	0.205
1455	5031.78	-	-	-	3.150	-	0.205
1456	5031.73	-	-	-	3.150	-	0.202
1457	5031.69	-	-	-	3.150	-	0.202
1458	5031.64	-	-	-	3.160	-	0.203
1459	5031.60	-	-	-	3.160	-	0.203
1460	5031.55	-	-	-	3.160	-	0.203
1461	5031.51	-	-	-	3.170	-	0.202
1462	5031.46	-	-	-	3.170	-	0.203
1463	5031.42	-	-	-	3.170	-	0.203
1464	5031.38	-	-	-	3.170	-	0.203
1465	5031.33	-	-	-	3.170	-	0.203
1466	5031.29	-	-	-	3.180	-	0.204
1467	5031.24	-	-	-	3.180	-	0.203
1468	5031.20	-	-	-	3.180	-	0.202
1469	5031.15	-	-	-	3.180	-	0.203
1470	5031.11	-	-	-	3.190	-	0.203
1471	5031.07	-	-	-	3.190	-	0.202
1472	5031.02	-	-	-	3.190	-	0.203
1473	5030.98	-	-	-	3.190	-	0.203
1474	5030.93	-	-	-	3.200	-	0.204
1475	5030.89	-	-	-	3.200	-	0.204

Continued on next page

Table 14 – continued from previous page - IEEE8500 - n3637

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
1476	5030.85	-	-	-	3.200	-	0.205
1477	5030.80	-	-	-	3.210	-	0.205
1478	5030.76	-	-	-	3.210	-	0.206
1479	5030.71	-	-	-	3.210	-	0.205
1480	5030.67	-	-	-	3.210	-	0.205
1481	5030.63	-	-	-	3.210	-	0.205
1482	5030.58	-	-	-	3.210	-	0.205
1483	5030.54	-	-	-	3.220	-	0.205
1484	5030.50	-	-	-	3.220	-	0.206
1485	5030.45	-	-	-	3.220	-	0.205
1486	5030.41	-	-	-	3.230	-	0.205
1487	5030.37	-	-	-	3.230	-	0.206
1488	5030.32	-	-	-	3.230	-	0.205
1489	5030.28	-	-	-	3.230	-	0.206
1490	5030.24	-	-	-	3.240	-	0.205
1491	5030.20	-	-	-	3.240	-	0.205
1492	5030.15	-	-	-	3.240	-	0.206
1493	5030.11	-	-	-	3.240	-	0.206
1494	5030.07	-	-	-	3.250	-	0.206
1495	5030.03	-	-	-	3.250	-	0.206
1496	5029.99	-	-	-	3.250	-	0.206
1497	5029.94	-	-	-	3.250	-	0.206
1498	5029.90	-	-	-	3.250	-	0.207
1499	5029.86	-	-	-	3.260	-	0.208
1500	5029.82	-	-	-	3.260	-	0.206
1501	5029.78	-	-	-	3.260	-	0.206
1502	5029.73	-	-	-	3.260	-	0.206
1503	5029.69	-	-	-	3.270	-	0.206
1504	5029.65	-	-	-	3.270	-	0.207
1505	5029.61	-	-	-	3.270	-	0.207
1506	5029.57	-	-	-	3.270	-	0.208
1507	5029.53	-	-	-	3.280	-	0.208
1508	5029.49	-	-	-	3.280	-	0.208
1509	5029.44	-	-	-	3.280	-	0.208
1510	5029.40	-	-	-	3.290	-	0.208
1511	5029.36	-	-	-	3.290	-	0.208
1512	5029.32	-	-	-	3.290	-	0.208
1513	5029.28	-	-	-	3.290	-	0.210
1514	5029.24	-	-	-	3.300	-	0.210
1515	5029.20	-	-	-	3.300	-	0.208
1516	5029.16	-	-	-	3.300	-	0.208
1517	5029.12	-	-	-	3.300	-	0.209
1518	5029.08	-	-	-	3.310	-	0.210
1519	5029.04	-	-	-	3.310	-	0.209
1520	5029.00	-	-	-	3.310	-	0.209
1521	5028.96	-	-	-	3.310	-	0.209
1522	5028.92	-	-	-	3.310	-	0.212
1523	5028.88	-	-	-	3.320	-	0.214
1524	5028.84	-	-	-	3.320	-	0.209
1525	5028.80	-	-	-	3.390	-	0.209
1526	5028.76	-	-	-	3.360	-	0.209
1527	5028.72	-	-	-	3.500	-	0.211

Continued on next page

Table 14 – continued from previous page - IEEE8500 - n3637

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
1528	5028.68	-	-	-	3.690	-	0.227
1529	5028.64	-	-	-	3.650	-	0.226
1530	5028.60	-	-	-	3.610	-	0.228
1531	5028.56	-	-	-	3.570	-	0.227
1532	5028.53	-	-	-	3.600	-	0.227
1533	5028.49	-	-	-	3.540	-	0.227
1534	5028.45	-	-	-	3.420	-	0.228
1535	5028.41	-	-	-	3.480	-	0.227
1536	5028.37	-	-	-	3.490	-	0.228
1537	5028.33	-	-	-	3.320	-	0.229
1538	5028.29	-	-	-	3.310	-	0.229
1539	5028.26	-	-	-	3.310	-	0.229
1540	5028.22	-	-	-	3.310	-	0.229
1541	5028.18	-	-	-	3.310	-	0.229
1542	5028.14	-	-	-	3.310	-	0.229
1543	5028.10	-	-	-	3.320	-	0.229
1544	5028.07	-	-	-	3.320	-	0.229
1545	5028.03	-	-	-	3.320	-	0.229
1546	5027.99	-	-	-	3.330	-	0.228
1547	5027.95	-	-	-	3.330	-	0.228
1548	5027.92	-	-	-	3.330	-	0.228
1549	5027.88	-	-	-	3.330	-	0.229
1550	5027.84	-	-	-	3.340	-	0.228
1551	5027.81	-	-	-	3.330	-	0.228
1552	5027.77	-	-	-	3.340	-	0.228
1553	5027.73	-	-	-	3.340	-	0.228
1554	5027.69	-	-	-	3.340	-	0.229
1555	5027.66	-	-	-	3.350	-	0.229
1556	5027.62	-	-	-	3.350	-	0.228
1557	5027.59	-	-	-	3.350	-	0.229
1558	5027.55	-	-	-	3.350	-	0.229
1559	5027.51	-	-	-	3.360	-	0.229
1560	5027.48	-	-	-	3.360	-	0.229
1561	5027.44	-	-	-	3.360	-	0.229
1562	5027.41	-	-	-	3.360	-	0.229
1563	5027.37	-	-	-	3.370	-	0.229
1564	5027.33	-	-	-	3.370	-	0.229
1565	5027.30	-	-	-	3.370	-	0.229
1566	5027.26	-	-	-	3.370	-	0.230
1567	5027.23	-	-	-	3.380	-	0.231
1568	5027.19	-	-	-	3.380	-	0.229
1569	5027.16	-	-	-	3.380	-	0.229
1570	5027.12	-	-	-	3.380	-	0.229
1571	5027.09	-	-	-	3.390	-	0.235
1572	5027.05	-	-	-	3.390	-	0.230
1573	5027.02	-	-	-	3.400	-	0.229
1574	5026.98	-	-	-	3.400	-	0.230
1575	5026.95	-	-	-	3.400	-	0.230
1576	5026.91	-	-	-	3.400	-	0.231
1577	5026.88	-	-	-	3.400	-	0.229
1578	5026.84	-	-	-	3.400	-	0.230
1579	5026.81	-	-	-	3.410	-	0.229

Continued on next page

Table 14 – continued from previous page - IEEE8500 - n3637

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
1580	5026.77	-	-	-	3.410	-	0.230
1581	5026.74	-	-	-	3.410	-	0.229
1582	5026.70	-	-	-	3.420	-	0.229
1583	5026.67	-	-	-	3.420	-	0.229
1584	5026.63	-	-	-	3.420	-	0.229
1585	5026.60	-	-	-	3.420	-	0.229
1586	5026.56	-	-	-	3.420	-	0.229
1587	5026.53	-	-	-	3.430	-	0.229
1588	5026.50	-	-	-	3.430	-	0.229
1589	5026.46	-	-	-	3.430	-	0.229
1590	5026.43	-	-	-	3.430	-	0.229
1591	5026.39	-	-	-	3.440	-	0.230
1592	5026.36	-	-	-	3.440	-	0.231
1593	5026.33	-	-	-	3.440	-	0.231
1594	5026.29	-	-	-	3.440	-	0.231
1595	5026.26	-	-	-	3.440	-	0.230
1596	5026.22	-	-	-	3.450	-	0.230
1597	5026.19	-	-	-	3.450	-	0.233
1598	5026.16	-	-	-	3.450	-	0.229
1599	5026.12	-	-	-	3.460	-	0.229
1600	5026.09	-	-	-	3.460	-	0.229
1601	5026.05	-	-	-	3.460	-	0.229
1602	5026.02	-	-	-	3.460	-	0.228
1603	5025.99	-	-	-	3.470	-	0.228
1604	5025.95	-	-	-	3.470	-	0.228
1605	5025.92	-	-	-	3.470	-	0.229
1606	5025.89	-	-	-	3.470	-	0.229
1607	5025.85	-	-	-	3.480	-	0.228
1608	5025.82	-	-	-	3.480	-	0.229
1609	5025.79	-	-	-	3.480	-	0.229
1610	5025.76	-	-	-	3.480	-	0.229
1611	5025.72	-	-	-	3.490	-	0.205
1612	5025.69	-	-	-	3.490	-	0.205
1613	5025.66	-	-	-	3.490	-	0.206
1614	5025.63	-	-	-	3.500	-	0.205
1615	5025.59	-	-	-	3.500	-	0.206
1616	5025.56	-	-	-	3.500	-	0.205
1617	5025.53	-	-	-	3.500	-	0.206
1618	5025.50	-	-	-	3.500	-	0.206
1619	5025.47	-	-	-	3.510	-	0.206
1620	5025.43	-	-	-	3.510	-	0.206
1621	5025.40	-	-	-	3.510	-	0.206
1622	5025.37	-	-	-	3.510	-	0.182
1623	5025.34	-	-	-	3.520	-	0.182
1624	5025.31	-	-	-	3.520	-	0.182
1625	5025.28	-	-	-	3.520	-	0.183
1626	5025.25	-	-	-	3.520	-	0.182
1627	5025.22	-	-	-	3.520	-	0.157
1628	5025.18	-	-	-	3.530	-	0.157
1629	5025.15	-	-	-	3.530	-	0.157
1630	5025.12	-	-	-	3.540	-	0.157
1631	5025.09	-	-	-	3.540	-	0.157

Continued on next page

Table 14 – continued from previous page - IEEE8500 - n3637

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
1632	5025.06	-	-	-	3.540	-	0.157
1633	5025.03	-	-	-	3.540	-	0.157
1634	5025.00	-	-	-	3.540	-	0.157
1635	5024.97	-	-	-	3.550	-	0.157
1636	5024.94	-	-	-	3.550	-	0.157
1637	5024.91	-	-	-	3.550	-	0.157
1638	5024.88	-	-	-	3.550	-	0.159
1639	5024.85	-	-	-	3.560	-	0.158
1640	5024.82	-	-	-	3.560	-	0.158
1641	5024.79	-	-	-	3.560	-	0.159
1642	5024.76	-	-	-	3.560	-	0.158
1643	5024.73	-	-	-	3.570	-	0.160
1644	5024.70	-	-	-	3.570	-	0.161
1645	5024.67	-	-	-	3.570	-	0.159
1646	5024.63	-	-	-	3.350	-	0.151
1647	5024.60	-	-	-	3.350	-	0.151
1648	5024.57	-	-	-	3.350	-	0.151
1649	5024.54	-	-	-	3.350	-	0.151
1650	5024.51	-	-	-	3.280	-	0.149
1651	5024.48	-	-	-	3.290	-	0.150
1652	5024.45	-	-	-	3.290	-	0.149
1653	5024.42	-	-	-	3.290	-	0.149
1654	5024.39	-	-	-	3.290	-	0.150
1655	5024.36	-	-	-	3.290	-	0.150
1656	5024.34	-	-	-	3.290	-	0.149
1657	5024.31	-	-	-	3.300	-	0.150
1658	5024.28	-	-	-	3.300	-	0.150
1659	5024.25	-	-	-	3.300	-	0.149
1660	5024.22	-	-	-	3.170	-	0.145
1661	5024.19	-	-	-	3.170	-	0.145
1662	5024.16	-	-	-	3.170	-	0.145
1663	5024.13	-	-	-	3.170	-	0.147
1664	5024.10	-	-	-	3.170	-	0.147
1665	5024.07	-	-	-	3.180	-	0.146
1666	5024.04	-	-	-	3.180	-	0.123
1667	5024.01	-	-	-	3.180	-	0.122
1668	5023.98	-	-	-	3.030	-	0.118
1669	5023.95	-	-	-	3.040	-	0.117
1670	5023.92	-	-	-	3.040	-	0.117
1671	5023.90	-	-	-	3.040	-	0.118
1672	5023.87	-	-	-	3.040	-	0.118
1673	5023.84	-	-	-	3.040	-	0.118
1674	5023.81	-	-	-	3.050	-	0.118
1675	5023.78	-	-	-	2.960	-	0.116
1676	5023.75	-	-	-	2.960	-	0.116
1677	5023.72	-	-	-	2.960	-	0.116
1678	5023.69	-	-	-	2.960	-	0.115
1679	5023.67	-	-	-	2.960	-	0.115
1680	5023.64	-	-	-	2.960	-	0.116
1681	5023.61	-	-	-	2.900	-	0.114
1682	5023.58	-	-	-	2.900	-	0.114
1683	5023.55	-	-	-	2.900	-	0.113

Continued on next page

Table 14 – continued from previous page - IEEE8500 - n3637

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
1684	5023.52	-	-	-	2.900	-	0.113
1685	5023.50	-	-	-	2.910	-	0.113
1686	5023.47	-	-	-	2.910	-	0.113
1687	5023.44	-	-	-	2.910	-	0.113
1688	5023.41	-	-	-	2.960	-	0.113
1689	5023.39	-	-	-	2.960	-	0.113
1690	5023.36	-	-	-	2.960	-	0.114
1691	5023.33	-	-	-	2.960	-	0.113
1692	5023.30	-	-	-	2.960	-	0.113
1693	5023.27	-	-	-	2.880	-	0.111
1694	5023.25	-	-	-	2.890	-	0.111
1695	5023.22	-	-	-	2.890	-	0.111
1696	5023.19	-	-	-	2.810	-	0.108
1697	5023.16	-	-	-	2.820	-	0.110
1698	5023.14	-	-	-	2.740	-	0.107
1699	5023.11	-	-	-	2.740	-	0.106
1700	5023.08	-	-	-	2.700	-	0.106
1701	5023.06	-	-	-	2.700	-	0.107
1702	5023.03	-	-	-	2.700	-	0.107
1703	5023.00	-	-	-	2.710	-	0.107
1704	5022.97	-	-	-	2.710	-	0.107
1705	5022.95	-	-	-	2.710	-	0.107
1706	5022.92	-	-	-	2.710	-	0.107
1707	5022.89	-	-	-	2.710	-	0.107
1708	5022.87	-	-	-	2.720	-	0.107
1709	5022.84	-	-	-	2.720	-	0.107
1710	5022.81	-	-	-	2.720	-	0.107
1711	5022.79	-	-	-	2.720	-	0.107
1712	5022.76	-	-	-	2.720	-	0.108
1713	5022.73	-	-	-	2.720	-	0.108
1714	5022.71	-	-	-	2.730	-	0.108
1715	5022.68	-	-	-	2.730	-	0.108
1716	5022.65	-	-	-	2.730	-	0.108
1717	5022.63	-	-	-	2.730	-	0.108
1718	5022.60	-	-	-	2.730	-	0.108
1719	5022.57	-	-	-	2.730	-	0.108
1720	5022.55	-	-	-	2.740	-	0.107
1721	5022.52	-	-	-	2.740	-	0.108
1722	5022.50	-	-	-	2.780	-	0.108
1723	5022.47	-	-	-	2.780	-	0.107
1724	5022.44	-	-	-	2.750	-	0.108
1725	5022.42	-	-	-	2.750	-	0.109
1726	5022.39	-	-	-	2.740	-	0.108
1727	5022.37	-	-	-	2.750	-	0.108
1728	5022.34	-	-	-	2.750	-	0.107
1729	5022.31	-	-	-	2.750	-	0.107
1730	5022.29	-	-	-	2.680	-	0.105
1731	5022.26	-	-	-	2.680	-	0.104
1732	5022.24	-	-	-	2.690	-	0.104
1733	5022.21	-	-	-	2.690	-	0.104
1734	5022.19	-	-	-	2.690	-	0.104
1735	5022.16	-	-	-	2.690	-	0.104

Continued on next page

Table 14 – continued from previous page - IEEE8500 - n3637

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
1736	5022.14	-	-	-	2.690	-	0.104
1737	5022.11	-	-	-	2.690	-	0.105
1738	5022.08	-	-	-	2.690	-	0.105
1739	5022.06	-	-	-	2.620	-	0.103
1740	5022.03	-	-	-	2.620	-	0.103
1741	5022.01	-	-	-	2.620	-	0.103
1742	5021.98	-	-	-	2.630	-	0.103
1743	5021.96	-	-	-	2.630	-	0.102
1744	5021.93	-	-	-	2.540	-	0.100
1745	5021.91	-	-	-	2.540	-	0.100
1746	5021.88	-	-	-	2.550	-	0.102
1747	5021.86	-	-	-	2.550	-	0.101
1748	5021.83	-	-	-	2.550	-	0.101
1749	5021.81	-	-	-	2.550	-	0.102
1750	5021.78	-	-	-	2.550	-	0.101
1751	5021.76	-	-	-	2.550	-	0.102
1752	5021.74	-	-	-	2.560	-	0.102
1753	5021.71	-	-	-	2.560	-	0.101
1754	5021.69	-	-	-	2.600	-	0.102
1755	5021.66	-	-	-	2.600	-	0.102
1756	5021.64	-	-	-	2.600	-	0.101
1757	5021.62	-	-	-	2.600	-	0.102
1758	5021.59	-	-	-	2.600	-	0.101
1759	5021.57	-	-	-	2.600	-	0.101
1760	5021.54	-	-	-	2.600	-	0.101
1761	5021.52	-	-	-	2.610	-	0.101
1762	5021.50	-	-	-	2.610	-	0.101
1763	5021.47	-	-	-	2.610	-	0.101
1764	5021.45	-	-	-	2.610	-	0.101
1765	5021.42	-	-	-	2.610	-	0.102
1766	5021.40	-	-	-	2.610	-	0.102
1767	5021.38	-	-	-	2.620	-	0.102
1768	5021.35	-	-	-	2.620	-	0.101
1769	5021.33	-	-	-	2.620	-	0.101
1770	5021.31	-	-	-	2.620	-	0.101
1771	5021.28	-	-	-	2.630	-	0.101
1772	5021.26	-	-	-	2.620	-	0.101
1773	5021.24	-	-	-	2.630	-	0.101
1774	5021.21	-	-	-	2.630	-	0.102
1775	5021.19	-	-	-	2.630	-	0.102
1776	5021.17	-	-	-	2.630	-	0.102
1777	5021.14	-	-	-	2.630	-	0.102
1778	5021.12	-	-	-	2.630	-	0.102
1779	5021.10	-	-	-	2.630	-	0.101
1780	5021.07	-	-	-	2.640	-	0.101
1781	5021.05	-	-	-	2.640	-	0.101
1782	5021.03	-	-	-	2.640	-	0.101
1783	5021.00	-	-	-	2.640	-	0.101
1784	5020.98	-	-	-	2.640	-	0.101
1785	5020.96	-	-	-	2.640	-	0.101
1786	5020.94	-	-	-	2.650	-	0.101
1787	5020.91	-	-	-	2.650	-	0.101

Continued on next page

Table 14 – continued from previous page - IEEE8500 - n3637

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
1788	5020.89	-	-	-	2.650	-	0.101
1789	5020.87	-	-	-	2.650	-	0.101
1790	5020.84	-	-	-	2.650	-	0.101
1791	5020.82	-	-	-	2.650	-	0.101
1792	5020.80	-	-	-	2.660	-	0.101
1793	5020.78	-	-	-	2.660	-	0.081
1794	5020.75	-	-	-	2.660	-	0.081
1795	5020.73	-	-	-	2.660	-	0.081
1796	5020.71	-	-	-	2.660	-	0.080
1797	5020.69	-	-	-	2.660	-	0.081
1798	5020.66	-	-	-	2.660	-	0.080
1799	5020.64	-	-	-	2.670	-	0.080
1800	5020.62	-	-	-	2.670	-	0.081
1801	5020.60	-	-	-	2.670	-	0.081
1802	5020.58	-	-	-	2.670	-	0.081
1803	5020.55	-	-	-	2.670	-	0.081
1804	5020.53	-	-	-	2.670	-	0.081
1805	5020.51	-	-	-	2.680	-	0.081
1806	5020.49	-	-	-	2.680	-	0.081
1807	5020.47	-	-	-	2.680	-	0.081
1808	5020.44	-	-	-	2.680	-	0.081
1809	5020.42	-	-	-	2.680	-	0.081
1810	5020.40	-	-	-	2.690	-	0.081
1811	5020.38	-	-	-	2.690	-	0.081
1812	5020.36	-	-	-	2.690	-	0.081
1813	5020.34	-	-	-	2.690	-	0.081
1814	5020.31	-	-	-	2.690	-	0.081
1815	5020.29	-	-	-	2.690	-	0.081
1816	5020.27	-	-	-	2.690	-	0.081
1817	5020.25	-	-	-	2.690	-	0.081
1818	5020.23	-	-	-	2.700	-	0.081
1819	5020.21	-	-	-	2.700	-	0.080
1820	5020.19	-	-	-	2.700	-	0.080
1821	5020.17	-	-	-	2.700	-	0.080
1822	5020.15	-	-	-	2.710	-	0.080
1823	5020.13	-	-	-	2.710	-	0.080
1824	5020.10	-	-	-	2.710	-	0.080
1825	5020.08	-	-	-	2.710	-	0.081
1826	5020.06	-	-	-	2.710	-	0.081
1827	5020.04	-	-	-	2.710	-	0.080
1828	5020.02	-	-	-	2.710	-	0.080
1829	5020.00	-	-	-	2.710	-	0.080
1830	5019.98	-	-	-	2.710	-	0.080
1831	5019.96	-	-	-	2.720	-	0.080
1832	5019.94	-	-	-	2.720	-	0.080
1833	5019.92	-	-	-	2.720	-	0.079
1834	5019.90	-	-	-	2.720	-	0.080
1835	5019.88	-	-	-	2.720	-	0.080
1836	5019.86	-	-	-	2.720	-	0.080
1837	5019.84	-	-	-	2.730	-	0.081
1838	5019.82	-	-	-	2.730	-	0.080
1839	5019.80	-	-	-	2.730	-	0.080

Continued on next page

Table 14 – continued from previous page - IEEE8500 - n3637

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
1840	5019.78	-	-	-	2.730	-	0.080
1841	5019.76	-	-	-	2.730	-	0.080
1842	5019.74	-	-	-	2.730	-	0.080
1843	5019.72	-	-	-	2.740	-	0.081
1844	5019.71	-	-	-	2.740	-	0.080
1845	5019.69	-	-	-	2.740	-	0.080
1846	5019.67	-	-	-	2.740	-	0.080
1847	5019.65	-	-	-	2.740	-	0.080
1848	5019.63	-	-	-	2.740	-	0.080
1849	5019.61	-	-	-	2.750	-	0.080
1850	5019.59	-	-	-	2.750	-	0.078
1851	5019.57	-	-	-	2.750	-	0.078
1852	5019.55	-	-	-	2.750	-	0.078
1853	5019.53	-	-	-	2.750	-	0.078
1854	5019.51	-	-	-	2.750	-	0.078
1855	5019.49	-	-	-	2.760	-	0.078
1856	5019.48	-	-	-	2.750	-	0.078
1857	5019.46	-	-	-	2.760	-	0.078
1858	5019.44	-	-	-	2.760	-	0.078
1859	5019.42	-	-	-	2.760	-	0.078
1860	5019.40	-	-	-	2.760	-	0.078
1861	5019.38	-	-	-	2.770	-	0.078
1862	5019.36	-	-	-	2.770	-	0.078
1863	5019.34	-	-	-	2.770	-	0.078
1864	5019.33	-	-	-	2.770	-	0.078
1865	5019.31	-	-	-	2.770	-	0.078
1866	5019.29	-	-	-	2.770	-	0.078
1867	5019.27	-	-	-	2.770	-	0.078
1868	5019.25	-	-	-	2.780	-	0.078
1869	5019.24	-	-	-	2.780	-	0.078
1870	5019.22	-	-	-	2.780	-	0.078
1871	5019.20	-	-	-	2.780	-	0.078
1872	5019.18	-	-	-	2.780	-	0.078
1873	5019.16	-	-	-	2.790	-	0.078
1874	5019.15	-	-	-	2.790	-	0.078
1875	5019.13	-	-	-	2.790	-	0.078
1876	5019.11	-	-	-	2.790	-	0.078
1877	5019.09	-	-	-	2.790	-	0.078
1878	5019.08	-	-	-	2.790	-	0.078
1879	5019.06	-	-	-	2.800	-	0.078
1880	5019.04	-	-	-	2.800	-	0.078
1881	5019.02	-	-	-	2.800	-	0.078
1882	5019.01	-	-	-	2.800	-	0.078
1883	5018.99	-	-	-	2.800	-	0.077
1884	5018.97	-	-	-	2.800	-	0.078
1885	5018.96	-	-	-	2.800	-	0.077
1886	5018.94	-	-	-	2.810	-	0.078
1887	5018.92	-	-	-	2.810	-	0.078
1888	5018.91	-	-	-	2.810	-	0.078
1889	5018.89	-	-	-	2.810	-	0.078
1890	5018.87	-	-	-	2.810	-	0.078
1891	5018.85	-	-	-	2.810	-	0.078

Continued on next page

Table 14 – continued from previous page - IEEE8500 - n3637

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
1892	5018.84	-	-	-	2.810	-	0.078
1893	5018.82	-	-	-	2.820	-	0.078
1894	5018.80	-	-	-	2.820	-	0.079
1895	5018.79	-	-	-	2.820	-	0.078
1896	5018.77	-	-	-	2.820	-	0.080
1897	5018.76	-	-	-	2.830	-	0.078
1898	5018.74	-	-	-	2.830	-	0.078
1899	5018.72	-	-	-	2.830	-	0.078
1900	5018.71	-	-	-	2.830	-	0.078
1901	5018.69	-	-	-	2.830	-	0.078
1902	5018.67	-	-	-	2.830	-	0.078
1903	5018.66	-	-	-	2.830	-	0.078
1904	5018.64	-	-	-	2.840	-	0.078
1905	5018.63	-	-	-	2.840	-	0.078
1906	5018.61	-	-	-	2.840	-	0.078
1907	5018.59	-	-	-	2.850	-	0.078
1908	5018.58	-	-	-	2.840	-	0.079
1909	5018.56	-	-	-	2.850	-	0.078
1910	5018.55	-	-	-	2.850	-	0.078
1911	5018.53	-	-	-	2.850	-	0.077
1912	5018.52	-	-	-	2.850	-	0.077
1913	5018.50	-	-	-	2.850	-	0.078
1914	5018.49	-	-	-	2.850	-	0.078
1915	5018.47	-	-	-	2.860	-	0.078
1916	5018.45	-	-	-	2.860	-	0.078
1917	5018.44	-	-	-	2.860	-	0.077
1918	5018.42	-	-	-	2.860	-	0.078
1919	5018.41	-	-	-	2.860	-	0.078
1920	5018.39	-	-	-	2.860	-	0.078
1921	5018.38	-	-	-	2.780	-	0.076
1922	5018.36	-	-	-	2.780	-	0.075
1923	5018.35	-	-	-	2.790	-	0.075
1924	5018.33	-	-	-	2.790	-	0.075
1925	5018.31	-	-	-	2.790	-	0.075
1926	5018.30	-	-	-	2.700	-	0.073
1927	5018.28	-	-	-	2.700	-	0.073
1928	5018.27	-	-	-	2.710	-	0.073
1929	5018.25	-	-	-	2.700	-	0.073
1930	5018.24	-	-	-	2.710	-	0.073
1931	5018.22	-	-	-	2.710	-	0.073
1932	5018.21	-	-	-	2.710	-	0.073
1933	5018.19	-	-	-	2.710	-	0.073
1934	5018.18	-	-	-	2.710	-	0.073
1935	5018.16	-	-	-	2.710	-	0.072
1936	5018.15	-	-	-	2.710	-	0.072
1937	5018.13	-	-	-	2.710	-	0.072
1938	5018.12	-	-	-	2.650	-	0.071
1939	5018.10	-	-	-	2.650	-	0.071
1940	5018.09	-	-	-	2.580	-	0.069
1941	5018.07	-	-	-	2.590	-	0.069
1942	5018.06	-	-	-	2.590	-	0.069
1943	5018.04	-	-	-	2.590	-	0.070

Continued on next page

Table 14 – continued from previous page - IEEE8500 - n3637

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
1944	5018.03	-	-	-	2.590	-	0.070
1945	5018.01	-	-	-	2.590	-	0.070
1946	5018.00	-	-	-	2.590	-	0.070
1947	5017.99	-	-	-	2.520	-	0.068
1948	5017.97	-	-	-	2.480	-	0.068
1949	5017.96	-	-	-	2.400	-	0.113
1950	5017.94	-	-	-	2.400	-	0.113
1951	5017.93	-	-	-	2.410	-	0.113
1952	5017.91	-	-	-	2.400	-	0.113
1953	5017.90	-	-	-	2.410	-	0.113
1954	5017.89	-	-	-	2.410	-	0.113
1955	5017.87	-	-	-	2.410	-	0.112
1956	5017.86	-	-	-	2.410	-	0.113
1957	5017.84	-	-	-	2.410	-	0.112
1958	5017.83	-	-	-	2.410	-	0.112
1959	5017.82	-	-	-	2.340	-	0.064
1960	5017.80	-	-	-	2.340	-	0.064
1961	5017.79	-	-	-	2.340	-	0.064
1962	5017.77	-	-	-	2.340	-	0.064
1963	5017.76	-	-	-	2.340	-	0.064
1964	5017.75	-	-	-	2.340	-	0.064
1965	5017.73	-	-	-	2.350	-	0.064
1966	5017.72	-	-	-	2.350	-	0.064
1967	5017.71	-	-	-	2.350	-	0.064
1968	5017.69	-	-	-	2.350	-	0.063
1969	5017.68	-	-	-	2.350	-	0.063
1970	5017.66	-	-	-	2.350	-	0.065
1971	5017.65	-	-	-	2.350	-	0.108
1972	5017.64	-	-	-	2.350	-	0.107
1973	5017.62	-	-	-	2.290	-	0.105
1974	5017.61	-	-	-	2.290	-	0.104
1975	5017.60	-	-	-	2.290	-	0.104
1976	5017.58	-	-	-	2.300	-	0.104
1977	5017.57	-	-	-	2.290	-	0.104
1978	5017.56	-	-	-	2.290	-	0.105
1979	5017.54	-	-	-	2.300	-	0.105
1980	5017.53	-	-	-	2.300	-	0.107
1981	5017.52	-	-	-	2.300	-	0.106
1982	5017.50	-	-	-	2.300	-	0.106
1983	5017.49	-	-	-	2.300	-	0.105
1984	5017.48	-	-	-	2.300	-	0.105
1985	5017.46	-	-	-	2.300	-	0.105
1986	5017.45	-	-	-	2.310	-	0.105
1987	5017.44	-	-	-	2.250	-	0.103
1988	5017.43	-	-	-	2.250	-	0.103
1989	5017.41	-	-	-	2.260	-	0.103
1990	5017.40	-	-	-	2.260	-	0.103
1991	5017.39	-	-	-	2.260	-	0.103
1992	5017.37	-	-	-	2.200	-	0.102
1993	5017.36	-	-	-	2.200	-	0.130
1994	5017.35	-	-	-	2.200	-	0.129
1995	5017.34	-	-	-	2.200	-	0.129

Continued on next page

Table 14 – continued from previous page - IEEE8500 - n3637

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
1996	5017.32	-	-	-	2.200	-	0.129
1997	5017.31	-	-	-	2.200	-	0.129
1998	5017.30	-	-	-	2.210	-	0.129
1999	5017.29	-	-	-	2.210	-	0.129
2000	5017.28	-	-	-	2.210	-	0.129
2001	5017.26	-	-	-	2.140	-	0.095
2002	5017.25	-	-	-	2.140	-	0.095
2003	5017.24	-	-	-	2.140	-	0.095
2004	5017.23	-	-	-	2.140	-	0.095
2005	5017.22	-	-	-	2.140	-	0.095
2006	5017.20	-	-	-	2.140	-	0.095
2007	5017.19	-	-	-	2.140	-	0.095
2008	5017.18	-	-	-	2.140	-	0.095
2009	5017.17	-	-	-	2.150	-	0.095
2010	5017.16	-	-	-	2.150	-	0.095
2011	5017.14	-	-	-	2.150	-	0.095
2012	5017.13	-	-	-	2.150	-	0.095
2013	5017.12	-	-	-	2.150	-	0.095
2014	5017.11	-	-	-	2.150	-	0.095
2015	5017.10	-	-	-	2.150	-	0.095
2016	5017.09	-	-	-	2.150	-	0.096
2017	5017.08	-	-	-	2.150	-	0.096
2018	5017.07	-	-	-	2.150	-	0.096
2019	5017.05	-	-	-	2.150	-	0.096
2020	5017.04	-	-	-	2.150	-	0.127
2021	5017.03	-	-	-	2.090	-	0.125
2022	5017.02	-	-	-	2.090	-	0.125
2023	5017.01	-	-	-	2.090	-	0.125
2024	5017.00	-	-	-	2.090	-	0.125
2025	5016.99	-	-	-	2.100	-	0.125
2026	5016.98	-	-	-	2.090	-	0.155
2027	5016.97	-	-	-	2.040	-	0.153
2028	5016.96	-	-	-	2.040	-	0.153
2029	5016.95	-	-	-	1.980	-	0.152
2030	5016.94	-	-	-	1.980	-	0.152
2031	5016.92	-	-	-	1.920	-	0.150
2032	5016.91	-	-	-	1.920	-	0.150
2033	5016.90	-	-	-	1.860	-	0.116
2034	5016.89	-	-	-	1.860	-	0.116
2035	5016.88	-	-	-	1.870	-	0.116
2036	5016.87	-	-	-	1.870	-	0.116
2037	5016.86	-	-	-	1.870	-	0.116
2038	5016.85	-	-	-	1.870	-	0.116
2039	5016.84	-	-	-	1.870	-	0.116
2040	5016.83	-	-	-	1.870	-	0.116
2041	5016.82	-	-	-	1.870	-	0.116
2042	5016.81	-	-	-	1.870	-	0.116
2043	5016.80	-	-	-	1.870	-	0.116
2044	5016.79	-	-	-	1.870	-	0.116
2045	5016.78	-	-	-	1.870	-	0.116
2046	5016.77	-	-	-	1.870	-	0.116
2047	5016.76	-	-	-	1.910	-	0.116

Continued on next page

Table 14 – continued from previous page - IEEE8500 - n3637

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
2048	5016.75	-	-	-	1.910	-	0.116
2049	5016.74	-	-	-	1.910	-	0.117
2050	5016.73	-	-	-	1.910	-	0.117
2051	5016.72	-	-	-	1.920	-	0.116
2052	5016.71	-	-	-	1.920	-	0.118
2053	5016.70	-	-	-	1.910	-	0.118
2054	5016.70	-	-	-	1.910	-	0.117
2055	5016.69	-	-	-	1.910	-	0.117
2056	5016.68	-	-	-	1.920	-	0.117
2057	5016.67	-	-	-	1.910	-	0.117
2058	5016.66	-	-	-	1.920	-	0.118
2059	5016.65	-	-	-	1.920	-	0.118
2060	5016.64	-	-	-	1.920	-	0.117
2061	5016.63	-	-	-	1.920	-	0.117
2062	5016.62	-	-	-	1.890	-	0.117
2063	5016.61	-	-	-	1.890	-	0.117
2064	5016.60	-	-	-	1.890	-	0.117
2065	5016.59	-	-	-	1.890	-	0.118
2066	5016.59	-	-	-	1.890	-	0.119
2067	5016.58	-	-	-	1.900	-	0.118
2068	5016.57	-	-	-	1.900	-	0.117
2069	5016.56	-	-	-	1.900	-	0.117
2070	5016.55	-	-	-	1.900	-	0.117
2071	5016.54	-	-	-	1.830	-	0.116
2072	5016.53	-	-	-	1.830	-	0.115
2073	5016.52	-	-	-	1.830	-	0.115
2074	5016.52	-	-	-	1.830	-	0.116
2075	5016.51	-	-	-	1.780	-	0.114
2076	5016.50	-	-	-	1.780	-	0.114
2077	5016.49	-	-	-	1.790	-	0.114
2078	5016.48	-	-	-	1.770	-	0.113
2079	5016.48	-	-	-	1.720	-	0.081
2080	5016.47	-	-	-	1.720	-	0.080
2081	5016.46	-	-	-	1.720	-	0.080
2082	5016.45	-	-	-	1.720	-	0.080
2083	5016.45	-	-	-	1.720	-	0.080
2084	5016.44	-	-	-	1.720	-	0.080
2085	5016.43	-	-	-	1.720	-	0.080
2086	5016.42	-	-	-	1.720	-	0.083
2087	5016.41	-	-	-	1.720	-	0.082
2088	5016.41	-	-	-	1.720	-	0.082
2089	5016.40	-	-	-	1.660	-	0.083
2090	5016.39	-	-	-	1.660	-	0.093
2091	5016.38	-	-	-	1.660	-	0.091
2092	5016.38	-	-	-	1.670	-	0.104
2093	5016.37	-	-	-	1.610	-	0.054
2094	5016.36	-	-	-	1.610	-	0.052
2095	5016.35	-	-	-	1.610	-	0.051
2096	5016.34	-	-	-	1.610	-	0.050
2097	5016.34	-	-	-	1.610	-	0.048
2098	5016.33	-	-	-	1.610	-	0.048
2099	5016.32	-	-	-	1.610	-	0.048

Continued on next page

Table 14 – continued from previous page - IEEE8500 - n3637

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
2100	5016.31	-	-	-	1.610	-	0.049
2101	5016.31	-	-	-	1.610	-	0.048
2102	5016.30	-	-	-	1.550	-	0.046
2103	5016.29	-	-	-	1.550	-	0.046
2104	5016.28	-	-	-	1.500	-	0.044
2105	5016.28	-	-	-	1.500	-	0.045
2106	5016.27	-	-	-	1.500	-	0.044
2107	5016.26	-	-	-	1.460	-	0.042
2108	5016.25	-	-	-	1.460	-	0.039
2109	5016.25	-	-	-	1.410	-	0.036
2110	5016.24	-	-	-	1.420	-	0.035
2111	5016.23	-	-	-	1.370	-	0.033
2112	5016.22	-	-	-	1.370	-	0.033
2113	5016.22	-	-	-	1.320	-	0.031
2114	5016.21	-	-	-	1.320	-	0.031
2115	5016.20	-	-	-	1.320	-	0.031
2116	5016.19	-	-	-	1.320	-	0.031
2117	5016.19	-	-	-	1.320	-	0.031
2118	5016.18	-	-	-	1.320	-	0.031
2119	5016.17	-	-	-	1.320	-	0.031
2120	5016.16	-	-	-	1.320	-	0.030
2121	5016.16	-	-	-	1.320	-	0.031
2122	5016.15	-	-	-	1.320	-	0.033
2123	5016.14	-	-	-	1.320	-	0.032
2124	5016.13	-	-	-	1.320	-	0.032
2125	5016.13	-	-	-	1.320	-	0.031
2126	5016.12	-	-	-	1.320	-	0.031
2127	5016.11	-	-	-	1.320	-	0.031
2128	5016.11	-	-	-	1.320	-	0.060
2129	5016.10	-	-	-	1.330	-	0.059
2130	5016.09	-	-	-	1.340	-	0.059
2131	5016.09	-	-	-	1.330	-	0.059
2132	5016.08	-	-	-	1.330	-	0.059
2133	5016.07	-	-	-	1.330	-	0.061
2134	5016.07	-	-	-	1.340	-	0.069
2135	5016.06	-	-	-	1.330	-	0.069
2136	5016.05	-	-	-	1.330	-	0.094
2137	5016.05	-	-	-	1.330	-	0.094
2138	5016.04	-	-	-	1.330	-	0.093
2139	5016.03	-	-	-	1.340	-	0.092
2140	5016.03	-	-	-	1.330	-	0.094
2141	5016.02	-	-	-	1.330	-	0.094
2142	5016.01	-	-	-	1.330	-	0.094
2143	5016.01	-	-	-	1.340	-	0.093
2144	5016.00	-	-	-	1.340	-	0.094
2145	5015.99	-	-	-	1.340	-	0.084
2146	5015.99	-	-	-	1.340	-	0.098
2147	5015.98	-	-	-	1.340	-	0.098
2148	5015.97	-	-	-	1.340	-	0.100
2149	5015.97	-	-	-	1.340	-	0.098
2150	5015.96	-	-	-	1.340	-	0.098
2151	5015.95	-	-	-	1.340	-	0.098

Continued on next page

Table 14 – continued from previous page - IEEE8500 - n3637

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
2152	5015.95	-	-	-	1.340	-	0.097
2153	5015.94	-	-	-	1.340	-	0.098
2154	5015.94	-	-	-	1.340	-	0.100
2155	5015.93	-	-	-	1.340	-	0.098
2156	5015.92	-	-	-	1.340	-	0.113
2157	5015.92	-	-	-	1.340	-	0.113
2158	5015.91	-	-	-	1.340	-	0.113
2159	5015.91	-	-	-	1.340	-	0.116
2160	5015.90	-	-	-	1.340	-	0.114
2161	5015.90	-	-	-	1.350	-	0.114
2162	5015.89	-	-	-	1.350	-	0.113
2163	5015.89	-	-	-	1.350	-	0.113
2164	5015.89	-	-	-	1.350	-	0.115
2165	5015.88	-	-	-	1.350	-	0.115
2166	5015.88	-	-	-	1.350	-	0.114
2167	5015.87	-	-	-	1.350	-	0.119
2168	5015.87	-	-	-	1.350	-	0.114
2169	5015.86	-	-	-	1.350	-	0.114
2170	5015.86	-	-	-	1.350	-	0.116
2171	5015.85	-	-	-	1.350	-	0.114
2172	5015.85	-	-	-	1.350	-	0.114
2173	5015.84	-	-	-	1.350	-	0.113
2174	5015.84	-	-	-	1.350	-	0.114
2175	5015.83	-	-	-	1.350	-	0.116
2176	5015.83	-	-	-	1.360	-	0.115
2177	5015.82	-	-	-	1.350	-	0.115
2178	5015.82	-	-	-	1.350	-	0.116
2179	5015.82	-	-	-	1.360	-	0.115
2180	5015.81	-	-	-	1.360	-	0.118
2181	5015.81	-	-	-	1.360	-	0.117
2182	5015.80	-	-	-	1.360	-	0.119
2183	5015.80	-	-	-	1.360	-	0.119
2184	5015.79	-	-	-	1.360	-	0.116
2185	5015.79	-	-	-	1.360	-	0.118
2186	5015.78	-	-	-	1.360	-	0.116
2187	5015.78	-	-	-	1.360	-	0.118
2188	5015.77	-	-	-	1.360	-	0.117
2189	5015.77	-	-	-	1.360	-	0.116
2190	5015.77	-	-	-	1.360	-	0.118
2191	5015.76	-	-	-	1.360	-	0.117
2192	5015.76	-	-	-	1.360	-	0.116
2193	5015.75	-	-	-	1.360	-	0.116
2194	5015.75	-	-	-	1.370	-	0.116
2195	5015.74	-	-	-	1.370	-	0.118
2196	5015.74	-	-	-	1.370	-	0.117
2197	5015.73	-	-	-	1.370	-	0.117
2198	5015.73	-	-	-	1.370	-	0.119
2199	5015.73	-	-	-	1.370	-	0.117
2200	5015.72	-	-	-	1.370	-	0.118
2201	5015.72	-	-	-	1.370	-	0.117
2202	5015.71	-	-	-	1.370	-	0.117
2203	5015.71	-	-	-	1.370	-	0.116

Continued on next page

Table 14 – continued from previous page - IEEE8500 - n3637

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
2204	5015.70	-	-	-	1.370	-	0.116
2205	5015.70	-	-	-	1.370	-	0.116
2206	5015.70	-	-	-	1.370	-	0.118
2207	5015.69	-	-	-	1.370	-	0.116
2208	5015.69	-	-	-	1.370	-	0.116
2209	5015.68	-	-	-	1.280	-	0.114
2210	5015.68	-	-	-	1.280	-	0.114
2211	5015.68	-	-	-	1.230	-	0.115
2212	5015.67	-	-	-	1.230	-	0.115
2213	5015.67	-	-	-	1.230	-	0.113
2214	5015.66	-	-	-	1.230	-	0.113
2215	5015.66	-	-	-	1.230	-	0.114
2216	5015.66	-	-	-	1.250	-	0.116
2217	5015.65	-	-	-	1.250	-	0.113
2218	5015.65	-	-	-	1.250	-	0.113
2219	5015.65	-	-	-	1.250	-	0.113
2220	5015.65	-	-	-	1.240	-	0.113
2221	5015.64	-	-	-	1.240	-	0.115
2222	5015.64	-	-	-	1.240	-	0.114
2223	5015.64	-	-	-	1.240	-	0.113
2224	5015.63	-	-	-	1.240	-	0.113
2225	5015.63	-	-	-	1.240	-	0.113
2226	5015.63	-	-	-	1.190	-	0.112
2227	5015.63	-	-	-	1.190	-	0.115
2228	5015.62	-	-	-	1.190	-	0.112
2229	5015.62	-	-	-	1.190	-	0.112
2230	5015.62	-	-	-	1.190	-	0.114
2231	5015.62	-	-	-	1.190	-	0.113
2232	5015.62	-	-	-	1.190	-	0.115
2233	5015.62	-	-	-	1.190	-	0.112
2234	5015.62	-	-	-	1.190	-	0.112
2235	5015.61	-	-	-	1.190	-	0.112
2236	5015.61	-	-	-	1.190	-	0.113
2237	5015.61	-	-	-	1.190	-	0.114
2238	5015.61	-	-	-	1.150	-	0.111
2239	5015.61	-	-	-	1.150	-	0.111
2240	5015.61	-	-	-	1.150	-	0.111
2241	5015.61	-	-	-	1.150	-	0.111
2242	5015.61	-	-	-	1.150	-	0.112
2243	5015.61	-	-	-	1.150	-	0.113
2244	5015.61	-	-	-	1.150	-	0.111
2245	5015.61	-	-	-	1.150	-	0.111
2246	5015.61	-	-	-	1.150	-	0.111
2247	5015.60	-	-	-	1.150	-	0.111
2248	5015.60	-	-	-	1.110	-	0.112
2249	5015.60	-	-	-	1.110	-	0.110
2250	5015.60	-	-	-	1.070	-	0.113
2251	5015.60	-	-	-	1.070	-	0.114
2252	5015.60	-	-	-	1.070	-	0.113
2253	5015.60	-	-	-	1.070	-	0.115
2254	5015.60	-	-	-	1.070	-	0.114
2255	5015.60	-	-	-	1.070	-	0.113

Continued on next page

Table 14 – continued from previous page - IEEE8500 - n3637

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
2256	5015.60	-	-	-	1.070	-	0.114
2257	5015.60	-	-	-	1.070	-	0.113
2258	5015.60	-	-	-	1.070	-	0.119
2259	5015.60	-	-	-	1.070	-	0.117
2260	5015.60	-	-	-	1.020	-	0.091
2261	5015.60	-	-	-	1.020	-	0.091
2262	5015.60	-	-	-	1.020	-	0.091
2263	5015.60	-	-	-	1.020	-	0.091
2264	5015.60	-	-	-	0.970	-	0.090
2265	5015.60	-	-	-	0.970	-	0.092
2266	5015.60	-	-	-	0.970	-	0.090
2267	5015.60	-	-	-	0.970	-	0.090
2268	5015.60	-	-	-	0.970	-	0.093
2269	5015.60	-	-	-	0.970	-	0.093
2270	5015.60	-	-	-	0.970	-	0.093
2271	5015.60	-	-	-	0.970	-	0.095
2272	5015.60	-	-	-	0.970	-	0.094
2273	5015.60	-	-	-	0.970	-	0.093
2274	5015.60	-	-	-	0.990	-	0.093
2275	5015.60	-	-	-	0.980	-	0.093
2276	5015.60	-	-	-	0.990	-	0.093
2277	5015.60	-	-	-	0.990	-	0.095
2278	5015.60	-	-	-	0.940	-	0.079
2279	5015.60	-	-	-	0.940	-	0.078
2280	5015.60	-	-	-	0.930	-	0.076
2281	5015.60	-	-	-	0.890	-	0.075
2282	5015.60	-	-	-	0.890	-	0.075
2283	5015.60	-	-	-	0.890	-	0.075
2284	5015.60	-	-	-	0.890	-	0.075
2285	5015.60	-	-	-	0.890	-	0.076
2286	5015.60	-	-	-	0.890	-	0.076
2287	5015.60	-	-	-	0.890	-	0.075
2288	5015.60	-	-	-	0.890	-	0.075
2289	5015.60	-	-	-	0.890	-	0.075
2290	5015.60	-	-	-	0.890	-	0.074
2291	5015.60	-	-	-	0.850	-	0.049
2292	5015.60	-	-	-	0.840	-	0.048
2293	5015.60	-	-	-	0.810	-	0.047
2294	5015.60	-	-	-	0.810	-	0.047
2295	5015.60	-	-	-	0.810	-	0.049
2296	5015.60	-	-	-	0.810	-	0.048
2297	5015.60	-	-	-	0.810	-	0.047
2298	5015.60	-	-	-	0.760	-	0.046
2299	5015.60	-	-	-	0.760	-	0.046
2300	5015.60	-	-	-	0.760	-	0.046
2301	5015.60	-	-	-	0.760	-	0.046
2302	5015.60	-	-	-	0.760	-	0.046
2303	5015.60	-	-	-	0.760	-	0.046
2304	5015.60	-	-	-	0.760	-	0.046
2305	5015.60	-	-	-	0.760	-	0.046
2306	5015.60	-	-	-	0.760	-	0.046
2307	5015.60	-	-	-	0.760	-	0.046

Continued on next page

Table 14 – continued from previous page - IEEE8500 - n3637

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
2308	5015.60	-	-	-	0.760	-	0.048
2309	5015.60	-	-	-	0.720	-	0.019
2310	5015.60	-	-	-	0.720	-	0.018
2311	5015.60	-	-	-	0.720	-	0.018
2312	5015.60	-	-	-	0.720	-	0.017
2313	5015.60	-	-	-	0.680	-	0.016
2314	5015.60	-	-	-	0.680	-	0.016
2315	5015.60	-	-	-	0.680	-	0.016
2316	5015.60	-	-	-	0.680	-	0.016
2317	5015.60	-	-	-	0.680	-	0.016
2318	5015.60	-	-	-	0.680	-	0.016
2319	5015.60	-	-	-	0.680	-	0.016
2320	5015.60	-	-	-	0.650	-	0.015
2321	5015.60	-	-	-	0.650	-	0.016
2322	5015.60	-	-	-	0.650	-	0.015
2323	5015.60	-	-	-	0.650	-	0.015
2324	5015.60	-	-	-	0.650	-	0.015
2325	5015.60	-	-	-	0.650	-	0.015
2326	5015.60	-	-	-	0.650	-	0.015
2327	5015.60	-	-	-	0.610	-	0.015
2328	5015.60	-	-	-	0.610	-	0.015
2329	5015.60	-	-	-	0.610	-	0.014
2330	5015.60	-	-	-	0.610	-	0.014
2331	5015.60	-	-	-	0.610	-	0.014
2332	5015.60	-	-	-	0.580	-	0.014
2333	5015.60	-	-	-	0.580	-	0.014
2334	5015.60	-	-	-	0.540	-	0.013
2335	5015.60	-	-	-	0.540	-	0.013
2336	5015.60	-	-	-	0.540	-	0.013
2337	5015.60	-	-	-	0.540	-	0.013
2338	5015.60	-	-	-	0.540	-	0.013
2339	5015.60	-	-	-	0.540	-	0.013
2340	5015.60	-	-	-	0.510	-	0.012
2341	5015.60	-	-	-	0.510	-	0.012
2342	5015.60	-	-	-	0.510	-	0.012
2343	5015.60	-	-	-	0.500	-	0.012
2344	5015.60	-	-	-	0.500	-	0.012
2345	5015.60	-	-	-	0.500	-	0.013
2346	5015.60	-	-	-	0.500	-	0.015
2347	5015.60	-	-	-	0.500	-	0.014
2348	5015.60	-	-	-	0.500	-	0.013
2349	5015.60	-	-	-	0.500	-	0.013
2350	5015.60	-	-	-	0.500	-	0.013
2351	5015.60	-	-	-	0.500	-	0.012
2352	5015.60	-	-	-	0.500	-	0.012
2353	5015.60	-	-	-	0.500	-	0.012
2354	5015.60	-	-	-	0.500	-	0.012
2355	5015.60	-	-	-	0.500	-	0.012
2356	5015.60	-	-	-	0.500	-	0.012
2357	5015.60	-	-	-	0.500	-	0.012
2358	5015.60	-	-	-	0.500	-	0.017
2359	5015.60	-	-	-	0.500	-	0.017

Continued on next page

Table 14 – continued from previous page - IEEE8500 - n3637

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
2360	5015.60	-	-	-	0.500	-	0.017
2361	5015.60	-	-	-	0.500	-	0.017
2362	5015.60	-	-	-	0.510	-	0.020
2363	5015.60	-	-	-	0.500	-	0.020
2364	5015.60	-	-	-	0.500	-	0.020
2365	5015.60	-	-	-	0.500	-	0.020
2366	5015.60	-	-	-	0.510	-	0.020
2367	5015.60	-	-	-	0.500	-	0.020
2368	5015.60	-	-	-	0.510	-	0.020
2369	5015.60	-	-	-	0.510	-	0.020
2370	5015.60	-	-	-	0.510	-	0.020
2371	5015.60	-	-	-	0.510	-	0.020
2372	5015.60	-	-	-	0.510	-	0.020
2373	5015.60	-	-	-	0.510	-	0.020
2374	5015.60	-	-	-	0.510	-	0.020
2375	5015.60	-	-	-	0.510	-	0.020
2376	5015.60	-	-	-	0.510	-	0.023
2377	5015.60	-	-	-	0.510	-	0.024
2378	5015.60	-	-	-	0.510	-	0.026
2379	5015.60	-	-	-	0.510	-	0.029
2380	5015.60	-	-	-	0.510	-	0.027
2381	5015.60	-	-	-	0.510	-	0.026
2382	5015.60	-	-	-	0.510	-	0.026
2383	5015.60	-	-	-	0.510	-	0.026
2384	5015.60	-	-	-	0.510	-	0.025
2385	5015.60	-	-	-	0.510	-	0.025
2386	5015.60	-	-	-	0.510	-	0.025
2387	5015.60	-	-	-	0.510	-	0.026
2388	5015.60	-	-	-	0.510	-	0.026
2389	5015.60	-	-	-	0.510	-	0.026
2390	5015.60	-	-	-	0.510	-	0.026
2391	5015.60	-	-	-	0.510	-	0.026
2392	5015.60	-	-	-	0.510	-	0.026
2393	5015.60	-	-	-	0.510	-	0.026
2394	5015.60	-	-	-	0.510	-	0.026
2395	5015.60	-	-	-	0.510	-	0.026
2396	5015.60	-	-	-	0.510	-	0.026
2397	5015.60	-	-	-	0.510	-	0.026
2398	5015.60	-	-	-	0.510	-	0.026
2399	5015.60	-	-	-	0.510	-	0.026
2400	5015.60	-	-	-	0.510	-	0.026
2401	5015.60	-	-	-	0.510	-	0.027
2402	5015.60	-	-	-	0.510	-	0.028
2403	5015.60	-	-	-	0.510	-	0.027
2404	5015.60	-	-	-	0.510	-	0.026
2405	5015.60	-	-	-	0.510	-	0.026
2406	5015.60	-	-	-	0.510	-	0.026
2407	5015.60	-	-	-	0.510	-	0.026
2408	5015.60	-	-	-	0.510	-	0.026
2409	5015.60	-	-	-	0.510	-	0.026
2410	5015.60	-	-	-	0.510	-	0.026
2411	5015.60	-	-	-	0.510	-	0.026

Continued on next page

Table 14 – continued from previous page - IEEE8500 - n3637

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
2412	5015.60	-	-	-	0.510	-	0.026
2413	5015.60	-	-	-	0.510	-	0.026
2414	5015.60	-	-	-	0.510	-	0.026
2415	5015.60	-	-	-	0.510	-	0.026
2416	5015.60	-	-	-	0.510	-	0.026
2417	5015.60	-	-	-	0.510	-	0.026
2418	5015.60	-	-	-	0.510	-	0.026
2419	5015.60	-	-	-	0.510	-	0.026
2420	5015.60	-	-	-	0.510	-	0.026
2421	5015.60	-	-	-	0.510	-	0.026
2422	5015.60	-	-	-	0.520	-	0.026
2423	5015.60	-	-	-	0.520	-	0.026
2424	5015.60	-	-	-	0.520	-	0.029
2425	5015.60	-	-	-	0.520	-	0.028
2426	5015.60	-	-	-	0.520	-	0.027
2427	5015.60	-	-	-	0.520	-	0.026
2428	5015.60	-	-	-	0.520	-	0.026
2429	5015.60	-	-	-	0.520	-	0.026
2430	5015.60	-	-	-	0.520	-	0.026
2431	5015.60	-	-	-	0.520	-	0.026
2432	5015.60	-	-	-	0.520	-	0.026
2433	5015.60	-	-	-	0.520	-	0.026
2434	5015.60	-	-	-	0.520	-	0.027
2435	5015.60	-	-	-	0.520	-	0.026
2436	5015.60	-	-	-	0.520	-	0.026
2437	5015.60	-	-	-	0.520	-	0.026
2438	5015.60	-	-	-	0.520	-	0.026
2439	5015.60	-	-	-	0.520	-	0.027
2440	5015.60	-	-	-	0.520	-	0.027
2441	5015.60	-	-	-	0.520	-	0.027
2442	5015.60	-	-	-	0.520	-	0.027
2443	5015.60	-	-	-	0.520	-	0.027
2444	5015.60	-	-	-	0.520	-	0.027
2445	5015.60	-	-	-	0.520	-	0.027
2446	5015.60	-	-	-	0.520	-	0.029
2447	5015.60	-	-	-	0.520	-	0.028
2448	5015.60	-	-	-	0.520	-	0.027
2449	5015.60	-	-	-	0.520	-	0.028
2450	5015.60	-	-	-	0.520	-	0.029
2451	5015.60	-	-	-	0.520	-	0.028
2452	5015.60	-	-	-	0.520	-	0.027
2453	5015.60	-	-	-	0.520	-	0.027
2454	5015.60	-	-	-	0.520	-	0.027
2455	5015.60	-	-	-	0.520	-	0.027
2456	5015.60	-	-	-	0.520	-	0.027
2457	5015.60	-	-	-	0.520	-	0.027
2458	5015.60	-	-	-	0.520	-	0.027
2459	5015.60	-	-	-	0.520	-	0.027
2460	5015.60	-	-	-	0.520	-	0.027
2461	5015.60	-	-	-	0.530	-	0.027
2462	5015.60	-	-	-	0.530	-	0.027
2463	5015.60	-	-	-	0.530	-	0.027

Continued on next page

Table 14 – continued from previous page - IEEE8500 - n3637

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
2464	5015.60	-	-	-	0.530	-	0.027
2465	5015.60	-	-	-	0.530	-	0.027
2466	5015.60	-	-	-	0.530	-	0.027
2467	5015.60	-	-	-	0.530	-	0.028
2468	5015.60	-	-	-	0.530	-	0.030
2469	5015.60	-	-	-	0.530	-	0.028
2470	5015.60	-	-	-	0.520	-	0.028
2471	5015.60	-	-	-	0.530	-	0.028
2472	5015.60	-	-	-	0.520	-	0.028
2473	5015.60	-	-	-	0.520	-	0.028
2474	5015.60	-	-	-	0.520	-	0.027
2475	5015.60	-	-	-	0.520	-	0.028
2476	5015.60	-	-	-	0.520	-	0.028
2477	5015.60	-	-	-	0.520	-	0.027
2478	5015.60	-	-	-	0.530	-	0.028
2479	5015.60	-	-	-	0.530	-	0.028
2480	5015.60	-	-	-	0.520	-	0.028
2481	5015.60	-	-	-	0.530	-	0.028
2482	5015.60	-	-	-	0.530	-	0.028
2483	5015.60	-	-	-	0.530	-	0.028
2484	5015.60	-	-	-	0.530	-	0.028
2485	5015.60	-	-	-	0.530	-	0.028
2486	5015.60	-	-	-	0.530	-	0.028
2487	5015.60	-	-	-	0.530	-	0.028
2488	5015.60	-	-	-	0.530	-	0.028
2489	5015.60	-	-	-	0.530	-	0.031
2490	5015.60	-	-	-	0.530	-	0.029
2491	5015.60	-	-	-	0.530	-	0.029
2492	5015.60	-	-	-	0.530	-	0.029
2493	5015.60	-	-	-	0.530	-	0.028
2494	5015.60	-	-	-	0.530	-	0.028
2495	5015.60	-	-	-	0.530	-	0.028
2496	5015.60	-	-	-	0.530	-	0.028
2497	5015.60	-	-	-	0.530	-	0.028
2498	5015.60	-	-	-	0.530	-	0.028
2499	5015.60	-	-	-	0.530	-	0.028
2500	5015.60	-	-	-	0.530	-	0.028
2501	5015.60	-	-	-	0.530	-	0.028
2502	5015.60	-	-	-	0.530	-	0.028
2503	5015.60	-	-	-	0.530	-	0.028
2504	5015.60	-	-	-	0.530	-	0.028
2505	5015.60	-	-	-	0.530	-	0.028
2506	5015.60	-	-	-	0.530	-	0.028
2507	5015.60	-	-	-	0.530	-	0.028
2508	5015.60	-	-	-	0.530	-	0.028
2509	5015.60	-	-	-	0.530	-	0.029
2510	5015.60	-	-	-	0.530	-	0.031
2511	5015.60	-	-	-	0.530	-	0.030
2512	5015.60	-	-	-	0.530	-	0.029
2513	5015.60	-	-	-	0.530	-	0.029
2514	5015.60	-	-	-	0.530	-	0.029
2515	5015.60	-	-	-	0.530	-	0.028

Continued on next page

Table 14 – continued from previous page - IEEE8500 - n3637

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
2516	5015.60	-	-	-	0.530	-	0.029
2517	5015.60	-	-	-	0.530	-	0.028
2518	5015.60	-	-	-	0.530	-	0.029
2519	5015.60	-	-	-	0.530	-	0.029
2520	5015.60	-	-	-	0.530	-	0.029
2521	5015.60	-	-	-	0.530	-	0.029
2522	5015.60	-	-	-	0.530	-	0.029
2523	5015.60	-	-	-	0.530	-	0.026
2524	5015.60	-	-	-	0.530	-	0.026
2525	5015.60	-	-	-	0.530	-	0.026
2526	5015.60	-	-	-	0.530	-	0.026
2527	5015.60	-	-	-	0.530	-	0.023
2528	5015.60	-	-	-	0.530	-	0.023
2529	5015.60	-	-	-	0.530	-	0.023
2530	5015.60	-	-	-	0.530	-	0.023
2531	5015.60	-	-	-	0.530	-	0.025
2532	5015.60	-	-	-	0.530	-	0.025
2533	5015.60	-	-	-	0.530	-	0.024
2534	5015.60	-	-	-	0.530	-	0.023
2535	5015.60	-	-	-	0.530	-	0.023
2536	5015.60	-	-	-	0.530	-	0.023
2537	5015.60	-	-	-	0.530	-	0.023
2538	5015.60	-	-	-	0.540	-	0.023
2539	5015.60	-	-	-	0.540	-	0.023
2540	5015.60	-	-	-	0.540	-	0.023
2541	5015.60	-	-	-	0.540	-	0.023
2542	5015.60	-	-	-	0.540	-	0.021
2543	5015.60	-	-	-	0.540	-	0.021
2544	5015.60	-	-	-	0.540	-	0.020
2545	5015.60	-	-	-	0.540	-	0.017
2546	5015.60	-	-	-	0.540	-	0.017
2547	5015.60	-	-	-	0.540	-	0.017
2548	5015.60	-	-	-	0.540	-	0.017
2549	5015.60	-	-	-	0.540	-	0.017
2550	5015.60	-	-	-	0.540	-	0.017
2551	5015.60	-	-	-	0.550	-	0.017
2552	5015.60	-	-	-	0.550	-	0.017
2553	5015.60	-	-	-	0.550	-	0.017
2554	5015.60	-	-	-	0.550	-	0.017
2555	5015.60	-	-	-	0.550	-	0.017
2556	5015.60	-	-	-	0.550	-	0.017
2557	5015.60	-	-	-	0.550	-	0.017
2558	5015.60	-	-	-	0.550	-	0.017
2559	5015.60	-	-	-	0.550	-	0.017
2560	5015.60	-	-	-	0.550	-	0.017
2561	5015.60	-	-	-	0.550	-	0.020
2562	5015.60	-	-	-	0.550	-	0.019
2563	5015.60	-	-	-	0.550	-	0.018
2564	5015.60	-	-	-	0.550	-	0.018
2565	5015.60	-	-	-	0.550	-	0.018
2566	5015.60	-	-	-	0.550	-	0.018
2567	5015.60	-	-	-	0.550	-	0.018

Continued on next page

Table 14 – continued from previous page - IEEE8500 - n3637

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
2568	5015.60	-	-	-	0.550	-	0.018
2569	5015.60	-	-	-	0.550	-	0.018
2570	5015.60	-	-	-	0.550	-	0.018
2571	5015.60	-	-	-	0.550	-	0.018
2572	5015.60	-	-	-	0.550	-	0.018
2573	5015.60	-	-	-	0.550	-	0.018
2574	5015.60	-	-	-	0.550	-	0.018
2575	5015.60	-	-	-	0.550	-	0.018
2576	5015.60	-	-	-	0.550	-	0.018
2577	5015.60	-	-	-	0.550	-	0.018
2578	5015.60	-	-	-	0.540	-	0.018
2579	5015.60	-	-	-	0.540	-	0.018
2580	5015.60	-	-	-	0.550	-	0.018
2581	5015.60	-	-	-	0.540	-	0.018
2582	5015.60	-	-	-	0.540	-	0.018
2583	5015.60	-	-	-	0.540	-	0.018
2584	5015.60	-	-	-	0.540	-	0.018
2585	5015.60	-	-	-	0.540	-	0.018
2586	5015.60	-	-	-	0.540	-	0.018
2587	5015.60	-	-	-	0.540	-	0.018
2588	5015.60	-	-	-	0.540	-	0.018
2589	5015.60	-	-	-	0.540	-	0.018
2590	5015.60	-	-	-	0.550	-	0.018
2591	5015.60	-	-	-	0.540	-	0.018
2592	5015.60	-	-	-	0.540	-	0.018
2593	5015.60	-	-	-	0.540	-	0.021
2594	5015.60	-	-	-	0.550	-	0.020
2595	5015.60	-	-	-	0.540	-	0.019
2596	5015.60	-	-	-	0.550	-	0.019
2597	5015.60	-	-	-	0.550	-	0.019
2598	5015.60	-	-	-	0.550	-	0.018
2599	5015.60	-	-	-	0.550	-	0.019
2600	5015.60	-	-	-	0.550	-	0.019
2601	5015.60	-	-	-	0.550	-	0.019
2602	5015.60	-	-	-	0.550	-	0.019
2603	5015.60	-	-	-	0.550	-	0.019
2604	5015.60	-	-	-	0.550	-	0.019
2605	5015.60	-	-	-	0.550	-	0.019
2606	5015.60	-	-	-	0.550	-	0.019
2607	5015.60	-	-	-	0.550	-	0.019
2608	5015.60	-	-	-	0.550	-	0.019
2609	5015.60	-	-	-	0.550	-	0.019
2610	5015.60	-	-	-	0.550	-	0.019
2611	5015.60	-	-	-	0.550	-	0.019
2612	5015.60	-	-	-	0.550	-	0.019
2613	5015.60	-	-	-	0.550	-	0.019
2614	5015.60	-	-	-	0.560	-	0.019
2615	5015.60	-	-	-	0.560	-	0.019
2616	5015.60	-	-	-	0.560	-	0.019
2617	5015.60	-	-	-	0.560	-	0.019
2618	5015.60	-	-	-	0.560	-	0.019
2619	5015.60	-	-	-	0.560	-	0.019

Continued on next page

Table 14 – continued from previous page - IEEE8500 - n3637

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
2620	5015.60	-	-	-	0.560	-	0.019
2621	5015.60	-	-	-	0.560	-	0.019
2622	5015.60	-	-	-	0.560	-	0.019
2623	5015.60	-	-	-	0.550	-	0.019
2624	5015.60	-	-	-	0.550	-	0.021
2625	5015.60	-	-	-	0.550	-	0.021
2626	5015.60	-	-	-	0.550	-	0.020
2627	5015.60	-	-	-	0.550	-	0.020
2628	5015.60	-	-	-	0.550	-	0.020
2629	5015.60	-	-	-	0.550	-	0.020
2630	5015.60	-	-	-	0.550	-	0.020
2631	5015.60	-	-	-	0.550	-	0.020
2632	5015.60	-	-	-	0.550	-	0.020
2633	5015.60	-	-	-	0.550	-	0.020
2634	5015.60	-	-	-	0.550	-	0.020
2635	5015.60	-	-	-	0.550	-	0.020
2636	5015.60	-	-	-	0.550	-	0.020
2637	5015.60	-	-	-	0.550	-	0.020
2638	5015.60	-	-	-	0.550	-	0.019
2639	5015.60	-	-	-	0.550	-	0.019
2640	5015.60	-	-	-	0.550	-	0.020
2641	5015.60	-	-	-	0.550	-	0.020
2642	5015.60	-	-	-	0.550	-	0.020
2643	5015.60	-	-	-	0.550	-	0.019
2644	5015.60	-	-	-	0.550	-	0.020
2645	5015.60	-	-	-	0.550	-	0.020
2646	5015.60	-	-	-	0.550	-	0.020
2647	5015.60	-	-	-	0.550	-	0.020
2648	5015.60	-	-	-	0.550	-	0.020
2649	5015.60	-	-	-	0.550	-	0.020
2650	5015.60	-	-	-	0.560	-	0.020
2651	5015.60	-	-	-	0.550	-	0.020
2652	5015.60	-	-	-	0.560	-	0.020
2653	5015.60	-	-	-	0.560	-	0.020
2654	5015.60	-	-	-	0.560	-	0.023
2655	5015.60	-	-	-	0.560	-	0.021
2656	5015.60	-	-	-	0.560	-	0.021
2657	5015.60	-	-	-	0.560	-	0.020
2658	5015.60	-	-	-	0.560	-	0.020
2659	5015.60	-	-	-	0.560	-	0.020
2660	5015.60	-	-	-	0.560	-	0.020
2661	5015.60	-	-	-	0.560	-	0.020
2662	5015.60	-	-	-	0.570	-	0.020
2663	5015.60	-	-	-	0.560	-	0.020
2664	5015.60	-	-	-	0.560	-	0.020
2665	5015.60	-	-	-	0.560	-	0.020
2666	5015.60	-	-	-	0.570	-	0.020
2667	5015.60	-	-	-	0.570	-	0.020
2668	5015.60	-	-	-	0.570	-	0.020
2669	5015.60	-	-	-	0.570	-	0.020
2670	5015.60	-	-	-	0.570	-	0.020
2671	5015.60	-	-	-	0.570	-	0.020

Continued on next page

Table 14 – continued from previous page - IEEE8500 - n3637

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
2672	5015.60	-	-	-	0.570	-	0.021
2673	5015.60	-	-	-	0.570	-	0.020
2674	5015.60	-	-	-	0.570	-	0.020
2675	5015.60	-	-	-	0.570	-	0.020
2676	5015.60	-	-	-	0.570	-	0.020
2677	5015.60	-	-	-	0.560	-	0.020
2678	5015.60	-	-	-	0.560	-	0.020
2679	5015.60	-	-	-	0.560	-	0.020
2680	5015.60	-	-	-	0.560	-	0.020
2681	5015.60	-	-	-	0.560	-	0.020
2682	5015.60	-	-	-	0.560	-	0.021
2683	5015.60	-	-	-	0.560	-	0.024
2684	5015.60	-	-	-	0.560	-	0.022
2685	5015.60	-	-	-	0.560	-	0.021
2686	5015.60	-	-	-	0.560	-	0.021
2687	5015.60	-	-	-	0.560	-	0.021
2688	5015.60	-	-	-	0.560	-	0.021
2689	5015.60	-	-	-	0.560	-	0.021
2690	5015.60	-	-	-	0.560	-	0.021
2691	5015.60	-	-	-	0.560	-	0.021
2692	5015.60	-	-	-	0.560	-	0.021
2693	5015.60	-	-	-	0.560	-	0.021
2694	5015.60	-	-	-	0.560	-	0.021
2695	5015.60	-	-	-	0.560	-	0.021
2696	5015.60	-	-	-	0.560	-	0.021
2697	5015.60	-	-	-	0.560	-	0.021
2698	5015.60	-	-	-	0.560	-	0.021
2699	5015.60	-	-	-	0.560	-	0.021
2700	5015.60	-	-	-	0.560	-	0.021
2701	5015.60	-	-	-	0.560	-	0.021
2702	5015.60	-	-	-	0.560	-	0.021
2703	5015.60	-	-	-	0.560	-	0.021
2704	5015.60	-	-	-	0.560	-	0.021
2705	5015.60	-	-	-	0.560	-	0.021
2706	5015.60	-	-	-	0.560	-	0.021
2707	5015.60	-	-	-	0.560	-	0.021
2708	5015.60	-	-	-	0.560	-	0.021
2709	5015.60	-	-	-	0.560	-	0.021
2710	5015.60	-	-	-	0.560	-	0.021
2711	5015.60	-	-	-	0.560	-	0.024
2712	5015.60	-	-	-	0.570	-	0.022
2713	5015.60	-	-	-	0.560	-	0.022
2714	5015.60	-	-	-	0.560	-	0.021
2715	5015.60	-	-	-	0.570	-	0.021
2716	5015.60	-	-	-	0.570	-	0.021
2717	5015.60	-	-	-	0.570	-	0.021
2718	5015.60	-	-	-	0.570	-	0.021
2719	5015.60	-	-	-	0.570	-	0.021
2720	5015.60	-	-	-	0.570	-	0.021
2721	5015.60	-	-	-	0.570	-	0.021
2722	5015.60	-	-	-	0.580	-	0.021
2723	5015.60	-	-	-	0.580	-	0.021

Continued on next page

Table 14 – continued from previous page - IEEE8500 - n3637

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
2724	5015.60	-	-	-	0.580	-	0.021
2725	5015.60	-	-	-	0.580	-	0.021
2726	5015.60	-	-	-	0.580	-	0.021
2727	5015.60	-	-	-	0.580	-	0.021
2728	5015.60	-	-	-	0.580	-	0.021
2729	5015.60	-	-	-	0.580	-	0.021
2730	5015.60	-	-	-	0.580	-	0.021
2731	5015.60	-	-	-	0.580	-	0.021
2732	5015.60	-	-	-	0.580	-	0.021
2733	5015.60	-	-	-	0.580	-	0.021
2734	5015.60	-	-	-	0.580	-	0.021
2735	5015.60	-	-	-	0.580	-	0.022
2736	5015.60	-	-	-	0.580	-	0.021
2737	5015.60	-	-	-	0.580	-	0.022
2738	5015.60	-	-	-	0.580	-	0.024
2739	5015.60	-	-	-	0.580	-	0.023
2740	5015.60	-	-	-	0.570	-	0.022
2741	5015.60	-	-	-	0.570	-	0.022
2742	5015.60	-	-	-	0.570	-	0.022
2743	5015.60	-	-	-	0.570	-	0.022
2744	5015.60	-	-	-	0.570	-	0.022
2745	5015.60	-	-	-	0.570	-	0.022
2746	5015.60	-	-	-	0.570	-	0.022
2747	5015.60	-	-	-	0.570	-	0.022
2748	5015.60	-	-	-	0.570	-	0.022
2749	5015.60	-	-	-	0.570	-	0.022
2750	5015.60	-	-	-	0.570	-	0.022
2751	5015.60	-	-	-	0.570	-	0.022
2752	5015.60	-	-	-	0.570	-	0.022
2753	5015.60	-	-	-	0.570	-	0.022
2754	5015.60	-	-	-	0.570	-	0.022
2755	5015.60	-	-	-	0.570	-	0.022
2756	5015.60	-	-	-	0.570	-	0.022
2757	5015.60	-	-	-	0.570	-	0.022
2758	5015.60	-	-	-	0.570	-	0.022
2759	5015.60	-	-	-	0.570	-	0.022
2760	5015.60	-	-	-	0.570	-	0.022
2761	5015.60	-	-	-	0.570	-	0.022
2762	5015.60	-	-	-	0.570	-	0.022
2763	5015.60	-	-	-	0.570	-	0.022
2764	5015.60	-	-	-	0.570	-	0.022
2765	5015.60	-	-	-	0.570	-	0.025
2766	5015.60	-	-	-	0.570	-	0.023
2767	5015.60	-	-	-	0.570	-	0.023
2768	5015.60	-	-	-	0.570	-	0.022
2769	5015.60	-	-	-	0.570	-	0.022
2770	5015.60	-	-	-	0.570	-	0.022
2771	5015.60	-	-	-	0.570	-	0.022
2772	5015.60	-	-	-	0.570	-	0.022
2773	5015.60	-	-	-	0.580	-	0.022
2774	5015.60	-	-	-	0.570	-	0.022
2775	5015.60	-	-	-	0.580	-	0.022

Continued on next page

Table 14 – continued from previous page - IEEE8500 - n3637

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
2776	5015.60	-	-	-	0.580	-	0.022
2777	5015.60	-	-	-	0.580	-	0.022
2778	5015.60	-	-	-	0.580	-	0.022
2779	5015.60	-	-	-	0.580	-	0.022
2780	5015.60	-	-	-	0.580	-	0.022
2781	5015.60	-	-	-	0.580	-	0.022
2782	5015.60	-	-	-	0.580	-	0.022
2783	5015.60	-	-	-	0.580	-	0.022
2784	5015.60	-	-	-	0.580	-	0.022
2785	5015.60	-	-	-	0.580	-	0.022
2786	5015.60	-	-	-	0.580	-	0.022
2787	5015.60	-	-	-	0.580	-	0.022
2788	5015.60	-	-	-	0.580	-	0.022
2789	5015.60	-	-	-	0.580	-	0.022
2790	5015.60	-	-	-	0.580	-	0.022
2791	5015.60	-	-	-	0.580	-	0.025
2792	5015.60	-	-	-	0.580	-	0.024
2793	5015.60	-	-	-	0.580	-	0.023
2794	5015.60	-	-	-	0.580	-	0.023
2795	5015.60	-	-	-	0.580	-	0.023
2796	5015.60	-	-	-	0.580	-	0.023
2797	5015.60	-	-	-	0.580	-	0.023
2798	5015.60	-	-	-	0.580	-	0.022
2799	5015.60	-	-	-	0.580	-	0.023
2800	5015.60	-	-	-	0.580	-	0.023
2801	5015.60	-	-	-	0.580	-	0.022
2802	5015.60	-	-	-	0.580	-	0.023
2803	5015.60	-	-	-	0.590	-	0.022
2804	5015.60	-	-	-	0.590	-	0.023
2805	5015.60	-	-	-	0.590	-	0.023
2806	5015.60	-	-	-	0.590	-	0.023
2807	5015.60	-	-	-	0.590	-	0.023
2808	5015.60	-	-	-	0.590	-	0.023
2809	5015.60	-	-	-	0.590	-	0.023
2810	5015.60	-	-	-	0.590	-	0.023
2811	5015.60	-	-	-	0.590	-	0.023
2812	5015.60	-	-	-	0.590	-	0.023
2813	5015.60	-	-	-	0.590	-	0.023
2814	5015.60	-	-	-	0.590	-	0.023
2815	5015.60	-	-	-	0.590	-	0.023
2816	5015.60	-	-	-	0.590	-	0.025
2817	5015.60	-	-	-	0.590	-	0.025
2818	5015.60	-	-	-	0.590	-	0.024
2819	5015.60	-	-	-	0.590	-	0.023
2820	5015.60	-	-	-	0.590	-	0.023
2821	5015.60	-	-	-	0.590	-	0.023
2822	5015.60	-	-	-	0.590	-	0.023
2823	5015.60	-	-	-	0.590	-	0.023
2824	5015.60	-	-	-	0.590	-	0.023
2825	5015.60	-	-	-	0.590	-	0.023
2826	5015.60	-	-	-	0.590	-	0.023
2827	5015.60	-	-	-	0.590	-	0.023

Continued on next page

Table 14 – continued from previous page - IEEE8500 - n3637

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
2828	5015.60	-	-	-	0.590	-	0.023
2829	5015.60	-	-	-	0.590	-	0.023
2830	5015.60	-	-	-	0.590	-	0.023
2831	5015.60	-	-	-	0.590	-	0.023
2832	5015.60	-	-	-	0.590	-	0.023
2833	5015.60	-	-	-	0.590	-	0.023
2834	5015.60	-	-	-	0.590	-	0.023
2835	5015.60	-	-	-	0.590	-	0.023
2836	5015.60	-	-	-	0.600	-	0.023
2837	5015.60	-	-	-	0.600	-	0.023
2838	5015.60	-	-	-	0.600	-	0.023
2839	5015.60	-	-	-	0.600	-	0.023
2840	5015.60	-	-	-	0.600	-	0.023
2841	5015.60	-	-	-	0.600	-	0.025
2842	5015.60	-	-	-	0.600	-	0.026
2843	5015.60	-	-	-	0.600	-	0.024
2844	5015.60	-	-	-	0.600	-	0.024
2845	5015.60	-	-	-	0.600	-	0.024
2846	5015.60	-	-	-	0.600	-	0.024
2847	5015.60	-	-	-	0.600	-	0.024
2848	5015.60	-	-	-	0.600	-	0.024
2849	5015.60	-	-	-	0.600	-	0.024
2850	5015.60	-	-	-	0.600	-	0.024
2851	5015.60	-	-	-	0.600	-	0.024
2852	5015.60	-	-	-	0.600	-	0.024
2853	5015.60	-	-	-	0.600	-	0.024
2854	5015.60	-	-	-	0.600	-	0.024
2855	5015.60	-	-	-	0.600	-	0.024
2856	5015.60	-	-	-	0.600	-	0.024
2857	5015.60	-	-	-	0.600	-	0.024
2858	5015.60	-	-	-	0.600	-	0.024
2859	5015.60	-	-	-	0.600	-	0.024
2860	5015.60	-	-	-	0.600	-	0.024
2861	5015.60	-	-	-	0.600	-	0.024
2862	5015.60	-	-	-	0.600	-	0.024
2863	5015.60	-	-	-	0.600	-	0.033
2864	5015.60	-	-	-	0.600	-	0.033
2865	5015.60	-	-	-	0.600	-	0.035
2866	5015.60	-	-	-	0.600	-	0.034
2867	5015.60	-	-	-	0.600	-	0.040
2868	5015.60	-	-	-	0.600	-	0.040
2869	5015.60	-	-	-	0.600	-	0.039
2870	5015.60	-	-	-	0.600	-	0.039
2871	5015.60	-	-	-	0.600	-	0.039
2872	5015.60	-	-	-	0.600	-	0.039
2873	5015.60	-	-	-	0.600	-	0.040
2874	5015.60	-	-	-	0.600	-	0.040
2875	5015.60	-	-	-	0.590	-	0.039
2876	5015.60	-	-	-	0.590	-	0.039
2877	5015.60	-	-	-	0.590	-	0.040
2878	5015.60	-	-	-	0.590	-	0.040
2879	5015.60	-	-	-	0.590	-	0.040

Continued on next page

Table 14 – continued from previous page - IEEE8500 - n3637

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
2880	5015.60	-	-	-	0.590	-	0.042
2881	5015.60	-	-	-	0.590	-	0.047
2882	5015.60	-	-	-	0.590	-	0.046
2883	5015.60	-	-	-	0.590	-	0.050
2884	5015.60	-	-	-	0.590	-	0.050
2885	5015.60	-	-	-	0.600	-	0.050
2886	5015.60	-	-	-	0.600	-	0.050
2887	5015.60	-	-	-	0.600	-	0.050
2888	5015.60	-	-	-	0.600	-	0.050
2889	5015.60	-	-	-	0.600	-	0.050
2890	5015.60	-	-	-	0.600	-	0.050
2891	5015.60	-	-	-	0.600	-	0.050
2892	5015.60	-	-	-	0.600	-	0.052
2893	5015.60	-	-	-	0.600	-	0.051
2894	5015.60	-	-	-	0.600	-	0.051
2895	5015.60	-	-	-	0.600	-	0.050
2896	5015.60	-	-	-	0.600	-	0.050
2897	5015.60	-	-	-	0.600	-	0.050
2898	5015.60	-	-	-	0.600	-	0.050
2899	5015.60	-	-	-	0.610	-	0.051
2900	5015.60	-	-	-	0.610	-	0.051
2901	5015.60	-	-	-	0.610	-	0.050
2902	5015.60	-	-	-	0.610	-	0.050
2903	5015.60	-	-	-	0.610	-	0.051
2904	5015.60	-	-	-	0.610	-	0.054
2905	5015.60	-	-	-	0.610	-	0.051
2906	5015.60	-	-	-	0.610	-	0.051
2907	5015.60	-	-	-	0.610	-	0.051
2908	5015.60	-	-	-	0.610	-	0.051
2909	5015.60	-	-	-	0.610	-	0.051
2910	5015.60	-	-	-	0.610	-	0.051
2911	5015.60	-	-	-	0.610	-	0.051
2912	5015.60	-	-	-	0.610	-	0.051
2913	5015.60	-	-	-	0.610	-	0.051
2914	5015.60	-	-	-	0.610	-	0.051
2915	5015.60	-	-	-	0.610	-	0.052
2916	5015.60	-	-	-	0.610	-	0.053
2917	5015.60	-	-	-	0.610	-	0.051
2918	5015.60	-	-	-	0.610	-	0.051
2919	5015.60	-	-	-	0.610	-	0.051
2920	5015.60	-	-	-	0.610	-	0.051
2921	5015.60	-	-	-	0.610	-	0.051
2922	5015.60	-	-	-	0.610	-	0.051
2923	5015.60	-	-	-	0.610	-	0.051
2924	5015.60	-	-	-	0.610	-	0.051
2925	5015.60	-	-	-	0.610	-	0.051
2926	5015.60	-	-	-	0.610	-	0.051
2927	5015.60	-	-	-	0.610	-	0.054
2928	5015.60	-	-	-	0.610	-	0.053
2929	5015.60	-	-	-	0.610	-	0.052
2930	5015.60	-	-	-	0.610	-	0.051
2931	5015.60	-	-	-	0.600	-	0.051

Continued on next page

Table 14 – continued from previous page - IEEE8500 - n3637

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
2932	5015.60	-	-	-	0.600	-	0.052
2933	5015.60	-	-	-	0.600	-	0.052
2934	5015.60	-	-	-	0.600	-	0.052
2935	5015.60	-	-	-	0.600	-	0.052
2936	5015.60	-	-	-	0.610	-	0.052
2937	5015.60	-	-	-	0.600	-	0.051
2938	5015.60	-	-	-	0.600	-	0.052
2939	5015.60	-	-	-	0.610	-	0.054
2940	5015.60	-	-	-	0.610	-	0.052
2941	5015.60	-	-	-	0.610	-	0.051
2942	5015.60	-	-	-	0.610	-	0.051
2943	5015.60	-	-	-	0.610	-	0.051
2944	5015.60	-	-	-	0.610	-	0.051
2945	5015.60	-	-	-	0.610	-	0.051
2946	5015.60	-	-	-	0.620	-	0.051
2947	5015.60	-	-	-	0.620	-	0.051
2948	5015.60	-	-	-	0.620	-	0.051
2949	5015.60	-	-	-	0.620	-	0.051
2950	5015.60	-	-	-	0.620	-	0.054
2951	5015.60	-	-	-	0.620	-	0.052
2952	5015.60	-	-	-	0.620	-	0.052
2953	5015.60	-	-	-	0.620	-	0.052
2954	5015.60	-	-	-	0.620	-	0.051
2955	5015.60	-	-	-	0.620	-	0.052
2956	5015.60	-	-	-	0.620	-	0.052
2957	5015.60	-	-	-	0.620	-	0.054
2958	5015.60	-	-	-	0.620	-	0.053
2959	5015.60	-	-	-	0.620	-	0.053
2960	5015.60	-	-	-	0.620	-	0.052
2961	5015.60	-	-	-	0.620	-	0.054
2962	5015.60	-	-	-	0.620	-	0.053
2963	5015.60	-	-	-	0.620	-	0.052
2964	5015.60	-	-	-	0.620	-	0.052
2965	5015.60	-	-	-	0.620	-	0.052
2966	5015.60	-	-	-	0.620	-	0.052
2967	5015.60	-	-	-	0.620	-	0.052
2968	5015.60	-	-	-	0.620	-	0.052
2969	5015.60	-	-	-	0.620	-	0.052
2970	5015.60	-	-	-	0.620	-	0.052
2971	5015.60	-	-	-	0.620	-	0.052
2972	5015.60	-	-	-	0.620	-	0.052
2973	5015.60	-	-	-	0.620	-	0.055
2974	5015.60	-	-	-	0.620	-	0.053
2975	5015.60	-	-	-	0.620	-	0.052
2976	5015.60	-	-	-	0.620	-	0.052
2977	5015.60	-	-	-	0.620	-	0.052
2978	5015.60	-	-	-	0.620	-	0.052
2979	5015.60	-	-	-	0.620	-	0.052
2980	5015.60	-	-	-	0.620	-	0.052
2981	5015.60	-	-	-	0.620	-	0.052
2982	5015.60	-	-	-	0.620	-	0.052
2983	5015.60	-	-	-	0.620	-	0.052

Continued on next page

Table 14 – continued from previous page - IEEE8500 - n3637

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
2984	5015.60	-	-	-	0.620	-	0.054
2985	5015.60	-	-	-	0.620	-	0.053
2986	5015.60	-	-	-	0.620	-	0.052
2987	5015.60	-	-	-	0.620	-	0.052
2988	5015.60	-	-	-	0.620	-	0.052
2989	5015.60	-	-	-	0.620	-	0.052
2990	5015.60	-	-	-	0.620	-	0.052
2991	5015.60	-	-	-	0.620	-	0.052
2992	5015.60	-	-	-	0.620	-	0.052
2993	5015.60	-	-	-	0.620	-	0.052
2994	5015.60	-	-	-	0.620	-	0.052
2995	5015.60	-	-	-	0.620	-	0.053
2996	5015.60	-	-	-	0.620	-	0.054
2997	5015.60	-	-	-	0.620	-	0.053
2998	5015.60	-	-	-	0.620	-	0.052
2999	5015.60	-	-	-	0.620	-	0.052
3000	5015.60	-	-	-	0.620	-	0.052
3001	5015.60	-	-	-	0.630	-	0.053
3002	5015.60	-	-	-	0.630	-	0.053
3003	5015.60	-	-	-	0.630	-	0.053
3004	5015.60	-	-	-	0.630	-	0.053
3005	5015.60	-	-	-	0.630	-	0.052
3006	5015.60	-	-	-	0.630	-	0.052
3007	5015.60	-	-	-	0.630	-	0.056
3008	5015.60	-	-	-	0.630	-	0.054
3009	5015.60	-	-	-	0.630	-	0.053
3010	5015.60	-	-	-	0.630	-	0.053
3011	5015.60	-	-	-	0.630	-	0.053
3012	5015.60	-	-	-	0.630	-	0.053
3013	5015.60	-	-	-	0.630	-	0.055
3014	5015.60	-	-	-	0.630	-	0.055
3015	5015.60	-	-	-	0.630	-	0.055
3016	5015.60	-	-	-	0.630	-	0.055
3017	5015.60	-	-	-	0.630	-	0.057
3018	5015.60	-	-	-	0.630	-	0.060
3019	5015.60	-	-	-	0.630	-	0.058
3020	5015.60	-	-	-	0.630	-	0.057
3021	5015.60	-	-	-	0.630	-	0.057
3022	5015.60	-	-	-	0.630	-	0.057
3023	5015.60	-	-	-	0.630	-	0.057
3024	5015.60	-	-	-	0.630	-	0.057
3025	5015.60	-	-	-	0.630	-	0.057
3026	5015.60	-	-	-	0.630	-	0.042
3027	5015.60	-	-	-	0.630	-	0.042
3028	5015.60	-	-	-	0.630	-	0.041
3029	5015.60	-	-	-	0.630	-	0.044
3030	5015.60	-	-	-	0.630	-	0.042
3031	5015.60	-	-	-	0.630	-	0.044
3032	5015.60	-	-	-	0.630	-	0.044
3033	5015.60	-	-	-	0.630	-	0.045
3034	5015.60	-	-	-	0.630	-	0.045
3035	5015.60	-	-	-	0.630	-	0.045

Continued on next page

Table 14 – continued from previous page - IEEE8500 - n3637

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
3036	5015.60	-	-	-	0.630	-	0.045
3037	5015.60	-	-	-	0.630	-	0.045
3038	5015.60	-	-	-	0.630	-	0.045
3039	5015.60	-	-	-	0.630	-	0.045
3040	5015.60	-	-	-	0.630	-	0.045
3041	5015.60	-	-	-	0.630	-	0.045
3042	5015.60	-	-	-	0.630	-	0.047
3043	5015.60	-	-	-	0.630	-	0.047
3044	5015.60	-	-	-	0.630	-	0.046
3045	5015.60	-	-	-	0.630	-	0.046
3046	5015.60	-	-	-	0.640	-	0.046
3047	5015.60	-	-	-	0.630	-	0.045
3048	5015.60	-	-	-	0.630	-	0.045
3049	5015.60	-	-	-	0.640	-	0.045
3050	5015.60	-	-	-	0.640	-	0.045
3051	5015.60	-	-	-	0.630	-	0.046
3052	5015.60	-	-	-	0.640	-	0.045
3053	5015.60	-	-	-	0.640	-	0.045
3054	5015.60	-	-	-	0.630	-	0.045
3055	5015.60	-	-	-	0.640	-	0.046
3056	5015.60	-	-	-	0.640	-	0.047
3057	5015.60	-	-	-	0.640	-	0.046
3058	5015.60	-	-	-	0.640	-	0.046
3059	5015.60	-	-	-	0.640	-	0.046
3060	5015.60	-	-	-	0.640	-	0.046
3061	5015.60	-	-	-	0.640	-	0.045
3062	5015.60	-	-	-	0.640	-	0.045
3063	5015.60	-	-	-	0.640	-	0.045
3064	5015.60	-	-	-	0.640	-	0.045
3065	5015.60	-	-	-	0.640	-	0.046
3066	5015.60	-	-	-	0.640	-	0.046
3067	5015.60	-	-	-	0.640	-	0.045
3068	5015.60	-	-	-	0.640	-	0.046
3069	5015.60	-	-	-	0.640	-	0.047
3070	5015.60	-	-	-	0.640	-	0.046
3071	5015.60	-	-	-	0.640	-	0.045
3072	5015.60	-	-	-	0.640	-	0.042
3073	5015.60	-	-	-	0.640	-	0.042
3074	5015.60	-	-	-	0.640	-	0.042
3075	5015.60	-	-	-	0.640	-	0.042
3076	5015.60	-	-	-	0.640	-	0.043
3077	5015.60	-	-	-	0.640	-	0.043
3078	5015.60	-	-	-	0.640	-	0.043
3079	5015.60	-	-	-	0.640	-	0.043
3080	5015.60	-	-	-	0.640	-	0.043
3081	5015.60	-	-	-	0.640	-	0.043
3082	5015.60	-	-	-	0.640	-	0.044
3083	5015.60	-	-	-	0.640	-	0.043
3084	5015.60	-	-	-	0.640	-	0.043
3085	5015.60	-	-	-	0.640	-	0.043
3086	5015.60	-	-	-	0.640	-	0.042
3087	5015.60	-	-	-	0.640	-	0.043

Continued on next page

Table 14 – continued from previous page - IEEE8500 - n3637

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
3088	5015.60	-	-	-	0.640	-	0.043
3089	5015.60	-	-	-	0.640	-	0.043
3090	5015.60	-	-	-	0.640	-	0.043
3091	5015.60	-	-	-	0.640	-	0.043
3092	5015.60	-	-	-	0.640	-	0.043
3093	5015.60	-	-	-	0.640	-	0.043
3094	5015.60	-	-	-	0.640	-	0.043
3095	5015.60	-	-	-	0.640	-	0.043
3096	5015.60	-	-	-	0.640	-	0.045
3097	5015.60	-	-	-	0.640	-	0.043
3098	5015.60	-	-	-	0.640	-	0.043
3099	5015.60	-	-	-	0.640	-	0.043
3100	5015.60	-	-	-	0.640	-	0.042
3101	5015.60	-	-	-	0.640	-	0.042
3102	5015.60	-	-	-	0.640	-	0.042
3103	5015.60	-	-	-	0.640	-	0.042
3104	5015.60	-	-	-	0.640	-	0.042
3105	5015.60	-	-	-	0.640	-	0.042
3106	5015.60	-	-	-	0.650	-	0.042
3107	5015.60	-	-	-	0.650	-	0.042
3108	5015.60	-	-	-	0.640	-	0.042
3109	5015.60	-	-	-	0.650	-	0.042
3110	5015.60	-	-	-	0.650	-	0.044
3111	5015.60	-	-	-	0.650	-	0.043
3112	5015.60	-	-	-	0.650	-	0.043
3113	5015.60	-	-	-	0.650	-	0.043
3114	5015.60	-	-	-	0.650	-	0.043
3115	5015.60	-	-	-	0.650	-	0.046
3116	5015.60	-	-	-	0.650	-	0.046
3117	5015.60	-	-	-	0.650	-	0.046
3118	5015.60	-	-	-	0.650	-	0.045
3119	5015.60	-	-	-	0.650	-	0.045
3120	5015.60	-	-	-	0.650	-	0.045
3121	5015.60	-	-	-	0.650	-	0.045
3122	5015.60	-	-	-	0.650	-	0.045
3123	5015.60	-	-	-	0.650	-	0.047
3124	5015.60	-	-	-	0.650	-	0.046
3125	5015.60	-	-	-	0.650	-	0.046
3126	5015.60	-	-	-	0.650	-	0.046
3127	5015.60	-	-	-	0.650	-	0.045
3128	5015.60	-	-	-	0.650	-	0.045
3129	5015.60	-	-	-	0.650	-	0.045
3130	5015.60	-	-	-	0.650	-	0.045
3131	5015.60	-	-	-	0.650	-	0.045
3132	5015.60	-	-	-	0.650	-	0.045
3133	5015.60	-	-	-	0.650	-	0.043
3134	5015.60	-	-	-	0.650	-	0.043
3135	5015.60	-	-	-	0.650	-	0.042
3136	5015.60	-	-	-	0.650	-	0.044
3137	5015.60	-	-	-	0.650	-	0.044
3138	5015.60	-	-	-	0.650	-	0.043
3139	5015.60	-	-	-	0.650	-	0.042

Continued on next page

Table 14 – continued from previous page - IEEE8500 - n3637

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
3140	5015.60	-	-	-	0.650	-	0.043
3141	5015.60	-	-	-	0.650	-	0.043
3142	5015.60	-	-	-	0.650	-	0.043
3143	5015.60	-	-	-	0.650	-	0.042
3144	5015.60	-	-	-	0.650	-	0.042
3145	5015.60	-	-	-	0.650	-	0.042
3146	5015.60	-	-	-	0.650	-	0.042
3147	5015.60	-	-	-	0.640	-	0.042
3148	5015.60	-	-	-	0.640	-	0.042
3149	5015.60	-	-	-	0.640	-	0.042
3150	5015.60	-	-	-	0.640	-	0.044
3151	5015.60	-	-	-	0.640	-	0.043
3152	5015.60	-	-	-	0.640	-	0.043
3153	5015.60	-	-	-	0.640	-	0.042
3154	5015.60	-	-	-	0.640	-	0.042
3155	5015.60	-	-	-	0.640	-	0.042
3156	5015.60	-	-	-	0.640	-	0.043
3157	5015.60	-	-	-	0.640	-	0.042
3158	5015.60	-	-	-	0.640	-	0.042
3159	5015.60	-	-	-	0.640	-	0.043
3160	5015.60	-	-	-	0.650	-	0.042
3161	5015.60	-	-	-	0.640	-	0.042
3162	5015.60	-	-	-	0.650	-	0.043
3163	5015.60	-	-	-	0.650	-	0.042
3164	5015.60	-	-	-	0.650	-	0.044
3165	5015.60	-	-	-	0.650	-	0.043
3166	5015.60	-	-	-	0.650	-	0.043
3167	5015.60	-	-	-	0.650	-	0.043
3168	5015.60	-	-	-	0.650	-	0.043
3169	5015.60	-	-	-	0.650	-	0.042
3170	5015.60	-	-	-	0.650	-	0.042
3171	5015.60	-	-	-	0.660	-	0.043
3172	5015.60	-	-	-	0.660	-	0.042
3173	5015.60	-	-	-	0.660	-	0.042
3174	5015.60	-	-	-	0.660	-	0.042
3175	5015.60	-	-	-	0.660	-	0.042
3176	5015.60	-	-	-	0.660	-	0.034
3177	5015.60	-	-	-	0.660	-	0.034
3178	5015.60	-	-	-	0.660	-	0.034
3179	5015.60	-	-	-	0.650	-	0.036
3180	5015.60	-	-	-	0.650	-	0.026
3181	5015.60	-	-	-	0.650	-	0.026
3182	5015.60	-	-	-	0.650	-	0.026
3183	5015.60	-	-	-	0.650	-	0.026
3184	5015.60	-	-	-	0.650	-	0.026
3185	5015.60	-	-	-	0.650	-	0.026
3186	5015.60	-	-	-	0.650	-	0.026
3187	5015.60	-	-	-	0.650	-	0.026
3188	5015.60	-	-	-	0.650	-	0.025
3189	5015.60	-	-	-	0.650	-	0.025
3190	5015.60	-	-	-	0.650	-	0.025
3191	5015.60	-	-	-	0.650	-	0.026

Continued on next page

Table 14 – continued from previous page - IEEE8500 - n3637

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
3192	5015.60	-	-	-	0.650	-	0.025
3193	5015.60	-	-	-	0.650	-	0.025
3194	5015.60	-	-	-	0.650	-	0.025
3195	5015.60	-	-	-	0.660	-	0.025
3196	5015.60	-	-	-	0.660	-	0.018
3197	5015.60	-	-	-	0.660	-	0.018
3198	5015.60	-	-	-	0.660	-	0.010
3199	5015.60	-	-	-	0.660	-	0.009
3200	5015.60	-	-	-	0.660	-	0.008
3201	5015.60	-	-	-	0.660	-	0.007
3202	5015.60	-	-	-	0.660	-	0.007
3203	5015.60	-	-	-	0.660	-	0.008
3204	5015.60	-	-	-	0.660	-	0.008
3205	5015.60	-	-	-	0.660	-	0.007
3206	5015.60	-	-	-	0.660	-	0.009
3207	5015.60	-	-	-	0.660	-	0.011
3208	5015.60	-	-	-	0.660	-	0.010
3209	5015.60	-	-	-	0.660	-	0.010
3210	5015.60	-	-	-	0.660	-	0.010
3211	5015.60	-	-	-	0.660	-	0.008
3212	5015.60	-	-	-	0.660	-	0.007
3213	5015.60	-	-	-	0.660	-	0.007
3214	5015.60	-	-	-	0.660	-	0.007
3215	5015.60	-	-	-	0.660	-	0.007
3216	5015.60	-	-	-	0.660	-	0.007
3217	5015.60	-	-	-	0.660	-	0.007
3218	5015.60	-	-	-	0.660	-	0.008
3219	5015.60	-	-	-	0.670	-	0.008
3220	5015.60	-	-	-	0.670	-	0.007
3221	5015.60	-	-	-	0.670	-	0.007
3222	5015.60	-	-	-	0.670	-	0.007
3223	5015.60	-	-	-	0.670	-	0.007
3224	5015.60	-	-	-	0.670	-	0.007
3225	5015.60	-	-	-	0.670	-	0.008
3226	5015.60	-	-	-	0.670	-	0.007
3227	5015.60	-	-	-	0.670	-	0.007
3228	5015.60	-	-	-	0.670	-	0.007
3229	5015.60	-	-	-	0.670	-	0.007
3230	5015.60	-	-	-	0.670	-	0.007
3231	5015.60	-	-	-	0.670	-	0.007
3232	5015.60	-	-	-	0.670	-	0.007
3233	5015.60	-	-	-	0.670	-	0.007
3234	5015.60	-	-	-	0.670	-	0.007
3235	5015.60	-	-	-	0.670	-	0.007
3236	5015.60	-	-	-	0.670	-	0.007
3237	5015.60	-	-	-	0.670	-	0.007
3238	5015.60	-	-	-	0.670	-	0.007
3239	5015.60	-	-	-	0.670	-	0.007
3240	5015.60	-	-	-	0.670	-	0.007
3241	5015.60	-	-	-	0.670	-	0.007
3242	5015.60	-	-	-	0.670	-	0.007
3243	5015.60	-	-	-	0.670	-	0.007

Continued on next page

Table 14 – continued from previous page - IEEE8500 - n3637

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
3244	5015.60	-	-	-	0.670	-	0.007
3245	5015.60	-	-	-	0.670	-	0.007
3246	5015.60	-	-	-	0.670	-	0.007
3247	5015.60	-	-	-	0.670	-	0.007
3248	5015.60	-	-	-	0.670	-	0.007
3249	5015.60	-	-	-	0.670	-	0.007
3250	5015.60	-	-	-	0.670	-	0.007
3251	5015.60	-	-	-	0.670	-	0.007
3252	5015.60	-	-	-	0.670	-	0.007
3253	5015.60	-	-	-	0.670	-	0.007
3254	5015.60	-	-	-	0.670	-	0.007
3255	5015.60	-	-	-	0.670	-	0.007
3256	5015.60	-	-	-	0.670	-	0.007
3257	5015.60	-	-	-	0.670	-	0.007
3258	5015.60	-	-	-	0.670	-	0.007
3259	5015.60	-	-	-	0.660	-	0.007
3260	5015.60	-	-	-	0.660	-	0.007
3261	5015.60	-	-	-	0.660	-	0.007
3262	5015.60	-	-	-	0.660	-	0.007
3263	5015.60	-	-	-	0.660	-	0.007
3264	5015.60	-	-	-	0.660	-	0.007
3265	5015.60	-	-	-	0.660	-	0.007
3266	5015.60	-	-	-	0.660	-	0.007
3267	5015.60	-	-	-	0.680	-	0.007
3268	5015.60	-	-	-	0.670	-	0.007
3269	5015.60	-	-	-	0.670	-	0.007
3270	5015.60	-	-	-	0.680	-	0.007
3271	5015.60	-	-	-	0.670	-	0.007
3272	5015.60	-	-	-	0.670	-	0.007
3273	5015.60	-	-	-	0.680	-	0.011
3274	5015.60	-	-	-	0.680	-	0.011
3275	5015.60	-	-	-	0.680	-	0.011
3276	5015.60	-	-	-	0.680	-	0.011
3277	5015.60	-	-	-	0.680	-	0.014
3278	5015.60	-	-	-	0.680	-	0.014
3279	5015.60	-	-	-	0.680	-	0.014
3280	5015.60	-	-	-	0.680	-	0.014
3281	5015.60	-	-	-	0.680	-	0.016
3282	5015.60	-	-	-	0.680	-	0.016
3283	5015.60	-	-	-	0.680	-	0.015
3284	5015.60	-	-	-	0.680	-	0.015
3285	5015.60	-	-	-	0.680	-	0.014
3286	5015.60	-	-	-	0.680	-	0.014
3287	5015.60	-	-	-	0.680	-	0.014
3288	5015.60	-	-	-	0.680	-	0.014
3289	5015.60	-	-	-	0.680	-	0.014
3290	5015.60	-	-	-	0.680	-	0.014
3291	5015.60	-	-	-	0.680	-	0.017
3292	5015.60	-	-	-	0.680	-	0.017
3293	5015.60	-	-	-	0.680	-	0.020
3294	5015.60	-	-	-	0.680	-	0.020
3295	5015.60	-	-	-	0.680	-	0.019

Continued on next page

Table 14 – continued from previous page - IEEE8500 - n3637

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
3296	5015.60	-	-	-	0.680	-	0.019
3297	5015.60	-	-	-	0.680	-	0.019
3298	5015.60	-	-	-	0.680	-	0.019
3299	5015.60	-	-	-	0.680	-	0.020
3300	5015.60	-	-	-	0.680	-	0.020
3301	5015.60	-	-	-	0.680	-	0.022
3302	5015.60	-	-	-	0.680	-	0.021
3303	5015.60	-	-	-	0.680	-	0.020
3304	5015.60	-	-	-	0.680	-	0.020
3305	5015.60	-	-	-	0.680	-	0.020
3306	5015.60	-	-	-	0.680	-	0.021
3307	5015.60	-	-	-	0.680	-	0.021
3308	5015.60	-	-	-	0.680	-	0.020
3309	5015.60	-	-	-	0.680	-	0.020
3310	5015.60	-	-	-	0.680	-	0.020
3311	5015.60	-	-	-	0.680	-	0.020
3312	5015.60	-	-	-	0.680	-	0.020
3313	5015.60	-	-	-	0.680	-	0.022
3314	5015.60	-	-	-	0.680	-	0.022
3315	5015.60	-	-	-	0.680	-	0.021
3316	5015.60	-	-	-	0.680	-	0.020
3317	5015.60	-	-	-	0.680	-	0.020
3318	5015.60	-	-	-	0.680	-	0.020
3319	5015.60	-	-	-	0.680	-	0.020
3320	5015.60	-	-	-	0.680	-	0.020
3321	5015.60	-	-	-	0.680	-	0.020
3322	5015.60	-	-	-	0.680	-	0.020
3323	5015.60	-	-	-	0.690	-	0.020
3324	5015.60	-	-	-	0.680	-	0.019
3325	5015.60	-	-	-	0.680	-	0.020
3326	5015.60	-	-	-	0.680	-	0.020
3327	5015.60	-	-	-	0.680	-	0.019
3328	5015.60	-	-	-	0.690	-	0.019
3329	5015.60	-	-	-	0.690	-	0.019
3330	5015.60	-	-	-	0.690	-	0.019
3331	5015.60	-	-	-	0.690	-	0.019
3332	5015.60	-	-	-	0.690	-	0.019
3333	5015.60	-	-	-	0.690	-	0.020
3334	5015.60	-	-	-	0.690	-	0.020
3335	5015.60	-	-	-	0.690	-	0.020
3336	5015.60	-	-	-	0.690	-	0.020
3337	5015.60	-	-	-	0.690	-	0.019
3338	5015.60	-	-	-	0.690	-	0.019
3339	5015.60	-	-	-	0.690	-	0.019
3340	5015.60	-	-	-	0.690	-	0.019
3341	5015.60	-	-	-	0.690	-	0.019
3342	5015.60	-	-	-	0.690	-	0.020
3343	5015.60	-	-	-	0.690	-	0.023
3344	5015.60	-	-	-	0.690	-	0.021
3345	5015.60	-	-	-	0.690	-	0.020
3346	5015.60	-	-	-	0.690	-	0.020
3347	5015.60	-	-	-	0.690	-	0.019

Continued on next page

Table 14 – continued from previous page - IEEE8500 - n3637

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
3348	5015.60	-	-	-	0.690	-	0.020
3349	5015.60	-	-	-	0.690	-	0.020
3350	5015.60	-	-	-	0.690	-	0.033
3351	5015.60	-	-	-	0.690	-	0.033
3352	5015.60	-	-	-	0.690	-	0.032
3353	5015.60	-	-	-	0.690	-	0.032
3354	5015.60	-	-	-	0.690	-	0.033
3355	5015.60	-	-	-	0.690	-	0.041
3356	5015.60	-	-	-	0.690	-	0.041
3357	5015.60	-	-	-	0.690	-	0.042
3358	5015.60	-	-	-	0.690	-	0.041
3359	5015.60	-	-	-	0.690	-	0.041
3360	5015.60	-	-	-	0.690	-	0.032
3361	5015.60	-	-	-	0.690	-	0.031
3362	5015.60	-	-	-	0.690	-	0.032
3363	5015.60	-	-	-	0.690	-	0.033
3364	5015.60	-	-	-	0.690	-	0.022
3365	5015.60	-	-	-	0.690	-	0.020
3366	5015.60	-	-	-	0.690	-	0.020
3367	5015.60	-	-	-	0.690	-	0.019
3368	5015.60	-	-	-	0.690	-	0.019
3369	5015.60	-	-	-	0.690	-	0.020
3370	5015.60	-	-	-	0.690	-	0.019
3371	5015.60	-	-	-	0.690	-	0.019
3372	5015.60	-	-	-	0.690	-	0.020
3373	5015.60	-	-	-	0.690	-	0.020
3374	5015.60	-	-	-	0.690	-	0.020
3375	5015.60	-	-	-	0.690	-	0.020
3376	5015.60	-	-	-	0.690	-	0.030
3377	5015.60	-	-	-	0.690	-	0.031
3378	5015.60	-	-	-	0.690	-	0.038
3379	5015.60	-	-	-	0.690	-	0.039
3380	5015.60	-	-	-	0.690	-	0.038
3381	5015.60	-	-	-	0.690	-	0.031
3382	5015.60	-	-	-	0.690	-	0.030
3383	5015.60	-	-	-	0.690	-	0.021
3384	5015.60	-	-	-	0.550	-	0.018
3385	5015.60	-	-	-	0.550	-	0.017
3386	5015.60	-	-	-	0.500	-	0.019
3387	5015.60	-	-	-	0.500	-	0.018
3388	5015.60	-	-	-	0.500	-	0.017
3389	5015.60	-	-	-	0.500	-	0.016
3390	5015.60	-	-	-	0.500	-	0.016
3391	5015.60	-	-	-	0.500	-	0.016
3392	5015.60	-	-	-	0.500	-	0.016
3393	5015.60	-	-	-	0.500	-	0.016
3394	5015.60	-	-	-	0.500	-	0.016
3395	5015.60	-	-	-	0.500	-	0.016
3396	5015.60	-	-	-	0.500	-	0.016
3397	5015.60	-	-	-	0.500	-	0.016
3398	5015.60	-	-	-	0.500	-	0.016
3399	5015.60	-	-	-	0.460	-	0.015

Continued on next page

Table 14 – continued from previous page - IEEE8500 - n3637

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
3400	5015.60	-	-	-	0.460	-	0.015
3401	5015.60	-	-	-	0.460	-	0.015
3402	5015.60	-	-	-	0.460	-	0.015
3403	5015.60	-	-	-	0.430	-	0.014
3404	5015.60	-	-	-	0.420	-	0.014
3405	5015.60	-	-	-	0.390	-	0.014
3406	5015.60	-	-	-	0.390	-	0.013
3407	5015.60	-	-	-	0.390	-	0.013
3408	5015.60	-	-	-	0.390	-	0.013
3409	5015.60	-	-	-	0.390	-	0.013
3410	5015.60	-	-	-	0.380	-	0.013
3411	5015.60	-	-	-	0.350	-	0.010
3412	5015.60	-	-	-	0.350	-	0.010
3413	5015.60	-	-	-	0.350	-	0.010
3414	5015.60	-	-	-	0.350	-	0.010
3415	5015.60	-	-	-	0.320	-	0.009
3416	5015.60	-	-	-	0.320	-	0.009
3417	5015.60	-	-	-	0.280	-	0.008
3418	5015.60	-	-	-	0.280	-	0.006
3419	5015.60	-	-	-	0.280	-	0.006
3420	5015.60	-	-	-	0.280	-	0.005
3421	5015.60	-	-	-	0.280	-	0.005
3422	5015.60	-	-	-	0.290	-	0.004
3423	5015.60	-	-	-	0.280	-	0.004
3424	5015.60	-	-	-	0.280	-	0.005
3425	5015.60	-	-	-	0.280	-	0.005
3426	5015.60	-	-	-	0.280	-	0.005
3427	5015.60	-	-	-	0.280	-	0.004
3428	5015.60	-	-	-	0.280	-	0.004
3429	5015.60	-	-	-	0.280	-	0.004
3430	5015.60	-	-	-	0.280	-	0.004
3431	5015.60	-	-	-	0.280	-	0.005
3432	5015.60	-	-	-	0.280	-	0.005
3433	5015.60	-	-	-	0.280	-	0.004
3434	5015.60	-	-	-	0.280	-	0.004
3435	5015.60	-	-	-	0.280	-	0.005
3436	5015.60	-	-	-	0.280	-	0.005
3437	5015.60	-	-	-	0.260	-	0.004
3438	5015.60	-	-	-	0.250	-	0.004
3439	5015.60	-	-	-	0.220	-	0.003
3440	5015.60	-	-	-	0.220	-	0.001
3441	5015.60	-	-	-	0.220	-	0.001
3442	5015.60	-	-	-	0.180	-	0.001
3443	5015.60	-	-	-	0.180	-	0.001
3444	5015.60	-	-	-	0.180	-	0.001
3445	5015.60	-	-	-	0.180	-	0.001
3446	5015.60	-	-	-	0.180	-	0.001
3447	5015.60	-	-	-	0.180	-	0.001
3448	5015.60	-	-	-	0.180	-	0.001
3449	5015.60	-	-	-	0.180	-	0.001
3450	5015.60	-	-	-	0.180	-	0.001
3451	5015.60	-	-	-	0.180	-	0.001

Continued on next page

Table 14 – continued from previous page - IEEE8500 - n3637

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
3452	5015.60	-	-	-	0.180	-	0.001
3453	5015.60	-	-	-	0.180	-	0.001
3454	5015.60	-	-	-	0.180	-	0.001
3455	5015.60	-	-	-	0.180	-	0.001
3456	5015.60	-	-	-	0.190	-	0.001
3457	5015.60	-	-	-	0.190	-	0.001
3458	5015.60	-	-	-	0.190	-	0.001
3459	5015.60	-	-	-	0.190	-	0.001
3460	5015.60	-	-	-	0.180	-	0.001
3461	5015.60	-	-	-	0.150	-	0.001
3462	5015.60	-	-	-	0.150	-	0.001
3463	5015.60	-	-	-	0.150	-	0.001
3464	5015.60	-	-	-	0.150	-	0.001
3465	5015.60	-	-	-	0.150	-	0.001
3466	5015.60	-	-	-	0.150	-	0.001
3467	5015.60	-	-	-	0.150	-	0.001
3468	5015.60	-	-	-	0.150	-	0.001
3469	5015.60	-	-	-	0.150	-	0.001
3470	5015.60	-	-	-	0.150	-	0.001
3471	5015.60	-	-	-	0.150	-	0.001
3472	5015.60	-	-	-	0.150	-	0.001
3473	5015.60	-	-	-	0.150	-	0.001
3474	5015.60	-	-	-	0.150	-	0.001
3475	5015.60	-	-	-	0.150	-	0.001
3476	5015.60	-	-	-	0.150	-	0.001
3477	5015.60	-	-	-	0.150	-	0.001
3478	5015.60	-	-	-	0.150	-	0.001
3479	5015.60	-	-	-	0.150	-	0.001
3480	5015.60	-	-	-	0.150	-	0.001
3481	5015.60	-	-	-	0.150	-	0.001
3482	5015.60	-	-	-	0.150	-	0.001
3483	5015.60	-	-	-	0.150	-	0.001
3484	5015.60	-	-	-	0.150	-	0.001
3485	5015.60	-	-	-	0.150	-	0.001
3486	5015.60	-	-	-	0.150	-	0.001
3487	5015.60	-	-	-	0.150	-	0.001
3488	5015.60	-	-	-	0.150	-	0.001
3489	5015.60	-	-	-	0.150	-	0.001
3490	5015.60	-	-	-	0.150	-	0.001
3491	5015.60	-	-	-	0.150	-	0.001
3492	5015.60	-	-	-	0.150	-	0.001
3493	5015.60	-	-	-	0.160	-	0.001
3494	5015.60	-	-	-	0.150	-	0.001
3495	5015.60	-	-	-	0.150	-	0.001
3496	5015.60	-	-	-	0.160	-	0.001
3497	5015.60	-	-	-	0.160	-	0.001
3498	5015.60	-	-	-	0.160	-	0.001
3499	5015.60	-	-	-	0.160	-	0.001
3500	5015.60	-	-	-	0.160	-	0.001
3501	5015.60	-	-	-	0.160	-	0.001
3502	5015.60	-	-	-	0.160	-	0.001
3503	5015.60	-	-	-	0.160	-	0.001

Continued on next page

Table 14 – continued from previous page - IEEE8500 - n3637

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
3504	5015.60	-	-	-	0.160	-	0.001
3505	5015.60	-	-	-	0.160	-	0.001
3506	5015.60	-	-	-	0.160	-	0.001
3507	5015.60	-	-	-	0.160	-	0.001
3508	5015.60	-	-	-	0.160	-	0.001
3509	5015.60	-	-	-	0.160	-	0.001
3510	5015.60	-	-	-	0.160	-	0.001
3511	5015.60	-	-	-	0.160	-	0.001
3512	5015.60	-	-	-	0.160	-	0.001
3513	5015.60	-	-	-	0.150	-	0.001
3514	5015.60	-	-	-	0.130	-	0.000
3515	5015.60	-	-	-	0.130	-	0.000
3516	5015.60	-	-	-	0.130	-	0.000
3517	5015.60	-	-	-	0.130	-	0.000
3518	5015.60	-	-	-	0.110	-	0.000
3519	5015.60	-	-	-	0.100	-	0.000
3520	5015.60	-	-	-	0.080	-	0.000
3521	5015.60	-	-	-	0.080	-	0.000
3522	5015.60	-	-	-	0.080	-	0.000
3523	5015.60	-	-	-	0.080	-	0.000
3524	5015.60	-	-	-	0.080	-	0.000
3525	5015.60	-	-	-	0.060	-	0.000
3526	5015.60	-	-	-	0.060	-	0.000
3527	5015.60	-	-	-	0.060	-	0.000
3528	5015.60	-	-	-	0.060	-	0.000
3529	5015.60	-	-	-	0.060	-	0.000
3530	5015.60	-	-	-	0.060	-	0.000
3531	5015.60	-	-	-	0.060	-	0.000
3532	5015.60	-	-	-	0.060	-	0.000
3533	5015.60	-	-	-	0.060	-	0.000
3534	5015.60	-	-	-	0.060	-	0.000
3535	5015.60	-	-	-	0.060	-	0.000
3536	5015.60	-	-	-	0.060	-	0.000
3537	5015.60	-	-	-	0.060	-	0.000
3538	5015.60	-	-	-	0.040	-	0.000
3539	5015.60	-	-	-	0.040	-	0.000
3540	5015.60	-	-	-	0.040	-	0.000
3541	5015.60	-	-	-	0.040	-	0.000
3542	5015.60	-	-	-	0.040	-	0.000
3543	5015.60	-	-	-	0.040	-	0.000
3544	5015.60	-	-	-	0.040	-	0.000
3545	5015.60	-	-	-	0.040	-	0.000
3546	5015.60	-	-	-	0.040	-	0.000
3547	5015.60	-	-	-	0.040	-	0.000
3548	5015.60	-	-	-	0.040	-	0.000
3549	5015.60	-	-	-	0.040	-	0.000
3550	5015.60	-	-	-	0.040	-	0.000
3551	5015.60	-	-	-	0.040	-	0.000
3552	5015.60	-	-	-	0.040	-	0.000
3553	5015.60	-	-	-	0.040	-	0.000
3554	5015.60	-	-	-	0.040	-	0.000
3555	5015.60	-	-	-	0.040	-	0.000

Continued on next page

Table 14 – continued from previous page - IEEE8500 - n3637

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
3556	5015.60	-	-	-	0.040	-	0.000
3557	5015.60	-	-	-	0.040	-	0.000
3558	5015.60	-	-	-	0.040	-	0.000
3559	5015.60	-	-	-	0.040	-	0.000
3560	5015.60	-	-	-	0.040	-	0.000
3561	5015.60	-	-	-	0.040	-	0.000
3562	5015.60	-	-	-	0.040	-	0.000
3563	5015.60	-	-	-	0.040	-	0.000
3564	5015.60	-	-	-	0.040	-	0.000
3565	5015.60	-	-	-	0.040	-	0.000
3566	5015.60	-	-	-	0.040	-	0.000
3567	5015.60	-	-	-	0.040	-	0.000
3568	5015.60	-	-	-	0.040	-	0.000
3569	5015.60	-	-	-	0.040	-	0.000
3570	5015.60	-	-	-	0.040	-	0.000
3571	5015.60	-	-	-	0.040	-	0.000
3572	5015.60	-	-	-	0.040	-	0.000
3573	5015.60	-	-	-	0.040	-	0.000
3574	5015.60	-	-	-	0.040	-	0.000
3575	5015.60	-	-	-	0.040	-	0.000
3576	5015.60	-	-	-	0.040	-	0.000
3577	5015.60	-	-	-	0.040	-	0.000
3578	5015.60	-	-	-	0.040	-	0.000
3579	5015.60	-	-	-	0.040	-	0.000
3580	5015.60	-	-	-	0.040	-	0.000
3581	5015.60	-	-	-	0.040	-	0.000
3582	5015.60	-	-	-	0.040	-	0.000
3583	5015.60	-	-	-	0.040	-	0.000
3584	5015.60	-	-	-	0.040	-	0.000
3585	5015.60	-	-	-	0.040	-	0.000
3586	5015.60	-	-	-	0.040	-	0.000
3587	5015.60	-	-	-	0.040	-	0.000
3588	5015.60	-	-	-	0.040	-	0.000
3589	5015.60	-	-	-	0.040	-	0.000
3590	5015.60	-	-	-	0.040	-	0.000
3591	5015.60	-	-	-	0.040	-	0.000
3592	5015.60	-	-	-	0.040	-	0.000
3593	5015.60	-	-	-	0.040	-	0.000
3594	5015.60	-	-	-	0.040	-	0.000
3595	5015.60	-	-	-	0.040	-	0.000
3596	5015.60	-	-	-	0.040	-	0.000
3597	5015.60	-	-	-	0.040	-	0.000
3598	5015.60	-	-	-	0.040	-	0.000
3599	5015.60	-	-	-	0.040	-	0.000
3600	5015.60	-	-	-	0.040	-	0.000
3601	5015.60	-	-	-	0.040	-	0.000
3602	5015.60	-	-	-	0.040	-	0.000
3603	5015.60	-	-	-	0.040	-	0.000
3604	5015.60	-	-	-	0.040	-	0.000
3605	5015.60	-	-	-	0.040	-	0.000
3606	5015.60	-	-	-	0.040	-	0.000
3607	5015.60	-	-	-	0.040	-	0.000

Continued on next page

Table 14 – continued from previous page - IEEE8500 - n3637

		Time (sec)					
m	**best ENS**	**ILP-GALIAS**	**ILP-IFLOWS**	**DP-TS**	**DP-N2M2**	**ILP-CUTS**	**DP-PC**
3608	5015.60	-	-	-	0.040	-	0.000
3609	5015.60	-	-	-	0.040	-	0.000
3610	5015.60	-	-	-	0.040	-	0.000
3611	5015.60	-	-	-	0.040	-	0.000
3612	5015.60	-	-	-	0.040	-	0.000
3613	5015.60	-	-	-	0.040	-	0.000
3614	5015.60	-	-	-	0.040	-	0.000
3615	5015.60	-	-	-	0.040	-	0.000
3616	5015.60	-	-	-	0.040	-	0.000
3617	5015.60	-	-	-	0.040	-	0.000
3618	5015.60	-	-	-	0.040	-	0.000
3619	5015.60	-	-	-	0.040	-	0.000
3620	5015.60	-	-	-	0.020	-	0.000
3621	5015.60	-	-	-	0.020	-	0.000
3622	5015.60	-	-	-	0.020	-	0.000
3623	5015.60	-	-	-	0.020	-	0.000
3624	5015.60	-	-	-	0.020	-	0.000
3625	5015.60	-	-	-	0.020	-	0.000
3626	5015.60	-	-	-	0.010	-	0.000
3627	5015.60	-	-	-	0.010	-	0.000
3628	5015.60	-	-	-	0.010	-	0.000
3629	5015.60	-	-	-	0.010	-	0.000
3630	5015.60	-	-	-	0.010	-	0.000
3631	5015.60	-	-	-	0.010	-	0.000
3632	5015.60	-	-	-	0.000	-	0.000
3633	5015.60	-	-	-	0.000	-	0.000
3634	5015.60	-	-	-	0.000	-	0.000
3635	5015.60	-	-	-	0.000	-	0.000
3636	5015.60	-	-	-	0.000	-	0.000
Total		**7886.00**	**7518.44**	**7211.02**	**5857.92**	**7217625.76**	**17708.39**