

Modern C++ Programming

4. UTILITIES

Federico Busato

University of Verona, Dept. of Computer Science
2018, v1.0



Agenda

- **I/O Stream**

- Manipulators
- Filestream
(ifstream/ofstream)

- **Math Functions**

- CMath library
- Numerical limits
- Integer division

- **Algorithm Library**

- **String**

- Methods
- Operators
- Conversion

- **Random Numbers**

- Period and quality
- Engines
- Distributions

- **Time Measuring**

- Wall-clock time
- User time
- System time

some usefull details about outout stream (I/O Stream manipulator):

- `flush` flushes the output stream `cout << flush;`
- `endl` shortcut for `cout << "\n" << flush;`
- `flush` and `endl` force the program to synchronize with the terminal → very slow operation!
- **Set integral representation:** default: dec

```
cout << dec << 0xF; prints 16
```

```
cout << hex << 16; prints 0xF
```

```
cout << oct << 8; prints 10
```

Print the underlying **bit representation** of a value:

```
#include <bitset>

std::cout << std::bitset<32>(3.45f); // (32: num. of bits)
// print 01000000010111001100110011001101
```

- **Print true/false text:**

```
cout << boolalpha << 1; prints true
```

```
cout << boolalpha << 0; prints false
```

```
#include <iomanip>
```

- **Set decimal precision:** default: 6

```
cout << setprecision(2) << 3.538; → 3.54
```

- **Set float representation:** default: `std::defaultfloat`

```
cout << setprecision(2) << fixed << 32.5; → 32.50
```

```
cout << setprecision(2) << scientific << 32.5; → 3.25e+01
```

- **Set alignment:** default: `right`

```
cout << right << setw(7) << "abc" << "##"; → ____abc##
```

```
cout << left << setw(7) << "abc" << "##"; → abc____##
```

(better than using `tab \t`)

I/O Stream (std::cin)

`std::cin` is an example of *input* stream. Data coming from a source is read by the program. In this example `cin` is the standard input

```
#include <iostream>

int main() {
    int a;
    std::cout << "Please enter an integer value:" << endl;
    std::cin >> a;

    int b;
    float c;
    std::cout << "Please enter an integer value "
               << "followed by a float value:" << endl;
    std::cin >> b >> c; // read an integer and store into "b",
                        // then read a float value, and store
                        // into "c"
}
```

`ifstream`, `ofstream` are output and input stream too

```
#include <fstream>
```

- **Open a file for reading**

Open a file in input mode: `ifstream my_file("example.txt")`

- **Open a file for writing**

Open a file in output mode: `ofstream my_file("example.txt")`

Open a file in append mode:

```
ofstream my_file("example.txt", ios::out | ios::app)
```

- **Read a line** `getline(my_file, string)`

- **Close a file** `my_file.close()`

- **Check the stream integrity** `my_file.good()`

- **Peek the next character**

```
char current_char = my_file.peek()
```

- **Get the next character (and advance)**

```
char current_char = my_file.get()
```

- **Get the position of the current character in the input stream**

```
int byte_offset = my_file.tellg()
```

- **Set the char position in the input sequence**

```
my_file.seekg(byte_offset) (absolute position)
```

```
my_file.seekg(byte_offset, position) (relative position)
```

where position can be:

<code>ios::beg</code>	(the begin),	<code>ios::end</code>	(the end),
<code>ios::cur</code>	(current position)		

- **Ignore characters until the delimiter is found**

```
my_file.ignore(max_stream_size, <delim>)
```

e.g. skip until end of line `\n`

- **Get a pointer to the stream buffer object currently associated with the stream**

```
my_file.rdbuf()
```

can be used to redirect file stream

Open a file and print line by line:

```
#include <iostream>
#include <fstream>

int main() {
    std::ifstream fin("example.txt");
    std::string str;
    while (fin.good()) {
        std::getline(fin, str);
        std::cout << str << "\n";
    }
    fin.close();
}
```

An alternative version with redirection:

```
#include <iostream>
#include <fstream>

int main() {
    std::ifstream fin("example.txt");
    std::cout << fin.rdbuf();
    fin.close();
}
```

example.txt:

```
23_70__44\n
\t57\t89
```

The input stream is independent from the type of space (multiple space, tab, newline `\n`, `\r\n`, etc.)

Another example:

```
#include <iostream>
#include <fstream>

int main() {
    std::ifstream fin("example.txt");
    char c = fin.peek(); // c = '2'
    while (fin.good()) {
        int var;
        fin >> var;
        std::cout << var;
    }           // print 2370445789
    fin.seekg(4);
    c = fin.peek(); // c = '0'
    fin.close();
}
```

Check if a file is a **regular file** and can be read/written (it exists, it is not a directory, it is not a device, you have read/write permissions, etc.)

```
#include <sys/types.h>
#include <sys/stat.h>
bool checkRegularFile(const char* file_path) {
    struct stat info;
    if (::stat( file_path, &info ) != 0)
        return false;           // unable to access
    if (info.st_mode & S_IFDIR)
        return false;           // is a directory
    std::ifstream fin(file_path); // additional checking
    if (!fin.is_open() || !fin.good())
        return false;
    try {                        // try to read
        char c; fin >> c;
    } catch (std::ios_base::failure&) {
        return false;
    }
    return true;
}
```

Get the **file size** in bytes in a **portable** way:

```
long long int fileSize(const char* file_path) {  
    std::ifstream fin(file_path);    // open the file  
    fin.seekg(0, ios::beg);          // move to the first byte  
    std::istream::pos_type start_pos = fin.tellg();  
                                     // get the start offset  
    fin.seekg(0, ios::end);          // move to the last byte  
    std::istream::pos_type end_pos = fin.tellg();  
                                     // get the end offset  
    return end_pos - start_pos;      // position difference  
}
```

Math Functions

```
#include <cmath>
using namespace std;
```

- `fabs(x)` computes absolute value, $|x|$, C++11
- `exp(x)` returns e raised to the given power, e^x
- `exp2(x)` returns 2 raised to the given power, 2^x , C++11
- `log(x)` computes natural (base e) logarithm, $\log_e(x)$
- `log10(x)` computes base 10 logarithm, $\log_{10}(x)$
- `log2(x)` computes base 2 logarithm, $\log_2(x)$, C++11
- `pow(x, y)` raises a number to the given power, x^y
- `sqrt(x)` computes square root, \sqrt{x}

- `cqrt(x)` computes cubic root, $\sqrt[3]{x}$, C++11
- `sin(x)` computes sine, $\sin(x)$
- `cos(x)` computes cosine, $\cos(x)$
- `tan(x)` computes tangent, $\tan(x)$
- `ceil(x)` nearest integer not less than the given value, $\lceil x \rceil$
- `floor(x)` nearest integer not greater than the given value, $\lfloor x \rfloor$
- `round|lround|llround(x)` nearest integer, $\lfloor x + \frac{1}{2} \rfloor$
(return type: floating point, long, long long respectively)

Math functions in C++11 can be applied directly to integral types without implicit/explicit casting (return type: floating point).

Full list: en.cppreference.com/w/cpp/numeric/math

Numerical Limits

Get numeric limits of a given type: C++11

```
#include <limits>
using namespace std;
```

```
T numeric_limits<T>::max() // returns the maximum finite value
                          // representable by the numeric type T

T numeric_limits<T>::min() // returns the minimum finite value
                          // representable by the numeric type T

T numeric_limits<T>::lowest() // returns the lowest finite value
                              // representable by the numeric type T
```


Integer Division

Integer ceiling division and rounded division:

- **Ceiling Division:** $\left\lceil \frac{\text{value}}{\text{div}} \right\rceil$

```
unsigned ceil_div(unsigned value, unsigned div) {  
    return (value + div - 1) / div;  
} // note: may overflow
```

- **Rounded Division:** $\left\lfloor \frac{\text{value}}{\text{div}} + \frac{1}{2} \right\rfloor$

```
unsigned round_div(unsigned value, unsigned div) {  
    return (value + div / 2) / div;  
} // note: may overflow
```

Algorithm Library

std algorithms can be applied to **any objects** (see next lectures). In these slides, we focus on primitives types and array only

```
#include <algorithm>
```

- `swap(value1, value2)` Swaps the values of two objects
- `min(x, y)` Finds the minimum value between x and y
- `max(x, y)` Finds the maximum value between x and y
- `min_element(begin, end)` (returns a pointer)
Finds the minimum element in the range [begin, end)
- `max_element(begin, end)` (returns a pointer)
Finds the maximum element in the range [begin, end)
- `minmax_element(begin, end)` C++11 (returns pointers <min,max>)
Finds the minimum and the maximum element in the range [begin, end)

- `equal(begin1, end1, begin2)`
Determines if two sets of elements are the same in
[begin1, end1), [begin2, begin2 + end1 - begin1)
- `mismatch(begin1, end1, begin2)` (returns pointers <pos1,pos2>)
Finds the first position where two ranges differ in
[begin1, end1), [begin2, begin2 + end1 - begin1)
- `find(begin, end, value)` (returns a pointer)
Finds the first element in the range [begin, end) equal to value
- `count(begin, end, value)`
Counts the number of elements in the range [begin, end) equal to value

- `sort(begin, end)` (in-place)
Sorts the elements in the range `[begin, end)` in ascending order
- `merge(begin1, end1, begin2, end2, output)`
Merges two sorted ranges `[begin1, end1)`, `[begin2, end2)`, and store the results in `[output, output + end1 - start1)`
- `unique(begin, end)` (in-place)
Removes consecutive duplicate elements in the range `[begin, end)`
- `binary_search(begin, end, value)`
Determines if an element value exists in the (sorted) range `[begin, end)`
- `accumulate(begin, end, value)`
Sums up the range `[begin, end)` of elements with initial value (common case equal to zero)
- `partial_sum(begin, end)` (in-place)
Computes the inclusive prefix-sum of the range `[begin, end)`

- `fill(begin, end, value)`
Fills a range of elements `[begin, end)` with `value`
- `iota(begin, end, value)` C++11
Fills the range `[begin, end)` with successive increments of the starting `value`
- `copy(begin1, end1, begin2)`
Copies the range of elements `[begin1, end1)` to the new location `[begin2, begin2 + end1 - begin1)`
- `swap_ranges(begin1, end1, begin2)`
Swaps two ranges of elements `[begin1, end1)`, `[begin2, begin2 + end1 - begin1)`
- `remove(begin, end, value)` (in-place)
Removes elements equal to `value` in the range `[begin, end)`

- `includes(begin1, end1, begin2, end2)`
Checks if the (sorted) set `[begin1, end1)` is a subset of `[begin2, end2)`
- `set_difference(begin1, end1, begin2, end2, output)`
Computes the difference between two (sorted) sets
- `set_intersection(begin1, end1, begin2, end2, output)`
Computes the intersection of two (sorted) sets
- `set_symmetric_difference(begin1, end1, begin2, end2, output)`
Computes the symmetric difference between two (sorted) sets
- `set_union(begin1, end1, begin2, end2, output)`
Computes the union of two (sorted) sets
- `make_heap(begin, end)` Creates a max heap out of the range of elements
- `push_heap(begin, end)` Adds an element to a max heap
- `pop_heap(begin, end)` Remove an element (top) to a max heap

```
#include <algorithm>
using namespace std;

int a = max(2, 5); // a = 5
int array1[] = {7, 6, -1, 6, 3};
int array2[] = {8, 2, 0, 3, 7};

int b = *max_element(array1, array1 + 5); // b = 7
auto c = minmax_element(array1, array1 + 5);
//c.first = -1, c.second = 7
bool d = equal(array1, array1 + 5, array2); // d = false

sort(array1, array1 + 5); // [-1, 3, 6, 6, 7]
unique(array1, array1 + 5); // [-1, 3, 6, 7]
int e = accumulate(array1, array1 + 5, 0); // 15
partial_sum(array1, array1 + 5); // [-1, 2, 8, 15]
iota(array1, array1 + 5, 2); // [2, 3, 4, 5, 6]
make_heap(array2, array2 + 5); // [8, 7, 0, 3, 2]
```


String

String

C++ Strings are wrappers of character sequences

More flexible and safer than raw char array but can be slower

```
#include <string>

int main() {
    std::string a;           // empty string
    std::string b("first");

    using namespace std::string_literals; // C++14
    std::string c = "second"s;           // C++14
}
```

- `empty()` returns `true` if the string is empty, `false` otherwise
- `size()` returns the number of characters in the string
- `find(string)` returns the position of the first substring equal to the given character sequence or `npos` if no substring is found
- `rfind(string)` returns the position of the last substring equal to the given character sequence or `npos` if no substring is found
- `find_first_of(char_seq)` returns the position of the first character equal to one of the characters in the given character sequence or `npos` if no characters is found
- `find_last_of(char_seq)` returns the position of the last character equal to one of the characters in the given character sequence or `npos` if no characters is found

`npos` special value returned by string methods

- `new_string substr(start_pos)`
returns a substring `[start_pos, end]`
`new_string substr(start_pos, count)`
returns a substring `[start_pos, start_pos + count)`
- `clear()` removes all characters from the string
- `erase(pos)` removes the character at position
`erase(start_pos, count)`
removes the characters at positions `[start_pos, start_pos + count)`
- `replace(start_pos, count, new_string)`
replaces the part of the string indicated by `[start_pos, start_pos + count)`
with `new_string`
- `c_str()`
returns a pointer to the raw char sequence

- **access specified character** `string1[i]`
- **string copy** `string1 = string2`
- **string compare** `string1 == string2`
works also with `!=, <, ≤, >, ≥`
- **concatenate two strings**
`string_concat = string1 + string2`
- **append characters to the end** `string1 += string2`

Converts a string to a numeric value C++11:

- `stoi(string)` string to signed integer
- `stol(string)` string to long signed integer
- `stoul(string)` string to long unsigned integer
- `stoull(string)` string to long long unsigned integer
- `stof(string)` string to floating point value (float)
- `stod(string)` string to floating point value (double)
- `stold(string)` string to floating point value (long double)

Converts a numeric value to a string C++11:

- `to_string(numeric_value)` numeric value to string

```
std::string str("si vis pacem para bellum");

cout << str.size();           // print 24
cout << str.find("vis");      // print 3
cout << str.find_last_of("bla"); // print 21, 'l' found

cout << str.substr(7, 5); // print "pacem", pos=7 and count=5
cout << str[1];           // print 'i'
cout << (str == "vis");    // print false
cout << (str < "z");       // print true
const char* raw_str = str.c_str();

cout << string("a") + "b";    // print "ab"
cout << string("ab").erase(0); // print 'b'

char*      str2 = "34";
int        a    = std::stoi(str2); // a = 34;
std::string str3 = std::to_string(a); // str3 = "34"
```

- Conversion from integer to char letter (e.g. $3 \rightarrow 'C'$):

```
static_cast<char>('A' + value)
```

$value \in [0, 26]$ (English alphabet)

- Conversion from char to integer (e.g. $'C' \rightarrow 3$):

```
value - 'A'
```

$value \in [0, 26]$

- Conversion from digit to char number (e.g. $3 \rightarrow '3'$):

```
static_cast<char>('0' + value)
```


$value \in [0, 9]$

- char to string `std::string(1, char_value)`

Random Number



www.dilbert.com
scottadams@aol.com



© 2001 United Feature Syndicate, Inc.



The problem:

C rand() function produces poor quality random numbers

- C++14 discourage the use of rand() and srand()

C++11 introduces pseudo random number generation (PRNG) facilities to produce random numbers by using combinations of generators and distributions

A random generator requires four steps:

(1) **Select the seed**

(2) **Define the random engine**

```
<type_of_random_engine> generator(seed)
```

(3) **Define the distribution**

```
<type_of_distribution> distribution(range_start, range_end)
```

(4) **Produce the random number**

```
distribution(generator)
```

Simplest example:

```
#include <iostream>
#include <random>

int main() {
    unsigned seed = ...;
    std::default_random_engine generator(seed);
    std::uniform_int_distribution<int> distribution(0, 9);
    std::cout << std::distribution(generator);
                // first random number
    std::cout << std::distribution(generator);
                // second random number
}
```

It generates two random integer numbers in the range $[0, 9]$ by using the default random engine

Given a **seed**, the generator produces always the **same sequence**

The seed should be selected randomly by using the actual time:

```
#include <random>
#include <chrono>

int main() {
    unsigned seed = std::chrono::system_clock::now()
                    .time_since_epoch().count();
    std::default_random_engine generator(seed);
}
```

`chrono::system_clock::now()` return an object representing the current point in time

`.time_since_epoch().count()` returns the count of ticks that have elapsed since January 1, 1970 (midnight UTC/GMT)

Pseudorandom Number Generator (PRNG)

PRNG Period

The period (or cycle length) of a PRNG is the length of the sequence of numbers that the PRNG generates before repeating.

PRNG Quality

(informal) If it's hard to distinguish a generator's output from truly random sequences we call it a high quality generator. If it's easy, we call it a low quality generator.

Generator	Quality	Period	Performance
Linear congruential	Poor	10^9	fast
Mersenne Twister	High	10^{6000}	good
Subtract-with-carry	Highest	10^{171}	slow

Random Engines

- **Default random engine** Implementation defined
- **Linear congruential** The simplest generator engine. It implements the following transition algorithm:

$$x_{i+1} = (\alpha x_i + c) \bmod m$$

where α, c, m are implementation defined

The generator has a period of m , where m is $2^{31} - 1$

- **Mersenne Twister** (*M. Matsumoto and T. Nishimura, 1997*)
Fast generation of high-quality pseudorandom number. It relies on Mersenne prime number. (used as default random generator in linux)
The generator `mt19937`, `mt19937_64` has a period of $2^{(n-1)*w} - 1$, where w is 32 and n is 624, $\approx 10^{6000}$
- **Subtract-with-carry** (*G. Marsaglia and A. Zaman, 1991*)
Pseudo-random generation based on Lagged Fibonacci algorithm (used for example by physicists at CERN)
The generator `ranlux24_base`/`ranlux48_base` have a period of 10^{171}

Distribution

Common distributions:

- **Uniform random**

```
uniform_int_distribution<T>(range_start, range_end)
```

where T is integral type

```
uniform_real_distribution<T>(range_start, range_end)
```

where T is floating point type

- **Normal distribution** $P(x) = \frac{1}{\sigma\sqrt{2\pi}} e^{-\frac{(x-\mu)^2}{2\sigma^2}}$

```
normal_distribution<T>(mean, std_dev)
```

where T is floating point type

- **Exponential distribution** $P(x, \lambda) = \lambda e^{-\lambda x}$

```
exponential_distribution<T>(lambda)
```

where T is floating point type

Examples

```
unsigned seed = chrono::system_clock::now()
                .time_since_epoch().count();

minstd_rand0    lc1_generator(seed);  // original linear congruential
minstd_rand     lc2_generator(seed);  // linear congruential (better tuning)
mt19937         mt_generator(seed);   // standard mersenne twister (32-bit)
mt19937_64      mt64_generator(seed); // standard mersenne twister (64-bit)
ranlux24_base   swc24_generator(seed); // subtract with carry (24-bit)
ranlux48_base   swc48_generator(seed); // subtract with carry (48-bit)

uniform_int_distribution<int>    int_distribution(0, 10);
uniform_real_distribution<float> real_distribution(-3.0f, 4.0f);
exponential_distribution<float>  exp_distribution(3.5f);
normal_distribution<double>      norm_distribution(5.0, 2.0);

lc1_generator.discart(10);  // advances the internal state by 10 times
// i.e. the sequence start point is equal to apply distribution() 10 times
```

Time Measuring

Wall-Clock/Real time

It is the human perception of the passage of time from the start to the completion of a task

User/CPU time

The amount of time spent by the CPU to compute in user code

System time

The amount of time spent by the CPU to compute system calls (including I/O calls) executed into kernel code

Note: if the system workload (except the current program) is very low and the program uses only one thread then

Wall-clock time = User time + System time

`::gettimeofday()` (linux, not portable)

```
#include <time.h>      //struct timeval
#include <sys/time.h> //gettimeofday()
#include <iostream>

int main() {
    struct timeval start, end; // timeval {second, microseconds}
    ::gettimeofday(&start, NULL);
    ...    // code
    ::gettimeofday(&end, NULL);

    long start_time = start.tv_sec * 1000000 + start.tv_usec;
    long end_time   = end.tv_sec * 1000000 + end.tv_usec;
    std::cout << "Elapsed: " << end_time - start_time;
}                // in microsec
```

Problems: not portable, the time is not monotonic increasing (timezone)

`std::chrono` C++11

```
#include <iostream>
#include <chrono>

int main() {
    auto start_time = std::chrono::system_clock::now();
    ... // code
    auto end_time    = std::chrono::system_clock::now();

    std::chrono::duration<double> diff = end_time - start_time;
    cout << "Elapsed: " << diff.count(); // in seconds
    cout << std::chrono::duration_cast<milli>(diff).count();
}
    // in ms
```

Problems: The time is not monotonic increasing (timezone)

An alternative of `system_clock` is `steady_clock` which ensures monotonic increasing time

`std::clock`

```
#include <iostream>
#include <chrono>

int main() {
    clock_t start_time = std::clock();
    ... // code
    clock_t end_time    = std::clock();

    float diff = static_cast<float>(end_time - start_time)
                / CLOCKS_PER_SEC;
    cout << "Elapsed: " << diff; // in seconds
}
```

`::times` (linux)

```
#include <iostream>
#include <sys/times.h>

int main() {
    struct ::tms start_time, end_time;
    ::times(&start_time);
    ... // code
    ::times(&end_time);

    auto user_diff = end_time.tmus_utime - start_time.tms_utime;
    auto sys_diff  = end_time.tms_stime - start_time.tms_stime;
    float user = static_cast<float>(user_diff) / ::sysconf(_SC_CLK_TCK);
    float sys  = static_cast<float>(sys_diff) / ::sysconf(_SC_CLK_TCK);
    std::cout << "user time: " << user;    // in seconds
    std::cout << "system time: " << sys;    // in seconds
}
```