

# Package ‘PolyGIM’

May 6, 2023

**Type** Package

**Title** Integrative Analysis of Polytomous Individual-Level Data and Summary Statistics From Subtypes

**Version** 1.0.0

**Date** 2023-5-6

**Author** Sheng Fu, Kai Yu

**Maintainer** Sheng Fu <fusheng1007@gmail.com>

**Description** A procedure that integrates individual-level and summary data from multiple external binary logistic regression models to fit the polytomous logistic regression (PLR) model, enabling more efficient statistical inference.

**License** MIT + file LICENSE

**Encoding** UTF-8

**LazyData** true

**Imports** VGAM

**RoxygenNote** 7.2.3

## R topics documented:

PolyGIM-package . . . . .	1
data . . . . .	2
polygim_opt . . . . .	3
polygim_v . . . . .	3
<b>Index</b>	<b>5</b>

---

PolyGIM-package	<i>Improve the model of disease subtype heterogeneity by leveraging external summary data</i>
-----------------	---

---

## Description

This package proposes a generalized integration procedure that utilizes individual-level data and summary data from multiple binary logistic regression models obtained from external sources, in order to fit the polytomous logistic regression (PLR) model for more efficient statistical inference.

## Details

Researchers are often interested in understanding the disease subtype heterogeneity by testing whether a risk exposure has the same level of effect on different disease subtypes. The polytomous logistic regression (PLR) model provides a flexible tool for such an evaluation. Disease subtype heterogeneity can also be investigated with a case-only study that uses a case-case comparison procedure to directly assess the difference between risk effects on two disease subtypes. We develop PolyGIM, a procedure to fit the PLR model by integrating individual-level data with summary data extracted from multiple studies under different designs. The summary data consist of coefficient estimates from working logistic regression models established by external studies.

## Author(s)

Sheng Fu, Kai Yu

## References

Fu, S., Purdue M. P., Zhang H., Qin J., Song L., Berndt S. I., and Yu K. (2023) Improve the model of disease subtype heterogeneity by leveraging external summary data. Submitted

Zhang, H., Deng, L., Schiffman, M., Qin, J., Yu, K. (2020) Generalized integration model for improved statistical inference by leveraging external summary data. *Biometrika*. asaa014, <https://doi.org/10.1093/biomet/asaa014>

---

data

*Data for example in [PolyGIM](#)*

---

## Description

data is a data frame used in the example of [PolyGIM](#).

## Usage

```
data("data")
```

## Format

A data frame with 4000 observations on the following 4 variables.

`int` a data frame with 21 covariates ( $X_1, \dots, X_{21}$ ), a PRS score covariate (`score`) and polytomous outcomes (`y`)

`moedls` a list of 147 summary data and models from marginal binary logistic regression models

`nctrl` a matrix specifying the number of cases shared in datasets that are used to fit the working models given in `models`

`nctrl` a matrix specifying the number of controls shared in datasets that are used to fit the working models given in `models`

## Details

This is a dataset from which internal and external data are extracted for the example.

---

polygim\_opt

PolyGIM

**Description**

Integrating Summary Statistics and Individual-level Data Using the Optimal V

**Usage**

```
polygim_opt(formula, data, models, ncase, nctrl)
```

**Arguments**

formula	A formula.
data	A internal individual-level data frame containing all variables that are specified in formula and models.
models	A list of external model and summary statistics from multiple external studies.
ncase	A matrix specifying the number of cases shared in datasets that are used to fit the working models given in models.
nctrl	A matrix specifying the number of controls shared in datasets that are used to fit the working models given in models.

**Examples**

```
data(data, package="PolyGIM")

formula = "y~score"
V = diag(length(models))

fit = polygim_opt(formula, data = int, models, ncase, nctrl)
# estimate
fit$theta
# the correspondng standard errors
fit$se
```

---

polygim\_v

PolyGIM

**Description**

Integrating Summary Statistics and Individual-level Data with Fixed V

**Usage**

```
polygim_v(formula, data, models, ncase, nctrl, V)
```

**Arguments**

formula	A formula.
data	A internal individual-level data frame containing all variables that are specified in formula and models.
models	A list of external model and summary statistics from multiple external studies.
ncase	A matrix specifying the number of cases shared in datasets that are used to fit the working models given in models.
nctrl	A matrix specifying the number of controls shared in datasets that are used to fit the working models given in models.
V	The variance-covariance matrix of external estimate summary data in models.

**Examples**

```
data(data, package="PolyGIM")

formula = "y~score"
V = diag(length(models))

fit = polygim_v(formula, data = int, models, ncase, nctrl, V)
# estimate
fit$theta
# the correspondng standard errors
fit$se
```

# Index

- \* **Case-control studies; Disease subtype heterogeneity; Empirical likelihood; Genome-wide association studies;**  
PolyGIM-package, [1](#)
- \* **Polygenic risk score; Polytomous logistic regression model**  
PolyGIM-package, [1](#)
- \* **datasets**  
data, [2](#)
- data, [2](#)
- PolyGIM, [2](#)
- PolyGIM-package, [1](#)
- polygim\_opt, [3](#)
- polygim\_v, [3](#)