

STARTING APRIL 2026

SERVERLESS COMPUTE AUTO-ENABLED FOR ALL WORKSPACES

Notebooks, Jobs & Lakeflow Declarative Pipelines

WHAT'S CHANGING?

Sign Up to the newsletter

 [Databricks.news](#)

Find more databricks tips @

[dailydatabricks.tips](#)

AUTOMATIC ENABLEMENT FOR ALL WORKSPACES

- **Auto-Enablement** — Serverless compute will be automatically enabled for all eligible accounts and workspaces if not already enabled.
- **No Disruption** — Your existing workloads will not be affected. You can continue to use classic compute as before.
- **Toggle Removed** — The account-level serverless toggle will be removed. Serverless will be available in all eligible workspaces.
- **What is Serverless?** — Databricks' most stable compute product with auto-optimizing infrastructure and versionless Spark.



STANDARD MODE

Sign Up to the newsletter



Find more databricks tips @

dailydatabricks.tips

NEW LOWER-COST COMPUTE MODE

Standard mode is now generally available for serverless Lakeflow Jobs and Declarative Pipelines

UP TO 70%
LOWER COST

- ✓ Fully managed compute by Databricks
- ✓ Versionless — receives updates automatically
- ✓ Compared to performance optimized mode
- ✓ Best for scheduled workloads with flexible latency



EGRESS CONTROL

Sign Up to the newsletter

 [Databricks.news](#)

Find more databricks tips @

[dailydatabricks.tips](#)

SERVERLESS EGRESS CONTROL (GA)

Control outbound connections from serverless compute resources to the Internet and cloud storage

Important: Default Behavior

Serverless Notebooks, Jobs, and Lakeflow Declarative Pipelines have unrestricted access to the public internet by default.

- ❏ Configure a Network Policy to restrict outbound traffic
- ❏ Only allow explicitly permitted destinations
- ❏ Mitigate data exfiltration risks
- ❏ Enable dry-run mode first to safely test on production



NOTEBOOK TIMEOUT

CONTROL LONG-RUNNING QUERIES

Serverless notebooks have a default execution timeout of **2.5 hours**. You can manually set the timeout length by configuring a Spark property.

○ ○ ○

```
1 # Default: 2.5 hours (9000s)
2 # Set custom timeout in seconds
3
4 spark.conf.set(
5   "spark.databricks.execution.timeout",
6   "14400s" # 4 hours
7 )
```

Tip: This also works for serverless jobs. See the Spark properties documentation for more options.

Sign Up to the newsletter



Find more databricks tips @

[dailydatabricks.tips](#)

WANT MORE TIPS?

FOLLOW FOR DAILY DATABRICKS TIPS

SIGN UP TO THE NEWSLETTER

 `Databricks.news`

dailydatabricks.tips