

Table of Contents

Table of Contents	1
FUTU-PY-CONFFI DEVOPS GUIDE	2
1. INSTALLATION AND DEPLOYMENT	2
1.1. Prerequisites	2
1.1.1. Install python	2
1.1.2. Install pip	2
1.1.3. Install the Google oauth2client	2
1.1.4. Install the gspread	3
1.2. Fetch the source	3
1.3. Create you local conf file	3
1.4. run the tests	3
2. CONFIGURATION	4
2.1. oAuthClient configuration	4
3. INTERNALS	4
3.1. Configure logging	4
3.2. Python objects listing	4
3.3. Configure the credentials for the oAuth2Client	4
3.4. sfw/python/futu_py_confii.py	4
3.5. sfw/python/ctrl/GoogleSheetToYAML.py	4
3.6. sfw/python/utlis/Initializer.py	4
3.7. sfw/python/utlis/Configurator.py	4
4. TESTING	5
4.1. How-to add / remove tests	5
5. PACKAGING AND DEPLOYMENT	5
5.1. to create a zip file for deploy	5
5.2. to create a password protected file for deploy	5

FUTU-PY-CONFFI DEVOPS GUIDE

1. INSTALLATION AND DEPLOYMENT

1.1. Prerequisites

The must have binaries are:
bash, perl, zip, python3

The nice to have are:
tmux, vim ,ctags

The examples are for Ubuntu - use you OS package manager ...

```
apt-get autoclean
apt-get install --only-upgrade bash
sudo apt-get install -y perl

# optionally
sudo apt-get install -y excuberant-ctags
sudo apt-get install -y 7z

apt-get upgrade
```

1.1.1. Install python

Install the python3 binary as follows:

```
sudo apt-get install python3

# and verify
python3 -V
Python 3.5.2
```

1.1.2. Install pip

Install the python package manager:

The example is for Ubuntu - use the package manager of your OS by choice.

```
sudo apt-get install python-pip
pip install --upgrade pip
```

1.1.3. Install the Google oauth2client

Install the Google oauth2client (<https://github.com/google/oauth2client>) as follows:

```
pip install --upgrade oauth2client
```

1.1.4. Install the gspread

The Google Spreadsheets Python API is utilized and it must be imported via the pip manager.

Use the gspread module

<https://github.com/burnash/gspread>

```
sudo pip install gspread
```

```
# output:
```

Downloading requests-2.12.4-py2.py3-none-any.whl (576kB)

100% ██████████ 583kB 1.7MB/s

Installing collected packages: requests, gspread

Successfully installed gspread-0.6.2 requests-2.12.4

1.2. Fetch the source

Fetch the source from git hub as follows:

```
# create your product dir:
```

```
mkdir -p /opt/futu/futu-pyconfi
```

```
cd /opt/futu/futu-pyconffi/
```

```
git clone https://github.com/futurice/futu-py-conf
```

```
mv -v /opt/futu/futu-py-conffi /opt/futu/futu-py-conffi.0.1.0.dev.$USER
```

1.3. Create you local conf file

The default conf file provides only limited functionality (this is by design) , thus copy and configure the configuration file for your host

```
# go to the product version dir
```

```
cd /opt/futu/futu-py-conffi.0.1.0.dev.$USER
```

```
mv -v sfw/bash/futu-pyconffi/futu-pyconffi.set-your-host.conf \ sfw/bash/futu-pyconffi/futu-pyconffi.`hostname -s`.conf
```

1.4. run the tests

To run all the tests issue the following call

```
# go to the product version dir
```

```
cd /opt/futu/futu-py-confi.0.1.0.dev.$USER  
bash sfw/bash/futu-py-confi/test-futu-py-confi.sh
```

2. CONFIGURATION

2.1. oAuthClient configuration

oAuthClient configuration todo ...

3. INTERNALS

3.1. Configure logging

To configure the logging edit the logging.conf file by consulting the following documentation:
<https://docs.python.org/3.5/howto/logging.html#logging-basic-tutorial>

3.2. Python objects listing

The following section provides short explanation on the python objects

3.3. Configure the credentials for the oAuth2Client

Using the :
<http://gspread.readthedocs.io/en/latest/oauth2.html>
<https://github.com/burnash/gspread>

3.4. sfw/python/futu_py_conf.py

This is the main entry of the python code ...
Kicks up the configurator and the GoogleSheetToYAML controller obj

3.5. sfw/python/ctrl/GoogleSheetToYAML.py

Implements the control flow for reading the Google Spreadsheet data , data transformations and writing to yaml configuration files

3.6. sfw/python/utils/Initializer.py

A "self-reflecting" module to fetch generically from the project dirs , configuration files etc.

3.7. sfw/python/utils/Configurator.py

Responsible for the global configuration of the tool.

4. TESTING

4.1. How-to add / remove tests

To add remove tests edit the test run action files

```
# go to the product version dir
cd /opt/futu/futu-py-confii.0.1.4.dev.$USER

sfw/bash/futu-py-confii/tests/run-futu-py-confii-tests.lst
```

5. PACKAGING AND DEPLOYMENT

5.1. to create a zip file for deploy

to create a zip file for deploy issue the following call

```
# go to the product version dir
cd /opt/futu/futu-py-confii.0.1.4.dev.$USER

bash sfw/bash/futu-py-confii/futu-py-confii.sh -a create-full-package
```

5.2. to create a password protected file for deploy

to create a password protected file for deploy issue the following call

```
# go to the product version dir
cd /opt/futu/futu-py-confii.0.1.4.dev.$USER

bash sfw/bash/futu-py-confii/futu-py-confii.sh -a create-full-7z-package
```

You will be prompted to add a secret pass for the package if you have not configured the pw in you shell as follows:
export pcking_pw=***