


Why Rotate ?



Data Structures and Algorithms in Java

The DSW Algorithm

- Colin **Day**, Quentin F. **Stout**, Bette L. **Warren**
- The building block for tree transformations in this algorithm is the **rotation**
- There are two types of rotation, left and right, which are symmetrical to one another


Data Structures and Algorithms in Java

2

The DSW Algorithm (continued)

```

rotateRight (Gr, Par, Ch)
  if Par is not the root of the tree // i.e., if Gr is not null
    grandparent Gr of child Ch becomes Ch's parent;
  right subtree of Ch becomes left subtree of Ch's parent Par;
  node Ch acquires Par as its right child;
  
```



```


Par.left = Ch.right; //1
Ch.right = Par;      //2
Gr.right = Ch;       //3
  
```

Figure 6-37 Right rotation of child Ch about parent Par

Data Structures and Algorithms in Java





3

Rotate RIGHT - LEFT




Data Structures and Algorithms in Java

4




Example



Data Structures and Algorithms in Java

9

Example



Data Structures and Algorithms in Java

10

The DSW Algorithm (continued)




Figure 6-38 Transforming a binary search tree into a backbone
(Use the DSW rotateRight algorithm)

Data Structures and Algorithms in Java

Degrading tree
Cây suy biến

11

The DSW Algorithm (continued)




Figure 6-39 Transforming a backbone into a perfectly balanced tree

Data Structures and Algorithms in Java

12

DAY 4

Data Structures and Algorithms in Java

13

Giới thiệu

- Do G.M. Adelsen Velskii và E.M. Lendis đưa ra vào năm 1962, đặt tên là cây AVL.

Data Structures and Algorithms in Java

14

Định nghĩa


- Cây cân bằng AVL là cây nhị phân tìm kiếm mà tại mỗi đỉnh của cây, độ cao của cây con trái và cây con phải **không chênh lệch quá 1**.

Data Structures and Algorithms in Java

15

Cây AVL

◦ Ví dụ :



Data Structures and Algorithms in Java

16

Xây dựng cây cân bằng

- Việc xây dựng cây cân bằng dựa trên cây nhị phân tìm kiếm, chỉ bổ sung thêm 1 giá trị cho biết sự cân bằng của các cây con như thế nào.
- Cách làm gợi ý:

```


struct NODE {
    Data key;
    NODE *pLeft, *pRight;
    int bal;
};

```
- Trong đó giá trị bal (balance, cân bằng) có thể là: 0: cân bằng; -1: lệch trái; 1: lệch phải

Data Structures and Algorithms in Java

17

Mô tả cấu trúc cây AVL



Data Structures and Algorithms in Java

18

Các trường hợp mất cân bằng


- Mất cân bằng trái-trái (L-L)
- Mất cân bằng trái-phải (L-R)
- Mất cân bằng phải-phải (R-R)
- Mất cân bằng phải-trái (R-L)

Data Structures and Algorithms in Java

19

Các trường hợp mất cân bằng

- Mất cân bằng trái-trái (L-L)




Data Structures and Algorithms in Java

20

Các trường hợp mất cân bằng

- Mất cân bằng trái-phải (L-R)




Data Structures and Algorithms in Java

21

Các trường hợp mất cân bằng

- Mất cân bằng phải-phải (R-R)




Data Structures and Algorithms in Java

22

Các trường hợp mất cân bằng

- Mất cân bằng phải-trái (R-L)



Data Structures and Algorithms in Java

23

Xử lý mất cân bằng


- Giả sử tại một node cây xảy ra mất cân bằng bên phải (cây con phải chênh lệch với cây con trái hơn một đơn vị):
 - ▢ Mất cân bằng phải-phải (RR)
 - Quay trái
 - ▢ Mất cân bằng phải-trái (R-L)
 - Quay phải
 - Quay trái

Data Structures and Algorithms in Java

24

Xử lý mất cân bằng

- P mất cân bằng phải-phải (RR):




Data Structures and Algorithms in Java

25

Xử lý mất cân bằng

- P mất cân bằng phải-trái (RL) – Bước 1:




Data Structures and Algorithms in Java

26

Xử lý mất cân bằng

- P mất cân bằng phải-trái (RL) - Bước 2:



Data Structures and Algorithms in Java

27

Xử lý mất cân bằng


- Khi một node cây xảy ra mất cân bằng bên trái (cây con trái chênh lệch với cây con phải hơn một đơn vị): (thực hiện đối xứng với trường hợp mất cân bằng bên phải)
 - ▣ Mất cân bằng trái-trái (LL)
 - Quay phải
 - ▣ Mất cân bằng trái-phải (L-R)
 - Quay trái
 - Quay phải

Data Structures and Algorithms in Java

28

Thao tác tìm kiếm

- Thực hiện hoàn toàn tương tự cây nhị phân tìm kiếm.



Data Structures and Algorithms in Java

29

Thao tác thêm phần tử

- Thực hiện tương tự với việc thêm phần tử của cây nhị phân tìm kiếm.
- Nếu xảy ra việc mất cân bằng thì xử lý bằng các trường hợp mất cân bằng đã biết.

Data Structures and Algorithms in Java

30

Thao tác xóa phần tử


- Thực hiện tương tự cây nhị phân tìm kiếm: xét 3 trường hợp, và tìm phần tử thế mạng nếu cần.
- Sau khi xóa, nếu cây mất cân bằng, thực hiện cân bằng cây.
- Lưu ý: *việc cân bằng sau khi hủy có thể xảy ra dây chuyền.*

Data Structures and Algorithms in Java

31

Thao tác xóa phần tử

- Ví dụ: xóa 35




mở rộng thêm công dụng

Data Structures and Algorithms in Java

32

Thao tác xóa phần tử

- Xóa phần tử 45




Node 50 bị lệch phải !!!

Data Structures and Algorithms in Java

33

Thao tác xóa phần tử

- Xóa phần tử 45: cân bằng lại cây
Quay trái tại node 50




Data Structures and Algorithms in Java


34

Các lỗi có thể xảy ra


Mất cân bằng phải-phải (R-R)




Mất cân bằng phải-trái (R-L)



Mất cân bằng trái-trái (L-L)



Mất cân bằng trái-phải (L-R)



Data Structures and Algorithms in Java

Quy tắc

MẤT CÂN BẰNG PHẢI

Mất cân bằng phải-phải (R-R)

- Quay trái tại node bị mất cân bằng

Mất cân bằng phải-trái (R-L)

- Quay phải tại node con phải của node bị mất cân bằng
- Quay trái tại node bị mất cân bằng

MẤT CÂN BẰNG TRÁI

Mất cân bằng trái-trái (L-L)

- Quay phải tại node bị mất cân bằng

Mất cân bằng trái-phải (L-R)

- Quay trái tại node con trái của node bị mất cân bằng
- Quay phải tại node bị mất cân bằng

Bài tập

❖ Tạo cây AVL với các khóa lần lượt là: 30, 20, 10. Sau đó thêm lần lượt các khóa: 15, 40, 25, 27, 26, 5, 13, 14 vào cây trên.
❖

AVL Trees

- An **AVL tree** is one in which the height of the left and right subtrees of every **node differ by at most one**
- A balance factor is the height of the right subtree **minus** the height of the left subtree.




Figure 6-40 Examples of AVL trees

AVL Trees (continued)




Figure 6-41 Balancing a tree after insertion of a node in the right subtree of node Q

AVL Trees (continued)




Figure 6-42 Balancing a tree after insertion of a node in the left subtree of node Q

AVL Trees (continued)




Figure 6-43 An example of inserting a new node (b) in an AVL tree (a), which requires one rotation (c) to restore the height balance

Data Structures and Algorithms in Java

41

AVL Trees (continued)




Figure 6-44 In an AVL tree (a) a new node is inserted (b) requiring no height adjustments

Data Structures and Algorithms in Java

42

AVL Trees (continued)




Figure 6-45 Rebalancing an AVL tree after deleting a node

Data Structures and Algorithms in Java

43

AVL Trees (continued)




Figure 6-45 Rebalancing an AVL tree after deleting a node (continued)

Data Structures and Algorithms in Java

44

AVL Trees (continued)




Figure 6-45 Rebalancing an AVL tree after deleting a node (continued)

Data Structures and Algorithms in Java

45

Self-Adjusting Trees

- The strategy in self-adjusting trees is to restructure trees by moving up the tree with only those elements that are used more often, and creating a **priority tree** → **These elements will be found faster**

Data Structures and Algorithms in Java

46

Self-Restructuring Trees

- Single rotation** – Rotate a child about its parent if an element in a child is accessed, unless it is the root




Figure 6-46 Restructuring a tree by using (a) a single rotation or (b) moving to the root when accessing node R

Data Structures and Algorithms in Java

47

Self-Restructuring Trees (continued)

- Moving to the root** – Repeat the child–parent rotation until the element being accessed is in the root




Figure 6-46 Restructuring a tree by using (a) a single rotation or (b) moving to the root when accessing node R (continued)

Data Structures and Algorithms in Java

48

Self-Restructuring Trees (continued)




Figure 6-47 (a–e) Moving element *T* to the root and then (e–i) moving element *S* to the root

Data Structures and Algorithms in Java

49

Splaying

- A modification of the move-to-the-root strategy is called **splaying**
- Splaying applies single rotations in pairs in an order depending on the links between the child, parent, and grandparent
- **Semisplaying** requires only one rotation for a homogeneous splay and continues splaying with the parent of the accessed node, not with the node itself

Data Structures and Algorithms in Java

50

Splaying (continued)




Figure 6-48 Examples of splaying (The node *R* is accessed)

Data Structures and Algorithms in Java

51

Splaying (continued)




Figure 6-48 Examples of splaying (continued) – The node *R* is accessed

Data Structures and Algorithms in Java

52

Splaying (continued)




Figure 6-49 Restructuring a tree with splaying (a–c) after accessing *T* and (c–d) then *R*

Data Structures and Algorithms in Java

53

Splaying (continued)




Figure 6-50 (a–c) Accessing *T* and restructuring the tree with semisplaying; (c–d) accessing *T* again

Data Structures and Algorithms in Java

54

Heaps

- A particular kind of binary tree, called a **heap**, has two properties:
 - The value of each node is greater (max heap)/less (min heap) than or equal to the values stored in each of its children
 - The tree is perfectly balanced, and the leaves in the last level are all in the leftmost positions
- These two properties define a **max heap**
- If “greater” in the first property is replaced with “less,” then the definition specifies a **min heap**

Data Structures and Algorithms in Java

55

Heaps (continued)

With the view of Max heaps




Figure 6-51 Examples of (a) heaps and (b–c) nonheaps

Data Structures and Algorithms in Java

56

Heaps (continued)

Heap can be implemented by an array, this array is partitioned to groups of same-level elements.




Figure 6-52 The array [2 8 6 1 10 15 3 12 11] seen as a tree
This array is not a heap because the first property is violated.

Heaps (continued)




Figure 6-53 Different heaps constructed with the same elements

Heaps as Priority Queues




Figure 6-54 Enqueuing an element to a heap

Heaps as Priority Queues (continued)




Figure 6-55 Dequeuing an element from a heap

Heaps as Priority Queues (continued)

```
void moveDown(Object[] data, int first, int last) {
    int largest = 2*first + 1;
    while (largest <= last) {
        if (largest < last && // first has two children (at 2*first+1 and
                               // 2*first+2)
            ((Comparable)data[largest]).compareTo(data[largest+1]) < 0)
            largest++;
        if (((Comparable)data[first]).compareTo(data[largest]) < 0) {
            swap(data, first, largest); // if necessary, swap values
            first = largest;           // and move down;
            largest = 2*first + 1;
        }
        else largest = last + 1; // to exit the loop: the heap property
                                // isn't violated by data[first]
    }
}
```

Figure 6-56 Implementation of an algorithm to move the root element down a tree

Data Structures and Algorithms in Java

61

Organizing Arrays as Heaps




Figure 6-57 Organizing an array as a heap with a top-down method

Data Structures and Algorithms in Java

62

Organizing Arrays as Heaps




Figure 6-57 Organizing an array as a heap with a top-down method (continued)

Data Structures and Algorithms in Java

63

Organizing Arrays as Heaps




Figure 6-57 Organizing an array as a heap with a top-down method (continued)

Data Structures and Algorithms in Java

64

Organizing Arrays as Heaps (continued)




Figure 6-58 Transforming the array [2 8 6 1 10 15 3 12 11] into a heap with a bottom-up method

Data Structures and Algorithms in Java

65

Organizing Arrays as Heaps (continued)




Figure 6-58 Transforming the array [2 8 6 1 10 15 3 12 11] into a heap with a bottom-up method (continued)

Data Structures and Algorithms in Java

66

Organizing Arrays as Heaps (continued)




Figure 6-58 Transforming the array [2 8 6 1 10 15 3 12 11] into a heap with a bottom-up method (continued)

Data Structures and Algorithms in Java

67

Polish Notation and Expression Trees

- **Polish notation (postfix notation)** is a special notation for propositional logic that eliminates all parentheses from formulas
- The compiler rejects everything that is not essential to retrieve the proper meaning of formulas rejecting it as “syntactic sugar”

Data Structures and Algorithms in Java

68

Polish Notation and Expression Trees (continued)





Figure 6-59 Examples of three expression trees and results of their traversals

Data Structures and Algorithms in Java

69

Diagram



Data Structures and Algorithms in Java

70

Operations on Expression Trees




Figure 6-60 An expression tree

Data Structures and Algorithms in Java

71

Operations on Expression Trees (continued)




Figure 6-61 Tree transformations for differentiation of multiplication and division

Data Structures and Algorithms in Java

72

Case Study: Computing Word Frequencies




Figure 6-62 Semisplay tree used for computing word frequencies

Data Structures and Algorithms in Java

73

Case Study: Computing Word Frequencies (continued)

```

/***** BSTNode.java *****/
*      node of a generic binary search tree
*/

public class BSTNode {
    protected Comparable el;
    protected BSTNode left, right;
    public BSTNode() {
        left = right = null;
    }
    public BSTNode(Comparable el) {
        this(el, null, null);
    }
    public BSTNode(Comparable el, BSTNode lt, BSTNode rt) {
        this.el = el; left = lt; right = rt;
    }
}

```

Figure 6-63 Implementation of word frequency computation

Data Structures and Algorithms in Java

74

Case Study: Computing Word Frequencies (continued)

```

/***** BST.java *****/
*      generic binary search tree
*/

public class BST {
    protected BSTNode root = null;
    public BST() {
    }
    public Comparable search(Comparable el) {
        return search(root, el);
    }
}

```

Figure 6-63 Implementation of word frequency computation (continued)

Data Structures and Algorithms in Java

75

Case Study: Computing Word Frequencies (continued)

```

protected Comparable search(BSTNode p, Comparable el) {
    while (p != null)
        if (el.equals(p.el))
            return p.el;
        else if (el.compareTo(p.el) < 0)
            p = p.left;
        else p = p.right;
    return null;
}

public void insert(Comparable el) {
    BSTNode p = root, prev = null;
    while (p != null) { // find a place for inserting new node;
        prev = p;
    }
}

```

Figure 6-63 Implementation of word frequency computation (continued)

Data Structures and Algorithms in Java

76

Case Study: Computing Word Frequencies (continued)

```

        if (p.el.compareTo(el) < 0)
            p = p.right;
        else p = p.left;
    }
    if (root == null) // tree is empty;
        root = new BSTNode(el);
    else if (prev.el.compareTo(el) < 0)
        prev.right = new BSTNode(el);
    else prev.left = new BSTNode(el);
}
protected void visit(BSTNode p) {
    System.out.print(p.el + " ");
}

```

Figure 6-63 Implementation of word frequency computation (continued)

Data Structures and Algorithms in Java

77

Case Study: Computing Word Frequencies (continued)

```

    }
    public void inorder() {
        inorder(root);
    }
    protected void inorder(BSTNode p) {
        if (p != null) {
            inorder(p.left);
            visit(p);
            inorder(p.right);
        }
    }
    .....
}

```

Figure 6-63 Implementation of word frequency computation (continued)

Data Structures and Algorithms in Java

78

Case Study: Computing Word Frequencies (continued)

```

/***** SplayTreeNode.java *****/
*      node for generic splaying tree class
*/

public class SplayTreeNode extends BSTNode {
    protected BSTNode parent;
    public SplayTreeNode() {
        left = right = parent = null;
    }
    public SplayTreeNode(Comparable el) {
        this(el, null, null, null);
    }
    public SplayTreeNode(Comparable ob, SplayTreeNode lt,
        SplayTreeNode rt, SplayTreeNode pr) {
        el = ob; left = lt; right = rt; parent = pr;
    }
}

```

Figure 6-63 Implementation of word frequency computation (continued)

Data Structures and Algorithms in Java

79

Case Study: Computing Word Frequencies (continued)

```

/***** SplayTree.java *****/
*      generic splaying tree class
*/

public class SplayTree extends BST {
    public SplayTree() {
        super();
    }
    private void continueRotation(BSTNode gr, BSTNode par,
        BSTNode ch, BSTNode desc) {
        if (gr != null) { // if par has a grandparent;
            if (gr.right == ((SplayTreeNode)ch).parent)
                gr.right = ch;
            else gr.left = ch;
        }
    }
}

```

Figure 6-63 Implementation of word frequency computation (continued)

Data Structures and Algorithms in Java

80

Case Study: Computing Word Frequencies (continued)

```

    }
    else root = ch;
    if (desc != null)
        ((SplayTreeNode)desc).parent = par;
    ((SplayTreeNode)par).parent = ch;
    ((SplayTreeNode)ch).parent = gr;
}
private void rotateR(SplayTreeNode p) {
    p.parent.left = p.right;
    p.right = p.parent;
    continueRotation(((SplayTreeNode)p.parent).parent,
        p.right, p, p.right.left);
}
private void rotateL(SplayTreeNode p) {
    p.parent.right = p.left;
    p.left = p.parent;
    continueRotation(((SplayTreeNode)p.parent).parent,
        p.left, p, p.left.right);
}

```

Figure 6-63 Implementation of word frequency computation (continued)

Data Structures and Algorithms in Java

81

Case Study: Computing Word Frequencies (continued)

```

}
private void semisplay(SplayTreeNode p) {
    while (p != root) {
        if (((SplayTreeNode)p.parent).parent == null) // if p's
            parent is
                if (p.parent.left == p) // the root;
                    rotateR(p);
                else rotateL(p);
        else if (p.parent.left == p) // if p is a left child;
            if (((SplayTreeNode)p.parent).parent.left == p.parent) {

```

Figure 6-63 Implementation of word frequency computation (continued)

Data Structures and Algorithms in Java

82

Case Study: Computing Word Frequencies (continued)

```

        rotateR((SplayTreeNode)p.parent);
        p = (SplayTreeNode)p.parent;
    }
    else {
        rotateR((SplayTreeNode)p); // rotate p and its
        parent;
        rotateL((SplayTreeNode)p); // rotate p and its new
        parent;
    }
    else // if p is a right child;
        if (((SplayTreeNode)p.parent).parent.right == p.parent) {
            rotateL((SplayTreeNode)p.parent);
            p = (SplayTreeNode)p.parent;
        }
    }
}

```

Figure 6-63 Implementation of word frequency computation (continued)

Data Structures and Algorithms in Java

83

Case Study: Computing Word Frequencies (continued)

```

    }
    else {
        rotateL(p); // rotate p and its parent;
        rotateR(p); // rotate p and its new
    }
    // parent;
    if (root == null) // update the root;
        root = p;
}
}
}

```

Figure 6-63 Implementation of word frequency computation (continued)

Data Structures and Algorithms in Java

84

Case Study: Computing Word Frequencies (continued)

```

/***** WordPlaying.java *****/
import java.io.*;

class Word implements Comparable {
    private String word = "";
    public int freq = 1;
    public Word() {
    }
    public Word(String s) {
        word = s;
    }
    public boolean equals(Object el) {
        return word.equals(((Word)el).word);
    }
    public int compareTo(Object el) {
        return word.compareTo(((Word)el).word);
    }
}

```

Figure 6-63 Implementation of word frequency computation (continued)

Data Structures and Algorithms in Java

85

Case Study: Computing Word Frequencies (continued)

```

    }
    public String toString() {
        return word + ": " + freq + " ";
    }
}

class WordSplay extends SplayTree {
    private int differentWords, // counter of different words in text
        // file;
        wordCnt; // counter of all words in the same file;
    public WordSplay() {
        differentWords = wordCnt = 0;
    }
    protected void visit(BSTNode p) {
        differentWords++;
        wordCnt += ((Word)p.el).freq;
    }
}

```

Figure 6-63 Implementation of word frequency computation (continued)

Data Structures and Algorithms in Java

86

Case Study: Computing Word Frequencies (continued)

```

    }
    public void run(InputStream fIn, String fileName) {
        int ch = 1;
        Word p;
        try {
            while (ch > -1) {
                while (true)
                    if (ch > -1 && !Character.isLetter((char)ch)) // skip
                        ch = fIn.read(); // nonletters;
                    else break;
                if (ch == -1)
                    break;
                String s = "";

```

Figure 6-63 Implementation of word frequency computation (continued)

Data Structures and Algorithms in Java

87

Case Study: Computing Word Frequencies (continued)

```

        while (ch > -1 && Character.isLetter((char)ch)) {
            s += Character.toUpperCase((char)ch);
            ch = fIn.read();
        }
        if ((p = (Word)search(new Word(s))) == null)
            insert(new Word(s));
        else ((Word)p).freq++;
    }
    catch (IOException io) {
        System.err.println("A problem with input");
    }
    inorder();
    System.out.println("\n\nFile " + fileName

```

Figure 6-63 Implementation of word frequency computation (continued)

Data Structures and Algorithms in Java

88

Case Study: Computing Word Frequencies (continued)

```

        + " contains " + wordCnt + " words among which "
        + differentWords + " are different\n");
    }
}

class WordSplaying {
    static public void main(String args[]) {
        String fileName = "";
        InputStream fIn;
        BufferedReader buffer = new BufferedReader(
            new InputStreamReader(System.in));

        try {
            if (args.length == 0) {
                System.out.print("Enter a file name: ");
                fileName = buffer.readLine();
                fIn = new FileInputStream(fileName);
            }
        }
    }
}

```

Figure 6-63 Implementation of word frequency computation (continued)

Data Structures and Algorithms in Java

89

Case Study: Computing Word Frequencies (continued)

```

    }
    else {
        fIn = new FileInputStream(args[0]);
        fileName = args[0];
    }
    (new WordSplay()).run(fIn, fileName);
    fIn.close();
} catch (IOException io) {
    System.err.println("Cannot open " + fileName);
}
}
}

```

Figure 6-63 Implementation of word frequency computation (continued)

Data Structures and Algorithms in Java

90

Summary

- A tree is a data type that consists of nodes and arcs.
- The root is a node that has no parent; it can have only child nodes.
- Each node has to be reachable from the root through a unique sequence of arcs, called a path.
- An orderly tree is where all elements are stored according to some predetermined criterion of ordering.

Data Structures and Algorithms in Java

91

Summary (continued)

- A binary tree is a tree whose nodes have two children (possibly empty), and each child is designated as either a left child or a right child.
- A decision tree is a binary tree in which all nodes have either zero or two nonempty children.
- Tree traversal is the process of visiting each node in the tree exactly one time.
- Threads are references to the predecessor and successor of the node according to an inorder traversal.

Data Structures and Algorithms in Java

92

Summary (continued)

- An AVL tree is one in which the height of the left and right subtrees of every node differ by at most one.
- A modification of the move-to-the-root strategy is called splaying.
- Polish notation is a special notation for propositional logic that eliminates all parentheses from formulas.