

BOURNEMOUTH UNIVERSITY

TRANSFER DOCUMENT

From Brush Painting to Bas-relief

Author:
Yunfei FU

First Supervisor:
Dr. Hongchuan YU
Second Supervisor:
Pro. Jian Jun ZHANG

September 18, 2017

Contents

1	INTRODUCTION	3
---	--------------	---

List of Figures

Chapter 1

INTRODUCTION

Relief is a kind of sculpture in which 3D models are carved into a relatively flat surface. In essence, it creates a bridge between a full 3D sculpture and a 2D painting. As an artistic form, relief spans the continuum between a 2D painting and a full 3D sculpture[1]. On this spectrum, alto-relievo (high relief) is closest to full 3D, whereas flatter artworks are described as basso-relievo (low relief, and also called bas-relief). Among all the sculpture forms, bas-relief is arguably the closest to 2D paintings, as claimed by[2] and[3].

Currently, most existing bas-relief production methods focus on compressing 3D scenes/models into surfaces with a small depth[1]and[2]. This approach requires a 3D model as a starting point.

Another option is to generate bas-reliefs directly from 2D images. There have been some image based bas-relief production approaches available in[4][5] and [6]. These approaches almost follow the “bas-relief ambiguity”[7], that is, roughly speaking, from a frontal view the sculpture looks like a full 3D object while a side-view reveals the disproportional depth.

While most image based methods are focusing on general photographs, which are unsuited for specific problems for brush paintings, such as spatial occlusion (i.e. one stroke occludes other strokes in the painting to demonstrate the depth perception) and stroke transparency. Another clear shortcoming is current image based methods can’t take the artistic intent into account, as all that they do is to infer the height information from the image. Concerning reproduction or modifying of an artistic painting, it is crucial that the style of the originals is preserved, which is not considered in existing image-based methods. However, little is done in the area of bas-relief generation from artistic paintings, as maintaining the styles of the brush paintings proves much trickier than simply manipulating the height of the contour lines. In the case of bas-reliefs, although there is no 3D model available, pseudo 3D effect reflecting the style and subtlety is crucial in preserving the artistic essence.

The aim of our research is to provide the bas-relief sculptors with a new tool allowing them to convert and recompose existing brush paintings to bas-reliefs. We also argue that because traditional paintings are produced with individual strokes, ‘3D bas-relief strokes’ will enable them to ‘paint/sculpt’ a bas-relief naturally, especially if they wanted to quickly convert an existing painting into a relief. With the commonly and cheaply available 3D printing facilities, there is a growing trend in the need of bas-relief art products. A brush painting can be regarded as the union of a set of hypothetical strokes

by a brush [8]. Differing from the other bas-relief generation methods, our method will honor this very feature by constructing the brush strokes individually as 3D geometric entities. This however demands to conquer several challenges. First, each brush stroke covers a region on the canvas and they may overlap each other, some quite heavily in a painting. To make sure the information is retained, every stroke has to be faithfully extracted. Second, spatial occlusion has to be dealt with, since artists are used to depicting it through controlling the transparency of strokes as one of the art elements. Third, as an artistic tool, the generated bas-relief should be further editable allowing the artist to rearrange, tweaking and reshaping the extracted strokes.

The shape, color and opacity of a stroke vary due to the shape and firmness of the brush as well as the forces the artist imposes. Although these variables add the complexity to stroke extraction, stylized strokes often follow distinct patterns. For example, Rosemaling paintings, a typical example of brush painting popular in North Europe, is a traditional form of decorative folk art that originated in the rural valleys of Norway. The Rosemaling designs use C and S strokes, feature scroll, flowing lines, floral designs, and both subtle and vibrant colors. The brush strokes may further be viewed as graphical objects which are meaningful with respect to the objects the painting portraits. Moreover, each stroke is clearly visible due to both subtle and vibrant colors. The similar properties may be found in some Chinese brush paints. To extract the strokes from a brush painting, we need to identify and segment the overlapped strokes. We will then generate the depth map for every stroke separately using the shape from shading (SFS) technique on the opacity. All the strokes are finally merged together to yield the resulting bas-relief with the original 2D painting preserved. Our contributions include,

- (1) Extraction of brush strokes. We develop a novel method to extract brush strokes from input paintings with palette analysis and decomposed layers.
- (2) 3D modeling of brush strokes. We develop a novel method which may entirely construct every stroke in 3D based on the opacity of paintings.
- (3) Recomposition in bas-relief design. Artists may redefine the brush strokes' order and shapes by sketches, which enable recomposition in bas-relief design, making it a useful tool for sculpture artists.

Bibliography

- [1] Tim Weyrich, Jia Deng, Connelly Barnes, Szymon Rusinkiewicz, and Adam Finkelstein. Digital bas-relief from 3d scenes. In *ACM Transactions on Graphics (TOG)*, volume 26, page 32. ACM, 2007.
- [2] Jens Kerber, Art Tevs, Alexander Belyaev, Rhaleb Zayer, and Hans-Peter Seidel. Feature sensitive bas relief generation. In *Shape Modeling and Applications, 2009. SMI 2009. IEEE International Conference on*, pages 148–154. IEEE, 2009.
- [3] Jonathan Barron and Jitendra Malik. Color constancy, intrinsic images, and shape estimation. *Computer Vision–ECCV 2012*, pages 57–70, 2012.
- [4] Qiong Zeng, Ralph R Martin, Lu Wang, Jonathan A Quinn, Yuhong Sun, and Changhe Tu. Region-based bas-relief generation from a single image. *Graphical Models*, 76(3):140–151, 2014.
- [5] Jing Wu, Ralph R Martin, Paul L Rosin, X-F Sun, Frank C Langbein, Y-K Lai, A David Marshall, and Y-H Liu. Making bas-reliefs from photographs of human faces. *Computer-Aided Design*, 45(3):671–682, 2013.
- [6] Marc Alexa and Wojciech Matusik. Reliefs as images. *ACM Trans. Graph.*, 29(4):60–1, 2010.
- [7] Peter N Belhumeur, David J Kriegman, and Alan L Yuille. The bas-relief ambiguity. *International journal of computer vision*, 35(1):33–44, 1999.
- [8] Songhua Xu, Yingqing Xu, Sing Bing Kang, David H Salesin, Yunhe Pan, and Heung-Yeung Shum. Animating chinese paintings through stroke-based decomposition. *ACM Transactions on Graphics (TOG)*, 25(2):239–267, 2006.
- [9] Christian Richardt, Jorge Lopez-Moreno, Adrien Bousseau, Maneesh Agrawala, and George Drettakis. Vectorising bitmaps into semi-transparent gradient layers. In *Computer Graphics Forum*, volume 33, pages 11–19. Wiley Online Library, 2014.
- [10] James McCann and Nancy Pollard. Local layering. *ACM Transactions on Graphics (TOG)*, 28(3):84, 2009.
- [11] James McCann and Nancy S Pollard. Soft stacking. In *Computer Graphics Forum*, volume 31, pages 469–478. Wiley Online Library, 2012.
- [12] Jianchao Tan, Jyh-Ming Lien, and Yotam Gingold. Decomposing images into layers via rgb-space geometry. *ACM Transactions on Graphics (TOG)*, 36(1):7, 2016.

- [13] Jia Li, Lei Yao, Ella Hendriks, and James Z Wang. Rhythmic brushstrokes distinguish van gogh from his contemporaries: findings via automated brushstroke extraction. *IEEE transactions on pattern analysis and machine intelligence*, 34(6):1159–1176, 2012.
- [14] Jiri Matas, Ondrej Chum, Martin Urban, and Tomás Pajdla. Robust wide-baseline stereo from maximally stable extremal regions. *Image and vision computing*, 22(10):761–767, 2004.
- [15] Lukas Neumann and Jiri Matas. Text localization in real-world images using efficiently pruned exhaustive search. In *Document Analysis and Recognition (ICDAR), 2011 International Conference on*, pages 687–691. IEEE, 2011.
- [16] Lluís Gomez and Dimosthenis Karatzas. Multi-script text extraction from natural scenes. In *Document Analysis and Recognition (ICDAR), 2013 12th International Conference on*, pages 467–471. IEEE, 2013.
- [17] Lluís Gomez and Dimosthenis Karatzas. A fast hierarchical method for multi-script and arbitrary oriented scene text extraction. *International Journal on Document Analysis and Recognition (IJDAR)*, 19(4):335–349, 2016.
- [18] Michael Donoser and Horst Bischof. Efficient maximally stable extremal region (mscr) tracking. In *Computer Vision and Pattern Recognition, 2006 IEEE Computer Society Conference on*, volume 1, pages 553–560. IEEE, 2006.
- [19] Henry Kang, Seungyong Lee, and Charles K Chui. Coherent line drawing. In *Proceedings of the 5th international symposium on Non-photorealistic animation and rendering*, pages 43–50. ACM, 2007.
- [20] Meili Wang, Jian Chang, Junjun Pan, and J Zhang. Image-based bas-relief generation with gradient operation. In *Proceedings of the 11th IASTED International Conference Computer Graphics and Imaging, Innsbruck*, volume 679, page 33, 2010.
- [21] Zhuwen Li, Song Wang, Jinhui Yu, and Kwan-Liu Ma. Restoration of brick and stone relief from single rubbing images. *IEEE Transactions on Visualization and Computer Graphics*, 18(2):177–187, 2012.
- [22] Ruo Zhang, Ping-Sing Tsai, James Edwin Cryer, and Mubarak Shah. Shape-from-shading: a survey. *IEEE transactions on pattern analysis and machine intelligence*, 21(8):690–706, 1999.
- [23] Emmanuel Prados and Olivier D Faugeras. ” perspective shape from shading” and viscosity solutions. In *ICCV*, volume 3, page 826, 2003.
- [24] Pierre-Louis Lions, Elisabeth Rouy, and A Tourin. Shape-from-shading, viscosity solutions and edges. *Numerische Mathematik*, 64(1):323–353, 1993.
- [25] Emmanuel Prados and Olivier Faugeras. Unifying approaches and removing unrealistic assumptions in shape from shading: Mathematics can help. *Computer Vision-ECCV 2004*, pages 141–154, 2004.

- [26] Neil G Alldrin, Satya P Mallick, and David J Kriegman. Resolving the generalized bas-relief ambiguity by entropy minimization. In *Computer Vision and Pattern Recognition, 2007. CVPR'07. IEEE Conference on*, pages 1–7. IEEE, 2007.
- [27] Micah K Johnson and Edward H Adelson. Shape estimation in natural illumination. In *Computer Vision and Pattern Recognition (CVPR), 2011 IEEE Conference on*, pages 2553–2560. IEEE, 2011.
- [28] Michael Kolomenkin, George Leifman, Ilan Shimshoni, and Ayellet Tal. Reconstruction of relief objects from line drawings. In *Computer Vision and Pattern Recognition (CVPR), 2011 IEEE Conference on*, pages 993–1000. IEEE, 2011.
- [29] Peter AC Varley and Ralph R Martin. Estimating depth from line drawing. In *Proceedings of the seventh ACM symposium on Solid modeling and applications*, pages 180–191. ACM, 2002.
- [30] Jitendra Malik. Interpreting line drawings of curved objects. *International Journal of Computer Vision*, 1(1):73–103, 1987.
- [31] Daniel Šykora, Ladislav Kavan, Martin Čadík, Ondřej Jamriška, Alec Jacobson, Brian Whited, Maryann Simmons, and Olga Sorkine-Hornung. Ink-and-ray: Bas-relief meshes for adding global illumination effects to hand-drawn characters. *ACM Transactions on Graphics (TOG)*, 33(2):16, 2014.
- [32] David Nistér and Henrik Stewénus. Linear time maximally stable extremal regions. *Computer Vision–ECCV 2008*, pages 183–196, 2008.
- [33] Michel Couprie, Laurent Najman, and Gilles Bertrand. Algorithms for the topological watershed. In *Discrete geometry for computer imagery*, pages 172–182. Springer, 2005.