

A PYTHON PROGRAM TO IMPLEMENT DIMENSIONALITY REDUCTION USING PCA

EXP NO. 10

Name: MOHAMED FUZAIL A

Roll no: 241801162

Code:

```
from sklearn import datasets
import pandas as pd
from sklearn.preprocessing import StandardScaler
from sklearn.decomposition import PCA
import seaborn as sns
import matplotlib.pyplot as plt

iris = datasets.load_iris()
df = pd.DataFrame(iris['data'], columns=iris['feature_names'])
print(df.head())

scalar = StandardScaler()
```


```
scaled_data = pd.DataFrame(scalar.fit_transform(df),
columns=df.columns)

plt.figure(figsize=(6, 4))
sns.heatmap(scaled_data.corr(), annot=True, cmap='coolwarm')
plt.title('Correlation Heatmap (Before PCA)')
plt.show()

pca = PCA(n_components=3)
pca.fit(scaled_data)
data_pca = pca.transform(scaled_data)
data_pca = pd.DataFrame(data_pca, columns=['PC1', 'PC2',
'PC3'])
print(data_pca.head())

plt.figure(figsize=(6, 4))
sns.heatmap(data_pca.corr(), annot=True, cmap='coolwarm')
plt.title('Correlation Heatmap (After PCA)')
plt.show()
```

output:



	PC1	PC2	PC3
0	-2.264703	0.480027	0.127706
1	-2.080961	-0.674134	0.234609
2	-2.364229	-0.341908	-0.044201
3	-2.299384	-0.597395	-0.091290
4	-2.389842	0.646835	-0.015738

