

Richard Johnson

ToorCon San Diego 2016

Go Speed Tracer



Introduction

- Richard Johnson
  - Research Manager
  - Cisco Talos
- Team
  - Aleksandar Nikolich
  - Ali Rizvi-Santiago
  - Marcin Noga
  - Piotr Bania
  - Tyler Bohan
  - Yves Younan
- Special Contributor
  - Andrea Allevi

- Talos Vulndev
  - Third party vulnerability research
    - 170 bug finds in last 12 months
      - Microsoft
      - Apple
      - Oracle
      - Adobe
      - Google
      - IBM, HP, Intel
      - 7zip, libarchive, NTP
  - Security tool development
    - Fuzzers, Crash Triage
  - Mitigation development
    - FreeSentry

Introduction

- Agenda
  - Tracing Applications
  - Guided Fuzzing
  - Binary Translation
  - Hardware Tracing
- Goals
  - Understand the attributes required for optimal guided fuzzing
  - Identify areas that can be optimized today
  - Deliver performant and reusable tracing engines

Applications

- Software Engineering
  - Performance Monitoring
  - Unit Testing
- Malware Analysis
  - Unpacking
  - Runtime behavior
  - Sandboxing
- Mitigations
  - Shadow Stacks
  - Memory Safety checkers

Applications

- Software Security
  - Corpus distillation
    - Minimal set of inputs to reach desired conditions
  - Guided fuzzing
    - Automated refinement / genetic mutation
  - Crash analysis
    - Crash bucketing
    - Graph slicing
    - Root cause determination
  - Interactive Debugging

Tracing Engines

- OS Provided APIs
  - Debuggers
    - ptrace
    - dbgeng
    - signals
  - Hook points
    - Linux LTT(ng)
    - Linux perf
    - Windows Nirvana
    - Windows AppVerifier
    - Windows Shim Engine

Check out Alex Ionescu's RECON 2015 talk

  - Performance counters
    - Linux perf
    - Windows PDH

Tracing Engines

- Binary Instrumentation
  - Compiler plugins
    - gcc-gcov
    - llvm-cov
  - Binary translation
    - Valgrind
    - DynamoRIO
    - Pin
    - DynInst
    - Frida and others
    - ...

TALOS

Tracing Engines

- Native Hardware Support
  - Single Step / Breakpoint
  - Intel Branch Trace Flag
  - Intel Last Branch Record
  - Intel Branch Trace Store
  - Intel Processor Trace
  - ARM CoreSight

TALOS

Guided Fuzzing

Evolutionary Testing

- Early work was whitebox testing
- Source code allowed graph analysis prior to testing
- Fitness based on distance from defined target
- Complex fitness landscape
  - Difficult to define properties that will get from A to B
- Applications were not security specific
  - Safety critical system DoS

TALOS

Guided Fuzzing

- Incrementally better mutational dumb fuzzing
- Trace while fuzzing and provide feedback signal
- Evolutionary algorithms
  - Assess fitness of current input
  - Manage a pool of possible inputs
- Focused on security bugs

TALOS

Sidewinder

- Embleton, Sparks, Cunningham 2006
- Features
  - Simple genetic algorithm approach
    - crossover, mutation, fitness
  - Mutated context free grammar instead of sample fuzzing
  - Markov process for fitness
    - Analyzes probability of path taken by sample
  - Block coverage via debugger API
    - Reduced overhead by focusing on subgraphs



Sidewinder

- Embleton, Sparks, Cunningham 2006
- Contributions
  - Genetic algorithms for fuzzing
  - Markov process for fitness
  - System allows selection of target code locations
- Observations
  - Never opensourced
  - Interesting concepts not duplicated



TALOS

Evolutionary Fuzzing System

- Jared DeMott 2007
- Features
  - Block coverage via Process Stalker
    - Windows Debug API
    - Intel BTF
  - Stored trace results in SQL database
    - Lots of variables required structured storage
  - Traditional genetic programming techniques
    - Code coverage + diversity for fitness
    - Sessions
    - Pools
    - Crossover
    - Mutation

TALOS

Evolutionary Fuzzing System

- Jared DeMott 2007
- Contributions
  - First opensource implementation of guided fuzzing
  - Evaluated function vs block tracing
    - For large programs found function tracing was equally effective
    - Likely an artifact of doing text based protocols
- Observations
  - Academic
    - Approach was too closely tied to traditional genetic algorithms
    - Not enough attention to performance or real world targets
    - Only targeted text protocols

TALOS

Amercian Fuzzy Lop

- Michal Zalewski 2013
  - Bunny The Fuzzer 2007
- Features
  - Block coverage via compile time instrumentation
  - Simplified approach to genetic algorithm
    - Edge transitions are encoded as tuple and tracked in global map
    - Includes coverage and frequency
  - Uses variety of traditional mutation fuzzing strategies
  - Dictionaries of tokens/constants
  - First practical high performance guided fuzzer
  - Helper tools for minimizing test cases and corpus
  - Attempts to be idiot proof

TALOS

Amercian Fuzzy Lop

- Michal Zalewski 2013
  - Bunny The Fuzzer 2007
- Contributions
  - Tracks edge transitions
    - Not just block entry
  - Global coverage map
    - Generation tracking
  - Fork server
    - Reduce fuzz target initialization
  - Persistent mode fuzzing
  - Builds corpus of unique inputs reusable in other workflows



TALOS

Amercian Fuzzy Lop

- Michal Zalewski 2013
  - Bunny The Fuzzer 2007
- Observations
  - KISS works when applied to guided fuzzing
  - Performance top level priority in design
    - Source instrumentation can't be beat
    - Evolutionary system hard to beat without greatly increasing complexity / cost
  - Simple to use, finds tons of bugs
  - Fostered a user community
    - Developer contributions somewhat difficult
  - Current state of the art due to good engineering and feature set
  - Only mutational fuzzer system to have many third-party contributions
    - Binary support via QEMU and Dyninst
    - More robust compiler instrumentations, ASAN support

TALOS

honggfuzz

- Robert Swiecki 2010
  - Guided fuzzing added in 2015
- Features
  - Block coverage
    - Hardware performance counters
    - ASanCoverage
  - Bloom filter for trace recording
  - User-supplied mutation functions
  - Linux, FreeBSD, OSX, Cygwin support
- Contributions
  - First guided fuzzer to focus on hardware tracing support
- Observations
  - Naive seed selection for most algorithms, only the elite survive (OTTES)
    - Some modes use bloom filter
  - Easy to extend, active development

TALOS

Choronzon

- Features
  - Brings back specific genetic programming concepts
  - Contains strategies for dealing with high level input structure
    - Chunk based
    - Hierarchical
    - Containers
  - Format aware serialization functionality
  - Uses DBI engines for block coverage (PIN / DynamoRIO)
  - Attempts to be cross-platform
- Contributions
  - Reintroduction of more complex genetic algorithms
  - Robust handling of complex inputs through user supplied serialization routines
- Observations
  - Performance not a focus

Honorable mentions

- autodafe
  - Martin Vuagnoux 2004
  - First generation guided fuzzer using pattern matching via API hooks
- Blind Code Coverage Fuzzer
  - Joxean Koret 2014
  - Uses off-the-shelf components to assemble a guided fuzzer
    - radamsa, zzuf, custom mutators
    - drcov, COSEINC RunTracer for coverage
- covFuzz
  - Atte Kettunen 2015
  - Simple node.js server for guided fuzzing
  - custom fuzzers, ASanCoverage

TALOS

Guided Fuzzing

- Required
  - Fast tracing engine
    - Block based granularity
  - Fast logging
    - Memory resident coverage map
  - Fast evolutionary algorithm
    - Minimum of global population map, pool diversity
- Desired
  - Portable
  - Easy to use
  - Helper tools
  - Grammar detection
- AFL and Honggfuzz still most practical options

TALOS

Binary Translation

Binary Translation

- Binary translation is a robust program modification technique
  - JIT for hardware ISAs
- General overview is straightforward
  - Copy code to cache for translation
  - Insert instructions to modify original binary
  - Link blocks into traces
- Performance comes from smart trace creation
  - Originally profiling locations for hot trace
  - Early optimizations in Dynamo from HP
    - Next Executing Tail
    - Traces begin at backedge or other trace exit
  - Ongoing optimization work happens here
    - VMware - Early Exit guided

TaLOS

Binary Translation

- Advantages
  - Supported on most mainstream OS/archs
  - Can be faster than hardware tracing
  - Can easily be targeted at certain parts of code
  - Can be tuned for specific applications
- Disadvantages
  - Performance overhead
    - Introduces additional context switch
  - ISA compatibility not guarenteed
  - Not always robust against detection or escape

TALOS

Valgrind

- Obligatory slide
- Lots of deep inspection tools
- VEX IR is well suited for security applications

- Slow and Linux only, DynamoRIO good replacement

- Many cool tools already exist
  - Flayer
  - Memgrind

TALOS

Pin

- “DBT with training wheels”
- Features
  - Trace granularity instrumentation
    - Begin at branch targets, end at indirect branch
  - Block/instruction level hooking supported
  - Higher level C++ API w/ helper routines
  - Closed source
- Observations
  - Delaying instrumentation until trace generation is slower
  - Seems most popular with casual adventurers
  - Limited inlining support
  - Less tuning options
  - Cannot observe blocks added to cache so ‘hit trace’ not possible

talos

Pin

- Example

```
VOID Trace(TRACE trace, VOID *v)
{
    for (BBL bbl = TRACE_BblHead(trace); BBL_Valid(bbl); bbl
            = BBL_Next(bbl))
    {
        BBL_InsertCall(bbl, IPOINT_ANYWHERE, AFUNPTR(basic_block_hook),
                       IARG_FAST_ANALYSIS_CALL, IARG_END);
    }
}
```

TALOS

DynamoRIO

- “A connoisseur's DBT”
- Features
  - Block level instrumentation
    - Blocks are directly copied into code cache
  - Direct modification of IL possible
  - Portable
    - Linux, Windows, Android
    - x86/x64, ARM
  - C API / BSD Licensed (since 2009)
- Observations
  - Much more flexible for block level instrumentation
  - Performance is a priority, Windows is a priority
  - Powerful tools like Dr Memory
    - Shadow memory, taint tracking
    - Twice as fast as Valgrind memcheck

TALOS

DynamoRIO

- Example

```
event_basic_block(void *drcontext, void *tag, instrlist_t *bb,
                  bool for_trace, bool translating)
{
   instr_t *instr, *first = instrlist_first(bb);
   uint flags;
   /* Our inc can go anywhere, so find a spot where flags are dead. */
   for (instr = first; instr != NULL; instr = instr_get_next(instr))
   {
      flags = instr_get_arith_flags(instr);
      /* OP_inc doesn't write CF but not worth distinguishing */
      if (TESTALL(EFLAGS_WRITE_6, flags) && !TESTANY(EFLAGS_READ_6,
          flags))
        break;
   }
…
```

TALOS

DynamoRIO

- Example

```
if (instr == NULL)
  dr_save_arith_flags(drcontext, bb, first, SPILL_SLOT_1);

instrlist_meta_preinsert(bb,
 (instr == NULL) ? first : instr,
  INSTR_CREATE_inc(drcontext,
    OPND_CREATE_ABSMEM((byte *)&global_count, OPSZ_4)));

if (instr == NULL)
  dr_restore_arith_flags(drcontext, bb, first, SPILL_SLOT_1);
return DR_EMIT_DEFAULT;
}
```

TALOS

DynInst

- “Static rewriting IS possible!”
- Features
  - Static rewriting support
    - Dynamically linked binaries only
    - Eliminates issues with instruction cache misses common to DBT engines
  - Function level analysis
    - Tools must manually walk Dyninst provided CFG to instrument blocks
  - Modular C++ API / LGPL
- Observations
  - Fastest binary instrumentation out there
  - Development is slow
    - Patches we sent in for PE relocation support still not merged
  - Building Dyninst is NP-Hard
    - Use my Dockerfile on github.com/talos-vulndev/afl-dyninst

DynInst

- Example

```
bool insertBBCallback(BPatch_binaryEdit * appBin, BPatch_function * curFunc,
            char *funcNam e, BPatch_function * instBBIncFunc, int *bbIndex)
{
  unsigned short randID;
  BPatch_flowGraph *appCFG = curFunc->getCFG ();
  BPatch_Set< BPatch_basicBlock *> allBlocks;
  BPatch_Set< BPatch_basicBlock *>::iterator iter;
  for(iter= allBlocks.begin (); iter != allBlocks.end (); iter++ )
  {
    unsigned long address = (*iter)->getStartAddress ();

    randID = rand()% USHRT_MAX;
    BPatch_Vector< BPatch_snippet *> instArgs;
    BPatch_constExpr bbId (randID);
    instArgs.push_back (&bbId);
…
```

TALOS

DynInst

- Example

```
…
    BPatch_point *bbEntry = (*iter)->findEntryPoint();
    BPatch_funcCallExpr instIncExpr(*instBBIncFunc, instArgs);
    BPatchSnippetHandle *handle =
      appBin->insertSnippet(instIncExpr, *bbEntry, BPatch_callBefore,
                            BPatch_lastSnippet);
    (*bbIndex)++;
  }
  return true;
}
```

TALOS

Tuning Binary Translation

- Only instrument indirect branches
- Delay instrumentation until input is seen
- Only instrument threads that access the data
- Move instrumentation logic to analysis routines
  - Some APIs provide IF-THEN-ELSE analysis with optimization
- Avoid trampolines
  - Be aware of code locality and instruction cache
  - Directly inline instructions, modify AST if possible
- Inject a fork server if repeatedly executing DBT
  - See our turbotrace tool

TaLOS

Hardware Tracing

CPU Event Monitoring

- Modern CPUs contain Performance Monitoring Units (PMU)
- Model Specific Registers (MSR) used for configuration
  - Requires privileged execution (kernel or better) to access
- Types
  - Event Counters
    - Polled on-demand
  - Event Sampling (non-precise)
    - Interrupts triggered when counters hit modulus value
  - Precise Event Sampling (PEBS)
    - Uses 'Debug Store'
    - Physical memory buffers
    - Interrupt when full
- Use Linux perf / pmu-tools to experiment

TALOS

Interrupt Programming

- Interrupts - low level messaging system for system devices
  - CPU Exceptions
    - GPF, SINGLE_STEP
  - Hardware Interrupts
    - Memory mapped or IRQ based
    - All Device I/O
  - Software Interrupts
    - System calls (int 0x80)
    - Breakpoints
- OS/hypervisor drivers required to configure interrupt handlers
  - Privileged registers or interrupt vector tables

TALOS

Interrupt Programming

- Interrupt Service Routines (ISR)
  - Registered by operating systems and drivers as callbacks
- CPU checks interrupt flag (IF) register after each instruction
  - cli and sti instructions control whether IF is checked
- CPU indexes the interrupt vector table to find appropriate handler
  - Context stored / restored while servicing interrupt

- Historically Familiar Interrupts:
  - int 1 - Single Step (TF)
  - int 3 - Single opcode, specifically designed for debugging
  - int 10h - Any Demosceners?
  - int 24h - DOS Critical Error Handler

Who remembers:

I/O Device Specific Error
Message
Abort, Retry, Ignore, Fail?

Interrupt Programming

- Programmer checklist
  - Memory must not be swapped
  - Use static variables if necessary
  - Must wrap functions with assembly
    - disable interrupts
    - push all registers
    - call interrupt handler
    - pop all registers
    - iretd

Its a Trap

- Single Stepping
  - Enabled by setting the Trap Flag
  - After each instruction, CPU checks flag and fires exception if enabled
  - Accessible from userspace
- Branch Trace Flag
  - Modifies single step behavior to trap on branch
  - Single flag in IA32_DEBUGCTL MSR
  - Requires kernel privileges to write to MSR
  - Windows includes a mapping from DR7 to set MSR

- SS/BTF traps are slooooooooow, not applicable for vulnerability research

TALOS

IA32_DEBUGCTL Register

- MSR Address 0x1d9
  - LBR [0] - Enable Last Branch Record mechanism
  - BTF [1] - when enabled with TF in EFLAGS does single stepping on branches
  - TR [6] - enables Tracing (sending BTMs to system bus)
  - BTS [7] - enables sending BTMs to memory buffer from system bus
  - BTINT [8] - full buffer generates interrupt otherwise circular write
  - BTS_OFF_OS [9] - does not count for priv. level 0
  - BTS_OFF_USR [10] - does not count for priv. level 1,2,3
  - FRZ_LBRS_ON_PMI [11] - freeze LBR stack on a PMI
  - FRZ_PERFMON_ON_PMI [12] - disable all performance counters on a PMI
  - UNCORE_PMI_EN [13] - uncore counter interrupt generation
  - SMM_FRZ [14] - event counters are frozen during SMM

TALOS

Branch Trace Store

- First generation hardware branch tracing via PMU
- Allows configurable memory buffer for trace storage
- MSR_IA32_DS_AREA MSR defines storage location
- DS_AREA_RECORD stored for each branch

```
struct DS_AREA {
    u64 bts_buffer_base;
    u64 bts_index;
    u64 bts_absolute_maximum;
    u64 bts_interrupt_threshold;
    u64 pebs_buffer_base;
    u64 pebs_index;
    u64 pebs_absolute_maximum;
    u64 pebs_interrupt_threshold;
    u64 pebs_event_reset[4];
};

struct DS_AREA_RECORD {
    u64 flags;
    u64 ip;
    u64 regs[16];
    u64 status;
    u64 dla;
    u64 dse;
    u64 lat;
};
```

TALOS

Branch Trace Store



TALOS

Branch Trace Store

- Branches in LBR registers spill to DS_AREA
- Interrupts only when buffer is full
- Steps to enable BTS
  - Allocate memory and set MSR_IA32_DS_AREA
  - Add interrupt handler to IDT
  - Register interrupt vector with APIC
    - apic_write(APIC_LVTPC, pebs_vector);
  - Select events with MSR_IA32_EVNTSEL0
    - EVTSEL_EN | EVTSEL_USR | EVTSEL_OS
  - Enable PEBS mode with MSR_IA32_PEBS_ENABLE
  - Enable CPU perf recording with MSR_IA32_GLOBAL_CTRL
- Significantly faster than BTF
- Still impractical for high speed tracing

TALOS

Intel Processor Trace

- Next generation hardware tracing support
  - Introduced in Broadwell/Skylake architecture
  - Per-hardware tracing thread
- Goal: full system branch tracing with 5-15% overhead

- Software support available in
  - Linux 4.1+ perf subsystem
  - Standalone Linux reference driver simple-pt
  - Intel VTune / System Studio**
    - Remote debugging only
  - Talos IntelPT driver!

Intel Processor Trace

- Features
  - Can trace *SMM, HyperVisor, Kernel, Userspace [CPL -2 to 3]
  - Logs directly to physical memory
    - Bypasses CPU cache and eliminates TLB cache misses
    - Can be a contiguous segment or a set of ranges
    - Ringbuffer snapshot or interrupt mode supported
  - Minimal log format
    - One bit per conditional branch
    - Only indirect branches log dest address
    - Interrupts log source and destination
    - Decoding log requires original binaries and memory map
  - Filter logging based on CR3
  - Linux can automatically add log to coredump
  - GDB Support

TALOS

Intel Processor Trace

- 90+ pages in Intel Software Developer Manuals
- Randomly flipping bits doesn't work here

- Check with CPUID
- EAX = 0x14 - Intel Processor Trace
- EBX
  - Bit 00: If 1, Indicates that IA32_RTIT_CTL.CR3Filter can be set to 1, and that IA32_RTIT_CR3_MATCH MSR can be accessed.
  - Bit 01: If 1, Indicates support of Configurable PSB and Cycle-Accurate Mode.
  - Bit 02: If 1, Indicates support of IP Filtering, TraceStop filtering, and preservation of Intel PT MSRs across warm reset.
  - Bit 03: If 1, Indicates support of MTC timing packet and suppression of COFI-based packets.
- ECX
  - Bit 00: If 1, Tracing can be enabled with IA32_RTIT_CTL.ToPA = 1, hence utilizing the ToPA output scheme; IA32_RTIT_OUTPUT_BASE and IA32_RTIT_OUTPUT_MASK_PTRS MSRs can be accessed.
  - Bit 01: If 1, ToPA tables can hold any number of output entries, up to the maximum allowed by the MaskOrTableOffset field of IA32_RTIT_OUTPUT_MASK_PTRS.
  - Bit 02: If 1, Indicates support of Single-Range Output scheme.
  - Bit 03: If 1, Indicates support of output to Trace Transport subsystem.
  - Bit 31: If 1, Generated packets which contain IP payloads have LIP values, which include the CS base component
- Packet Generation (ECX = 1)
- EAX
  - Bits 2:0: Number of configurable Address Ranges for filtering.
  - Bit 31:16: Bitmap of supported MTC period encodings
- EBX
  - Bits 15-0: Bitmap of supported Cycle Threshold value encodings
  - Bit 31:16: Bitmap of supported Configurable PSB frequency encodings

TALOS

Intel Processor Trace (for programmers)

- Hardware support detection
  - CPUID with leaf 0x7 indicates support for Intel PT
  - If supported, CPUID with leaf 0x14 can return the supported PT features
- Trace Record Filtering
  - Code Privileged Level (CPL) - kernel vs userspace
  - PML4 Page Table – single process / CR3 (page-table) filtering
  - Instruction Pointer – up to 4 ranges of addresses can be specified
- Log Output Configuration
  - Single range
  - Table of Physical Addresses (ToPA)

TALOS

Intel Processor Trace (for programmers)

- Single Buffer Trace Logging
  - Circular or Interrupt modes (Hardware logging support)
  - Reserve memory – *MmAllocateContiguousMemory* (Windows Drivers)
  - Set the proper MSRs
    - MSR_IA32_RTIT_OUTPUT_BASE
    - MSR_IA32_RTIT_OUTPUT_MASK_PTRS
  - Start the Tracing setting the “TraceEn” flag in the control register
  - Processor logs to in a circular-manner unless interrupt flag configured

TALOS

Intel Processor Trace (for programmers)

- Table of Physical Address (ToPA) Trace Logging
  - For large traces, non-contiguous physical memory must be used
  - ToPA is compatible with Windows Memory Descriptor List (MDL)
  - MDL is a Windows data structure for tracking physical->linear mappings
    - ToPA is compatible with Windows MDL data structure!

```
// Grab the physical address:
PHYSICAL_ADDRESS physAddr = MmGetPhysicalAddress(lpBuffVa);
perCpuData.u.Simple.lpTraceBuffPhysAddr = (ULONG_PTR)physAddr.QuadPart;

// Allocate the relative MDL
PMDL pPtMdl = IoAllocateMdl(lpBuffVa, (ULONG)perCpuData.qwBuffSize, FALSE, FALSE, NULL);
if (pPtMdl) perCpuData.pTraceMdl = pPtMdl;
```

TALOS

Intel Processor Trace



mplex log format - decode with opensource libipt library!

TALOS

Intel Processor Trace (for programmers)

- Packet Types
  - Packet Stream Boundary (PSB)
    - Heartbeat packet generated at regular intervals (configurable)
  - Paging Information (PIP)
    - Notifcation of CR3 Page Table changes
  - Timing (TSC, MTC & CYC)
    - Useful for wall-clock comparisons or synchronization of logs across CPU threads
  - Control Flow (TNT, TIP, FUP)
    - TNT – Taken/Not-Taken for conditional branches
    - TIP – Taken IP address for indirect branches
    - FUP – Flow Update

TALOS

Intel Processor Trace



TALOS

Intel Processor Trace

- How to use: Linux perf tools (apt: linux-tools-common)

```
$ perf list | grep intel_pt
intel_pt//                                [Kernel PMU event]

$ perf record -e intel_pt//u date
Sun Oct 11 11:35:07 EDT 2015
[ perf record: Woken up 1 times to write data ]
[ perf record: Captured and wrote 0.027 MB perf.data ]

$ perf report
...
# Samples: 1  of event 'instructions:u'
# Event count (approx.): 157207
#
# Overhead  Command  Shared Object  Symbol
# ........  .......  .............  ............................
#
   100.00%  date     libc-2.21.so   [.] _nl_intern_locale_data
               |
               ---_nl_intern_locale_data
                  _nl_load_locale_from_archive
                  _nl_find_locale
                  setlocale
...
```

Intel Processor Trace

- How to use: simple-pt reference driver

```
% sptcmd  -c tcall taskset -c 0 ./tcall
cpu   0 offset 1027688,  1003 KB, writing to ptout.0
...
Wrote sideband to ptout.sideband
% sptdecode --sideband ptout.sideband --pt ptout.0 | less
TIME      DELTA  INSNs   OPERATION
frequency 32
0        [+0]     [+   1] _dl_aux_init+436
                  [+   6] __libc_start_main+455 -> _dl_discover_osversio
n
...
                  [+  13] __libc_start_main+446 -> main
                  [+   9]     main+22 -> f1
                  [+   4]             f1+9 -> f2
                  [+   2]             f1+19 -> f2
                  [+   5]     main+22 -> f1
                  [+   4]             f1+9 -> f2
                  [+   2]             f1+19 -> f2
                  [+   5]     main+22 -> f1
...
```

TALOS

Intel Processor Trace

- Talos IntelPT driver

```
struct PER_PROCESSOR_PT_DATA {
    LPVOID lpTraceBuffVa;     // + 0x00 - VA Pointer to a contiguous memory buffer
    ULONG_PTR lpTraceBuffPhysAddr;    // + 0x08 - The physical address of the contiguous memory
buffer
    DWORD dwBuffSize;         // + 0x10 - The physical buffer size
    ULONG_PTR lpTargetProcCr3;        // + 0x18 - The process to monitor CR3
};
```

Intel Processor Trace

- Talos IntelPT driver

```
struct INTEL_PT_CAPABILITIES {
    BOOLEAN bCr3Filtering : 1;        // [0] - CR3 Filtering Support (Indicates that
                  // IA32_RTIT_CTL.CR3Filter can be set to 1)
    BOOLEAN bConfPsbAndCycSupported : 1;   // [1] - Configurable PSB and Cycle-Accurate Mode
    BOOLEAN bIpFiltering : 1;     // [2] - IP Filtering and TraceStop   supported, and
                  // Preserve Intel PT MSRs across warm reset
    BOOLEAN bMtcSupport : 1;      // [3] - IA32_RTIT_CTL.MTCEn can be set to 1, and MTC
                  // packets will be generated (section 36.2.5)
    BOOLEAN bTopaOutput : 1;      // [4] - Utilize the ToPA output scheme
    BOOLEAN bTopaMultipleEntries : 1; // [5] - ToPA tables maximum allowed (MaskOrTableOffset)

...
```

Intel Processor Trace

- Talos IntelPT driver

```
    BOOLEAN bSingleRangeSupport : 1;  // [6] - Single-Range Output Supported
    BOOLEAN bTransportOutputSupport : 1;  // [7] - Output to Trace Transport Subsystem
Supported
                                          // (Setting IA32_RTIT_CTL.FabricEn to 1 is
supported)
    BOOLEAN bIpPcksAreLip : 1;        // [8] - IP Payloads are LIP
    BYTE numOfAddrRanges;     // + 0x01 - Number of Address Ranges
    SHORT mtcPeriodBmp;       // + 0x02 - Bitmap of supported MTC Period Encodings
    SHORT cycThresholdBmp;        // + 0x04 - Bitmap of supported Cycle Threshold values
    SHORT psbFreqBmp;         // + 0x06 - Bitmap of supported   Configurable PSB Frequency
encoding
};
```

Intel Processor Trace

- Talos IntelPT driver

```
// Write the target CR3 value
__writemsr(MSR_IA32_RTIT_CR3_MATCH, targetCr3);

// Start tracing:
rtitCtlDesc.Fields.CR3Filter = 1;
rtitCtlDesc.Fields.FabricEn = 0;
rtitCtlDesc.Fields.Os = 0;
rtitCtlDesc.Fields.User = 1;      // Trace the user mode process
rtitCtlDesc.Fields.ToPA = 0;      // We use the single-range output scheme
rtitCtlDesc.Fields.BranchEn = 1;
//if (ptCap.bMtcSupport) {
//   rtitCtlDesc.Fields.MTCEn = 1;
//   rtitCtlDesc.Fields.MTCFreq = 10;
//}
rtitCtlDesc.Fields.TSCEn = 1;
rtitCtlDesc.Fields.TraceEn = 1;        // Switch the tracing to ON dude :-)
__writemsr(MSR_IA32_RTIT_CTL, rtitCtlDesc.All);
```

Intel Processor Trace

- Talos IntelPT driver

```
C:\code\intelpt>instdrv.exe /I windowsptdriver.sys
C:\code\intelpt>testintelpt.exe c:\windows\system32\notepad.exe
C:\code\intelpt>..\libipt\ptdump pt_dump.bin  | findstr /V pad | more
00000000000006e8  psb
00000000000006fe  tsc        4e1ef46cbc
0000000000000708  cbr        1f
000000000000070c  psbend
0000000000000716  tsc        4e1ef8afb9
. . .
0000000000000ce0  cbr        1c
0000000000000cf0  tip        2: ????????4d515400
0000000000000cf5  tnt.8      ..!
0000000000000cf8  tip        2: ????????4bb10ca0
0000000000000cfd  tnt.8      !!....
0000000000000cfe  tnt.8      !
0000000000000d00  tip        2: ????????4d515400
0000000000000d05  tnt.8      ..!
0000000000000d08  tip        2: ????????1a91e4f0
0000000000000d0d  tnt.8      !!!!!!
```

Outro

Conclusion

- Evoloutionary algorithms have a lot to offer for automation
  - https://github.com/talos-vulndev/
- Initial investment in development pays dividends
  - Use correct engine for long term deployment
  - Designing tracing engines is not for everyone
- Hardware tracing is approaching software performance
- This code is opensource software
  - https://github.com/talos-vulndev/
    - `

Thank You!

talosintel.com
blog.talosintel.com
@talossecurity

@richinseattle
rjohnson@moflow.org