

Binance Alpha 2.0 Liquidity Provision Program

Binance Alpha 2.0 integrates Binance Alpha directly within the Binance Exchange, bridging the gap between centralized (CEX) and decentralized (DEX) trading. It enables Binance.com users to access assets, liquidity, and volatility that are not directly available on Binance Spot or Future trading.

Here Binance Alpha 2.0 goes into new phases to allow users to enjoy more liquidity from market makers in addition to the current ones across decentralized exchanges on BSC, Ethereum, Solana, Base, and more.

Binance Alpha 2.0 Liquidity APIs

Besides the current User Interface for Instant and Limit orders, a new suite of APIs is available for market makers to send limit orders. All the limit orders will together join a call-auction-based trade and settlement system to trade. This system is defined with below features that make it different from the order book market Binance.com Spot trading provides:

1. Binance Alpha tokens can only be traded against stablecoins and major native tokens.
2. Only orders with limit prices are allowed, which are all good-till-cancel.
3. Orders are matched with periodic, automated call auctions. Different trading pairs may have different random auction time periods according to the blocking time of different blockchains that the tokens are on.
4. A price range is defined based on the live market prices of the tokens and a series of other parameters, such as the volatility of the token prices. The concluded auction price of each trading pair will be within this corresponding price range.

Similar to the current Alpha 2.0 users, allowed market makers can use their stablecoins and native tokens in their Binance.com 'Funding Wallet' to buy Alpha tokens; their bought tokens will be deposited into their 'Alpha Wallet'; they can sell these tokens into the stablecoins and native tokens back to their Funding Wallet.

Several groups of APIs are available to facilitate the full lifecycle of trades:

- Trade APIs to place, cancel, and query orders
- WebSocket APIs to get real-time feeds about order status in the system
- Fund APIs to withdraw Alpha tokens from Alpha Wallet, while market makers can also deposit Alpha tokens into specified addresses. (Binance.com listed tokens remain with the current deposit/withdrawal process and APIs.)

Please refer to the API documentation for both APIs.

Call Auction Match Logic

Examples

The chosen price level row would have "*" on the row where the price was concluded as the EP because of the column.

Java

// Example A: Choose the largest execution (Step 1)

SUM	SELL	PRICE	BUY	SUM	EXECUTION	IMBALANCE
300		100	150	150	150	-150
300		99		150	150	-150
300	250	98	150	300	300*	0
50	50	97		300	50	250

Java

// Example B: Choose the largest execution (Step 1)

SUM	SELL	PRICE	BUY	SUM	EXECUTION	IMBALANCE
300		100	150	150	150	-150
300		99	50	200	200	-100
300		98		200	200	-100
300	200	97	300	500	300*	200
100	100	96		500	100	400

Java

// Example C: the least abs surplus imbalance (Step 2)

SUM	SELL	PRICE	BUY	SUM	EXECUTION	IMBALANCE
1500		102	300	300	300	-1200
1500		101		300	300	-1200
1500		100	100	400	400	-1100
1500		99	200	600	600	-900

1500	250	98	300	900	900	-600
1250	250	97		900	900	-350
1000	1000	96		900	900	-100*

Java

// Example D: the least abs surplus imbalance (Step 2)

SUM	SELL	PRICE	BUY	SUM	EXECUTION	IMBALANCE
110		102	30	30	30	-80
110		101	10	40	40	-70
110		100		40	40	-70
110		99	50	90	90	-20
110	10	98		90	90	-20
100	50	97		90	90	-10*
50		96	15	105	50	55
50	50	95		105	50	55

Java

// Example E: if several prices have the same smallest absolute surplus amount and are all negative, choose the closest to L to indicate sell pressure (Step 3)

SUM	SELL	PRICE	BUY	SUM	EXECUTION	IMBALANCE
50		102	10	10	10	-40
50		101		10	10	-40
50		100		10	10	-40
50		99		10	10	-40
50		98		10	10	-40
50		97	10	20	20	-30
50		96		20	20	-30
50	50	95		20	20	-30*

Java

// Example F: if several prices have the same smallest absolute surplus amount and are all positive, choose the closest to H to indicate buy pressure (Step 3)

SUM	SELL	PRICE	BUY	SUM	EXECUTION	IMBALANCE
50		99	100	100	50	50*
50		98		100	50	50
50		97		100	50	50
50		96		100	50	50
50		95		100	50	50
50		94		100	50	50
50		93		100	50	50
50	50	92		100	50	50

Java

//Example G: The last price is 99. Choose the closest to the last trade price 99 (Step 4)

SUM	SELL	PRICE	BUY	SUM	EXECUTION	IMBALANCE
50		100	25	25	25	-25
50		99		25	25	-25*
50	25	98		25	25	-25
25		97	25	50	25	25
25		96		50	25	25
25	25	95		50	25	25

Java

//Example H: The last price is 105. Choose the closest to the last trade price 100 (Step 4)

SUM	SELL	PRICE	BUY	SUM	EXECUTION	IMBALANCE
50		100	25	25	25	-25*
50		99		25	25	-25
50	25	98		25	25	-25
25		97	25	50	25	25
25		96		50	25	25

25

25

95

50

25

25

...

Order Fill/Execution

After the execution price EP is concluded. Order match would happen in sequence of the price and time, i.e.

- Orders with best bid price would match with order with best ask price;
- If the orders on one price cannot be fully filled by the opposite orders for the orders with the same price, the orders would be selected based on the time they arrive into RAME or the time set when selecting as candidates. There can be partial filled orders on the leftover side.

Alpha APIs

Quote Assets (USER_DATA)

API Description

Fetch quote assets supported on alpha market.

HTTP Request

GET /sapi/v1/alpha-trade/get-from-asset

Request Weight(IP)

1

Request Parameters

Name	Type	Mandatory	Description
recvWindow	Long	NO	
timestamp	Long	YES	

Response Example

```
[ "USDT", "USDC" ]
```

Exchange Info (USER_DATA)

API Description

Fetch all exchange info supported on alpha market.

HTTP Request

GET /sapi/v1/alpha-trade/get-exchange-info

Request Weight(IP)

1

Request Parameters

Name	Type	Mandatory	Description
recvWindow	Long	NO	
timestamp	Long	YES	

Response Example

```
{
  "timezone": "UTC",
  "assets": [
    {
      "asset": "USDT"
    },
    {
      "asset": "ALPHA_116"
    }
  ],
  "symbols": [
    {
      "symbol": "ALPHA_116USDT",
      "status": "TRADING",
      "baseAsset": "ALPHA_116",
```

```
"quoteAsset": "USDT",
"pricePrecision": 8,
"quantityPrecision": 8,
"baseAssetPrecision": 8,
"quotePrecision": 8,
"filters": [
  {
    "filterType": "PRICE_FILTER",
    "minPrice": "0.10000000",
    "maxPrice": "100000",
    "tickSize": "0.10000000"
  },
  {
    "filterType": "LOT_SIZE",
    "stepSize": "0.00000100",
    "maxQty": "9000000",
    "minQty": "0.00000100"
  },
  {
    "filterType": "MAX_NUM_ORDERS",
    "limit": 200
  },
  {
    "filterType": "MIN_NOTIONAL",
    "minNotional": "5"
  },
  {
    "filterType": "MAX_NOTIONAL",
    "maxNotional": "100000"
  },
  {
    "filterType": "NOTIONAL",
    "minNotional": "5",
    "maxNotional": "100000"
  },
  {
```

```

        "filterType": "PERCENT_PRICE",
        "multiplierDown": "0.01",
        "multiplierUp": "100000"
    },
    {
        "filterType": "PERCENT_PRICE_BY_SIDE",
        "bidMultiplierUp": "100000",
        "askMultiplierUp": "100000",
        "bidMultiplierDown": "0.01",
        "askMultiplierDown": "0.01"
    }
],
"orderTypes": [
    "LIMIT"
]
}
]
}

```

Commission Fee (USER_DATA)

API Description

Fetch all commission fee info by symbol. Need to divide by 1 million .

HTTP Request

GET /sapi/v1/alpha-trade/get-fee-rate

Request Weight(IP)

1

Request Parameters

Name	Type	Mandatory	Description
recvWindow	Long	NO	
timestamp	Long	YES	
symbol	Long	YES	

Response Example

```
{
  "buyerCommission": 1000,
  "sellerCommission": 1000
}
```

Listen Key (TRADE)

API Description

Get listen key to subscribe websocket

HTTP Request

POST /sapi/v1/alpha-trade/get-listen-key

Request Weight(IP)

1

Request Parameters

Name	Type	Mandatory	Description
------	------	-----------	-------------

recvWindow	Long	NO	
timestamp	Long	YES	

Response Example

```
{
  "listenKey":
    "df1f0c273c887e03f2d2ca12834994e8"
}
```

Place Order (USER_DATA)

API Description

Place alpha order

HTTP Request

POST /sapi/v1/alpha-trade/order/place

Request Weight(IP)

1

Request Parameters

Name	Type	Mandatory	Description
recvWindow	Long	NO	
timestamp	Long	YES	
baseAsset	String	YES	

quoteAsset	String	YES	
side	Enum	YES	BUY/SELL
quantity	Decimal	YES	
price	Decimal	YES	^[a-zA-Z0-9-_{32,36}\$
clientOrderId	String	NO	It is recommended to use uuid

Response Example

```
{
  "orderId": "144193",
  "status": "S" // P:Processing, S:Success, F:Failure
}
```

Cancel Order (TRADE)

API Description

Cancel alpha order

HTTP Request

POST /sapi/v1/alpha-trade/order/cancel

Request Weight(IP)

1

Request Parameters

Name	Type	Mandatory	Description
recvWindow	Long	NO	
timestamp	Long	YES	
symbol	String	YES	
orderId	String	YES	

Response Example

```
{
  "orderId": "144193",
  "orderStatus": "CANCELED"
}
```

Cancel All Order (TRADE)

API Description

Cancel all alpha order

HTTP Request

POST /sapi/v1/alpha-trade/order/cancel-all

Request Weight(IP)

1

Request Parameters

Name	Type	Mandatory	Description
------	------	-----------	-------------

recvWindow	Long	NO	
timestamp	Long	YES	
symbol	String	NO	cancel all orders by symbol
baseAsset	String	NO	cancel all orders by baseAsset

if both symbol & baseAsset is not input, then we will cancel all the open orders

Response Example

```
{
  "success": true
}
```

Get Open Order (TRADE)

API Description

Get open orders

HTTP Request

GET /sapi/v1/alpha-trade/order/get-open-order

Request Weight(IP)

1

Request Parameters

Name	Type	Mandatory	Description
recvWindow	Long	NO	
timestamp	Long	YES	

symbol	String	NO	
side	Enum	NO	BUY/SELL

Response Example

```
[
  {
    "orderId": "144195",
    "symbol": "ALPHA_172USDT",
    "status": "NEW",
    "clientOrderId": "default_b3e7de38d9df4fc49bc7ba207f25",
    "price": "0.00000049",
    "avgPrice": "0",
    "origQty": "12245100.47",
    "executedQty": "0",
    "cumQuote": "0",
    "timeInForce": "GTC",
    "type": "LIMIT",
    "side": "BUY",
    "stopPrice": "0",
    "origType": "LIMIT",
    "time": 1743506038544,
    "updateTime": 1743506038544,
    "orderListId": "-1",
    "pageId": "18546215",
    "baseAsset": "ALPHA_172",
    "quoteAsset": "USDT"
  }
]
```

Get Order History (TRADE)

API Description

Get order history

HTTP Request

GET /sapi/v1/alpha-trade/order/get-order-history

Request Weight(IP)

1

Request Parameters

Name	Type	Mandatory	Description
recvWindow	Long	NO	
timestamp	Long	YES	
baseAsset	String	NO	
side	Enum	NO	BUY/SELL
orderStatus	String	NO	NEW,CANCELED,FILLED,PARTIALLY_FILLED any combination, separated by comma
startTime	Long	NO	
endTime	Long	NO	
limit	Long	NO	
pageld	Long	NO	pageld for pagination order:desc

Response Example

```
[
  {
    "orderId": "144195",
    "symbol": "ALPHA_172USDT",
```

```
    "status": "NEW",
    "clientOrderId": "default_b3e7de38d9df4fc49bc7ba207f25",
    "price": "0.00000049",
    "avgPrice": "0",
    "origQty": "12245100.47",
    "executedQty": "0",
    "cumQuote": "0",
    "timeInForce": "GTC",
    "type": "LIMIT",
    "side": "BUY",
    "stopPrice": "0",
    "origType": "LIMIT",
    "time": 1743506038544,
    "updateTime": 1743506038544,
    "orderListId": "-1",
    "pageId": "18546215",
    "baseAsset": "ALPHA_172",
    "quoteAsset": "USDT"
  }
]
```

Get Order Detail (TRADE)

API Description

Get order history

HTTP Request

GET /sapi/v1/alpha-trade/order/get-order-detail

Request Weight(IP)

Request Parameters

Name	Type	Mandatory	Description
recvWindow	Long	NO	
timestamp	Long	YES	
symbol	String	YES	
orderId	String	YES	

Response Example

```
[
  {
    "orderId": "144195",
    "symbol": "ALPHA_172USDT",
    "status": "NEW",
    "clientOrderId": "default_b3e7de38d9df4fc49bc7ba207f25",
    "price": "0.00000049",
    "avgPrice": "0",
    "origQty": "12245100.47",
    "executedQty": "0",
    "cumQuote": "0",
    "timeInForce": "GTC",
    "type": "LIMIT",
    "side": "BUY",
    "stopPrice": "0",
    "origType": "LIMIT",
    "time": 1743506038544,
    "updateTime": 1743506038544,
    "orderListId": "-1",
    "pageId": "18546215",
    "baseAsset": "ALPHA_172",
    "quoteAsset": "USDT"
  }
]
```

```
}  
]
```

Get User Trades (TRADE)

API Description

Get user trades

HTTP Request

GET /sapi/v1/alpha-trade/order/get-user-trades

Request Weight(IP)

1

Request Parameters

Name	Type	Mandatory	Description
recvWindow	Long	NO	
timestamp	Long	YES	
baseAsset	String	NO	
side	Enum	NO	BUY/SELL
orderId	String	NO	
startTime	Long	NO	
endTime	Long	NO	
limit	Long	NO	

pageId	Long	NO	pageId for pagination order:desc
--------	------	----	----------------------------------

(startTime or endTime) required or orderId is required

Response Example

```
[
  {
    "symbol": "ALPHA_172USDT",
    "id": "708",
    "orderId": "96311",
    "tradeId": "708",
    "side": "BUY",
    "price": "0.00003132000",
    "qty": "122451.4700",
    "quoteQty": "3.83518004",
    "commission": "122.4515",
    "commissionAsset": "ALPHA_172",
    "time": 1743425641228,
    "pageId": "15942375",
    "buyer": true,
    "baseAsset": "ALPHA_172",
    "quoteAsset": "USDT",
    "orderType": "LIMIT",
    "lastTrade": false
  }
]
```

Kline Data (USER_DATA)

API Description

Fetch kline data supported on alpha market.

HTTP Request

GET /sapi/v1/alpha-trade/market/klines

Request Weight(IP)

1

Request Parameters

Name	Type	Mandatory	Description
symbol	String	YES	
interval	Enum	YES	interval: [1m, 3m, 5m, 15m, 30m, 1h, 2h, 4h, 6h, 8h, 12h, 1d, 3d, 1w, 1M]
startTime	Long	NO	
endTime	Long	NO	
limit	Integer	NO	
recvWindow	Long	NO	
timestamp	Long	YES	

Response Example

```
[  
  1499040000000,  
  "0.01634790",  
  "0.80000000", // High  
  "0.01575800",  
  "0.01577100",  
  "148976.11427815",  
  1499644799999,  
  "2434.19055334",  
]
```

```

308,

    "1756.87402397",
    "28.46694368",
    "0"
]
[
    [
        "1744977600000
        ",
        // Open time
        "0.19910000",
        // Open
        "0.19910000",
        // High
        "0.19910000",
        // Low
        "0.19910000",
        // Close
        "0.00000000",
        // Volume
        "1744981199999
        ",
        // Close time
        "0.00000000",
        // Quote asset volume
        "0",
        // Number of trades
        // Taker buy base asset volume, will remove
        "0.00000000",
        the field,
        legacy code
        // Taker buy quote asset volume, will remove
        "0.00000000",
        the field,
        legacy code
        "0"
        // Ignore. will remove the field, legacy code
    ],
    [
        "1744981200000
        ",
        "0.19910000",
        "0.19910000",
        "0.19910000",
        "0.19910000",
        "0.00000000",
        "1744984799999",
        "0.00000000",
        "0",
        "0.00000000",
        "0.00000000",
        "0"
    ]
]

```

]

Ticker Info (USER_DATA)

API Description

Fetch 24hr ticker price change statistics

HTTP Request

GET /sapi/v1/alpha-trade/market/ticker

Request Weight(IP)

1

Request Parameters

Name	Type	Mandatory	Description
symbol	String	YES	
recvWindow	Long	NO	
timestamp	Long	YES	

Response Example

```
{  
  "symbol": "ALPHA_175USDT",  
  "priceChange": "0.05320000",  
  "priceChangePercent": "36.463",
```

```
{
  "weightedAvgPrice": "0.16324830",
  "lastPrice": "0.19910000",
  "lastQty": "44.00000000",
  "openPrice": "0.14590000",
  "highPrice": "0.19910000",
  "lowPrice": "0.13170000",
  "volume": "1056.00000000",
  "quoteVolume": "172.39020000",
  "openTime": 1744105260000,
  "closeTime": 1744189233388,
  "firstId": 93,
  "lastId": 115,
  "count": 24
}
```

Symbol Price Ticker (USER_DATA)

API Description

Fetch symbol price ticker.

HTTP Request

GET /sapi/v1/alpha-trade/market/ticker-price

Request Weight(IP)

1

Request Parameters

Name	Type	Mandatory	Description
symbol	String	YES	

recvWindow	Long	NO	
timestamp	Long	YES	

Response Example

```
{
  "symbol": "ALPHA_175USDT",
  "price": "0.19910000",
  "time": 1744188294643
}
```

Aggregate Trade List (USER_DATA)

API Description

Fetch aggregate trade list

HTTP Request

GET /sapi/v1/alpha-trade/market/agg-trades

Request Weight(IP)

1

Request Parameters

Name	Type	Mandatory	Description
symbol	String	YES	
fromId	Long	NO	
startTime	Long	NO	

endTime	Long	NO	
limit	Integer	NO	
recvWindow	Long	NO	
timestamp	Long	YES	

Response Example

```
[
  {
    "a": 114, // aggTradeId
    "p": "0.19910000", // trade price, aka equilibrium price
    "q": "44.00000000", // quantity, trade total qty
    "f": 114, // firstBatchTradeId, orders are matches in batches at an
    random
    interval, not immediately filled
    "l": 114, // lastBatchTradeId, orders are matches in batches, not
    immediately
    filled
    "m": false, // isBuyerMaker, best trade will be removed
    // there are no maker-taker fees
  },
  {
    "a": 115,
    "p": "0.19910000",
    "q": "44.00000000",
    "f": 115,
    "l": 115,
    "m": false
  }
]
```

Symbol Order Book Ticker (USER_DATA)

API Description

Fetch symbol order book ticker

HTTP Request

GET /sapi/v1/alpha-trade/market/book-ticker

Request Weight(IP)

1

Request Parameters

Name	Type	Mandatory	Description
symbol	String	YES	
recvWindow	Long	NO	
timestamp	Long	YES	

Response Example

```
{
  "symbol": "ALPHA_175USDT",
  "bidPrice": "0.00000000",
  "bidQty": "0.00000000",
  "askPrice": "0.13010000",
  "askQty": "47.00000000",
  "time": 1744984787471
}
```

Order Book Depth (USER_DATA)

API Description

Fetch order book depth

HTTP Request

GET /sapi/v1/alpha-trade/market/depth

Request Weight(IP)

1

Request Parameters

Name	Type	Mandatory	Description
symbol	String	YES	
limit	Integer	NO	
recvWindow	Long	NO	
timestamp	Long	YES	

Response Example

```
{
  "lastUpdateId": 181404900,
  "symbol": "ALPHA_175USDT",
  "bids": [
    [
      "0.13010000", // PRICE
      "47.00000000" // QTY
    ]
  ],
  "asks": [
    [
      "0.13010000", // PRICE
      "47.00000000" // QTY
    ]
  ]
}
```

```
],  
  "t": 0, // Transaction time  
  "e": 0 // Message output time  
}
```

Alpha Asset Balance (USER_DATA)

API Description

Fetch alpha wallet asset balance

HTTP Request

GET /sapi/v1/asset/get-alpha-asset

Request Weight(IP)

1

Request Parameters

Name	Type	Mandatory	Description
recvWindow	Long	NO	
timestamp	Long	YES	

Response Example

```
[  
  {  
    "chainId": "56",  
    "contractAddress": "0xe6df05ce8c8301223373cf5b969afcb1498c5528",  
    "alphaId": "ALPHA_210",  
    "cexAssetCode": "",  
    "free": "9",
```

```
    "freeze": "1",
    "locked": "1",
    "withdrawing": "1",
    "amount": "12",
    "valuation": "572.54839554"
  },
  {
    "chainId": "",
    "contractAddress": "",
    "alphaId": "",
    "cexAssetCode": "USDT",
    "free": "9",
    "freeze": "1",
    "locked": "1",
    "withdrawing": "1",
    "amount": "12",
    "valuation": "12"
  }
]
```

Alpha Token Mapping (USER_DATA)

API Description

Fetch alphald & CA mapping info

HTTP Request

GET /sapi/v1/alpha-trade/token/all/list

Request Weight(IP)

1

Request Parameters

Name	Type	Mandatory	Description
recvWindow	Long	NO	

timestamp	Long	YES	
-----------	------	-----	--

Response Example

```
[
  {
    "tokenId": "2CBEADBC555C72F33ACE06724CE40F09",
    "chainId": "146", // chain id
    "chainIconUrl":
      "https://www.binance.com/image/admin_mgs_image_upload/20250313/2ee3cdc6-417a-4509-a63d-w975e2599eaben.png",
    "chainName": "Sonic",
    "contractAddress": "0x79bbf4508b1391af3a0f4b30bb5fc4aa9ab0e07c", //
    address
    "name": "HeyAnon",
    "symbol": "Anon",
    "price": "5.404655700848514",
    "percentChange24h": "5.27",
    "volume24h": "867323.646352",
    "marketCap": "85137306.812400260985844151688",
    "fdv": "85137306.812400260985844151688",
    "liquidity": "579060.947307",
    "totalSupply": "15752586.570692",
    "circulatingSupply": "15752586.570692",
    "holders": "1",
    "decimals": 18,
    "listingCex": false,
    "hotTag": false,
    "cexCoinName": "",
    "canTransfer": false,
    "denomination": 1,
    "offline": true,
    "tradeDecimal": 8,
    "alphaId": "ALPHA_1000", //alpha token
    "offsell": false,
    "priceHigh24h": "5.491860723628665",
    "priceLow24h": "5.404655700848514",
```

```
        "onlineTge": false,  
        "onlineAirdrop": false  
    }  
]
```

Alpha transfer between master and subaccount

Please refer to:

https://developers.binance.com/docs/sub_account/asset-management/Universal-Transfer

Alpha Withdraw

API Description

Submit a withdrawal request.

HTTP Request

POST /sapi/v1/capital/alpha-withdraw/apply

Request Weight(IP)

1

Request param:

Name	Type	Required	Description
network	string	yes	network code <-> chain id
alphald	string	yes	alpha id <-> coin
contractAddress	string	yes	token contract address
address	string	yes	target address
addressTag	string	no	address memo
amount	decimal	yes	withdraw amount
clientOrderId	string	no	client id for withdraw
recvWindow	long	no	

timestamp	long	yes	
-----------	------	-----	--

API Response:

```
{
  "id":"string" // withdraw id
}
```

Alpha Withdraw History

API Description

Fetch withdraw history.

HTTP Request

GET /sapi/v1/capital/alpha-withdraw/history

Request Weight(IP)

1

Request param:

Name	Type	Required	Description
alphaId	string	no	alpha id
clientId	string	no	client id for withdraw
status	int	no	withdraw status (2:awaiting approval,3:rejected,4:processing,5:failed,6:success)
startTime	long	no	Default: 90 days from current timestamp
endTime	long	no	Default: present timestamp
offset	int	no	Default:0
limit	int	no	Default: 1000, Max: 1000
idList	string	no	id list returned in the response of POST /sapi/v1/capital/alpha-withdraw/apply, separated by ,

recvWindow	long	no	
timestamp	long	yes	

API Response:

```
[
  {
    "id": "string",
    "network": "string",
    "alphaId": "string",
    "contractAddress": "string",
    "coinName": "string",
    "address": "string",
    "addressTag": "string",
    "amount": 0,
    "txId": "string",
    "applyTime": "string",
    "completeTime": "string",
    "confirmNo": 0,
    "status": 0,
    "transactionFee": 0,
    "info": "string"
  }
]
```

Alpha Deposit History

API Description

Fetch deposit history.

HTTP Request

GET /sapi/v1/capital/alpha-deposit/history

Request Weight(IP)

1

Request Param:

Name	Type	Required	Description
alphaid	string	no	alpha id

txId	string	no	tx hash
status	int	no	depoist status, 0.pending, 1.success, 2.rejected, 5.awaiting approval, 6.credited but cannot withdraw
startTime	long	no	Default: 90 days from current timestamp
endTime	long	no	Default: present timestamp
includeSource	boolean	no	Default: false, return sourceAddressfield when set to true
offset	int	no	Default:0
limit	int	no	Default:1000, Max:1000
recvWindow	long	no	
timestamp	long	yes	

API Response:

```
[
  {
    "id": "string",
    "network":"string",
    "alphahId":"string",
    "contractAddress":"string",
    "coinName":"string",
    "address": "string",
    "addressTag": "string",
    "amount": 0,
    "txId": "string",
    "completeTime": 0,
    "confirmationNo": "string",
    "insertTime": 0,
    "sourceAddress": "string",
    "status": 0,
    "unlockConfirm": 0
  }
]
```

Alpha Fetch deposit address

API Description

Fetch deposit history.

HTTP Request

GET /sapi/v1/capital/alpha-deposit/address

Request Weight(IP)

1

Request Param:

name	type	required	description
network	string	yes	
recvWindow	long	no	
timestamp	long	yes	

API Response: `

```
{
  "network": "BTC",
  "address": "1HPn8Rx2y6nNSfagQBKy27GB99Vbzg89wv",
  "tag": ""
}
```

Websocket

<wss://nbstream.binance.com/w3w/alpha>

Subscribe one/multiple stream(s)

```
{ "method": "SUBSCRIBE", "params": ["alpha_111usdt@depth",
"f79757ca63456c313d5fbd4106b5b09a"], "id": 1 } //
f79757ca63456c313d5fbd4106b5b09a is the listen key
```

Received data will be in json format, the stream data will be inside the 'data' field.

```
{ "stream": "alpha_111usdt@depth", "data": <json_data> }
```

Available streams 'data' format (all <symbol> in stream names are in lowercase)

<symbol>@miniTicker

```
{
  "e": "24hrMiniTicker",
  "E": 1676980794596, // timestamp
  "s": "ALPHA_111USDT",
  "c": "265.000000000", // lastPrice
  "o": "265.000000000", // openPrice
  "h": "265.000000000", // highPrice
  "l": "265.000000000", // lowPrice
  "v": "7.037735", // volume
  "q": "1864.999775000" // quoteVolume
}
```

<symbol>@ticker

```
{
  "e": "24hrTicker",
  "E": 1676982939357,
  "s": "ALPHA_111USDT",
  "p": "0.000000000", // priceChange
  "P": "0.00", // priceChangePercent
  "w": "265.000000000", // weightedAvgPrice
  "c": "265.000000000", // lastPrice
  "Q": "0.339615", // lastQty
  "o": "265.000000000", // openPrice
  "h": "265.000000000", // highPrice
  "l": "265.000000000", // lowPrice
  "v": "8.037735", // volume
  "q": "2129.999775000", // quoteVolume
  "O": 1676899380000, // openTime
  "C": 1676982939337, // closeTime
  "F": 1381, // firstTradeId
  "L": 1397, // lastTradeId
  "n": 17 // numOfTrades
}
```

<symbol>@aggTrade

```
{
  "e": "aggTrade",
  "E": 1676985687671, // currentTimeMillis
  "a": 1106,           // aggTradeId
  "s": "ALPHA_111USDT",
  "p": "265.000000000", // price
  "q": "0.660385", // quantity
  "f": 1398,          // firstTradeId
  "l": 1398,          // lastTradeId
  "T": 1676985687498, // lastTransactTime
  "m": false          // isBuyerMaker
  (not useful, since alpha limit trading has no maker taker concept)
}
```

<symbol>@trade

```
{
  "e": "trade",
  "E": 1677039110296, // currentTimeMillis
  "T": 1677039110268, // timeStampOfExecutionReport
  "s": "ALPHA_111USDT",
  "t": 1406,           // batch trade id, all trades with same symbol
  auction share same value
  (trades are executed in batch because of the auction matching
  mechanism)
  "p": "265.500000000", // fillPrice
  "q": "0.100000",      // fillQty
  "m": true             // isBuyerMaker
  (not useful, since alpha limit trading has no maker taker concept)
```

```
}
```

Depth Diff: <symbol>@depth

```
{  
  "e": "depthUpdate",  
  "E": 1677038400454, // currentTimeMillis  
  "T": 1677038400160, // transactTime  
  "s": "ALPHA_111USDT",  
  "U": 306910,        // firstUpdateId  
  "u": 306910,        // lastUpdateId  
  "pu": -1,           // prevUpdateId  
  "b": [],            // bid  
  "a": [              // ask  
    [  
      "300.000000", // price  
      "0.20"        // qty  
    ]  
  ]  
}
```

Depth Diff Custom Interval: <symbol>@depth@0ms available values: [0ms, 100ms, 500ms]

```
{
  "e": "depthUpdate",
  "E": 1677038400454, // currentTimeMillis
  "T": 1677038400160, // transactTime
  "s": "ALPHA_111USDT",
  "U": 306910,          // firstUpdateId
  "u": 306910,          // lastUpdateId
  "pu": -1,             // prevUpdateId
  "b": [],              // bid
  "a": [                // ask
    [
      "300.000000", // price
      "0.20"        // qty
    ]
  ]
}
```

Depth Partial: <symbol>@depth5 available values: [5, 10, 20, 50]

```
{
  "e": "depthUpdate",
  "E": 1677055009172, // currentTimeMillis
  "T": 1677055008894, // transactTime
  "s": "ALPHA_111USDT",
  "U": 30608390,      // firstUpdateId
  "u": 30608390,      // lastUpdateId
  "pu": 30608383,     // prevUpdateId
  "b": [
    [
      "265.5000000000",
      "1.600000"
    ],
    [
      "265.0000000000",
      "2.339615"
    ],
    [
      "256.0000000000",
      "1.325781"
    ],
    [
      "255.5000000000",
      "1.000000"
    ],
    [
      "255.0000000000",
```

```
        "5.000000"
    ]
],
"a": [
    [
        "266.000000000",
        "1.924814"
    ],
    [
        "275.000000000",
        "3.000000"
    ]
]
}
```

<symbol>@bookTicker

```
{
    "u": 30608330,    // update id
    "e": "bookTicker",
    "s": "ALPHA_111USDT",
    "b": "265.500000000", // bestBidPrice
    "B": "2.000000",      // bestBidQty
    "a": "266.000000000", // bestAskPrice
    "A": "1.962407",      // bestAskQty
    "T": 1676989489943,   // lastTransactionTime
    "E": 1676989489958.   // currentTimeMillis
}
```

<symbol>@bookTicker

```
{  
  "u": 30608330,    // update id  
  "e": "bookTicker",  
  "s": "ALPHA_111USDT",  
  "b": "265.500000000", // bestBidPrice  
  "B": "2.000000",      // bestBidQty  
  "a": "266.000000000", // bestAskPrice  
  "A": "1.962407",      // bestAskQty  
  "T": 1676989489943,   // lastTransactionTime  
  "E": 1676989489958.   // currentTimeMillis  
}
```

!bookTicker (all symbols' book tickers update)

```
[{  
  "u": 30608330,  
  "e": "bookTicker",  
  "s": "ALPHA_111USDT",  
  "b": "265.500000000",  
  "B": "2.000000",  
  "a": "266.000000000",  
  "A": "1.962407",  
  "T": 1676989489943,  
  "E": 1676989489958  
}]
```

!miniTicker@arr (all symbols' mini tickers update)

```
[  
  {  
    "e": "24hrMiniTicker",  
    "E": 1677038094077,  
    "s": "ALPHA_111USDT",  
    "c": "265.500000000",  
    "o": "265.000000000",  
    "h": "266.000000000",  
    "l": "265.000000000",  
    "v": "10.997978",  
    "q": "2916.151763000"  
  }  
]
```

!ticker@arr (all symbols' tickers update)

```
[
  {
    "e": "24hrTicker",
    "E": 1677041026812,
    "s": "ALPHA_111USDT",
    "p": "0.500000000",
    "P": "0.189",
    "w": "265.16264795",
    "c": "265.500000000",
    "Q": "0.100000",
    "o": "265.000000000",
    "h": "266.000000000",
    "l": "265.000000000",
    "v": "11.297978",
    "q": "2995.801763000",
    "O": 1676980020000,
    "C": 1677041026788,
    "F": 1384,
    "L": 1408,
    "n": 25
  }
]
```

listen key stream

(listen key will expire in 1 hour, you can call the get listen key API to refresh the listen key. If the listen key not expired when calling the get listen key API, same listen key will be return and get extended 1 hour)

```
// auction window push
{
  "symbols": [
    "ALPHA_172USDC",
    "ALPHA_22USDC"
  ],
  "auctionWindowEndTimes": [
    1742984540012,
    1742984541783,
    1742984543178,
    1742984544736,
    1742984546300
  ],
  "batchId": 15917,
  "e": "auctionWindowUpdate"
}

// order push
{
  "s": "ALPHA_130USDT", // symbol
  "c": "Xzh0gnxT41PStbwqOtXnjD", // client order id
  "S": "SELL", // order direction
  "o": "LIMIT", // order type
  "f": "GTC", // Time in force
  "q": "10.001000", // Order quantity
  "p": "19.1000000000", // Order price
  "ap": "19.0999999955550656", //average price
}
```

```

"P":"0", //stop price
"x":"TRADE", // Current execution type
"X":"PARTIALLY_FILLED", // Current order status
"i":"27", // Order ID
"l":"1", // Last executed quantity
"z":"8.999000", // Cumulative filled quantity
"L":"19.1000000000", // Last executed price
"n":"0.00382000", // Commission amount, absent if no commission
"N":"ALPHA_130", // Commission asset, absent if no commission
"T":1649926447190,, //Transaction Time
"t":"18", // batch trade id, all trades with same symbol auction
share same value

(trades are executing in batch because of the auction matching
mechanism)

"m":true, // is this trade the maker side?
(not useful, since alpha limit trading has no maker taker concept)
"ot":"LIMIT", //original order type
"O":0, // Order creation time
"Z":"171.88089996", // Cumulative quote asset transacted quantity
"u":1649926447190, //Transaction Time, same as T
"Y":"19.1000000000000000", // Last quote asset transacted quantity
(i.e. lastPrice * lastQty)
"Q":"0", // Quote Order Qty
"e":"executionReport", // event
"E":1649926447209, // event time,
"ba": ALPHA_130, // base asset
"qa": USDT // quote asset
}
// index price push
{

```

```

"indexPriceInfo": [
  {
    "tokenId": "ALPHA_131",
    "price": "0.0007072874583545417",    // index price
    "upperBand": "0.000742651831272268", // final matching price will
    be less than or equal to the upper band price
    "lowerBand": "0.000671923085436814", // final matching price will
    be greater than or equal to the lower band price
    "time": 1745413782420
  },
  {
    "tokenId": "ALPHA_152",
    "price": "152.86007924947654",
    "upperBand": "160.503083211950367",
    "lowerBand": "145.217075287002713",
    "time": 1745413782420
  }
],
"e": "indexPriceUpdate"
}

// listen key expired event
{
  "E": 1746199438136,
  "e": "listenKeyExpired"
}

```

<symbol>@kline_<interval> interval available values: [1m, 3m, 5m, 15m, 30m, 1h, 2h, 4h, 6h, 8h, 12h, 1d, 3d, 1w, 1M]

```

{
  "e": "kline",
  "E": 1677132298231,    // currentTimeMillis
  "s": "ALPHA_111USDT",
  "k": {
    "t": 1677132000000, // openTime
    "T": 1677132899999, // closeTime
    "s": "ALPHA_111USDT",
    "i": "15m",          // interval
    "f": 28,              // firstBatchTradeId
    "L": 28,              // lastBatchTradeId
    "o": "260.000000000", // open
    "c": "260.000000000", // close
    "h": "260.000000000", // high
    "l": "260.000000000", // low
    "v": "0.100000",      // volume
    "n": 1,               // numberOfTrades
    "x": false,           // isClosed
    "q": "26.000000000",  // quoteVolume
    "V": "0.000000",      // takerBuyVolume
    (not useful, since alpha limit trading has no maker taker concept)
    "Q": "0",             // takerBuyQuoteVolume
    (not useful, since alpha limit trading has no maker taker concept)
    "B": "0"              // always 0
  }
}

```

How to manage a local order book correctly

1. Open a stream to <wss://nbstream.binance.com/w3w/alpha> Subscribe symbol depth ws by sending message `{"method":"SUBSCRIBE","params":["ALPHA_111USDT@depth"],"id":1}`

2. Buffer the events you receive from the stream. For same price, latest received update covers the previous one.
3. Get a depth snapshot from SAPI get depth
4. Drop any event where **u** is < **lastUpdateId** in the snapshot.
5. The first processed event should have **U** <= **lastUpdateId** AND **u** >= **lastUpdateId**.
6. While listening to the stream, each new event's **pu** should be equal to the previous event's **u**, otherwise initialize the process from step 3.
7. The data in each event is the **absolute** quantity for a price level.
8. If the quantity is 0, **remove** the price level.
9. Receiving an event that removes a price level that is not in your local order book can happen and is normal.

FAQ

Q) Only Binance Alpha tokens are going to be available?

A: Yes, and once Alpha tokens are listed in Spot, they will be delisted

Q) Will MMs be matched only with retail or other MMs?

A: Everyone can match everyone for now

Q) If two MMs have a limit order with the same price, how will execution logic work?

A: price first and then time

Q) From the doc it seems that external withdrawals of Alpha tokens are allowed, but will it be allowed to withdraw those to clients' Fireblocks address? to what addresses we can send?

A: it follows same whitelist address of binance exchange

Q) Will there be any trading limits?

A: exchange_info API will return most of the limits

Q) all data seems to be only accessible with api key, correct?

A: yes

Q) For the order books, I assume we will see crossed orderbook in the depth feeds, is there also a feed that publishes the indicative uncross price?

A: yes, it's periodically call auction base, you will see crossed orderbook. Please refer to the auction logic for potential price based on the orderbook.

Q) is order placement cancellation solely accessible through rest?

A: Yes, for now.

Q) what api keys are supported? also ed25519?

A: Whatever is supported by binance exchange