

Table 1: Bootstrap-percentile interval coverage of $\log \text{HR}_p(l)$ for the knot-search and term-search RCsplines, by true weighting shape and lag l . For each of 300 simulated data sets, the $\widehat{\log \text{HR}_p(l)}$ is estimated and a 95% percentile interval is obtained from 300 cluster bootstrap resamples.

Method	Lag l	$\log \text{HR}_p(l)$	Median $\widehat{\log \text{HR}_p(l)}$	Coverage	Empirical 95% interval	Mean bootstrap 95% interval
<i>Unimodal</i>						
Knot-search	1	0.0076	0.0069	0.7833	[0.0056, 0.0081]	[0.0055, 0.0082]
	8	0.0091	0.0089	0.9533	[0.0072, 0.0101]	[0.0073, 0.0102]
	15	0.0004	0.0005	0.9467	[-0.0032, 0.0031]	[-0.0030, 0.0032]
Term-search	1	0.0076	0.0064	0.9533	[0.0028, 0.0138]	[0.0013, 0.0141]
	8	0.0091	0.0091	0.9533	[0.0032, 0.0157]	[0.0026, 0.0159]
	15	0.0004	0.0004	0.9500	[-0.0055, 0.0056]	[-0.0051, 0.0056]
<i>Damped exponential</i>						
Knot-search	1	0.0246	0.0247	0.9367	[0.0234, 0.0264]	[0.0233, 0.0266]
	8	0.0061	0.0059	0.9367	[0.0047, 0.0077]	[0.0046, 0.0079]
	15	0.0015	0.0016	0.9500	[-0.0013, 0.0055]	[-0.0017, 0.0054]
Term-search	1	0.0246	0.0256	0.9500	[0.0175, 0.0293]	[0.0174, 0.0323]
	8	0.0061	0.0060	0.9767	[-0.0005, 0.0121]	[-0.0016, 0.0138]
	15	0.0015	0.0016	0.9633	[-0.0041, 0.0078]	[-0.0044, 0.0080]
<i>Bimodal 1</i>						
Knot-search	1	0.0182	0.0188	0.4167	[0.0179, 0.0196]	[0.0183, 0.0199]
	8	-0.0027	-0.0047	0.0000	[-0.0053, -0.0037]	[-0.0054, -0.0038]
	15	-0.0097	-0.0102	0.8933	[-0.0119, -0.0074]	[-0.0118, -0.0082]
Term-search	1	0.0182	0.0182	0.9633	[0.0145, 0.0219]	[0.0148, 0.0221]
	8	-0.0027	-0.0028	0.9767	[-0.0061, 0.0007]	[-0.0064, 0.0008]
	15	-0.0097	-0.0096	0.9600	[-0.0123, -0.0072]	[-0.0127, -0.0070]
<i>Bimodal 2</i>						
Knot-search	1	0.0182	0.0188	0.8833	[0.0171, 0.0207]	[0.0171, 0.0206]
	8	0.0021	0.0013	0.7933	[-0.0006, 0.0032]	[-0.0006, 0.0029]
	15	0.0019	0.0012	0.9100	[-0.0025, 0.0043]	[-0.0028, 0.0042]
Term-search	1	0.0182	0.0173	0.9533	[0.0127, 0.0275]	[0.0104, 0.0271]
	8	0.0021	0.0020	0.9533	[-0.0053, 0.0099]	[-0.0064, 0.0102]
	15	0.0019	0.0017	0.9733	[-0.0040, 0.0077]	[-0.0047, 0.0087]
<i>Constant null effects</i>						
Knot-search	1	0.0000	0.0000	0.9633	[-0.0005, 0.0007]	[-0.0006, 0.0008]
	8	0.0000	0.0000	0.9600	[-0.0007, 0.0008]	[-0.0007, 0.0008]
	15	0.0000	0.0000	0.9500	[-0.0018, 0.0015]	[-0.0016, 0.0016]
Term-search	1	0.0000	0.0000	0.9933	[-0.0033, 0.0025]	[-0.0035, 0.0032]
	8	0.0000	0.0000	0.9767	[-0.0029, 0.0030]	[-0.0035, 0.0035]
	15	0.0000	0.0000	0.9600	[-0.0026, 0.0023]	[-0.0029, 0.0027]
<i>Constant positive effects</i>						
Knot-search	1	0.0100	0.0100	0.9567	[0.0082, 0.0120]	[0.0081, 0.0120]
	8	0.0100	0.0101	0.9767	[0.0083, 0.0116]	[0.0080, 0.0122]
	15	0.0100	0.0100	0.9700	[0.0055, 0.0138]	[0.0054, 0.0145]
Term-search	1	0.0100	0.0099	0.9867	[0.0011, 0.0194]	[0.0000, 0.0194]
	8	0.0100	0.0101	0.9700	[0.0027, 0.0177]	[0.0003, 0.0198]
	15	0.0100	0.0099	0.9467	[0.0028, 0.0177]	[0.0023, 0.0180]