

Bradley J. Clement
Jet Propulsion Laboratory
California Institute of Technology
February, 2013

AI PLANNING FOR SPACE

NASA Jet Propulsion Laboratory



Jet Propulsion Laboratory
California Institute of
Technology



JPL Mission Control Room



JPL Mars Yard



Why automate planning for space missions?


- Spacecraft have limited resources
 - cost limits mass
 - mass limits power
 - power limits communication bandwidth
- Many flight rules and constraints
 - Don't point the camera at the sun.
- Inefficiency is expensive.
- A mistake can end the mission.
- Missions need to work out details in advance.

How has artificial intelligence (AI) planning been used by space missions?


- Help science and operations planning
 - which targets
 - when to take images
 - when to downlink data
 - how to sequence commands
- Autonomous spacecraft commanding
- Generate schedules allocating ground antennas to spacecraft.
- Create plans for solar array manipulation on the International Space Station.
- Project management for the construction of rockets.

What's challenging?

- Scale
 - a week-long plan could have tens of thousands of actions
 - often tens or hundreds of state and resource variables
- Slow processors and limited memory
- Complex states and resources
 - power, battery, and solar arrays
 - temperature
 - file system
- Complex and unspecified goals
 - The plan is safe, but is it what the user wanted?
- Validation
 - Are all possible plans safe?
- Usability





Deployments of AI planners for Space Missions



DEVISER – early 1980s

- NASA JPL temporal planner based on Nonlin, written in Lisp.
- Activity planning for Voyager mission in its encounter with Uranus
- Partial order planning, subgoaling, backward chaining
- Time windows
 - Metric time
 - Concurrency
 - Simple temporal constraints




```

(ROLL ACTION
  (CONTEXT
    (NEQ refstar.1 refstar.2)
    (AZI MUTH refstar.1 star1.azi muth)
    (AZI MUTH refstar.2 star2.azi muth))
  ((SC. AZI MUTH star1.azi muth)
    (LOCKED. ONTO refstar.1 )) →
    ((SC. AZI MUTH star2.azi muth)
    (LOCKED. ONTO refstar.2))
  (DURATION (84 + 5 * (SCOPE. 0. TO. 180
    (star2.azi muth - star1.azi muth))))))
    
```

```


(GOALS ((A))
  ((WINDOW BETWEEN 15 300) (DURATION 1000) (B) (C))
  ((DURATION INFINITY) (D)))
    
```




Plan-IT – 1987 to 2001

"Plan-IT" refers to both Plan-IT and Plan-IT-2.

- JPL's Plan-IT is an iterative repair local search planner written in Lisp and improving on DEVISER.
- 1987 – Rescheduled Deep Space Network (DSN) ground antennas.
- 1994 – As MIRAGE, created activity plans for Galileo at Jupiter.
- 1995 – present, created long range plans for Spitzer along with Spike.
- 1996 to 1997 – Used for science and ops planning for the Mars Sojourner rover.
- 1997 – As DCAPS, Plan-IT generated commands for SCL executive onboard the DATA-CHASER shuttle payload.
 - 80% reduction in operations effort
 - 40% increase in science return
- 1998 to 2001 - Generated all command sequences for Deep Space 1.
- Domain modeling with depletable and non-depletable resources
- Heuristic iterative repair:
 1. select a conflict
 2. choose how to resolve: move, add, or delete
 3. select an activity
 4. pick start time and duration



DCAPS GUI




MIRAGE = Mission Integration, Real-time Analysis, and Graphical Timeline Editor
SCL = Spacecraft Command Language
DCAPS = DATA-CHASER Automated Planner/Scheduler
DATA-CHASER = Distribution and Automation Technology Advancement, Colorado
Hitchhiker and Student Experiment of solar Radiation

Shepperd, R.; Willis, J.; Hansen, E.; Faber, J.; Siewert, S.; Rabideau, G.; "DATA-CHASER: a demonstration of advanced mission operations technologies," *Aerospace Conference, 1998 IEEE*, vol.2, no., pp.419-427 vol.2, 21-28 Mar 1998

T-SCHED – 1989

- British National Space Center
- T-SAT Technology Proving Spacecraft Project
- T-SCHED generated a 24-hour plan that was uploaded and executed live onboard UoSAT-II.



T-SAT concept

Spike – 1990 to present

- Space Telescope Science Institute (STScI)
- Used to schedule long term observation schedules for the Great Observatories
 - 1990 - Hubble Space Telescope (HST)
 - 1998 - Spitzer Space Telescope (formerly SIRTf)
 - 1999 - Chandra X-Ray Observatory (CXC)
- Used by many others!
FUSE, VLT, Subaru Telescope, German Space Operations Center, EUVE, ASCA, XTE
- Stochastic constraint-based schedule optimization in Lisp
 - trial assignment
 - repair
 - deconflict – remove activities or relax constraints
- Constraints & preferences
 - Observations of the same target must be at least 2 months apart.
 - Target must be at least 50° away from the Sun.
 - Minimize change in attitude (rotation).




$$B_{i\alpha}(t; t_{j \neq i}) = \exp[W_{i\alpha}(t; t_{j \neq i})] \quad W_{i\alpha}(t; t_{j \neq i}) > -w_0$$

$$= 0$$

$$W_{i\alpha}(t; t_{j \neq i}) \leq -w_0$$

$$S_{i\alpha}(t) = \max\{B_{i\alpha}(t; t_{j \neq i}) | t_{j \neq i}\}$$

$$S_f(t) = R_f(t) \prod_{\alpha} S_{i\alpha}(t)$$



Optimum-AIV – 1993


- European Space Agency (ESA)
- Optimum-AIV automated planning for the project management of the assembly, integration, and verification (AIV) of the vehicle equipment bays of the Ariane 4 rockets.
- Inherits from the PlanERS-1 planner (built for the ERS-1 mission), Nonlin, and O-Plan.
- Integrated with the commercial ARTEMIS project management system.
- Rich plan representation
- Scheduling is solved as a constraint satisfaction problem involving resource and temporal constraints.





RAX, Remote Agent Experiment - 1999

- NASA Ames Research Center (ARC) and JPL
- Deep Space 1 (DS-1) technology demonstration
- Three main Lisp components autonomously operated DS-1 for two days:
 - Planner/Scheduler (PS) is a constraint-based temporal planner and resource scheduler
 - EXEC executive
 - Livingstone mode identification and reconfiguration (MIR)
- Also demonstrated response to unexpected events in simulation while onboard.
- Examples of constraints
 - Total power usage < 2600 watts.
 - Ion engine thrust uses 2300W.
 - During a thrust the Attitude Control System must not be turning the spacecraft.



Autonomous Sciencecraft Experiment on EO-1

- Aqua downlinks images.
- Sensor web ground software detects changes since last image.
- Requests high resolution image from EO-1.
- ASE replans operations onboard EO-1 for the new high priority target.
- Autonomous planning enables quick response to forest fire.





ASPEN/CASPER – 2000 to present

Automated Scheduling and Planning Environment
Continuous Activity Scheduling Planning Execution and Replanning

- JPL stochastic iterative repair planner written in C++
- Similar to Plan-IT, adding hierarchical task network (HTN)
- Intuitive language designed for (and by) non-AI experts
- 2000 - Modified Antarctic Mapping Mission (MAMM)
 - reduced planning effort by 80%; saved > \$1M
- 2004 - present - onboard EO-1 satellite as part of the Autonomous Sciencecraft Experiment
 - Integrated with SCL executive
 - 55% reduction in operations costs
- 2007 - ground planning for DARPA Orbital Express
 - saved more than \$10 million
 - natural language processing to generate model
- 2009 - present – DSN Service Scheduling Software (S³)
 - generates schedules and aids negotiation among 20+ missions

```
Activity fire_engine {  
  constraint =  
    starts_after end_of catbed_htr_on  
    by [1800, infinity];  
  reservation engine_sv change_to "firing";  
}*  
}
```




* B. Smith, G. Rabideau, R. Sherwood, A. Govindjee, St Chien, D. Yan, and A. Fukunaga.
Representing Spacecraft Mission Planning Knowledge in ASPEN. In Proc. of Artificial
Intelligence Planning Systems Workshop on Knowledge Acquisition. 1998.

PROBA – 2001

- ESA Project for On Board Autonomy series of spacecraft
- PROBA-1 launched in 2001
 - Demonstrated onboard scheduling and resource management.

EUROPA – 2004 to present


- NASA Ames Research Center planner inheriting from RAX PS, written in C++
- 2004 - MAPGEN (Mixed Initiative Activity Planning Generator)
 - Increased scientific return, estimated between 20% and 30%
- 2011 - SACE – Solar Array Constraints Engine
 - Used to plan the orientation and movements of the International Space Station's eight large solar arrays.
- Constraint programming approach to planning and scheduling.
- States and actions are both represented as temporal variables, called "tokens."
- SPIFe and an Eclipse-based IDE are often used as user interfaces.



Mike McCurdy, Arash Aghevoli, Alfredo Bencomo, *Scheduling and Planning Interface for Exploration (SPIfE), Demonstrations ICAPS 2011.*

MEXAR and RAXEM – 2005 to present

- ESA planners for Mars Express (MEX) downlink and uplink
- 2005 - present – MEXAR (Mars EXpress ARchitecture)
 - Data downlink planning for MEX
 - Constraint-based planner employing max-flow algorithm
 - Saved 50% of time for producing plans
 - Minimized data loss (due to the ability to generate plans for multiple days quickly)
- 2007 - present – RAXEM
 - Uplink planning for MEX to help with the limited buffer size for commands
 - Shortened planning from hours to minutes



AI Planning for Space – the Future

Autonomous rovers

What about the Mars Science Laboratory (MSL) mission's Curiosity rover?

- The MER and MSL rovers use D* path planning.

- 2009 – present – AEGIS


(Autonomous Exploration for Gathering Increased Science)

- Opportunity autonomously investigates rocks while on long traverses.
- Machine learning employed for onboard image processing, but no planning, yet.



AI Planning for Space – the Future

- Autonomous and teleoperated robots for the space station and crew exploration missions
- Automated scheduling for crewmembers
- Space mission and spacecraft design
- Planetary and in-space construction
- Testing, verification, and validation
- Planetary exploration with aerobots or hydrobots.



Mike McCurdy,
Demonstration

SPiFe),

References

- Mike McCurdy, Arash Agheveli, Alfredo Bencomo, Scheduling and Planning Interface for Exploration (SPIFe), *ICAPS Demonstrations*, ICAPS, Freiberg, Germany, 2011.
- Mark D. Johnston and Glenn E. Miller. SPIKE: Intelligent Scheduling of Hubble Space Telescope Observations. *Intelligent Scheduling*. 1994.
- Ben Smith, Gregg Rabideau, Rob Sherwood, Anita Govindjee, Steve Chien, David Yan, and Alex Fukunaga. Representing Spacecraft Mission Planning Knowledge in ASPEN. In Proc. of *Artificial Intelligence Planning Systems Workshop on Knowledge Acquisition*. 1998.
- M.M. Arentoft, Y. Parrod, J. Stader, I. Stokes, H. Vadon, OPTIMUM-AIV: A planning and scheduling system for spacecraft AIV, *Telematics and Informatics*, Volume 8, Issue 4, 1991, Pages 239-252.
- Steven A. Vere. Planning in Time: Windows and Durations for Activities and Goals, *IEEE Transactions On Pattern Analysis And Machine Intelligence*, vol. PAMI-5, no. 3, May 1983.
- Shepperd, R.; Willis, J.; Hansen, E.; Faber, J.; Siewert, S.; Rabideau, G. DATA-CHASER: a demonstration of advanced mission operations technologies. *Aerospace Conference, 1998 IEEE*, vol.2, no., pp.419-427 vol.2, 21-28 Mar 1998.
- Drabble, B.; , Mission scheduling for spacecraft: the diaries of T-SCHED. *Expert Planning Systems, 1991., First International Conference on Expert Planning Systems*, pp.76-81, IEE, Savoy Place, London, UK, 27-29 Jun 1990.
- Nicola Muscettola, P. Pandurang Nayak, Barney Pell, and Brian C. Williams. 1998. Remote Agent: to boldly go where no AI system has gone before. *Artif. Intell.* 103, 1-2 (August 1998), 5-47.



Jet Propulsion Laboratory
California Institute of
Technology