

Database Management System (DBMS)

Chapter 5-7

Applications

Web
Forms

Embedded
SQL

Interactive
SQL

DBMS

SQL Commands

Query
Evaluation Engine

Concurrency
Control

Files and Access Methods

Buffer Manager

Disk Space Manager

Recovery
Manager

Database

Data

Indexes

Catalog

Relational Database Management Systems

□ Data Abstraction

- Overview
- SQL Queries
- Views
- Integrity Constraints
- Complex Integrity Constraints

Complex Integrity Constraints

- A constraint is expressed as a **Predicate**
 - A condition similar to the one in the WHERE-clause of an SQL query

- Three DDL constructs
 - Checks
 - Assertions
 - Triggers



Queries and Transactions

- ❑ Queries: requests to the DBMS to retrieve data from the database
- ❑ Updates: requests to the DMBS to insert, delete or modify existing data
- ❑ Transactions: logical grouping of query and update requests to perform a task
 - Logical unit of work (like a function/subroutine)

ACID Properties

Atomicity

Consistency

I solation

Durability

ACID Properties

☐ Atomicity

Either all the operations associated with a transaction happen or none of them happens

☐ Consistency

It satisfies the **integrity constraints** on the database at the transaction's boundaries

☐ Isolation

The result of the execution of concurrent transactions is the same as if transactions were executed serially

☐ Durability

The effects of completed transactions become permanent surviving any subsequent failures

SQL Transactions

□ Basic transaction statements:

- SET TRANSACTION READ WRITE NAME <name>;
(DECLARE TRANSACTION READ WRITE;)
- SET TRANSACTION READ ONLY NAME <name>;
(DECLARE TRANSACTION READ ONLY;)
- COMMIT ;
- ROLLBACK;

Transaction Consistency

T_1 : UPDATE **Accounts** SET **balance= balance - 100** WHERE **client=7**

- ❑ **Consistency:** It satisfies the integrity constraints on the database at the transaction's boundaries
 - ❑ E.g., balance is not allowed to be negative
- ❑ Mechanism: **Integrity Constraints (ICs)**
 - ❑ *Checks, Assertions, Triggers, etc.*



Transaction Atomicity



- ❑ What do we expect with Atomicity?

- “All or nothing”

- ❑ Consider a transaction:

```
set transaction read write name 'test';  
  insert into Student values (23, 'John', 'CS');  
  insert into Dept values ('CS', 'ITEE');  
Commit;
```

- ❑ What happens if the first insert fails, e.g., due to a referential constraint violation?
 - Is the new tuple inserted into Department? No?

Modes of Constraints Enforcement

☐ **NON DEFERRABLE** or **IMMEDIATE**

- Evaluation is performed at input time
- By default constraints are created as NON DEFERRABLE
- It *cannot* be changed during execution

☐ **DEFERRED**

- Constraints are not evaluated until commit time

☐ **DEFERRABLE**

- It can be changed within a transaction to be DEFERRED using SET CONSTRAINT

☐ Modes can be specified when a table is created

- **INITIALLY IMMEDIATE**: constraint validation happen immediately
- **INITIALLY DEFERRED**: constraint validation defer until commit

Specifying Initial Evaluation Mode in Tables

□ **CREATE TABLE** SECTION

(SectNo sectno_dom,
Name section_dom,
HeadSSN ssn_dom,
Budget budget_dom,

);

Specifying Initial Evaluation Mode in Tables

❑ **CREATE TABLE** SECTION

(SectNo sectno_dom,

 Name section_dom,

 HeadSSN ssn_dom,

 Budget budget_dom,

CONSTRAINT section_PK

PRIMARY KEY (SectNo) DEFERRABLE,

CONSTRAINT section_FK

FOREIGN KEY (HeadSSN) REFERENCES LIBRARIAN(SSN)

 INITIALLY DEFERRED DEFERRABLE,

CONSTRAINT section_name_UN **UNIQUE** (Name)

 DEFERRABLE INITIALLY IMMEDIATE

);

Changing Constraint Evaluation Mode

- It is permitted only for deferrable constraints
- Setting the constraint validation mode **within** a transaction
 - Set mode of all deferrable constraints

```
SET CONSTRAINT ALL IMMEDIATE;
```

```
SET CONSTRAINT ALL DEFERRED;
```
 - Set mode of specific deferrable constraints (list)

```
SET CONSTRAINT section_budget_IC IMMEDIATE;
```

```
SET CONSTRAINT section_budget_IC DEFERRED;
```

Specifying Transaction Atomicity 1

- ❑ Errors at commit time: only when **deferred constraints** are violated
 - Constraints can be deferred if specified as **deferrable** in the table schema, and
 - Deferred in the scope of the transaction
- ❑ E.g. 1, *assume the constraints are deferrable*

```
set transaction read write name 'test';  
set constraints all deferred;  
insert into Student values (23, 'John', 'CS');  
insert into Dept values ('CS', 'ITEE');  
Commit;
```
- ❑ No constraint violation of the first insert is detected at *commit time* → the whole transaction is committed

Specifying Transaction Atomicity 2

- ❑ Errors at commit time: only when **deferred constraints** are violated

- ❑ E.g. 2, *assume the constraints are deferrable*
and assume SID 23 exists in that Database

```
set transaction read write name 'test' ;  
set constraints all deferred;  
insert into Student values (23, 'John', 'CS');  
insert into Dept values ('CS', 'ITEE');  
Commit;
```

- ❑ The constraint violation of the first insert is detected at *commit time* → the whole transaction is rollback

Specifying Transaction Atomicity 3

- ❑ Errors at commit time: only when **deferred constraints** are violated
 - ❑ E.g. 3, *assume the primary key constraints are non-deferrable but the foreign key constraints are deferrable and assume SID 23 exists in that Database*

```
set transaction read write name 'test' ;  
set constraints all deferred;  
insert into Student values (23, 'John', 'CS');  
insert into Dept values ('CS', 'ITEE');  
Commit;
```

- ❑ What would happen?

Complex Integrity Constraints

- Three DDL constructs
 - Checks
 - Assertions
 - Triggers



Example Schema

<i>SID</i>	<i>Name</i>	<i>Age</i>	<i>GPA</i>	<i>Major</i>
546007	Peter	18	3.8	IT
546100	Bob	19	6.65	Cinema
546500	Peter	20	4.7	History

Example Schema

```
CREATE TABLE Student (  
    Sid INTEGER,  
    Name CHAR (20) ,  
    Age INTEGER,  
    GPA REAL,  
    Major CHAR (10) ,  
  
    PRIMARY KEY (Sid));
```


CHECK Constraint 1

```
CREATE TABLE Student (  
    Sid INTEGER,  
    Name CHAR(20) ,  
    Age INTEGER,  
    GPA REAL,  
    CHECK (GPA >= 0.0 AND GPA <= 7.0) ;  
    Major CHAR(10) ,  
  
    PRIMARY KEY (Sid));
```

CHECK Constraint 2

```
CREATE TABLE Student (  
    Sid INTEGER,  
    Name CHAR (20) ,  
    Age INTEGER,  
    GPA REAL,  
    Major CHAR (10) ,  
        CHECK (Major IN ( 'IT' , 'Cinema' , 'History' ));  
  
    PRIMARY KEY (Sid));
```

Be Careful with Your Database Inputs ☺



CHECK Constraint and DOMAIN

```
CREATE DOMAIN M_Code AS CHAR(10)  
CHECK (M_Code IN ('IT', 'Cinema', 'History'));
```

```
CREATE TABLE Student (  
    Sid INTEGER,  
    Name CHAR(20) ,  
    Age INTEGER,  
    GPA REAL,  
    Major M_Code ,  
    PRIMARY KEY (Sid));
```

CHECK: Attribute- vs. Tuple-based

- ❑ CHECK prohibits an operation on a table that would violate a constraint
- ❑ CHECK clause restricts acceptable attribute values according to some definition
 - **Attribute-based**
- ❑ CHECK is also used as a **tuple-based** constraint:
 - Apply to each tuple individually
 - Checked whenever a tuple is inserted or modified
 - See next example...


Example

```
CREATE DOMAIN M_Code AS CHAR(10)
CHECK (M_Code IN ('IT' , 'Cinema' , 'History' ));
CREATE TABLE Student (
    Sid INTEGER,
    Name CHAR(20) ,
    Age INTEGER,
    GPA REAL,
    Major M_Code,
    Minor ..., what constraints are needed for Minor?
    PRIMARY KEY (Sid));
```

IC1: Minor IN ...
IC2: Minor \neq Major

Example: Attribute-based


```
CREATE DOMAIN M_Code AS CHAR(10)
CHECK (M_Code IN ('IT', 'Cinema', 'History'));
CREATE TABLE Student (
    Sid INTEGER,
    Name CHAR(20),
    Age INTEGER,
    GPA REAL,
    Major M_Code,
    Minor M_Code,
    PRIMARY KEY (Sid));
```



IC1:
attribute-
based

Example: Attribute- and Tuple-based

```
CREATE DOMAIN M_Code AS CHAR(10)
CHECK (M_Code IN ('IT', 'Cinema', 'History'));
CREATE TABLE Student (
    Sid INTEGER,
    Name CHAR(20),
    Age INTEGER,
    GPA REAL,
    Major M_Code,
    Minor M_Code, CHECK (Major != Minor);
    PRIMARY KEY (Sid));
```



IC1: attribute-based

IC2: tuple-based

Naming Constraints

- A constraint may be given a name using the keyword **CONSTRAINT**
 - E.g., **CONSTRAINT** Major_Minor

- Advantages of naming a constraint:
 - Facilitates editing
 - Identifies a particular constraint
 1. For reporting
 2. For constraint management

Naming Constraints

```
CREATE DOMAIN M_Code AS CHAR(10)
CHECK (M_Code IN ('IT', 'Cinema', 'History'));
CREATE TABLE Student (
    Sid INTEGER,
    Name CHAR(20),
    Age INTEGER,
    GPA REAL,
    Major M_Code,
    Minor M_Code,
    CONSTRAINT Major_Minor
        CHECK (Major != Minor));
```

Constraint Management

```
ALTER TABLE Student DROP CONSTRAINT Major_Minor;
```

```
ALTER TABLE Student ADD CONSTRAINT Major_Minor  
CHECK (Major != Minor);
```

- ❑ To modify a constraint:
 - Drop it first and then add a new one

Assertions

- ❑ Similar to `CHECK` but they are **global** constraints

```
CREATE ASSERTION <assertion_name>  
CHECK <condition>;
```

- Global: schema-based
 - <condition> must be TRUE for each database state
- ❑ Examples:
 - # of IT students cannot exceed 1800
 - # of students in a prac cannot exceed lab capacity
 - ...

Assertions

```
CREATE ASSERTION <assertion_name>  
CHECK NOT EXISTS (vquery);
```

1. Specify a query <*vquery*> such that:
vquery selects any tuple that **violates** <*condition*>
2. Include vquery inside a **NOT EXISTS** clause

Assertions

```
CREATE ASSERTION <assertion_name>  
CHECK NOT EXISTS (vquery);
```

Result of <i>vquery</i>	NOT EXISTS (<i>vquery</i>)	CHECK
Empty (no tuples violate the condition)	TRUE	Satisfied
Not Empty (some tuples violate the condition)	FALSE	Violated

Example Schema

<i>SID</i>	<i>Name</i>	<i>Age</i>	<i>GPA</i>	<i>Major_Code</i>
546007	Peter	18	3.8	0
546100	Bob	19	3.65	50
546500	Peter	20	3.7	1

<i>Major_Code</i>	<i>Major_name</i>
0	IT
1	History
...	
50	Cinema

Example

- Number of students in any major cannot exceed 1800

```
CREATE ASSERTION Major_Limit
CHECK NOT EXISTS (
    SELECT Major_Code, COUNT (*)
    FROM Student
    GROUP BY Major_Code
    HAVING COUNT (*) > 1800 );
```

Example

- The Number of students cannot exceed 1800 in each of the IT or Cinema majors

```
CREATE ASSERTION Major_Limit
CHECK NOT EXISTS (
    SELECT Major_Code, COUNT (*)
    FROM Student AS S , Major AS M
    WHERE S.major_code = M.major_code
    AND (M.major_name="IT" OR M.major_name="Cinema")
    GROUP BY Major_Code
    HAVING COUNT (*) > 1800 );
```

Triggers

□ A trigger consists of 3 parts:

1. Event(s),
2. Condition, and
3. Action

■ E.g., notify the Dean whenever the number of students in any major exceeds 1800

Triggers vs. Assertions

□ Assertion

- Condition must be true for each database state
- DBMS rejects operations that violate such condition

□ Trigger

- DBMS takes a certain **action** when condition is true
- Action could be: stored procedure, SQL statements, Rollback, etc.

Example

- Notify the Dean when the # of students in any major exceeds 1800

CREATE TRIGGER Major_Limit

Event(s)

Condition

Action

Example

- Notify the Dean when the # of students in any major exceeds 1800

CREATE TRIGGER Major_Limit

Event(s)

```
WHEN ( EXISTS (
    SELECT Major_Code, COUNT (*)
    FROM Student
    GROUP BY Major_Code
    HAVING COUNT (*) > 1800 ) )
```

Action

Example

- Notify the Dean when the # of students in any major exceeds 1800

CREATE TRIGGER Major_Limit

Event(s)

```
WHEN ( EXISTS (  
        SELECT Major_Code, COUNT (*)  
        FROM Student  
        GROUP BY Major_Code  
        HAVING COUNT (*) > 1800 ) )
```

```
CALL email_dean(Major_code);
```

Example

- Notify the Dean when the # of students in any major exceeds 1800

CREATE TRIGGER Major_Limit

**AFTER INSERT OR UPDATE OF Major_Code
ON Student**

WHEN(EXISTS (
 SELECT Major_Code, COUNT (*)
 FROM Student
 GROUP BY Major_Code
 HAVING COUNT (*) > 1800))

CALL email_dean(Major_code);

Triggers (SQL99)

- ❑ `CREATE or REPLACE TRIGGER <trigger-name>`
 `<time events> ON <list-of-tables>`
 `REFERENCING { NEW | OLD } AS <user-name>`
 `[FOR EACH { ROW | STATEMENT }]`
 `[WHEN (<Predicate>)]`
 `<action>`
- ❑ time: **before** or **after**
- ❑ events: **Insert, Delete, Update** [of **<list of attributes>**]
- ❑ **NEW & OLD** refer to new & old (existing) tuples/table respectively
- ❑ The REFERENCING clause assigns aliases to NEW and OLD
- ❑ action: Stored procedure or
 `BEGIN ATOMIC {<SQL procedural statements>} END`

Oracle Example: Statement Trigger

- ❑ Statement-level trigger fires **once** by the triggering statement
- ❑ No **WHEN-clause** in the definition of statement trigger
- ❑ **CREATE OR REPLACE TRIGGER** Audit_Updater
 AFTER
 INSERT OR DELETE OR UPDATE
 ON STUDENTS
 BEGIN
 INSERT INTO AUDIT_Table VALUES ('STUDENT', sysdate);
 END;
 /
❑ The end slash ("**/**") installs and activates the trigger

Oracle Example: Row-Level Trigger

- ❑ Row- or tuple-level trigger fires once **for each row** affected by the triggering statement
- ❑ **CREATE OR REPLACE TRIGGER** trigger_deans_list
AFTER INSERT ON STUDENTS
REFERENCING NEW AS newRow
FOR EACH ROW
WHEN (newRow.GPA > 6.0)
BEGIN
INSERT INTO DL VALUES (:newRow.SID, :newRow.GPA);
END;
/

❑ Scope Rules: In the trigger body, NEW and OLD must be preceded by a colon (":"), but in the WHEN clause (triggering condition), they do not have a preceding colon!