

Database Management System (DBMS)

Chapter 5-7

Applications

Web
Forms

Embedded
SQL

Interactive
SQL

DBMS

SQL Commands

Query
Evaluation Engine

Concurrency
Control

Files and Access Methods

Buffer Manager

Disk Space Manager

Recovery
Manager

Database

Data

Indexes

Catalog

Relational Database Management Systems

□ Data & Execution Abstraction

- Overview
- SQL Queries
- Views
- Integrity Constraints
- Complex Integrity Constraints

Database Languages

☐ **Data Definition Language (*DDL*):**

- Define schemas
- Define **Integrity Constraints**
 - ☐ Example: unique *SIDs*
- More...

☐ **Data Manipulation Language (*DML*):**

- To ask questions = ***Query***
 - ☐ Example: Which students have GPA > 3.75?
- To insert, delete and update data

☐ ***SQL***: Most widely used database language

DDL -- Creating Relations in SQL

CREATE TABLE Students (

sid: CHAR (20) ,

name: CHAR (20) ,

login: CHAR (20) ,

age: INTEGER,

gpa: REAL)



- ❑ Corresponding database is at an **empty** state!
- ❑ **Initial state** when the database is **populated** (loaded)
- ❑ Domain (type) of each field is **specified** and **enforced** by the DBMS whenever tuples are added or modified

Example: Domain Constraints

<i>SID</i>	<i>Name</i>	<i>Login</i>	<i>Age</i>	<i>GPA</i>
546007	Jones	jones@cs	18	3.4
546100	Smith	smith@ee	18	3.2
546500	Smith	smith@math	19	3.8

❑ Example of **IC Violation**:


UPDATE *Students S*

SET *S.age* = 'Eighteen' ❌ ❌ ❌

WHERE *S.name* = 'Jones'

Integrity Constraints (ICs)

- ❑ **IC**: condition that must be true for *any* instance of the database (e.g., domain constraints)
- A **legal** instance of a relation is one that satisfies all specified ICs
- ICs are specified when schema is **defined**
 - ❑ DBMS Data Abstraction (DDL)
- ICs are enforced when tables are **modified**
 - ❑ DBMS Reliability




Integrity Constraints (IC)

- ☐ Primary Key IC
- ☐ Unique Value IC
- ☐ Foreign Key IC

- ☐ Complex Integrity Constraints
 - Utilize the full power of SQL queries



Primary Key Constraint



- A set of fields is a **key** for a relation if :
 - No two distinct tuples can have same values in all key fields

- If there is more than one key for a relation:
 - Each is called a **candidate key**
 - One candidate key is designated as the **primary key**
 - Other candidate key(s) are designated as **unique key(s)**

Example of Keys

<i>SID</i>	<i>Name</i>	<i>Login</i>	<i>Age</i>	<i>GPA</i>
546007	Jones	jones@cs	18	3.4
546100	Smith	smith@ee	18	3.2
546500	Smith	smith@math	19	3.8

- ❑ **Candidate Keys:** *SID*, and *Login*
- ❑ **Primary Key:** *SID*
- ❑ **Unique Key:** *Login*

Specifying Key Constraints in SQL

<i>SID</i>	<i>Name</i>	<i>Login</i>	<i>Age</i>	<i>GPA</i>
546007	Jones	jones@cs	18	3.4
546100	Smith	smith@ee	18	3.2
546500	Smith	smith@math	19	3.8

CREATE TABLE Students (

sid: CHAR (20) ,

name: CHAR (20) ,

login: CHAR (10) ,

age: INTEGER,

gpa: REAL,

UNIQUE (*login*),

PRIMARY KEY (*sid*))

Enforcing Primary Key Constraints

<i>SID</i>	<i>Name</i>	<i>Login</i>	<i>Age</i>	<i>GPA</i>
546007	Jones	jones@cs	18	3.4
546100	Smith	smith@ee	18	3.2
546500	Smith	smith@math	19	3.8

INSERT INTO Students

VALUES (546100, 'Mike', 'mike@ee', 21, 3.9)

INSERT INTO Students

VALUES (*null*, 'Mike', 'mike@ee', 21, 3.9)

Enforcing Primary Key Constraints

<i>SID</i>	<i>Name</i>	<i>Login</i>	<i>Age</i>	<i>GPA</i>
546007	Jones	jones@cs	18	3.4
546100	Smith	smith@ee	18	3.2
546500	Smith	smith@math	19	3.8

❑ Examples of IC Violations:

INSERT INTO Students

VALUES (~~546100~~, 'Mike', 'mike@ee', 21, 3.9)

INSERT INTO Students

VALUES (~~null~~, 'Mike', 'mike@ee', 21, 3.9)



NULL and DEFAULT

<i>SID</i>	<i>Name</i>	<i>Login</i>	<i>Age</i>	<i>GPA</i>
546007	Jones	jones@cs	18	3.4
546100	Smith	smith@ee	18	3.2
546500	Smith	smith@math	19	3.8

CREATE TABLE Students (

sid: CHAR (20) ,

name: CHAR (20) **NOT NULL**,

login: CHAR (10) ,


age: INTEGER,

gpa: REAL **DEFAULT** 7.0 ,

UNIQUE (*login*),

PRIMARY KEY (*sid*))

Foreign Key




- ❑ **Foreign key** : Set of fields in one relation that is used to “refer” to a tuple in another relation
- Must correspond to primary key of the referred relation
 - E.g. *SID* is a foreign key referring to *Students*

Foreign Key Constraints

- ❑ If foreign key constraints are enforced, **referential integrity** is achieved
 - E.g.: Only students can enroll in a class
 - ❑ Only students listed in the “Students” relation should be allowed to enroll for courses
- ❑ Like a “logical pointer”
 - There shouldn't be dangling references




Specifying Foreign Key in SQL



```
CREATE TABLE Enrolled(  
    sid CHAR(20), cid CHAR(20), grade CHAR(2),  
    PRIMARY KEY (sid,cid),  
    FOREIGN KEY (sid) REFERENCES Students  
    FOREIGN KEY (cid) REFERENCES Courses)
```


Referential Integrity Constraints




DELETE

FROM *Enrolled E*

WHERE *E.sid* = 546500

No Violations! ✓

Referential Integrity Constraints



❑ Example of **IC Violation**:

INSERT INTO Enrolled

VALUES (546105, CSC 207, B+)

❑ **Insert** might cause a violation, but **Delete** is ok

❑ The opposite for the “Students” relation !

Referential Integrity Enforcement

- What are the alternatives when a “Students” tuple is **deleted**?
 1. **Delete all** Enrolled tuples that refer to it
 2. **Disallow** deletion of a Students tuple that is referred to
 3. **Set** sid in Enrolled tuples that refer to it to some “**default**” *sid* (e.g., 000000)
 4. **Set** sid in Enrolled tuples that refer to it to a special value “**null**”, denoting “*unknown*” or “*inapplicable*”

Referential Integrity in SQL

- ☐ SQL/92 and SQL:1999 support all 4 options on delete and update:
 - **NO ACTION** (default)
 - ☐ Delete/update is rejected
 - **CASCADE**
 - ☐ Also delete all tuples that refer to deleted tuple
 - **SET NULL / SET DEFAULT**
 - ☐ Set foreign key value of referencing tuple

Referential Integrity Constraints

<u>SID</u>	Name	Age
546007	Peter	18
546100	Bob	19
546500	Bill	20

Students

<u>SID</u>	<u>CID</u>	Grade
546007	CSC 343	A
546007	CSC 369	B+
546500	CSC 343	B

Enrolled

<u>CID</u>	CName
CSC 343	DB
CSC 207	SW
CSC 369	OS

Courses

❑ CREATE TABLE Enrolled(

sid CHAR(20), *cid* CHAR(20), *grade* CHAR(2),

PRIMARY KEY (*sid*,*cid*),

FOREIGN KEY (*sid*) REFERENCES *Students*

ON UPDATE CASCADE

ON DELETE NO ACTION)