Functions that return system date and time

FUNCTIONS FOR MANIPULATING DATA IN SQL SERVER

SQL

Ana VoicuData Engineer



Common mistakes when working with dates and time

- Inconsistent date time formats or patterns
- Arithmetic operations
- Issues with time zones



Time zones in SQL Server

- Local time zone
- UTC time zone (Universal Time Coordinate)

Functions that return the date and time of the operating system

Higher-precision

- SYSDATETIME()
- SYSUTCDATETIME()
- SYSDATETIMEOFFSET()

Lower-precision

- GETDATE()
- GETUTCDATE()
- CURRENT_TIMESTAMP



Higher-precision functions example

```
SELECT

SYSDATETIME() AS [SYSDATETIME],

SYSDATETIMEOFFSET() AS [SYSDATETIMEOFFSET],

SYSUTCDATETIME() AS [SYSUTCDATETIME];
```



Lower-precision functions example

```
SELECT

CURRENT_TIMESTAMP AS [CURRENT_TIMESTAMP],

GETDATE() AS [GETDATE] ,

GETUTCDATE() AS [GETUTCDATE];
```

Retrieving only the date

```
SELECT
   CONVERT(date, SYSDATETIME()) AS [SYSDATETIME],
   CONVERT(date, SYSDATETIMEOFFSET()) AS [SYSDATETIMEOFFSET],
   CONVERT(date, SYSUTCDATETIME()) AS [SYSUTCDATETIME],
   CONVERT(date, CURRENT_TIMESTAMP) AS [CURRENT_TIMESTAMP],
   CONVERT(date, GETDATE()) AS [GETDATE],
   CONVERT(date, GETUTCDATE()) AS [GETUTCDATE];
```



Retrieving only the time

```
SELECT

CONVERT(time, SYSDATETIME()) AS [SYSDATETIME],

CONVERT(time, SYSDATETIMEOFFSET()) AS [SYSDATETIMEOFFSET],

CONVERT(time, SYSUTCDATETIME()) AS [SYSUTCDATETIME],

CONVERT(time, CURRENT_TIMESTAMP) AS [CURRENT_TIMESTAMP],

CONVERT(time, GETDATE()) AS [GETDATE],

CONVERT(time, GETUTCDATE()) AS [GETUTCDATE]
```

Let's practice!

FUNCTIONS FOR MANIPULATING DATA IN SQL SERVER



Functions returning date and time parts

FUNCTIONS FOR MANIPULATING DATA IN SQL SERVER



Ana VoicuData Engineer



YEAR(date)

Returns the year from the specified date

```
SELECT
    first_name,
    first_vote_date,
    YEAR(first_vote_date) AS first_vote_year
FROM voters;
```

MONTH(date)

Returns the month from the specified date

```
SELECT
    first_name,
    first_vote_date,
    YEAR(first_vote_date) AS first_vote_year,
    MONTH(first_vote_date) AS first_vote_month
FROM voters;
```

DAY(date)

Returns the day from the specified date

```
SELECT
    first_name,
    first_vote_date,
    YEAR(first_vote_date) AS first_vote_year,
    MONTH(first_vote_date) AS first_vote_month,
    DAY(first_vote_date) AS first_vote_day
FROM voters;
```

| | first_name first_vote_date first_vote_year first_vote_month first_vote_day | | | | | |
|-------------------------------------|--|------------|------------|---|---------|--|
| Ana | Canol | 2015-03-00 | 2015 | | 0 | |
| Melissa 2015-04-09 2015 4 9 | | | | 1 | 17 | |
| | Melissa | 2015-04-09 | 2015 | 4 | 9 | |

DATENAME(datepart, date)

• Returns a character string representing the specified date part of the given date

| datepart | abbreviations |
|-----------|---------------|
| year | yy, yyyy |
| month | mm, m |
| dayofyear | dy, y |
| week | wk, ww |
| weekday | dw, w |

DATENAME() example

```
DECLARE @date datetime = '2019-03-24'

SELECT

YEAR(@date) AS year,

DATENAME(YEAR, @date) AS year_name,

MONTH(@date) AS month,

DATENAME(MONTH, @date) AS month_name,

DAY(@date) AS day,

DATENAME(DAY, @date) AS day_name,

DATENAME(WEEKDAY, @date) AS weekday
```

DATEPART(datepart, date)

- It is similar to DATENAME()
- Returns an integer representing the specified part of the given date

```
DECLARE @date datetime = '2019-03-24'
SELECT
    DATEPART(YEAR, @date) AS year_name,
    DATENAME(YEAR, @date) AS year_name,
    DATEPART(MONTH, @date) AS month_name,
    DATENAME(MONTH, @date) AS month_name
```

```
| year | year_name | month | month_name |
|-----|
| 2019 | 2019 | 3 | March |
```

DATEFROMPARTS(year, month, day)

- Receives 3 parameters: year, month, and day values
- Generates a date

```
SELECT
DATEFROMPARTS(2019, 3, 5) AS new_date;
```

```
| new_date |
|-----|
| 2019-03-05 |
```

DATEFROMPARTS(year, month, day)

```
SELECT
    YEAR('2019-03-05')    AS date_year,
    MONTH('2019-03-05')    AS date_month,
    DAY('2019-03-05')    AS date_day,
    DATEFROMPARTS(YEAR('2019-03-05'), MONTH('2019-03-05'), DAY('2019-03-05'))    AS reconstructed_date;
```

```
| date_year | date_month | date_day | reconstructed_date |
|-----|
| 2019 | 3 | 5 | 2019-03-05 |
```

Let's practice!

FUNCTIONS FOR MANIPULATING DATA IN SQL SERVER



Performing arithmetic operations on dates

FUNCTIONS FOR MANIPULATING DATA IN SQL SERVER

SQL

Ana VoicuData Engineer



Types of operations with dates

- Operations using arithmetic operators (+, -)
- Modify the value of a date DATEADD()
- Return the difference between two dates DATEDIFF()

Arithmetic operations

```
DECLARE @date1 datetime = '2019-01-01';
DECLARE @date2 datetime = '2020-01-01';
SELECT
          @date2 + 1 AS add_one,
          @date2 - 1 AS subtract_one,
          @date2 + @date1 AS add_dates,
          @date2 - @date1 AS subtract_date;
```

DATEADD(datepart, number, date)

Add or subtract a number of time units from a date

```
SELECT

first_name,
birthdate,

DATEADD(YEAR, 5, birthdate) AS fifth_birthday,

DATEADD(YEAR, -5, birthdate) AS subtract_5years,

DATEADD(DAY, 30, birthdate) AS add_30days,

DATEADD(DAY, -30, birthdate) AS subtract_30days

FROM voters;
```

DATEDIFF(datepart, startdate, enddate)

Returns the number of units between two dates

```
SELECT
    first_name,
    birthdate,
    first_vote_date,
    DATEDIFF(YEAR, birthdate, first_vote_date) AS age_years,
    DATEDIFF(QUARTER, birthdate, first_vote_date) AS age_quarters,
    DATEDIFF(DAY, birthdate, first_vote_date) AS age_days,
    DATEDIFF(HOUR, birthdate, first_vote_date) AS age_hours
    FROM voters;
```

```
| first_name | birthdate | first_vote_date | age_years | age_quarters | age_days | age_hours | | -------| -------| | Carol | 1989-01-15 | 2015-03-09 | 26 | 104 | 9549 | 229176 | | Dennis | 1972-03-11 | 2013-10-29 | 41 | 167 | 15207 | 364968 |
```

Let's practice!

FUNCTIONS FOR MANIPULATING DATA IN SQL SERVER



Validating if an expression is a date

FUNCTIONS FOR MANIPULATING DATA IN SQL SERVER



Ana VoicuData Engineer



ISDATE(expression)

Determines whether an expression is a valid date data type

| ISDATE() expression | Return type |
|----------------------|-------------|
| date, time, datetime | 1 |
| datetime2 | 0 |
| other type | 0 |

ISDATE(expression)

```
DECLARE @date1 NVARCHAR(20) = '2019-05-05'
DECLARE @date2 NVARCHAR(20) = '2019-01-XX'
DECLARE @date3 CHAR(20) = '2019-05-05 12:45:59.9999999'
DECLARE @date4 CHAR(20) = '2019-05-05 12:45:59'
SELECT
    ISDATE(@date1) AS valid_date,
    ISDATE(@date2) AS invalid_date,
    ISDATE(@date3) AS valid_datetime2,
    ISDATE(@date4) AS valid_datetime;
```

SET DATEFORMAT

```
SET DATEFORMAT {format}
```

- Sets the order of the date parts for interpreting strings as dates
- Valid formats:
 - o mdy, dmy, ymd, ydm, myd, dym

SET DATEFORMAT

```
DECLARE @date1 NVARCHAR(20) = '12-30-2019'
DECLARE @date2 NVARCHAR(20) = '30-12-2019'

SET DATEFORMAT dmy;
SELECT
    ISDATE(@date1) AS invalid_dmy,
    ISDATE(@date2) AS valid_dmy;
```

SET LANGUAGE

SET LANGUAGE {language}

- Sets the language for the session
- Implicitly sets the setting of SET DATEFORMAT
- Valid languages: English, Italian, Spanish, etc.

SET LANGUAGE

```
SET LANGUAGE English;

SELECT

ISDATE('12-30-2019') AS mdy,

ISDATE('30-12-2019') AS dmy;
```

```
| mdy | dmy |
|----|---|
| 1 | 0 |
```

SET LANGUAGE

```
SET LANGUAGE French;
SELECT
    ISDATE('12-30-2019') AS mdy,
    ISDATE('30-12-2019') AS dmy;
```

```
| mdy | dmy |
|----|
| 0 | 1 |
```

Let's practice!

FUNCTIONS FOR MANIPULATING DATA IN SQL SERVER

