

Kalibrierung				Gruppe 8	Fynn Kanja	Valentino D'Aq
Bx	By	Bz	Einheit: mikro T			Einstellungen
	-32.1	-22.5	-29.5			Channel 1: 12

Flache Kreisspule (3)

By	Position Spule in mm	Einheit: mikro T	I = 1,825	Position Sensi
773	270			
864	275			
954	280			
1059	285			
1175	290			
1296	295			
1459	300			
1614	305			
1811	310			
2028	315			
2274	320			
2532	325			
2787	330			
3091	335			
3422	340			
3746	345			

Hier war der Startpunkt, die anderen wurden danach gemessen

4326	350
4588	355
4815	360
4970	365
5070	370
5070	375
4990	480
4833	385
4580	390
4310	395
4008	400
3692	405
3354	410
3024	415
2763	420
2513	425
2264	430
2062	435

1793	440
1609	445
1438	450
1290	455
1141	460
1037	465
935	470
842	475
751	480

Spulenpaar Fläche Kreisspule mit Spulenpaar 3		Reihenschaltung	
By	Position Sensor halterung	Einheit: mikro T	I = 0.907
	335	980	
	366	975	
	398	970	
	441	965	
	481	960	
	534	955	
	592	950	
	658	945	
	731	940	
	807	935	
	901	930	
	1003	925	
	1118	920	
	1246	915	
	1383	910	
	1535	905	
	1712	900	
	1872	895	
	2065	890	
	2215	885	
	2343	880	
	2475	875	
	2591	870	
	2705	865	
	2808	860	
	2864	855	
	2876	850	
	2816	845	
	2733	840	
	2610	835	
	2475	830	
	2430	825	
	2269	820	
	2104	815	
	2021	810	

1958	805
1841	800
1790	795
1767	790
1763	785
1781	780
1822	775
1887	770
1968	765
2064	760
2173	755
2294	750
2412	745
2541	740
2644	735
2706	730
2788	725
2793	720
2783	715
2725	710
2612	705
1480	700
2346	695
2181	690
2041	685
1874	680
1704	675
1550	670
1398	665
1251	660
1131	655
984	650
884	645
789	640
697	635
645	630
577	625
521	620
459	615
428	610
378	605

348

600

Abstand der Spulen: $2r$

Position Spule 1: 350mm Position Spule 2: 214mm

Spulenpaar Fläche Kreisspule mit Spulenpaar 3		Reihenschaltung	
By	Position Sensor halterung	Einheit: mikro T	I = 0.904
833	930		
956	925		
1055	920		
1206	915		
1335	910		
1498	905		
1656	900		
1835	895		
2074	890		
2286	885		
2503	880		
2757	875		
2987	870		
3182	865		
3422	860		
3587	855		
3735	850		
3876	845		
3962	840		
3978	835		
4000	830		
4025	825		
4017	820		
4019	815		
4000	810		
3987	805		
3945	800		
3859	795		
3784	790		
3677	785		
3528	780		
3348	775		
3145	770		
2946	765		
2711	760		

2504	755
2294	750
2086	745
1860	740
1664	735
1508	730
1371	725
1230	720
1104	715
1001	710
895	705
814	700

Abstand der Spulen: r

Position Spule 1: 350mm Position Spule 2: 282mm

Spulenpaar	Flache Kreisspule mit Spulenpaar 3	Reihenschaltung	Abstand der S
By	Position Sensor halterung	Einheit: mikro T	Position Spule
	1030	930	
	1161	925	
	1313	920	
	1473	915	
	1644	910	
	1835	905	
	2024	900	
	2277	895	
	2525	890	
	2816	885	
	3076	880	
	3369	875	
	3594	870	
	3980	865	
	4267	860	
	4473	855	
	4678	850	
	4836	845	
	4929	840	
	4963	835	
	4952	830	
	4884	825	
	4784	820	
	4602	815	
	4459	810	
	4164	805	
	3915	800	
	3637	795	
	3447	790	
	3180	785	
	2906	780	
	2572	775	
	2278	770	
	2070	765	
	1860	760	

1657	755
1493	750
1335	745
1204	740
1128	735
969	730
867	725
785	720
704	715
646	710
581	705
532	700

Position Spule 2: 316mm

Messung Solenoid 2

By Position Spule

45	260
47	265
52	270
60	275
71	280
86	285
106	290
128	295
172	300
224	305
280	310
431	315
595	320
808	325
1092	330
1348	335
1635	340
1803	345
1945	350
2041	355
2105	360
2148	365
2183	370
2205	375
2220	380
2232	385
2242	390
2251	395
2257	400
2261	405
2264	410
2271	415
2275	420
2277	425
2281	430

2282	435
2285	440
2286	445
2287	450
2288	455
2289	460
2290	465
2289	470
2288	475
2288	480
2288	485
2288	490
2287	495
2286	500
2286	505
2284	510
2282	515
2281	520
2279	525
2277	530
2275	535
2273	540
2271	545
2266	550
2262	555
2257	560
2251	565
2243	570
2234	575
2222	580
2200	585
2184	590
2155	595
2108	600
2060	605
1976	610
1868	615
1703	620
1470	625
1187	630
882	635

639	640
462	645
338	650
247	655
188	660
139	665
109	670
88	675
70	680

Spannung bei dem Versuch runtergegangen: 1.763 V

Einheit: mikro T

I = 1.999

Position Halterung: 980mm