

# Front End Considerations

When calling services

- What does the Front End need to consider?

# The Biggest Lie in Web Dev



- We use "spinners" to tell the user to wait
- Does NOT indicate actual computer activity

# Using a Spinner




- Add to page before starting a (long?) async action
- Remove when complete
- If something breaks and you don't remove it
- ...it keeps spinning
- ...does NOT indicate anything is "thinking".
- It is just an animated image

# Spinner Example

```
appEl.addEventListener('click', (e) => {  
  if( e.target.classList.contains('show-cats') ) {  
    state.isLoadingCats = true;  
    render(); // Shows spinner  
    fetchCats() // Starts async  
      .then( cats => { // Runs after fetch delay  
        state.cats = cats;  
        state.isLoadingCats = false;  
        render(); // shows data, not spinner  
      })  
      .catch( err => {  
        state.error = err;  
        state.isLoadingCats = false;  
        render(); // shows error, not spinner  
      });  
  }  
});
```

# What is the Spinner?

- Can be image
  - With or without CSS to "spin"
- Can be text (Ex: )
- Can be pure CSS
  - **<https://css.gg/app?s=spinner>**

# When to show Spinner/Loading Indicator

- To signal user that something is coming
- Async calls can take surprising time!
- Don't show misleading state
- Users get
  - Frustrated
  - Confused
  - And worst, BORED
    - Start clicking
- May show one spinner for multiple loads
  - Rather than many small spinners

# Separating Service Call Concerns

Complexity can drag your code down

- Hard to find bugs
- Hard to fix bugs
- Hard to add features

Write it clean from the start

- Good, meaningful names
- Keep concerns separate

# Example HTML for poor JS coding

Sample HTML for a simple TODO list

```
<ul class="tasks">
  <li class="task">Do INF06250 work ONTIME</li>
</ul>

<div class="to-add">
  <input name="taskName" class="task-to-add">
  <button class="add-task">
</div>
```



# Handling a user action?

- Attach a listener
  - Start spinner
  - Gather any user data for service call
  - Make service call
    - On success:
      - Stop spinner
      - Show updated results
      - Update form fields
    - On failure
      - Stop spinner
      - Show error message

# **That's a LOT!**

Doing a lot makes it hard to

- Skim code to find the part you are looking for
- Know what all the effects are
- Make changes with confidence of results

# Breaking into functions

Breaking the code into smaller functions

- Helps readability
- Doesn't inherently reduce complexity!

Many functions with "side-effects" is BAD!

- Even harder to find coder
- Even harder to make changes with confidence

# Separation of Concerns

- We are using Model View Controller (MVC)
  - One form of Separation of Concerns (SOC)
- Goal is to reduce "side-effects"
  - All changes related to one purpose
  - Without impacting different purposes
  - "Side effects" is hard to define
- "Decoupled" code
  - Can change one part of code without requiring changes in other parts
  - One part "does not know" about other part

# **SOC is why MVC is valuable in service calls**

- We have state
- We have functions to update state
- Event listener calls functions to update state
- Render() shows HTML corresponding to state
- Event listener doesn't "know" the rendered HTML
- Render() doesn't know what action just happened

# Service Call Wrapper Functions

We made service call wrappers

- Not part of MVC
- Are Separation of Concerns (SOC)

Wrapper function

- Passed any needed data
- Calls fetch()
- Returns promise that resolves with parsed data
  - Or rejects with formatted error object

# Service Call Wrapper Function is Decoupled

- Doesn't read HTML
- Doesn't change HTML
- Doesn't read/change state
- Doesn't "know" what event just happened
- Is reusable in other parts of app
- Handling of resolved/rejected object
  - Left to calling function

This is an example of Separation of Concerns

- Decoupled code
- Separates all fetch()/http code

# Code "Responsibility"

- Consider "the responsibility" of some code
  - Don't change values outside responsibility
  - Pass in needed values outside responsibility
- Ex: functions that fetch and transform results
  - return promise of results or error
  - Separate concerns of "getting data" and "displaying data"
- Ex: structured Errors
  - Separate concerns of "deciding error" and "handling error"



# Code that "works" isn't enough

**Quality code** allows for

- Ease of understanding
- Ease of finding the correct part of code
- Ease of making change
- Confidence that change won't impact other code
- Confidence that you know all needed change(s)

Poor quality code gets worse over time

- Changes exponentially get more complex

# **"It's working, I'm afraid to touch it"**

- Common when you are starting
- REMAINS common if poor quality code!
- Coding shouldn't be guessing

As you start, it will ABSOLUTELY feel that way

- That's fine and normal
- It should not STAY that way

# Client - Server Synchronization

- The server is the source of truth
- State on the client
  - potentially out of date
- Double state-changing actions
  - Double-click on button?

# Why does it matter?

- Deleting an element already gone?
  - VERY BAD if using array index!
    - Delete unintended element
- Increment/Decrement too much?
- Pay \$ based on inaccurate total?
  - Pay twice?
- Overwrite values on server?

# Options to deal with data desync?

"Correct" answer depends on app

- Just trust the client
  - Make user responsible for knowing
- Keep a hash/timestamp of state
  - When client sends wrong value
    - Server refuses certain actions

# Updating Client After Action

When do you update client state

- To be more likely in-sync with server?

Important to consider after sending a change

- Updates mean loading time!

Example:

- Load list from server
- Tell server to delete an item?
- Do you delete the item in the local state?
- Do you reload the list from server?

# The "Back" Button

A SPA has issues with the browser "Back" button

- SPA is a single changing page
- "Back" completely leaves that page
- "Forward" reloads the page
- State before you hit "Back" is lost

This is a notable problem!

- But we will ignore until React
  - Solutions don't require React
- "Deeplinking" will be the solution

# Long Results

Too much data to show user at once

- Option 1: Pagination of Results
- Option 2: Infinite Scroll



# Results Pagination

- Like with service, but visible on screen
- Specific page numbers
  - And/Or "Previous"/"Next"
- Changes shown data
  - May or may not have to RETRIEVE data
  - May have more data than shown
    - Ex: Already have prev/next pages data
    - Show immediately on change
      - Start loading NEW data
      - Creates impression of speed

# Infinite Scroll

- As user approaches end of displayed content
  - (scrolling)
  - Load additional data
  - Append to HTML
- May need to "remove" HTML from top
  - Otherwise it gets slow
- Accessibility problems
- Hard to save/link where you are at
- Best to use only on temporary data

# Polling for Updates

The web request/response cycle:

- means the client has to ASK for an update
- ...even if there isn't one yet

This can feel (and be) inefficient

- But is also very common
- We'll do periodic polling because it's simple
- ...not because it is better

# Polling methods

- Periodic Polling ("Basic", "Regular")
  - Periodic web requests
- "Long Polling"
  - Server keeps res open
  - Server finishes res once there is an update
  - Client immediately opens new request
    - On success or error
- Websockets
  - Not HTTP
  - A different protocol started *from* HTTP
  - Allows server "push" actions

# Long Polling

- Client makes request
  - "Give me updates" vs "Are there updates"
- Server does NOT respond right away
  - Once it has an update, will respond
- Client auto times out connection (2-5 mins?)
  - Client will try again
- When Client gets response with data
  - Use data
  - Make new long polling request

All Client request behavior is in JS code

- Not automatic

# Websockets

- Not HTTP: `ws://`, `wss://`
  - JS code requests a WebSocket connection
  - From server, with `ws` url
- Longer-lasting connection
- Not request/response
- Allows server to send unprompted messages
  - Once connection exists

# Regular Polling

All I expect for this course

## Pros

- Easy to implement
- Easy to understand

## Cons

- Generates a lot of requests

# setTimeout()

```
const timeoutId = setTimeout(callback, milliseconds);
```

- Calls passed **callback**
- No sooner than **milliseconds** from now
  - But could take longer (event queue!)
- Returns a `timeoutId`
  - Used by `clearTimeout(timeoutId)` to cancel



# setInterval()

```
const intervalId = setInterval(callback, msec);
```

- Very similar to `setTimeout()`
  - Call callback
- But repeats *every* msec (ish)
  - Not just once
- canceled by `clearInterval(intervalId);`

# Implementing Regular Polling

- use `setInterval()` or `setTimeout()`
  - `setTimeout()` must schedule next run
  - `setInterval()` automatically schedules
    - Watch out for results taking too long
    - Coming back in wrong order
- **callback** issues a `fetch()`
  - and sets callbacks for `.then()`

# Regular Polling Example

```
function refreshCats() {  
  fetchCats()  
  .then( cats => {  
    state.names = cats;  
    render();  
  })  
  // omitted error reporting for space  
}  
  
function pollCats() {  
  refreshCats(); // fetch and use data  
  setTimeout( pollCats, 2000 );  
}
```

# CORS on Client-side

Request a Cross-Origin Service is easy

- Just use URL with a different origin
- Browser enforces CORS
- Server is responsible for including CORS headers

# When you get a CORS error

Use DevTools-Network

- Confirm URL is correct
- Confirm Server sent a success
- Check Response has CORS headers
- Fix Request or Server

Don't waste time trying to "turn CORS off"

- Don't use "no-cors"

# Cookies not sent by default when Cross-Origin

- `fetch()` must use `credentials: include` option
  - Will silently not send cookies otherwise
  - Only client-side control we have for this
- Cookie NOT created with `SameSite=Strict` option
  - Default is `Lax`, which does work
- Service must send `access-control-allow-credentials: true` header
  - Otherwise browser will give CORS error when credentials sent