Table 1: Complete personalized-execution results on AndroidIntent. All values are percentages. Higher is better. Qwen3-VL baseline values are from PersonalAlign Table 5; the other baseline columns and all TRACE values are our complete evaluations.

	Qwen3-VL-8B			MAI-UI-8B			Qwen3.5-9B			GUI-Owl-1.5-8B		
Method	Type	SSR	CSR	Type	SSR	CSR	Type	SSR	CSR	Type	SSR	CSR
Base	46.600	20.600	26.600	51.762	17.890	22.260	50.120	17.183	21.427	58.181	22.742	21.515
Recent†	49.400	21.100	33.200	47.593	18.143	21.158	49.387	17.915	25.471	59.078	23.917	27.244
Retrieve	51.000	22.400	35.400	49.690	21.554	32.707	49.210	19.949	32.535	60.253	28.187	41.641
LLM-UM‡	51.200	22.300	35.200	48.086	19.015	28.323	52.445	20.708	39.831	57.941	24.839	30.762
HIM-Agent	52.000	24.000	42.300	48.162	19.912	28.673	51.358	20.960	37.833	58.724	27.189	35.583
TRACE (ours)	**58.825**	**39.116**	**53.615**	**58.939**	**39.330**	**53.812**	**59.495**	**39.949**	**54.870**	**60.430**	**40.076**	**54.875**

LATENT STATE ADDRESSING FOR LONG-HORIZON PERSONALIZED GUI AGENTS

Anonymous authors
Paper under double-blind review

ABSTRACT

The abstract paragraph should be indented 1/2 inch (3 picas) on both left and right-hand margins. Use 10 point type, with a vertical spacing of 11 points. The word ABSTRACT must be centered, in small caps, and in point size 12. Two line spaces precede the abstract. The abstract must be limited to one paragraph.

1 INTRODUCTION

REFERENCES

A APPENDIX

You may include other additional sections here.