



≡ CLI commands > **agents**

CLI commands

agents

Manage isolated agents (workspaces + auth + routing).

Related:

Multi-agent routing: [Multi-Agent Routing](#)

Agent workspace: [Agent workspace](#)

Examples

```
openclaw agents list
openclaw agents add work --workspace ~/.openclaw/workspace-work
openclaw agents set-identity --workspace ~/.openclaw/workspace --from-identity
openclaw agents set-identity --agent main --avatar avatars/openclaw.png
openclaw agents delete work
```

Identity files

Each agent workspace can include an `IDENTITY.md` at the workspace root:

Example path: `~/.openclaw/workspace/IDENTITY.md`

`set-identity --from-identity` reads from the workspace root (or an explicit `--identity-file`)

Avatar paths resolve relative to the workspace root.

Set identity



`set-identity` writes fields into `agents.list[].identity` :

`>`
`name`

`theme`

`emoji`

`avatar` (workspace-relative path, http(s) URL, or data URI)

Load from `IDENTITY.md` :

```
openclaw agents set-identity --workspace ~/.openclaw/workspace --from-
```

Override fields explicitly:

```
openclaw agents set-identity --agent main --name "OpenClaw" --emoji "🦞"
```

Config sample:

```
{
  agents: {
    list: [
      {
        id: "main",
        identity: {
          name: "OpenClaw",
          theme: "space lobster",
          emoji: "🦞",
          avatar: "avatars/openclaw.png",
        },
      },
    ],
  },
}
```

< agent

approvals >



Powered by mintlify

>